

CAL NAME	COMMON NAME	SIZE	CONDITION	REMARKS
				·
jens	Colorado Spruce	1.8m Ht.	B&B	See Plan
manii	Freeman's Maple	60mm ø	B&B	See Plan
dentalis	Hackberry	60mm ø	B&B	See Plan
iacanthos	Honeylocust	60mm ø	B&B	See Plan
ous	White Pine	1.8m Ht.	B&B	See Plan
ca	White Spruce	1.8m Ht.	B&B	See Plan
		-		
arborescens 'Annabelle'	Annabelle Hydrangea	1 Gallon Pot	Potted	Space 1000mm O.C
orbifolia 'Sem'	Sem False Spirea	600mm Ht.	Potted	Space 1000mm O.C
arguta	Garland Spirea	800mm Ht.	Potted	Space 1200mm O.C
atica 'Gro Low'	Gro Low Fragrant Sumac	600mm Ht.	Potted	Space 800mm O.C
sa 'Hansa'	Hansa Rugosa Rose	600mm Ht.	Potted	Space 1000mm O.C
kalmianum 'Ames'	Ames' St. John's Wort	600mm Ht.	Potted	Space 800mm O.C.
	AL GRASSES			
tumn Joy'	Autumn Joy Sedum	250mm Pot.	Potted	Space 500mm O.C.
tis x acutiflora 'Karl Foerster'	Feather Reed Grass	250mm Pot.	Potted	Space 800mm O.C.
ndinacea 'Picta'	Picta Ribbon Grass	250mm Pot.	Potted	Space 600mm O.C.
triplicifolia	Russian Sage	250mm Pot.	Potted	Space 500mm O.C.

GENERAL NOTES:
<ol> <li>It is the responsibility of the appropriate contractor or official to report any errors, omissions or discrepancies on this plan with actual site conditions to the Landscape Architect before proceeding with construction.</li> </ol>
<ol><li>The contractor is to notify all utility companies and authorities prior to any excavation and ascertain locations of underground services.</li></ol>
<ol> <li>The contractor is to reinstate all areas and items damaged as a result of construction activity.</li> </ol>
4. The contractor is to comply with all pertinent codes and by-laws.
5. The contractor is to maintain a positive surface run-off throughout the entire construction period.
6. The Landscape Architect is not responsible for subsurface conditions.
<ol><li>The contractor is to identify all existing trees to remain on site with the Landscape Architect prior to construction.</li></ol>
8. The contractor is to stake the proposed location of all plant material in conjunction with the Landscape Architect prior to excavation.
<ul> <li>9. Minimum distances for selected deciduous trees are as follows:</li> <li>Building Foundations 7.5m</li> <li>Sidewalks 1.5m</li> <li>Public Streets 2.5m</li> <li>Underground Infrastructure 2.0m</li> </ul>
10. All trees within 1m of underground utility trenches are to be excavated by hand.
11. Remove all protective wrapping from tree trunks after installation.
12. Staking of trees shall only be performed if necessary.
13. Ensure that mulch is pulled back a min. distance of 75mm from base of tree trunk.

PLAN # 17523