


J:\14326\_1\pblg\14326\14326.dwg Drawing: 14326\14326.dwg Plot Scale: 1:25.4 Printed At: 6/17/2018 1:41 PM Last Saved By: D:\J.M. Moodie Last Saved At: Jun. 6, 18



#### REMOVALS LEGEND:

- CONCRETE CURB/SIDEWALK TO BE REMOVED
- REMOVE AND RELOCATE EXISTING STREETLIGHTS PER ELECTRICAL DRAWINGS
- REMOVE AND RELOCATE EXISTING CATCHBASING PER CIVIL DRAWINGS
- EXISTING LIGHT DUTY PAVEMENT STRUCTURE TO BE REMOVED AND REPLACED WITH HEAVY DUTY PAVEMENT STRUCTURE
- EXISTING ASPHALT TO BE REMOVED

#### REMOVALS DETAIL

N.T.S.

**APPROVED**

By Derrick Moodie at 11:45 am, Jul 17, 2018

*Derrick Moodie*

**DERRICK MOODIE**

**MANAGER**

**PLANNING, INFRASTRUCTURE & ECONOMIC  
DEVELOPMENT DEPARTMENT, CITY OF OTTAWA**

#### DRAWING NOTES

##### 1.0 GENERAL

- 1.1 CONTRACTOR TO VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION.
- 1.2 DO NOT SCALE DRAWINGS.
- 1.3 CONTRACTOR TO REPORT ALL DISCOVERIES OF ERRORS, OMISSIONS OR DISCREPANCIES TO THE ARCHITECT OR DESIGN ENGINEER AS APPLICABLE.
- 1.4 USE ONLY THE LATEST REVISED DRAWINGS OR THOSE THAT ARE MARKED "ISSUED FOR CONSTRUCTION".
- 1.5 ALL CONSTRUCTION SHALL COMPLY WITH CURRENT CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.
- 1.6 THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ALL RELEVANT DRAWINGS AND SPECIFICATIONS.
- 1.7 FOR LEGAL SURVEY INFORMATION REFER TO REGISTERED PLAN NUMBER 4M-1554 BY STANTEC GEOMATICS LIMITED.
- 1.8 REFER TO SITE PLAN (DRAWING NO A1-176) BY TURNER FLEISCHER FOR SITE PLAN LAYOUT.
- 1.9 REFER TO LANDSCAPE ARCHITECTURAL DRAWINGS (DRAWING NO. L1-L4) BY BBI GROUP FOR SURFACE FEATURES DETAILS.

- 1.10 CONTRACTOR TO IMPLEMENT EROSION AND SEDIMENT CONTROL MEASURES AS IDENTIFIED IN THE EROSION AND SEDIMENT CONTROL PLAN TO THE SATISFACTION OF THE CITY OF OTTAWA, PRIOR TO UNDERTAKING ANY SITE ALTERATIONS (FILLING, GRADING, REMOVAL OF VEGETATION, ETC.), DURING ALL PHASES OF THE SITE PREPARATION AND CONSTRUCTION THE MEASURES ARE TO BE MAINTAINED TO THE SATISFACTION OF THE ENGINEER AND CITY OF OTTAWA IN ACCORDANCE WITH THE BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL. SHOULD ANY ADDITIONAL MEASURES BE REQUIRED TO ADDRESS FIELD CONDITIONS THEY SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER OR THE CITY OF OTTAWA. SUCH ADDITIONAL MEASURES MAY INCLUDE BUT NOT BE LIMITED TO INSTALLATION OF FILTER CLOTHS ACROSS MANHOLE AND CATCH BASIN LIDS TO PREVENT SEDIMENT FROM ENTERING THE STRUCTURE AND INSTALLATION AND MAINTENANCE OF A LIGHT DUTY SILT FENCE BARRIER AS REQUIRED.

- 1.11 ALL IRON WORK ELEVATIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR ADJUSTMENTS AS DETERMINED BY THE ENGINEER.

- 1.12 ALL CONCRETE CURBS AND SIDEWALKS TO CONFORM TO O.P.S. AND CONSTRUCTED TO CITY STANDARDS. ALL ON-SITE CURBS TO BE BARRIER TYPE, WITH DEPRESSIONS AS NOTED.

- 1.13 ALL CONCRETE SHALL BE "NORMAL PORTLAND CEMENT" IN ACCORDANCE WITH O.P.S.S. 1350 AND SHALL ACHIEVE A MINIMUM STRENGTH OF 30MPa AT 28 DAYS.

- 1.14 ALL CONSTRUCTION TRAFFIC TO ACCESS SITE FROM PALLADIUM DRIVE.

- 1.15 FOR DETAILS OF TEST PITS SEE GEOTECHNICAL REPORT.

- 1.16 CONTRACTOR TO PROTECT EXISTING INFRASTRUCTURE AND PROPERTY SUCH AS TREES, PARKING METERS, SIDEWALKS, CURBS, ASPHALT, AND STREET SIGNS FROM DAMAGE DURING CONSTRUCTION. CONTRACTOR TO PAY THE COST TO REINSTATE OR REPLACE ANY DAMAGED INFRASTRUCTURE OR PROPERTY TO THE SATISFACTION OF THE CITY.

- 1.17 THE POSITION OF POLE LINES, CONDUITS, WATERMAIN, SEWERS, AND OTHER UNDERGROUND AND ABOVEGROUND UTILITIES AND STRUCTURES ARE NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK THE CONTRACTOR SHALL INFORM THE CITY OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, SHALL PROTECT ALL UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

- 1.18 CONTRACTOR TO SUPPLY SUITABLE FILL MATERIAL, WHERE REQUIRED TO ROUGH GRADE THE SITE. ALL IMPORTED FILL MATERIAL TO BE CERTIFIED AS ACCEPTABLE BY THE GEOTECHNICAL ENGINEER.

- 1.19 CONTRACTOR TO HAUL EXCESS MATERIAL OFF-SITE AS NECESSARY TO GRADE SITE TO MEET THE PROPOSED GRADES. ALL EXCESS MATERIAL TO BE HAULED OFF-SITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY HAZARDOUS MATERIAL, CONTRACTOR IS TO NOTIFY ENGINEER. ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.

- 1.20 FILL MATERIAL, WITHIN THE PARKING LOT AND BUILDING PAD AREAS, AND SUPPORTING BUILDING FOUNDATIONS SHALL BE COMPACTED TO 98% STANDARD MODIFIED PROCTOR DENSITY AND TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER.

- 1.21 ALL COMPACTION METHODS TO BE PERFORMED TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO INCLUDE BUT NOT BE LIMITED TO THE THICKNESS OF LIFTS, AND COMPACTION EQUIPMENT USED.

- 1.22 ALL DISTURBED BOULEVARDS TO BE REINSTATED WITH 500 ON 100mm TOPSOIL.

- 1.23 UTILITY DUCTS TO BE INSTALLED PRIOR TO ROAD BASE CONSTRUCTION.

- 1.24 CLAY DIKES TO BE INSTALLED WHERE INDICATED ON THE DRAWINGS OR AS APPROVED AND DIRECTED BY THE GEOTECHNICAL ENGINEER ALL IN ACCORDANCE WITH CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.

##### 2.0 SANITARY

- 2.1 ALL SANITARY SEWER MAINS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ONLY FACTORY FITTINGS TO BE USED. SEWER TO BE INSTALLED AS PER OPSD 1005.01. SANITARY SEWER MATERIALS TO BE: 250mmØ AND SMALLER - PVC DR 35

- 2.2 ALL SANITARY MAINTENANCE HOLES TO BE 1.2m DIAMETER AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, FRAME AND COVER, DROP PIPES WHERE NEEDED.

- 2.3 SANITARY MANHOLE COVERS TO BE CITY OF OTTAWA STD. 525 (MOD. OPSD. 401.020). SANITARY MANHOLE COVER TO BE CLOSED COVER TYPE, AS PER CITY STANDARD S24.

- 2.4 SANITARY SEWER LEAKAGE TEST AND CCTV INSPECTION SHALL BE COMPLETED AS PER CITY SPECIFICATIONS PRIOR TO INSTALLATION OF BASE COURSE ASPHALT.

- 2.5 ANY SANITARY SEWER WITH LESS THAN 2.0m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

- 2.6 CONNECTION TO THE EXISTING SANITARY SEWER TO BE INCLUDED IN THE COST FOR SANITARY SEWER INSTALLATION. THIS INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARDS.

##### 3.0 STORM

- 3.1 ALL STORM SEWERS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ALL STORM SEWERS TO BE INSTALLED PER MANUFACTURER'S INSTRUCTIONS. ONLY FACTORY FITTINGS TO BE USED. STORM SEWER MATERIALS TO BE: 375mmØ AND SMALLER - PVC DR 35

- 3.2 ALL STORM MAINTENANCE HOLES TO BE SIZED IN ACCORDANCE WITH THE PLANS AND AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, AND FRAME AND COVER.

- 3.3 STORM MH COVERS TO BE OPEN TYPE, AS PER CITY STANDARD S24. FRAMES TO BE PER CITY OF OTTAWA STD. S25. CONTRACTOR TO INSTALL FILTER FABRIC UNDER STORM MH COVER UNTIL SCODING IS COMPLETE.

- 3.4 STORM MAINTENANCE HOLES TO BE OPSD. SIZE AS SPECIFIED, TAPER TOP.

- 3.5 ALL CATCH BASINS TO BE AS PER OPSD 705.010, FRAME & FISH TYPE GRATE AS PER CITY OF OTTAWA STD. S19.1.

- 3.6 150mm DIAMETER SOCK-WRAPPED PERFORATED PVC SUBRANS TO BE INSTALLED AT THE LIMIT OF THE HEAVY DUTY ROAD STRUCTURE WHERE IT MEETS THE LIGHT DUTY ROAD STRUCTURE AND AT ALL C&B'S IN HEAVY DUTY ROADS AS IDENTIFIED ON PLAN. SUBRANS TO DISCHARGE TO C&B'S AS SHOWN.

- 3.7 ANY STORM SEWER WITH LESS THAN 2.0m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

- 3.8 CONNECTION TO THE EXISTING STORM SEWER TO BE INCLUDED IN THE COST FOR STORM SEWER INSTALLATION. THIS INCLUDES REINSTATEMENT OF ROAD CUT TO CITY STANDARDS.

- 3.9 CONTRACTOR TO PROVIDE IPEX-TEMPEST MHF-ICD'S SHOP DRAWINGS, OR EQUIVALENT, FOR ENGINEERS REVIEW PRIOR TO ORDERING ICD'S.

- 3.10 TRENCH DRAINS SHALL BE EQUIVALENT TO ZURN 2882-HDG.

##### 4.0 WATER

- 4.1 ALL WATERMANS TO BE PVC DR 18, WITH MINIMUM COVER OF 2.4m AND INSTALLED PER CITY OF OTTAWA STANDARDS. ALL DOMESTIC WATER SERVICES ARE TO BE 200mmØ.

- 4.2 THRUST BLOCKS TO BE INSTALLED AT ALL BENDS, TEES, AND CAPS ALL AS PER OPSD 1103.01 AND 1103.02.

- 4.3 CONTRACTOR TO CONDUCT PRESSURE AND LEAKAGE TESTING OF ALL WATERMANS AND DISINFECT AND CHLORINATE ALL WATERMANS TO THE SATISFACTION OF M.O.E. AND THE CITY OF OTTAWA.

- 4.4 TRACER WIRE TO BE INSTALLED ALONG THE FULL LENGTH OF WATERMAIN AND ATTACHED TO EACH MAIN STOP AS PER CITY OF OTTAWA STANDARDS.

- 4.5 ALL COMPONENTS OF THE WATER DISTRIBUTION SYSTEM SHALL BE CATHODICALLY PROTECTED AS PER CITY OF OTTAWA STANDARDS.

- 4.6 ALL VALVES & VALVE BOXES AND CHAMBERS, HYDRANTS, AND HYDRANT VALVES AND ASSEMBLIES SHALL BE INSTALLED AS PER CITY OF OTTAWA STANDARDS.

- 4.7 ANY WATERMAIN WITH LESS THAN 2.4m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

- 4.8 CONTRACTOR IS RESPONSIBLE FOR ACQUIRING THE WATER PERMIT FROM THE CITY OF OTTAWA AND PAYMENT OF ANY FEES ASSOCIATED WITH SECURING THE WATER PERMIT. OWNER IS RESPONSIBLE FOR REIMBURSING THE CONTRACTOR FOR THE ACTUAL COST OF ACQUIRING THE WATER PERMIT.

- 4.9 CONNECTION TO EXISTING WATERMAIN TO BE INCLUDED IN THE COST FOR THE WATERMAIN INSTALLATION. THIS COST INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARDS.

- 4.10 THESE CROSSINGS WERE PROVIDED FOR THE PREVIOUS SITE PLAN APPLICATION AND ARE NO LONGER NECESSARY BASED ON THE REVISED SANITARY SEWER WATERMAIN CONFIGURATION.

##### 5.0 PARKING LOT AND WORK IN PUBLIC RIGHTS OF WAY

- 5.1 CONTRACTOR TO REINSTATE ROAD CUTS PER CITY OF OTTAWA STANDARD R-10.

- 5.2 THE CONTRACTOR SHALL PREPARE A TRAFFIC MANAGEMENT PLAN FOR REVIEW AND APPROVAL BY THE CITY OF OTTAWA. CONTRACTOR TO MAINTAIN TRAFFIC FLOW DURING THE ENTIRE CONSTRUCTION PERIOD. MAINTENANCE OF ROAD CUTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. PROVISION OF FLAGMEN, DETOURS AS NECESSARY, BARRICADES AND SIGNS TO THE FULL SATISFACTION OF THE ENGINEER AND ROAD AUTHORITY SHALL BE THE CONTRACTOR'S RESPONSIBILITY.

- 5.3 CONTRACTOR TO PREPARE SUBGRADE, INCLUDING PROOFROLLING, TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER PRIOR TO THE COMMENCEMENT OF PLACEMENT OF GRANULAR B MATERIAL.

- 5.4 FILL TO BE PLACED AND COMPACTED PER THE GEOTECHNICAL REPORT REQUIREMENTS.

- 5.5 CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR B MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR B MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

- 5.6 GRANULAR A MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR B PLACEMENT.

- 5.7 CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR A MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR A MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

- 5.8 ASPHALT MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR A PLACEMENT.

- 5.9 CONTRACTOR TO SUPPLY, PLACE AND COMPACT ASPHALT MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF ASPHALT MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

- 5.10 CONTRACTOR IS RESPONSIBLE FOR ESTABLISHING LINE AND GRADE IN ACCORDANCE WITH THE PLANS, AND FOR PROVIDING THE ENGINEER WITH VERIFICATION PRIOR TO PLACEMENT.

- 5.11 DITCHES DISTURBED DURING CULVERT INSTALLATION AND GRADING OPERATIONS ARE TO BE REINSTATED TO THEIR ORIGINAL CONDITION AND FLOWLINE GRADES.

- 5.12 EXISTING EAST SIDE ROAD DITCH ALONG PALLADIUM DRIVE TO BE REGRADED AS PER THE GRADING PLAN. ADJACENT AREAS BETWEEN ROAD, SIDE DITCH AND PARKING LOT TO BE RE-GRADDED AS PER THE GRADING PLAN. ALL RE-GRADDED AREAS IN EXISTING PUBLIC RIGHTS OF WAY AND ANY OTHER DISTURBED AREAS IN EXISTING PUBLIC RIGHTS OF WAY ARE TO BE FINISHED WITH 500 ON 100mm TOPSOIL.

- 5.13 ALL EXCESS MATERIAL TO BE HAULED OFF-SITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY HAZARDOUS MATERIAL, CONTRACTOR IS TO NOTIFY ENGINEER, ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.

- 5.14 PAVEMENT STRUCTURE (MATERIAL TYPES AND THICKNESSES) FOR HEAVY DUTY AND LIGHT DUTY AREAS TO BE AS SPECIFIED IN THE GEOTECHNICAL REPORT AND SHOWN ON THE PLANS.

#### LEGEND:

- EXISTING STORM MANHOLE & NUMBER
- EXISTING SANITARY MANHOLE & NUMBER
- EXISTING STORM SEWER & FLOW DIRECTION
- EXISTING SANITARY SEWER & FLOW DIRECTION
- EXISTING FIRE HYDRANT
- EXISTING WATER VALVE BOX
- EXISTING WATER VALVE CHAMBER
- EXISTING BOUNDARY VALVE CHAMBER
- EXISTING CATCHBASIN
- EXISTING CURB
- EXISTING CURB TO BE REMOVED
- EXISTING DEPRESSED CURB
- EXISTING DEPRESSED CURB WITH RAMP
- EXISTING GRADE STANTEC PICKUP 2017-11-23
- EXISTING GRADE IBI GRADING PLAN
- EXISTING DITCH AND FLOW DIRECTION
- EXISTING SIAMESE CONNECTION
- EXISTING METER
- EXISTING REMOTE METER
- EXISTING PRESSURE REDUCING VALVE
- EXISTING CLAY DYKE
- HEAVY DUTY PAVING AREA
- CONCRETE PAD
- CONTROLLED ROOF RELEASE RATE

- PROPOSED STORM MANHOLE & NUMBER
- PROPOSED SANITARY MANHOLE & NUMBER
- PROPOSED STORM SEWER & FLOW DIRECTION
- PROPOSED SANITARY SEWER & FLOW DIRECTION
- PROPOSED FIRE HYDRANT
- PROPOSED WATER VALVE BOX
- PROPOSED WATER VALVE CHAMBER
- PROPOSED BOUNDARY VALVE CHAMBER
- PROPOSED CATCHBASIN
- PROPOSED CURB
- PROPOSED DEPRESSED CURB
- PROPOSED DEPRESSED CURB WITH RAMP
- PROPOSED GRADE
- PROPOSED DITCH AND FLOW DIRECTION
- SIAMESE CONNECTION
- METER
- REMOTE METER
- PRESSURE REDUCING VALVE
- WATERMAIN IDENTIFICATION
- PIPE CROSSING IDENTIFICATION
- CLAY DYKE
- RAISED CROSSWALK
- TRANSFORMER C/W BOLLARDS
- OVERLAND FLOW ROUTE


#### PAVEMENT STRUCTURE

##### LIGHT DUTY

- 50mm 12.5 SUPERPAVE
- 150mm GRANULAR 'A'
- 400mm GRANULAR 'B'

##### HEAVY DUTY

- 40mm 12.5 SUPERPAVE
- 50mm 19.0 SUPERPAVE
- 150mm GRANULAR 'A'
- 450mm GRANULAR 'B'



KEY PLAN  
N.T.S.

No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	RE-ISSUED FOR SITE PLAN APPROVAL	JIM	18.06.06
2	RE-ISSUED FOR SITE PLAN APPROVAL	JIM	18.04.19
1	ISSUED FOR SITE PLAN APPROVAL	JIM	18.01.31

PROJECT ARCHITECT

**TURNER FLEISCHER**  
TURNER FLEISCHER ARCHITECTS INC.  
67 Lesmill Road Toronto ON Canada M5N 3Y8  
Telephone (416) 443-1411 Fax (416) 443-4777  
turnerfleischer.com

DESIGN ARCHITECT

**CREATE**  
Architecture Planning & Design LLC  
The Chrysler Building  
405 Lexington Avenue, Tower Suite 70  
New York, NY 10174  
Phone: (212) 297-0880  
www.createworldwide.com

SITE / CIVIL

**IBI**  
Architects, Engineers, Planners  
5th Floor, 230 Richmond Street West  
Toronto, ON  
M5V 1Y6, Canada  
Tel: (416) 596-1930  
Fax: (416) 596-0644

333 Preston Street  
Tower 1, Suite 400  
Ottawa, Ontario  
Canada K1S 5M4  
Tel: (613) 225-1511  
Fax: (613) 225-9668

**h** HAMMERSCHLAG + JOFFE INC.  
69 Leslie Road Toronto  
Ontario Canada M2B 2T8  
T: (416) 444-5263  
F: (416) 444-5463  
E: chag@hamjoff.com

PLANNER

**FOTENN** PLANNING & URBAN DESIGN  
223 McLeod Street | Ottawa, ON | K2P 0Z8  
T: 613.730.5709 ext.234 | F: 613.730.1136

DEVELOPER

**RIOCAN**  
RioCan Real Estate Investment Trust  
2300 Yonge Street  
Suite 500  
Toronto, Ontario  
M4P 1E4  
(416) 646 8330

DEVELOPER

**TangerOutlets**  
Tanger Outlets  
3200 Northline Avenue, Suite 360  
Greensboro, North Carolina  
27408

Project :

**TANGER OUTLETS KANATA**  
BUILDINGS 14 & 15  
KANATA, ONTARIO

Drawing Name :

**NOTES AND DETAILS**

Proj no.: 114326 Date: JAN. 2018

Drawn by: D.P.S. Scale: N.T.S.

Checked by: J.I.M. Design: M.B.

Drawing No :

**C-101**