

**FUNCTIONAL SERVICING AND
STORMWATER MANAGEMENT
REPORT**

FOR

**MATTAMY HOMES
WATERIDGE VILLAGE – BLOCK 19**

CITY OF OTTAWA

PROJECT NO.: 17-947

OCTOBER 2019 – REV 2
© DSEL

**FUNCTIONAL SERVICING AND STORMWATER MANAGEMENT REPORT
FOR
WATERIDGE VILLAGE – BLOCK 19
MATTAMY HOMES
OCTOBER 2019 – REV 2**

**CITY OF OTTAWA
PROJECT NO.: 17-947**

TABLE OF CONTENTS

1.0	INTRODUCTION	1
1.1	Existing Conditions	2
1.2	Required Permits / Approvals	3
1.3	Pre-consultation.....	3
2.0	GUIDELINES, PREVIOUS STUDIES, AND REPORTS.....	4
2.1	Existing Studies, Guidelines, and Reports.....	4
3.0	WATER SUPPLY SERVICING	6
3.1	Existing Water Supply Services.....	6
3.2	Water Supply Servicing Design	6
3.3	Water Supply Conclusion	8
4.0	WASTEWATER SERVICING.....	9
4.1	Existing Wastewater Services	9
4.2	Wastewater Design	9
4.3	Wastewater Servicing Conclusions	10
5.0	STORMWATER MANAGEMENT	11
5.1	Existing Stormwater Services	11
5.2	Post-development Stormwater Management Target	11
5.3	Proposed Stormwater Management System	11
5.4	Low Impact Development (LID) Practices	12
5.5	Stormwater Servicing Conclusions	13
6.0	UTILITIES.....	13
7.0	EROSION AND SEDIMENT CONTROL	14
8.0	CONCLUSION AND RECOMMENDATIONS	15

FIGURES

Figure 1 Site Location

TABLES

Table 1	Summary of Water Demand per <i>Design Brief Phase 1B</i>
Table 2	Water Supply Design Criteria
Table 3	Water Demand and Boundary Conditions Proposed Conditions
Table 4	Resulting Pressures Proposed Conditions
Table 5	Wastewater Flow per Design Brief Phase 1B – Total Site Area
Table 6	Wastewater Design Criteria
Table 7	Summary of Estimated Peak Wastewater Flow
Table 8	Summary of Release Rates for Anticipated and Proposed Scenarios - Flow directed to Codd's Road
Table 9	Stormwater Flowrate Summary

APPENDICES

Appendix A	Pre-consultation Notes
Appendix B	Water Supply
Appendix C	Wastewater Collection
Appendix D	Stormwater Management
Drawings / Figures	Site Plan

**FUNCTIONAL SERVICING AND STORMWATER MANAGEMENT REPORT
FOR
WATERIDGE VILLAGE – BLOCK 19
MATTAMY HOMES
OCTOBER 2019 – REV 2**

**CITY OF OTTAWA
PROJECT NO.: 17-947**

1.0 INTRODUCTION

David Schaeffer Engineering Limited (DSEL) has been retained to prepare a Functional Servicing and Stormwater Management report in support of the Site Plan Application for Block 19 of the former CFB Rockcliffe lands, which are currently under re-development by the Canada Lands Company.

The subject property is located within the City of Ottawa urban boundary, in the Rideau-Rockcliffe Ward. As illustrated in **Figure 1**, the subject property is encompassed by Hemlock Road to the north, Mikinak Road to the south, Codd's Road to the west and Bareille-Snow Street to the east, all of which are currently under construction. Comprised of a single parcel, the subject property measures approximately **1.63 ha** and is zoned General Mixed Use Zone 31 H(30).




Figure 1: Site Location

The proposed development by Mattamy Homes involves the construction of four (4), 7-floor mixed use buildings, and an underground parking garage.

The objective of this report is to demonstrate the availability of site services in support the application for site plan control (SPC).

1.1 Existing Conditions

The existing lands are vacant, but it should be noted that construction of the surrounding road network and underground services are currently underway at the time of this publication. Historically, the lands were part of the Canadian Forces Base Rockcliffe (CFB Rockcliffe).

A geotechnical investigation was completed by Paterson Group Inc. in August 2017. Per the geotechnical report, the subject site consists of a layer of existing fill from the previous land use, underlain by stiff to very stiff brown silty clay.

Supplemental information from Paterson Group Inc. was also received regarding the anticipated infiltration rates. An infiltration rate of 50 mm/day was estimated for Block 19; collaborating correspondence is found in **Appendix A**.

The Canada Lands Company will be delivering the site to a pre-grade condition in accordance with Mattamy Homes requirements.

The infrastructure described below is based on design drawings, not as-built drawings. The design drawings are as per the **Wateridge Village at Rockcliffe Phase 1B** drawing set, by **IBI Group, December 6, 2017** and **Wateridge Village at Rockcliffe Phase 1A** drawing set, by **IBI Group, April 2016**, received by DSEL on July 21, 2017.

Hemlock Road

- 300mm diameter watermain
- 1200mm diameter storm sewer
- 300mm diameter sanitary sewer

Mikinak Road

- 300mm diameter watermain
- 2700mm diameter storm sewer
- 375mm diameter sanitary sewer

Codd's Road

- 400mm diameter watermain
- 3000mm diameter storm sewer

- 375mm diameter sanitary sewer

Bareille-Snow Street

- 675mm diameter storm sewer
- 250mm diameter sanitary sewer
- 200mm watermain

1.2 Required Permits / Approvals

The proposed development is subject to the site plan control approval process. The City of Ottawa must approve the engineering design drawings and reports prior to the issuance of site plan control.

1.3 Pre-consultation

Pre-consultation correspondence, along with the servicing guidelines checklist, are located in **Appendix A**.

2.0 GUIDELINES, PREVIOUS STUDIES, AND REPORTS

2.1 Existing Studies, Guidelines, and Reports

The following studies were utilized in the preparation of this report:

- **Ottawa Sewer Design Guidelines,**
City of Ottawa, *SDG002*, October 2012
(City Standards)
- **Ottawa Design Guidelines – Water Distribution**
City of Ottawa, July 2010.
(Water Supply Guidelines)
 - **Technical Bulletin ISD-2010-2**
City of Ottawa, December 15, 2010.
(ISD-2010-2)
 - **Technical Bulletin ISDTB-2014-02**
City of Ottawa, May 27, 2014.
(ISDTB-2014-02)
 - **Technical Bulletin ISDTB-2018-02**
City of Ottawa, March 21, 2018.
(ISDTB-2018-02)
- **Design Guidelines for Sewage Works,**
Ministry of the Environment, 2008.
(MOE Design Guidelines)
 - **Technical Bulletin ISDTB-2014-01**
City of Ottawa, February 5, 2014.
(ITSB-2014-01)
 - **Technical Bulletin PIEDTB-2016-01**
City of Ottawa, September 6, 2016.
(PIEDTB-2016-01)
 - **Technical Bulletin ISTB-2018-01**
City of Ottawa, March 21, 2018.
(ISTB-2018-01)
- **Stormwater Planning and Design Manual,**
Ministry of the Environment, March 2003.
(SWMP Design Manual)
- **Ontario Building Code Compendium**
Ministry of Municipal Affairs and Housing Building Development Branch,

January 1, 2010 Update.
(OBC)

- **Water Supply for Public Fire Protection**
Fire Underwriters Survey, 1999.
(FUS)
- **Low Impact Development Stormwater Management Planning and Design Guide**
Credit Valley Conservation & Toronto and Region Conservation, 2010.
(LID Guide)
- **Former CFB Rockcliffe Master Servicing Study**
IBI Group, August 2015.
(MSS)
- **Low Impact Development (LID) Demonstration Project**
Aquafor Beech Ltd., August 2015.
(LID Demonstration Project)
- **Design Brief Wateridge Village at Rockcliffe Phase 1A**
IBI Group., April 2016.
(Design Brief Phase 1A)
- **Design Brief Wateridge Village at Rockcliffe Phase 1B**
IBI Group., June 2017.
(Design Brief Phase 1B)

3.0 WATER SUPPLY SERVICING

3.1 Existing Water Supply Services

The subject property lies within the City of Ottawa MONT pressure zone, as shown by the Pressure Zone map in **Appendix B**. A local 200 mm diameter watermain currently exists within Bareille Snow Street, and a local 400mm watermain currently exists within Codd's Road, which are available to service the subject site.

The water servicing for the subject site was accounted for in the design of the water distribution system outlined in the **Design Brief Phase 1B** with a population of **514**. Contemplated water demand according to the design brief for the subject property is summarized below:

Table 1
Summary of Water Demand per *Design Brief Phase 1B*

Design Parameter	Total Demand (L/min)
Average Day	99.9
Peak Hour	549.7
Max Day	249.9

Table 2 summarizes the available fire flow for the hydrants adjacent to the subject site according to **Design Brief Phase 1B**.

Table 2
Available Fire Flow at Hydrants per *Design Brief Phase 1B*

Street Name	Available Fire Flow (L/min)
Codd's Road	53,759
Mikinak Road	49,504
Hemlock Road	48,265
Bareille-Snow Street	30,173

Refer to **Appendix B** for relevant extracted pages from the **Design Brief Phase 1B**.

3.2 Water Supply Servicing Design

It is proposed to provide one connection to the 200mm watermain within Bareille-Snow Street and one connection to the 400mm watermain within Codd's Road. The site is serviced by surrounding fire hydrants on Squadron Hemlock Road, Mikinak Road, Codd's Road and Bareille-Snow Street.

Table 3 summarizes the **Water Supply Guidelines** employed in the preparation of the water demand estimate for the proposed development.

Table 3
Water Supply Design Criteria

Design Parameter	Value
Townhouse	2.7 P/unit
Residential Average Daily Demand	280 L/d/P***
Residential Maximum Daily Demand	2.5 x avg. day *
Residential Maximum Hourly	5.5 x avg. day *
Minimum Watermain Size	150mm diameter
Minimum Depth of Cover	2.4m from top of watermain to finished grade
During normal operating conditions desired operating pressure is within	350kPa and 480kPa
During normal operating conditions pressure must not drop below	275kPa
During normal operating conditions pressure must not exceed	552kPa
During fire flow operating pressure must not drop below	140kPa
<p>*Daily average based on Appendix 4-A from Water Supply Guidelines ** Residential Max. Daily and Max. Hourly peaking factors per MOE Guidelines for Drinking-Water Systems Table 3-3 for 0 to 500 persons. -Table updated to reflect ISD-2014-02 ***Daily consumption rate to align with the revised wastewater rates identified by City of Ottawa Technical Bulletin ISTB-2018-03. As a result, DSEL is submitting for a deviation from the Water Supply Guidelines</p>	

Table 4 summarizes the anticipated water supply demand and proposed boundary conditions. The City of Ottawa was contacted to obtain boundary conditions associated with the estimated water demand as indicated in the boundary request correspondence included in **Appendix B**.

Table 4
Water Demand and Boundary Conditions
Proposed Conditions

Design Parameter	Anticipated Demand ¹ (L/min)	Boundary Condition ² Connection 1 (m H ₂ O / kPa)		Boundary Condition ² Connection 2 (m H ₂ O / kPa)	
Average Daily Demand	157.1	59.1	579.8	58.4	572.9
Peak Hour	391.4	57.1	560.2	52.4	514.0
Max Day + Fire Flow	11,000 + 860.3	58.8	576.8	58.1	570.0
<p>1) Water demand calculation per Water Supply Guidelines. See Appendix B for detailed calculations. 2) Boundary conditions supplied by the City of Ottawa for the demands indicated in the correspondence; assumed ground elevation 87.9m at Connection 1 (Codd's Road) and 88.6m at Connection 2 (Barielle-Snow Street). See Appendix B.</p>					

The City provided both the anticipated minimum and maximum water pressures, as well as the estimated water pressure during fire flow demand for the demands as indicated by the correspondence in **Appendix B**. The maximum pressures exceed the required range identified in **Table 3**. A pressure check is recommended during installation to determine if pressure reducing valves are required.

Fire flow requirements are to be determined in accordance with Local Guidelines (**ISDTB-2018-02**), City of Ottawa **Water Supply Guidelines**, and the Ontario Building Code.

Using the Technical Bulletin **ISDTB-2018-02** method, a conservative estimation of fire flow had been established. As coordinated with the building architect, the following assumptions were made:

- Type of construction – Fire-Resistant Construction;
- Occupancy type – Non-Combustible; and
- Sprinkler Protection – Sprinklered - Supervised.

The above assumptions result in an estimated fire flow of approximately **11,000 L/min**, noting that actual building materials selected will affect the estimated flow; see **Appendix B** for detailed FUS calculations. The estimated fire flow for the proposed development can be accommodated by any of the hydrants adjacent to the subject property as the available fire flows as per **Table 2**, exceeds the estimated fire flow for the proposed development.

3.3 Water Supply Conclusion

Anticipated water demand under proposed conditions was submitted to the City of Ottawa for establishing boundary conditions.

The anticipated water demand under proposed conditions was submitted to the City of Ottawa for establishing boundary conditions. As demonstrated by **Table 4**, the maximum pressures exceed the required range identified in the **Water Supply Guidelines**. A pressure check is recommended during installation to determine if pressure reducing valves are required.

As indicated in **Table 3**, DSEL employed a daily consumption rate of 280 L/person/day to align with the revised wastewater rates identified by City of Ottawa Technical Bulletin **ISTB-2018-01**. As a result, DSEL is submitting for a deviation from the **Water Supply Guidelines**.

4.0 WASTEWATER SERVICING

4.1 Existing Wastewater Services

The sanitary flow from the subject property was considered in the wastewater design for the Wateridge Subdivision. A portion of Block 19 was contemplated to drain to the 375mm sanitary sewer within Codd's Road. The total wastewater flow from the **Design Brief Phase 1A** is summarized in **Table 5** below.

Table 5
Wastewater Flow per Design Brief Phase 1A – Directed to Codd's Road

Design Parameter	Total Flow (L/s)
Estimated Average Dry Weather Flow	0.88
Estimated Peak Dry Weather Flow	3.51
Estimated Peak Wet Weather Flow	4.22

The total flow summarized in **Table 5** is from the drainage areas from Block 19 directed to Codd's road per **Design Brief Phase 1A**. Please refer to **Appendix C** for reduced copies of the IBI sanitary design calculations and drainage area map.

4.2 Wastewater Design

It is proposed that the development will connect to the 375mm diameter sanitary sewer within the Codd's Road right-of-way, as contemplated in the **Design Brief Phase 1A**.

Table 6 summarizes the **City Standards** employed in the design of the proposed wastewater sewer system.

Table 6
Wastewater Design Criteria

Design Parameter	Value
Townhouse	2.7 P/unit
Average Daily Demand - Residential	280 L/d/per
Peaking Factor	Harmon's Peaking Factor. 3.8
Infiltration and Inflow Allowance	0.28L/s/ha
Sanitary sewers are to be sized employing the Manning's Equation	$Q = \frac{1}{n} AR^{\frac{2}{3}} S^{\frac{1}{2}}$
Minimum Sewer Size	200mm diameter
Minimum Manning's 'n'	0.013
Minimum Depth of Cover	2.5m from crown of sewer to grade
Minimum Full Flowing Velocity	0.6m/s
Maximum Full Flowing Velocity	3.0m/s
Extracted from Sections 4 and 6 of the City of Ottawa Sewer Design Guidelines, October 2012.	

Table 7 demonstrates the anticipated peak flow from the proposed development. See **Appendix C** for associated calculations.

Table 7
Summary of Estimated Peak Wastewater Flow

Design Parameter	Total Flow (L/s)
Estimated Average Dry Weather Flow	2.69
Estimated Peak Dry Weather Flow	10.16
Estimated Peak Wet Weather Flow	10.61

The estimated sanitary flow, based on the site plan provided in *Drawings/Figures*, anticipates a peak wet weather flow of **10.61 L/s**.

The anticipated peak wastewater flow generated from the proposed site is **5.94 L/s** greater than the flow that was considered to enter the external system between MH176A and MH141A per *Design Brief Phase 1A*.

Based on the analysis completed in *Design Brief Phase 1A* there is available capacity in the local sanitary sewer up to the discharge to the Codd's Road Shaft. The most restrictive leg of local sewer, located between MH141A and MH124A, has **16.76 L/s** of available capacity, which is sufficient to convey the **5.94 L/s** proposed increase in flow. Refer to Appendix C for drainage area map and sanitary design sheets prepared in *Design Brief Phase 1A*.

4.3 Wastewater Servicing Conclusions

The sanitary flow from the subject property has been considered with respect to the wastewater design for the Wateridge Subdivision, outlined in the *Design Brief Phase 1A*.

The proposed development results in a total wastewater flow of **10.61 L/s**, which is **5.94 L/s** greater than the contemplated wastewater flow in the *Design Brief Phase 1A*. As per *Design Brief Phase 1A*, there is sufficient capacity within the designed sanitary system to accommodate the proposed increased sanitary flow.

The proposed wastewater design conforms to all relevant *City Standards*.

5.0 STORMWATER MANAGEMENT

5.1 Existing Stormwater Services

The flow from the subject site was accounted for in **Design Brief Phase 1A** to be conveyed via 3000 mm storm mains to the Eastern SWM Facility. For the development the subject site, major flow is proposed to be directed to a dry pond to the south of Mikinak Road for quantity control. Eventually discharging through the minor system to the Eastern SWM Facility.

The **Design Brief Phase 1A** contemplated that the drainage from the subject site would flow partially into the storm sewer within Codd's Road, Mikinak Road and Bareille-Snow Street. Refer to **Appendix D** for reduced copy of the storm design sheet and drainage area figures prepared by IBI.

Flows that influence the watershed in which the subject property is located are further reviewed by the principal authority. The subject property is located within the Ottawa River watershed, and is therefore subject to review by the Rideau Valley Conservation Authority (RVCA).

5.2 Post-development Stormwater Management Target

Stormwater management requirements for the proposed development were reviewed with the City of Ottawa and CLC, where the proposed development is required to:

- Follow quantity and quality controls outlined in the **Design Brief Phase 1A**;
- Incorporate Low Impact Development measures in accordance with the **Design Brief Phase 1A** and **LID Demonstration Project**.

5.3 Proposed Stormwater Management System

It is proposed that the stormwater from the proposed development will be directed to the 3000 mm storm sewer within Codd's Road.

The following analysis was completed to confirm that adequate capacity is available to convey the minor storm event from the subject property:

Table 8
Summary of Release Rates for Anticipated and Proposed Scenarios – Flow directed to Codd's Road

Storm Event	5-Year Release Rate per Design Brief Phase 1A* (L/s)	5-Year Release Rate Proposed (L/s)
5-Year Storm	194	358.5
Minor System Capture in 100-Year Storm	283	475
* Captured Flow to Codd's Road Sewer per Design Brief Phase 1A		

The stormwater management plan proposes to direct an additional **75.5 L/s** of flow to the Codd's Road storm sewer in the 5-year storm event compared to the 5-year storm event release rate from **Design Brief Phase 1A**. A connection from the subject site to the sewer within Codd's Road is proposed between MH142 and MH141, which has an available capacity of **2617 L/s**, sufficient capacity to convey the minor system flow from the subject site.

As per correspondence with IBI Group, found in **Appendix A**, the minor system flow in the 100-year storm event for the site cannot exceed **475 L/s**. Restrictions include an inlet control device installed at the proposed rainwater harvesting cistern, roof controls and area drains to restrict flow to a maximum of **475 L/s** directed to the minor system on Codd's Road in the major system event. Refer to detailed calculation sheet included in **Appendix D** for further details.

Major flow was contemplated to be directed overland to Mikinak Road from the subject site to the Dry Pond south of the subject site. It is proposed to re-directed the major flow to Codd's Road where it will travel 60m south before discharging to the Dry Pond.

A major overland flow route is located between Building C and Building D with a conveyance capacity of **823 L/s** adequate to convey the 100-year storm event less the **475 L/s** minor storm capture equal to **293.1 L/s**. Refer to **Appendix D** for overland flow route capacity calculation.

5.4 Low Impact Development (LID) Practices

LID measures are proposed in accordance with the **Design Brief Phase 1A** and **LID Demonstration Project**. It is proposed to direct all roof, landscaped and hardscaping flow to pre-treatment LIDs and an internal rainwater harvesting cistern to be used for irrigation purposes.

Table 9, below, summarizes post-development flow rates based on the proposed Site Plan.

Table 9
Stormwater Flow Rate Summary

Control Area	5-Year Release Rate	5-Year Storage	100-Year Release Rate	100-Year Storage Required
	(L/s)	(m ³)	(L/s)	(m ³)
Unattenuated Areas	47.31	0.0	101.36	0.0
Attenuated Areas	169.69	98.7	355.64	206.9
Total	217.0	98.73	457.00	206.9

It is calculated that **206.9 m³** of storage will be required on site to attenuate flow to the established release rate of **355.6 L/s** and will be provided via a rainwater harvesting cistern.

The rainwater harvesting tank has been sized to store the minimum of the 15 mm event directed from a total of **1.41 ha** collected by roof drains and surface drains above the parking garage, refer to **SWM-1** for drainage directed to the building. A rainwater harvesting tank in combination with pre-treatment LIDs with **244.5 m³** of storage is required to provide the adequate storage per the **LID Demonstration Project**.

5.5 Stormwater Servicing Conclusions

The proposed flow entering the sewers within Codd's Road is increased in the proposed development compared to that in **Design Brief Phase 1A**, there is sufficient capacity within the sewers to accommodate this increased flow in the 5-year event.

A rainwater harvesting system is proposed to collect runoff from roof drains and surface drains above the parking garage to be used for irrigation. The rainwater harvesting system is proposed to be **244.5 m³** per the **LID Demonstration Project**.

The proposed stormwater design conforms to all relevant **City Standards** and Policies

6.0 UTILITIES

Utility servicing will be coordinated with the individual utility companies prior to site development.

7.0 EROSION AND SEDIMENT CONTROL

Soil erosion occurs naturally and is a function of soil type, climate and topography. During construction the extent of erosion losses is exaggerated due to the removal of vegetation and the top layer of soil becoming agitated.

Prior to topsoil stripping, earthworks or underground construction, erosion and sediment controls will be implemented and will be maintained throughout construction.

Silt fence will be installed around the perimeter of the site and will be cleaned and maintained throughout construction. Silt fence will remain in place until the working areas have been stabilized and re-vegetated.

Catch basins will have SILTSACKS or an approved equivalent installed under the grate during construction to protect from silt entering the storm sewer system.

A mud mat will be installed at the construction access in order to prevent mud tracking onto adjacent roads.

Erosion and sediment controls must be in place during construction. The following recommendations to the contractor will be included in contract documents:

- Limit extent of exposed soils at any given time;
- Re-vegetate exposed areas as soon as possible;
- Minimize the area to be cleared and grubbed;
- Protect exposed slopes with plastic or synthetic mulches;
- Install silt fence to prevent sediment from entering existing ditches;
- No refueling or cleaning of equipment near existing watercourses;
- Provide sediment traps and basins during dewatering;
- Install filter cloth between catch basins and frames;
- Plan construction at proper time to avoid flooding; and
- Establish material stockpiles away from watercourses, so that barriers and filters may be installed.

The contractor will, at every rainfall, complete inspections and guarantee proper performance. The inspection is to include:

- Verification that water is not flowing under silt barriers; and
- Clean and change filter cloth at catch basins.

8.0 CONCLUSION AND RECOMMENDATIONS

David Schaeffer Engineering Ltd. (DSEL) has been retained to prepare a Functional Servicing and Stormwater Management Report for the proposed development for Block 19 of the former CFB Rockcliffe lands, which are currently under re-development. The preceding report outlines the following:

- Based on boundary conditions provided by the City the existing municipal water infrastructure is capable of providing the contemplated development, however pressures exceed the City's required pressure range. A pressure check is recommended during installation to determine if pressure reducing valves are required;
- Based on estimated fire flow per the **FUS**, there is sufficient pressure within the local system to provide the required fire flow;
- The proposed development is anticipated to have a peak wet weather flow of **10.61 L/s**; the adjacent sanitary sewer has capacity to convey the flow;
- The quantity and quality controls are provided for the site through a dry pond to the south of the site and the Eastern SWM Facility, as outlined in the **Design Brief Phase 1A**;
- Minor system flow is restricted to a maximum of **475 L/s** through inlet control device within the rainwater harvesting tank, roof controls and restrictions on area drains overtop of the parking garage.
- Collection of rainwater for the purpose of irrigation is proposed by the use of a rainwater harvesting tank in accordance with the **LID Demonstration Project**.

Prepared by,
David Schaeffer Engineering Ltd.



Per: Alison J. Gosling, EIT

Reviewed by,
David Schaeffer Engineering Ltd.



Per: Steven J. Pichette, P.Eng.

APPENDIX A

Pre-Consultation

DEVELOPMENT SERVICING STUDY CHECKLIST

18-947

16/10/2019

4.1 General Content		
<input type="checkbox"/>	Executive Summary (for larger reports only).	N/A
<input checked="" type="checkbox"/>	Date and revision number of the report.	Report Cover Sheet
<input checked="" type="checkbox"/>	Location map and plan showing municipal address, boundary, and layout of proposed development.	Drawings/Figures
<input checked="" type="checkbox"/>	Plan showing the site and location of all existing services.	Figure 1
<input checked="" type="checkbox"/>	Development statistics, land use, density, adherence to zoning and official plan, and reference to applicable subwatershed and watershed plans that provide context to applicable subwatershed and watershed plans that provide context to which individual developments must adhere.	Section 1.0
<input checked="" type="checkbox"/>	Summary of Pre-consultation Meetings with City and other approval agencies.	Section 1.3
<input checked="" type="checkbox"/>	Reference and confirm conformance to higher level studies and reports (Master Servicing Studies, Environmental Assessments, Community Design Plans), or in the case where it is not in conformance, the proponent must provide justification and develop a defensible design criteria.	Section 2.1
<input checked="" type="checkbox"/>	Statement of objectives and servicing criteria.	Section 1.0
<input checked="" type="checkbox"/>	Identification of existing and proposed infrastructure available in the immediate area.	Sections 3.1, 4.1, 5.1
<input type="checkbox"/>	Identification of Environmentally Significant Areas, watercourses and Municipal Drains potentially impacted by the proposed development (Reference can be made to the Natural Heritage Studies, if available).	N/A
<input checked="" type="checkbox"/>	Concept level master grading plan to confirm existing and proposed grades in the development. This is required to confirm the feasibility of proposed stormwater management and drainage, soil removal and fill constraints, and potential impacts to neighbouring properties. This is also required to confirm that the proposed grading will not impede existing major system flow paths.	N/A
<input type="checkbox"/>	Identification of potential impacts of proposed piped services on private services (such as wells and septic fields on adjacent lands) and mitigation required to address potential impacts.	N/A
<input type="checkbox"/>	Proposed phasing of the development, if applicable.	N/A
<input type="checkbox"/>	Reference to geotechnical studies and recommendations concerning servicing.	N/A
<input checked="" type="checkbox"/>	All preliminary and formal site plan submissions should have the following information: -Metric scale -North arrow (including construction North) -Key plan -Name and contact information of applicant and property owner -Property limits including bearings and dimensions -Existing and proposed structures and parking areas -Easements, road widening and rights-of-way -Adjacent street names	N/A
4.2 Development Servicing Report: Water		
<input type="checkbox"/>	Confirm consistency with Master Servicing Study, if available	N/A
<input checked="" type="checkbox"/>	Availability of public infrastructure to service proposed development	Section 1.1
<input checked="" type="checkbox"/>	Identification of system constraints	Section 3.1
<input checked="" type="checkbox"/>	Identify boundary conditions	Section 3.1, 3.2
<input checked="" type="checkbox"/>	Confirmation of adequate domestic supply and pressure	Section 3.3

<input checked="" type="checkbox"/>	Confirmation of adequate fire flow protection and confirmation that fire flow is calculated as per the Fire Underwriter's Survey. Output should show available fire flow at locations throughout the development.	Section 3.2
<input type="checkbox"/>	Provide a check of high pressures. If pressure is found to be high, an assessment is required to confirm the application of pressure reducing valves.	N/A
<input type="checkbox"/>	Definition of phasing constraints. Hydraulic modeling is required to confirm servicing for all defined phases of the project including the ultimate design	N/A
<input type="checkbox"/>	Address reliability requirements such as appropriate location of shut-off valves	N/A
<input type="checkbox"/>	Check on the necessity of a pressure zone boundary modification	N/A
<input checked="" type="checkbox"/>	Reference to water supply analysis to show that major infrastructure is capable of delivering sufficient water for the proposed land use. This includes data that shows that the expected demands under average day, peak hour and fire flow conditions provide water within the required pressure range	Section 3.2, 3.3
<input type="checkbox"/>	Description of the proposed water distribution network, including locations of proposed connections to the existing system, provisions for necessary looping, and appurtenances (valves, pressure reducing valves, valve chambers, and fire hydrants) including special metering provisions.	N/A
<input type="checkbox"/>	Description of off-site required feeder mains, booster pumping stations, and other water infrastructure that will be ultimately required to service proposed development, including financing, interim facilities, and timing of implementation.	N/A
<input checked="" type="checkbox"/>	Confirmation that water demands are calculated based on the City of Ottawa Design Guidelines.	Section 3.2
<input type="checkbox"/>	Provision of a model schematic showing the boundary conditions locations, streets, parcels, and building locations for reference.	N/A

4.3 Development Servicing Report: Wastewater

<input checked="" type="checkbox"/>	Summary of proposed design criteria (Note: Wet-weather flow criteria should not deviate from the City of Ottawa Sewer Design Guidelines. Monitored flow data from relatively new infrastructure cannot be used to justify capacity requirements for proposed infrastructure).	Section 4.2
<input type="checkbox"/>	Confirm consistency with Master Servicing Study and/or justifications for deviations.	N/A
<input type="checkbox"/>	Consideration of local conditions that may contribute to extraneous flows that are higher than the recommended flows in the guidelines. This includes groundwater and soil conditions, and age and condition of sewers.	N/A
<input checked="" type="checkbox"/>	Description of existing sanitary sewer available for discharge of wastewater from proposed development.	Section 4.1
<input checked="" type="checkbox"/>	Verify available capacity in downstream sanitary sewer and/or identification of upgrades necessary to service the proposed development. (Reference can be made to previously completed Master Servicing Study if applicable)	Section 4.2
<input checked="" type="checkbox"/>	Calculations related to dry-weather and wet-weather flow rates from the development in standard MOE sanitary sewer design table (Appendix 'C') format.	Section 4.2, Appendix C
<input checked="" type="checkbox"/>	Description of proposed sewer network including sewers, pumping stations, and forcemains.	Section 4.2
<input type="checkbox"/>	Discussion of previously identified environmental constraints and impact on servicing (environmental constraints are related to limitations imposed on the development in order to preserve the physical condition of watercourses, vegetation, soil cover, as well as protecting against water quantity and quality).	N/A

<input type="checkbox"/>	Pumping stations: impacts of proposed development on existing pumping stations or requirements for new pumping station to service development.	N/A
<input type="checkbox"/>	Forcemain capacity in terms of operational redundancy, surge pressure and maximum flow velocity.	N/A
<input type="checkbox"/>	Identification and implementation of the emergency overflow from sanitary pumping stations in relation to the hydraulic grade line to protect against basement flooding.	N/A
<input type="checkbox"/>	Special considerations such as contamination, corrosive environment etc.	N/A

4.4 Development Servicing Report: Stormwater Checklist

<input checked="" type="checkbox"/>	Description of drainage outlets and downstream constraints including legality of outlets (i.e. municipal drain, right-of-way, watercourse, or private property)	Section 5.1
<input checked="" type="checkbox"/>	Analysis of available capacity in existing public infrastructure.	Section 5.1, Appendix D
<input checked="" type="checkbox"/>	A drawing showing the subject lands, its surroundings, the receiving watercourse, existing drainage patterns, and proposed drainage pattern.	Drawings/Figures
<input checked="" type="checkbox"/>	Water quantity control objective (e.g. controlling post-development peak flows to pre-development level for storm events ranging from the 2 or 5 year event (dependent on the receiving sewer design) to 100 year return period); if other objectives are being applied, a rationale must be included with reference to hydrologic analyses of the potentially affected subwatersheds, taking into account long-term cumulative effects.	Section 5.2
<input checked="" type="checkbox"/>	Water Quality control objective (basic, normal or enhanced level of protection based on the sensitivities of the receiving watercourse) and storage requirements.	Section 5.2
<input checked="" type="checkbox"/>	Description of the stormwater management concept with facility locations and descriptions with references and supporting information	Section 5.3
<input type="checkbox"/>	Set-back from private sewage disposal systems.	N/A
<input type="checkbox"/>	Watercourse and hazard lands setbacks.	N/A
<input checked="" type="checkbox"/>	Record of pre-consultation with the Ontario Ministry of Environment and the Conservation Authority that has jurisdiction on the affected watershed.	Appendix A
<input type="checkbox"/>	Confirm consistency with sub-watershed and Master Servicing Study, if applicable study exists.	N/A
<input checked="" type="checkbox"/>	Storage requirements (complete with calculations) and conveyance capacity for minor events (1:5 year return period) and major events (1:100 year return period).	Section 5.3
<input type="checkbox"/>	Identification of watercourses within the proposed development and how watercourses will be protected, or, if necessary, altered by the proposed development with applicable approvals.	N/A
<input checked="" type="checkbox"/>	Calculate pre and post development peak flow rates including a description of existing site conditions and proposed impervious areas and drainage catchments in comparison to existing conditions.	Section 5.1, 5.3
<input type="checkbox"/>	Any proposed diversion of drainage catchment areas from one outlet to another.	N/A
<input type="checkbox"/>	Proposed minor and major systems including locations and sizes of stormwater trunk sewers, and stormwater management facilities.	N/A
<input type="checkbox"/>	If quantity control is not proposed, demonstration that downstream system has adequate capacity for the post-development flows up to and including the 100-year return period storm event.	N/A
<input type="checkbox"/>	Identification of potential impacts to receiving watercourses	N/A
<input type="checkbox"/>	Identification of municipal drains and related approval requirements.	N/A

<input checked="" type="checkbox"/>	Descriptions of how the conveyance and storage capacity will be achieved for the development.	Section 5.3
<input type="checkbox"/>	100 year flood levels and major flow routing to protect proposed development from flooding for establishing minimum building elevations (MBE) and overall grading.	N/A
<input type="checkbox"/>	Inclusion of hydraulic analysis including hydraulic grade line elevations.	N/A
<input type="checkbox"/>	Description of approach to erosion and sediment control during construction for the protection of receiving watercourse or drainage corridors.	N/A
<input type="checkbox"/>	Identification of floodplains – proponent to obtain relevant floodplain information from the appropriate Conservation Authority. The proponent may be required to delineate floodplain elevations to the satisfaction of the Conservation Authority if such information is not available or if information does not match current conditions.	N/A
<input type="checkbox"/>	Identification of fill constraints related to floodplain and geotechnical investigation.	N/A

4.5 Approval and Permit Requirements: Checklist

<input checked="" type="checkbox"/>	Conservation Authority as the designated approval agency for modification of floodplain, potential impact on fish habitat, proposed works in or adjacent to a watercourse, cut/fill permits and Approval under Lakes and Rivers Improvement Act. The Conservation Authority is not the approval authority for the Lakes and Rivers Improvement ct. Where there are Conservation Authority regulations in place, approval under the Lakes and Rivers Improvement Act is not required, except in cases of dams as defined in the Act.	Section 1.2
<input type="checkbox"/>	Application for Certificate of Approval (CofA) under the Ontario Water Resources Act.	N/A
<input type="checkbox"/>	Changes to Municipal Drains.	N/A
<input type="checkbox"/>	Other permits (National Capital Commission, Parks Canada, Public Works and Government Services Canada, Ministry of Transportation etc.)	N/A

4.6 Conclusion Checklist

<input checked="" type="checkbox"/>	Clearly stated conclusions and recommendations	Section 7.0
<input type="checkbox"/>	Comments received from review agencies including the City of Ottawa and information on how the comments were addressed. Final sign-off from the responsible reviewing agency.	
<input type="checkbox"/>	All draft and final reports shall be signed and stamped by a professional Engineer registered in Ontario	

Steve Merrick

From: David Gilbert <DGilbert@Patersongroup.ca>
Sent: Friday, September 22, 2017 2:30 PM
To: Steve Merrick
Subject: RE: Wateridge Village Phase 1B - Geotech Report

Hi Steve,

As discussed, the upper portion of the soils profile within Block 19 consists mainly of a silty clay. If this material were re-compacted across the other blocks, we estimate that the infiltration rate would be approximately 50 mm/day. To provide an accurate infiltration rate assessment, we could complete a series of pack permeameter tests once the material has been placed and re-compacted or in its presence state within Block 19.

Best regards,

David Gilbert, P.Eng.
Senior Geotechnical Engineer

patersongroup

Solution Oriented Engineering
60 years serving our clients

154 Colonnade Road South
Ottawa, Ontario
K2E 7J5
Tel: 613.226-7381 ext. 205

From: Steve Merrick [mailto:SMerrick@dsel.ca]
Sent: Thursday, September 21, 2017 9:21 AM
To: David Gilbert <DGilbert@Patersongroup.ca>
Subject: RE: Wateridge Village Phase 1B - Geotech Report

Hi Dave, same project but a different question. Can Paterson please provide an average infiltration rate for the Block 19? We are looking for this to size our LID systems understanding that the LID measures for Blocks 15, 22 and 24 will be within fill taken from Block 19.

I'll follow up with a phone call this morning to discuss.

Thanks!

Steve Merrick, P.Eng.
Project Manager / Intermediate Designer

DSEL

david schaeffer engineering ltd.

120 Iber Road, Unit 103
Stittsville, ON K2S 1E9

phone: (613) 836-0856 ext. 561
cell: (613) 222-7816
email: smerrick@DSEL.ca

This email, including any attachments, is for the sole use of the intended recipient(s) and may contain private, confidential, and privileged information. Any unauthorized review, use, disclosure, or distribution is prohibited. If you are not the intended recipient, or if this information has been inappropriately forwarded to you, please contact the sender by reply email and destroy all copies of the original.

From: Steve Merrick
Sent: Wednesday, September 20, 2017 4:03 PM
To: 'David Gilbert' <DGilbert@Patersongroup.ca>
Cc: 'Adam Fobert' <afobert@dsel.ca>
Subject: RE: Wateridge Village Phase 1B - Geotech Report

Thanks Dave, we are trying to get the feasibility of this option back to Mattamy quickly and your input would really help.

Thanks!

Steve Merrick, P.Eng.
Project Manager / Intermediate Designer

DSEL
david schaeffer engineering ltd.

120 Iber Road, Unit 103
Stittsville, ON K2S 1E9

phone: (613) 836-0856 ext. 561
cell: (613) 222-7816
email: smerrick@DSEL.ca

This email, including any attachments, is for the sole use of the intended recipient(s) and may contain private, confidential, and privileged information. Any unauthorized review, use, disclosure, or distribution is prohibited. If you are not the intended recipient, or if this information has been inappropriately forwarded to you, please contact the sender by reply email and destroy all copies of the original.

From: Steve Merrick
Sent: Wednesday, September 20, 2017 3:29 PM
To: David Gilbert <DGilbert@Patersongroup.ca>
Cc: 'Adam Fobert' <afobert@dsel.ca>
Subject: RE: Wateridge Village Phase 1B - Geotech Report

Hi Dave,

We are looking at some servicing options for Mattamy' blocks at Wateridge and wanted to input from Paterson on zone of influence and sewers in close proximity to the units. I have attached 3 sketches (very rough) showing some restrictive areas. Can you advise on the zone of influence from the footings and provide any other geotechnical recommendations or issues with the proposed sections?

Please refer to the servicing plans for locations of the 3 sections.

Thanks!

Steve Merrick, P.Eng.
Project Manager / Intermediate Designer

DSEL

david schaeffer engineering ltd.

120 Iber Road, Unit 103
Stittsville, ON K2S 1E9

phone: (613) 836-0856 ext. 561
cell: (613) 222-7816
email: smerrick@DSEL.ca

This email, including any attachments, is for the sole use of the intended recipient(s) and may contain private, confidential, and privileged information. Any unauthorized review, use, disclosure, or distribution is prohibited. If you are not the intended recipient, or if this information has been inappropriately forwarded to you, please contact the sender by reply email and destroy all copies of the original.

From: Jillian Normand [<mailto:Jillian.Normand@mattamycorp.com>]

Sent: Wednesday, August 9, 2017 5:21 PM

To: Adam Fobert <AFobert@dsel.ca>; Steve Merrick <SMerrick@dsel.ca>; Anne-Claude Schellenberg <ACSchellenberg@nak-design.com>; Sean Leogreen <sleogreen@nak-design.com>; Anita Bennell <abennell@nak-design.com>; Kevin Murphy <Kevin.Murphy@mattamycorp.com>; Jessica McLellan <Jessica.McLellan@mattamycorp.com>; Marco VanderMaas <MVanderMaas@g4architects.com>; Daniel Potechin <Daniel.Potechin@mattamycorp.com>

Subject: Wateridge Village Phase 1B - Geotech Report

Hi team,

Please see attached for the updated Geotech Report, for your reference.

Jillian



Jillian Normand

Land Development Manager

T (613) 831-5144 (direct). C (613) 415-7786. F (613) 831-9060

Jillian.Normand@mattamycorp.com

Ottawa Office: 50 Hines Road, Suite 100, Ottawa, ON Canada K2K 2M5

Notice: This email is intended for use of the party to whom it is addressed and may contain confidential information. If you have received this email in error, please inform me and delete it. Thank you.

Steve Merrick

From: Winston Yang <Winston.Yang@ibigroup.com>
Sent: Wednesday, August 16, 2017 11:50 AM
To: Adam Fobert; Jean Lachance
Cc: Jillian Normand; Jim Moffatt
Subject: RE: 918 Mattamy - Wateridge: IBI Servicing Review

Hi Adam and Jean,

I have reviewed the impact as per DSEL design for Block 15, 22 and 24.

Upon review of the proposed grading plans for Blocks 15, 22, and 24, we found the leave grades provided by DSEL to be reasonable.

We do not have a conceptual plan for Block 19 yet. The leave grades for that block seem low for a typical basement development. However they might be fine if underground parking is planned.

For the Servicing side, the storm and sanitary outlets location for each block were changed compared to the MSS and Design Brief.

Then we have implemented the changes DSEL made into our sewer design and have examined the capacity for each downstream sewers.

The result shows that the downstream sewers for storm and sanitary have the capacity to convey the flow for all new outlets for blocks, 15, 22 and 24.

In order to minimize the impact and cost, we are going to shift some manholes to accommodate the new outlets base on DSEL design.

For Block 22, MH210 and MH210A can be shifted to the south to replace the STM101 and SAN1 along Michael Stoqua Street.

For Block 24, MH213 and MH213A can be shifted to the south to replace the STM101 and SAN1 along Moses Tenisco Street. At the same time, MH212 and MH212A will be shifted to the south in order to reduce the length of the sewers. For Block 15, there is no choice, the manhole STM101 and SAN1 are required for Squadron Crescent.

Since the typical 1200mm Dia. Manholes have been already ordered by the contractor.

We will contact the contractor to find out any further impacts will be caused by shifting the manholes.

For the storm section below. DSEL met the IBI criteria for the proposed lots.

In regards to Block 19, the drainage areas should be corresponded to IBI Lot141, Lot 167 in Phase 1A and Lot208B, Lot209 in Phase 1B.

And the IBI 100 year capture rate is 475l/s (283l/s+63l/s+46l/s+83l/s). Please considered in your design later on.

Should you have any questions please do not hesitate to contact either Jim or me.

Yours truly,

Winston Yang P.Eng.

email Winston.Yang@ibigroup.com web www.ibigroup.com

IBI GROUP

Suite 400, 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel +1 613 225 1311 fax +1 613 225 9868



NOTE: This email message/attachments may contain privileged and confidential information. If received in error, please notify the sender and delete this e-mail message.

NOTE: Ce courriel peut contenir de l'information privilégiée et confidentielle. Si vous avez reçu ce message par erreur, veuillez le mentionner immédiatement à l'expéditeur et effacer ce courriel.

From: Adam Fobert [mailto:AFobert@dsel.ca]
Sent: Tuesday, August 15, 2017 5:27 PM
To: Winston Yang <Winston.Yang@ibigroup.com>; Jim Moffatt <jmoffatt@IBIGroup.com>
Cc: Jean Lachance <JLachance@clc.ca>; Jillian Normand <Jillian.Normand@mattamycorp.com>
Subject: 918 Mattamy - Wateridge: IBI Servicing Review

Hello Jim and Winston,

How is your review of our site servicing is coming along? I have reviewed your Design Brief's for Phase 1A and 1B and have compared the analysis contained within to our proposed design.

I offer the following considerations based on my review:

General:

DSEL proposed one storm and one sanitary connection to each block. The City indicated that this was their expectation during our pre-consultation as it is their standard practice for multi-block parcels.

Block 15: The servicing brief shows three connections to Squadron Crescent. DSEL are proposing one connection downstream of the contemplated connections.

Block 22: The surrounding grades slope from east to west. The servicing brief shows a drainage divide mid-block, where half the site drains to Moses Tenisco and the other to Michael Stoqua. Moses Tenisco is 1.14m higher than Michael Stoqua at the proposed road connection points. As such, to avoid fighting grades DSEL proposed storm and sanitary connections to Michael Stoqua only.

Block 24: Moses Tenisco slopes from north to south 1.1m from Hemlock to Mikinak. The servicing brief shows a drainage divide mid-block with connections to Moses Tenisco and Mikinak. DSEL proposed a storm and sanitary outlet at the southern road connection on Moses Tenisco based on Mattamy's proposed site. This avoids fighting grades internally.

Wastewater:

Block 15:

IBI Servicing Brief = 487.3p

Mattamy Proposal = 335p

Proposed connections are downstream of IBI contemplated connections. Population is less than included in servicing brief. Therefore, we do not expect servicing issues with Block 15.

Block 22:

IBI Servicing Brief ~ 105p (note that I am interpolating since half of Block 22 is included in northern half of Block 24.)

Mattamy Proposal = 52p

IBI servicing brief assumed 52.5p tributary to Moses Tenisco. Therefore, we do not expect capacity issues.

Block 24:

IBI Servicing Brief ~284.4p (note that I am interpolating based on the population shown on phase 1A southern half of block 24).

Mattamy Proposal = 364p

DSEL reviewed the available capacity in the receiving sewers and did not see any capacity issues.

Note: Mattamy's proposed servicing eliminates the need for 63.8m of sanitary sewer on Moses Tennisco from MH213A to MH212A. Savings to CLC.

Stormwater:

I have reviewed Appendix E of the servicing briefs to compare our calculations to the assumptions used in the model.

Review of the Summary of DDSWMM Parameters

Block 15:

IBI Servicing brief: No storage assumed. 5 and 100 year capture 396L/s

Mattamy's proposal: 275m³ of storage provided. DSEL's estimated 5-year peak 357.4L/s

Block 19:

IBI Servicing brief: No storage assumed. 194 + 57 (note that Lot 209 and 208B are missing from chart).

Mattamy's proposal: TBD.

Block 22:

IBI Servicing brief: No storage assumed. 5 and 100 year (46 + 46) 92L/s

Mattamy's proposal: 46.5m³ of storage provided. DSEL's estimated 5-year peak 87L/s.

Block 24:

IBI Servicing brief: No Storage. 5 and 100 year capture (162 +162) 324L/s.

Mattamy's proposal: 27.3m³ of storage provided. DSEL's estimated 5-year peak 325.7L/s.

Let me know if you have any comments or questions. Thank you for your time.

Adam Fobert, P.Eng.
Manager of Site Plan Design

DSEL

david schaeffer engineering ltd.

120 Iber Road, Unit 103
Stittsville, ON K2S 1E9

office: (613) 836-0856
direct: (613) 836-0626
cell: (613) 222-9493
email: afobert@DSEL.ca

This email, including any attachments, is for the sole use of the intended recipient(s) and may contain private, confidential, and privileged information. Any unauthorized review, use, disclosure, or distribution is prohibited. If you are not the intended recipient or if this information has been inappropriately forwarded to you, please contact the sender by reply email and destroy all copies of the original.

APPENDIX B

Water Supply

Ogilvie Rd.
Backup P.S.


FOREST RIDGE P.S.

ORLEANS RES.

MONTREAL ROAD P.S.

BRITTANY DRIVE P.S.

REET P.S.



Alison Gosling

From: Fraser, Mark <Mark.Fraser@ottawa.ca>
Sent: October 2, 2019 2:01 PM
To: Alison Gosling
Cc: Charlotte Kelly
Subject: RE: 17-947 Wateridge Block 19 - Boundary Condition Request
Attachments: wtr-2019-09-23_947.pdf; Wateridge Village (rockcliffe) Block 19 Sept 2019.pdf

Follow Up Flag: Follow up
Flag Status: Completed

Hi Alison,

Please find below boundary conditions, HGL, for hydraulic analysis at 681 Mikinak Road (Wateridge Village-Block 19) assumed to be connected to the existing 406mm dia. watermain within Codd's Road and the existing 203mm dia. watermain within Barielle-Snow Street (see attached for connection locations):

Block 19-Wateridge Village Subdivision

Type of Development: Residential and Commercial

Site Address: 681 Mikinak Road

Average Day Demand: 2.62 L/s

Maximum Daily Demand: 6.52 L/s

Maximum Hourly Demand: 14.34 L/s

Fire Flow: 11,000 L/min.

Existing Conditions based on current pump operations:

CONNECTION 1 (406mm dia. - Codd's Road)

MAX HGL = 147.0m, the maximum pressure is estimated to be more than 80 psi. A pressure check at completion of construction is recommended to determine if pressure control is required.

MIN HGL = 146.7m

MXDY+Fire (183 L/s) = 145.0m

CONNECTION 2 (203mm dia. - Barielle-Snow Street)

MAX HGL = 147.0m, the maximum pressure is estimated to be more than 80 psi. A pressure check at completion of construction is recommended to determine if pressure control is required.

MIN HGL = 146.7m

MXDY+Fire (183 L/s) = 141.0m

Please note the following:

- *Boundary conditions provided above are for existing conditions. Upgrades to the Montreal and Brittany pump stations are currently being planned to support the CFB Rockcliffe development. The City plans to control the discharge HGL to 143.0m. Furthermore, the current plan is to use a different pumping strategy that will try to maintain a constant HGL of 143.0m even during peak hour and/or fire flow conditions.*

These are for current conditions and are based on computer model simulation.

Disclaimer: The boundary condition information is based on current operation of the city water distribution system. The computer model simulation is based on the best information available at the time. The operation of the water distribution system can change on a regular basis, resulting in a variation in boundary conditions. The physical properties

of watermains deteriorate over time, as such must be assumed in the absence of actual field test data. The variation in physical watermain properties can therefore alter the results of the computer model simulation.

Regards,

Mark Fraser

Project Manager, Planning Services
Development Review Central Branch
City of Ottawa | Ville d'Ottawa
Planning, Infrastructure and Economic Development Department
110 Laurier Avenue West, 4th Floor, Ottawa ON, K1P 1J1
Tel: [613.580.2424](tel:613.580.2424) ext. 27791
Fax: 613-580-2576
Mail: Code 01-14
Email: Mark.Fraser@ottawa.ca

**Please consider your environmental responsibility before printing this e-mail*

This message, including any document or file attached, is intended only for the addressee and may contain privileged and /or confidential information. Any person is strictly prohibited from reading, using, disclosing or copying this message. If you received this message in error, please notify the sender and delete the message. Thank you.

From: Alison Gosling <AGosling@dsel.ca>
Sent: September 24, 2019 5:55 PM
To: Fraser, Mark <Mark.Fraser@ottawa.ca>
Cc: Charlotte Kelly <CKelly@dsel.ca>
Subject: 17-947 Wateridge Block 19 - Boundary Condition Request

CAUTION: This email originated from an External Sender. Please do not click links or open attachments unless you recognize the source.

ATTENTION : Ce courriel provient d'un expéditeur externe. Ne cliquez sur aucun lien et n'ouvrez pas de pièce jointe, excepté si vous connaissez l'expéditeur.


Good afternoon Mark,

We would like to request water boundary conditions for 681 Mikinak Road, located within the Wateridge development, using the following proposed development demands:

1. Location of Service / Street Number: Codd's Road / Barielle-Snow Street
2. Type of development and the amount of fire flow required for the proposed development:
 - The development would include approximately **791 m²** of commercial space **445 units** divided between **four** 6-storey condominium buildings.
 - It is anticipated that the development will have a dual connection to be serviced from the existing 406mm diameter watermain within Codd's Road and the existing 203mm diameter watermain within Barielle-Snow Street, as shown by the map below.
 - Fire demand based on Technical Bulletin ISTB-2018-02 has been used to estimate a maximum fire demand of **11,000 L/min**. Refer to the attached for detailed calculations.

Additional Demand	L/min	L/s
Avg. Daily	157.1	2.62
Max Day	391.4	6.52

If you have any questions, please feel free to contact me.



Thank you,

Alison Gosling, E.I.T.
Junior Project Manager

DSEL

david schaeffer engineering ltd.

120 Iber Road, Unit 103
Stittsville, ON K2S 1E9

phone: (613) 836-0856 ext.542

email: agosling@dsel.ca

This email, including any attachments, is for the sole use of the intended recipient(s) and may contain private, confidential, and privileged information. Any unauthorized review, use, disclosure, or distribution is prohibited. If you are not the intended recipient, or if this information has been inappropriately forwarded to you, please contact the sender by reply email and destroy all copies of the original.

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.

Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

Boundary Condition for Wateridge Village (CFB Rockcliffe) Block 19




Connection 1
























Connection 2

Legend
w_Pipe
Ownership
— Private
— Public
























Phase 1A - Node ID's























Basic Day Future HGL 143.0m - Junction Report

		ID	Demand (L/s)	Elevation (m)	Head (m)	Pressure (kPa)
1		J01	0.20	88.50	143.00	534.04
2		J02	0.12	87.60	143.00	542.86
3		J04	0.14	87.00	143.00	548.73
4		J06	0.08	85.35	143.00	564.90
5		J10	0.18	85.60	143.00	562.44
6		J12	0.11	85.50	143.00	563.42
7		J14	0.16	88.10	143.00	537.94
8		J16	0.26	88.50	143.00	534.02
9		J18	0.15	89.00	143.00	529.12
10		J20	0.13	86.60	143.00	552.64
11		J22	0.22	87.45	143.00	544.31
12		J24	0.26	88.30	143.00	535.98
13		J26	0.22	86.10	143.00	557.54
14		J28	0.26	87.50	143.00	543.82
15		J30	0.08	88.90	143.00	530.10
16		J32	0.00	88.10	143.00	537.96
17		J34	1.01	88.30	143.00	535.99
18		J36	0.00	85.65	143.00	561.96
19		R01	0.00	103.00	143.00	391.97
20		R02	0.36	105.00	143.00	372.36
21		R03	0.00	92.00	143.00	499.76
22		R04	0.00	92.60	143.00	493.88
23		R05	0.00	92.20	143.00	497.80

Peak Hour Future HGL 142.0m - Junction Report

		ID	Demand (L/s)	Elevation (m)	Head (m)	Pressure (kPa)
1		J01	1.08	88.50	141.98	524.04
2		J02	0.66	87.60	141.97	532.82
3		J04	0.78	87.00	141.96	538.57
4		J06	0.42	85.35	141.96	554.72
5		J10	0.96	85.60	141.92	551.91
6		J12	0.61	85.50	141.92	552.86
7		J14	0.88	88.10	141.92	527.35
8		J16	1.45	88.50	141.92	523.43
9		J18	0.80	89.00	141.92	518.55
10		J20	0.74	86.60	141.92	542.06
11		J22	1.19	87.45	141.92	533.72
12		J24	1.45	88.30	141.92	525.44
13		J26	1.21	86.10	141.94	547.15
14		J28	1.45	87.50	141.94	533.43
15		J30	0.45	88.90	141.92	519.52
16		J32	0.00	88.10	141.97	527.86
17		J34	2.73	88.30	141.96	525.84
18		J36	0.00	85.65	141.96	551.80
19		R01	0.00	103.00	142.00	382.17
20		R02	1.97	105.00	141.99	362.47
21		R03	0.00	92.00	142.00	489.96
22		R04	0.00	92.60	141.99	484.03
23		R05	0.00	92.20	142.00	487.96

Max Day + Fire HGL 139.5 - 140.2m - Fireflow Report

		ID	Total Demand (L/s)	Critical Node 1 ID	Critical Node 1 Pressure (kPa)	Critical Node 1 Head (m)	Adjusted Fire-Flow (L/s)	Available Flow @Hydrant (L/s)	Critical Node 2 ID	Critical Node 2 Pressure (kPa)	Critical Node 2 Head (m)	Adjusted Available Flow (L/s)	Design Flow (L/s)
1		J01	167.16	R02	332.18	122.40	1,098.43	926.94	J01	139.97	102.78	926.95	926.95
2		J02	166.97	R02	332.55	121.54	1,142.62	861.82	J18	126.12	100.47	844.12	844.12
3		J04	167.03	R02	332.55	120.94	1,142.68	642.80	J18	126.46	99.91	629.88	629.88
4		J06	166.86	R02	332.55	119.29	1,142.51	605.19	J06	139.97	99.63	605.19	605.19
5		J10	167.11	R02	332.55	119.54	1,142.76	297.57	J10	139.96	99.88	297.57	297.57
6		J12	166.95	R02	332.55	119.44	1,142.60	257.59	J12	139.96	99.78	257.59	257.59
7		J14	167.07	R02	332.55	122.04	1,142.72	253.71	J14	139.96	102.38	253.71	253.71
8		J16	167.33	J16	319.53	121.11	243.72	243.72	J16	139.96	102.78	243.72	243.72
9		J18	167.03	J18	331.60	122.84	255.01	255.01	J18	139.96	103.28	255.01	255.01
10		J20	167.01	J20	315.09	118.75	234.17	234.17	J20	139.96	100.88	234.17	234.17
11		J22	167.21	J22	206.65	108.54	186.24	186.24	J22	139.96	101.73	186.24	186.24
12		J24	167.33	R02	332.55	122.24	1,142.99	294.22	J24	139.96	102.58	294.22	294.22
13		J26	167.22	R02	332.55	120.04	1,142.88	378.63	J26	139.96	100.38	378.63	378.63
14		J28	167.33	R02	332.55	121.44	1,142.99	373.90	J28	139.96	101.78	373.90	373.90
15		J30	166.88	J30	308.66	120.40	236.80	236.80	J30	139.96	103.18	236.80	236.80
16		J32	216.67	R02	328.96	121.67	1,142.31	606.25	J32	139.97	102.38	606.25	606.25
17		J34	218.19	R02	328.96	121.87	1,143.85	549.00	J34	139.97	102.58	549.01	549.01
18		J36	216.67	R02	328.96	119.22	1,142.31	564.62	J36	139.97	99.93	564.62	564.62
19		R02	167.57	R02	331.05	138.78	981.61	981.52	R02	139.97	119.28	981.55	981.55
20		R04	166.67	R02	336.96	126.99	2,727.42	789.43	R04	139.97	106.88	789.44	789.44

Date: Wednesday, June 29, 2016

Basic Day Future HGL 142.0m - Junction Report

	ID	Demand (L/s)	Elevation (m)	Head (m)	Pressure (kPa)
1	J01	0.20	88.50	142.98	533.88
2	J02	0.12	88.10	142.98	537.76
3	J04	0.14	87.00	142.98	548.53
4	J06	0.08	85.35	142.98	564.70
5	J10	0.18	85.60	142.98	562.23
6	J12	0.11	85.50	142.98	563.21
7	J14	0.16	88.10	142.98	537.73
8	J16	0.26	88.50	142.98	533.81
9	J18	0.15	89.00	142.98	528.91
10	J20	0.13	86.60	142.98	552.43
11	J22	0.22	87.45	142.98	544.10
12	J24	0.26	88.30	142.98	535.77
13	J26	0.22	86.10	142.98	557.34
14	J28	0.26	87.50	142.98	543.62
15	J30	0.08	88.90	142.98	529.89
16	J32	0.85	88.10	142.98	537.75
17	J34	1.45	88.30	142.98	535.79
18	J36	0.00	85.65	142.98	561.76
19	J50	0.31	88.40	142.98	534.81
20	J52	0.59	88.90	142.98	529.90
21	J54	0.81	89.40	142.98	525.00
22	J56	1.44	91.00	142.98	509.33
23	J58	1.29	90.60	142.97	513.23
24	J60	0.86	90.00	142.97	519.11
25	J62	0.52	89.85	142.98	520.60
26	J64	1.49	89.10	142.98	527.94
27	J66	0.98	89.40	142.98	525.00
28	J68	0.62	90.50	142.98	514.22
29	J70	0.65	92.50	142.98	494.63
30	J72	1.45	94.05	142.98	479.45
31	J74	0.52	94.80	142.98	472.12
32	J76	0.38	94.00	142.98	479.97
33	J78	1.23	89.90	142.98	520.10
34	J80	0.43	89.25	142.98	526.47
35	J82	1.05	88.75	142.98	531.37
36	J84	0.51	92.60	142.98	493.69
37	J86	1.78	92.60	142.98	493.72
38	J88	0.55	92.20	142.99	497.68
39	R01	0.00	103.00	143.00	391.95
40	R02	0.36	105.00	142.99	372.29
41	R03	0.00	104.00	143.00	382.15

Phase 1B - Peak Hour Future HGL 142.0m - Junction Report

	ID	Demand (L/s)	Elevation (m)	Head (m)	Pressure (kPa)
1	J01	1.08	88.50	141.67	521.02
2	J02	0.66	88.10	141.60	524.24
3	J04	0.78	87.00	141.58	534.83
4	J06	0.42	85.35	141.57	550.95
5	J10	0.96	85.60	141.54	548.15
6	J12	0.61	85.50	141.54	549.10
7	J14	0.88	88.10	141.53	523.59
8	J16	1.45	88.50	141.53	519.67
9	J18	0.80	89.00	141.53	514.79
10	J20	0.74	86.60	141.53	538.30
11	J22	1.19	87.45	141.53	529.97
12	J24	1.45	88.30	141.54	521.68
13	J26	1.21	86.10	141.55	543.39
14	J28	1.45	87.50	141.55	529.67
15	J30	0.45	88.90	141.53	515.76
16	J32	4.70	88.10	141.58	524.04
17	J34	3.91	88.30	141.57	522.04
18	J36	0.00	85.65	141.57	548.01
19	J50	1.69	88.40	141.57	521.02
20	J52	3.26	88.90	141.56	516.05
21	J54	4.44	89.40	141.56	511.15
22	J56	3.89	91.00	141.59	495.71
23	J58	7.11	90.60	141.53	499.05
24	J60	4.73	90.00	141.53	504.97
25	J62	2.87	89.85	141.58	506.89
26	J64	8.18	89.10	141.56	514.05
27	J66	5.38	89.40	141.56	511.11
28	J68	3.42	90.50	141.56	500.35
29	J70	3.58	92.50	141.57	480.85
30	J72	7.99	94.05	141.59	465.84
31	J74	1.41	94.80	141.65	459.09
32	J76	1.02	94.00	141.66	467.03
33	J78	6.78	89.90	141.55	506.15
34	J80	2.34	89.25	141.56	512.58
35	J82	5.79	88.75	141.56	517.46
36	J84	1.38	92.60	141.67	480.88
37	J86	4.80	92.60	141.72	481.33
38	J88	1.48	92.20	141.80	485.99
39	R01	0.00	103.00	141.96	381.81
40	R02	1.97	105.00	141.84	361.01
41	R03	0.00	104.00	141.97	372.06

Phase 1B - Max Day + Fire HGL 139.5 - 140.2m - Fireflow Design Report

		ID	Total Demand (L/s)	Critical Node 1 ID	Critical Node 1 Pressure (kPa)	Critical Node 1 Head (m)	Adjusted Fire-Flow (L/s)	Available Flow @Hydrant (L/s)	Critical Node 2 ID	Critical Node 2 Pressure (kPa)	Critical Node 2 Head (m)	Adjusted Available Flow (L/s)	Design Flow (L/s)
1		J01	167.16	R02	331.32	122.31	1,121.92	1,021.46	J01	139.97	102.78	1,021.48	1,021.48
2		J02	166.97	R02	331.94	121.97	1,198.01	976.69	J62	129.72	101.34	960.99	960.99
3		J04	167.03	R02	331.97	120.88	1,201.90	700.87	J18	129.19	100.18	689.35	689.35
4		J06	166.86	R02	331.98	119.23	1,203.78	660.69	J06	139.97	99.63	660.69	660.69
5		J10	167.11	R02	331.97	119.48	1,202.62	302.21	J10	139.96	99.88	302.21	302.21
6		J12	166.95	R02	331.97	119.38	1,202.42	260.38	J12	139.96	99.78	260.38	260.38
7		J14	167.07	R02	331.97	121.98	1,202.50	256.53	J14	139.96	102.38	256.53	256.53
8		J16	167.33	J16	321.74	121.33	246.17	246.17	J16	139.96	102.78	246.17	246.17
9		J18	167.03	R02	331.97	122.88	1,202.42	257.94	J18	139.96	103.28	257.94	257.94
10		J20	167.01	J20	317.31	118.98	236.20	236.20	J20	139.96	100.88	236.20	236.20
11		J22	167.21	J22	208.86	108.76	187.09	187.09	J22	139.96	101.73	187.09	187.09
12		J24	167.33	R02	331.97	122.18	1,202.69	298.92	J24	139.96	102.58	298.92	298.92
13		J26	167.22	R02	331.97	119.98	1,202.95	389.43	J26	139.96	100.38	389.43	389.43
14		J28	167.33	R02	331.97	121.38	1,202.60	384.11	J28	139.96	101.78	384.11	384.11
15		J30	166.88	J30	310.88	120.63	239.06	239.06	J30	139.96	103.18	239.06	239.06
16		J32	218.80	R02	328.76	121.65	1,230.08	895.98	J62	122.82	100.63	872.30	872.30
17		J34	218.84	R02	328.59	121.83	1,215.80	642.28	J34	139.97	102.58	642.29	642.29
18		J36	216.67	R02	328.53	119.18	1,208.48	630.89	J36	139.97	99.93	630.90	630.90
19		J50	217.44	R02	329.56	122.03	1,306.50	825.07	J50	139.97	102.68	825.07	825.07
20		J52	218.15	R02	330.35	122.61	1,395.62	807.70	J52	139.97	103.18	807.70	807.70
21		J54	218.69	R02	331.05	123.18	1,484.86	790.43	J54	139.97	103.68	790.44	790.44
22		J56	218.83	R02	331.90	124.87	1,607.21	734.61	J56	139.97	105.28	734.61	734.61
23		J58	219.90	J58	320.28	123.28	332.38	332.38	J58	139.96	104.88	332.39	332.38
24		J60	218.82	J60	305.43	121.17	312.36	312.37	J60	139.96	104.28	312.37	312.36
25		J62	217.98	R02	328.76	123.40	1,229.26	773.19	J62	139.97	104.13	773.20	773.20
26		J64	220.39	R02	329.62	122.74	1,315.85	804.42	J64	139.97	103.38	804.43	804.43
27		J66	219.12	R02	330.35	123.11	1,397.22	794.11	J66	139.97	103.68	794.12	794.12
28		J68	218.22	R02	331.00	124.28	1,479.87	767.72	J68	139.97	104.78	767.73	767.73
29		J70	218.30	R02	331.59	126.34	1,563.02	702.65	J70	139.97	106.78	702.65	702.65
30		J72	220.30	R02	332.08	127.94	1,632.26	691.52	J72	139.97	108.33	691.53	691.53
31		J74	217.45	R02	332.67	128.75	1,753.48	804.04	J74	139.97	109.08	804.04	804.04
32		J76	217.23	R02	332.82	127.96	1,794.90	864.82	J74	137.21	108.00	860.44	860.44
33		J78	219.75	R02	330.85	123.66	1,467.48	492.19	J78	139.96	104.18	492.19	492.19
34		J80	217.73	R02	330.27	122.95	1,388.98	491.89	J80	139.96	103.53	491.90	491.90
35		J82	219.30	R02	329.53	122.38	1,306.06	502.89	J82	139.96	103.03	502.89	502.89
36		J84	217.43	R02	333.09	126.59	1,866.81	977.08	J74	126.62	105.52	953.70	953.70
37		J86	219.33	R02	333.73	126.66	2,029.46	1,034.26	J86	139.97	106.88	1,034.28	1,034.28
38		J88	217.49	R02	334.75	126.36	2,359.29	1,166.02	J88	139.98	106.48	1,166.05	1,166.05
39		R02	167.57	R02	329.43	138.62	951.03	951.01	R02	139.97	119.28	951.03	951.03

Water Demand Design Flows per Unit Count
City of Ottawa - Water Distribution Guidelines, July 2010



Domestic Demand

Type of Housing	Per / Unit	Units	Pop
Single Family	3.4		0
Semi-detached	2.7		0
Townhouse	2.7		0
Apartment			0
Bachelor	1.4		0
1 Bedroom	1.4		0
2 Bedroom	2.1		0
3 Bedroom	3.1		0
Average	1.8	445	801

	Pop	Avg. Daily		Max Day		Peak Hour	
		m ³ /d	L/min	m ³ /d	L/min	m ³ /d	L/min
Total Domestic Demand	801	224.3	155.8	560.7	389.4	1233.5	856.6

Institutional / Commercial / Industrial Demand

Property Type	Unit Rate	Units	Avg. Daily		Max Day		Peak Hour	
			m ³ /d	L/min	m ³ /d	L/min	m ³ /d	L/min
Commercial floor space	2.5 L/m ² /d	791	1.98	1.4	3.0	2.1	5.3	3.7
Office	75 L/9.3m ² /d		0.00	0.0	0.0	0.0	0.0	0.0
Industrial - Light	35,000 L/gross ha/d		0.00	0.0	0.0	0.0	0.0	0.0
Industrial - Heavy	55,000 L/gross ha/d		0.00	0.0	0.0	0.0	0.0	0.0
Total I/CI Demand			2.0	1.4	3.0	2.1	5.3	3.7
Total Demand			226.3	157.1	563.7	391.4	1238.9	860.3

Fire Flow Estimation per Fire Underwriters Survey

Water Supply For Public Fire Protection - 1999



Fire Flow Required

1. Base Requirement

$$F = 220C\sqrt{A}$$

L/min

Where **F** is the fire flow, **C** is the Type of construction and **A** is the Total floor area

Type of Construction:

Non-Combustible Construction

C 0.8

Type of Construction Coefficient per FUS Part II, Section 1

A 8569.2

m² Total floor area based on FUS Part II section 1

Fire Flow

16292.3 L/min

16000.0 L/min rounded to the nearest 1,000 L/min

Adjustments

2. Reduction for Occupancy Type

Non-Combustible

-25%

Fire Flow

12000.0 L/min

3. Reduction for Sprinkler Protection

Sprinklered - Supervised

-50%

Reduction

-6000 L/min

4. Increase for Separation Distance

Cons. of Exposed Wall

	S.D	Lw	Ha	LH	EC	
N Wood Frame	20.1m-30m	79.57		2	160	10%
S Non-Combustible	20.1m-30m	18.65		6	112	10%
E Wood Frame	20.1m-30m	18.68		2	38	8%
W Non-Combustible	10.1m-20m	18.68		6	113	15%
% Increase						43% value not to exceed 75%

Increase

5160.0 L/min

Lw = Length of the Exposed Wall

Ha = number of storeys of the adjacent structure. Max 5 stories

LH = Length-height factor of exposed wall. Value rounded up.

EC = Exposure Charge

Total Fire Flow

Fire Flow

11160.0 L/min

11000.0 L/min

fire flow not to exceed 45,000 L/min nor be less than 2,000 L/min per FUS Section 4
rounded to the nearest 1,000 L/min

Notes:

-Type of construction, Occupancy Type and Sprinkler Protection information provided by RLA Architecture

-Calculations based on Fire Underwriters Survey - Part II

Fire Flow Estimation per Fire Underwriters Survey

Water Supply For Public Fire Protection - 1999



Fire Flow Required

1. Base Requirement

$$F = 220C\sqrt{A}$$

L/min

Where **F** is the fire flow, **C** is the Type of construction and **A** is the Total floor area

Type of Construction:

Non-Combustible Construction

C 0.8

Type of Construction Coefficient per FUS Part II, Section 1

A 9211.2

m² Total floor area based on FUS Part II section 1

Fire Flow

16891.6 L/min

17000.0 L/min rounded to the nearest 1,000 L/min

Adjustments

2. Reduction for Occupancy Type

Non-Combustible

-25%

Fire Flow

12750.0 L/min

3. Reduction for Sprinkler Protection

Sprinklered - Supervised

-50%

Reduction

-6375 L/min

4. Increase for Separation Distance

Cons. of Exposed Wall

N Non-Combustible

S.D 20.1m-30m

Lw 18.65

Ha

LH

EC

10%

S Wood Frame

>45m

18.65

2

38

0%

E Wood Frame

20.1m-30m

86.1

2

173

10%

W Non-Combustible

10.1m-20m

18.7

6

113

15%

% Increase

35% value not to exceed 75%

Increase

4462.5 L/min

Lw = Length of the Exposed Wall

Ha = number of storeys of the adjacent structure. Max 5 stories

LH = Length-height factor of exposed wall. Value rounded up.

EC = Exposure Charge

Total Fire Flow

Fire Flow

10837.5 L/min

fire flow not to exceed 45,000 L/min nor be less than 2,000 L/min per FUS Section 4

11000.0 L/min

rounded to the nearest 1,000 L/min

Notes:

-Type of construction, Occupancy Type and Sprinkler Protection information provided by RLA Architecture

-Calculations based on Fire Underwriters Survey - Part II

Fire Flow Estimation per Fire Underwriters Survey

Water Supply For Public Fire Protection - 1999



Fire Flow Required

1. Base Requirement

$$F = 220C\sqrt{A}$$

L/min

Where **F** is the fire flow, **C** is the Type of construction and **A** is the Total floor area

Type of Construction:

Non-Combustible Construction

C 0.8 Type of Construction Coefficient per FUS Part II, Section 1
A 8506.8 m² Total floor area based on FUS Part II section 1

Fire Flow	16232.9 L/min
	16000.0 L/min rounded to the nearest 1,000 L/min

Adjustments

2. Reduction for Occupancy Type

Non-Combustible -25%

Fire Flow	12000.0 L/min
-----------	----------------------

3. Reduction for Sprinkler Protection

Sprinklered - Supervised -50%

Reduction	-6000 L/min
-----------	--------------------

4. Increase for Separation Distance

Cons. of Exposed Wall	S.D	Lw	Ha	LH	EC	
N Non-Combustible	20.1m-30m	18.65		6	112	10%
S Wood Frame	>45m	79.55		2	160	0%
E Non-Combustible	10.1m-20m	18.7		6	113	15%
W Wood Frame	30.1m-45m	18.7		2	38	5%
% Increase						30% value not to exceed 75%

Increase	3600.0 L/min
----------	---------------------

Lw = Length of the Exposed Wall

Ha = number of storeys of the adjacent structure. Max 5 stories

LH = Length-height factor of exposed wall. Value rounded up.

EC = Exposure Charge

Total Fire Flow

Fire Flow	9600.0 L/min	fire flow not to exceed 45,000 L/min nor be less than 2,000 L/min per FUS Section 4
	10000.0 L/min	rounded to the nearest 1,000 L/min

Notes:

-Type of construction, Occupancy Type and Sprinkler Protection information provided by RLA Architecture

-Calculations based on Fire Underwriters Survey - Part II

Fire Flow Estimation per Fire Underwriters Survey

Water Supply For Public Fire Protection - 1999



Fire Flow Required

1. Base Requirement

$$F = 220C\sqrt{A}$$

L/min

Where **F** is the fire flow, **C** is the Type of construction and **A** is the Total floor area

Type of Construction:

Non-Combustible Construction

C 0.8

Type of Construction Coefficient per FUS Part II, Section 1

A 9330.0

m² Total floor area based on FUS Part II section 1

Fire Flow

17000.2 L/min

17000.0 L/min rounded to the nearest 1,000 L/min

Adjustments

2. Reduction for Occupancy Type

Non-Combustible

-25%

Fire Flow

12750.0 L/min

3. Reduction for Sprinkler Protection

Sprinklered - Supervised

-50%

Reduction

-6375 L/min

4. Increase for Separation Distance

Cons. of Exposed Wall

	S.D	Lw	Ha	LH	EC	
N Wood Frame	20.1m-30m	18.65		2	38	8%
S Non-Combustible	20.1m-30m	18.65		6	112	10%
E Wood Frame	10.1m-20m	86.1		2	173	15%
W Non-Combustible	30.1m-45m	18.68		6	113	5%
% Increase						38% value not to exceed 75%

Increase

4845.0 L/min

Lw = Length of the Exposed Wall

Ha = number of storeys of the adjacent structure. Max 5 stories

LH = Length-height factor of exposed wall. Value rounded up.

EC = Exposure Charge

Total Fire Flow

Fire Flow

11220.0 L/min

11000.0 L/min

fire flow not to exceed 45,000 L/min nor be less than 2,000 L/min per FUS Section 4
rounded to the nearest 1,000 L/min

Notes:

-Type of construction, Occupancy Type and Sprinkler Protection information provided by RLA Architecture

-Calculations based on Fire Underwriters Survey - Part II

Boundary Conditions Unit Conversion**Connection 1 - Codd's Road**


	Height (m)	Elevation (m)	m H ₂ O	PSI	kPa
Avg. DD	147.0	87.9	59.1	84.1	579.8
Max Day	146.7	87.9	58.8	83.7	576.8
FF	145.0	87.9	57.1	81.2	560.2


Connection 2 - Barielle-Snow Street

	Height (m)	Elevation (m)	m H ₂ O	PSI	kPa
Avg. DD	147.0	88.6	58.4	83.1	572.9
Max Day	146.7	88.6	58.1	82.7	570.0
FF	141.0	88.6	52.4	74.6	514.0

APPENDIX C

Wastewater Collection







Signed _____

Plan Number _____

LEGEND :





14			
13			
12			
11			
10			
9			
8			
7			
6	REVISED PER CITY COMMENTS	J.I.M.	2016: 01: 27
5	REVISED PER CITY COMMENTS	J.I.M.	2015: 11: 30
4	REVISED PER CITY COMMENTS	J.I.M.	2015: 11: 20
3	REVISED PER CITY COMMENTS	J.I.M.	2015: 11: 13
2	ISSUED FOR CITY INTERNAL CIRCULATION	J.I.M.	2015: 09: 22
1	SUBMISSION No.1 FOR CITY REVIEW	J.I.M.	2015: 06: 30
No.	REVISIONS	By	Date



Project Title

**WATERIDGE VILLAGE
AT ROCKCLIFFE**

PHASE 1A



Drawing Title

**SANITARY DRAINAGE
AREA PLAN**

Scale 1 : 2000

Design J.I.M./M.B.	Date JUNE 2015
Drawn D.D. / M.M.	Checked J.I.M.
Project No. 38298	Drawing No. 501



IBI GROUP
400-333 Preston Street
Ottawa, Ontario K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

SANITARY SEWER DESIGN SHEET

Former CFB Rockcliffe
City of Ottawa
Canada Lands Company

LOCATION				RESIDENTIAL								ICI AREAS								INFILTRATION ALLOWANCE			FIXED FLOW (L/s)	TOTAL FLOW (L/s)	PROPOSED SEWER DESIGN							
STREET	AREA ID	FROM MH	TO MH	AREA Ph1 (Ha)	UNIT TYPES				AREA External (Ha)	POPULATION		PEAK FACTOR	PEAK FLOW (L/s)	AREA (Ha)				PEAK FLOW (L/s)	AREA (Ha)		FLOW (L/s)	CAPACITY (L/s)			LENGTH (m)	DIA (mm)	SLOPE (%)	VELOCITY (full) (m/s)	AVAILABLE CAPACITY			
					SF	SD	TH	APT		IND	CUM			IND	CUM	IND	CUM	IND	CUM		IND	CUM						L/s	%			
cercle AVRO CIRCLE	100A(a)	MH100A	MH108A	0.76	14	3				55.7	55.7	4.00	0.90		0.00		0.00		0.00	0.00	0.76	0.76	0.21		1.12	39.24	93.65	250	0.40	0.774	38.12	97.16%
cercle AVRO CIRCLE	108A	MH108A	MH109A	0.74	13	3				52.3	108.0	4.00	1.75		0.00		0.00		0.00	0.00	0.74	1.50	0.42		2.17	39.24	98.01	250	0.40	0.774	37.07	94.47%
---	FRHVN	SAN EXT	MH109A						8.98	538.2	538.2	3.96	8.63		0.00		0.00		0.00	0.00	8.98	8.98	2.51		11.14	94.09	53.04	250	2.30	1.857	82.94	88.16%
voie CHENE WAY	109A	MH109A	MH117A	0.18	3					10.2	656.4	3.91	10.40		0.00		0.00		0.00	0.00	0.18	10.66	2.98		13.38	62.04	44.52	250	1.00	1.224	48.66	78.43%
	117A	MH117A	MH118A	0.15	2	1				9.5	665.9	3.91	10.54		0.00		0.00		0.00	0.00	0.15	10.81	3.03		13.57	62.04	36.30	250	1.00	1.224	48.47	78.13%
PLACE LYSANDER	102A(a)	MH102A	MH119A	0.77	12	9				65.1	65.1	4.00	1.05		0.00		0.00		0.00	0.00	0.77	0.77	0.22		1.27	48.45	103.71	250	0.61	0.956	47.18	97.38%
PLACE LYSANDER	119A	MH119A	MH118A	0.55	9	3				38.7	103.8	4.00	1.68		0.00		0.00		0.00	0.00	0.55	1.32	0.37		2.05	55.49	102.75	250	0.80	1.095	53.44	96.30%
voie CHENE WAY	118A	MH118A	MH118C	0.37	2	7				25.7	795.4	3.86	12.44		0.00		0.00		0.00	0.00	0.37	12.50	3.50		15.94	48.06	65.25	250	0.60	0.948	32.11	66.82%
voie CHENE WAY		MH118C	MH116A							0.0	795.4	3.86	12.44		0.00		0.00		0.00	0.00	0.00	12.50	3.50		15.94	48.06	14.10	250	0.60	0.948	32.11	66.82%
cercle AVRO CIRCLE	109A(b)	MH109A	Mh110A	0.27	3					10.2	10.2	4.00	0.17		0.00		0.00		0.00	0.00	0.27	0.27	0.08		0.24	80.89	72.73	250	1.70	1.596	80.65	99.70%
PLACE LYSANDER	---	Mh110A	Mh111A							0.0	10.2	4.00	0.17		0.00		0.00		0.00	0.00	0.00	0.27	0.08		0.24	67.96	9.98	250	1.20	1.341	67.72	99.65%
cercle AVRO CIRCLE	110A	MH111A	MH112A	0.16	2					6.8	17.0	4.00	0.28		0.00		0.00		0.00	0.00	0.16	0.43	0.12		0.40	67.96	26.44	250	1.20	1.341	67.56	99.42%
voie VEDETTE WAY	112A	MH112A	MH113A	0.19	3					10.2	27.2	4.00	0.44		0.00		0.00		0.00	0.00	0.19	0.62	0.17		0.61	50.02	40.55	250	0.65	0.987	49.40	98.77%
voie CHENE WAY	113A	MH113A	MH114A	0.32	5					17.0	44.2	4.00	0.72		0.00		0.00		0.00	0.00	0.32	0.94	0.26		0.98	57.20	63.75	250	0.85	1.129	56.22	98.29%
Street No. 18	114A	MH114A	MH115A	0.08	1					3.4	47.6	4.00	0.77		0.00		0.00		0.00	0.00	0.08	1.02	0.29		1.06	36.70	12.10	250	0.35	0.724	35.65	97.12%
Street No. 19	115A	MH115A	MH116A	0.35	5					17.0	64.6	4.00	1.05		0.00		0.00		0.00	0.00	0.35	1.37	0.38		1.43	36.70	82.09	250	0.35	0.724	35.27	96.10%
cercle AVRO CIRCLE	116A	MH116A	MH120A	0.21		2	4			16.2	876.2	3.84	13.62		0.00		0.00		0.00	0.00	0.21	14.08	3.94		17.56	31.02	39.22	250	0.25	0.612	13.46	43.39%
cercle AVRO CIRCLE	PARKa	BULK120AS	MH120A	0.40						0.0	0.0	4.00	0.00		0.00		0.00		0.00	0.00	0.40	0.40	0.11		0.11	43.87	12.01	250	0.50	0.866	43.76	99.74%
cercle AVRO CIRCLE	120A	MH120A	MH121A	0.25		4	1			13.5	889.7	3.83	13.81		0.00		0.00		0.00	0.00	0.25	14.73	4.12		17.94	31.02	49.86	250	0.25	0.612	13.08	42.18%
cercle AVRO CIRCLE	105A(b)	MH105A	MH122A	0.43	4	6	3			37.9	37.9	4.00	0.61		0.00		0.00		0.00	0.00	0.43	0.43	0.12		0.73	62.04	61.74	250	1.00	1.224	61.30	98.82%
cercle AVRO CIRCLE	122A	MH122A	MH121A	0.45	3	8	3			39.9	77.8	4.00	1.26		0.00		0.00		0.00	0.00	0.45	0.88	0.25		1.51	55.14	61.74	250	0.79	1.088	53.63	97.27%
voie VEDETTE WAY	121A	MH121A	MH127A	0.16						0.0	967.5	3.81	14.93		0.00		0.00		0.00	0.00	0.16	15.77	4.42		19.34	31.02	90.10	250	0.25	0.612	11.67	37.64%
voie VEDETTE WAY	182A(a)	MH182A	MH128A	0.60			32			86.4	86.4	4.00	1.40		0.00		0.00		0.00	0.00	0.60	0.60	0.17		1.57	50.40	117.51	250	0.66	0.995	48.83	96.89%
voie VEDETTE WAY	INST	BULK128AE	MH128A							0.0	0.0	4.00	0.00	2.53	2.53		0.00		0.00	2.20	2.53	2.53	0.71		2.90	39.24	13.48	250	0.40	0.774	36.33	92.60%
voie VEDETTE WAY	128A	MH128A	MH127A	0.22			10			27.0	113.4	4.00	1.84		0.00		0.00		0.00	0.00	0.22	3.35	0.94		2.78	39.24	47.30	250	0.40	0.774	36.46	92.93%
hemin MIESHIMIN ROA	127A	MH127A	MH126A	0.38		4	4			21.6	1102.5	3.77	16.85		0.00		0.00		0.00	0.00	0.38	19.50	5.46		22.31	47.32	67.16	300	0.22	0.648	25.01	52.86%
hemin MIESHIMIN ROA	126A	MH126A	MH125A	0.32		4	2			16.2	1118.7	3.77	17.08		0.00		0.00		0.00	0.00	0.32	19.82	5.55		22.63	47.32	56.33	300	0.22	0.648	24.69	52.18%
cercle AVRO CIRCLE	100A(b)	MH100A	MH101A	0.22	2					6.8	6.8	4.00	0.11		0.00		0.00		0.00	0.00	0.22	0.22	0.06		0.17	43.87	9.43	250	0.50	0.866	43.70	99.61%
PLACE LYSANDER	101A	MH101A	MH102A	0.44		2	5			18.9	25.7	4.00	0.42		0.00		0.00		0.00	0.00	0.44	0.66	0.18		0.60	69.36	73.24	250	1.25	1.369	68.76	99.13%
cercle AVRO CIRCLE	102A(b)	MH1027																														



IBI GROUP
400-333 Preston Street
Ottawa, Ontario K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

SANITARY SEWER DESIGN SHEET

Former CFB Rockcliffe
City of Ottawa
Canada Lands Company

LOCATION				AREA Ph1 (Ha)	RESIDENTIAL				AREA External (Ha)	POPULATION		PEAK FACTOR	PEAK FLOW (L/s)	ICI AREAS						INFILTRATION ALLOWANCE			FIXED FLOW (L/s)	TOTAL FLOW (L/s)	PROPOSED SEWER DESIGN																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
STREET	AREA ID	FROM MH	TO MH		UNIT TYPES					IND	CUM			AREA (Ha)				PEAK FLOW (L/s)	AREA (Ha)		FLOW (L/s)	CAPACITY (L/s)			LENGTH (m)	DIA (mm)	SLOPE (%)	VELOCITY (full) (m/s)	AVAILABLE CAPACITY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
					SF	SD	TH	APT						IND	CUM	INSTITUTIONAL			COMMERCIAL										INDUSTRIAL		IND	CUM	IND	CUM	IND	CUM	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s	L/s

**Mattamy Homes
Wateridge Block 19
Contemplated Site Conditions
(Design Brief Phase 1A)**

**Wastewater Design Flows per Unit Count
City of Ottawa Sewer Design Guidelines, 2012**



Site Area 2.540 ha

Extraneous Flow Allowances

Infiltration / Inflow 0.71 L/s

Domestic Contributions

Unit Type	Unit Rate	Units	Pop
Single Family	3.4		0
Semi-detached and duplex	2.7		0
Townhouse	2.7		0
Apartment			
Bachelor	1.4		0
1 Bedroom	1.4		0
2 Bedroom	2.1		0
3 Bedroom	3.1		0
Average	1.8		0

Total Pop 271

Average Domestic Flow 0.88 L/s

Peaking Factor 4.00

Peak Domestic Flow 3.51 L/s

Institutional / Commercial / Industrial Contributions

Property Type	Unit Rate	No. of Units	Avg Wastewater (L/s)
Commercial floor space*	5 L/m ² /d		0.00
Hospitals	900 L/bed/d		0.00
School	70 L/student/d		0.00
Industrial - Light**	35,000 L/gross ha/d		0.00
Industrial - Heavy**	55,000 L/gross ha/d		0.00

Average I/C/I Flow 0.00

Peak Institutional / Commercial Flow 0.00

Peak Industrial Flow 0.00**

Peak I/C/I Flow 0.00

* assuming a 12 hour commercial operation

** peak industrial flow per City of Ottawa Sewer Design Guidelines Appendix 4B

Total Estimated Average Dry Weather Flow Rate	0.88 L/s
Total Estimated Peak Dry Weather Flow Rate	3.51 L/s
Total Estimated Peak Wet Weather Flow Rate	4.22 L/s

Wastewater Design Flows per Unit Count
City of Ottawa Sewer Design Guidelines, 2012



Site Area 1.632 ha

Extraneous Flow Allowances

Infiltration / Inflow 0.46 L/s

Domestic Contributions

Unit Type	Unit Rate	Units	Pop
Single Family	3.4		0
Semi-detached and duplex	2.7		0
Townhouse	2.7		0
Apartment			
Bachelor	1.4		0
1 Bedroom	1.4		0
2 Bedroom	2.1		0
3 Bedroom	3.1		0
Average	1.8	445	801

Total Pop 801

Average Domestic Flow 2.60 L/s

Peaking Factor 3.86

Peak Domestic Flow 10.02 L/s

Institutional / Commercial / Industrial Contributions

Property Type	Unit Rate	No. of Units	Avg Wastewater (L/s)
Commercial floor space*	5 L/m ² /d	791	0.09
Hospitals	900 L/bed/d		0.00
School	70 L/student/d		0.00
Industrial - Light**	35,000 L/gross ha/d		0.00
Industrial - Heavy**	55,000 L/gross ha/d		0.00

Average I/C/I Flow 0.09

Peak Institutional / Commercial Flow 0.14

Peak Industrial Flow** 0.00

Peak I/C/I Flow 0.14


* assuming a 12 hour commercial operation

** peak industrial flow per City of Ottawa Sewer Design Guidelines Appendix 4B

Total Estimated Average Dry Weather Flow Rate	2.69 L/s
Total Estimated Peak Dry Weather Flow Rate	10.16 L/s
Total Estimated Peak Wet Weather Flow Rate	10.61 L/s

APPENDIX D

Stormwater Management



Sheet No.

Project Title

Drawing Title

DESIGN BRIEF

WATERIDGE VILLAGE

AT ROCKCLIFFE

PHASE 1A

RECOMMENDED MINOR

STORM PLAN

FIGURE 4.2

Scale

IBI

0 100 200



IBI GROUP
400-333 Preston Street
Ottawa, Ontario K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

STORM SEWER DESIGN SHEET

Former CFB Rockcliffe
City of Ottawa
Canada Lands Company

LOCATION				RATIONAL DESIGN FLOW																		SEWER DATA												
STREET	AREA ID	FROM	TO	C= 0.20	C= 0.30	C= 0.50	C= 0.45	C= 0.56	C= 0.67	C= 0.73	C= 0.80	IND 2.78AC	CUM 2.78AC	INLET (min)	TIME IN PIPE	TOTAL (min)	i (5) (mm/hr)	i (10) (mm/hr)	i (100) (mm/hr)	5yr PEAK FLOW (L/s)	10yr PEAK FLOW (L/s)	100yr PEAK FLOW (L/s)	FIXED FLOW (L/s)	DESIGN FLOW (L/s)	CAPACITY (L/s)	LENGTH (m)	PIPE SIZE (mm)			SLOPE (%)	VELOCITY (m/s)	AVAIL CAP (5yr)		
																											DIA	W	H			(L/s)	(%)	
Temp Ditch	---	DICB 2	PIPE141																				3,270.00	3,270.00	3,402.95	18.95	1200			0.70	2.915	132.95	3.91%	
Codd's Road	S141A,B, EX141	MH141	MH142							0.31	0.96	2.76	46.08	19.33	0.63	19.96	71.75	83.97	122.53	3,306.18			8,884.00	12,190.18	14,807.43	76.59	3000			0.10	2.029	2617.25	17.68%	
Park Block 141	P141	CBMH142W	MH142		0.86							0.72	0.72	10.00	0.22	10.22	104.19	122.14	178.56	74.73				74.73	129.34	15.00	375			0.50	1.134	54.61	42.22%	
Codd's Road	S142	MH142	MH176							0.18		0.37	47.16	19.96	0.65	20.61	70.34	82.31	120.10	3,317.10			8,884.00	12,201.10	14,807.43	79.32	3000			0.10	2.029	2606.33	17.60%	
Future Hemlock Rd E	S176C, EX176A	BULK176E	MH176							0.05	8.78	19.63	19.63	16.59	0.27	16.86	78.75	92.20	134.60	1,545.70				1,545.70	2,156.55	24.06	1350			0.15	1.460	610.85	28.33%	
Future Codd's Road N	EX176B	BULK176N	MH176								1.78	3.96	3.96	10.78	0.15	10.93	100.25	117.49	171.73	396.84				396.84	572.93	18.21	600			0.80	1.963	176.09	30.73%	
Hemlock Road	S176D,E	MH176	BEND177							0.22		0.45	71.19	20.61	0.31	20.92	68.93	80.66	117.68	4,907.69			8,884.00	13,791.69	18,135.33	46.25	3000			0.15	2.485	4343.64	23.95%	
Hemlock Road	---	BEND177	MH178									0.00	71.19	20.92	0.31	21.23	68.29	79.90	116.57	4,861.72			8,884.00	13,745.72	18,135.33	45.59	3000			0.15	2.485	4389.61	24.20%	
Hemlock Road	---	MH178	BEND179									0.00	71.19	21.23	0.28	21.51	67.66	79.17	115.49	4,817.33			8,884.00	13,701.33	18,135.33	42.27	3000			0.15	2.485	4434.00	24.45%	
Hemlock Road	---	BEND179	MH180									0.00	71.19	21.51	0.21	21.72	67.10	78.51	114.52	4,776.97			8,884.00	13,660.97	18,135.33	30.68	3000			0.15	2.485	4474.36	24.67%	
Future Street No. 19	S180, EX180	MH180	MH190							0.16	0.54	1.53	99.46	21.72	0.43	22.14	66.69	78.03	113.82	6,633.26			8,884.00	15,517.26	18,135.33	63.40	3000			0.15	2.485	2618.06	14.44%	
	EX190B	MH190	MH191								1.08	2.40	101.86	22.14	0.76	22.90	65.87	77.07	112.41	6,709.96			8,884.00	15,593.96	18,135.33	112.71	3000			0.15	2.485	2541.37	14.01%	
Future Street No. 18	EX190A	BULK191E	MH191								2.01	4.47	4.47	12.26	0.10	12.36	93.60	109.67	160.24	418.41				418.41	640.56	13.71	600			1.00	2.195	222.15	34.68%	
	EX191B-C	MH191	MH192		0.82						0.90	2.69	109.02	22.90	0.77	23.67	64.47	75.42	110.00	7,028.34			8,884.00	15,912.34	18,135.33	115.55	3000			0.15	2.485	2222.98	12.26%	
	EX192	MH192	MH193								0.47	1.05	110.06	23.67	0.27	23.94	63.10	73.81	107.64	6,944.82			8,884.00	15,828.82	18,730.09	41.34	3000			0.16	2.567	2901.27	15.49%	
Future Park Block 36	P193	MH193	MH 194		1.94							1.62	111.68	23.94	0.64	24.59	62.64	73.27	106.84	6,995.54			8,884.00	15,879.54	20,940.87	110.85	3000			0.20	2.870	5061.33	24.17%	
Temp Ditch	---	DICB 3	PIPE193																				1,560.00	1,560.00	1,956.07	2.67	975			0.70	2.538	396.07	20.25%	
	---	MH 194	OUTLET									0.00	111.68	24.59	0.02	24.60	61.56	72.01	105.00	6,875.66			8,884.00	15,759.66	20,940.87	3.00	3000			0.20	2.870	5181.21	24.74%	
From MSS Document	---	BULK195E	OUTLET									34.91	34.91	22.83	0.08	22.91	64.59	75.57	110.21	2,255.01				2,255.01	4,754.27	10.00	1650			0.25	2.154	2499.26	52.57%	
chemin WANAKI ROAD	S152, EX152A-B	MH152	MH151							0.23	0.92	2.51	2.51	10.00	1.10	11.10	104.19	122.14	178.56	261.82				261.82	438.47	78.40	675			0.25	1.187	176.65	40.29%	
chemin WANAKI ROAD	S151, EX151	MH151	MH150							0.02	0.41	0.95	3.47	11.10	0.58	11.68	98.72	115.69	169.09	342.08				342.08	438.47	41.34	675			0.25	1.187	96.39	21.98%	
chemin WANAKI ROAD	S150, EX150	MH150	MH149							0.18	0.96	2.50	5.97	11.68	0.44	12.12	96.08	112.59	164.52	573.17				573.17	748.75	35.95	825			0.25	1.357	175.58	23.45%	
chemin WANAKI ROAD	S149	MH149	MH148							0.15		0.30	6.27	12.12	0.55	12.68	94.17	110.34	161.23	590.47				590.47	748.75	45.17	825			0.25	1.357	158.28	21.14%	
Burma Road	S148	MH148	MH157							0.12		0.24	6.21	12.12	0.63	12.76	94.17	110.34	161.23	584.74				584.74	865.46	50.00	900			0.21	1.318	280.72	32.44%	
Burma Road	---	MH157	MH154									0.00	6.27	12.68	0.85	13.53	91.90	107.66	157.30	576.20				576.20	844.60	65.50	900			0.20	1.286	268.41	31.78%	
Block 71	EXSC154	BULK154N	MH154								2.62	5.83	5.83	12.00	0.20	12.20	94.70	110.96	162.13	551.78				551.78	687.10	17.90	750			0.35	1.507	135.32	19.69%	
SW Swale	---	BULK SWL	EX MH																				1704.00	1,704.00	1,707.41	80.70	825	1.25			1.30	3.094	3.41	0.20%
Definitions: Q = 2.78CiA, where: Q = Peak Flow in Litres per Second (L/s) A = Area in Hectares (Ha) i = Rainfall intensity in millimeters per hour (mm/hr) [i = 998.071 / (TC+6.053)*0.814] 5 YEAR [i = 1174.184 / (TC+6.014)*0.816] 10 YEAR [i = 1735.688 / (TC+6.014)*0.820] 100 YEAR				Notes: 1. Mannings coefficient (n) = 0.013								Designed: MB, WY				No.		Revision						Date										
																		Submission No. 1 for City Review						2015-06-30										
																		Submission No. 2 for City Review						2015-11-30										
																		Submission No. 3 for City Review						2016-01-27										
												Checked: JIM																						
												Dwg. Reference: 38298-500																						
																		File Reference: 38298.5.7.1						Date: 2015-06-30										
																								Sheet No: 3 of 3										

Stormwater - Existing Conditions
City of Ottawa Sewer Design Guidelines, 2004



Existing Drainage Area Characteristics

Area	1.63 ha
L	188.3 m, longest flow path
H1	87.5 m, elevation of hydraulically most remote location
H2	86.2 m, elevation at outlet
S	0.69 %
C	0.2 Rational Method runoff coefficient

Existing Time of Concentration (per Federal Aviation Administration)

t_c 45.6 min

Estimated Existing Peak Flow

	5-year	100-year
i	40.3	68.4 mm/hr
Q	36.5	62.0 L/s

Stormwater - Proposed Development
City of Ottawa Sewer Design Guidelines, 2012



Proposed Post Development Minor System Flow to Codd's Road

Total Area	1.63 ha		
C	0.76	Rational Method runoff coefficient	
t_c	10 min,	tc at outlet without restriction	
	5-year	100-year	
i	104.2	178.6 mm/hr	mm/hr
Q	358.5	768.1 L/s	L/s

Note: Reference target requirements

									Ditch Data												
Up	Down	Area	C	Indiv AxC	Acc AxC	T _C	I	Q*	depth	Side Slope	Bot. Width	Mannings	Slope	Length	A _{flow}	Wet. Per.	R	Velocity	Qcap	Time Flow	Q / Q full
		(ha)	(-)			(min)	(mm/hr)	(L/s)	(mm)	(X:1)	(m)	n	(%)	(m)	(m ²)	(m)	(m)	(m/s)	(L/s)	(min)	(-)
		1.630	0.76	1.24	1.24	10.0	178.6	293.1	180	33.3	0	0.03	1.30	20	1.079	11.993	0.09	0.76	823.3	0.4	0.36
	*100-year Flow - 475 L/s minor storm capture																				

STORAGE SUMMARY
BLOCK 19
STORAGE VOLUME AVAILABLE BELOW OVERFLOW

Total Site		
Rainfall (mm)	Drainage Area (sq.m)	Volume Required (cu.m)
15	16300	244.5

Stormwater - Proposed Development
City of Ottawa Sewer Design Guidelines, 2012

Post Development Drainage Area Characteristics

Total Area 1.63 ha
C 0.76 Rational Method runoff coefficient
t_c 10 min, t_c at outlet without restriction

5-year **100-year**
Q 358.8 L/s **Q** 457 L/s

*Based on consultation with IBI dated August 16, 2017

Estimated Post Development Peak Flow from Unattenuated Areas

Total Area 0.218 ha
C 0.75 Rational Method runoff coefficient

t _c (min)	5-year					100-year				
	i (mm/hr)	Q _{actual} (L/s)	Q _{release} (L/s)	Q _{stored} (L/s)	V _{stored} (m ³)	i (mm/hr)	Q _{actual} (L/s)	Q _{release} (L/s)	Q _{stored} (L/s)	V _{stored} (m ³)
10.0	104.2	47.3	47.3	0.0	0.0	178.6	101.4	101.4	0.0	0.0

Note:

C value for the 100-year storm is increased by 25%, to a maximum of 1.0 per Ottawa Sewer Design Guidelines (5.4.5.2.1)

Estimated Post Development Peak Flow from Attenuated Areas

Total Area 1.41 ha
C 0.82 Rational Method runoff coefficient

t _c (min)	5-year					100-year				
	i (mm/hr)	Q _{actual} (L/s)	Q _{release} (L/s)	Q _{stored} (L/s)	V _{stored} (m ³)	i (mm/hr)	Q _{actual} (L/s)	Q _{release} (L/s)	Q _{stored} (L/s)	V _{stored} (m ³)
5	141.2	452.9	169.2	283.7	85.1	242.7	952.2	355.6	596.5	179.0
10	104.2	334.2	169.7	164.6	98.7	178.6	700.5	355.6	344.9	206.9
15	83.6	268.0	170.1	98.0	88.2	142.9	560.6	355.6	205.0	184.5
20	70.3	225.4	170.3	55.0	66.1	120.0	470.6	355.6	114.9	137.9
25	60.9	195.4	170.5	24.8	37.2	103.8	407.4	355.6	51.8	77.6
30	53.9	173.0	170.7	2.3	4.1	91.9	360.4	355.6	4.8	8.6
35	48.5	155.6	170.9	0.0	0.0	82.6	324.0	355.6	0.0	0.0
40	44.2	141.7	171.0	0.0	0.0	75.1	294.8	355.6	0.0	0.0
45	40.6	130.3	171.1	0.0	0.0	69.1	270.9	355.6	0.0	0.0
50	37.7	120.8	171.2	0.0	0.0	64.0	250.9	355.6	0.0	0.0
55	35.1	112.7	171.3	0.0	0.0	59.6	233.9	355.6	0.0	0.0
60	32.9	105.7	171.4	0.0	0.0	55.9	219.3	355.6	0.0	0.0
65	31.0	99.6	171.5	0.0	0.0	52.6	206.5	355.6	0.0	0.0
70	29.4	94.2	171.6	0.0	0.0	49.8	195.3	355.6	0.0	0.0
75	27.9	89.5	171.6	0.0	0.0	47.3	185.4	355.6	0.0	0.0
80	26.6	85.2	171.7	0.0	0.0	45.0	176.5	355.6	0.0	0.0
85	25.4	81.4	171.8	0.0	0.0	43.0	168.5	355.6	0.0	0.0
90	24.3	77.9	171.8	0.0	0.0	41.1	161.3	355.6	0.0	0.0
95	23.3	74.8	171.9	0.0	0.0	39.4	154.7	355.6	0.0	0.0
100	22.4	71.9	171.9	0.0	0.0	37.9	148.7	355.6	0.0	0.0
105	21.6	69.2	172.0	0.0	0.0	36.5	143.2	355.6	0.0	0.0

Note:


C value for the 100-year storm is increased by 25%, to a maximum of 1.0 per Ottawa Sewer Design Guidelines (5.4.5.2.1)

5-year Q_{attenuated} 169.69 L/s
5-year Max. Storage Required 98.7 m³
100-year Q_{attenuated} 355.64 L/s
100-year Max. Storage Required 206.9 m³

Summary of Release Rates and Storage Volumes

Control Area	5-Year Release Rate (L/s)	5-Year Storage (m ³)	100-Year Release Rate (L/s)	100-Year Storage (m ³)
Unattenuated Areas	47.31	0.0	101.36	0.0
Attenuated Areas	169.69	98.7	355.64	206.9
Total	217.0	98.73	457.00	206.9

DRAWINGS / FIGURES




SITE STATISTICS AND DEVELOPMENT DATA	
SITE AREA	16,250.85m ² (1.42 ha)
PAVED AREA	3,653.52m ² (22.5%)
LANDSCAPED AREA	6,668.65m ² (41.0%)
TOTAL BUILDING COVERAGE	5,928.68m ² (36.5%)
TOTAL GROSS FLOOR AREA	33,700.50m ²
BUILDING A (102 units)	8,004.60m ²
BUILDING B (121 Units)	8,839.80m ²
BUILDING C (107 units)	7,994.40m ²
BUILDING D (115 units)	8,861.70m ²
DENSITY (UPH)	275 UPH
ZONE CATEGORY	GM 31H(30)

BUILDING	BUILDING TYPE	GROUND FLOOR AREA (m ²)	UNITS
BUILDING A	RESIDENTIAL/ COMMERCIAL	1,431.40	102
BUILDING B	RESIDENTIAL	1,535.79	121
BUILDING C	RESIDENTIAL	1,410.35	107
BUILDING D	RESIDENTIAL/ COMMERCIAL	1,551.14	115
TOTAL		5,928.68	445

SECTION	ZONE PROVISION	REQUIRED	PROPOSED
187 (Table)	MIN. LOT WIDTH (m)	No minimum	N/A
187 (Table)	MIN. LOT AREA (m ²)	No minimum	N/A
187 (Table)(6)(A)	MAX. BUILDING HEIGHT (m)	30m	20.0m (6 storey)
188H-GM31 (Table)	MIN. FRONT YARD AND CORNER SIDE YARD SETBACK (m): 1. FOR A BUILDING WITH RESIDENTIAL LAND USE AT GRADE 2. ALL OTHER CASES (m)	5.0m 0.0m	2.85m*(Building C) 1.76m on Hemlock 1.76m
188H-GM31 (Table)	DESPITE ROW 1, ABOVE MAX. FRONT AND CORNER SIDE YARD SETBACK FOR LOTS EAST OF CODD'S ROAD WHERE THEY ABUT HEMLLOCK ROAD (m)	2.0m (Max)	
188H-GM31 (Table)	MIN. INTERIOR SIDE YARD (m)	N/A	N/A
188H-GM31 (Table)	MIN. REAR YARD SETBACK ABUTS A STREET (m)	3.0m	3.0m
188H-GM31 (Table)	MAX FLOOR SPACE INDEX (0.5/unit)	No max	N/A
101(3)(A), 101 (Table)	RESIDENT PARKING: WITH THE FIRST 12 UNITS NOT REQUIRED (0.5/unit)	217	422 (underground)
AREA X 102(2), 102 (Table)	VISITOR PARKING: WITH THE FIRST 12 UNITS NOT REQUIRED (0.1/unit)	44	44 (30 surface, 14 underground)
111A (Table)	BICYCLE PARKING (0.5/unit)	223	224 (79 surface, 145 underground)
111A (Table)(E)	COMMERCIAL BICYCLE PARKING (1/250m ² of GFA)	3	3
101 (Table)(N79)	COMMERCIAL PARKING (5/100m ² over 200m ²)	30	6.7m
107(1), 107 (Table)	MIN. WIDTH OF AISLE (m)	6.7m	2.870m ²
137 (Table)	MIN. TOTAL AMENITY AREA (6m ² /unit)	2,670m ²	2,581m ²
137 (Table)	MIN. COMMUNAL AMENITY AREA (Min. 50% area)	1,335m ²	

SECTION	ADDITIONAL PROVISIONS	REQUIRED	PROPOSED
65	MAX. PERMITTED PROJECTIONS INTO YARDS:		
65(5)	FIRE ESCAPES, OPEN STAIRWAYS, STOOP (m)	>0.6m to lot line	1.8m
65(6)	COVERED OR UNCOVERED BALCONY, PORCH, DECK	2m (Max) but >1.0m to lot line	1.9m
106(1)	MIN. PERPENDICULAR PARKING SPACE SIZE (m)	2.6m x 5.2m	2.6m x 5.2m
106(2)	BARRIER FREE PARKING: TYPE A PARKING SPACE SIZE (m) TYPE B PARKING SPACE SIZE (m) ACCESS AISLE (m)	3.4m x 5.2m 2.4m x 5.2m 1.5m	3.4m x 5.2m 2.4m x 5.2m 1.5m
111B (Table)	MIN. BICYCLE PARKING SPACE DIMENSIONS, HORIZONTAL	Width: 0.6m Length: 1.8m	0.6m 1.8m
111(P)	MIN. BICYCLE PARKING SPACE ACCESS AISLE WIDTH (m)	1.5m	1.5m
187 (Table)(H)	MIN. WIDTH OF LANDSCAPED AREA ABUTTING A STREET (m)	3.0m	2.85m *
GM31(31)(I)	DESPITE ITEM (H) IN TABLE 187, NO LANDSCAPED AREA IS REQUIRED ABUTTING A STREET FOR BUILDINGS WITH NO REQUIRED FRONT OR CORNER SIDE YARD SETBACK (m)	N/A	N/A
GM31(31)(M)	MIN. DRIVEWAY WIDTH FOR PARKING LOTS OR GARAGES (m)	3.0m	6.0m
GM31(31)(O)	MAX. DRIVEWAY WIDTH TO PARKING LOTS OR GARAGES (m)	6.0m	6.0m
GM31(31)(C)	WHERE THE BUILDING CONTAINS MORE THAN FOUR STOREYS BUT LESS THAN 13 STOREYS, AT AND ABOVE THE FOURTH STOREY A BUILDING MUST BE FURTHER SETBACK (m)	2.0m	2.0m *
GM31(31)(F)	MIN. SEPARATION DISTANCE BETWEEN PORTIONS OF A BUILDING ABOVE FOUR STOREYS (m)	23.0m	23.03m
????	MIN. CEILING HEIGHT FOR COMMERCIAL	4.5m	?

* SUBJECT TO MINOR VARIANCE



LEGEND	
APARTMENT BUILDING	NO PARKING
CURB (0.2m)	BENCH
SS SNOW STORAGE AREA	SHADE STRUCTURE
L/A LANDSCAPED AREA	BIKE RACKS
ENTRANCE	CUSTOM PLANTER (L/A)
V VISITOR PARKING	PRIVATE PATIO
C COMMERCIAL PARKING	BOLLARD
HYD FIRE HYDRANT	STAIRS TO UNDERGROUND
BLOCK BOUNDARY	R RISERS
UNDERGROUND PARKING	TACTILE WALKING SURFACE INDICATOR
PHASE LINE	
PATHWAY (PAVERS)	
DRIVEWAY (PAVERS)	

DATE	REVISION	BY
11/10/19	Draft Site Plan	SP

GENERAL NOTES
1. DO NOT SCALE DRAWINGS FOR PRINT.
2. THIS DRAWING IS THE EXCLUSIVE PROPERTY OF KORSIAK URBAN PLANNING AND MATTAMY HOMES. COPYRIGHT RESERVED.
3. SITE PLAN PREPARED IN ACCORDANCE WITH PLAN 4M-1559, PREPARED BY ANNIS O'SULLIVAN, VOLLEBERG LTD.
4. WALKWAYS AND CURBS TO BE TIED INTO PUBLIC ROW WHERE APPLICABLE.
5. REFERENCES CITY OF OTTAWA T.W.S.I. DETAIL SC7.3

PROJECT TEAM

SITE PLAN DESIGN: **KORSIAK** Urban Planning

PLANNING/STRUCTURAL: **Stantec**

ARCHITECTURE: **Q4A**

CIVIL ENGINEER: **DSEL**

LANDSCAPE ARCHITECTURE: **NAK** design strategies

TRANSPORTATION: **NOVATECH**

MECHANICAL/ELECTRICAL: **STOK** SALDIN & NEWELL

NOISE: **VALCOUSTICS**

GEOTECHNICAL & STRUCTURAL: **patersongroup**

ENVIRONMENTAL: **KILGOUR & Associates**

mattamyHOMES

WATERIDGE VILLAGE: PHASE 1B

BLOCK 19, REGISTERED PLAN 4M-1559
PART OF LOTS 21, 22 AND 23
CONCESSION 1 (OTTAWA FRONT)
GEOGRAPHIC TOWNSHIP OF GLOUCESTER
CITY OF OTTAWA

TITLE: **BLOCK 19 SITE PLAN**

DATE: October 11, 2019 | DRAWN BY: SP | CHECKED BY: CR

FILE NO.: | JOB NO.: Mattamy - Wateridge

DRAWING NO. **A1**