GENERAL CONCRETE NOTES: ALL CONCRETE FINISHES TO BE APPROVED BY GJA LANDSCAPE ARCHITECT.

SAWCUT LAYOUT FOR ALL AREAS TO BE MARKED ON SITE IN RED CHALK, REVIEWED, ADJUSTED AND APPROVED BY GJA LANDSCAPE ARCHITECT-PRIOR TO ANY CUTTING.

EXPANSION JOINT LAYOUT FOR ALL AREAS TO BE LAID OUT ON SITE , REVIEWED, ADJUSTED AND APPROVED BY GJA

LANDSCAPE ARCHITECT-PRIOR TO ANY CONCRETE POURING. FINISH: TOOL EDGE FIRST, THEN WIPE OFF TOOL MARKS WHILE APPLYING FINISH

Concrete 125mm Thick, 32mpa, 6% Air Entrainment 6x6 Wire Mesh, Fibre Exp. Joints at all Hard Edges, 6m O.C. in Both Directions, Sawcut Control Joints (1" depth) 2.0m O.C. minimum

	— 125mm Concrete
	——300mm Granular Base
	Undisturbed or Compacted Subgrade
CONCRETE PAVING	NTS

32 MPA C2 c/w FLOAT FINISH - TOOL EDGE FIRST, THEN WIPE OFF TOOL MARKS WHILE APPLYING FINISH





Plant List - Trees - <u>177 - 179 ARMSTRONG STREET OTTAWA APARTMENT BUILDING</u>

Code	Qty.	Botanical Name	Common Name	Size	Condition	
AC	8	Amelanchier canadensis	Tree Serviceberry	60mm cal	B + B specimen	
Plant List - Shrubs - <u>177 - 179 ARMSTRONG STREET OTTAWA APARTMENT BUILDING</u>						
Code	Qty.	Botanical Name	Common Name	Size	Condition	
НК	135	Hypericum kalmianum	St. John's Wort	40cm Ht.	Pot	
SA	75	Spiraea alba	Meadowsweet	60cm Ht.	Pot	





Minimum

TREE PLANTING IN PLANTING BED

PRUNE DAMAGED BRANCHES

75MM SHREDDED MULCH

ROOT CONDITION AS SPEC'D-

PLANT AT SAME GRADE AS GROWN

FINISH GRADE

PLANTING SOIL MIX-

During Excavation/Bed Preparation if Extreme Conditions are Encountered (Water, Rock, Gravel...) that Could Effect Planting, Notify GJALA Immediately.

350mm Planting Soil -Flush with Turf or Adjacent Surface Approved Subgrade

NTS

75mm Shredded Pine Mulch

SCARIFY BOTTOM OF PIT 50MM DEPTH

hall a local a local

