

ORIGINAL SHEET - ARCH D

6. FOR DEPRESSED CURB AT ENTRANCES USE 250.

. DEPRESSED CURB HEIGHT - FOR PEDESTRIAN CURB RAMPS 0 TO 6 mm AND FOR PRIVATE ENTRANCES 0 TO 25mm

CONCRETE BARRIER CURB

FOR GRANULAR BASE PAVEMENT

(MODIFIED OPSD-600.110)

3. FOR CURB RAMPS, SLOPE OF 2% TO 5%, MAXIMUM 8%...

CONCRETE BARRIER CURB

WITH SIDEWALK

. EXPANSION AND DUMMY JOINTS AS PER SC5.

JANUARY 2003

Revision

AS SHOWN

Scale

Sheet

Project No.

Drawing No.

DWG. No.: W22

160401234

3. DEPTH OF COVER LESS THAN 1200mm REQUIRES SPECIAL DESIGN

5. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS SHOWN OTHERWISE.

THERMAL INSULATION FOR

WATERMAINS IN SHALLOW

4. STAGGER JOINTS OF MULTIPLE SHEETS.

8. DESIGNED TO MEET THE INTENT OF THE MOE WATERMAIN DESIGN CRITERIA JUNE 2012.

WATERMAIN CROSSING

OVER SEWER

DWG. No.: W25.2

DATE: MAY 2001

REV. MARCH 2017

STANDARD TRENCH REINSTATMENT

IN PAVED SURFACE

REV. WARCH 2007

DWG, No.: SC8

VEHICLE ACCESS CROSSING

#18362