



THIS SITE IS LOCATED IN A REGION WHERE LIGHTING IS REGULATED BY LOCAL ORDINANCES

LUMINAIRE LOCATION SUMMARY		
LUM NO.	LABEL	MTG. HT.
1	A2B	18
2	A2B	18
3	A2B2	18
4	A2B6	18
5	A2B6	18
6	A3B8	18
7	A3F	21
8	A3F	21
9	A4-2	18
10	A473	18
11	A48	18
12	A482	18
13	A4B1	18
14	A4B1	18
15	A4B1	18
16	A4B1	18
17	A4B1	18
18	A4B3	18
19	BV	2
20	BV	2
21	BV	2
22	BV	2
23	BV	2
24	BV	2
25	BV	2
26	CAN	17.5
27	CAN	17.5
28	CAN	17.5
29	CAN	17.5
30	CAN	17.5
31	CAN	17.5
32	CAN	17.5
33	CAN	17.5
34	CAN	17.5
35	CAN	17.5
36	CAN	17.5
37	CAN	17.5

LUMINAIRE LOCATION SUMMARY		
LUM NO.	LABEL	MTG. HT.
38	CAN	17.5
39	CAN	17.5
40	CAN	17.5
41	CAN	17.5
42	CAN	17.5
43	CAN	17.5
44	CAN	17.5
45	CAN	17.5
46	CAN	17.5
47	CAN	17.5
48	CAN	17.5
49	CAN	17.5
50	L	12
51	L	12
52	L	12
53	L	12
54	L	12
55	L	12
56	L	12
57	L	12
58	L	12
59	WP1	14.5
60	WP1	14.5
61	WP2	14.5
62	WP2	14.5
63	WP2	14.5
64	WP2	14.5
65	WP3	14.5
66	WP3	14.5
67	WP3	14.5
68	WP3	14.5
69	WP3	14.5
70	WP4	14.5
71	WP4	14.5
72	WP4	14.5
73	WP4	14.5
74	WP4	14.5

## WOODROFFE AVENUE

NOTE:  
- ALL AREA LIGHTS ON NEW 15 FT. POLE MOUNTED ON 3 FT. CONCRETE BASE  
- ALL LUMINAIRES HAVE ZERO LUMENS ABOVE 90 DEGREES

FOOTCANDLE LEVELS CALCULATED AT GRADE USING INITIAL LUMEN VALUES					
LABEL	AVG	MAX	MIN	Avg/Min	Max/Min
PAVED AREA	3.13	14.4	0.5	6.26	28.80
PROPERTY LINE	0.22	1.0	0.0	N.A.	N.A.
UNDEFINED	0.67	11.8	0.0	N.A.	N.A.
UNDER CANOPY	21.59	28	14	1.54	2.00

LUMINAIRE SCHEDULE											MANUFACTURER	CATALOG LOGIC
SYMBOL	QTY	LABEL	ARRANGEMENT	LUMENS	LATF	DIMMING LUMEN MULTIPLIER	LLF	BUG RATING	WATTS/LUMINAIRE	TOTAL WATTS	MANUFACTURER	CATALOG LOGIC
■	2	A2B	SINGLE	3300	1.040	1.000	1.040	B1-U0-G1	29	58	Cree Inc	OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-2M-UL-NM-XX + OSQ-BLSMF
■	1	A2B2	SINGLE	2150	1.040	1.000	1.040	B1-U0-G1	18	18	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-2M-UL-NM-XX-Q2 + OSQ-BLSMF
■	2	A2B6	SINGLE	2810	1.040	1.000	1.040	B1-U0-G1	24	48	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-2M-UL-NM-XX-Q6 + OSQ-BLSMF
■	1	A3B8	SINGLE	3250	1.040	1.000	1.040	B1-U0-G1	27	27	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-3M-UL-NM-XX-Q8 + OSQ-BLSMF
■	2	A3F	SINGLE	4290	1.040	1.000	1.040	B1-U0-G1	29	58	Cree Lighting	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-3M-UL-NM-XX
■	1	A4-2	BACK-BACK	15498	1.040	1.000	1.040	B3-U0-G3	104	208	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-16L-30K7-4M-UL-NM-XX
■	1	A473	3 @ 90 Degrees	3950	1.040	1.000	1.040	B1-U0-G1	26	78	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q7
■	1	A48	SINGLE	4120	1.040	1.000	1.040	B1-U0-G1	27	27	Cree Inc	OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q8
■	1	A482	Back-Back	4120	1.040	1.000	1.040	B1-U0-G1	27	54	Cree Inc	OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q8
■	5	A4B1	Single	1820	1.040	1.000	1.040	B0-U0-G1	16	80	Cree Inc	OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q1 + OSQ-BLSMF
■	1	A4B3	SINGLE	2410	1.040	1.000	1.040	B1-U0-G1	20	20	Cree Inc	OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q3 + OSQ-BLSMF
●	7	BV	Single					VISO Lighting				BL1.24
*	24	CAN	SINGLE	10999	1.040	0.550	0.572					