


2705460 ONTARIO INC.

112 MONTREAL ROAD STORMWATER MANAGEMENT REPORT

SEPTEMBER 13, 2022





112 MONTREAL ROAD STORMWATER MANAGEMENT REPORT

2705460 ONTARIO INC.

PROJECT NO.: 19M-01935-00
CLIENT REF:
DATE: SEPTEMBER 13, 2022

WSP
SUITE 300
2611 QUEENSVIEW DRIVE
OTTAWA, ON, CANADA K2B 8K2

T: +1 613 829-2800
F: +1 613 829-8299
WSP.COM

REVISION HISTORY

FIRST ISSUE

February 21, 2020	Draft for Client review			
Prepared by	Reviewed by	Approved By		
Michael Stewart, M.A.Sc., E.I.T. Land Development, E.I.T.	Ben Worth, P.Eng., C.Eng., MICE Manager, Water Resources	Ben Worth, P.Eng., C.Eng., MICE Manager, Water Resources		
REVISION 1				
March 6, 2020	For City Review			
Prepared by	Reviewed by	Approved By		
Michael Stewart, M.A.Sc., E.I.T. Land Development, E.I.T.	Ben Worth, P.Eng., C.Eng., MICE Manager, Water Resources	Ben Worth, P.Eng., C.Eng., MICE Manager, Water Resources		
REVISION 2				
May 7, 2021	For City Review			
Prepared by	Reviewed by	Approved By		
Julia Wansbrough, M.Sc., EIT Designer, Water Resources	Michelle Hughes, M.Sc., P.Eng. Project Manager, Water Resources	Michelle Hughes, M.Sc., P.Eng. Project Manager, Water Resources		
REVISION 3				
September 13, 2022	For City Review			
Prepared by	Reviewed by	Approved By		

Kathryn Kerker, M.A.Sc. Designer, Water Resources	Ayham Jadallah, M.Eng., P.Eng. Project Engineer, Water Resources	Ayham Jadallah, M.Eng., P.Eng. Project Engineer, Water Resources		
--	---	---	--	--

SIGNATURES

PREPARED BY



September 13, 2022

Kathryn Kerker, M.A.Sc.
Designer, Water Resources

Date

APPROVED¹ BY



September 13, 2022

Ayham Jadallah, M.A.Sc., P.Eng.
Project Engineer, Water Resources

Date

WSP Canada Group Ltd. prepared this report solely for the use of the intended recipient, 2705460 ONTARIO INC., in accordance with the professional services agreement. The intended recipient is solely responsible for the disclosure of any information contained in this report. The content and opinions contained in the present report are based on the observations and/or information available to WSP Canada Group Ltd. at the time of preparation. If a third party makes use of, relies on, or makes decisions in accordance with this report, said third party is solely responsible for such use, reliance or decisions. WSP Canada Group Ltd. does not accept responsibility for damages, if any, suffered by any third party as a result of decisions made or actions taken by said third party based on this report. This limitations statement is considered an integral part of this report.

The original of this digital file will be conserved by WSP Canada Group Ltd. for a period of not less than 10 years. As the digital file transmitted to the intended recipient is no longer under the control of WSP Canada Group Ltd., its integrity cannot be assured. As such, WSP Canada Group Ltd. does not guarantee any modifications made to this digital file subsequent to its transmission to the intended recipient.

¹ Approval of this document is an administrative function indicating readiness for release and does not impart legal liability on to the Approver for any technical content contained herein. Technical accuracy and fit-for-purpose of this content is obtained through the review process. The Approver shall ensure the applicable review process has occurred prior to signing the document.



TABLE OF CONTENTS

1	INTRODUCTION.....	1
1.1	Scope.....	1
1.2	Site Location.....	1
1.3	Stormwater Management Plan Objectives.....	2
1.4	Design Criteria.....	2
2	PRE-DEVELOPMENT CONDITIONS	3
2.1	General	3
2.2	Rainfall Information.....	3
2.3	Allowable Flow Rates.....	3
3	POST-DEVELOPMENT CONDITIONS	4
3.1	General	4
3.2	Quantity Control	4
3.3	Water Quality Control	6
3.4	Erosion Control	6
4	RIDEAU RIVER FLOOD PLAIN	7
5	CONCLUSIONS.....	8

TABLES

TABLE 2-1: PRE-DEVELOPMENT PEAK FLOW RATE CALCULATIONS (RUNOFF COEFFICIENT, $C = 0.50$ AND $T_c=20$ MIN)	3
TABLE 3-1 POST-DEVELOPMENT MODELLING RESULTS (A)	5
TABLE 3-2 POST-DEVELOPMENT MODELLING RESULTS (B)	5
TABLE 3-3 POST-DEVELOPMENT MODELLING RESULTS (C)	6

FIGURES

FIGURE 1: SITE LOCATION	1
-------------------------------	---

APPENDICES

A	RVCA CORRESPONDENCE
B	EXISTING SITE CONDITIONS
C	PRE-DEVELOPMENT CALCULATIONS
D	PROPOSED SITE DRAWINGS
E	CATCHMENT PLAN
F	SUPPORTING DOCUMENTS
F-1	HYDRO-BRAKE RATING CURVE
F-2	WATTS ACUTROL ROOF DRAIN
G	HYDROCAD MODEL OUTPUT
G-1	5-YEAR ANALYSIS (PEAK DISCHARGE)
G-2	100-YEAR ANALYSIS (PEAK DISCHARGE)
G-3	100-YEAR ANALYSIS (PEAK CISTERN STORAGE)
G-4	100-YEAR ANALYSIS (PEAK ROOF STORAGE)
H	FLOOD PLAIN MAPPING AND ELEVATIONS

1 INTRODUCTION

1.1 SCOPE

WSP Canada Group Ltd. was retained by 2705460 Ontario Inc. to conduct a stormwater management study to service the proposed redevelopment of the existing Econolodge site into a new group of residential towers.

1.2 SITE LOCATION

The existing site is located at 112 Montreal Road in Ottawa, Ontario, close to the south-west corner of the Montreal Road and Vanier Parkway intersection. The location of the proposed re-development is illustrated in **Figure 1**.




Figure 1: Site Location

1.3 STORMWATER MANAGEMENT PLAN OBJECTIVES

The objectives of the stormwater management plan are as follows:

- Determine site specific stormwater management requirements to ensure that the plan is in conformance with the City of Ottawa Sewer Design Guidelines, October 2012.
- Prepare a stormwater management report documenting the strategy along with the technical information necessary for the justification and sizing of the proposed stormwater management facilities.

1.4 DESIGN CRITERIA

The City of Ottawa (the City) was contacted to determine the stormwater management (SWM) requirements for discharge into the local City sewers for the project site. Joshua White at the City specified that flows greater than the 5-year flow generated from a runoff coefficient of 0.50 must be controlled on site up to the 100-year return period (consistent with Section 8.3.7.3 of the Ottawa Sewer Design Guidelines, October 2012).

The runoff coefficient used for design (100-year return period), was increased by 25% to comply with section 5.4.5.2.1 of the Ottawa Sewer Design Guidelines (October 2012).

As per section 8.3.7 of the Ottawa Sewer Design Guidelines “New development draining to an existing system that has no stormwater treatment facility may be subject to on-site treatment (i.e. best management practice, oil grit separators, etc.). Some existing areas within the City may be subject to a cash-in-lieu policy with respect to stormwater treatment. The designer must confirm with the City if the development area in question is subject to this policy”. The City directed WSP to contact the Rideau Valley Conservation Authority (RVCA) to determine any applicable water quality criteria to be used in the design. The RVCA specified no treatment criteria for this site. A record of this conversation has been included in **Appendix A**. Similarly, the City has not specified any water quality requirements for use at this site. Therefore, none have been specifically included in the design.

In summary, the design criteria for stormwater management at the site are:

- Control the 100-year outflow from the site to the 5-year flow using a runoff coefficient of 0.50 and a T_c of 20 minutes; and
- No water quality treatment is required.

2 PRE-DEVELOPMENT CONDITIONS

2.1 GENERAL

The subject property pre-development includes an impervious at-grade parking lot, an existing group of commercial buildings (Econolodge) and a pervious landscaped area at the south-east corner of the project site. The total site area is 1.22 ha. Please refer to **Appendix B** for existing site conditions.

2.2 RAINFALL INFORMATION

The rainfall intensity is calculated in accordance with Section 5.4.2 of the Ottawa Sewer Design Guidelines (October 2012):

$$i = \left[\frac{A}{(Td + C)^B} \right]$$

Where;

- A, B, C = regression constants for each return period (defined in section 5.4.2)
- i = rainfall intensity (mm/hour)
- Td = storm duration (minutes)
- The IDF parameters/regression constants are included in **Appendix C**.

2.3 ALLOWABLE FLOW RATES

As noted in section 1.4, the City of Ottawa specified the allowable discharge rate from this site as the 5-year flow generated from a runoff coefficient of 0.50, controlled on site up to the 100-year return period.

The allowable release rate to the municipal storm sewer system from the proposed development is 119 l/sec, based on the 5-year pre-development flow rate calculated with a runoff coefficient value of 0.50.

The calculated peak flow rates for the site in the pre-development condition are summarized below in Table 2-1. Detailed calculations are contained within Appendix C.

Table 2-1: Pre-Development Peak Flow Rate Calculations (Runoff Coefficient, C = 0.50 and T_c=20 min)

RETURN PERIOD (YEARS)	RAINFALL INTENSITY (MM/HOUR)	PEAK FLOW RATE (L/SEC)	TARGET RELEASE RATE (L/SEC)
2	52.0	88.2	119.0
5	70.3	119.0	
10	82.2	139.3	
25	97.3	164.8	
50	108.5	183.8	
100	120.0	203.2	

3 POST-DEVELOPMENT CONDITIONS

3.1 GENERAL

The project proposals consist of a mixed-use development with 2 towers; a 37-storey residential tower (Tower B1), and an 8-storey mixed use building (Tower A). A multi-level basement structure is proposed over the majority of the project site area. As described further in subsequent sections of the report, a SWM cistern will be provided at the south end of the site with a connection to Montreal Road. Please refer to **Appendix D** for an illustration of the project (Storm Drainage Area Plan).

The analysis for the site and the sizing of the cistern has been completed with provisions for future development in the southeast quadrant of the site. A runoff coefficient of 0.8 has been assigned to represent the future land-use in this area (S06 and S07 on the Storm Drainage Area Plan).

The following assumptions have been used to quantify stormwater runoff for modelling/analysis purposes: 100% of proposed roof surfaces have been considered as impervious, and the top level of the rooftop area of each tower will be available for temporary surface ponding (via drainage by controlled discharge roof drains).

The entire project area will comply with the target allowable release rate.

3.2 QUANTITY CONTROL

As noted in section 2.3, the target allowable discharge rate to the municipal sewer system from the site is 119 L/sec. This is equivalent to the peak runoff rate under pre-development conditions during a 5-year design storm event with a runoff coefficient of 0.50. Compliance with the target offsite discharge rate will be achieved through use of controlled flow rooftop drains, and the provision of an underground cistern storage structure. Post-development runoff calculations have accounted for uncontrolled runoff from portions of the site that will not drain to storage features.

A cistern was identified as the preferred storage option given the substantial underground parking requirement for the site; surface storage was not considered a viable option and was not accounted for in this analysis.

The cistern is designed to receive runoff (for all events up to and including the 100-year return period), from roof surfaces and at-grade areas within the development area. The controlled and uncontrolled project areas are illustrated in **Appendix E**. The cistern will discharge to the existing municipal storm sewer system via gravity, and peak outflow rates will be controlled via a vortex flow control device (**Appendix F**).

To satisfy net target release rates for controlled and uncontrolled site areas, the recommended peak discharge rate for flow control device is 110 L/sec. If a storm event that occurs fills the cistern, the access hatch at the top of the cistern would allow water to spill to Palace Street. major system. It is noted that the return period associated with an overflow event requiring these facilities to spill would exceed 100-years.

As per the Site Servicing Plan Drawing, discharge from the cistern is proposed to the Montreal Road trunk storm sewer. This trunk storm sewer is 1050mm and it is believed that the City's flow control requirements for the site (which currently drains to this same storm sewer) are sufficient to ensure that there will be no adverse surcharging of the storm sewer.

As noted above, the top level of the rooftop area of each tower will be available for temporary surface ponding (via drainage by controlled discharge roof drains), and the remaining roof areas will drain directly to the cistern without any rooftop storage. Calculations were done based on the roof drain layouts, with four roof drains on Tower A and 6 roof drains on Tower B1. For modelling purposes, these outlets were simulated using rating curves for a *Watts Accutrol* product (in the "fully closed" position) (**Appendix F**).

Appendix E illustrates the small portions of the project site that will drain offsite uncontrolled in post-development conditions. These uncontrolled runoff rates contribute to the total allowable release rate modelled.

A HydroCAD model of the project was constructed and utilized to include:

- storage and controlled release of stormwater from top level of rooftop areas (Towers A and B1) to the cistern;
- runoff from the remaining rooftop areas (Towers A and B1) directly to the cistern;
- controlled runoff from at-grade areas directed to the cistern; and
- uncontrolled runoff rates generated from at grade areas (S08 and S09)

The Modified Rational Method (an inherent subroutine of the HydroCAD software) has been used for the modelling exercise, and the model has informed the maximum storage volume used in the stormwater cistern based on the proposed flow. Flow rates generated from uncontrolled drainage areas within the project site and controlled flow from the cistern meet the target offsite discharge rate required (119 l/s).

The rainfall intensity and storm duration combination resulting in the largest peak flow discharged to the sewer system occurs at the critical storm duration, $t_d = 10$ minutes for the 100-year event (determined iteratively using HydroCAD). A summary of the model results and storage controls are listed in Table 3-1 to

Table 3-3 and the full modelling output is included in **Appendix G**.

The modelled post-development peak flow rates comply with the allowable release rate for the 100-year return period (**Table 3-1**).

Table 3-1 Post-Development Modelling Results (A)

RETURN PERIOD (YEARS)	MODELLED POST-DEV. PEAK FLOW RATE (L/SEC) ¹	ALLOWABLE RELEASE RATE (L/SEC)
5	97.8	119
100	106.0	

¹ Includes flow rates generated from uncontrolled drainage areas within the project site and controlled flow from the cistern

The HydroCAD analysis completed allows the performance of the SWM drainage system to be verified in all possible storm durations (based on Modified Rational method calculations) and helps identify the critical duration for different components of the system. For example, the critical storm duration for the cistern (resulting in maximum storage utilized) was found to be $t_d = 32$ minutes. A summary of these modelling results is provided below.

The results show that the maximum utilized storage volume in the Cistern is 309 m³ to control the 100-year post-development runoff (**Table 3-2**).

Table 3-2 Post-Development Modelling Results (B)

RETURN PERIOD (YEARS)	MAXIMUM UTILIZED STORAGE AND ASSOCIATED PEAK FLOW (L/s)	
	(m ³)	(L/s)
100	309	97.6

¹ Critical duration resulting in maximum storage utilized in the cistern

Maximum rooftop storage volumes and release rates (based on the critical duration for each of the different components of the system), in addition to uncontrolled flow rates generated from uncontrolled areas are provided in

Table 3-3.

Table 3-3 Post-Development Modelling Results (C)

RETURN PERIOD (YEARS)	ROOFTOP MAXIMUM STORAGE VOLUME & PEAK RELEASE RATE ¹				UNCONTROLLED FLOW RATE ² (L/s)
	TOWER A		TOWER B1		
	(m ³)	(L/s)	(m ³)	(L/s)	
5	6.7	1.2	11.3	1.9	6.1
100	16.2	1.2	26.9	1.9	15.8

¹ Based on the critical duration resulting in maximum storage utilized on each roof surface

² Based on the critical duration resulting in the maximum flow released

3.3 WATER QUALITY CONTROL

As per Section 1.4, no water quality treatment is required.

3.4 EROSION CONTROL

Please refer to the Erosion and Sedimentation Control plan drawing C.05 as part of the Engineering Drawing Set.

4 RIDEAU RIVER FLOOD PLAIN

The RVCA were consulted to obtain flood plain mapping for the Rideau River in the vicinity of the subject site. Please refer to mapping excerpt provided in **Appendix H**.

It is noted that the 100-year flood plain extends onto Montreal Road, to a modelled elevation of 56.52 m (cross section reference 2474). The site design has accounted for this by setting the minimum ground elevation at the project threshold to an elevation of 56.62 m (refer to Grading and Drainage Plan Drawing C.02 for details), and by specifying the use of non-return backflow preventers within the flow control device associated with the cistern.

5 CONCLUSIONS

A stormwater management plan has been prepared to support the site plan application for the 112 Montreal Road development in the City of Ottawa. The key points are summarized below.

WATER QUANTITY

Controlled runoff collected from the project site will be directed to a stormwater cistern with a minimum active storage volume of 309 m³ to control the 100-year event. Discharge from the cistern to the municipal storm sewer will be controlled using a vortex flow control device (specified with a peak discharge rate of 98 l/sec).

For the 100-year return period, the uncontrolled runoff (A-06 and A-07) and flow control from the cistern directed to the municipal storm sewer system, will comply with the allowable 5-year release rate of 119 l/sec (calculated using a runoff coefficient of 0.50 and a T_c of 20 minutes).

WATER QUALITY

No specific water quality treatment features are required.

This report demonstrates that the proposed SWM strategy will address stormwater management related impacts from this project and meet the requirements of the City of Ottawa.

APPENDIX

A

RVCA
CORRESPONDENCE



1145 Hunt Club Road, Suite 300
Ottawa, Ontario K1V 0Y3
Tel: (613) 736-7200
Fax: (613) 736-8710

TELECOM RECORD

W.O.: 1013081
DATE: August 11, 2014
TIME: 2:30
CALL FROM: Bryan Orendorff
REPRESENTING: MMM
CALL TO: Brandon Williams
REPRESENTING: RVCA

REGARDING: SWM requirements for proposed 112 Montreal Road Development

DISCUSSION: MMM contacted the RVCA to determine if they had any SWM requirements for the proposed site. The City had previously directed MMM to take this action. Brandon replied that the RVCA did not anticipate any involvement was required on their part for this site from a floodplain perspective (the site is outside the floodplain) and that they typically would not comment on a site application until it was circulated to them by the City. He indicated that the RVCA in this case could rely on the City to ensure that all appropriate requirements were being met.

ACTION: No actions required.


CC:

APPENDIX

B

EXISTING SITE
CONDITIONS

METRIC
DISTANCES AND ELEVATIONS SHOWN ON THIS PLAN ARE IN METRES
AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048



TOPOGRAPHIC SURVEY OF LOT 5 AND PART OF LOTS 6 AND 7 BLOCK 2 REGISTERED PLAN 29 AND LOT 88 AND PART OF LOTS 40 & 41 REGISTERED PLAN 49 CITY OF OTTAWA

SCALE 1 : 250
FAIRHALL, MOFFATT & WOODLAND LIMITED
ONTARIO LAND SURVEYORS

ELEVATION NOTES
1. ELEVATIONS SHOWN HEREON ARE REFERRED TO GEODETIC DATUM.
2. ELEVATIONS FOR MANHOLE COVERS AND CATCH BASINS HAVE TO BE INDEPENDENTLY CONFIRMED BEFORE THEY CAN BE ACCEPTED FOR FINAL DESIGN OR CONSTRUCTION PURPOSES.
3. IT IS THE RESPONSIBILITY OF THE USER OF THIS INFORMATION TO VERIFY THAT THE JOB BENCHMARKS HAVE NOT BEEN ALTERED OR DISTURBED AND THAT THEIR RELATIVE ELEVATION AND DESCRIPTION AGREE WITH THE INFORMATION SHOWN ON THIS DRAWING.

UTILITY NOTES
1. THIS DRAWING CANNOT BE ACCEPTED AS ACKNOWLEDGING ALL OF THE UNDERGROUND UTILITIES AND IT WILL BE THE RESPONSIBILITY OF THE USER TO CONTACT THE RESPECTIVE UTILITY AUTHORITIES FOR CONFIRMATION OR LOCATION.
2. UNDERGROUND UTILITIES, AS REPORTED ON THIS DRAWING, ARE NOT BASED ON AN ACTUAL FIELD LOCATE BY THE RESPECTIVE UTILITY AGENCIES BUT HAVE BEEN COMPILED FROM DATA OBTAINED FROM THE FOLLOWING SOURCE:
a) CITY OF OTTAWA PUBLIC UTILITIES REGISTRY
3. BEFORE ANY WORK INVOLVING PROBING, EXCAVATING, ETC., A FIELD LOCATION OF UNDERGROUND PLANT BY THE PERTINENT UTILITY AUTHORITY IS MANDATORY.

NOTES
1. BEARINGS ARE ASTRONOMIC AND ARE DERIVED FROM THE WESTERLY LIMIT OF PART 1, PLAN SR-6112 SHOWN AS HAVING A BEARING OF N 28°27'30" W.
2. REVISION: JULY 16, 2014 - ADDED UTILITIES ALONG VANIER PARKWAY AND INTERSECTION OF VANIER PARKWAY AND MONTREAL ROAD.

SURVEYOR'S CERTIFICATE
I CERTIFY THAT:
1. THIS SURVEY AND PLAN ARE CORRECT AND IN ACCORDANCE WITH THE SURVEYS ACT, THE SURVEYORS ACT, THE LAND TITLES ACT AND THE REGULATIONS MADE UNDER THEM.
2. THE SURVEY WAS COMPLETED ON JULY 12, 2014.

DATE: _____ JOHN H. GUTHRIE
ONTARIO LAND SURVEYOR

Fairhall Moffatt & Woodland
100-600 1887 7TH AVE. S.W., SUITE 200, VANCOUVER, B.C. V6Z 2G6
TEL: (616) 591-2500 FAX: (616) 591-1450
www.fmw.com

JOB NO. T 25600
E 370053, N 5032955
REFERENCE No. 21(a)-49, 15(a)-29
TP2561.DWG (DWG)

- LEGEND**
- SURVEY MONUMENT FOUND
 - SIB — STANDARD IRON BAR
 - SIBB — SHORT STANDARD IRON BAR
 - IB — IRON BAR
 - MNW — MAGNETIC NAIL & WASHER
 - ROUND
 - (P) — PLAN SR-6112
 - (P1) — PLAN SR-258
 - (M) — MEASURED
 - (S) — SET
 - (857) — FAIRHALL, MOFFATT & WOODLAND LIMITED, O.L.S.
 - (CITY) — CITY OF OTTAWA
 - (SU) — SOURCE UNKNOWN
 - (W) — WITNESS
 - PIN — PROPERTY IDENTIFIER NUMBER
 - DIA. — DIAMETER
 - INV. — INVERT
 - BLDG. — BUILDING
 - E — EAST
 - W — WEST
 - N — NORTH
 - ▲ — PROJECT CONTROL MONUMENT
 - — PILLAR
 - CB — CATCH BASIN
 - — MANHOLE
 - LS — LAMP STANDARD
 - UP — UTILITY POLE
 - FH — FIRE HYDRANT
 - WV — WATER VALVE
 - BH — BOREHOLE
 - BP — BELL PEDESTAL
 - JB — JUNCTION BOX
 - FP — FLAG POLE
 - GUY WIRE AND ANCHOR
 - BOLLARD
 - SIGN
 - CONIFEROUS TREE
 - DECIDUOUS TREE
 - SHRUB
 - SHRUB
 - HANDICAP
 - NO PARKING
 - WATERMAIN
 - OVERHEAD UTILITY WIRES
 - UNDERGROUND HYDRO
 - UNDERGROUND BELL
 - GAS MAIN
 - STORM SEWER
 - SANITARY SEWER
 - ROGERS CABLE
 - CURB

INVERT TABLE

NUMBER	ELEVATION	INVERTS	NUMBER	ELEVATION	INVERTS
MH#1	56.52	53.86 North	CB#11	56.21	55.55 Northwest
		53.89 South			Full of Debris
MH#2	56.37	54.24 North	CB#12	56.71	55.40 South
		54.44 South			55.74 East
		54.34 South	CB#13	56.73	Full of Debris & Water
MH#3	56.06	53.42 North			Full of Water
		Full of Water	MH#14	56.81	55.41 North
MH#4	56.11	53.69 East			53.69 South
		53.65 North	CB#15	56.90	Inaccessible
CB#5	56.00	Invert Inaccessible	MH#16	57.45	55.13 North
CB#6	56.11	Northwest Inaccessible			55.12 South
		55.01 Southwest	CB#17	57.31	55.87 West
		West Inaccessible			54.05 East
MH#7	56.22	54.05 East	MH#18	56.70	54.07 North
		54.86 North			54.06 South
CB#8	55.80	54.80 West	MH#19	56.50	53.69 North
		Inaccessible			53.90 South
CB#9	55.79	Inaccessible	CB#20	56.33	55.52 West
CB#10	55.82	Inaccessible			

© COPYRIGHT 2014. REPRODUCTION, ALTERATION OR DISTRIBUTION OF THIS PLAN WITHOUT THE WRITTEN CONSENT OF FAIRHALL, MOFFATT & WOODLAND LIMITED IS PROHIBITED.

APPENDIX

C

PRE-DEVELOPMENT CALCULATIONS

	Stormwater Management Calculations	Project: 112 Montreal Road	No.: 19M-01935-00	
	Pre-Dev Release Rates	By: JW	Date: 5/7/2021	Page: 1
		Checked: MH		

Step 1: Determine Pre-development Flow using Rational Formula

* Runoff Coefficient, C in accordance with City of Ottawa Sewer Design Guidelines (section 8.3.7.3)
 Runoff Coefficient, C = 0.5 -

Rainfall intensity calculated in accordance with City of Ottawa Sewer Design Guidelines (section 5.4.2):

$$i = \left[\frac{A}{(Td + C)^B} \right]$$

Where: A, B, C = regression constants for each return period (defined in section 5.4.2)

i = rainfall intensity (mm/hour)

Td = storm duration (minutes) 180 minutes

Time of Concentration = 20 minutes

Catchment Area = 1.22 ha

Return Period	2	5	10	25	50	100
a =	733.0	998.1	1,174.2	1,402.9	1,569.6	1,735.7
b =	0.810	0.814	0.816	0.819	0.820	0.820
c =	6.199	6.053	6.014	6.018	6.014	6.014
Intensity _{peak} (mm/hr) =	52.0	70.3	82.2	97.3	108.5	120.0
Q _{peak} (L/s) =	88.2	119.0	139.3	164.8	183.8	203.2
Q _{peak} (m ³ /s) =	0.088	0.119	0.139	0.165	0.184	0.203

Return Period = 5 year

Q = 119.0 L/s Pre-development flow rate

Conclusion:

The 5-year pre-development flow rate for a 20 minute Tc governs the 100-year maximum post-development release rate and is 120.5 L/s.


Filepath:

L:\Water Resources\Projects\Pre-2017\1013081-000 - 112 Montreal Road\20210401 Updated Site Plan\210428_JW\112 Montreal Rd Calcs.xlsx\IDF Calcs

APPENDIX

D

PROPOSED SITE
DRAWINGS



FILENAME: V:\19\19M-01935-00 - 112 Montreal Road - Site Plan\Drawings\storm drainage\19M-01935-00_C_REV1.dwg
 PLOTDATE: Sep 07, 2022 - 3:30pm user:DBR241

D07-XX-XX-XXXX
 #XXXX

APPENDIX

E

CATCHMENT PLAN







GENERAL NOTES:
 THE ENGINEER WAIVES ANY AND ALL RESPONSIBILITY AND LIABILITY FOR PROBLEMS WHICH ARISE FROM FAILURE TO FOLLOW THE PLANS, SPECIFICATIONS AND THE DESIGN INTENT THEY CONVEY, OR FOR PROBLEMS WHICH ARISE FROM OTHERS FAILURE TO OBTAIN AND/OR FOLLOW THE ENGINEERS GUIDANCE WITH RESPECT TO ANY ERRORS, OMISSIONS, INCONSISTENCIES, AMBIGUITIES OR CONFLICTS WHICH ARE ALLEGED.
 CONTRACTOR TO VERIFY ALL DIMENSIONS AND NOTIFY THE ENGINEER OF ANY DISCREPANCIES BEFORE WORK COMMENCES. DO NOT SCALE DRAWINGS.



KEY PLAN (N.T.S.)

No.	REVISIONS	BY	DATE
01	ISSUED FOR SPA	D.Y.	2022-09-08



wsp
 2611 Queensway Dr. Ottawa, ON Canada K2B 8K2
 t: 613.829.2800 f: 613.829.8299 www.wspgroup.com

CLIENT: 2705460 ONTARIO INC.
 C/O ANAND AGGARWAL
 MANOR PARK MANAGEMENT
 231 BRITANNY DRIVE, SUITE D
 OTTAWA, ON K1K 0R8

rla/architecture
 rodrick lahey architect inc.
 54 beach street, ottawa, ontario k1s 3k4
 t: 613.734.9932 f: 613.734.1209 d: rla@rlaarchitect.com


ANNIS, O'SULLIVAN, VOLLEBECK
 Ontario Land Surveyors
 14 CONOURS GATE, SUITE 400, WILLOWDALE, ONTARIO, M2E 7S8
 TEL: (416) 372-0850 FAX: (416) 372-1079

DESIGNED BY: D.Y. DRAWN BY: J.T. APPROVED BY: D.Y.

PROJECT: 112 MONTREAL ROAD
 RESIDENTIAL DEVELOPMENT

DRAWING TITLE: STORM DRAINAGE
 AREA PLAN

PROJECT NO: 19M-01935-00 DRAWING NO: C04



FILENAME: V:\10_11\19M-01935-00 - 112 Montreal Road - Storm Drainage Drawing.dwg
 PLOTDATE: Sep 07, 2022 - 3:30pm
 USER: D.Y.

D07-XX-XX-XXXX

#XXXX

APPENDIX

F

SUPPORTING
DOCUMENTS

APPENDIX

F-1 *HYDRO-BRAKE RATING CURVE*

Technical Specification


Control Point	Head (m)	Flow (l/s)
Primary Design	2.000	98.000
Flush-Flo™	0.671	97.653
Kick-Flo®	1.418	82.712
Mean Flow		82.694

Hydro-Brake® Optimum Flow Control including:

- 5 mm grade 304L stainless steel
- Integral stainless steel pivoting by-pass door allowing clear line of sight through to outlet, c/w stainless steel operating rope outlet, c/w stainless steel operating rope
- Beed blasted finish to maximise corrosion resistance
- Stainless steel fixings
- Rubber gasket to seal outlet



hydro-int.com/patents



IMPORTANT: ○ LIMIT OF HYDRO INTERNATIONAL SUPPLY
 THE DEVICE WILL BE HANDED TO SUIT SITE CONDITIONS
 FOR SITE SPECIFIC DETAILS AND MINIMUM CHAMBER SIZE REFER TO HYDRO INTERNATIONAL
 ALL CIVIL AND INSTALLATION WORK BY OTHERS
 * WHERE SUPPLIED
 HYDRO-BRAKE® FLOW CONTROL & HYDRO-BRAKE® OPTIMUM FLOW CONTROL ARE REGISTERED TRADEMARKS FOR FLOW
 CONTROLS DESIGNED AND MANUFACTURED EXCLUSIVELY BY HYDRO INTERNATIONAL

THIS DESIGN LAYOUT IS FOR ILLUSTRATIVE PURPOSES ONLY. NOT TO SCALE.

DESIGN ADVICE



The head/flow characteristics of this SHE-0379-9800-2000-9800 Hydro-Brake® Optimum Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve.
The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.

Hydro
 International

DATE	3/3/2020 9:29 PM	SHE-0379-9800-2000-9800 Hydro-Brake® Optimum
SITE		
DESIGNER	Michael Stewart	
REF		

© 2020 Hydro International Ltd, 94 Hutchins Drive, Portland, Maine, 04102-1930. Tel: +1 (207) 756 6200 Fax: +1 (207) 756 6212 Web: www.hydro-int.com Email: enquiries@hydro-int.com


Technical Specification

Control Point	Head (m)	Flow (l/s)
Primary Design	2.000	98.000
Flush-Flo	0.671	97.653
Kick-Flo®	1.418	82.712
Mean Flow		82.694



PT/329/0412

hydro-int.com/patents



Head (m)	Flow (l/s)
0.000	0.000
0.069	5.223
0.138	19.426
0.207	39.978
0.276	63.440
0.345	85.082
0.414	93.850
0.483	95.829
0.552	96.996
0.621	97.547
0.690	97.641
0.759	97.411
0.828	96.960
0.897	96.359
0.966	95.642
1.034	94.799
1.103	93.775
1.172	92.463
1.241	90.714
1.310	88.336
1.379	85.109
1.448	83.571
1.517	85.475
1.586	87.335
1.655	89.154
1.724	90.936
1.793	92.681
1.862	94.393
1.931	96.073
2.000	97.723

DESIGN ADVICE

The head/flow characteristics of this SHE-0379-9800-2000-9800 Hydro-Brake Optimum® Flow Control are unique. Dynamic hydraulic modeling evaluates the full head/flow characteristic curve.



The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.



DATE 3/3/2020 9:29 PM

Site

DESIGNER Michael Stewart

Ref

SHE-0379-9800-2000-9800

Hydro-Brake Optimum®

APPENDIX

F-2 *WATTS ACUTROL ROOF DRAIN*



Adjustable Accutrol Weir

Tag: _____

Adjustable Flow Control for Roof Drains



ADJUSTABLE ACCUTROL (for Large Sump Roof Drains only)

For more flexibility in controlling flow with heads deeper than 2", Watts Drainage offers the Adjustable Accutrol. The Adjustable Accutrol Weir is designed with a single parabolic opening that can be covered to restrict flow above 2" of head to less than 5 gpm per inch, up to 6" of head. To adjust the flow rate for depths over 2" of head, set the slot in the adjustable upper cone according to the flow rate required. Refer to Table 1 below.
 Note: Flow rates are directly proportional to the amount of weir opening that is exposed.

EXAMPLE:

For example, if the adjustable upper cone is set to cover 1/2 of the weir opening, flow rates above 2" of head will be restricted to 2-1/2 gpm per inch of head.

Therefore, at 3" of head, the flow rate through the Accutrol Weir that has 1/2 the slot exposed will be:
 [5 gpm (per inch of head) x 2 inches of head] + 2-1/2 gpm (for the third inch of head) = 12-1/2 gpm.



1/2 Weir Opening Exposed Shown Above

TABLE 1. Adjustable Accutrol Flow Rate Settings

Weir Opening Exposed	1"	2"	3"	4"	5"	6"
	Flow Rate (gallons per minute)					
Fully Exposed	5	10	15	20	25	30
3/4	5	10	13.75	17.5	21.25	25
1/2	5	10	12.5	15	17.5	20
1/4	5	10	11.25	12.5	13.75	15
Closed	5	5	5	5	5	5

Job Name _____
 Job Location _____
 Engineer _____

Contractor _____
 Contractor's P.O. No. _____
 Representative _____

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: Tel: (800) 338-2581 • Fax: (828) 248-3929 • Watts.com
 Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • Watts.ca
 Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • Watts.com



APPENDIX

G

HYDROCAD MODEL
OUTPUT

APPENDIX

G-1 *5-YEAR ANALYSIS* *(PEAK DISCHARGE)*

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Printed 2022-09-02

Page 2

Area Listing (selected nodes)

Area (sq-meters)	C	Description (subcatchment-numbers)
3,790.0	0.71	S03 (43S)
720.0	0.74	S04 (43S)
250.0	0.61	S05 (43S)
5,200.0	0.80	S06 (43S)
690.0	0.80	S07 (43S)
105.0	0.90	S08 (47S)
99.0	0.58	S09 (47S)
500.0	0.90	Tower A (44S, 45S)
810.0	0.90	Tower B1 (44S, 46S)
12,164.0	0.77	TOTAL AREA



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 3

Time span=0.00-4.00 hrs, dt=0.01 hrs, 401 points

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment 43S: Controlled to CisternRunoff Area=10,650.0 m² Runoff Depth=17 mm
Tc=10.0 min C=0.76 Runoff=0.1686 m³/s 182.0 m³**Subcatchment 44S: Towers to Cistern**Runoff Area=325.0 m² Runoff Depth=20 mm
Tc=10.0 min C=0.90 Runoff=0.0061 m³/s 6.6 m³**Subcatchment 45S: Tower A to Rooftop**Runoff Area=375.0 m² Runoff Depth=20 mm
Tc=10.0 min C=0.90 Runoff=0.0070 m³/s 7.6 m³**Subcatchment 46S: Tower B1 to Rooftop**Runoff Area=610.0 m² Runoff Depth=20 mm
Tc=10.0 min C=0.90 Runoff=0.0114 m³/s 12.3 m³**Subcatchment 47S: Uncontrolled**Runoff Area=204.0 m² Runoff Depth=17 mm
Tc=10.0 min C=0.74 Runoff=0.0031 m³/s 3.4 m³**Pond 48P: Tower A Rooftop Storage**Peak Elev=100.068 m Storage=5.8 m³ Inflow=0.0070 m³/s 7.6 m³
Outflow=0.0012 m³/s 7.6 m³**Pond 49P: Tower B1 Rooftop Storage**Peak Elev=100.069 m Storage=9.7 m³ Inflow=0.0114 m³/s 12.3 m³
Outflow=0.0019 m³/s 12.3 m³**Pond 50P: Cistern**Peak Elev=55.237 m Storage=99.2 m³ Inflow=0.1777 m³/s 208.6 m³
Primary=0.0957 m³/s 208.6 m³ Secondary=0.0000 m³/s 0.0 m³ Outflow=0.0957 m³/s 208.6 m³**Link 51L: Site Release**Inflow=0.0978 m³/s 212.0 m³
Primary=0.0978 m³/s 212.0 m³**Total Runoff Area = 12,164.0 m² Runoff Volume = 212.0 m³ Average Runoff Depth = 17 mm****112MontrealRd_100 year**

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr


Printed 2022-09-02

Page 4

Summary for Subcatchment 43S: Controlled to CisternRunoff = 0.1686 m³/s @ 0.17 hrs, Volume= 182.0 m³, Depth= 17 mmRunoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Area (m ²)	C	Description
3,790.0	0.71	S03
5,200.0	0.80	S06
720.0	0.74	S04
250.0	0.61	S05
690.0	0.80	S07
10,650.0	0.76	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m ³ /s)	Description
10.0					Direct Entry,

Subcatchment 43S: Controlled to Cistern

112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 5

Summary for Subcatchment 44S: Towers to Cistern

Runoff = 0.0061 m³/s @ 0.17 hrs, Volume= 6.6 m³, Depth= 20 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Area (m²)	C	Description
125.0	0.90	Tower A
200.0	0.90	Tower B1
325.0	0.90	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 44S: Towers to Cistern

Hydrograph



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 6

Summary for Subcatchment 45S: Tower A to Rooftop

Runoff = 0.0070 m³/s @ 0.17 hrs, Volume= 7.6 m³, Depth= 20 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Area (m²)	C	Description
375.0	0.90	Tower A

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 45S: Tower A to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 7

Summary for Subcatchment 46S: Tower B1 to Rooftop

Runoff = 0.0114 m³/s @ 0.17 hrs, Volume= 12.3 m³, Depth= 20 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Area (m²)	C	Description
610.0	0.90	Tower B1

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 46S: Tower B1 to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 8

Summary for Subcatchment 47S: Uncontrolled

Runoff = 0.0031 m³/s @ 0.17 hrs, Volume= 3.4 m³, Depth= 17 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Area (m²)	C	Description
99.0	0.58	S09
105.0	0.90	S08
204.0	0.74	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 47S: Uncontrolled

Hydrograph



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 9

Summary for Pond 48P: Tower A Rooftop Storage

Inflow Area = 375.0 m², Inflow Depth = 20 mm for 5-Year event
 Inflow = 0.0070 m³/s @ 0.17 hrs, Volume= 7.6 m³
 Outflow = 0.0012 m³/s @ 0.12 hrs, Volume= 7.6 m³, Atten= 82%, Lag= 0.0 min
 Primary = 0.0012 m³/s @ 0.12 hrs, Volume= 7.6 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.068 m @ 0.44 hrs Surf.Area= 170.7 m² Storage= 5.8 m³

Plug-Flow detention time= 40.7 min calculated for 7.6 m³ (100% of inflow)
 Center-of-Mass det. time= 40.7 min (54.7 - 14.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	28.1 m ³	Custom Stage Data (Prismatic) Listed below (Recalc) x 4

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
100.000	0.0	0.0	0.0
100.150	93.7	7.0	7.0

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 4.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0012 m³/s @ 0.12 hrs HW=100.026 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0012 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 10

Pond 48P: Tower A Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 11

Summary for Pond 49P: Tower B1 Rooftop Storage

Inflow Area = 610.0 m², Inflow Depth = 20 mm for 5-Year event
 Inflow = 0.0114 m³/s @ 0.17 hrs, Volume= 12.3 m³
 Outflow = 0.0019 m³/s @ 0.12 hrs, Volume= 12.3 m³, Atten= 84%, Lag= 0.0 min
 Primary = 0.0019 m³/s @ 0.12 hrs, Volume= 12.3 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.069 m @ 0.44 hrs Surf.Area= 280.8 m² Storage= 9.7 m³

Plug-Flow detention time= 44.9 min calculated for 12.3 m³ (100% of inflow)
 Center-of-Mass det. time= 45.0 min (59.0 - 14.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	45.7 m ³	Custom Stage Data (Prismatic) Listed below (Recalc) x 6

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
100.000	0.0	0.0	0.0
100.150	101.6	7.6	7.6

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 6.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0019 m³/s @ 0.12 hrs HW=100.026 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0019 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 12

Pond 49P: Tower B1 Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 13

Summary for Pond 50P: Cistern

[44] Hint: Outlet device #1 is below defined storage

Inflow Area = 11,960.0 m², Inflow Depth = 17 mm for 5-Year event
 Inflow = 0.1777 m³/s @ 0.17 hrs, Volume= 208.6 m³
 Outflow = 0.0957 m³/s @ 0.38 hrs, Volume= 208.6 m³, Atten= 46%, Lag= 12.5 min
 Primary = 0.0957 m³/s @ 0.38 hrs, Volume= 208.6 m³
 Secondary = 0.0000 m³/s @ 0.00 hrs, Volume= 0.0 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 55.237 m @ 0.38 hrs Surf.Area= 250.0 m² Storage= 99.2 m³

Plug-Flow detention time= 13.3 min calculated for 208.0 m³ (100% of inflow)
 Center-of-Mass det. time= 13.3 min (31.4 - 18.1)

Volume	Invert	Avail.Storage	Storage Description
#1	54.840 m	325.0 m ³	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
54.840	250.0	0.0	0.0
56.140	250.0	325.0	325.0

Device	Routing	Invert	Outlet Devices
#1	Primary	54.760 m	Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800
#2	Secondary	56.790 m	***Overflow Check
			Head (meters) 0.000 0.010
			Disch. (m ³ /s) 0.00000 10.00000

Primary OutFlow Max=0.0957 m³/s @ 0.38 hrs HW=55.237 m (Free Discharge)
 ↳1=Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800 (Custom Controls 0.0957 m³/s)

Secondary OutFlow Max=0.0000 m³/s @ 0.00 hrs HW=54.840 m (Free Discharge)
 ↳2=***Overflow Check (Controls 0.0000 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC


Ottawa 5-Year Duration=18 min, Inten=75.0 mm/hr

Printed 2022-09-02

Page 14

Pond 50P: Cistern

Hydrograph




Summary for Link 51L: Site Release

Inflow Area = 12,164.0 m², Inflow Depth = 17 mm for 5-Year event
Inflow = 0.0978 m³/s @ 0.33 hrs, Volume= 212.0 m³
Primary = 0.0978 m³/s @ 0.33 hrs, Volume= 212.0 m³, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs

Link 51L: Site Release

Hydrograph




APPENDIX

G-2 *100-YEAR ANALYSIS (PEAK DISCHARGE)*

Area Listing (selected nodes)

Area (sq-meters)	C	Description (subcatchment-numbers)
3,790.0	0.89	S03 (9S)
720.0	0.93	S04 (9S)
250.0	0.76	S05 (9S)
5,200.0	1.00	S06 (9S)
690.0	1.00	S07 (9S)
105.0	1.00	S08 (14S)
99.0	0.72	S09 (14S)
500.0	1.00	Tower A (10S, 11S)
810.0	1.00	Tower B1 (10S, 12S)
12,164.0	0.95	TOTAL AREA



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 3

Time span=0.00-4.00 hrs, dt=0.01 hrs, 401 points

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment 9S: Controlled to CisternRunoff Area=10,650.0 m² Runoff Depth=28 mm
Tc=10.0 min C=0.95 Runoff=0.4930 m³/s 301.0 m³**Subcatchment 10S: Towers to Cistern**Runoff Area=325.0 m² Runoff Depth=30 mm
Tc=10.0 min C=1.00 Runoff=0.0158 m³/s 9.7 m³**Subcatchment 11S: Tower A to Rooftop**Runoff Area=375.0 m² Runoff Depth=30 mm
Tc=10.0 min C=1.00 Runoff=0.0183 m³/s 11.2 m³**Subcatchment 12S: Tower B1 to Rooftop**Runoff Area=610.0 m² Runoff Depth=30 mm
Tc=10.0 min C=1.00 Runoff=0.0297 m³/s 18.1 m³**Subcatchment 14S: Uncontrolled**Runoff Area=204.0 m² Runoff Depth=26 mm
Tc=10.0 min C=0.86 Runoff=0.0085 m³/s 5.2 m³**Pond 16P: Tower A Rooftop Storage**Peak Elev=100.089 m Storage=9.8 m³ Inflow=0.0183 m³/s 11.2 m³
Outflow=0.0012 m³/s 11.2 m³**Pond 17P: Tower B1 Rooftop Storage**Peak Elev=100.121 m Storage=16.0 m³ Inflow=0.0297 m³/s 18.1 m³
Outflow=0.0019 m³/s 18.2 m³**Pond 25P: Cistern**Peak Elev=55.766 m Storage=231.6 m³ Inflow=0.5120 m³/s 340.0 m³
Primary=0.0976 m³/s 340.0 m³ Secondary=0.0000 m³/s 0.0 m³ Outflow=0.0976 m³/s 340.0 m³**Link 19L: Site Release**Inflow=0.1060 m³/s 345.2 m³
Primary=0.1060 m³/s 345.2 m³**Total Runoff Area = 12,164.0 m² Runoff Volume = 345.2 m³ Average Runoff Depth = 28 mm****112MontrealRd_100 year**

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr


Printed 2022-09-02

Page 4

Summary for Subcatchment 9S: Controlled to CisternRunoff = 0.4930 m³/s @ 0.17 hrs, Volume= 301.0 m³, Depth= 28 mmRunoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Area (m ²)	C	Description
3,790.0	0.89	S03
5,200.0	1.00	S06
720.0	0.93	S04
250.0	0.76	S05
690.0	1.00	S07
10,650.0	0.95	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m ³ /s)	Description
10.0					Direct Entry,

Subcatchment 9S: Controlled to Cistern

112MontrealRd_100 year

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 5

Summary for Subcatchment 10S: Towers to Cistern

Runoff = 0.0158 m³/s @ 0.17 hrs, Volume= 9.7 m³, Depth= 30 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Area (m²)	C	Description
125.0	1.00	Tower A
200.0	1.00	Tower B1
325.0	1.00	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 10S: Towers to Cistern

Hydrograph

**112MontrealRd_100 year**

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 6

Summary for Subcatchment 11S: Tower A to Rooftop

Runoff = 0.0183 m³/s @ 0.17 hrs, Volume= 11.2 m³, Depth= 30 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Area (m²)	C	Description
375.0	1.00	Tower A

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 11S: Tower A to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 7

Summary for Subcatchment 12S: Tower B1 to Rooftop

Runoff = 0.0297 m³/s @ 0.17 hrs, Volume= 18.1 m³, Depth= 30 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Area (m²)	C	Description
610.0	1.00	Tower B1

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 12S: Tower B1 to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 8

Summary for Subcatchment 14S: Uncontrolled

Runoff = 0.0085 m³/s @ 0.17 hrs, Volume= 5.2 m³, Depth= 26 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Area (m²)	C	Description
99.0	0.72	S09
105.0	1.00	S08
204.0	0.86	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 14S: Uncontrolled

Hydrograph



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 9

Summary for Pond 16P: Tower A Rooftop Storage

Inflow Area = 375.0 m², Inflow Depth = 30 mm for 100-Year event
 Inflow = 0.0183 m³/s @ 0.17 hrs, Volume= 11.2 m³
 Outflow = 0.0012 m³/s @ 0.07 hrs, Volume= 11.2 m³, Atten= 93%, Lag= 0.0 min
 Primary = 0.0012 m³/s @ 0.07 hrs, Volume= 11.2 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.089 m @ 0.32 hrs Surf.Area= 221.8 m² Storage= 9.8 m³

Plug-Flow detention time= 67.0 min calculated for 11.1 m³ (100% of inflow)
 Center-of-Mass det. time= 67.1 min (77.1 - 10.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	28.1 m ³	Custom Stage Data (Prismatic) Listed below (Recalc) x 4

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
100.000	0.0	0.0	0.0
100.150	93.7	7.0	7.0

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 4.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0012 m³/s @ 0.07 hrs HW=100.026 m (Free Discharge)

↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0012 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 10

Pond 16P: Tower A Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 11

Summary for Pond 17P: Tower B1 Rooftop Storage

Inflow Area = 610.0 m², Inflow Depth = 30 mm for 100-Year event
 Inflow = 0.0297 m³/s @ 0.17 hrs, Volume= 18.1 m³
 Outflow = 0.0019 m³/s @ 0.03 hrs, Volume= 18.2 m³, Atten= 94%, Lag= 0.0 min
 Primary = 0.0019 m³/s @ 0.03 hrs, Volume= 18.2 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.121 m @ 0.32 hrs Surf.Area= 397.0 m² Storage= 16.0 m³

Plug-Flow detention time= 71.9 min calculated for 18.1 m³ (100% of inflow)
 Center-of-Mass det. time= 72.1 min (82.1 - 10.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	30.5 m ³	Custom Stage Data (Pyramidal) Listed below (Recalc) x 6

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)	Wet.Area (sq-meters)
100.000	0.0	0.0	0.0	0.0
100.150	101.6	5.1	5.1	101.6

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 6.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0019 m³/s @ 0.03 hrs HW=100.027 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0019 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 12

Pond 17P: Tower B1 Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 13

Summary for Pond 25P: Cistern

[44] Hint: Outlet device #1 is below defined storage

Inflow Area = 11,960.0 m², Inflow Depth = 28 mm for 100-Year event
 Inflow = 0.5120 m³/s @ 0.17 hrs, Volume= 340.0 m³
 Outflow = 0.0976 m³/s @ 0.57 hrs, Volume= 340.0 m³, Atten= 81%, Lag= 24.1 min
 Primary = 0.0976 m³/s @ 0.57 hrs, Volume= 340.0 m³
 Secondary = 0.0000 m³/s @ 0.00 hrs, Volume= 0.0 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 55.766 m @ 0.30 hrs Surf.Area= 250.0 m² Storage= 231.6 m³

Plug-Flow detention time= 22.2 min calculated for 340.0 m³ (100% of inflow)
 Center-of-Mass det. time= 22.2 min (38.3 - 16.1)

Volume	Invert	Avail.Storage	Storage Description
#1	54.840 m	325.0 m ³	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
54.840	250.0	0.0	0.0
56.140	250.0	325.0	325.0

Device	Routing	Invert	Outlet Devices
#1	Primary	54.760 m	Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800
#2	Secondary	56.790 m	***Overflow Check
			Head (meters) 0.000 0.010
			Disch. (m ³ /s) 0.00000 10.00000

Primary OutFlow Max=0.0976 m³/s @ 0.57 hrs HW=55.430 m (Free Discharge)
 ↳1=Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800 (Custom Controls 0.0976 m³/s)

Secondary OutFlow Max=0.0000 m³/s @ 0.00 hrs HW=54.840 m (Free Discharge)
 ↳2=***Overflow Check (Controls 0.0000 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC


Ottawa 100-Year Duration=10 min, Inten=178.6 mm/hr

Printed 2022-09-02

Page 14

Pond 25P: Cistern

Hydrograph




Summary for Link 19L: Site Release

Inflow Area = 12,164.0 m², Inflow Depth = 28 mm for 100-Year event
Inflow = 0.1060 m³/s @ 0.17 hrs, Volume= 345.2 m³
Primary = 0.1060 m³/s @ 0.17 hrs, Volume= 345.2 m³, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs

Link 19L: Site Release


Hydrograph



G-3 *100-YEAR ANALYSIS
(PEAK CISTERN
STORAGE)*

Area Listing (selected nodes)

Area (sq-meters)	C	Description (subcatchment-numbers)
3,790.0	0.89	S03 (9S)
720.0	0.93	S04 (9S)
250.0	0.76	S05 (9S)
5,200.0	1.00	S06 (9S)
690.0	1.00	S07 (9S)
105.0	1.00	S08 (14S)
99.0	0.72	S09 (14S)
500.0	1.00	Tower A (10S, 11S)
810.0	1.00	Tower B1 (10S, 12S)
12,164.0	0.95	TOTAL AREA



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 3

Time span=0.00-4.00 hrs, dt=0.01 hrs, 401 points

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment 9S: Controlled to CisternRunoff Area=10,650.0 m² Runoff Depth=45 mm
Tc=10.0 min C=0.95 Runoff=0.2470 m³/s 474.1 m³**Subcatchment 10S: Towers to Cistern**Runoff Area=325.0 m² Runoff Depth=47 mm
Tc=10.0 min C=1.00 Runoff=0.0079 m³/s 15.2 m³**Subcatchment 11S: Tower A to Rooftop**Runoff Area=375.0 m² Runoff Depth=47 mm
Tc=10.0 min C=1.00 Runoff=0.0092 m³/s 17.6 m³**Subcatchment 12S: Tower B1 to Rooftop**Runoff Area=610.0 m² Runoff Depth=47 mm
Tc=10.0 min C=1.00 Runoff=0.0149 m³/s 28.6 m³**Subcatchment 14S: Uncontrolled**Runoff Area=204.0 m² Runoff Depth=40 mm
Tc=10.0 min C=0.86 Runoff=0.0043 m³/s 8.2 m³**Pond 16P: Tower A Rooftop Storage** Peak Elev=100.109 m Storage=14.7 m³ Inflow=0.0092 m³/s 17.6 m³
Outflow=0.0012 m³/s 17.4 m³**Pond 17P: Tower B1 Rooftop Storage** Peak Elev=100.139 m Storage=24.1 m³ Inflow=0.0149 m³/s 28.6 m³
Outflow=0.0019 m³/s 26.7 m³**Pond 25P: Cistern** Peak Elev=56.075 m Storage=308.6 m³ Inflow=0.2580 m³/s 533.4 m³
Primary=0.0976 m³/s 533.4 m³ Secondary=0.0000 m³/s 0.0 m³ Outflow=0.0976 m³/s 533.4 m³**Link 19L: Site Release** Inflow=0.1019 m³/s 541.6 m³
Primary=0.1019 m³/s 541.6 m³**Total Runoff Area = 12,164.0 m² Runoff Volume = 543.7 m³ Average Runoff Depth = 45 mm****112MontrealRd_100 year**

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 4


Summary for Subcatchment 9S: Controlled to CisternRunoff = 0.2470 m³/s @ 0.17 hrs, Volume= 474.1 m³, Depth= 45 mmRunoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Area (m ²)	C	Description
3,790.0	0.89	S03
5,200.0	1.00	S06
720.0	0.93	S04
250.0	0.76	S05
690.0	1.00	S07
10,650.0	0.95	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m ³ /s)	Description
10.0					Direct Entry,

Subcatchment 9S: Controlled to Cistern

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 5

Summary for Subcatchment 10S: Towers to Cistern

Runoff = 0.0079 m³/s @ 0.17 hrs, Volume= 15.2 m³, Depth= 47 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Area (m²)	C	Description
125.0	1.00	Tower A
200.0	1.00	Tower B1
325.0	1.00	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 10S: Towers to Cistern

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 6

Summary for Subcatchment 11S: Tower A to Rooftop

Runoff = 0.0092 m³/s @ 0.17 hrs, Volume= 17.6 m³, Depth= 47 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Area (m²)	C	Description
375.0	1.00	Tower A

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 11S: Tower A to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 7

Summary for Subcatchment 12S: Tower B1 to Rooftop

Runoff = 0.0149 m³/s @ 0.17 hrs, Volume= 28.6 m³, Depth= 47 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Area (m²)	C	Description
610.0	1.00	Tower B1

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 12S: Tower B1 to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 8

Summary for Subcatchment 14S: Uncontrolled

Runoff = 0.0043 m³/s @ 0.17 hrs, Volume= 8.2 m³, Depth= 40 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Area (m²)	C	Description
99.0	0.72	S09
105.0	1.00	S08
204.0	0.86	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 14S: Uncontrolled

Hydrograph



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 9

Summary for Pond 16P: Tower A Rooftop Storage

Inflow Area = 375.0 m², Inflow Depth = 47 mm for 100-Year event
 Inflow = 0.0092 m³/s @ 0.17 hrs, Volume= 17.6 m³
 Outflow = 0.0012 m³/s @ 0.11 hrs, Volume= 17.4 m³, Atten= 86%, Lag= 0.0 min
 Primary = 0.0012 m³/s @ 0.11 hrs, Volume= 17.4 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.109 m @ 0.68 hrs Surf.Area= 271.3 m² Storage= 14.7 m³

Plug-Flow detention time= 99.0 min calculated for 17.4 m³ (99% of inflow)
 Center-of-Mass det. time= 99.1 min (120.1 - 21.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	28.1 m ³	Custom Stage Data (Prismatic) Listed below (Recalc) x 4

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
100.000	0.0	0.0	0.0
100.150	93.7	7.0	7.0

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 4.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0012 m³/s @ 0.11 hrs HW=100.027 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0012 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 10

Pond 16P: Tower A Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 11

Summary for Pond 17P: Tower B1 Rooftop Storage

Inflow Area = 610.0 m², Inflow Depth = 47 mm for 100-Year event
 Inflow = 0.0149 m³/s @ 0.17 hrs, Volume= 28.6 m³
 Outflow = 0.0019 m³/s @ 0.05 hrs, Volume= 26.7 m³, Atten= 88%, Lag= 0.0 min
 Primary = 0.0019 m³/s @ 0.05 hrs, Volume= 26.7 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.139 m @ 0.68 hrs Surf.Area= 521.2 m² Storage= 24.1 m³

Plug-Flow detention time= 100.9 min calculated for 26.7 m³ (93% of inflow)
 Center-of-Mass det. time= 99.7 min (120.7 - 21.0)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	30.5 m ³	Custom Stage Data (Pyramidal) Listed below (Recalc) x 6

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)	Wet.Area (sq-meters)
100.000	0.0	0.0	0.0	0.0
100.150	101.6	5.1	5.1	101.6

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 6.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0019 m³/s @ 0.05 hrs HW=100.028 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0019 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=32 min, Inten=87.9 mm/hr

Printed 2022-09-02

Page 12

Pond 17P: Tower B1 Rooftop Storage



Summary for Pond 25P: Cistern

[44] Hint: Outlet device #1 is below defined storage

Inflow Area = 11,960.0 m², Inflow Depth > 45 mm for 100-Year event
 Inflow = 0.2580 m³/s @ 0.17 hrs, Volume= 533.4 m³
 Outflow = 0.0976 m³/s @ 1.16 hrs, Volume= 533.4 m³, Atten= 62%, Lag= 59.4 min
 Primary = 0.0976 m³/s @ 1.16 hrs, Volume= 533.4 m³
 Secondary = 0.0000 m³/s @ 0.00 hrs, Volume= 0.0 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 56.075 m @ 0.64 hrs Surf.Area= 250.0 m² Storage= 308.6 m³

Plug-Flow detention time= 29.2 min calculated for 533.4 m³ (100% of inflow)
 Center-of-Mass det. time= 29.2 min (58.4 - 29.2)

Volume	Invert	Avail.Storage	Storage Description
#1	54.840 m	325.0 m ³	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
54.840	250.0	0.0	0.0
56.140	250.0	325.0	325.0


Device	Routing	Invert	Outlet Devices
#1	Primary	54.760 m	Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800
#2	Secondary	56.790 m	***Overflow Check
			Head (meters) 0.000 0.010
			Disch. (m ³ /s) 0.00000 10.00000

Primary OutFlow Max=0.0976 m³/s @ 1.16 hrs HW=55.431 m (Free Discharge)
 ↳1=Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800 (Custom Controls 0.0976 m³/s)

Secondary OutFlow Max=0.0000 m³/s @ 0.00 hrs HW=54.840 m (Free Discharge)
 ↳2=***Overflow Check (Controls 0.0000 m³/s)

Pond 25P: Cistern

Hydrograph




Summary for Link 19L: Site Release

Inflow Area = 12,164.0 m², Inflow Depth > 45 mm for 100-Year event
Inflow = 0.1019 m³/s @ 0.31 hrs, Volume= 541.6 m³
Primary = 0.1019 m³/s @ 0.31 hrs, Volume= 541.6 m³, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs

Link 19L: Site Release


Hydrograph



G-4 *100-YEAR ANALYSIS
(PEAK ROOF
STORAGE)*

Area Listing (selected nodes)

Area (sq-meters)	C	Description (subcatchment-numbers)
3,790.0	0.89	S03 (9S)
720.0	0.93	S04 (9S)
250.0	0.76	S05 (9S)
5,200.0	1.00	S06 (9S)
690.0	1.00	S07 (9S)
105.0	1.00	S08 (14S)
99.0	0.72	S09 (14S)
500.0	1.00	Tower A (10S, 11S)
810.0	1.00	Tower B1 (10S, 12S)
12,164.0	0.95	TOTAL AREA



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 3

Time span=0.00-4.00 hrs, dt=0.01 hrs, 401 points

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment 9S: Controlled to CisternRunoff Area=10,650.0 m² Runoff Depth=57 mm
Tc=10.0 min C=0.95 Runoff=0.1253 m³/s 608.7 m³**Subcatchment 10S: Towers to Cistern**Runoff Area=325.0 m² Runoff Depth=60 mm
Tc=10.0 min C=1.00 Runoff=0.0040 m³/s 19.6 m³**Subcatchment 11S: Tower A to Rooftop**Runoff Area=375.0 m² Runoff Depth=60 mm
Tc=10.0 min C=1.00 Runoff=0.0046 m³/s 22.6 m³**Subcatchment 12S: Tower B1 to Rooftop**Runoff Area=610.0 m² Runoff Depth=60 mm
Tc=10.0 min C=1.00 Runoff=0.0076 m³/s 36.7 m³**Subcatchment 14S: Uncontrolled**Runoff Area=204.0 m² Runoff Depth=52 mm
Tc=10.0 min C=0.86 Runoff=0.0022 m³/s 10.6 m³**Pond 16P: Tower A Rooftop Storage** Peak Elev=100.114 m Storage=16.2 m³ Inflow=0.0046 m³/s 22.6 m³
Outflow=0.0012 m³/s 17.5 m³**Pond 17P: Tower B1 Rooftop Storage** Peak Elev=100.144 m Storage=26.9 m³ Inflow=0.0076 m³/s 36.7 m³
Outflow=0.0019 m³/s 26.6 m³**Pond 25P: Cistern** Peak Elev=55.656 m Storage=204.0 m³ Inflow=0.1324 m³/s 672.4 m³
Primary=0.0976 m³/s 672.3 m³ Secondary=0.0000 m³/s 0.0 m³ Outflow=0.0976 m³/s 672.3 m³**Link 19L: Site Release** Inflow=0.0998 m³/s 682.9 m³
Primary=0.0998 m³/s 682.9 m³**Total Runoff Area = 12,164.0 m² Runoff Volume = 698.1 m³ Average Runoff Depth = 57 mm****112MontrealRd_100 year**

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr


Printed 2022-09-02

Page 4

Summary for Subcatchment 9S: Controlled to CisternRunoff = 0.1253 m³/s @ 0.17 hrs, Volume= 608.7 m³, Depth= 57 mmRunoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Area (m ²)	C	Description
3,790.0	0.89	S03
5,200.0	1.00	S06
720.0	0.93	S04
250.0	0.76	S05
690.0	1.00	S07
10,650.0	0.95	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m ³ /s)	Description
10.0					Direct Entry,

Subcatchment 9S: Controlled to Cistern

112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 5

Summary for Subcatchment 10S: Towers to Cistern


Runoff = 0.0040 m³/s @ 0.17 hrs, Volume= 19.6 m³, Depth= 60 mm

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Area (m²)	C	Description
125.0	1.00	Tower A
200.0	1.00	Tower B1
325.0	1.00	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 10S: Towers to Cistern



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 6

Summary for Subcatchment 11S: Tower A to Rooftop


Runoff = 0.0046 m³/s @ 0.17 hrs, Volume= 22.6 m³, Depth= 60 mm

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Area (m²)	C	Description
375.0	1.00	Tower A

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 11S: Tower A to Rooftop



112MontrealRd_100 year

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 7

Summary for Subcatchment 12S: Tower B1 to Rooftop

Runoff = 0.0076 m³/s @ 0.17 hrs, Volume= 36.7 m³, Depth= 60 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Area (m²)	C	Description
610.0	1.00	Tower B1

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 12S: Tower B1 to Rooftop

Hydrograph



112MontrealRd_100 year

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Prepared by WSP Canada inc.

Printed 2022-09-02

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Page 8

Summary for Subcatchment 14S: Uncontrolled

Runoff = 0.0022 m³/s @ 0.17 hrs, Volume= 10.6 m³, Depth= 52 mm


Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Area (m²)	C	Description
99.0	0.72	S09
105.0	1.00	S08
204.0	0.86	Weighted Average

Tc (min)	Length (meters)	Slope (m/m)	Velocity (m/sec)	Capacity (m³/s)	Description
10.0					Direct Entry,

Subcatchment 14S: Uncontrolled

Hydrograph



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 9

Summary for Pond 16P: Tower A Rooftop Storage

Inflow Area = 375.0 m², Inflow Depth = 60 mm for 100-Year event
 Inflow = 0.0046 m³/s @ 0.17 hrs, Volume= 22.6 m³
 Outflow = 0.0012 m³/s @ 0.15 hrs, Volume= 17.5 m³, Atten= 73%, Lag= 0.0 min
 Primary = 0.0012 m³/s @ 0.15 hrs, Volume= 17.5 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.114 m @ 1.47 hrs Surf.Area= 284.7 m² Storage= 16.2 m³

Plug-Flow detention time= 85.7 min calculated for 17.5 m³ (78% of inflow)
 Center-of-Mass det. time= 76.9 min (122.4 - 45.5)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	28.1 m ³	Custom Stage Data (Prismatic) Listed below (Recalc) x 4

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
100.000	0.0	0.0	0.0
100.150	93.7	7.0	7.0

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 4.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0012 m³/s @ 0.15 hrs HW=100.025 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0012 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 10

Pond 16P: Tower A Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 11

Summary for Pond 17P: Tower B1 Rooftop Storage

Inflow Area = 610.0 m², Inflow Depth = 60 mm for 100-Year event
 Inflow = 0.0076 m³/s @ 0.17 hrs, Volume= 36.7 m³
 Outflow = 0.0019 m³/s @ 0.08 hrs, Volume= 26.6 m³, Atten= 75%, Lag= 0.0 min
 Primary = 0.0019 m³/s @ 0.08 hrs, Volume= 26.6 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 100.144 m @ 1.48 hrs Surf.Area= 560.7 m² Storage= 26.9 m³

Plug-Flow detention time= 86.8 min calculated for 26.6 m³ (72% of inflow)
 Center-of-Mass det. time= 75.6 min (121.1 - 45.5)

Volume	Invert	Avail.Storage	Storage Description
#1	100.000 m	30.5 m ³	Custom Stage Data (Pyramidal) Listed below (Recalc) x 6

Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)	Wet.Area (sq-meters)
100.000	0.0	0.0	0.0	0.0
100.150	101.6	5.1	5.1	101.6

Device	Routing	Invert	Outlet Devices
#1	Primary	100.000 m	WATTS Accutrol_5-Closed X 6.00 Head (meters) 0.000 0.025 0.051 0.076 0.102 0.127 0.152 Disch. (m ³ /s) 0.00000 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031 0.00031

Primary OutFlow Max=0.0019 m³/s @ 0.08 hrs HW=100.028 m (Free Discharge)
 ↳1=WATTS Accutrol_5-Closed (Custom Controls 0.0019 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.


HydroCAD@ 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 12

Pond 17P: Tower B1 Rooftop Storage



112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC

Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 13

Summary for Pond 25P: Cistern

[44] Hint: Outlet device #1 is below defined storage

Inflow Area = 11,960.0 m², Inflow Depth > 56 mm for 100-Year event
 Inflow = 0.1324 m³/s @ 0.17 hrs, Volume= 672.4 m³
 Outflow = 0.0976 m³/s @ 0.92 hrs, Volume= 672.3 m³, Atten= 26%, Lag= 45.1 min
 Primary = 0.0976 m³/s @ 0.92 hrs, Volume= 672.3 m³
 Secondary = 0.0000 m³/s @ 0.00 hrs, Volume= 0.0 m³

Routing by Stor-Ind method, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs
 Peak Elev= 55.656 m @ 1.40 hrs Surf.Area= 250.0 m² Storage= 204.0 m³

Plug-Flow detention time= 21.5 min calculated for 672.3 m³ (100% of inflow)
 Center-of-Mass det. time= 21.5 min (72.0 - 50.5)

Volume	Invert	Avail.Storage	Storage Description
#1	54.840 m	325.0 m ³	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (meters)	Surf.Area (sq-meters)	Inc.Store (cubic-meters)	Cum.Store (cubic-meters)
54.840	250.0	0.0	0.0
56.140	250.0	325.0	325.0

Device	Routing	Invert	Outlet Devices
#1	Primary	54.760 m	Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800
#2	Secondary	56.790 m	***Overflow Check
			Head (meters) 0.000 0.010
			Disch. (m ³ /s) 0.00000 10.00000

Primary OutFlow Max=0.0976 m³/s @ 0.92 hrs HW=55.428 m (Free Discharge)
 ↳1=Hydrovex Hydro-Break Optimum SHE-0379-9800-2000-9800 (Custom Controls 0.0976 m³/s)

Secondary OutFlow Max=0.0000 m³/s @ 0.00 hrs HW=54.840 m (Free Discharge)
 ↳2=***Overflow Check (Controls 0.0000 m³/s)

112MontrealRd_100 year

Prepared by WSP Canada inc.

HydroCAD® 10.00-22 s/n 10697 © 2018 HydroCAD Software Solutions LLC


Ottawa 100-Year Duration=81 min, Inten=44.6 mm/hr

Printed 2022-09-02

Page 14

Pond 25P: Cistern

Hydrograph




Summary for Link 19L: Site Release

Inflow Area = 12,164.0 m², Inflow Depth > 56 mm for 100-Year event
Inflow = 0.0998 m³/s @ 0.92 hrs, Volume= 682.9 m³
Primary = 0.0998 m³/s @ 0.92 hrs, Volume= 682.9 m³, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-4.00 hrs, dt= 0.01 hrs

Link 19L: Site Release

Hydrograph




APPENDIX

H

FLOOD PLAIN
MAPPING AND
ELEVATIONS

Rideau River at Cumming Island




Legend

-  OHN Watercourse
-  RVCA Sub-Watersheds
-  RVCA Catchments
-  Floodplain Cross-sections
-  Regulation Limit
-  100yr Floodline
- Reg Limit Dominant Hazard**
-  Floodplain
-  Geo-technical Hazard Limit
-  Meander Belt
-  Stable Slope
-  Top of Slope
-  Unstable Slope
-  Wetland
-  Township Municipal
-  Geographic Township
-  Conservation Authorities (East)
- Roads**
-  Freeway
-  Expressway / Highway
-  Arterial
-  Local
-  Ramp
-  Rapid Transit
-  Service
-  Waterbody
- Wetlands**
-  Evaluated-Provincial
-  Evaluated-Other
-  Not evaluated per OWES
- DATE 2014



1: 15,084.78

Map Projection: WGS_1984_Web_Mercator_Auxiliary_Sphere



Notes

Parcel data is owned by Teranet Enterprises Inc and its suppliers. All rights reserved. May not be reproduced without permission.

Data Received from RVCA September 2015

FPM_UNIQUE	PROFILE	Q_TOTAL_C	WS_ELEV_M	EG_ELEV_M
Rideau - Reach 1 - 2474	50 Year	626	56.44	56.52
Rideau - Reach 1 - 2474	5 Year	513	56.1	56.17
Rideau - Reach 1 - 2474	25 Year	598	56.36	56.44
Rideau - Reach 1 - 2474	100 Year	654	56.52	56.6
Rideau - Reach 1 - 2474	10 Year	552	56.22	56.29
Rideau - Reach 1 - 2490	50 Year	626	56.46	56.54
Rideau - Reach 1 - 2490	5 Year	513	56.12	56.18
Rideau - Reach 1 - 2490	25 Year	598	56.38	56.46
Rideau - Reach 1 - 2490	100 Year	654	56.54	56.63
Rideau - Reach 1 - 2490	10 Year	552	56.24	56.31
Rideau - Reach 1 - 2512	50 Year	626	56.47	56.55
Rideau - Reach 1 - 2512	5 Year	513	56.13	56.19
Rideau - Reach 1 - 2512	25 Year	598	56.39	56.47
Rideau - Reach 1 - 2512	100 Year	654	56.56	56.64
Rideau - Reach 1 - 2512	10 Year	552	56.25	56.32