IBI GROUP 400 – 333 Preston Street Ottawa ON K1S 5N4 Canada tel 613 225 1311 fax 613 225 9868 ibigroup.com

PROPOSED SELF STORAGE DEVELOPMENT HUNTINGTON PROPERTIES



60 DENZEL DOYLE COURT CITY OF OTTAWA

CONTRACT NO. 135470

Sheet List TableSheet NumberSheet TitleC-001GENERAL PLAN OF SERVICESC-010DETAILS AND NOTESC-011CROSS SECTIONS				
Sheet NumberSheet TitleC-001GENERAL PLAN OF SERVICESC-010DETAILS AND NOTESC-011CROSS SECTIONS	Sheet List Table			
C-001GENERAL PLAN OF SERVICESC-010DETAILS AND NOTESC-011CROSS SECTIONS	Sheet Number	Sheet Title		
C-010 DETAILS AND NOTES C-011 CROSS SECTIONS	C-001	GENERAL PLAN OF SERVICES		
C-011 CROSS SECTIONS	C-010	DETAILS AND NOTES		
	C-011	CROSS SECTIONS		
C-200 GRADING PLAN	C-200	GRADING PLAN		
C-500 STORM DRAINAGE AREA PLAN	C-500	STORM DRAINAGE AREA PLAN		
C-600 PONDING PLAN	C-600	PONDING PLAN		
C-900 SEDIMENT - EROSION PLAN	C-900	SEDIMENT - EROSION PLAN		

2021-12-09

REVIEW

CIT

SUED FOR

<u>S</u>

								7
	P							R
	-							D
					27 2			
					PAR			
	,	1				sewer		
	Sewer	Sewer		\backslash		atermair orm Sew anitary S		
		Saniter A Storm Mate				omm St omm St		
		150mur 315mur 50r				375 10		
				\wedge				630 Eagleson I 1 Storey Retireme
	PART 82 –	7				e t p		Asphalt
PART 81			XXXX					
		PART 88			A Service Serv			EBMH130 ■ T/G 102.15
					200rtied 1000			
C H J					* 			BUILDING
	Contraction of the second	2004					//////////////////////////////////////	DREY PROPOSED BUILDING AF
200mm	Sanitary Sev	ier y						
	Service Se	wer Ma	a Sta					
300r	mm Storm	372	SOO SANITARY	RMAD	\sim			
300r	mm Storm -	33	300 SANITARY S			the second secon		
300r	mm Storin S	33	Motermony	RITATION AND AND AND AND AND AND AND AND AND AN			CBMH120	1 ST
300r	mm Storin S	33	150mm Material 150 25 25 25 25 25 25 25 25 25 25 25 25 25	RUTAN MILLA			TG TOT.TS	
300r	mm Storin S	37	150mm Mariemon, 25 25 25	Stand Scott Springer	Свт	2500 SAWIARY SEW. MINU	CBMH120 TIG T07:75	58 ^{.70} m [.] 825.
300r	Imm Storin S	33	12000000000000000000000000000000000000	Start South Start South		250e SANUISEX SEWER	CBMH120 TIG 107.75 TO 107.75	Starton - 825 mine
300r	mm Storm -		SQS SANJIARY S	Start 25 Miles		250a SAWIARY SEWER	CBMH120 TG T07.75	58.70m - 825.70mc
300r	mm Storin -	S	TM STRU	Stand Stand		T	CBMH120 TIG T07:75 V V V V V V V V V V V V V V V V V V V	58.70m - 825.70m 58.70m - 825.70m 5000 - 151 - 1
300r	RIM ELEV	S INVERT IN	TM STRU	Brinn Storm Spont Cal	TABLE TABLE	T DESCRIPTION	CBMH120 TIG T07:75 V V V V V V V V V V V V V V V V V V V	SEMER
300r 9 99 11 0 19 11 0 19	RIM ELEV 102.05 101.60	S INVERT IN	TM STRU	Brinn Storm Spont Call Brinn Storm Spont Call Spont Spont Call Spont Call Spont Call Spo	TABLE TABLE	T DESCRIPTION OPSD-705.010 OPSD-705.010	CBMH120 TIG T07:75 V V V V V V V V V V V V V V V V V V V	SEMER 3750 STOCO
300r 0111-01011 01011 01011 01001 0100 0100 0100 0100 0100 0100 010	RIM ELEV 102.05 101.60 101.80	S INVERT IN	TM STRU	JCTURE INVERT OU S99.650 NW99.223	TABLE TABLE	T DESCRIPTION OPSD-705.010 1500mmØ OPSD-701.010	MHE 3000 WATE	SEMER SEMER STORM SEMER
300r 1011 - 0-0-11 0-0-0-0-11 0-0-0-0-0-0-0 0-0-0-0-0-0-0-0-0 0-0-0-0-	RIM ELEV 102.05 101.60 102.05 102.00	S99.148 E99.064	TM STRU	JCTURE INVERT OU S99.650 NV99.223 W99.044	TABLE TABLE	T DESCRIPTION OPSD-705.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010	MHE 3000 WATE	SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER SEMER
3000 0111 010 0111 010	RIM ELEV 102.05 101.60 102.05 102.00 102.00 101.90	S99.148 E99.064 E98.998 N98.968	TM STRU	JCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938	TABLE TABLE	T DESCRIPTION OPSD-705.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1800mmØ OPSD-701.010	Mile 3000 WATE	SEMER 3750 STORM SEMER DYLE COURT MONITORING VALV
3000 3000 000 000 000 000 000 00	RIM ELEV 102.05 101.60 102.05 102.00 101.90	S99.148 E99.064 E98.998 N98.968 NW98.902	TM STRU	JCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938 E98.872	TABLE TABLE	T DESCRIPTION OPSD-705.010 OPSD-701.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1800mmØ OPSD-701.010 1800mmØ OPSD-701.010	MH6 3008 WATE DENZIL DO	States States
	RIM ELEV 102.05 101.60 101.80 102.05 102.00 101.90 101.90 101.90 102.15	S99.148 E99.064 E98.998 N98.968 NW98.902	TM STRU	UCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938 E98.872 N99.374	TABLE TABLE	T DESCRIPTION OPSD-705.010 OPSD-705.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1800mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010	MIS 3000 WATE	State St
3000 3000 0110 0100 0110 0100 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000	RIM ELEV 102.05 101.60 101.80 102.05 102.00 101.90 101.90 101.90 102.15 102.15	S99.148 E99.064 E98.998 N98.968 NW98.902 S99.394 N99.330 S90.220	TM STRU	UCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938 E98.872 N99.374 SW99.270	TABLE TABLE	T DESCRIPTION OPSD-705.010 OPSD-705.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1500mmØ OPSD-701.010	MIS 3000 MATE	A A A A A A A A A A A A A A A A A A A
3000 3000	RIM ELEV 102.05 101.60 101.80 102.05 102.00 101.90 101.90 102.15 102.15 102.15 102.15 102.15	S99.148 E99.064 E98.998 N98.968 NW98.902 S99.330 S99.330 S99.330 S99.330 S99.330	TM STRU	Contraction of the server of t	TABLE TABLE	T DESCRIPTION OPSD-705.010 OPSD-705.010 OPSD-705.010 OPSD-701.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010	TIC TOTIS	A A A A A A A A A A A A A A A A A A A
300r 300r 300r 2011 2011 2011 2011 2011 2011 2011 2	RIM ELEV 102.05 101.60 101.80 102.05 102.00 101.90 101.90 102.15 102.15 102.15 102.15 102.15 102.15	Several and a se	TM STRU	Anna Server Anna S		T DESCRIPTION 0PSD-705.010 0PSD-705.010 0PSD-705.010 0PSD-701.010 1500mmØ OPSD-701.010 1800mmØ OPSD-701.010 1500mmØ OPSD-701.010 1500mmØ OPSD-701.010	TIC TOTIS TO	A CONTORING VALUE A CONTORING V
3000 3000	RIM ELEV 102.05 101.60 101.80 102.05 102.05 102.00 101.90 102.15 102.15 102.15 102.15 102.15 101.85 101.75 101.80 102.15	Signal 107 Signal 207 Signal 207	TM STRU	Anne Score Server Anne Score Server Server JCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938 E98.872 N99.438 N99.374 SW99.270 S99.010 S99.202 S99.107 S99.382	TABLE TABLE	Image: Second State Sta	CONNECT TO E WITH TEE CO	AND DEVEKTING 300Ø WATERMA ONNECTION (CITY FORCE DEVEKTING 300Ø WATERMA ONNECTION (CITY FORCE DATA BACKFI
3000 3000	RIM ELEV 102.05 101.60 101.80 102.05 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.85 101.80 102.15 101.80	S99.148 E99.064 E98.998 N98.968 NW98.902 S99.394 N99.330 S99.330 S99.330 N99.040 N99.040	TM STRU	Anne Storm Seguration of the s		Image: Stress	PENZIL DO	AMARENSED CURB ANI SIDEWALK SIT ENTRANCE AS PER SC.7. BELL PEDESTAL TO BE RELOCATED EXISTING 300Ø WATERMA ONNECTION (CITY FORCE ON ECTION OBV= ±98.0
300r 300r 300r 300r 300r 300r 300r 300r	RIM ELEV 102.05 101.60 101.80 102.05 102.00 101.90 101.90 102.15 102.15 102.15 102.15 102.15 102.15 101.80 101.75 101.80 102.15	S99.148 E99.064 E98.998 NW98.902 S99.300 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330 S99.330	TM STRU	Anne Server Contraction of the server of the		T DESCRIPTION 0 OPSD-705.010 0 OPSD-705.010 1 S00mmØ OPSD-701.010 1 1500mmØ OPSD-701.010	PENZIL DO	AND REINSTATE AND RE
300r 300r 300r 300r 300r 300r 300r 300r	RIM ELEV 102.05 101.60 101.80 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.85 101.80 102.07 101.97	S99.148 E99.064 E98.998 N98.968 NW98.902 S99.394 N99.330 S99.330 S99.330 N99.040 N99.040 S99.152 SE99.201 W98.713 E98.728	TM STRU	Anne Score Server Anne Score Server Server JCTURE INVERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.374 SW99.270 S99.010 S99.010 S99.202 S99.107 S99.382 W98.768 N99.171 SW98.653		T DESCRIPTION 0 OPSD-705.010 0 OPSD-705.010 0 OPSD-705.010 1 S00mmø OPSD-701.010 1 1500mmø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTO	AND REINSTATED AS PER SC.7. BELL PEDESTAL TO BELL PEDESTAL AND REINSTACONNECTION OBV= ±98.00
300r 300r 300r 300r 300r 300r 300r 300r	RIM ELEV 102.05 101.60 101.80 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.80 102.15 101.80 102.15 101.80 102.17 102.17	Sign 148 Sign 148 Sig	TM STRU	Jorden Jorden JCTURE INVERT OU S99.650 N99.200 NW99.223 W99.088 W99.044 SE98.938 E98.872 N99.438 N99.374 SW99.270 S99.010 S99.202 S99.107 S99.382 W98.768 N99.171 SW98.768 N99.171 SW99.217 SW99.217		T DESCRIPTION 0 OPSD-705.010 0 OPSD-705.010 1 OPSD-705.010 1 Stommø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTO	AND REINSTATED AS PER CONNECTION (CITY FORCE DESISTING 300Ø WATERMA ONNECTION OBV= ±98.0
3000 3000	RIM ELEV 102.05 101.60 102.05 101.80 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.85 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15	Signal Signal INVERT IN INVERT IN S99.148 E99.064 E99.064 E98.998 N98.968 NW98.902 S99.394 N99.330 N99.330 S99.394 N99.330 S99.330 S99.152 SE99.201 W98.713 E98.728 NE99.247 E99.137 E99.174 E99.174	TM STRU	JUNERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.374 SW99.270 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.107 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.077 W99.144		T DESCRIPTION 0PSD-705.010 0PSD-705.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1800mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTOR TEE O	A Connection obver 198.00 Connection obver 19
3000 3000	RIM ELEV 102.05 101.60 101.80 102.05 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.85 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.11 102.11 102.11	 NVERT IN S99.148 E99.064 S99.148 E99.064 S99.304 NW98.902 S99.394 N99.330 S99.394 N99.330 S99.394 S99.394 S99.394 S99.394 S99.301 S99.137 S99.152 SE99.201 W98.713 E98.728 NE99.247 E99.137 N99.097 E99.174 		JUNERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.270 S99.010 S99.202 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.077 W99.144		T DESCRIPTION 0PSD-705.010 0PSD-705.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1800mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTOR TEE	A Connection (city force) A Connection (city fo
3000 3000	RIM ELEV 102.05 101.60 101.80 102.05 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 101.90 102.15 102.15 101.80 102.15 101.80 102.15 101.97 102.11 102.11 102.16	 Signal and a second seco		JUTURE JUTURE INVERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.374 SW99.202 S99.010 S99.202 S99.107 S99.382 W98.768 N99.171 SW98.768 N99.171 SW99.217 S99.077 W99.144		T DESCRIPTION OPSD-705.010 OPSD-705.010 IS00mmø OPSD-701.010 1800mmø OPSD-701.010 1500mmø OPSD-701.010 1800mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTO	AND REINSTATED AS PER CONNECTION (CITY FORCED DEPRESSED CURB ANI SIDEWALK SIT ENTRANCE AS PER SC. 7. BELL PEDESTAT TO BE RELOCATED EXISTING 300Ø WATERMA ONNECTION (CITY FORCED AND REINSTATED CONNECTION OBV= ±98.00 ROAD CUT TO E REINSTATED AS PE CITY DETAIL R-1 (±96m)
3000 3000 <t< td=""><td>RIM ELEV 102.05 101.60 101.80 102.05 101.90 102.15 102.15 102.15 101.80 102.15 102.15 101.80 101.75 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.17 102.18 MELEV.</td><td></td><td></td><td>JUNERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.200 SW99.270 S99.650 N99.374 SW99.270 S99.107 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.010 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.010 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.077 W99.144</td><td></td><td>T DESCRIPTION 0PSD-705.010 OPSD-705.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010</td><td>CONNECT TO E WITH TEE CO CONTRACTO</td><td>A Constant of the second secon</td></t<>	RIM ELEV 102.05 101.60 101.80 102.05 101.90 102.15 102.15 102.15 101.80 102.15 102.15 101.80 101.75 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.17 102.18 MELEV.			JUNERT OU S99.650 N99.200 NW99.223 W99.044 SE98.938 E98.872 N99.438 N99.200 SW99.270 S99.650 N99.374 SW99.270 S99.107 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.010 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.010 S99.107 S99.382 W98.768 N99.171 SW99.217 S99.077 W99.144		T DESCRIPTION 0PSD-705.010 OPSD-705.010 1500mmø OPSD-701.010 1500mmø OPSD-701.010	CONNECT TO E WITH TEE CO CONTRACTO	A Constant of the second secon
3000 3000 <t< td=""><td>RIM ELEV 102.05 101.60 101.80 102.05 101.90 102.05 102.15 102.15 102.15 101.80 101.80 101.90 101.90 101.91 102.15 102.15 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.11 102.12 102.13 102.14</td><td>× × × × × × × × × × × × × × × × × × ×</td><td></td><td>Jorden Score JCTURE INVERT OU S99.650 N99.200 NV99.223 W99.088 W99.088 W99.044 SE98.938 E98.872 N99.374 SW99.270 S99.651 N99.382 W99.088 W99.044 SE98.938 SW99.270 S99.010 S99.010 S99.010 S99.010 S99.010 S99.202 S99.010 S99.010 S99.202 S99.010 S99.202 S99.010 S99.202 S99.107 S99.202 S99.107 S99.382 W98.768 N99.171 SW98.761 VERT OUT S99.925 SW99.771</td><td></td><td>Image: statute statute</td><td>PENHUT20 TOTTS TOT</td><td>A Consection of the sector of</td></t<>	RIM ELEV 102.05 101.60 101.80 102.05 101.90 102.05 102.15 102.15 102.15 101.80 101.80 101.90 101.90 101.91 102.15 102.15 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.11 102.12 102.13 102.14	× × × × × × × × × × × × × × × × × × ×		Jorden Score JCTURE INVERT OU S99.650 N99.200 NV99.223 W99.088 W99.088 W99.044 SE98.938 E98.872 N99.374 SW99.270 S99.651 N99.382 W99.088 W99.044 SE98.938 SW99.270 S99.010 S99.010 S99.010 S99.010 S99.010 S99.202 S99.010 S99.010 S99.202 S99.010 S99.202 S99.010 S99.202 S99.107 S99.202 S99.107 S99.382 W98.768 N99.171 SW98.761 VERT OUT S99.925 SW99.771		Image: statute	PENHUT20 TOTTS TOT	A Consection of the sector of
3000 3000 <t< td=""><td>RIM ELEV 102.05 101.60 101.80 102.05 102.05 102.05 101.80 102.15 102.15 102.15 101.80 101.80 102.15 102.15 101.80 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.11 102.20 102.21 102.20 102.21 101.86</td><td>× × × × × × × × × × × × × × × × × × ×</td><td></td><td>Jorden Control JCTURE INVERT OU S99.650 N99.200 NV99.223 W99.088 W99.088 W99.088 W99.088 W99.088 W99.044 SE98.938 S99.650 N99.200 NV99.217 S99.010 S99.202 S99.0107 S99.202 S99.0107 S99.202 S99.107 S99.202 S99.0107 S99.202 S99.0107 S99.217 S99.0217 S99.925 SW99.771 SW99.383</td><td></td><td>Image: statute set in the set in th</td><td>CONNECT TO E WITH TEE CO CONTRACTO TEE</td><td>A Connection obve ±98.00 Connection obve ±98.00 Conn</td></t<>	RIM ELEV 102.05 101.60 101.80 102.05 102.05 102.05 101.80 102.15 102.15 102.15 101.80 101.80 102.15 102.15 101.80 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.15 101.80 102.11 102.20 102.21 102.20 102.21 101.86	× × × × × × × × × × × × × × × × × × ×		Jorden Control JCTURE INVERT OU S99.650 N99.200 NV99.223 W99.088 W99.088 W99.088 W99.088 W99.088 W99.044 SE98.938 S99.650 N99.200 NV99.217 S99.010 S99.202 S99.0107 S99.202 S99.0107 S99.202 S99.107 S99.202 S99.0107 S99.202 S99.0107 S99.217 S99.0217 S99.925 SW99.771 SW99.383		Image: statute set in the set in th	CONNECT TO E WITH TEE CO CONTRACTO TEE	A Connection obve ±98.00 Connection obve ±98.00 Conn



GENERAL LEGEND

())))(m)))	
0.01	
<u>UU</u> N.	
-	

LIMIT OF CONSTRUCTION PHASING LINE BARRIER CURB MOUNTABLE CURB DEPRESSED BARRIER CURB CONCRETE SIDEWALK - TACTILE WALKING SURFACE INDICATOR ASPHALT SIDEWALK / PATHWAY BUS STOP CONCRETE / ASPHALT

SERVICING LEGEND

O MH118A	SANITARY MANHOLE
200mmØ SAN	SANITARY SEWER
МН109 О МН118	STORM MANHOLE
825mmØ STM	STORM SEWER - LESS THAN 900Ø
900mmØ STM	STORM SEWER - 900Ø AND GREATER
200Ø WATERMAIN	WATERMAIN
CB100	STREET CATCHBASIN C/W TOP OF GRATE
CICB101	CURB INLET CATCHBASIN C/W GUTTER GRADE
DCB100	DOUBLE CATCHBASIN C/W TOP OF GRATE
DCICB101	DOUBLE CURB INLET CATCHBASIN C/W GUTTER GRADE
G/G 104.25	DITCH INLET MANHOLE C/W TOP OF GRATE
CBMH101	CATCHBASIN MANHOLE C/W TOP OF GRATE
■ RYCB T/G 104.35	REAR YARD CATCHBASIN IN ROAD CONNECTING STRUCTURE C/W SOLID GRATE
	REAR YARD "TEE" CATCHBASIN (300Ø) C/W TOP OF GRATE AND INVERT OUT
G ^{T/G} 104.50 NV 103.50	REAR YARD "END" CATCHBASIN (300Ø) C/W TOP OF GRATE AND INVERT OUT
T/G 104.35 INV 103.35	REAR YARD "CUSTOM ANGLED " CATCHBASIN (450Ø) C/W TOP OF GRATE AND INVERT OUT
T/G 104.35 NV 103.35	REAR YARD "THREE WAY" CATCHBASIN (450Ø) C/W TOP OF GRATE AND INVERT OUT
C 005	PERFORATED REAR YARD SUBDRAIN
300mmø CSP	CSP CULVERT C/W DIAMETER
⊗ ^{V&VB}	VALVE AND VALVE BOX
⊗ ^{V&VC}	VALVE AND VALVE CHAMBER
-+	PARK VALVE CHAMBER C/W SERVICE POST
+HYD 104.35	FIRE HYDRANT C/W BOTTOM OF FLANGE ELEVATION
200Ø WM RED 150Ø WM	WATERMAIN REDUCER
2 VBENDS	VERTICAL BEND LOCATION
\$	SIAMESE CONNECTION (IF REQUIRED)
M	METER (IF REQUIRED)
Ŕ	REMOTE METER (IF REQUIRED)
à	WATERMAIN IDENTIFICATION (IF REQUIRED)
	PIPE CROSSING IDENTIFICATION (IF REQUIRED)
\triangleleft	SINGLE SERVICE LOCATION
\triangleleft	DOUBLE SERVICE LOCATION
BH 12 102.00	INFERRED REFUSAL (SEE GEOTECHNICAL REPORT)
HGL	100 YEAR STORM HYDRAULIC GRADE LINE AT MANHOLE
USF 101.79	UNDERSIDE OF FOOTING ELEVATION
	CLAY SEAL IN SEWER / WATERMAIN TRENCH

ШСВ	- CATCH BASIN
О мн	- MANHOLE
О вмн	- BELL MANHOLE
O WMH	- WATER MANHOLE
🔘 нмн	- HYDRO MANHOLE
🔿 тмн	- TRAFFIC MANHOLE
🗌 ТНН	- TRAFFIC HANDHOLE
O FMH	- FIBRE OPTIC MANHOLE
LS	- LAMP STANDARD
⊗ UP	- UTILITY POLE
► WV	- WATER VALVE
ໍ ¢ FH	- FIRE HYDRANT
🕑 BH	- BOREHOLE
BP	- BELL PEDESTAL
₩ TL	- TRAFFIC LIGHT
🖾 TCB	- TRAFFIC CONTROL BOX
BB	- BELL BOX
-	- GUY WIRE AND ANCHOR
•	- BOLLARD
M	- SIGN
W C	- CONIFEROUS TREE
U W	- DECIDUOUS TREE
V v	
	- OVERHEAD UTILITY WIRES
IB	
G	
— UC —	
— F —	

Pipe Interference Table			
Crossing No.	PIPE 1	PIPE 2	Clearance
1	STM Bottom 99.027	WTR Top 99.649	0.622
2	STM Bottom 98.889	WTR Top 99.562	0.674
3	STM Bottom 98.818	WTR Top 99.621	0.804
4	STM Bottom 98.728	WTR Top 98.229	0.500
5	SAN Bottom 98.423	WTR Top 97.923	0.500
6	STM Bottom 99.141	WTR Top 99.867	0.726
7	STM Bottom 99.076	WTR Top 99.694	0.618
8	STM Bottom 98.990	WTR Top 99.519	0.528
9	SAN Bottom 99.519	STM Top 99.118	0.401
10	SAN Bottom 99.304	STM Top 99.021	0.283

WATERMAIN SCHEDULE

	Station	Description	Finished Grade	Top of Waterain	As Built Waterain
Δ	0+000.00	TEE	101.90	98.06	
	0+000.00	200mm \/P	102.05	90.00	
	0+008.75		102.05	99.60	
	0+013.43		101.99	99.59	
	0+015.51		101.92	99.52	
В	0+018.71	TEE	101.92	99.52	
	0+029.12	22 BEND	102.00	99.60	
С	0+032.44	TEE	102.00	99.60	
D	0+046.58	TEE	102.18	99.78	
E	0+063.28	TEE	102.28	99.88	
F	0+064.48	TEE	102.29	99.89	
G	0+067.62	CAP	102.29	99.89	
B	0+000.00	TEE	101 92	99.52	
	0+002.19		101.97	99.57	
	0+007.55		107.05	00.65	
	0+007.33		102.03	99.00	
	0+015.10		102.04	99.64	
	0+037.08	11 BEND	101.96	99.56	
	0+038.33	22 BEND	101.99	99.59	
	0+050.00		102.16	99.76	
	0+065.00		102.15	99.75	
	0+075.78	STM CROSSING	101.96	99.56	
	0+081.70	TEE	102.12	99.72	
	0+085.00	STM CROSSING	102.02	99.62	
	0+087.13	22BEND	101.96	99.56	
	0+098.73	200mm VB	101.16	98.76	
	0+110.00	STM CROSSING	100.65	98.22	
	0+111.00		100.66	97.83	
	0+112 72		100.00	08.65	
5	0+113.72		100.07	90.00	
	0.000.00		400.00	00.00	
F	0+000.00		102.29	99.89	
	0+001.95	VB	102.24	99.84	
	0+002.60	STM CROSSING	102.27	99.87	
	0+003.63	REDUCER	102.31	99.91	
BLDGB	0+004.55	BLDGB	102.35	99.95	
E	0+000.00	TEE	101.28	98.88	
	0+000.28	VB	102.29	98.88	
	0+000.61	REDUCER	102.30	98.88	
BLDGE	0+001.50	BLDGE	102.33	98.88	
D	0+000 00	TEF	102 18	99 78	
	0+000.30	VB	102.19	99.78	
	0+000.60	REDUCER	102.10	99.78	
	0+000.01		102.20	00.79	
BLDGF	0+001.30	BLDGF	102.23	99.70	
	0.000.00		100.00	00.00	
	0+000.00		102.00	99.60	
	0+003.13		102.10	99.70	
	0+005.97	45 BEND	102.11	99.71	
	0+008.63	45BEND	102.05	99.65	
	0+009.69	VB	102.12	99.72	
	0+010.36	REDUCER	102.16	99.76	
BLDGC	0+011.30	BLDGC	102.20	99.80	
Н	0+000.00	TEE	102.04	99.64	
	0+001 95	45BFND	102 09	99.69	
	0+005.41	VR	102.17	99.77	
	0+006 10		102.17	00.70	
	0+007.09		102.13	00.91	
	0+007.08		102.21	39.01	
			400.10		
	0+000.00		102.12	99.72	
	0+000.70	L VB	102.15	99.72	
	0+001.30	REDUCER	102.17	99.72	
BLDGA	0+002.24	BLDGA	102.22	99.72	

FAIRHALL, MOFFATT & WOODLAND LIMITED LEGEND

NOTES :

- 1. ALL MATERIALS AND CONSTRUCTION IS TO BE IN ACCORDANCE WITH THE CURRENT CITY OF OTTAWA STANDARD DRAWINGS & SPECIFICATIONS OR OPSD/OPSS IF CITY DRAWINGS AND SPECIFICATIONS DO NOT APPLY.
- 2. THE POSITION OF UNDERGROUND AND ABOVEGROUND SERVICE, UTILITIES AND STRUCUTRES ARE NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH SERVICE, UTILITIES AND STRUCTURES IS NOT GUARENTEED. THE CONTRACTOR IS RESPONSIBLE FOR DETERMINING THE EXACT LOCATION, SIZE, MATERIAL AND ELEVATION OF ALL EXISTING SERVICES AND UTILITIES PRIOR TO CONSTRUCTION.
- 3. THE CONTRACTOR SHALL REPORT ALL CONFLICTS, DISCOVERIES OF ERROR AND DESCREPENCIES TO THE ENGINEER.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT AND ASSUME RESPONSIBILITY FOR ALL UTILITIES WHETHER OR NOT SHOW ON THESE DRAWINGS.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL LANDS BEYOND THE SITE LIMITS. ANY AREAS BEYOND THE SITE LIMITS, WHICH ARE DISTURBED DURING CONSTRUCTION. SHALL BE REPAIRED AND RESTORED TO ORIGINAL CONDITION OR BETTER, TO THE SATISFACTION OF THE ADJACENT LAND OWNER, THE OWNER, THE OWNERS REPRESENTATIVES AND/OR THE AUTHORITY HAVING JURSIDICTION AT THE EXPENSE OF THE CONTRACTOR.
- 6. WHERE NECESSARY, THE CONTRACTOR SHALL IMPLEMENT A TRAFFIC MANAGEMENT PLAN TO THE SATISFACTION OF THE CITY OF OTTAWA. ALL CONSTRUCTION SIGNAGE MUST CONFORM TO THE LATEST VERSION OF THE M.T.O. MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES. ALL TEMPORARY TRAFFIC CONTROL MEASURES MUST BE REMOVED UPON THE COMPLETION OF THE WORKS.
- 7. SHOULD ANY BURIED ARCHAEOLOGICAL REMAINS BE FOUND ON THE PROPERTY DURING CONSTRUCTION ACTIVITIES, THE CONTRACTOR SHALL NOTIFY THE OWNER TO CONTACT THE HERITAGE OPERATIONS UNIT OF THE ONTARIO MINISTRY OF CULTURE MUST BE NOTIFIED IMMEDIATE, AND WORK WITHIN THE AREA SHALL BE CEASED UNTIL FUTHER NOTICE.
- 8. FOR GEOTECHNICAL INFORMATION REFER TO GEOTECHNICAL REPORT PG3798-2 REV1 DATED AUG,9 2021 PREPARED BY PATERSON GROUP.
- FOR GEODETIC BENCHMARK AND GEOMETRIC LAYOUT OF STREET AND LOTS, REFER TO TOPOGRAPHICAL SURVEY AND PLAN OF SUBDIVISION PREPARED BY ANNIS, O'SULLIVAN, VOLLEBEKK LTD. BENCHMARK BASED ON CAN--NET VIRTUAL REFERENCE SYSTEM NETWORK.
- 10. FOR SITE PLAN INFORMATION, REFER TO SITE PLAN PREPARED BY A49 ARCHITECTURE 11. THESE DRAWINGS ARE NOT TO BE SCALED OR USED FOR LAYOUT PURPOSES
- 12. ROADWAY SECTIONS REQUIRING GRADE RAISE TO PROPOSED SUB GRADE LEVEL TO BE FILLED WITH ACCEPTABLE NATIVE EARTH BORROW OR IMPORTED OPSS SELECTED SUBGRADE MATERIAL IF NATIVE MATERIAL IS DEFICIENT AS PER RECOMMENDATION OF GEOTECHNICAL ENGINEER.
- 13. IN AREAS WHERE EXISTING GROUND IS BELOW THE PROPOSED ELEVATION OF SEWER AND WATERMAINS, GRADE RAISING AND FILLING IS TO BE IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL REPORT. AS PER CITY GUIDELINES ALL WATERMAINS IN FILL AREAS ARE TO BE TIED WITH RESTRAINING JOINTS AND THRUST BLOCKS.
- 14. REFER TO DRAWING C-011 FOR CROSS SECTIONS.
- 15. THE CONTRACTOR SHALL IMPLEMENT THE EROSION AND SEDIMENT CONTROL PLAN PRIOR TO THE COMMENCEMENT OF ANY SITE CONSTRUCTION. ALL EROSION AND SEDIMENT CONTRAL MEASURES SHALL BE INSTALLED TO THE SATISFACTION OF THE ENGINEER, OR ANY REGULATORY AGENCY. ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED UNTIL VEGETATION IS ESTABLISH OR UNTIL THE START OF A SUBSEQUENT PHASE.
- 16. CONTRACTORS SHALL BE RESPONSIBLE FOR KEEPING CLEAN ALL ROADS WHICH BECOME COVERED IN DUST, DEBRIS AND/OR MUD AS A RESULT OF ITS CONSTRUCTION OPERATIONS. 17. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY ADDITIONAL BEDDING OR ADDITIONAL STRENGTH PIPE
- SHOULD THE MAXIMUM OPSD TRENCH WIDTH BE EXCEEDED.
- 18. ALL PIPE, CULVERTS, STRUCTURES REFER TO NOMINAL INSIDE DIMENSIONS. 19. SHOULD CLAY SEALS BE REQUIRED, THEY SHALL BE INSTALLED AS PER THE RECOMMENDATIONS WITHIN THE GEOTECHNICAL REPORT.
- 20. UNLESS SPECIFICALLY NOTED OTHERWISE, PIPE MATERIALS SHALL BE AS FOLLOWS; -WATERMAINS TO BE PVC DR18 -SANITARY SEWER TO BE PVC DR35 -PERFORATED STORM SEWERS IN REAR YARDS AND LANDSCAPE AREAS TO BE HDPE -STORM SEWERS 375MM DIAMETER AND LESS TO BE PVC DR35 -STORM SEWERS 450MM DIAMETER AND GREATER TO BE CONCRETE, CLASS AS PER OPSD 807.010 OR 807.030, OR HIGHER
- 21. ALL CONNECTIONS TO EXISTING WATERMAINS ARE TO BE COMPLETED BY CITY FORCES. CONTRACTOR IS TO EXCAVATE, BACKFILL, COMPACT AND REINSTATE.
- 22. ANY WATERMAIN WITH LESS THAN 2.4M, AND ANY SEWER WITH LESS THAN 2.0M DEPTH OF COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.
- 23. ALL FIRE HYDRANTS AS PER CITY STANDARD W19, c/w 150mmØ LEAD UNLESS OTHERWISE SPECIFIED. 24. ALL STUBBED SEWERS SHALL HAVE PRE-MANUFACTURED CAPS INSTALLED.
- 25. ALL CATCHBASINS SHALL HAVE A 600MM SUMP. ALL CATCHBASIN MANHOLES, AND ALL STORM MANHOLES WITH OUTLETTING PIPE SIZES LESS THAN 900MM, SHALL HAVE A 300MM SUMP.
- 26. ALL SANITARY MANHOLES SHALL BE EQUIPPED WITH A WATERTIGHT COVER.
- 27. ALL LEADS FOR STREET CATCHBASIN'S AND CURB INLET CATCHBASIN'S CONNECTED TO MAIN SHALL BE 200MMØ PVC DR35 @ MIN 2% SLOPE UNLESS NOTED OTHERWISE. ALL LEADS FOR RYCB'S CONNECTED TO MAIN SHALL BE 200MMØ PVC DR35 @ MIN 1% SLOPE UNLESS NOTED OTHERWISE.
- 28. UNLESS SPECIFICALLY NOTED OTHERWISE, ALL STREET CATCHBASINS SHALL BE INSTALLED WITH TWO 3.0M MINIMUM SUBDRAINS INSTALLED LONGITUDINALLY. PARALLEL WITH THE CURB. ALL CATCHBASINS IN ASPHALT AREAS, NOT ADJACENT TO A CURB, SHALL BE INSTALLED WITH FOUR - 3.0M MINIMUM SUBDRAINS INSTALLED ORTHOGONALLY.
- 29. INLET CONTROL DEVICES SHALL BE INSTALLED PRIOR TO COMPLETING THE ROAD BASE (GRANULAR A). 30. ALL SEWER SERVICE LATERALS WITH MAINLINE CONNECTIONS DEEPER THAN 5.0M REQUIRE A CONTROLLED
- SETTLEMENT JOINT.
- 31. EACH BUILDING SHALL BE EQUIPPED WITH A SANITARY AND STORM SEWER BACKWATER VALVE AND CLEAN-OUT ON ITS PRIMARY SERVICE, AS PER ONTARIO BUILDING CODE REQUIREMENTS (BY OTHERS).
- 32. THE HGL PROVIDED IS BASED ON HYDRAULIC MODELING COMPLETED USING PCSWMM AND THE 100 YEAR CHICAGO STORM EVENT (C3H10010).
- 33. THE SUBGRADE OF ALL STRUCTURES, PIPE, ROADS, SIDEWALKS, WALKWAYS, AND BUILDINGS SHALL BE INPSECTED BY THE GEOTECHNICAL ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
- 34. TOP COURSE ASPHALT SHALL NOT BE PLACED UNTIL THE FINAL CCTV INSPECTION AND NECESSARY REPAIRS HAVE BEEN COMPLETED TO THE SATISFACTION OF THE ENGINEER AND THE CITY OF OTTAWA. 35. ALL RETAINING WALLS GREATER THAN 1.0M IN HEIGHT SHALL BE DESIGNED BY A QUALIFIED STRUCTURAL
- ENGINEER 36. ALL RETAINING WALLS GREATER THAN 0.6M IN HEIGHT REQUIRE A GUARD. ANY GUARD ON A RETAINING WALL GREATER THAN 1.0M IN HEIGHT SHALL BE DESIGNED BY THE QUALIFIED STRUCTURAL ENGINEER RESPONSIBLE FOR THE WALL DESIGN.
- 37. UPON COMPLETION OF THE RETAINING WALL, THE CONTRACTOR SHALL REQUEST A CONFORMANCE
- CERTIFICATE FROM THE QUALIFIED ENGINEER RESPONSIBLE FOR THE WALL DESIGN.

ROADWAY STRUCTURE:

CAR ONLY PARKING AREAS:(500mm)

50mm	- SUPERPAVE 12.5 ASPHALTIC CONCRETE
50mm	- OPSS GRANULAR "A" CRUSHED STONE
800mm	- OPSS GRANULAR "B" TYPE II

COLLECTOR ROAD :(690mm)

- SUPERPAVE 12.5 ASPHALTIC CONCRETE 40mm - SUPERPAVE 19.0 ASPHALTIC CONCRETE 50mm
- 150mm - OPSS GRANULAR "A" CRUSHED STONE 450mm - OPSS GRANULAR "B" TYPE II



C-010

CITY PLAN No. XXXXX

XXXX-XX D07-XX-) No Ш CITY





	CLIENT
	HUNTINGTON
	PROPERTIES
	PROPERTIES
	COPYRIGHT This drawing has been prepared solely for the intended use, thus any reproduction or distribution for any purpose other than authorized by IBI Group is
	forbidden. Written dimensions shall have precedence over scaled dimensions. Contractors shall verify and be responsible for all dimensions and conditions on the job, and IBI Group shall be informed of any variations from the dimensions and conditions shown on the drawing. Shop drawings shall be submitted to IBI Group for drawing concerning and concerning the submitted to IBI Group
	IBI Group Professional Services (Canada) Inc.
	ISSUES No. DESCRIPTION DATE
	###### D FOR CITY REVIEW 20##### 00
	ICTIC
	STRU
	CONS
	ORU
	SHE OLD 011 012 FOR NOTES LEGEND OR TABLE
	REET SECTIONS AND DETAILS
	PLEASE CONFIRM KEYPLAN BOX
	Entry of the second sec
	SITE SITE
	It Base
	CONSULTANTS
	Project Coordinator:
	Architect: A49 Architecture
	Landscape: 8 Fotenn 8
1 - 101.20 G/G	Goodkey, Weedmark & Associates Limited العناقة Surveyor:
MATCH EXISTING GRADES AT PROPERTY LINE	Annis O'Sullivan Vollebekk Ltd.
0.50	Paterson Group
	mber 9, 5
OPERI	ay, Dece
	tted: Frid
	SEV Plot
	PROFESS/ONAL
	OL NCE OF ONTRE
	st Saved
	wg
	S.SNOIT:
	SSC SEC
	011 CR(
	IBI GROUP
	IBI 400 – 333 Presion Street 97 Ottawa ON K1S 5N4 Canada 57 tel 613 225 1311 fax 613 225 9868 97
	PROJECT NO: 135470
	DRAWN BY: S.L. / D.D. CHECKED BY: T.R.B.
	PROJECT MGR: APPROVED BY:
	SHEET TITLE
	CITY PLAN NO. XXXXX





CITY



D07-XX-XX-XXXX No CITY CITY

