

PEAK DESIGN LOW (L/s)	¹ 2 PEAK DESIGN FLOW (L/s)	DESIGN HEAD (m)	WATER ELEVATION (m)	VOLUME (m ³)	AVAILABLE STORAGE
3.4	1.7	0.74	101.23 (u/g)	6	
4.1	2.1	1.06	101.55 (u/g)	9	> 23 m ³
6.5	3.3	2.61	103.10	20	

N.T.S.	SITE MARKET PLAN N.T.S. KEY PLAN
--------	---

ITEM
CATCHBASIN (600x600mm)
CB INSTALLATION
DITCH INLET CB 'TYPE A' (600x1200mm) 'DICB'
STORM / SANITARY MANHOLE (1200mmØ)
CB, FRAME & COVER
SANITARY / STORM MH FRAME & COVER
WATERTIGHT MH FRAME AND COVER
DITCH INLET GRATING
TRENCH DRAINS c/w DUCTILE IRON GRATING
SEWER TRENCH

PVC DR 18

IONS:
SIN (600x600mm)
LATION
ET CB 'TYPE A' (600x1200mm) 'DICB'
ANITARY MANHOLE (1200mmØ)
& COVER
/ STORM MH FRAME & COVER
HT MH FRAME AND COVER
ET GRATING
RAINS c/w DUCTILE IRON GRATING
ENCH
/ STORM SEWER / CB LEAD