

Prepared for:

12714001 CANADA INC.
100-768 Boulevard St-Joseph
Gatineau, QC
J8Y 4B8

Prepared by:

J.L. RICHARDS & ASSOCIATES LIMITED
343 Preston Street, Suite 900 and 1000
Ottawa, ON
K1S 1N4

Site Servicing Report

2983 Navan Road – Block 16 Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Table of Contents

1.0	INTRODUCTION.....	1
1.1	General	1
1.2	Site Description	1
1.3	Proposed Development.....	1
1.4	Proposed Connections to Existing Infrastructure.....	1
1.5	Consultation and Permits	2
2.0	WATER SERVICING.....	2
2.1	Water Supply Design Criteria	2
2.2	Domestic Water Demands.....	3
2.3	Fire Flow Requirements	3
2.4	Proposed Water Servicing, Boundary Conditions and Water Model	3
2.4.1	Proposed Water Servicing	3
2.4.2	Boundary Conditions	4
2.4.3	Water Model	4
2.5	Simulation Results.....	4
2.5.1	Peak Hour.....	5
2.5.2	Maximum Day Plus Fire Flow	5
2.5.3	Maximum Pressure.....	5
2.6	Summary and Conclusions.....	5
3.0	WASTEWATER SERVICING	5
3.1	Design Criteria	5
3.2	Proposed Sanitary Servicing and Design Flows	6
3.3	Summary and Conclusions.....	7
4.0	STORM SERVICING AND STORMWATER MANAGEMENT.....	7
4.1	Design Criteria	7
4.2	Proposed Stormwater Management Approach	8
4.3	Proposed Minor System Servicing.....	8
4.4	Stormwater Management Modelling Approach	8
4.4.1	Dual Drainage Model	8
4.4.2	Boundary Conditions	9
4.4.3	Ditch Drainage	9
4.5	Modelling Parameters	9
4.5.1	Hydrological Modelling Parameters	9
4.5.2	Simulation of Storm Distributions	10
4.6	Simulation Results.....	10
4.6.1	Low Point Ponding Analysis.....	10
4.6.2	Site Release Rate	11
4.7	Water Quality	11
4.8	Summary and Conclusions.....	11
5.0	Erosion and Sediment Control	12
6.0	CONCLUSIONS	13

**Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash**

List of Tables

Table 1: Water Demands	3
Table 2: Hydraulic Boundary Conditions	4
Table 3: Watermain Internal Diameters and C-Factors.....	4
Table 4: Wastewater Key Design Parameters.....	6
Table 5: Sanitary Design Flow Summary	6
Table 6: Catchbasin Ponding Depths	10
Table 7: Release Rates.....	11

List of Appendices

Appendix A	Concept Plan, Draft Plan of Subdivision and Topographical Survey
Appendix B	Pre-consultation Meeting Notes and Site Servicing Report Checklist
Appendix C	Water Servicing
Appendix D	Sanitary Design Sheet
Appendix E	Storm Design Sheet
Appendix F	Stormwater Management

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

1.0 INTRODUCTION

1.1 General

In 2023, J.L. Richards & Associates Limited (JLR) was retained by 12714001 Canada Inc. (the Owner) to prepare the detailed design of municipal infrastructure for Site Plan Approval (SPA) of their parcel located at 2983 Navan Road. The mixed-use site known as “Block 16 - Gas Station, Commercial Building, Drive-Thru Restaurant and Car Wash” will be referred to herein as Block 16. This Site Servicing Report (SSR) presents the servicing constraints and strategies for water, wastewater, stormwater servicing, and stormwater management in accordance with the City of Ottawa Design Guidelines, the associated technical bulletins and relevant design excerpts. This SSR also includes strategies for implementing erosion and sedimentation control measures throughout the construction phase of the project.

1.2 Site Description

The Block 16 is located within the City of Ottawa’s Official Plan boundary and consists of a 0.77 ha parcel bounded by Navan Road to the south and existing residential properties to the east, the proposed East Ridge Orleans Subdivision and Future Mixed-Use Block 15 to the north, and Brian Coburn Boulevard to the west. The legal description of the subject property can be found in the Draft Plan of Subdivision attached to Appendix A.

A topographical survey was completed by Stantec Inc. in August 2023 (Appendix A). The survey indicates that the existing ground surface generally slopes downwards in a southeasterly direction towards Navan Road.

1.3 Proposed Development

The proposed commercial development will consist of a gas station including a car wash, a commercial retail space along with a Drive-Thru Restaurant. The Concept Plan for the Block 16 is attached to Appendix A.

1.4 Proposed Connections to Existing Infrastructure

The proposed site plan will be serviced via the future East Ridge Orleans Subdivision and via existing infrastructure on Navan Road as follows and as shown on the servicing drawings:

Watermain

- Connection to the proposed existing 204 mm diameter watermain along Navan Road

Sanitary

- Connection to the future East Ridge Orleans Subdivision. A 200mm sanitary sewer stub will be dropped to service Block 16 as part of this future subdivision.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Storm

- Connection to the future East Ridge Orleans Subdivision. A 525 mm storm sewer stub will be dropped to service Block 16 as part of this future subdivision.

1.5 Consultation and Permits

An initial pre-consultation meeting was held on July 6, 2022, followed by a Phase 2 Pre-consultation help on September 13, 2023, each to discuss the proposed site plan, the planning approval process requirements, provide clarifications on design criteria, and high level discussion on servicing constraints. A copy of the pre-consultation meeting notes and the site servicing checklist has been provided in Appendix B.

2.0 WATER SERVICING

2.1 Water Supply Design Criteria

A Hydraulic Network Analysis (HNA) was completed as part of the detailed design for the East Ridge Orleans subdivision to confirm that the proposed watermains could provide adequate supply while complying with both the Ottawa Design Guidelines for Water Distribution (July 2010) and Technical Bulletins ISDTB-2014-02, ISTB-2018-02 and ISTB-2021-03. These documents are herein referred to as the Design Guidelines and TB-2014-02, TB-2018-02, and TB-2021-03, respectively.

The HNA completed as part of the East Ridge Orleans Subdivision design included water demands for the Commercial Site Plan (Block 16). The HNA has since been updated to reflect the proposed water service lateral for Block 16 but is based on the same demands and the boundary conditions used in the original East Ridge Orleans Subdivision HNA (refer to Appendix C for a copy of City correspondence for boundary conditions).

Section 4.2.2 of the Design Guidelines states the following criteria for development additions to the public water distribution system:

- Under maximum hourly demand conditions (peak hour), the residual pressures shall not be less than 276 kPa (40 psi);
- During periods of maximum day and fire flow demand, the residual pressure at any point in the distribution system shall not be less than 140 kPa (20 psi);
- In accordance with the Ontario Building Code (OBC) in areas that may be occupied, the static pressure at any fixture shall not exceed 552 kPa (80 psi);
- The maximum pressure at any point in the distribution system in unoccupied areas shall not exceed 689 kPa (100 psi); and
- Feedermains, which have been provided primarily for the purpose of redundancy, shall meet, at a minimum, the basic day plus fire flow demand.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

2.2 Domestic Water Demands

The estimated commercial water demands presented in this section are based on the site layout proposed in the Site Plan (Appendix A). A plug flow of 3.60 L/s was added to each demand scenario to consider the demands required for the car wash (refer to Appendix D for a confirmation letter from the mechanical engineer). Table 1 summarizes the water demands projected for this site.

Table 1: Water Demands

Demand Scenario	Commercial Water Consumption or Peaking Factor	Commercial Water Demands (L/s)	Car Wash Demands (L/s)	Total Demands (L/s)
Average Day Demand	28,000 L/ha/d	0.25	3.60 L/s	3.85
Maximum Day Demand	1.5 x Avg Day	0.37	3.60 L/s	3.97
Peak Hour Demand	1.8 x Max Day	0.67	3.60 L/s	4.27

2.3 Fire Flow Requirements

The City has specified that the Fire Underwriters Survey (FUS) method shall be used for any public or private site where new fire hydrants are being designed. Specifically, the required fire flow (RFF) for each structure was calculated in accordance with TB-2018-02.

The required fire flow for the Commercial Site Plan (Block 16) was calculated to be 83 L/s. Refer to Appendix C for the detailed RFF calculations for the critical fire area.

2.4 Proposed Water Servicing, Boundary Conditions and Water Model

2.4.1 Proposed Water Servicing

Water will be supplied to the Commercial Site Plan (Block 16) by a 150 mm diameter water service that will connect to the existing 305 mm watermain on Navan Road, located east of the intersection between Navan Road and Brian Coburn Blvd. Fire protection will be provided by a new proposed hydrant within the site. As shown in the servicing plan, the car wash is serviced directly by the gas station. Design of the service will be verified by Owner's mechanical engineer however, as noted in Section 2.2, the demand from the car wash has been included in this HNA.

Watermain roughness coefficients were determined using friction factors presented in Section 4.2.12 of the Design Guidelines and the internal pipe diameters were modelled based on Section 4.3.5 of the design Guidelines.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

2.4.2 Boundary Conditions

Hydraulic boundary conditions were provided by the City at the proposed connection location listed in Section 2.4.1 above. Table 2 summarizes the hydraulic boundary conditions received by the City (refer to Appendix C for a copy of the City correspondence). The boundary condition for maximum day plus fire flow corresponds to a required fire flow of 100 L/s. It is noted that the fire flow demand for the City boundary condition is more conservative than the calculated fire flow requirement of 5000 L/min (83 L/s).

Table 2: Hydraulic Boundary Conditions

Demand Scenarios	Connection 3 Head (m)
Maximum HGL	130.7
Peak Hour	126.8
Max Day plus Fire Flow 6,000 L/min (100.00 L/s)	127.3

2.4.3 Water Model

A hydraulic water model within the WaterCAD® software platform was used to carry out the HNA (refer to the overall schematics presented in Appendix C). The water demands from Table 1 and the boundary conditions from Table 2 were input into the model for each demand scenario. Table 3 summarizes the watermain diameters and roughness coefficients used in the model, based on Sections 4.2.12 and 4.3.5 of the Design Guidelines.

Table 3: Watermain Internal Diameters and C-Factors

Nominal Diameter	Inside Diameter	C-Factor
150 mm	155 mm	100
200 mm	204 mm	110
300 mm	297 mm	120

2.5 Simulation Results

The HNA was carried out under steady-state peak hour, maximum day plus fire flow, and maximum pressure conditions to confirm that the proposed water servicing can meet the design criteria outlined in Section 2.1.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

2.5.1 Peak Hour

The simulation results found the minimum pressure at the site during the peak hour condition to be 399 kPa (57.9psi) (refer to Appendix C), which exceeds the minimum pressure criterion of 276 kPa (40 psi) per the Design Guidelines.

2.5.2 Maximum Day Plus Fire Flow

Fire water supply will be provided by a proposed hydrant off the 150 mm diameter water service for Block 16. Hydrant spacing was carried out in accordance with the Design Guidelines.

To ensure adequate fire protection, the maximum day demand shown in Table 1 was analyzed simultaneously with the fire flow requirements. The fire flow simulation was carried out by allowing WaterCAD® to calculate the maximum fire flow that can be drawn from the hydrant without allowing any part of the system to experience pressures less than 140 kPa (20 psi). Using the 6,000 L/min (100 L/s) boundary condition provided by the City (refer to Table 2), the system is expected to deliver a minimum of 6,000 L/min (100 L/s) within the site. Per Appendix I of TB-2018-02, adequate water supply can be provided by the hydrant to the proposed site.

2.5.3 Maximum Pressure

Based on a zero (0 L/s) demand condition, the simulation results found the maximum pressure at the site to be 437 kPa (63.4). This value is below the maximum pressure constraint of 552 kPa (80 psi), therefore pressure reducing valves (PRVs) are not anticipated to be required.

2.6 Summary and Conclusions

Based on the water simulation results, the proposed development can be serviced by the proposed 150 mm water service lateral connected to the 305 mm diameter watermain on Navan Road. Furthermore, adequate fire water supply can be achieved with the proposed hydrant off the 150 mm water lateral servicing Block 16.

3.0 WASTEWATER SERVICING

3.1 Design Criteria

The sanitary sewer system within the Block 16 is designed in accordance with the Ottawa Sewer Design Guidelines and subsequent technical bulletins. The design parameters are applied under two scenarios as per ISTB Technical Bulletin 2018-01. The key design parameters have been summarized in Table 4.

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Table 4: Wastewater Key Design Parameters

Design Parameter	Design Value
Commercial Average Flow	28,000 L/gross ha/Day
Residential Average Flow	280 L/Cap/Day
Residential Peaking Factor	Harmon's Formula
Commercial Peaking Factor	1.5
Harmon's Correction Factor (K)	0.8
Infiltration Allowance	0.33 L/s/ha
Manning's Roughness Coefficient (n)	0.013
Allowable Slopes	Varies (Refer to Section 6.1.2.2 of ODSG)
Allowable Velocities	0.6 m/s – 3.0 m/s
Allowable Freeboard	-

3.2 Proposed Sanitary Servicing and Design Flows

Wastewater generated from the Block 16 will be conveyed via a proposed 200 mm diameter sanitary sewer system. Wastewater will then discharge into the East Ridge Orleans Subdivision via a 200mm sanitary sewer stub proposed as part of the subdivision as shown on the Servicing Plan.

Wastewater flows from the proposed development are presented in the Block 16 Sanitary Design Sheet (refer to Appendix D). Based on the design criteria presented in Table 3-1 the total design peak flow of 4.23 L/s is calculated for the development which is based on the site area of 0.77ha. Table 5 summarizes the results from the sanitary design sheet.

Table 5: Sanitary Design Flow Summary

Commercial Type	Site Area	Average Flow	Com. Peak Flow	Infilt. Flow	Total Flow
Commercial Flows	0.77 ha	28,000 L/gross ha/Day	0.374 L/s	0.254 L/s	0.628 L/s
Car Wash Flows	-	-	-	-	3.6 L/s
Total Wastewater Flows – Block 16					4.23 L/s

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

The flows from Block 16 (4.23 L/s) were incorporated in the detailed design of the sanitary sewer within the future East Ridge Orleans Subdivision thus there is sufficient downstream capacity. It is proposed to adopt the sanitary servicing strategy described in this section.

3.3 Summary and Conclusions

Wastewater servicing for Block 16 will be designed in accordance with the City of Ottawa Sewer Design Guidelines, the associated technical bulletins, and various background documents as highlighted throughout this section. Wastewater generated from the Block 16 will be conveyed via a proposed 200 mm diameter sanitary sewer outletting to the East Ridge Orleans Subdivision to the north of the site. It is recommended that this wastewater servicing plan be implemented to provide adequate sanitary servicing for the proposed development.

4.0 STORM SERVICING AND STORMWATER MANAGEMENT

4.1 Design Criteria

Storm and stormwater management servicing for the Gas Bar Site Plan (Block 16) was developed in accordance with the City of Ottawa 2012 Sewer Design Guidelines (OSDG) and the more recent Technical Bulletin PIEDTB-2016-01 (September 6, 2016). These two documents are herein referred to as the Design Guidelines in this section. A summary of the key storm and stormwater management criteria follows:

- Control minor system flows to the allowable release rates of 68 L/s as identified in Table 5-4 Site Servicing Report 2983, 3053 and 3079 Navan Road & 2690 Pagé Road, Ottawa, Ontario (JLR 2024);
- The runoff coefficients (C-factors) to be calculated based on the ratio of pervious and impervious surfaces depicted on proposed site plans;
- Minimum roadway slope of 0.1% from crest-to-crest for overland flow route;
- Maximum parking ponding depth of 350 mm (static and dynamic) as per the Design Guidelines and maximum depth of surface flow to be 300 mm;
- Minimum vertical clearance of 0.15 m between the spill elevation on the street and the finished grade;
- Major system flows, up to and including the 1:100-year design storm event, are contained within the site.
- Quality control will be accommodated by Pond #3 to meet an MECP Enhanced Level of Protection (80% TSS removal) as identified in Site Servicing Report 2983, 3053 and 3079 Navan Road & 2690 Pagé Road, Ottawa, Ontario (JLR 2023).
- Ponding in landscaped areas to enhance groundwater recharge in accordance with the City of Ottawa Urban Design Guidelines for Gas Stations, Guideline 30.
- Provide measures to ensure that site preparation and construction is in accordance with the current Best Management Practices for Erosion and Sediment Control.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

4.2 Proposed Stormwater Management Approach

In order to achieve the allowable release rates, the stormwater management of the site will include:

- Surface storage within the site in greater than a 1:2-year event with captured flows conveyed to the minor system;
- Controlled release of the flows captured in the minor system for the entire site using Inlet Control Devices (ICDs).
- Flows stored in oversized storage pipes underground. Flows will accumulate in the storage pipes and be released from the site via an OGS and orifice control into the minor system on Paleo Drive.

4.3 Proposed Minor System Servicing

Internal to the gas station site, two minor system sewer runs will be provided on either side of the main building structure. Both of these sewer runs will be oversized and will connect into a single manhole upstream of the connection upstream of the easement stub, upstream of Paleo Drive. The connection manhole will have a 127mm diameter orifice plate on the downstream outlet sewer to control to the allowable release rate, 68 L/s, as defined in the Site Servicing Report 2983, 3053 and 3079 Navan Road & 2690 Pagé Road, Ottawa, Ontario (JLR 2023). The upsized storm sewers will be 525mm diameter.

Downstream of the orifice an Stormceptor EFO4 model, or equivalent, will provide 80% TSS removal as well as capture of oils and spills.

The runoff coefficient is based on the ratio of impervious surfaces and areas. A design sheet for sizing of the sewers to confirm capacity for the 1:2-year rational method flow is provided in Appendix E.

The gas station roof structure is uncontrolled and drains directly to the minor system.

There are no basements and therefore no HGL constraints in the system.

4.4 Stormwater Management Modelling Approach

4.4.1 Dual Drainage Model

The analysis of both major and minor drainage systems was carried out to demonstrate their compliance with respect to the design criteria described in Section 4.6. The performance of the major overland system and minor storm sewer system was analyzed with PCSWMM. This software is a dynamic model which allows both hydrologic and hydraulic components to be simulated in the same platform and also allows the simulation of the interaction between the major and minor systems. The PCSWMM software platform was used to:

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

- Generate the surface runoff hydrograph for each sub-area under various recurrences.
- Subdivide each inflow hydrograph into its minor and major system components based on the proposed inlet capture rates and roadway sag storage.
- Assess cascading, if any, and carry out dynamic routing of storm flows to determine flow depths along the roadways. As previously stated, the maximum major overland flow depths within the parking lot areas are to be limited to 350 mm or less, as per Technical Bulletin PIEDTB-2016-01.

PCSWMM was set-up to evaluate the proposed servicing as detailed on Drawing C01 and C02. Subcatchments were delineated for the structure roof areas, parking lot low points and landscaped low points. Model schematics are prepared in Appendix F.

4.4.2 Boundary Conditions

Boundary conditions are taken from the downstream subdivision model issued as part of the Site Servicing Report 2983, 3053 and 3079 Navan Road & 2690 Pagé Road, Ottawa, Ontario (JLR 2023).

The downstream 1:100-year HGL at the connection to the Subdivision at MH518A is identified as 81.28 m. The boundary condition in the model was set at this elevation as a constant during the storm simulations.

4.4.3 Ditch Drainage

The ditch drainage system surrounding the site currently contains a single 375mm diameter culvert at the proposed site access on Navan Road. Due to access requirements the culvert will have to be extended. Since the culvert is not to current Ottawa City design standards for the minimum driveway culvert, it is proposed to replace the undersized culvert with a new 600mm diameter culvert.

The outlet of the proposed access culvert will be such that a 1% grade on the existing ditch will be maintained to the downstream conveyance culvert under Navan Road. The Navan Road culvert inlet is lower than the proposed culvert outlet to facilitate conveyance of the stormwater and mitigate potential ponding in this ditch section.

4.5 Modelling Parameters

4.5.1 Hydrological Modelling Parameters

The following parameters were used in the hydrologic component of PCSWMM:

- **Areas and Imperviousness:** Catchment ID and drainage areas used by PCSWMM match those shown on either Drawing DST or Figure E-1 (Appendix

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

E1). Sealed and roof areas are set at 100% impervious and other grassed or landscaped areas are pervious.

- **Catchment Width:** The catchment width is estimated at the width of overland sheet flow based on the grading of the catchment and slope direction.
- **Manning's Roughness Coefficient:** Manning's Roughness Coefficients of 0.013 and 0.25 were used for the impervious and pervious surfaces, respectively.
- **Horton Infiltration parameters:** City of Ottawa OSDG Horton Infiltration Parameters have been used in the modelling.
- **Initial Abstraction:** Initial abstraction of 4.67 mm and 1.57 mm was used for the pervious and impervious surfaces respectively, consistent with the OSDG.

4.5.2 Simulation of Storm Distributions

To assess peak flow rates and peak volume storage requirements the 3-hour Chicago storm has been simulated for the site for the 1:2-year event and 1:100-year event and the 24-hour SCS storms for the 1:100-year event.

4.6 Simulation Results

4.6.1 Low Point Ponding Analysis

Ponding depths in the low points in the parking area and landscaped areas are shown in Table 6.

Table 6: Catchbasin Ponding Depths

Low Point ID	Top of Grate (m)	Maximum Static Depth (mm)	3-hour Chicago 1:2 year Depth (mm)	3-hour Chicago 1:100 year Depth (mm)	24-hour SCS 1:100 year Depth (mm)
1	85.25	190/300	-	250	230
2A	85.35	250	-	-	-
2B	85.40	220	-	-	-
3	85.35	300	-	60	30
4	84.75	150	-	100	-
5	85.35	150	-	100	70
6	85.37	80	-	100	90

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Low Point ID	Top of Grate (m)	Maximum Static Depth (mm)	3-hour Chicago 1:2 year Depth (mm)	3-hour Chicago 1:100 year Depth (mm)	24-hour SCS 1:100 year Depth (mm)
7	84.55	300	-	300	160
8	85.04	270	-	290	250
9	84.80	300	-	190	130
10	85.18	240	-	150	90
11	85.12	300	-	210	170
12	85.45	150	-	90	70
13	85.50	150	-	160	150

The simulation results compiled in Table 6 shows that:

- No ponding nor dynamic flow will occur in the 1:2-year event;
- Maximum ponding depth of 300 mm during the 1:100-year event; and,
- There is no spill from the site in the 1:100-year event.

4.6.2 Site Release Rate

Table 8 below shows the release rates from the site via the 127mm diameter orifice plate. All release rates are below the 68 L/s allowable release rate.

Table 7: Release Rates

	3-hour Chicago 1:2 year Release Rate (L/s)	3-hour Chicago 1:100 year Release Rate (L/s)	24-hour SCS 1:100 year Release Rate (L/s)
Flow at MH 514	46	66	65

4.7 Water Quality

An OGS unit is proposed for the site to provide site specific water quality to 80% TSS removal and capture of oils and spills. The sizing details for the unit are contained in Appendix F. The unit sized for the site is an Stormceptor EFO4, or equivalent.

4.8 Summary and Conclusions

The stormwater servicing achieves a release rate from the site to the minor system limited to the allowable release rate and contains up to the 1:100 year on site.

**Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash**

5.0 Erosion and Sediment Control

Erosion and sediment control measures, as outlined in the Ontario Ministry of Natural Resources (MNR) Guidelines on Erosion and Sediment Control for Urban Construction Sites, will be implemented to trap sediment on site. The following erosion and sediment control measures can be implemented during construction as shown on the Erosion and Sediment Control Plan (Drawing ESC):

- Supply and installation of a silt fence barrier, as per OPSD 219.110.
- Supply and installation of siltsack or sentinel CB inserts between the frame and cover of catch basins and maintenance holes adjacent to the project area during construction, to prevent sediment from entering the sewer system.
- Stockpiling of material during construction is to be located along flat areas away from drainage paths. For material placed on sloped areas, stockpiles are to be enclosed with a silt fence to protect watercourses.
- All catch basins are to be equipped with sumps, inspected frequently, and cleaned as required.
- Temporary ICDs are to be placed blocking part of the sewer pipe in the connecting storm maintenance holes to eliminate construction debris from entering the existing storm sewer system. The ICDs are to be removed after the proposed storm sewers have been fully cleaned.
- A mud mat is to be built at each of the site entranceways to prevent the transport of sediment onto paved surfaces. The mud mat shall be:
 - Minimum of 20 m in length for the full width of the entrance way (10 m wide minimum).
 - Minimum of 400 mm thick underlain with a geotextile (or graded aggregate filter); and
 - Constructed with 50 mm diameter clear stone for the first 10 m (extending from the paved street) and the remainder of the length with 150 mm diameter clear stone.

The proposed removal and reinstatement measures as well as the erosion control measures shall conform to the following documents:

- “Guidelines on Erosion and Sediment Control for Urban Construction Sites” published by Ontario Ministries of Natural Resources, Environment, Municipal Affairs, and Transportation & Communication, Association of Construction Authorities of Ontario and Urban Development Institute, Ontario, May 1987.
- “MTO Drainage Manual”, Chapter F: “Erosion of Materials and Sediment Control”, Ministry of Transportation & Communications, 1985.
- “Erosion and Sediment Control” Training Manual by Ministry of Environment, Spring 1998.
- Applicable Regulations and Guidelines of the Ministry of Natural Resources.

**Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash**

6.0 CONCLUSIONS

Block 16 will be serviced as follows:

- Water servicing will be provided by connection to the proposed watermain along the Navan Road.
- Wastewater servicing will be provided by a connection to the future East Ridge Orleans Subdivision
- Storm servicing will be provided by a connection to the future East Ridge Orleans Subdivision
- Flows exceeding the allowable peak flow for Block 16, will be held on-site, using a combination of both, above ground and underground storage.

Site Servicing Report

2983 Navan Road – Block 16

Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

This report has been prepared by J.L. Richards & Associates Limited for 12714001 CANADA INC.'s exclusive use. Its discussions and conclusions are summary in nature and cannot properly be used, interpreted or extended to other purposes without a detailed understanding and discussions with the client as to its mandated purpose, scope and limitations. This report is based on information, drawings, data, or reports provided by the named client, its agents, and certain other suppliers or third parties, as applicable, and relies upon the accuracy and completeness of such information. Any inaccuracy or omissions in information provided, or changes to applications, designs, or materials may have a significant impact on the accuracy, reliability, findings, or conclusions of this report.

This report was prepared for the sole benefit and use of the named client and may not be used or relied on by any other party without the express written consent of J.L. Richards & Associates Limited, and anyone intending to rely upon this report is advised to contact J.L. Richards & Associates Limited in order to obtain permission and to ensure that the report is suitable for their purpose.

J.L. RICHARDS & ASSOCIATES LIMITED

Prepared by:



William Rugamba,
Civil Engineering Graduate

Prepared by:



Bobby Pettigrew, P. Eng.
Senior Water Resource Engineer


Reviewed by:

Karla Ferrey, P. Eng.
Senior Associate, Manager,
Ottawa, Civil Development


Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix A

Concept Plan, Draft Plan of
Subdivision and Topographical
Survey



02 SITE & BUILDING DATA and ZONING REVIEW			
SP-A01			SCALE: NTS
Project			NEW RESTAURANT, CONVENIENCE STORE & GAS BAR
2130 BRIAN COBURN BLVD.			Drawing
SITE PLAN			
01 LOCATION PLAN			
SP-A01 Scale: NTS			



SP-A01
22-127
Date 12 MAY 2022

PLAN NO. _____





THIS PLAN IS NOT VALID
UNLESS ACCOMPANIED BY AN
ORIGINAL COPY
ISSUED BY AN ONTARIO SURVEYOR
RECORDED WITH THE LAND SURVEYOR
REGISTRATION BOARD OF ONTARIO

PAGE ROAD

ROAD ALLOWANCE BETWEEN LOTS 5 & 6 (AS WIDENED)

PIN 04404-0409





Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix B

Pre Consultation Meeting Notes
and Site Servicing Report
Checklist



File No.: PC2023-0227

Carmine Zayoun
12714001 Canada Inc (Zayoun Group)
Via email: carmine@zayoungroup.com

Subject: **Pre-Consultation: Meeting Feedback**
Proposed Site Plan Application – 2983 Navan Road ‘
Gas Station and Commercial Building – PC2023-0227

Please find below information regarding next steps as well as consolidated comments from the above-noted pre-consultation meeting held on September 13, 2023.

Pre-Consultation Preliminary Assessment

1 <input type="checkbox"/>	2 <input type="checkbox"/>	3 <input type="checkbox"/>	4 <input checked="" type="checkbox"/>	5 <input type="checkbox"/>
----------------------------	----------------------------	----------------------------	---------------------------------------	----------------------------

One (1) indicates that considerable major revisions are required while five (5) suggests that the proposal appears to meet the City's key land use policies and guidelines. This assessment is purely advisory and does not consider technical aspects of the proposal or in any way guarantee application approval.

Next Steps

1. A review of the proposal and materials submitted for the above-noted pre-consultation has been undertaken. Please proceed to complete a Phase 2 / Phase 3 Pre-consultation Application Form and submit it together with the necessary studies and/or plans to planningcirculations@ottawa.ca.
2. In your subsequent pre-consultation submission, please ensure that all comments or issues detailed herein are addressed. A detailed cover letter stating how each issue has been addressed must be included with the submission materials. Please coordinate the numbering of your responses within the cover letter with the comment number(s) herein.
3. Please note, if your development proposal changes significantly in scope, design, or density before the Phase 3 pre-consultation, you may be required to complete or repeat the Phase 2 pre-consultation process.

Supporting Information and Material Requirements

1. The attached **Study and Plan Identification List** outlines the information and material that has been identified, during this phase of pre-consultation, as either required (R) or advised (A) as part of a future complete application submission.
 - a. The required plans and studies must meet the City's Terms of Reference (ToR) and/or Guidelines, as available on Ottawa.ca. These ToR and Guidelines outline



the specific requirements that must be met for each plan or study to be deemed adequate.

Consultation with Technical Agencies

1. You are encouraged to consult with technical agencies early in the development process and throughout the development of your project concept. A list of technical agencies and their contact information is enclosed.

Planning

Comments:

1. In the Official Plan the subject site is designated as Neighbourhood is modified with the Evolving Neighbourhood overlay. Brian Coburn Boulevard is also designated as a Minor Corridor. The property is further identified as Low-density residential in the EUC – Phases 1 Community Design Plans (CDP). The subject lands are currently zoned GM[2546]H(14.5) General Mixed-Use, Exception.
2. Committee of Adjustment

No variances have been identified at this point. Staff will set up a meeting with a Committee of Adjustment Plan if any required.

3. Design guidelines

[Urban Design Guidelines for Drive-Through Facilities](#)

[Urban Design Guidelines for Gas Stations](#)

4. Landscape requirements

Landscape buffers will need to comply with Section 110 of the Zoning By-law and are consistent with the design guidelines.

The turning radius encroached into the landscape buffers on the demonstration plan. Ensure all landscaping is protected by barrier curbs

5. Parking requirements

Parking should comply with Sections 100, 101, 106, 109 and 111

Vehicle and bicycle parking should be situated with easily access while minimizing pavement. There seems to be a lot of pavement in front of this building.

6. Easements



Are there service easements required over the pedestrian walkway connecting this property with the subdivision?

7. Confirm that the location of the Car Wash will not become a noise problem for future residents of the townhouses behind it. Noise study will need to identify any issues and provide remediation measures.
8. Provide locations of signage and ensure that space is made available for tree planting

Urban Design

9. Relevant guidelines – The City's Urban Design Guidelines for Gas Stations and Urban Design Guidelines for Drive-Through Facilities are both applicable to this site. The applicant should ensure their submission meets the direction of these guidelines.
10. Design Brief - A Design Brief is required. Please refer to the attached Terms of Reference for details.
11. Public realm – Please refer to the attached PDF for Urban Design comments related to the location of sidewalks, walkways and pedestrian movements on the site
12. Landscaping - Extensive tree and shrub planting is needed on this site, in particular to soften the interface with the existing and future residential and to enhance the ROW.

Feel free to contact the Urban Design Planner, Christopher Moise, at Christopher.Moise@ottawa.ca, for follow-up questions

Engineering

Comments:

13. General Comments:
 - a. Review of the Phase 3 submission for this application will not occur until the detailed design of the subdivision that it is within (D07-16-21-0027) is approved.
 - b. At the stage of site plan approval, a condition will be imposed detailing that a commence work notification will not be issued until the subdivision's infrastructure is in-service.
14. Engineering Studies:
 - a. All engineering studies (detailed in the Study and Plan Identification List form) are to follow the to be approved draft plan of subdivision D07-16-21-0027.



- b. An interceptor pit is required with the provision of the car wash.
15. An MECP Environmental Compliance Approval **Industrial Sewage Works** will be required for the proposed development. Please contact the Ministry of the Environment, Conservation and Parks, Ottawa District Office to arrange a pre-submission consultation:

- b. Emily Diamond at (613) 521-3450, ext. 238 or
Emily.Diamond@ontario.ca

Note: this site does not meet the City's requirements for ToR. To have the ECA application reviewed under ToR, a request will need to be sent to Charles Warnock (charles.warnock@ottawa.ca).

Feel free to contact Reed Adams (reed.adams@ottawa.ca), Infrastructure Project Manager, for follow-up questions.

Noise

Comments:

16. A stationary noise report for the car wash is required because of the adjacent residential.

Feel free to contact the Senior Transportation Engineer, Mike Giampa, at Mike.Giampa@ottawa.ca, for follow-up questions.

Transportation

Comments:

17. A full TIA is not required as this site is covered under the recent subdivision TIA.
18. A memo including the pertinent subdivision trips is sufficient.
19. The right of way protection on Brian Coburn and Navan Roads is 40m and 37.5m, respectively

Feel free to contact the Senior Transportation Engineer, Mike Giampa, at Mike.Giampa@ottawa.ca, for follow-up questions

Planning Forestry

Comments:

20. A Tree Conservation Report and Landscape Plan must be submitted with both SPC applications



21. A permit is required prior to any tree removal on site. The tree permit will be released upon site plan approval. Please contact the File Lead or the Planning Forester, Hayley Murray (hayley.murray@ottawa.ca) for information on obtaining the tree permit.
22. If marine clay soils are present, setbacks on City properties must adhere to the 2017 SMC guidelines (attached). The Geotechnical report must address the implications of these soils, if present, on tree planting in relation to private land.
23. If underground parking is planned, a design must be provided for the site to support tree planting
24. We expect a very strong landscape plan to re-establish canopy cover across the properties. Tree planting and protecting existing urban forest canopy is imperative to reach the City's target of 40% canopy cover.

Feel free to contact Hayley Murray, Planning Forester, for follow-up questions.

Parkland

Comments:

25. Parkland contributions were made through the Subdivision process.

Feel free to contact Jessica Button, Parks Planner, for follow-up questions.

Conservation Authority

Comments:

26. The Rideau Valley Conservation authority will be commenting on this application

Feel free to contact RVCA, for follow-up questions.

Other

27. The High Performance Development Standard (HPDS) is a collection of voluntary and required standards that raise the performance of new building projects to achieve sustainable and resilient design. The HPDS was passed by Council on April 13, 2022.
 - a. At this time, the HPDS is not in effect and Council has referred the 2023 HPDS Update Report back to staff with direction to bring forward an updated report to Committee with recommendations for revised phasing timelines, resource requirements and associated amendments to the Site Plan Control By-law by no later than Q1 2024.



- b. Please refer to the HPDS information attached and ottawa.ca/HPDS for more information.

Submission Requirements and Fees

1. Outlines the application type/subtype required and the associated fees
 - a. Additional information regarding fees related to planning applications can be found [here](#).
2. The attached **Study and Plan Identification List** outlines the information and material that has been identified as either required (R) or advised (A) as part of a future complete application submission.
 - a. The required plans and studies must meet the City's Terms of Reference (ToR) and/or Guidelines, as available on [Ottawa.ca](#). These ToR and Guidelines outline the specific requirements that must be met for each plan or study to be deemed adequate.
3. All of the above comments or issues should be addressed to ensure the effectiveness of the application submission review.

Should there be any questions, please do not hesitate to contact myself or the contact identified for the above areas / disciplines.

Yours Truly,
Steve Belan

cc.

Tim Chadder
Raad Akrawi
Madelen Fellows
Karla Ferrey
Tatyana Roumie
Christopher Moise
Adam Reed
Mike Giampa
Haley Murray
Jessica Button

12714001 Canada Inc – Block 16 – Gas Bar, Commercial Building/Drive-Through Restaurant and Car Wash

2983 Navan Road

SITE SERVICING REPORT CHECKLIST

REFERENCED STUDIES AND REPORTS	REFERENCE
Site Servicing Report for 12714001 Canada Inc, Block 16 – Gas Bar, Commercial Building/Drive-Through Restaurant and Car Wash, 2983 Navan Road Road (J.L. Richards & Associates Limited, December 8, 2023)	Site Servicing Report

4.1	GENERAL CONTENT	REFERENCE
<input type="checkbox"/>	Executive Summary (for larger reports only).	N/A
<input checked="" type="checkbox"/>	Date and revision number of the report.	Site Servicing Report
<input checked="" type="checkbox"/>	Location map and plan showing municipal address, boundary, and layout of proposed development.	Site Servicing Report (Appendix A) All Drawings
<input checked="" type="checkbox"/>	Plan showing the site and location of all existing services.	Servicing Plan
<input checked="" type="checkbox"/>	Development statistics, land use, density, adherence to zoning and official plan, and reference to applicable subwatershed and watershed plans that provide context to which individual developments must adhere.	Site Servicing Report
<input checked="" type="checkbox"/>	Summary of Pre-consultation Meetings with City and other approval agencies.	Site Servicing Report (Appendix 'A')
<input checked="" type="checkbox"/>	Reference and confirm conformance to higher level studies and reports (Master Servicing Studies, Environmental Assessments, Community Design Plans), or in the case where it is not in conformance, the proponent must provide justification and develop a defendable design criteria.	Reference made to Stantec 2005 EUC ISSU
<input checked="" type="checkbox"/>	Statement of objectives and servicing criteria.	Site Servicing Report
<input checked="" type="checkbox"/>	Identification of existing and proposed infrastructure available in the immediate area.	Site Servicing Report Servicing Plan
<input type="checkbox"/>	Identification of Environmentally Significant Areas, watercourses and Municipal Drains potentially impacted by the proposed development (Reference can be made to the Natural Heritage Studies, if available).	N/A

<input checked="" type="checkbox"/>	Concept level master grading plan to confirm existing and proposed grades in the development. This is required to confirm the feasibility of proposed stormwater management and drainage, soil removal and fill constraints, and potential impacts to neighbouring properties. This is also required to confirm that the proposed grading will not impede existing major system flow paths.	Grading Plan
<input type="checkbox"/>	Identification of potential impacts of proposed piped services on private services (such as wells and septic fields on adjacent lands) and mitigation required to address potential impacts.	N/A
<input type="checkbox"/>	Proposed phasing of the development, if applicable.	N/A
<input checked="" type="checkbox"/>	Reference to geotechnical studies and recommendations concerning servicing.	Site Servicing Report and Drawings
<input checked="" type="checkbox"/>	All preliminary and formal site plan submissions should have the following information: <ul style="list-style-type: none"> ▪ Metric scale ▪ North arrow (including construction North) ▪ Key plan ▪ Name and contact information of applicant and property owner ▪ Property limits, including bearings and dimensions ▪ Existing and proposed structures and parking areas ▪ Easements, road widening and rights-of-way ▪ Adjacent street names 	All Drawings

4.2	SITE SERVICING REPORT: WATER	REFERENCE
<input type="checkbox"/>	Confirm consistency with Master Servicing Study, if available.	N/A
<input checked="" type="checkbox"/>	Availability of public infrastructure to service proposed development.	Site Servicing Report (Section 2.0) Servicing Plan
<input checked="" type="checkbox"/>	Identification of system constraints.	Site Servicing Report (Section 2.0) Servicing Plan
<input checked="" type="checkbox"/>	Identify boundary conditions.	Site Servicing Report (Section 2.0)
<input checked="" type="checkbox"/>	Confirmation of adequate domestic supply and pressure.	Site Servicing Report (Section 2.0)
<input checked="" type="checkbox"/>	Confirmation of adequate fire flow protection and confirmation that fire flow is calculated as per the Fire Underwriter's Survey. Output should show available fire flow at locations throughout the development.	Site Servicing Report (Section 2.0)
<input checked="" type="checkbox"/>	Provide a check of high pressures. If pressure is found to be high, an assessment is required to confirm the application of pressure reducing valves.	Site Servicing Report (Section 2.0)

<input type="checkbox"/>	Definition of phasing constraints. Hydraulic modelling is required to confirm servicing for all defined phases of the project, including the ultimate design.	N/A
<input checked="" type="checkbox"/>	Address reliability requirements, such as appropriate location of shutoff valves.	Site Servicing Report (Section 2.0)
<input type="checkbox"/>	Check on the necessity of a pressure zone boundary modification.	N/A
<input checked="" type="checkbox"/>	Reference to water supply analysis to show that major infrastructure can deliver sufficient water for the proposed land use. This includes data that shows that the expected demands under average day, peak hour and fire flow conditions provide water within the required pressure range.	Site Servicing Report (Section 2.0)
<input checked="" type="checkbox"/>	Description of the proposed water distribution network, including locations of proposed connections to the existing system, provisions for necessary looping, and appurtenances (valves, pressure reducing valves, valve chambers, and fire hydrants), including special metering provisions.	Site Servicing Report (Section 2.0) Servicing Plan
<input type="checkbox"/>	Description of off-site required feedermains, booster pumping stations, and other water infrastructure that will be ultimately required to service proposed development, including financing, interim facilities, and timing of implementation.	N/A
<input checked="" type="checkbox"/>	Confirmation that water demands are calculated based on the City of Ottawa Design Guidelines.	Site Servicing Report (Section 2.0)
<input checked="" type="checkbox"/>	Provision of a model schematic showing the boundary conditions locations, streets, parcels, and building locations for reference.	Site Servicing Report (Section 2.0)

4.3	SITE SERVICING REPORT: WASTEWATER	REFERENCE
<input checked="" type="checkbox"/>	Summary of proposed design criteria (Note: Wet weather flow criteria should not deviate from the City of Ottawa Sewer Design Guidelines. Monitored flow data from relatively new infrastructure cannot be used to justify capacity requirements for proposed infrastructure).	Site Servicing Report (Section 3.0,
<input type="checkbox"/>	Confirm consistency with Master Servicing Study and/or justifications for deviations.	Stantec 2005 EUC ISSU
<input type="checkbox"/>	Consideration of local conditions that may contribute to extraneous flows that are higher than the recommended flows in the Guidelines. This includes groundwater and soil conditions, and age and condition of sewers.	N/A
<input checked="" type="checkbox"/>	Description of existing sanitary sewer available for discharge of wastewater from proposed development.	Site Servicing Report (Section 3.0) Servicing Plan

<input checked="" type="checkbox"/>	Verify available capacity in downstream sanitary sewer and/or identification of upgrades necessary to service the proposed development. (Reference can be made to previously completed Master Servicing Study if applicable.)	Site Servicing Report (Section 3.0)
<input checked="" type="checkbox"/>	Calculations related to dry weather and wet weather flow rates from the development in standard MOE sanitary sewer design table (Appendix 'C') format.	Site Servicing Report (Section 3.0)
<input checked="" type="checkbox"/>	Description of proposed sewer network, including sewers, pumping stations and forcemains.	Site Servicing Report (Section 3.0) Servicing Plan
<input type="checkbox"/>	Discussion of previously identified environmental constraints and impact on servicing (environmental constraints are related to limitations imposed on the development in order to preserve the physical condition of watercourses, vegetation, soil cover, as well as protecting against water quantity and quality).	N/A
<input type="checkbox"/>	Pumping stations: impacts of proposed development on existing pumping stations or requirements for new pumping station to service development.	N/A
<input type="checkbox"/>	Forcemain capacity in terms of operational redundancy, surge pressure and maximum flow velocity.	N/A
<input type="checkbox"/>	Identification and implementation of the emergency overflow from sanitary pumping stations in relation to the hydraulic grade line to protect against basement flooding.	N/A
<input type="checkbox"/>	Special considerations, such as contamination, corrosive environment, etc.	N/A

4.4	SITE SERVICING REPORT: STORMWATER	REFERENCE
<input checked="" type="checkbox"/>	Description of drainage outlets and downstream constraints, including legality of outlets (i.e., municipal drain, right-of-way, watercourse, or private property).	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	Analysis of available capacity in existing public infrastructure.	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	A drawing showing the subject lands, its surroundings, the receiving watercourse, existing drainage patterns, and proposed drainage pattern.	Servicing, Grading and Drainage Plans
<input checked="" type="checkbox"/>	Water quantity control objective (e.g. controlling post-development peak flows to pre-development level for storm events ranging from the 2 or 5 year event (dependent on the receiving sewer design) to 100 year return period); if other objectives are being applied, a rationale must be included with reference to hydrologic analyses of the potentially affected subwatersheds, taking into account long-term cumulative effects.	Site Servicing Report (Section 4.0)

<input checked="" type="checkbox"/>	Water Quality control objective (basic, normal or enhanced level of protection based on the sensitivities of the receiving watercourse) and storage requirements.	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	Description of the stormwater management concept with facility locations and descriptions with references and supporting information.	Site Servicing Report (Section 4.0) Servicing, Grading and Drainage Plans
<input type="checkbox"/>	Setback from private sewage disposal systems.	N/A
<input type="checkbox"/>	Watercourse and hazard lands setbacks.	N/A
<input checked="" type="checkbox"/>	Record of pre-consultation with the Ontario Ministry of Environment and the Conservation Authority that has jurisdiction on the affected watershed.	Site Servicing Report (Appendix 'A')
<input type="checkbox"/>	Confirm consistency with subwatershed and Master Servicing Study, if applicable study exists.	Stantec 2005 EUC ISSU
<input checked="" type="checkbox"/>	Storage requirements (complete with calculations) and conveyance capacity for minor events (1:2 year return period) and major events (1:100 year return period).	Site Servicing Report (Section 4.0)
<input type="checkbox"/>	Identification of watercourses within the proposed development and how watercourses will be protected, or, if necessary, altered by the proposed development with applicable approvals.	N/A
<input checked="" type="checkbox"/>	Calculate pre- and post-development peak flow rates, including a description of existing site conditions and proposed impervious areas and drainage catchments in comparison to existing conditions.	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	Any proposed diversion of drainage catchment areas from one outlet to another.	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	Proposed minor and major systems, including locations and sizes of stormwater trunk sewers, and stormwater management facilities.	Servicing, Grading and Drainage Plans
<input type="checkbox"/>	If quantity control is not proposed, demonstration that downstream system has adequate capacity for the post-development flows up to and including the 100-year return period storm event.	Quantity control proposed per Site Servicing Report (Section 4.0)
<input type="checkbox"/>	Identification of potential impacts to receiving watercourses.	N/A
<input type="checkbox"/>	Identification of municipal drains and related approval requirements.	N/A
<input checked="" type="checkbox"/>	Description of how the conveyance and storage capacity will be achieved for the development.	Site Servicing Report (Section 4.0)

<input checked="" type="checkbox"/>	100 year flood levels and major flow routing to protect proposed development from flooding for establishing minimum building elevations (MBE) and overall grading.	Site Servicing Report (Section 4.0) Servicing, Grading and Drainage Plans
<input checked="" type="checkbox"/>	Inclusion of hydraulic analysis, including hydraulic grade line elevations.	Site Servicing Report (Section 4.0)
<input checked="" type="checkbox"/>	Description of approach to erosion and sediment control during construction for the protection of receiving watercourse or drainage corridors.	Site Servicing Report (Section 5.0) Servicing Plan
<input type="checkbox"/>	Identification of floodplains – proponent to obtain relevant floodplain information from the appropriate Conservation Authority. The proponent may be required to delineate floodplain elevations to the satisfaction of the Conservation Authority if such information is not available or if information does not match current conditions.	N/A
<input type="checkbox"/>	Identification of fill constraints related to floodplain and geotechnical investigation.	N/A

4.5 APPROVAL AND PERMIT REQUIREMENTS		REFERENCE
The Site Servicing Report shall provide a list of applicable permits and regulatory approvals necessary for the proposed development, as well as the relevant issues affecting such approval. The approval and permitting shall include but not be limited to the following:		
<input type="checkbox"/>	Conservation Authority as the designated approval agency for modification of floodplain, potential impact on fish habitat, proposed works in or adjacent to a watercourse, cut/fill permits and Approval under Lakes and Rivers Improvement Act. The Conservation Authority is not the approval authority for the Lakes and Rivers Improvement Act. Where there are Conservation Authority regulations in place, approval under the Lakes and Rivers Improvement Act is not required, except in cases of dams, as defined in the Act.	N/A
<input type="checkbox"/>	Application for Environmental Compliance Approval (ECA) under the Ontario Water Resources Act.	As part of future submission
<input type="checkbox"/>	Changes to Municipal Drains.	N/A
<input type="checkbox"/>	Other permits (National Capital Commission, Parks Canada, Public Works and Government Services Canada, Ministry of Transportation, etc.).	N/A

4.6 CONCLUSION CHECKLIST		REFERENCE
<input checked="" type="checkbox"/>	Clearly stated conclusions and recommendations.	Site Servicing Report
<input checked="" type="checkbox"/>	Comments received from review agencies, including the City of Ottawa and information on how the comments were addressed. Final sign-off from the responsible reviewing agency.	Not yet applicable

<input checked="" type="checkbox"/>	All draft and final reports shall be signed and stamped by a Professional Engineer registered in Ontario.	Site Servicing Report All Drawings

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix C

Water Servicing

WATERMAIN DEMAND CALCULATION SHEET

PROJECT : NAVAN ROAD DEVELOPMENT PROJECT - GAS BAR
LOCATION : CITY OF OTTAWA
DEVELOPER : 12714001 Canada Inc.

NODE	RESIDENTIAL		NON-RESIDENTIAL COMM (ha.)	AVERAGE DAILY DEMAND (l/s)				MAXIMUM DAILY DEMAND (l/s)				PEAK HOUR DEMAND (l/s)				
	UNITS			Res.	Non-res.	Plug flow	Total	Res.	Non-res.	Plug flow	Total	Res.	Non-res.	Plug flow	Total	
	Townhouses (TH)	Condo Units (CU)														
J-14	0	0	0	0.77	0.00	0.25	3.60	3.85	0.00	0.37	3.60	3.97	0.00	0.67	3.60	4.27
TOTALS	0	0	0	0.77	0.00	0.25	3.60	3.85	0.00	0.37	3.60	3.97	0.00	0.67	3.60	4.27

ASSUMPTIONS									
RESIDENTIAL DENSITIES			AVG. DAILY DEMAND			MAX. HOURLY DEMAND			
- Townhouse (TH)	2.7	p / p / u	- Residential		280 l / cap / day	- Residential			1,540 l / cap / day
- Condo Units (CU)	1.8	p / p / u	- Institutional		28,000 l / ha / day	- Institutional			75,600 l / ha / day
		p / p / u	- Commercial		28,000 l / ha / day	- Commercial			75,600 l / ha / day
			MAX. DAILY DEMAND						
		p / p / u	- Residential		700 l / cap / day				
			- Institutional		42,000 l / ha / day				
			- Commercial		42,000 l / ha / day				

FUS Fire Flow Calculations
NAVAN ROAD DEVELOPMENT PROJECT - Commercial Building
(JLR 29899-002)

Step	Parameter	Value	Note
A	Type of Construction	Non-combustible	
	Coefficient (C)	0.8	
B	Ground Floor Area	686	m ²
			Commercial area consisting of a Gas Retail and Drive Thru
C	Height in storeys	1	storeys
	Total Floor Area	686	m ²
D	Fire Flow Formula	$F=220C\sqrt{A}$	
	Fire Flow	4610	L/min
	Rounded Fire Flow	5000	L/min
			Flow rounded to nearest 1000 L/min.
E	Occupancy Class	Combustible	
	Occupancy Charge	0%	
	Occupancy Increase or Decrease	0	
	Fire Flow	5000	L/min
F	Sprinkler Protection	None	
	Sprinkler Credit	0%	
	Decrease for Sprinkler	0	L/min
G	North Side Exposure		
	Exposing Wall:	Non-combustible	Gas Retail/Drive Thru
	Exposed Wall:	Wood Frame	4 Storey Condo Unit
	Length of Exposed Wall:	32.2	m
	Height of Exposed Wall:	4	storeys
	Length-Height Factor	128.6	m-storeys
	Separation Distance	38.96	m
	North Side Exposure Charge	5%	
	East Side Exposure		
	Exposing Wall:	Non-combustible	Gas Retail/Drive Thru
	Exposed Wall:	Wood Frame	
	Length of Exposed Wall:	0.0	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	46	m
	East Side Exposure Charge	0%	
	South Side Exposure		
	Exposing Wall:	Non-combustible	
	Exposed Wall:	Wood Frame	
	Length of Exposed Wall:	0.0	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	46	m
	South Side Exposure Charge	0%	Over 45 m to next structure
	West Side Exposure		
	Exposing Wall:	Non-combustible	Gas Retail/Drive Thru
	Exposed Wall:	Wood Frame	
	Length of Exposed Wall:	0.0	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	46	m
	West Side Exposure Charge	0%	Over 200 m to next structure
	Total Exposure Charge	5%	The total exposure charge is below the maximum value of 75%.
	Increase for Exposures	250	L/min
H	Fire Flow	5250	L/min
	Rounded Fire Flow	5000	L/min
			Flow rounded to nearest 1000 L/min.
City Cap	Required Fire Flow (RFF)	5000	L/min
		83	L/s

Fire Underwriters Survey (FUS) Fire Flow Calculations
In accordance with City of Ottawa Technical Bulletin ISTB-2018-02 dated March 21, 2018

FUS Fire Flow Calculations

NAVAN ROAD DEVELOPMENT PROJECT - Commercial Building
(JLR 29899-002)

Step	Parameter	Value	Note
A	Type of Construction	Non-combustible	
	Coefficient (C)	0.8	
B	Ground Floor Area	107	m ²
C	Height in storeys	1	storeys
	Total Floor Area	107	m ²
D	Fire Flow Formula	$F=220C\sqrt{A}$	
	Fire Flow	1821	L/min
	Rounded Fire Flow	2000	L/min
			Flow rounded to nearest 1000 L/min.
E	Occupancy Class	Combustible	
	Occupancy Charge	0%	
	Occupancy Increase or Decrease	0	
	Fire Flow	2000	L/min
F	Sprinkler Protection	None	
	Sprinkler Credit	0%	
	Decrease for Sprinkler	0	L/min
G	North Side Exposure		
	Exposing Wall:	Non-combustible	Car Wash
	Exposed Wall:	Wood Frame	Townhomes
	Length of Exposed Wall:	14.4	m
	Height of Exposed Wall:	2	storeys
	Length-Height Factor	28.9	m-storeys
	Separation Distance	18.81	m
	North Side Exposure Charge	12%	
	East Side Exposure		
	Exposing Wall:	Non-combustible	Car Wash
	Exposed Wall:	Wood Frame	
	Length of Exposed Wall:	0.0	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	46	m
	East Side Exposure Charge	0%	
	South Side Exposure		
	Exposing Wall:	Non-combustible	Car Wash
	Exposed Wall:	Non-combustible	Gas Retail/Drive Thru
	Length of Exposed Wall:	5.4	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	32.22	m
	South Side Exposure Charge	5%	Over 45 m to next structure
	West Side Exposure		
	Exposing Wall:	Non-combustible	Gas Retail/Drive Thru
	Exposed Wall:	Wood Frame	
	Length of Exposed Wall:	0.0	m
	Height of Exposed Wall:	0	storeys
	Length-Height Factor	0.0	m-storeys
	Separation Distance	46	m
	West Side Exposure Charge	0%	Over 200 m to next structure
	Total Exposure Charge	17%	The total exposure charge is below the maximum value of 75%.
	Increase for Exposures	340	L/min
H	Fire Flow	2340	L/min
	Rounded Fire Flow	2000	L/min
	Required Fire Flow (RFF)	2000	L/min
		33	L/s

Fire Underwriters Survey (FUS) Fire Flow Calculations
In accordance with City of Ottawa Technical Bulletin ISTB-2018-02 dated March 21, 2018

William Rugamba

From: William Rugamba
Sent: July 15, 2024 4:00 PM
To: William Rugamba
Subject: FW: Navan Subdivision - Boundary Condition Request
Attachments: NavanSubdivision_Boundary Condition(4july2024).docx

William Rugamba, M.Eng., B.A.Sc., EIT

Civil Engineering Graduate

Ottawa, ON

Work: [343-804-4374](tel:343-804-4374)

From: Polyak, Alex <alex.polyak@ottawa.ca>
Sent: Monday, July 15, 2024 10:12 AM
To: Mahad Musse <mmusse@jlrichards.ca>
Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; Carmine Zayoun <carmine@zayoungroup.com>; Armstrong, Justin <justin.armstrong@ottawa.ca>; Tatyana Roumie <troumie@jlrichards.ca>
Subject: RE: Navan Subdivision - Boundary Condition Request

[CAUTION] This email originated from outside JLR. Do not click links or open attachments unless you recognize the sender and know the content is safe. Do not forward suspicious emails, if you are unsure, please send a separate message to Helpdesk.

Good morning Mahad,

Please find the boundary conditions attached.

Regards,

Oleksandr (Alex) Polyak, B.Eng., C.E.T., P.Eng. 

Project Manager, Infrastructure Approvals, Development Review East Branch | Gestionnaire de projet, Direction de l'examen des projets d'aménagement – Est.
Planning, Development and Building Services Department (PDBS) | Direction générale des services de la planification, de l'aménagement et du bâtiment (DGSPAB)

City of Ottawa | Ville d'Ottawa
110 Laurier Ave., 4th Fl East, Ottawa ON K1P 1J1
Email: alex.polyak@ottawa.ca
Cell : 613-857-4380
www.Ottawa.ca



From: Mahad Musse <mmusse@jlrichards.ca>
Sent: July 12, 2024 1:31 PM
To: Polyak, Alex <alex.polyak@ottawa.ca>
Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; Carmine Zayoun <carmine@zayoungroup.com>; Armstrong, Justin <justin.armstrong@ottawa.ca>; Tatyana Roumie <troumie@jlrichards.ca>
Subject: RE: Navan Subdivision - Boundary Condition Request

CAUTION: This email originated from an External Sender. Please do not click links or open attachments unless you recognize the source.

ATTENTION : Ce courriel provient d'un expéditeur externe. Ne cliquez sur aucun lien et n'ouvrez pas de pièce jointe, excepté si vous connaissez l'expéditeur.

Hi Alex,

Just wondering if you have a status update for the boundary conditions for Navan.

Thanks
Mahad



Mahad Musse, B.Eng., EIT
Civil Engineering Graduate

1000-343 Preston Street
Ottawa, ON, K1S 1N4



Work: [343-633-1501](tel:343-633-1501)
mmusse@jlrichards.ca



From: Mahad Musse <mmusse@jlrichards.ca>

Sent: Wednesday, July 3, 2024 11:02 AM

To: Polyak, Alex <alex.polyak@ottawa.ca>

Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; Carmine Zayoun <carmine@zayoungroup.com>; Armstrong, Justin <justin.armstrong@ottawa.ca>; Tatyana Roumie <troumie@jlrichards.ca>

Subject: RE: Navan Subdivision - Boundary Condition Request

Good morning Alex,

As we discussed last week our Client is looking into the option of converting the row townhouse units into duplex units (townhouse units with apartments in the basement). As a result, this will increase the total demand on the site and we will therefore require new water boundary conditions. We'd like to note that the footprint of the blocks will not change and neither will their layout or any of the offsets.

As a summary:

- Domestic demands were calculated based on a daily consumption rate of 280 L/cap/day with peaking factors consistent with City of Ottawa Guidelines
- Required Fire Flow (RFF) was calculated in accordance to the Fire Underwriters Survey (FUS) Water Supply for Public Fire Protection and the City of Ottawa FUS protocol (Bulletin ISDTB-2014-02 & Bulletin ISDTB-2018-02), which considers material, expose distance & height. We have attached the calculation spreadsheet and the figure.

We request boundary conditions under high pressure, peak hour, and maximum day + fire flow conditions (for each of the below fire flows). Domestic demand and fire flow calculations are attached. Please provide the boundary conditions at the proposed connection locations as shown in the attached figure.

Average Day Demand: 6.74 L/s

Maximum Day Demand: 10.53 L/s

Peak Hour Demand: 18.17 L/s

Required Fire Flow (per FUS): 6,000 L/min (100 L/s)

Required Fire Flow (per FUS): 10,000 L/min (167 L/s)

Required Fire Flow (per FUS): 14,000 L/min (233 L/s)

Required Fire Flow (per FUS): 15,000 L/min (250 L/s)

For your reference, the previous boundary condition received from the City is attached and below is the email chain.

If you have any questions or comments please let us know.

Thanks
Mahad



Mahad Musse, B.Eng., EIT
Civil Engineering Graduate

1000-343 Preston Street
Ottawa, ON, K1S 1N4

Work: [343-633-1501](tel:343-633-1501)
mmusse@jlrichards.ca

From: Polyak, Alex <alex.polyak@ottawa.ca>
Sent: Thursday, August 17, 2023 3:01 PM
To: William Rugamba <wrugamba@jlrichards.ca>
Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; Carmine Zayoun <carmine@zayoungroup.com>; Shahira Jalal <sjalal@jlrichards.ca>
Subject: RE: Navan Subdivision - Boundary Condition Request

[CAUTION] This email originated from outside JLR. Do not click links or open attachments unless you recognize the sender and know the content is safe. Do not forward suspicious emails, if you are unsure, please send a separate message to Helpdesk.

Hello William,

Sorry that I missed your call, I was in a meeting. The boundary conditions are attached.

Regards,

Oleksandr (Alex) Polyak, B.Eng., P.Eng

Project Manager, Infrastructure Approvals, Development Review East Branch | Gestionnaire de projet, Direction de l'examen des projets d'aménagement – Est.
Planning, Real Estate and Economic Development Department | Direction générale de la planification, des biens immobiliers et du développement économique

City of Ottawa | Ville d'Ottawa
110 Laurier Ave., 4th Fl East, Ottawa ON K1P 1J1
Email: alex.polyak@ottawa.ca
Cell : 613-857-4380
www.Ottawa.ca



From: William Rugamba <wrugamba@jlrichards.ca>
Sent: August 15, 2023 9:26 AM
To: Polyak, Alex <alex.polyak@ottawa.ca>
Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; Carmine Zayoun <carmine@zayoungroup.com>; Shahira Jalal <sjalal@jlrichards.ca>
Subject: RE: Navan Subdivision - Boundary Condition Request

CAUTION: This email originated from an External Sender. Please do not click links or open attachments unless you recognize the source.

ATTENTION : Ce courriel provient d'un expéditeur externe. Ne cliquez sur aucun lien et n'ouvrez pas de pièce jointe, excepté si vous connaissez l'expéditeur.

Good morning Alex,

Just wanted to follow up on the status of this boundary request. Please let me know if you need anything else from us.

Thanks,
William

William Rugamba, M.Eng.
Civil Engineering Intern

J.L. Richards & Associates Limited
1000-343 Preston Street, Ottawa, ON K1S 1N4
Direct: 343-804-4374



From: Tatyana Roumie
Sent: Tuesday, July 25, 2023 3:53 PM
To: 'alex.polyak@ottawa.ca' <alex.polyak@ottawa.ca>
Cc: Karla Ferrey <kferrey@jlrichards.ca>; Raad Akrawi <rakrawi@groupeheafey.com>; carmine <carmine@zayoungroup.com>; Shahira Jalal <sjalal@jlrichards.ca>
Subject: Navan Subdivision - Boundary Condition Request

Hello Alex.

To support our upcoming detailed design for the site, we are requesting updated boundary conditions for the 3079 Navan Road Development.

As a brief history, we received boundary conditions from the City in July 2021 (attached, but with incorrect connection locations) and again in April 2022 (also attached) in support of the functional servicing design. We understand from the April 2022 boundary conditions that the maximum available fire flow for the site is 250 L/s.

We are currently requesting updated boundary conditions for this site as we are commencing the detailed servicing design and this request will accommodate the recent site plan changes and proposed connection points. This request is also applicable to the upcoming site plan designs which will be submitted as separate applications.

We request boundary conditions under high pressure, peak hour, and maximum day + fire flow conditions (for each of the below fire flows). Domestic demand and fire flow calculations are attached. Please provide the boundary conditions at the proposed connection locations as shown in the attached figure.

Average Day Demand: 6.44 L/s

Maximum Day Demand: 9.77 L/s

Peak Hour Demand: 16.50 L/s

Required Fire Flow (per FUS): 6,000 L/min (100 L/s)

Required Fire Flow (per FUS): 10,000 L/min (167 L/s)

Required Fire Flow (per FUS): 14,000 L/min (233 L/s)

Required Fire Flow (per FUS): 15,000 L/min (250 L/s)

Thanks,
Tatyana

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.

Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.


Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

Boundary Conditions Navan Subdivision

Provided Information

Scenario	Demand	
	L/min	L/s
Average Daily Demand	404	6.74
Maximum Daily Demand	632	10.53
Peak Hour	1,090	18.17
Fire Flow Demand #1	6,000	100.00
Fire Flow Demand #2	10,000	166.67
Fire Flow Demand #3	14,000	233.33
Fire Flow Demand #4	15,000	250.00

Location



Results

Connection 1 - Page Road

Demand Scenario	Head (m)	Pressure ¹ (psi)
Maximum HGL	130.7	64.0
Peak Hour	127.0	58.6
Max Day plus Fire Flow #1	128.2	60.4
Max Day plus Fire Flow #2	126.8	58.3
Max Day plus Fire Flow #3	124.9	55.7
Max Day plus Fire Flow #4	124.4	55.0

¹ Ground Elevation = 85.7 m

Connection 2 - Navan Road East

Demand Scenario	Head (m)	Pressure ¹ (psi)
Maximum HGL	130.7	71.4
Peak Hour	126.8	65.9
Max Day plus Fire Flow #1	127.7	67.1
Max Day plus Fire Flow #2	125.5	64.1
Max Day plus Fire Flow #3	122.7	60.1
Max Day plus Fire Flow #4	121.9	58.9

¹ Ground Elevation = 80.5 m

Connection 3 - Navan Road West


Demand Scenario	Head (m)	Pressure ¹ (psi)
Maximum HGL	130.7	69.3
Peak Hour	126.8	63.8
Max Day plus Fire Flow #1	127.3	64.5
Max Day plus Fire Flow #2	124.6	60.6
Max Day plus Fire Flow #3	120.9	55.3
Max Day plus Fire Flow #4	119.8	53.8

¹ Ground Elevation = 81.9 m

Disclaimer

The boundary condition information is based on current operation of the city water distribution system. The computer model simulation is based on the best information available at the time. The operation of the water distribution system can change on a regular basis, resulting in a variation in boundary conditions. The physical properties of water mains deteriorate over time, as such must be assumed in the absence of actual field test data. The variation in physical watermain properties can therefore alter the results of the computer model simulation. Fire Flow analysis is a reflection of available flow in the watermain; there may be additional restrictions that occur between the watermain and the hydrant that the model cannot take into account.


Gas Bar, Commercial Building, and Car Wash (Block 16)
Model Schematic



Gas Bar, Commercial Building, and Car Wash (Block 16)


Model Schematic

Elevation Model



Gas Bar, Commercial Building, and Car Wash (Block 16)

Peak Hour Demand



Gas Bar, Commercial Building, and Car Wash (Block 16)

Peak Hour Demand

Junction Table

Label	Elevation (m)	Demand (L/s)	Hydraulic Grade (m)	Pressure (kPa)
J-14	86.00	4.27	126.74	399
J-13	85.50	0.00	126.79	404


Gas Bar, Commercial Building, and Car Wash (Block 16)

Peak Hour Demand

Pipe Table

ID	Label	Length (Scaled) (m)	Diameter (mm)	Material	Hazen-Williams C	Flow (L/s)	Velocity (m/s)
61	P-20	11	155	PVC	100.0	4.27	0.23
175	P-21(1)	49	155	PVC	100.0	4.27	0.23
176	P-21(2)	22	155	PVC	100.0	4.27	0.23

Gas Bar, Commercial Building, and Car Wash (Block 16)
Max Day + Fire Flow Requirement




Gas Bar, Commercial Building, and Car Wash (Block 16)

Max Day + Fire Flow Requirement

Label	Satisfies Fire Flow Constraints?	Fire Flow (Available) (L/s)	Flow (Total Available) (L/s)	Pressure (Residual Lower Limit) (kPa)	Pressure (Calculated Residual) (kPa)	Pressure (Calculated System Lower Limit) (kPa)	Junction w/ Minimum Pressure (System)
H-19	True	100	100	140	224	238	J-14

Gas Bar, Commercial Building, and Car Wash (Block 16)

Maximum Pressure Analysis



Gas Bar, Commercial Building, and Car Wash (Block 16)

Maximum Pressure Analysis

Junction Table

Label	Elevation (m)	Demand (L/s)	Hydraulic Grade (m)	Pressure (kPa)
J-14	86.00	0	130.70	437
J-13	85.50	0	130.70	442

Gas Bar, Commercial Building, and Car Wash (Block 16)

Maximum Pressure Analysis

Pipe Table

ID	Label	Length (Scaled) (m)	Diameter (mm)	Material	Hazen-Williams C	Flow (L/s)	Velocity (m/s)
61	P-20	11	155	PVC	100.0	0	0.00
175	P-21(1)	49	155	PVC	100.0	0	0.00
176	P-21(2)	22	155	PVC	100.0	0	0.00

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix D

Sanitary Design Sheet

Street Name	MH No.		Residential							Commercial/Institutional					Infiltration			Peak Design Flow L/s	Pipe Data							Upstream Geometry				Downstream Geometry							
	From	To	Multiples	Apartments	Area (ha)	Pop.	Cum. Pop.	Cum. Area (ha)	Peaking Factor	Residential Flow (L/s)	Area (ha)	Cum. Area (ha)	Peaking Factor	Inst. Flow (L/s)	Plug Flow (L/s)	Area (ha)	Cum. Area (ha)	Peak Extr. Flow L/s	Dia	Type	Actual Diameter	Slope	Q Full (L/s)	V Full	Length	Residual Capacity	% Full	TG From	Obvert	Invert	Cover	TG TO	Drop	Obvert	Invert	Cover	
GAS STATION	GAS BAR	22			0.00	0	0	0.00	3.80	0.00	0.77	0.77	1.50	0.37		0.77	0.77	0.25	0.63	200	Circular	203.20	1.00%	34.22	1.06	27.26	33.59	2%	86.000	83.369	83.165	2.631	85.590	0.510	83.096	82.893	2.494
GAS STATION	CAR WASH	22			0.00	0	0	0.00	3.80	0.00		0.00	1.50	0.00	3.60	0.00	0.00	0.00	3.60	200	Circular	203.20	1.00%	34.22	1.06	5.91	30.62	11%	85.770	82.705	82.502	3.065	85.590	0.060	82.646	82.443	2.944
GAS STATION TO EXISTING STUB	22	STUB 16			0.00	0	0	0.00	3.80	0.00		0.77	1.50	0.37	3.60	0.00	0.77	0.25	4.23	200	Circular	203.20	0.65%	27.59	0.85	2.02	23.36	15%	85.590	82.586	82.383	3.004	85.350		82.573	82.370	2.777
EXISTING STUB TO PALEO DRIVE	STUB 16	21			0.04	0	0	0.04	3.80	0.00	0.77	1.50	0.37	3.60	0.04	0.81	0.27	4.24	200	Circular	203.20	0.65%	27.59	0.85	38.75	23.34	15%	85.350	82.573	82.370	2.777	85.041		82.321	82.118	2.720	
			0	0	0.00	0																															

Design Parameters	
Single Family Population	3.4 Cap/Unit
Semi-Detached/Townhouse Population	2.7 Cap/Unit
Apartments Population	1.8 Cap/Unit
Residential Flows	0.30 L/Cap/Day
Infiltration Flows	0.33 L/s/ha
Correction Factor	0.8
Commercial Peak Factor	-
Institutional/Commercial Average Flow	28000 L/gross half d
Manning Coefficient	0.013



Friday, August 16, 2024

J. L. Richards
1000-343 Preston St.
Ottawa, Ontario, K1S 1N4

Attn: W. Rugamba

Re: 2983 Navan Road, Ontario - Gas Bar-Commercial-QM&E Project # 23-047
Confirmations

Dear William,

This letter serves as confirmation of items you sent by e-mail August 12, 2024.

1. Maximum domestic water flow rate is 57 gpm (3.60 L/s).
2. That quantity was arrived at by referring to data provided by the client's car wash specialist.
3. The design of the oil interceptor has been completed, it will be located entirely within the walls of the car wash building.

Please do not hesitate to contact us should you have any questions or comments.

Yours truly,

A handwritten signature in black ink that reads "C.W. Clark".

C. W. Clark, P.Eng
QM&E Engineering
CC: by you to whom it may concern

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix E

Storm Design Sheet

JLR NO. 29899-002 (NAVAN BLOCK 14)

PIPE REACH			Peak Flow Estimation												Sewer Data						Upstream Geometry				Downstream Geometry				Self Cleansing Velocities									
LOCATION	From MH	To MH	C-Factor (1:2)		Total Area (ha)	Cum. Total Area (ha)	Inlet Time (min.)	In Pipe Flow Time (min)	1:2 Year Storm (RATIONAL METHOD)			Plug Flows	Total Peak Flow ⁽⁶⁾ (L/s)	Type	Nominal Dia. (mm)	Actual Dia. (mm)	Slope	Length (m)	Q Full (L/s)	V Full (m/s)	Residual Capacity ⁽⁶⁾ (L/s)	% Full	TG From	Obvert	Invert	Cover	TG To	Drop	Obvert	Invert	Cover	Q/Q Ratio	Flow Depth (mm)	Actual Velocity ⁽⁷⁾ (m/s)	Flow Depth to Dia. Ratio (d/D)			
			0.20	0.90					2.78AR	Cum. 2.78AR	1:2 Year Intensity (mm/hr)		Orifice Flow ⁽¹⁾ MH518 (L/s)																									
GAS STATION	MH520	MH519	0.055	0.265	0.32	0.32	10.00	0.75	10.75	0.69	0.69	76.81	53.33		53.33	CONCRETE	525	533.40	0.40%	57.15	284.46	1.27	231.14	19%	85.374	83.320	82.787	2.05	85.709	0.060	83.090	82.557	2.62	0.19	156.29	0.98	0.29	
GAS STATION	MH519	MH518			0.00	0.32	10.75	0.38	11.12	0.00	0.69	74.05	51.41		51.41	CONCRETE	525	533.40	0.50%	31.97	317.25	1.42	265.84	16%	85.709	83.030	82.497	2.68	85.468	1.052	82.871	82.337	2.60	0.16	145.08	1.04	0.27	
GAS STATION	MH522	MH521	0.066	0.168	0.23	0.23	10.00	0.53	10.53	0.46	0.46	76.81	35.15		35.15	CONCRETE	525	533.40	0.50%	45.09	317.25	1.42	282.10	11%	85.505	83.016	82.482	2.49	85.630		82.790	82.257	2.84	0.11	119.48	0.93	0.22	
GAS STATION	MH521	MH518	0.030	0.149	0.18	0.41	10.53	0.38	10.91	0.39	0.85	74.83	63.33		63.33	CONCRETE	525	533.40	0.35%	27.21	265.81	1.19	202.48	24%	85.630	82.790	82.257	2.84	85.468	0.876	82.695	82.161	2.77	0.24	177.09	0.98	0.33	
GAS STATION	MH518	MH518A	0.021	0.016	0.04	0.77	11.12	0.29	11.41	0.05	1.59	72.74	115.83		66.14	66.14	CONCRETE	450	457.20	0.25%	15.62	148.72	0.91	32.89	78%	85.468	81.819	81.361	3.65	85.591	0.300	81.780	81.322	3.81	0.44	213.51	0.88	0.47
EAST ORLEANS RIDGE SUBDIVISION	EXST MH518A	EXST MH514 ⁽⁸⁾			Refer to Note 8	1.07	11.41	0.83	12.24	2.29	2.29	71.78	164.59		Refer to Note 8	CONCRETE	525	533.40	0.25%	50.21	224.33	1.00	69.74	73%	85.400	81.480	80.946	3.92	84.620		81.354	80.821	3.27		Refer to Note 8			

Design Parameters (Per OSDG)
Manning's Coefficient = 0.013
1:2 Year Intensity = $732.951 / (T_c + 6.199)^{0.810}$

Note: Tc is the time of concentration in minutes


Drainage Areas Breakdown
Total Site Area: 0.77 ha
Controlled Area Within Site Property Line: 0.77 ha →
Existing Navan Rd Rear-Yard Area Captured Within Site: 0.05 ha
Block 15 Rear-Yard area captured in 518A-514: 0.07 ha
Subdivision Block 11 Rear-Yard Area in 518A-514: 0.14
Existing Navan Rd Rear-Yard Area Captured in 518A-514: 0.04
Total Captured Areas: 1.07
Uncontrolled Area - Outlet to Subdivision: 0.00 ha →

Notes on Plug Flows
(1) Orifice Flow Rate from Block 16
Notes on Peak Flow and Pipe Sizing
(5) Peak flows are lower than the allowable release rate for Block 16 (68 L/s)
(6) Pipes are conservatively sized for 1:2 Year Peak Flow Rate
(7) Actual Velocities based on actual peak flows from Note 5
(8) Details from Existing Sewers Downstream of EXST MH518A (referred to as STUB 16) can be found within East Orleans Ridge Subdivision Design Sheet. This line is only used to carry over the downstream values for time of concentration and 1:2 year peak flow

Site Servicing Report
2983 Navan Road – Block 16
Gas Station, Commercial Building, Drive-Thru Restaurant & Car Wash

Appendix F

Stormwater Management



Legend

Junctions	Conduits
Outfalls	Storm Sewers
Storages	Storm Sewers
Manholes	Weirs
Catchbasins	Outlets
	Subcatchments



35 m

PROJECT:

2983 Navan Road - Block 16
Ottawa ON


DRAWING:

Overall System Model Schematic

J.L.Richards
ENGINEERS · ARCHITECTS · PLANNERS

This drawing is copyright protected and
may not be reproduced or used for purposes
other than execution of the described work
without the express written consent of J.L.
Richards & Associates Limited.

DESIGN:	ML	JLR NO.:	29899-002
DRAWN:	ML	DRAWING NO.:	
CHECKED:	BP		Figure 3



LEGEND:

— PRE-DEVELOPMENT DRAINAGE AREAS

■ NAVAN SITE PLAN AND SUBDIVISION BOUNDARY

NOTE:
UNDERLYING CATCHMENT DELINEATION FROM GLOUCESTER EUC INFRASTRUCTURE
SERVICING UPDATE 2005 WHICH INFORMED THE ALLOWABLE RELEASE RATES FROM
THE SITE AND NO PRE-DEVELOPMENT MODELLING WAS REQUIRED

PROJECT:

2983, 3053 AND 3079 NAVAN RD & 2690 PAGE RD

DRAWING:

PRE-DEVELOPMENT DRAINAGE PLAN



www.jlrichards.ca

This drawing is copyright protected and may
not be reproduced or used for purposes
other than execution of the described work
without the express written consent of
J.L. Richards & Associates Limited.

DESIGN:	BP
DRAWN:	KC
CHECKED:	BP
JLR #:	29899-002

FIGURE

Post-Development 3-hour Chicago 1:2 year Event

[TITLE]
;;Project Title/Notes

[OPTIONS]
;;Option Value
FLOW_UNITS LPS
INFILTRATION HORTON
FLOW_ROUTING DYNWAVE
LINK_OFFSETS ELEVATION
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO

START_DATE 01/01/2000
START_TIME 00:00:00
REPORT_START_DATE 01/01/2000
REPORT_START_TIME 00:00:00
END_DATE 01/01/2000
END_TIME 06:00:00
SWEEP_START 01/01
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 00:01:00
WET_STEP 00:01:00
DRY_STEP 00:01:00
ROUTING_STEP 1
RULE_STEP 00:00:00

INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_WAIN_EQNATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SURFAREA 0
MAX_TRIALS 8
HEAD_TOLERANCE 0.0015
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINTIMUM_STEP 0.5
THREADS 12

[EVAPORATION]
;;Data Source Parameters
;;-----
CONSTANT 0.0
DRY_ONLY NO

[RAINGAGES]
;;Name Format Interval SCF Source
;;-----
3CHI002 INTENSITY 0:10 1.0 TIMESERIES 3CHI002
3CHI100 INTENSITY 0:10 1.0 TIMESERIES 3CHI100

[SUBCATCHMENTS]
;;Name Rain Gage Outlet Area %Imperv Width %Slope CurbLen
;;-----
SnowPack 3CHI002 CB208 0.0187 0.061 29.61 2.2 0
S1 3CHI002 CB204 0.0307 99.617 55.32 2.2 0
S10 3CHI002 CB202 0.127 86.66 65.66 2.2 0
S11 3CHI002 CB213 0.0149 0.253 6.44 2.2 0
S14_1 3CHI002 CB211 0.0119 52.747 22.78 2.2 0
S14_2 3CHI002 CB212 0.0119 31.754 58.12 2.2 0
S15 3CHI002 CB209 0.0372 23.566 108.74 2.2 0
S2 3CHI002 CB209 0.0731 63.05 33.61 2.2 0
S3 3CHI002 CB207 0.071 96.627 45.79 2.2 0
S32 3CHI002 CB214 0.052 14.286 29.7 2.2 0
S4 3CHI002 CB206 0.045 99.974 24.67 2.2 0
S45 3CHI002 CB203 0.0222 99.961 14.32 2.2 0
S5 3CHI002 CB200 0.0868 89.897 82.96 2.2 0
S6 3CHI002 CB214 0.019 0.002 46.5 2.2 0
S7 3CHI002 520_(P-Stm) 0.0686 100 25.95 2.2 0
S8 3CHI002 CB201 0.0941 80.117 35.06 2.2 0
S9 3CHI002 CB205 0.0275 76.829 19.08 2.2 0

[SUBAREAS]
;;Subcatchment N-Imperv N-Perv S-Imperv S-Perv PctZero RouteTo PctRouted
;;-----
S1 0.013 0.25 1.57 4.67 0 OUTLET
S10 0.013 0.25 1.57 4.67 0 OUTLET
S11 0.013 0.25 1.57 4.67 0 OUTLET
S12 0.013 0.25 1.57 4.67 0 OUTLET
S14_1 0.013 0.25 1.57 4.67 0 PERVIOUS 100
S14_2 0.013 0.25 1.57 4.67 0 PERVIOUS 100
S15 0.013 0.25 1.57 4.67 0 PERVIOUS 100
S2 0.013 0.25 1.57 4.67 0 OUTLET
S3 0.013 0.25 1.57 4.67 0 OUTLET
S32 0.013 0.25 1.57 4.67 0 OUTLET
S4 0.013 0.25 1.57 4.67 0 OUTLET
S45 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S5 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S6 0.013 0.25 1.57 4.67 0 OUTLET
S7 0.013 0.25 1.57 4.67 0 OUTLET
S8 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S9 0.013 0.25 1.57 4.67 0 OUTLET

[INFILTRATION]
;;Subcatchment Param1 Param2 Param3 Param4 Param5
;;-----
S1 76.2 13.2 4.14 7 0
S10 76.2 13.2 4.14 7 0
S11 76.2 13.2 4.14 7 0
S12 76.2 13.2 4.14 7 0
S14_1 76.2 13.2 4.14 7 0
S14_2 76.2 13.2 4.14 7 0
S15 76.2 13.2 4.14 7 0
S2 76.2 13.2 4.14 7 0
S3 76.2 13.2 4.14 7 0
S32 76.2 13.2 4.14 7 0
S4 76.2 13.2 4.14 7 0
S45 76.2 13.2 4.14 7 0
S5 76.2 13.2 4.14 7 0
S6 76.2 13.2 4.14 7 0
S7 76.2 13.2 4.14 7 0
S8 76.2 13.2 4.14 7 0
S9 76.2 13.2 4.14 7 0

[JUNCTIONS]
;;Name Elevation MaxDepth InitDepth SurDepth Aponded
;;-----
518_Orifice 81.361 4.106 0 0 0

[OUTFALLS]
;;Name Elevation Type Stage Data Gated Route To
;;-----
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 80.646 FIXED 81.2 NO

[STORAGE]
;;Name Elev. MaxDepth InitDepth Shape Curve Name/Params
SurDepth Fevap Psi Ksat IMD
;;-----
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 81.061 4.406 0.139 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
519_(P-Stm) 82.197 3.512 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
520_(P-Stm) 82.487 2.888 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI

521_(P-Stm) 81.957 3.673 0 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
522_(P-Stm) 82.182 3.323 0 0 FUNCTIONAL 0 0 1.13 0
;85.1800000001676 CB200 83.18 2.32 0 TABULAR CB200 0
;85.5000000001435 CB201 83.09 2.66 0 TABULAR CB201 0
;85.36 CB202 82.76 2.89 0 TABULAR CB202 0
;85.3500080822731 CB204 82.75 2.75 0 TABULAR CB204 0
;85.4500080823662 CB205 82.85 2.75 0 TABULAR CB205 0
;85.48 CB206 82.77 2.73 0 TABULAR CB206 0
;85.05 CB207 83.15 2.3 0 TABULAR CB207 0
;84.9000080821652 CB208 83.3 2.04 0 TABULAR CB208 0
;84.8 CB209 83.2 1.9 0 TABULAR CB209 0
;85.25 CB210B 82.65 3 0 TABULAR CB210B 0
;85.35 CB211 83.7 1.9 0 TABULAR CB211 0
;85.4 CB212 83.2 2.42 0 TABULAR CB212 0
;85.500000000554 CB212A 83.62 2 0 TABULAR CB212A 0
;84.75 CB213 83.15 1.75 0 TABULAR CB213 0
;84.55 CB214 82.95 1.9 0 TABULAR CB214 0

[CONDUITS]
;;Name From Node To Node Length Roughness InOffset OutOffset
;;-----
InitFlow MaxFlow
;C2 0 CB208 CB207 9.666 0.013 83.3 83.2
;C4 0 CB212A CB212 18.475 0.013 83.62 83.25
;C5 0 CB211 CB212 22.346 0.013 83.7 83.25
;CB213 0 CB213 522_(P-Stm) 29.34 0.013 83.15 82.757
;CB214 0 CB214 522_(P-Stm) 21.65 0.013 82.95 82.757
;PVC Pipes 0 CB214 522_(P-Stm) 15.623 0.013 81.361 81.322
;PVC Pipes 0 0 518_(P-Stm) 518_Orifice 518A_(P-Stm) 15.623 0.013 81.361 81.322
;PVC Pipes 0 0 518_(P-Stm) 518_(P-Stm) 27.209 0.013 82.257 82.161
;PVC Pipes 0 0 522_(P-Stm) 522_(P-Stm) 45.094 0.013 82.482 82.257
;Concrete Pipes 100-D 0 0 519_(P-Stm) 519_(P-Stm) 57.146 0.013 82.787 82.557
;Concrete Pipes 100-D 0 0 519_(P-Stm) 519_(P-Stm) 31.967 0.013 82.497 82.337
;OR1 0 518_(P-Stm) 518_Orifice SIDE 81.361 0.65 NO
;WEIRS
;;Name From Node To Node Type Offset Qcoeff Gated
;;-----
EndCon EndCoeff Surcharge RoadWidth RoadSurf Type CrestHt Qcoeff Gated
;W1 0 CB208 CB209 TRANSVERSE 85.31 1.84 NO
;W2 0 CB210B CB211 TRANSVERSE 85.6 1.84 NO
;W3 0 CB210B CB202 TRANSVERSE 85.45 1.84 NO
;W4 0 CB204 CB204 TRANSVERSE 85.55 1.84 NO
;W5 0 CB200 CB207 TRANSVERSE 85.45 1.84 NO
;W6 0 CB201 CB200 TRANSVERSE 85.65 1.84 NO
;W7 0 CB200 CB209 TRANSVERSE 85.42 1.84 NO
;OUTLETS
;;Name From Node To Node Offset Type QTable/Qcoeff
;;-----
Qexon Gated
;CB200 CB200 520_(P-Stm) 83.18 TABULAR/HEAD IPEX_Type_A
;Critical CB201 520_(P-Stm) 83.09 TABULAR/HEAD Vortex_ICD_100
;Critical CB202 521_(P-Stm) 82.76 TABULAR/HEAD IPEX_Type_A
;CB203 521_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_70
;CB204 522_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_65
;CB205 522_(P-Stm) 82.85 TABULAR/HEAD Vortex_ICD_65
;CB206 522_(P-Stm) 82.77 TABULAR/HEAD Vortex_ICD_70
;CB207 522_(P-Stm) 83.15 TABULAR/HEAD Vortex_ICD_100
;CB209 520_(P-Stm) 83.2 TABULAR/HEAD IPEX_Type_A
;CB210B 518_(P-Stm) 82.65 TABULAR/HEAD Vortex_ICD_65
;CB212 521_(P-Stm) 83.2 TABULAR/HEAD Vortex_ICD_100

[XSECTIONS]

:Link	Shape	Geom1	Geom2	Geom3	Geom4	Barrels	Vortex ICD_100	1	8.9
Culvert							Vortex ICD_100	1.2	9.8
C2	CIRCULAR	0.25	0	0	0	1	Vortex ICD_100	1.4	10.6
C4	CIRCULAR	0.25	0	0	0	1	Vortex ICD_100	1.6	11.3
C5	CIRCULAR	0.25	0	0	0	1	Vortex ICD_100	1.8	12
CB213	CIRCULAR	0.25	0	0	0	1	Vortex ICD_100	2	12.6
CB214	CIRCULAR	0.25	0	0	0	1	Vortex ICD_100	2.5	14.1
Pipe_-(104)_-(P-Stm)_2	CIRCULAR	0.45	0	0	0	1	;Tempest Rating Curve for Vortex ICD 105, No grate allowance		
Pipe_-(110)_-(P-Stm)	CIRCULAR	0.525	0	0	0	1	Vortex ICD_105	0	0
Pipe_-(111)_-(P-Stm)	CIRCULAR	0.525	0	0	0	1	Vortex ICD_105	0.1	3.1
Pipe_-(71)_-(P-Stm)	CIRCULAR	0.525	0	0	0	1	Vortex ICD_105	0.2	4.4
Pipe_-(72)_-(P-Stm)	CIRCULAR	0.525	0	0	0	1	Vortex ICD_105	0.3	5.4
OPI	CIRCULAR	0.525	0	0	0	1	Vortex ICD_105	0.4	6.2
W1	RECT_OPEN	0.03	1.5	0	0	1	Vortex ICD_105	0.5	6.9
W2	RECT_OPEN	0.05	2.59	0	0	1	Vortex ICD_105	0.6	7.6
W3	RECT_OPEN	0.2	3.34	0	0	1	Vortex ICD_105	0.7	8.2
W4	RECT_OPEN	0.1	4.9	0	0	1	Vortex ICD_105	0.8	8.8
W5	RECT_OPEN	0.05	4.725	0	0	1	Vortex ICD_105	0.9	9.3
W6	RECT_OPEN	0.1	6	0	0	1	Vortex ICD_105	1	9.8
W7	RECT_OPEN	0.08	10.5	0	0	1	Vortex ICD_105	1.2	10.7
[LOSSES]									
:Link	Kentry	Kexit	Kavg	Flap	Gate	Seepage	Vortex ICD_105	1.4	11.6
[CURVES]									
:Name	Type	X-Value	Y-Value				;Tempest Rating Curve for Vortex ICD 40, No grate allowance		
CB210-OUT85.5	Rating	0	0				Vortex ICD_40	0	0
CB210-OUT85.5		85.5	0.04				Vortex ICD_40	0.1	0.4
CB210-OUT85.5		100	0.04				Vortex ICD_40	0.2	0.6
CB210-OUT-85.6	Rating	0	0				Vortex ICD_40	0.3	0.7
CB210-OUT-85.6		85.6	0.08				Vortex ICD_40	0.4	0.9
CB210-OUT-85.6		100	0.08				Vortex ICD_40	0.5	1
;IPEX Type A ICD Rating Curve									
IPEX_Type_A	Rating	0	0				Vortex ICD_40	0.6	1
IPEX_Type_A		0.1	5.7				Vortex ICD_40	0.7	1.1
IPEX_Type_A		0.2	8.1				Vortex ICD_40	0.8	1.2
IPEX_Type_A		0.3	9.9				Vortex ICD_40	0.9	1.3
IPEX_Type_A		0.4	11.4				Vortex ICD_40	1	1.4
IPEX_Type_A		0.5	12.8				Vortex ICD_40	1.2	1.5
IPEX_Type_A		0.6	14				Vortex ICD_40	1.4	1.6
IPEX_Type_A		0.7	15.1				Vortex ICD_40	1.6	1.7
IPEX_Type_A		0.8	16.2				Vortex ICD_40	1.8	1.8
IPEX_Type_A		0.9	17.2				Vortex ICD_40	2	1.9
IPEX_Type_A		1	18.1				Vortex ICD_40	2.5	2.2
IPEX_Type_A		1.2	19.8				Vortex ICD_40	3	2.4
IPEX_Type_A		1.4	21.4				;Tempest Rating Curve for Vortex ICD 45, No grate allowance		
IPEX_Type_A		1.6	22.9				Vortex ICD_45	0	0
IPEX_Type_A		1.8	24.3				Vortex ICD_45	0.1	0.6
IPEX_Type_A		2	25.6				Vortex ICD_45	0.2	0.8
IPEX_Type_A		2.5	28.6				Vortex ICD_45	0.3	1
IPEX_Type_A		3	31.3				Vortex ICD_45	0.4	1.1
;IPEX Type B ICD Rating Curve									
IPEX_Type_B	Rating	0	0				Vortex ICD_45	0.5	1.2
IPEX_Type_B		0.1	8.1				Vortex ICD_45	0.6	1.3
IPEX_Type_B		0.2	11.5				Vortex ICD_45	0.7	1.4
IPEX_Type_B		0.3	14.1				Vortex ICD_45	0.8	1.5
IPEX_Type_B		0.4	16.2				Vortex ICD_45	0.9	1.6
IPEX_Type_B		0.5	18.2				Vortex ICD_45	1	1.7
IPEX_Type_B		0.6	19.9				Vortex ICD_45	1.2	1.8
IPEX_Type_B		0.7	21.5				Vortex ICD_45	1.4	2
IPEX_Type_B		0.8	23				Vortex ICD_45	1.6	2.2
IPEX_Type_B		0.9	24.4				Vortex ICD_45	1.8	2.4
IPEX_Type_B		1	25.7				Vortex ICD_45	2	2.6
IPEX_Type_B		1.2	28.1				Vortex ICD_45	2.5	3.1
IPEX_Type_B		1.4	30.4				;Tempest Rating Curve for Vortex ICD 50, No grate allowance		
IPEX_Type_B		1.6	32.5				Vortex ICD_50	0	0
IPEX_Type_B		1.8	34.4				Vortex ICD_50	0.1	0.7
IPEX_Type_B		2	36.3				Vortex ICD_50	0.2	1
IPEX_Type_B		2.5	40.6				Vortex ICD_50	0.3	1.2
IPEX_Type_B		3	44.5				Vortex ICD_50	0.4	1.4
;IPEX Type C ICD Rating Curve									
IPEX_Type_C	Rating	0	0				Vortex ICD_50	0.5	1.6
IPEX_Type_C		0.1	10.6				Vortex ICD_50	0.6	1.9
IPEX_Type_C		0.2	15				Vortex ICD_50	0.7	2.1
IPEX_Type_C		0.3	18.3				Vortex ICD_50	0.8	2.3
IPEX_Type_C		0.4	21.2				Vortex ICD_50	0.9	2.5
IPEX_Type_C		0.5	23.7				Vortex ICD_50	1	2.7
IPEX_Type_C		0.6	25.9				Vortex ICD_50	1.2	2.9
IPEX_Type_C		0.7	28				Vortex ICD_50	1.4	3
IPEX_Type_C		0.8	29.9				Vortex ICD_50	1.6	3.2
IPEX_Type_C		0.9	31.7				Vortex ICD_50	1.8	3.6
IPEX_Type_C		1	33.5				Vortex ICD_50	2	3.9
IPEX_Type_C		1.2	36.6				;Tempest Rating Curve for Vortex ICD 55, No grate allowance		
IPEX_Type_C		1.4	39.6				Vortex ICD_55	0	0
IPEX_Type_C		1.6	42.3				Vortex ICD_55	0.1	0.7
IPEX_Type_C		1.8	44.9				Vortex ICD_55	0.2	1
IPEX_Type_C		2	47.3				Vortex ICD_55	0.3	1.2
IPEX_Type_C		2.5	52.9				Vortex ICD_55	0.4	1.4
IPEX_Type_C		3	57.9				Vortex ICD_55	0.5	1.6
;IPEX Type AA ICD Rating Curve									
IPEX_Type_D	Rating	0	0				;Tempest Rating Curve for Vortex ICD 55, No grate allowance		
IPEX_Type_D		0.1	15.4				Vortex ICD_55	0	0
IPEX_Type_D		0.2	21.7				Vortex ICD_55	0.1	0.9
IPEX_Type_D		0.3	26.6				Vortex ICD_55	0.2	1.2
IPEX_Type_D		0.4	30.7				Vortex ICD_55	0.3	1.5
IPEX_Type_D		0.5	34.3				Vortex ICD_55	0.4	1.7
IPEX_Type_D		0.6	37.6				Vortex ICD_55	0.5	1.9
IPEX_Type_D		0.7	40.6				Vortex ICD_55	0.6	2.1
IPEX_Type_D		0.8	43.4				Vortex ICD_55	0.7	2.3
IPEX_Type_D		1	48.5				Vortex ICD_55	0.8	2.4
IPEX_Type_D		1.2	53.2				Vortex ICD_55	0.9	2.6
IPEX_Type_D		1.4	57.4				Vortex ICD_55	1	2.7
IPEX_Type_D		1.6	61.4				;Tempest Rating Curve for Vortex ICD 60, No grate allowance		
IPEX_Type_D		1.8	65.1				Vortex ICD_60	0	0
IPEX_Type_D		2	68.7				Vortex ICD_60	0.1	1.1
IPEX_Type_D		2.5	76.8				Vortex ICD_60	0.2	1.5
IPEX_Type_D		3	84.1				Vortex ICD_60	0.3	1.8
;IPEX Type E ICD Rating Curve									
IPEX_Type_E	Rating	0	0				;Tempest Rating Curve for Vortex ICD 60, No grate allowance		
IPEX_Type_E		0.1	20.5				Vortex ICD_60	0	0
IPEX_Type_E		0.2	28.9				Vortex ICD_60	0.1	1.5
IPEX_Type_E		0.3	35.5				Vortex ICD_60	0.2	2
IPEX_Type_E		0.4	40.9				Vortex ICD_60	0.3	2.4
IPEX_Type_E		0.5	45.8				Vortex ICD_60	0.4	3.1
IPEX_Type_E		0.6	50.1				Vortex ICD_60	0.5	3.8
IPEX_Type_E		0.7	54.2				Vortex ICD_60	0.6	4.3
IPEX_Type_E		0.8	57.9				Vortex ICD_60	0.7	4.7
IPEX_Type_E		0.9	61.4				;Tempest Rating Curve for Vortex ICD 65, No grate allowance		
IPEX_Type_E		1	64.7				Vortex ICD_65	0	0
IPEX_Type_E		1.2	70.9				Vortex ICD_65	0.1	1.2
IPEX_Type_E		1.4	76.6				Vortex ICD_65	0.2	1.6
IPEX_Type_E		1.6	81.9				Vortex ICD_65	0.3	2
IPEX_Type_E		1.8	86.8				Vortex ICD_65	0.4	2.3
IPEX_Type_E		2	91.5				Vortex ICD_65	0.5	2.5
IPEX_Type_E		2.5	102.3				Vortex ICD_65	0.6	2.8
IPEX_Type_E		3	112.1				Vortex ICD_65	0.7	3
;Tempest Rating Curve for Vortex ICD 100, No grate allowance									
Vortex_ICD_100	Rating	0	0				Vortex ICD_65	0.8	3.2
Vortex_ICD_100		0.1	2.8				Vortex ICD_65	0.9	3.4
Vortex_ICD_100		0.2	4				Vortex ICD_65	1	3.6
Vortex_ICD_100		0.3	4.9				Vortex ICD_65	1.2	4
Vortex_ICD_100		0.4	5.6				Vortex ICD_65	1.4	4.3
Vortex_ICD_100		0.5	6.3				Vortex ICD_65	1.6	4.6
Vortex_ICD_100		0.6	6.9				Vortex ICD_65	1.8	4.9
Vortex_ICD_100		0.7	7.5				Vortex ICD_65	2	5.1
Vortex_ICD_100		0.8	8				Vortex ICD_65	2.5	5.7
Vortex_ICD_100		0.9	8.5				Vortex ICD_65	3	6.3

Post-Development 3-hour Chicago 1:2 year Event

January 2025

```
;Tempest Rating Curve for Vortex ICD 70, No grate allowance
Vortex ICD 70    Rating   0      0
Vortex ICD 70    Rating   0.1    1.3
Vortex ICD 70    Rating   0.2    1.9
Vortex ICD 70    Rating   0.3    2.3
Vortex ICD 70    Rating   0.4    2.7
Vortex ICD 70    Rating   0.5    3
Vortex ICD 70    Rating   0.6    3.3
Vortex ICD 70    Rating   0.7    3.6
Vortex ICD 70    Rating   0.8    3.8
Vortex ICD 70    Rating   0.9    4.1
Vortex ICD 70    Rating   1      4.3
Vortex ICD 70    Rating   1.2    4.7
Vortex ICD 70    Rating   1.4    5.1
Vortex ICD 70    Rating   1.6    5.5
Vortex ICD 70    Rating   1.8    5.8
Vortex ICD 70    Rating   2      6.1
Vortex ICD 70    Rating   2.5    6.8
Vortex ICD 70    Rating   3      7.5
```

```
;Tempest Rating Curve for Vortex ICD 75, No grate allowance
Vortex ICD 75    Rating   0      0
Vortex ICD 75    Rating   0.1    1.6
Vortex ICD 75    Rating   0.2    2.2
Vortex ICD 75    Rating   0.3    2.7
Vortex ICD 75    Rating   0.4    3.2
Vortex ICD 75    Rating   0.5    3.5
Vortex ICD 75    Rating   0.6    3.9
Vortex ICD 75    Rating   0.7    4.2
Vortex ICD 75    Rating   0.8    4.5
Vortex ICD 75    Rating   0.9    4.8
Vortex ICD 75    Rating   1      5
Vortex ICD 75    Rating   1.2    5.5
Vortex ICD 75    Rating   1.4    5.9
Vortex ICD 75    Rating   1.6    6.3
Vortex ICD 75    Rating   1.8    6.7
Vortex ICD 75    Rating   2      7.1
Vortex ICD 75    Rating   2.5    7.9
Vortex ICD 75    Rating   3      8.7
```

```
;Tempest Rating Curve for Vortex ICD 80, No grate allowance
Vortex ICD 80    Rating   0      0
Vortex ICD 80    Rating   0.1    1.8
Vortex ICD 80    Rating   0.2    2.6
Vortex ICD 80    Rating   0.3    3.1
Vortex ICD 80    Rating   0.4    3.6
Vortex ICD 80    Rating   0.5    4
Vortex ICD 80    Rating   0.6    4.4
Vortex ICD 80    Rating   0.7    4.8
Vortex ICD 80    Rating   0.8    5.1
Vortex ICD 80    Rating   0.9    5.4
Vortex ICD 80    Rating   1      5.7
Vortex ICD 80    Rating   1.2    6.3
Vortex ICD 80    Rating   1.4    6.8
Vortex ICD 80    Rating   1.6    7.2
Vortex ICD 80    Rating   1.8    7.7
Vortex ICD 80    Rating   2      8.1
Vortex ICD 80    Rating   2.5    9
Vortex ICD 80    Rating   3      9.9
```

```
;Tempest Rating Curve for Vortex ICD 85, No grate allowance
Vortex ICD 85    Rating   0      0
Vortex ICD 85    Rating   0.1    2
Vortex ICD 85    Rating   0.2    2.9
Vortex ICD 85    Rating   0.3    3.5
Vortex ICD 85    Rating   0.4    4.1
Vortex ICD 85    Rating   0.5    4.5
Vortex ICD 85    Rating   0.6    5
Vortex ICD 85    Rating   0.7    5.4
Vortex ICD 85    Rating   0.8    5.7
Vortex ICD 85    Rating   0.9    6.1
Vortex ICD 85    Rating   1      6.4
Vortex ICD 85    Rating   1.2    7
Vortex ICD 85    Rating   1.4    7.6
Vortex ICD 85    Rating   1.6    8.1
Vortex ICD 85    Rating   1.8    8.6
Vortex ICD 85    Rating   2      9.1
Vortex ICD 85    Rating   2.5    10.1
Vortex ICD 85    Rating   3      11.1
```

```
;Tempest Rating Curve for Vortex ICD 90, No grate allowance
Vortex ICD 90    Rating   0      0
Vortex ICD 90    Rating   0.1    2.2
Vortex ICD 90    Rating   0.2    3.2
Vortex ICD 90    Rating   0.3    3.9
Vortex ICD 90    Rating   0.4    4.5
Vortex ICD 90    Rating   0.5    5.1
Vortex ICD 90    Rating   0.6    5.5
Vortex ICD 90    Rating   0.7    6
Vortex ICD 90    Rating   0.8    6.4
Vortex ICD 90    Rating   0.9    6.8
Vortex ICD 90    Rating   1      7.2
Vortex ICD 90    Rating   1.2    7.9
Vortex ICD 90    Rating   1.4    8.5
Vortex ICD 90    Rating   1.6    9.1
Vortex ICD 90    Rating   1.8    9.6
Vortex ICD 90    Rating   2      10.2
Vortex ICD 90    Rating   2.5    11.4
Vortex ICD 90    Rating   3      12.5
```

```
;Tempest Rating Curve for Vortex ICD 95, No grate allowance
Vortex ICD 95    Rating   0      0
Vortex ICD 95    Rating   0.1    2.6
Vortex ICD 95    Rating   0.2    3.6
Vortex ICD 95    Rating   0.3    4.4
Vortex ICD 95    Rating   0.4    5.1
Vortex ICD 95    Rating   0.5    5.7
Vortex ICD 95    Rating   0.6    6.2
Vortex ICD 95    Rating   0.7    6.7
Vortex ICD 95    Rating   0.8    7.1
Vortex ICD 95    Rating   0.9    7.6
Vortex ICD 95    Rating   1      8
Vortex ICD 95    Rating   1.2    8.7
Vortex ICD 95    Rating   1.4    9.4
Vortex ICD 95    Rating   1.6    10.1
Vortex ICD 95    Rating   1.8    10.7
Vortex ICD 95    Rating   2      11.3
Vortex ICD 95    Rating   2.5    12.6
Vortex ICD 95    Rating   3      13.8
```

```
CB200      Storage  0      0.36
CB200      Storage  2      0.36
CB200      Storage  2.24   217.87
CB200      Storage  2.32   217.87
```

```
CB201      Storage  0      0.36
CB201      Storage  2.41   0.36
CB201      Storage  2.56   169.64
CB201      Storage  2.66   169.64
```

```
CB202      Storage  0      0.36
CB202      Storage  2.6    0.36
CB202      Storage  2.79   273.92
CB202      Storage  2.89   273.92
```

```
CB203      Storage  0      0.36
CB203      Storage  2.6    0.36
CB203      Storage  2.9    178.09
```

```
CB204      Storage  0      0.36
CB204      Storage  2.6    0.36
CB204      Storage  2.75   146.08
```

```
CB205      Storage  0      0.36
CB205      Storage  2.6    0.36
CB205      Storage  2.75   86.52
```

```
CB206      Storage  0      0.36
CB206      Storage  2.6    0.36
```

	CB206	CB206	CB206	CB206
	2.68	2.73	57.95	57.95
	CB207	Storage	0	0.36
	CB207	CB207	1.97	0.36
	CB207	CB207	2.3	178.5
	CB208	Storage	0	0.073
	CB208	CB208	1.74	0.073
	CB208	CB208	2.01	67.88
	CB208	CB208	2.04	67.88
	CB209	Storage	0	0.073
	CB209	CB209	1.6	0.073
	CB209	CB209	1.9	84.87
	CB210B	Storage	0	0.073
	CB210B	CB210B	2.6	0.073
	CB210B	CB210B	2.9	70.98
	CB210B	CB210B	3	70.98

	CB211	CB211	CB211	CB211
	Storage	0	0.073	0.073
	CB211	CB211	1.65	0.073
	CB211	CB211	1.9	21.99

	CB212	CB212	CB212	CB212
	Storage	0	0.36	0.36
	CB212	CB212	2.2	55.12
	CB212	CB212	2.42	

	CB212A	CB212A	CB212A	CB212A
	Storage	0	0.073	0.073
	CB212A	CB212A	2	0.073

	CB213	CB213	CB213	CB213
	Storage	0	0.073	0.073
	CB213	CB213	1.6	9.05
	CB213	CB213	1.75	

	CB214	CB214	CB214	CB214
	Storage	0	0.073	0.073
	CB214	CB214	1.6	0.073
	CB214	CB214	1.9	34.75

[TIMESERIES]

	Name	Date	Time	Value
	:Rainfall (mm/hr)			
3CH1002		01/01/2000	00:00:00	2,491
3CH1002		01/01/2000	00:10:00	2,966
3CH1002		01/01/2000	00:20:00	3,696
3CH1002		01/01/2000	00:30:00	4,976
3CH1002		01/01/2000	00:40:00	7,828
3CH1002		01/01/2000	00:50:00	19,636
3CH1002		01/01/2000	01:00:00	76,805
3CH1002		01/01/2000	01:10:00	22,777
3CH1002		01/01/2000	01:20:00	11,852
3CH1002		01/01/2000	01:30:00	8,025
3CH1002		01/01/2000	01:40:00	6,096
3CH1002		01/01/2000	01:50:00	4,938
3CH1002		01/01/2000	02:00:00	4,165
3CH1002		01/01/2000	02:10:00	3,133
3CH1002		01/01/2000	02:20:00	3,197
3CH1002		01/01/2000	02:30:00	2,873
3CH1002		01/01/2000	02:40:00	2,613
3CH1002		01/01/2000	02:50:00	2.4
3CH1002		01/01/2000	03:00:00	0

	Name	Date	Time	Value
	:Rainfall (mm/hr)			
3CH1100		01/01/2000	00:00:00	5,339
3CH1100		01/01/2000	00:10:00	6,376
3CH1100		01/01/2000	00:20:00	7,977
3CH1100		01/01/2000	00:30:00	10,797
3CH1100		01/01/2000	00:40:00	17,136
3CH1100		01/01/2000	00:50:00	45,128
3CH1100		01/01/2000	01:00:00	178,057
3CH1100		01/01/2000	01:10:00	51,056
3CH1100		01/01/2000	01:20:00	26,163
3CH1100		01/01/2000	01:30:00	17,571
3CH1100		01/01/2000	01:40:00	13,277
3CH1100		01/01/2000	01:50:00	10,712
3CH1100		01/01/2000	02:00:00	9,008
3CH1100		01/01/2000	02:10:00	7,933
3CH1100		01/01/2000	02:20:00	6,883
3CH1100		01/01/2000	02:30:00	6,174
3CH1100		01/01/2000	02:40:00	5,607
3CH1100		01/01/2000	02:50:00	5,142
3CH1100		01/01/2000	03:00:00	0

[REPORT]

;Reporting Options

INPUT YES

CONTROLS NO

SUBCATCHMENTS ALL

NODES ALL

LINKS ALL

	Node	518 Orifice	RV Manhole
	Node	CB200	RV_Manhole
	Node	CB201	RV_Manhole
	Node	CB202	RV_Manhole
	Node	CB203	RV_Manhole
	Node	CB204	RV_Manhole
	Node	CB205	RV_Manhole
	Node	CB206	RV_Manhole
	Node	CB207	RV_Manhole
	Node	CB208	RV_Manhole
	Node	CB209	RV_Manhole
	Node	CB210B	RV_Manhole
	Node	CB211	RV_Manhole
	Node	CB212	RV_Manhole
	Node	CB212A	RV_Manhole
	Node	CB213	RV_Manhole
	Node	CB214	RV_Manhole
	Link	C2	RV_Sewer
	Link	C4	RV_Sewer
	Link	C5	RV_Sewer

[MAP]

DIMENSIONS	381219.0294	5032865.6782	381334.8286	5033009.9278
UNITS	Meters			

[COORDINATES]

	Node	X-Coord	Y-Coord

518 Orifice	381303.7	5032953.188
518A (P-Stm)	381317.029	5032955.797
518 (P-Stm)	381301.695	5032952.807
519 (P-Stm)	381278.558	5032974.866
520 (P-Stm)	381240.562	5032932.182
521 (P-Stm)	381265.744	5032914.957
522 (P-Stm)	381267.739	5032909.252
CB206	381246.119	5032946.933
CB207	381266.142	5032969.504
CB208	381305.816	5032949.229
CB209	381314.519	5032914.342
CB204	381291.187	5032821.779
CB205	381274.939	5032818.022
CB206	381270.933	5032913.017
CB207	381253.811	5032910.356
CB208	381248.314	5032902.406
CB209	381228.288	5032926.78
CB210B	381314.246	5032963.095
CB211	381319.351	5032851.771
CB212	381272.283	5032812.238
CB212A	381266.875	5032812.9
CB213	381296.875	5032912.718
CB214	381282.831	5032893.727

[VERTICES]

	Link	X-Coord	Y-Coord

Post-Development 3-hour Chicago 1:2 year Event

January 2025

W2 381318.013 5032956.452
 W4 381305.808 5032934.267
 W4 381304.151 5032928.843

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

[POLYGONS]
 ;Subcatchment X-Coord Y-Coord
 ;-----
 S1 381237.464 5032904.825
 S1 381240.329 5032905.467
 ...
 S9 381290.74 5032939.886
 ;Storage Node X-Coord Y-Coord
 ;-----

 Element Count

 Number of rain gages 2
 Number of subcatchments 17
 Number of nodes 23
 Number of links 29
 Number of pollutants 0
 Number of land uses 0

[SYMBOLS]
 ;Gage X-Coord Y-Coord
 ;-----

 Rainage Summary

 Name Data Source Data Type Recording Interval
 3CHI002 3CHI002 INTENSITY 10 min.
 3CHI100 3CHI100 INTENSITY 10 min.

 Subcatchment Summary

 Name Area Width %Imperv %Slope Rain Gage Outlet

 S1 0.02 29.61 0.06 2.2000 3CHI002 CB208
 S10 0.03 55.32 99.62 2.2000 3CHI002 CB204
 S11 0.13 65.66 86.68 2.2000 3CHI002 CB202
 S12 0.01 6.44 0.00 2.2000 3CHI002 CB213
 S14_1 0.01 24.78 50.75 2.2000 3CHI002 CB211
 S14_2 0.02 58.12 31.75 2.2000 3CHI002 CB212
 S15 0.04 108.74 25.77 2.2000 3CHI002 CB210B
 S2 0.07 33.61 63.05 2.2000 3CHI002 CB209
 S3 0.07 45.79 96.63 2.2000 3CHI002 CB207
 S32 0.05 29.70 14.29 2.2000 3CHI002 CB214
 S4 0.04 24.67 97.00 2.2000 3CHI002 CB205
 S45 0.02 11.22 99.96 2.2000 3CHI002 CB203
 S5 0.09 82.96 89.90 2.2000 3CHI002 CB200
 S6 0.02 40.30 0.00 2.2000 3CHI002 CB214
 S7 0.07 25.95 100.00 2.2000 3CHI002 520_(P-
 Stm)
 S8 0.09 35.06 80.12 2.2000 3CHI002 CB201
 S9 0.03 19.08 76.83 2.2000 3CHI002 CB205

 Node Summary

 Name Type Invert Elev. Max. Depth Ponded Area External Inflow

 518 Orifice JUNCTION 81.36 4.11 0.0
 518A_(P-Stm) OUTFALL 80.65 1.13 0.0
 518_(P-Stm) STORAGE 81.06 4.41 0.0
 519_(P-Stm) STORAGE 82.20 3.51 0.0
 520_(P-Stm) STORAGE 82.49 2.89 0.0
 521_(P-Stm) STORAGE 81.96 3.67 0.0
 522_(P-Stm) STORAGE 82.19 3.32 0.0
 CB200 STORAGE 83.18 2.22 0.0
 CB201 STORAGE 83.09 2.66 0.0
 CB202 STORAGE 82.76 2.89 0.0
 CB203 STORAGE 82.75 2.90 0.0
 CB204 STORAGE 82.75 2.75 0.0
 CB205 STORAGE 82.85 2.75 0.0
 CB206 STORAGE 82.77 2.73 0.0
 CB207 STORAGE 83.15 2.30 0.0
 CB208 STORAGE 83.30 2.04 0.0
 CB209 STORAGE 83.20 1.90 0.0
 CB210B STORAGE 82.65 3.00 0.0
 CB211 STORAGE 83.70 1.90 0.0
 CB212 STORAGE 83.20 2.42 0.0
 CB212A STORAGE 83.62 2.00 0.0
 CB213 STORAGE 83.15 1.75 0.0
 CB214 STORAGE 82.95 1.90 0.0

 Link Summary

 Name From Node To Node Type Length %Slope
 Roughness

 C2 CB208 CB207 CONDUIT 9.7 1.0346
 0.0130 CB212A CB212 CONDUIT 18.5 2.0031
 0.0130 CB211 CB212 CONDUIT 22.3 2.0142
 0.0130 CB213 522_(P-Stm) CONDUIT 29.3 1.3396
 0.0130 CB214 522_(P-Stm) CONDUIT 21.6 0.8915
 0.0130 Pipe_(104)_ (P-Stm) 518_(P-Stm) CONDUIT 15.6 0.2496
 0.0130 Pipe_(110)_ (P-Stm) 521_(P-Stm) 518_(P-Stm) CONDUIT 27.2 0.3528
 0.0130 Pipe_(111)_ (P-Stm) 522_(P-Stm) 521_(P-Stm) CONDUIT 45.1 0.4990
 0.0130 Pipe_(71)_ (P-Stm) 520_(P-Stm) 519_(P-Stm) CONDUIT 57.1 0.4025
 0.0130 Pipe_(72)_ (P-Stm) 519_(P-Stm) 518_(P-Stm) CONDUIT 32.0 0.5005
 0.0130 OR1 518_(P-Stm) 518 Orifice ORIFICE
 W1 CB208 CB209 WEIR
 W2 CB210B CB211 WEIR
 W3 CB209 CB202 WEIR
 W4 CB202 CB204 WEIR
 W5 CB206 CB207 WEIR
 W6 CB201 CB200 WEIR
 W7 CB200 CB209 WEIR
 CB200 CB200 520_(P-Stm) OUTLET
 CB201 CB201 520_(P-Stm) OUTLET
 CB202 CB202 521_(P-Stm) OUTLET
 CB203 CB203 521_(P-Stm) OUTLET
 CB204 CB204 522_(P-Stm) OUTLET
 CB205 CB205 522_(P-Stm) OUTLET
 CB206 CB206 522_(P-Stm) OUTLET
 CB207 CB207 522_(P-Stm) OUTLET
 CB209 CB209 520_(P-Stm) OUTLET
 CB210B CB210B 518_(P-Stm) OUTLET
 CB212 CB212 521_(P-Stm) OUTLET

 Cross Section Summary

 Conduit Shape Full Depth Full Area Hyd. Rad. Max. Width No. of Barrels Full Flow

 C2 CIRCULAR 0.25 0.05 0.06 0.25 1 60.49
 C4 CIRCULAR 0.25 0.05 0.06 0.25 1 84.17
 C5 CIRCULAR 0.25 0.05 0.06 0.25 1 84.40
 CB213 CIRCULAR 0.25 0.05 0.06 0.25 1 68.83
 CB214 CIRCULAR 0.25 0.05 0.06 0.25 1 56.15
 Pipe_(104)_ (P-Stm) CIRCULAR 0.45 0.16 0.11 0.45 1
 142.46 Pipe_(110)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 255.80
 Pipe_(111)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 303.80
 Pipe_(71)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 272.85
 Pipe_(72)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 304.28

Post-Development 3-hour Chicago 1:2 year Event

January 2025

Analysis Options

Flow Units LPS
 Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
 Infiltration Method HORTON
 Flow Routing Method HYDRAVE
 Surcharge Method EXTRAN
 Starting Date 01/01/2000 00:00:00
 Ending Date 01/01/2000 06:00:00
 Antecedent Dry Days 0.0
 Report Time Step 00:01:00
 Wet Time Step 00:01:00
 Dry Time Step 00:01:00
 Routing Time Step 0.00 sec
 Variable Time Step YES
 Maximum Trials 8
 Number of Threads 1
 Head Tolerance 0.001500 m

Runoff Quantity Continuity	Volume hectare-m	Depth mm
Total Precipitation	0.026	31.880
Evaporation Loss	0.000	0.000
Infiltration Loss	0.008	9.225
Surface Runoff	0.018	21.549
Final Storage	0.001	1.137
Continuity Error (%)	-0.099	

Flow Routing Continuity	Volume hectare-m	Volume 10 ⁶ ltr
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.018	0.177
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.018	0.176
Flooded Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.002
Continuity Error (%)	0.000	

Highest Continuity Errors
 Node 520_(P-Stm) (1.34%)

Time-Step Critical Elements
 None

Highest Flow Instability Indexes
 All links are stable.

Most Frequent Nonconverging Nodes
 Convergence obtained at all time steps.

Routing Time Step Summary		
Minimum Time Step	0.50 sec	
Average Time Step	1.00 sec	
Maximum Time Step	1.00 sec	
% of Time in Steady State	0.00	
Average Iterations per Step	2.00	
% of Steps Not Converging	0.00	
Time Step Frequencies		
1.000 - 0.875 sec	100.00 %	
0.875 - 0.818 sec	0.00 %	
0.818 - 0.660 sec	0.00 %	
0.660 - 0.574 sec	0.00 %	
0.574 - 0.500 sec	0.00 %	

Subcatchment Runoff Summary

Total Runoff	Total Runoff	Peak Runoff	Total Runon	Total Evap	Total Infil	Imperv	Perv
Runoff Subcatchment	Runoff Runoff	Runoff Preflt Coeff	Runon mm	Evap mm	Infil mm	Runoff mm	Runoff mm
mm	10 ⁶ ltr	LPS	mm	mm	mm	mm	mm
S1	0.00	31.88	0.00	0.00	31.67	0.02	0.20
0.22	0.00	0.20	0.07				
S10	0.01	6.54	0.949	31.88	0.00	0.12	30.24
30.25	0.01						
S11	0.03	23.88	0.826	31.88	0.00	4.21	26.29
26.34	0.00						
S12	0.00	31.88	0.00	0.00	31.73	0.08	0.07
0.13	0.00	0.05	0.005				
S14_1	0.00	2.04	0.347	31.88	0.00	20.07	16.01
11.05	0.00						
S14_2	0.00	31.88	0.00	0.00	25.36	9.63	6.08
6.08	0.00	2.56	0.191				
S15	0.00	31.88	0.00	0.00	26.75	7.82	4.77
4.77	0.00	4.58	0.150				
S2	0.00	31.88	0.00	0.00	11.72	19.13	0.06
19.20	0.01	10.06	0.422				
S3	0.02	14.82	0.920	31.88	0.00	1.05	29.32
29.34	0.02						
S32	0.00	1.28	0.063	31.88	0.00	29.66	4.34
2.01	0.00						
S4	0.01	9.60	0.951	31.88	0.00	0.01	30.33
30.33	0.01						
S5	0.01	4.74	0.951	31.88	0.00	0.01	30.33
30.33	0.01						
S6	0.02	16.72	0.858	31.88	0.00	3.17	27.34
27.34	0.02						
S7	0.00	0.27	0.007	31.88	0.00	0.00	31.68
0.21	0.00						
S8	0.02	14.63	0.741	31.88	0.00	0.00	30.33
30.33	0.02						
S9	0.02	16.11	0.764	31.88	0.00	0.00	24.35
24.35	0.02						
S10	0.01	4.63	0.734	31.88	0.00	0.00	7.32
23.39	0.01						

Post-Development 3-hour Chicago 1:2 year Event

January 2025

CB207	0.000	0.1	0.0	0.0	0.001	1.9	0	01:10
12.84								
CB208	0.000	0.0	0.0	0.0	0.000	0.9	0	01:10
2.78								
CB209	0.000	0.0	0.0	0.0	0.000	0.2	0	01:10
9.92								
CB210B	0.000	0.0	0.0	0.0	0.000	0.3	0	01:12
1.86								
CB211	0.000	0.0	0.0	0.0	0.000	0.1	0	01:10
2.03								
CB212	0.000	0.0	0.0	0.0	0.000	0.8	0	01:11
3.35								
CB212A	0.000	0.0	0.0	0.0	0.000	0.0	0	00:00
0.00								
CB213	0.000	0.0	0.0	0.0	0.000	0.0	0	01:12
0.03								
CB214	0.000	0.0	0.0	0.0	0.000	0.3	0	01:16
8.59								

***** Outfall Loading Summary *****

Outfall Node	Flow Freq Pcnt	Avg Flow LPS	Max Flow LPS	Total Volume 10^6 ltr
518A (P-Stm)	62.49	13.01	46.39	0.176
System	62.49	13.01	46.39	0.176

***** Link Flow Summary *****

Link	Type	Maximum Flow LPS	Time of Occurrence days hr:min	Maximum Velocity m/sec	Max/Full Flow	Max/Full Depth
C2	CONDUIT	3.97	0 01:02	0.10	0.07	1.00
C4	CONDUIT	0.00	0 00:00	0.00	0.00	0.19
C5	CONDUIT	2.03	0 01:10	0.67	0.02	0.24
CB213	CONDUIT	0.03	0 01:12	0.08	0.00	0.51
CB214	CONDUIT	8.59	0 01:12	0.33	0.15	0.92
Pipe_-(104)_-(P-Stm)_2	CONDUIT	46.39	0 01:19	0.94	0.33	0.35
Pipe_-(110)_-(P-Stm)	CONDUIT	55.22	0 01:19	0.97	0.40	1.00
Pipe_-(111)_-(P-Stm)	CONDUIT	30.95	0 01:11	0.51	0.20	0.85
Pipe_-(71)_-(P-Stm)	CONDUIT	54.76	0 01:10	1.00	0.20	0.85
Pipe_-(72)_-(P-Stm)	CONDUIT	51.62	0 01:06	0.97	0.17	1.00
OR1	ORIFICE	46.41	0 01:18			1.00
W1	WEIR	0.00	0 00:00			0.00
W2	WEIR	0.00	0 00:00			0.00
W3	WEIR	0.00	0 00:00			0.00
W4	WEIR	0.00	0 00:00			0.00
W5	WEIR	0.00	0 00:00			0.00
W6	WEIR	0.00	0 00:00			0.00
W7	WEIR	0.00	0 00:00			0.00
CB200	DUMMY	16.60	0 01:10			
CB201	DUMMY	13.84	0 01:10			
CB202	DUMMY	22.58	0 01:08			
CB203	DUMMY	0.65	0 00:08			
CB204	DUMMY	4.39	0 01:10			
CB205	DUMMY	3.34	0 01:09			
CB206	DUMMY	6.37	0 01:10			
CB207	DUMMY	11.17	0 01:10			
CB209	DUMMY	9.92	0 01:10			
CB210B	DUMMY	1.86	0 01:11			
CB212	DUMMY	3.35	0 01:11			

***** Flow Classification Summary *****

Conduit	Adjusted /Actual Length	Fraction of Time in Flow Class
	Dry Up Dry Sub Sup Up Down Norm Inlet	
Conduit	Dry Up Dry Sub Sup Crit Up Crit Crit Crit Ltd Ctrl	
C2	1.00 0.10 0.00 0.00 0.16 0.00 0.00 0.75 0.07 0.00	
C4	1.00 0.09 0.03 0.00 0.16 0.00 0.00 0.75 0.07 0.00	
C5	1.00 0.17 0.00 0.00 0.02 0.00 0.00 0.80 0.03 0.00	
CB213	1.00 0.09 0.00 0.00 0.09 0.00 0.00 0.82 0.09 0.00	
CB214	1.00 0.09 0.00 0.00 0.09 0.00 0.00 0.83 0.03 0.00	
Pipe_-(104)_-(P-Stm)_2	1.00 0.11 0.00 0.00 0.00 0.00 0.00 0.89 0.00 0.00	
Pipe_-(110)_-(P-Stm)	1.00 0.11 0.00 0.00 0.14 0.00 0.00 0.75 0.00 0.00	
Pipe_-(111)_-(P-Stm)	1.00 0.10 0.00 0.00 0.89 0.00 0.00 0.00 0.00 0.00	
Pipe_-(71)_-(P-Stm)	1.00 0.10 0.00 0.00 0.11 0.00 0.00 0.79 0.04 0.00	
Pipe_-(72)_-(P-Stm)	1.00 0.11 0.00 0.00 0.13 0.00 0.00 0.76 0.01 0.00	

***** Conduit Surcharge Summary *****

Conduit	Hours Both Ends	Hours Upstream	Hours Dnstream	Hours Above Normal Flow	Hours Capacity Limited
C2	0.34	0.34	0.38	0.01	0.01
CB213	0.01	0.01	0.30	0.01	0.01
CB214	0.01	0.01	0.30	0.01	0.01
Pipe_-(110)_-(P-Stm)	0.51	0.51	0.60	0.01	0.01
Pipe_-(111)_-(P-Stm)	0.30	0.30	0.51	0.01	0.01
Pipe_-(71)_-(P-Stm)	0.01	0.01	0.19	0.01	0.01
Pipe_-(72)_-(P-Stm)	0.27	0.27	0.44	0.01	0.01

Analysis begun on: Tue Jan 28 12:44:04 2025
 Analysis ended on: Tue Jan 28 12:44:05 2025
 Total elapsed time: 00:00:01

Post-Development 3-hour Chicago 1:100 year Event

[TITLE]
;;Project Title/Notes

[OPTIONS]
;;Option Value
FLOW_UNITS LPS
INFILTRATION HORTON
FLOW_ROUTING DYNWAVE
LINK_OFFSETS ELEVATION
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO
START_DATE 01/01/2000
START_TIME 00:00:00
REPORT_START_DATE 01/01/2000
REPORT_START_TIME 00:00:00
END_DATE 01/01/2000
END_TIME 06:00:00
SWEEP_START 01/01
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 00:01:00
WET_STEP 00:01:00
DRY_STEP 00:01:00
ROUTING_STEP RULE_STEP 00:00:00
INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_MAIN_EQNATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SLOPE 0
MAX_TRIALS 8
HEAD_TOLERANCE 0.0015
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINIMUM_STEP 0.5
THREADS 12

[EVAPORATION]
;;Data Source Parameters
;;-----
CONSTANT 0.0
DRY_ONLY NO

[RAINGAGES]
;;Name Format Interval SCF Source
;;-----
3CHI100 INTENSITY 0:10 1.0 TIMESERIES 3CHI100

[SUBCATCHMENTS]
;;Name Rain Gage Outlet Area %Imperv Width %Slope CurbLen
;;-----
S1 3CHI100 CB208 0.0187 0.061 29.61 2.2 0
S10 3CHI100 CB204 0.0307 99.617 55.32 2.2 0
S11 3CHI100 CB202 0.127 86.66 65.66 2.2 0
S12 3CHI100 CB213 0.0149 0.253 6.44 2.2 0
S14_1 3CHI100 CB211 0.0156 52.177 22.78 2.2 0
S14_2 3CHI100 CB212 0.0179 31.754 58.2 2.2 0
S15 3CHI100 CB210B 0.0372 25.766 108.74 2.2 0
S2 3CHI100 CB209 0.0731 63.05 33.61 2.2 0
S3 3CHI100 CB207 0.071 96.627 45.79 2.2 0
S22 3CHI100 CB214 0.052 14.286 29.7 2.2 0
S4 3CHI100 CB206 0.045 99.974 24.67 2.2 0
S45 3CHI100 CB203 0.062 99.961 14.32 2.2 0
S5 3CHI100 CB200 0.0868 99.897 82.96 2.2 0
S6 3CHI100 CB214 0.0239 0.002 40.1 2.2 0
S7 3CHI100 520_(P-Stm) 0.0689 100 25.95 2.2 0
S8 3CHI100 CB201 0.0941 80.117 35.06 2.2 0
S9 3CHI100 CB205 0.0275 76.829 19.08 2.2 0

[SUBAREAS]
;;Subcatchment N-Imperv N-Perv S-Imperv S-Perv PctZero RouteTo PctRouted
;;-----
S1 0.013 0.25 1.57 4.67 0 OUTLET
S10 0.013 0.25 1.57 4.67 0 OUTLET
S11 0.013 0.25 1.57 4.67 0 OUTLET
S12 0.013 0.25 1.57 4.67 0 OUTLET
S14_1 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S14_2 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S15 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S2 0.013 0.25 1.57 4.67 0 OUTLET
S3 0.013 0.25 1.57 4.67 0 OUTLET
S32 0.013 0.25 1.57 4.67 0 PREVIOUS 80
S4 0.013 0.25 1.57 4.67 0 OUTLET
S45 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S5 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S6 0.013 0.25 1.57 4.67 0 OUTLET
S7 0.013 0.25 1.57 4.67 0 OUTLET
S8 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S9 0.013 0.25 1.57 4.67 0 OUTLET

[INFILTRATION]
;;Subcatchment Param1 Param2 Param3 Param4 Param5
;;-----
S1 76.2 13.2 4.14 7 0
S10 76.2 13.2 4.14 7 0
S11 76.2 13.2 4.14 7 0
S12 76.2 13.2 4.14 7 0
S14_1 76.2 13.2 4.14 7 0
S14_2 76.2 13.2 4.14 7 0
S15 76.2 13.2 4.14 7 0
S2 76.2 13.2 4.14 7 0
S3 76.2 13.2 4.14 7 0
S32 76.2 13.2 4.14 7 0
S4 76.2 13.2 4.14 7 0
S45 76.2 13.2 4.14 7 0
S5 76.2 13.2 4.14 7 0
S6 76.2 13.2 4.14 7 0
S7 76.2 13.2 4.14 7 0
S8 76.2 13.2 4.14 7 0
S9 76.2 13.2 4.14 7 0

[JUNCTIONS]
;;Name Elevation MaxDepth InitDepth SurDepth Apended
;;-----
518_Orifice 81.361 4.106 0 0 0

[OUTFALLS]
;;Name Elevation Type Stage Data Gated Route To
;;-----
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 80.646 FIXED 81.28 NO

[STORAGE]
;;Name Elev. MaxDepth InitDepth Shape Curve Name/Params
;;-----
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 81.061 4.406 0.219 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
519_(P-Stm) 82.197 3.512 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
0 CB200 82.487 2.888 0 FUNCTIONAL 0 0 1.13 0
0 CB201 81.957 3.673 0 FUNCTIONAL 0 0 1.13 0
0 CB202 82.182 3.323 0 FUNCTIONAL 0 0 1.13 0
0 CB203 85.1800000001676 0
0 CB200 83.18 2.32 0 TABULAR CB200
0 CB201 85.5000000001435 0
0 CB202 82.76 2.89 0 TABULAR CB202
0 CB203 85.350000000931 0
0 CB204 82.75 2.75 0 TABULAR CB204
0 CB205 85.4500008023662 0
0 CB206 82.85 2.75 0 TABULAR CB205
0 CB207 85.540000000822731 0
0 CB208 83.3 2.04 0 TABULAR CB208
0 CB209 85.450000000821652 0
0 CB210 82.65 3 0 TABULAR CB210B
0 CB211 85.35 0
0 CB212 83.2 2.42 0 TABULAR CB212
0 CB213 84.75 0
0 CB214 83.15 1.75 0 TABULAR CB213
0 CB215 85.4 0
0 CB216 82.95 1.9 0 TABULAR CB214

[CONDUITS]
;;Name From Node To Node Length Roughness InOffset OutOffset
;;-----
C2 0 CB208 CB207 9.666 0.013 83.3 83.2
0 CB212A CB212 18.475 0.013 83.62 83.25
0 CB211 CB212 22.346 0.013 83.7 83.25
0 CB213 522_(P-Stm) 29.34 0.013 83.15 82.757
0 CB214 522_(P-Stm) 21.65 0.013 82.95 82.757
0 CB215 522_(P-Stm) 15.623 0.013 81.361 81.322
0 CB216 518_(P-Stm) 27.209 0.013 82.257 82.161
0 CB217 522_(P-Stm) 45.094 0.013 82.482 82.257
0 CB218 521_(P-Stm) 57.146 0.013 82.787 82.557
0 CB219 519_(P-Stm) 31.967 0.013 82.497 82.337
0 CB220 518_(P-Stm) 85.31 1.84 NO
0 CB221 85.6 1.84 NO
0 CB222 85.45 1.84 NO
0 CB223 85.55 1.84 NO
0 CB224 85.45 1.84 NO
0 CB225 85.65 1.84 NO
0 CB226 85.42 1.84 NO

[ORIFICES]
;;Name CloseTime From Node To Node Type Offset Qcoeff Gated
;;-----
OR1 0 518_(P-Stm) 518_Orifice SIDE 81.361 0.65 NO

[WEIRS]
;;Name EndCon EndCoeff From Node Surcharge To Node RoadWidth SurfType Coeff Curve CrestHt Qcoeff Gated
;;-----
W1 0 CB208 CB209 TRANSVERSE 85.31 1.84 NO
0 CB210B CB211 TRANSVERSE 85.6 1.84 NO
0 CB210B CB202 TRANSVERSE 85.45 1.84 NO
0 CB202 CB204 TRANSVERSE 85.55 1.84 NO
0 CB206 CB207 TRANSVERSE 85.45 1.84 NO
0 CB201 CB200 TRANSVERSE 85.65 1.84 NO
0 CB200 CB209 TRANSVERSE 85.42 1.84 NO

[OUTLETS]
;;Name Qexpon Gated From Node To Node Offset Type QTable/Qcoeff
;;-----
CB200 CB200 520_(P-Stm) 83.18 TABULAR/HEAD IPEX_Type_A
NO CB201 520_(P-Stm) 83.09 TABULAR/HEAD Vortex_ICD_100
NO CB202 521_(P-Stm) 82.76 TABULAR/HEAD IPEX_Type_A
NO CB203 521_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_70
NO CB204 522_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_65
NO CB205 522_(P-Stm) 82.85 TABULAR/HEAD Vortex_ICD_65
NO CB206 522_(P-Stm) 82.77 TABULAR/HEAD Vortex_ICD_70
NO CB207 522_(P-Stm) 83.15 TABULAR/HEAD Vortex_ICD_100
NO CB209 520_(P-Stm) 83.2 TABULAR/HEAD IPEX_Type_A

Post-Development 3-hour Chicago 1:100-year Event

January 2025

CB210B	CB210B	518_(P-Stm)	82.65	TABULAR/HEAD	Vortex_ICD_65	Vortex ICD 100	0.4	5.6	
NO						Vortex ICD 100	0.5	6.3	
CB212	CB212	521_(P-Stm)	83.2	TABULAR/HEAD	Vortex_ICD_100	Vortex ICD 100	0.6	6.9	
NO						Vortex ICD 100	0.7	7.5	
[XSECTIONS]						Vortex ICD 100	0.8	8	
;Link	Shape	Geom1	Geom2	Geom3	Geom4	Barrels	Vortex ICD 100	0.9	8.5
Culvert							Vortex ICD 100	1	8.9
;							Vortex ICD 100	1.2	9.8
;							Vortex ICD 100	1.4	10.6
C2	CIRCULAR	0.25	0	0	0	1	Vortex ICD 100	1.6	11.3
C4	CIRCULAR	0.25	0	0	0	1	Vortex ICD 100	1.8	12
C5	CIRCULAR	0.25	0	0	0	1	Vortex ICD 100	2	12.6
CB213	CIRCULAR	0.25	0	0	0	1	Vortex ICD 100	2.5	14.1
CB214	CIRCULAR	0.25	0	0	0	1	Vortex ICD 100	3	15.5
Pipe_-(104)_(P-Stm)_2_CIRCULAR_0.45							;Tempest Rating Curve for Vortex ICD 105, No grate allowance		
Pipe_-(110)_(P-Stm)_CIRCULAR_0.525							Vortex ICD 105	Rating	0
Pipe_-(111)_(P-Stm)_CIRCULAR_0.525							Vortex ICD 105		0
Pipe_-(71)_(P-Stm)_CIRCULAR_0.525							Vortex ICD 105		0.1
Pipe_-(72)_(P-Stm)_CIRCULAR_0.525							Vortex ICD 105		0.2
OR1	CIRCULAR	0.127	0	0	0	1	Vortex ICD 105		0.3
W1	RECT_OPEN	0.19		1.5	0		Vortex ICD 105		0.4
W2	RECT_OPEN	0.05		2.59	0		Vortex ICD 105		0.5
W3	RECT_OPEN	0.2		1.34	0		Vortex ICD 105		0.6
W4	RECT_OPEN	0.1		4.9	0		Vortex ICD 105		0.7
W5	RECT_OPEN	0.05		4.725	0		Vortex ICD 105		0.8
W6	RECT_OPEN	0.1		6	0		Vortex ICD 105		0.9
W7	RECT_OPEN	0.08		10.5	0		Vortex ICD 105		9.3
[LOSSES]							Vortex ICD 105		9.8
;Link	Kentry	Kexit	Kavg	Flap	Gate	Seepage	Vortex ICD 105		10.7
;							Vortex ICD 105		11.6
							Vortex ICD 105		12.4
							Vortex ICD 105		13.1
							Vortex ICD 105		13.9
							Vortex ICD 105		15.5
							Vortex ICD 105		17
[CURVES]									
;Name	Type	X-Value	Y-Value						
;									
CB210-OUT85.5	Rating	0	0				;Tempest Rating Curve for Vortex ICD 40, No grate allowance		
CB210-OUT85.5		85.5	0.04				Vortex ICD 40	Rating	0
CB210-OUT85.5		100	0.04				Vortex ICD 40		0.1
CB210-OUT85.5							Vortex ICD 40		0.2
CB210-OUT85.5							Vortex ICD 40		0.3
CB210-OUT85.5							Vortex ICD 40		0.4
CB210-OUT85.5							Vortex ICD 40		0.5
CB210-OUT85.5							Vortex ICD 40		0.6
CB210-OUT85.5							Vortex ICD 40		0.7
IPEX Type A ICD Rating Curve							Vortex ICD 40		0.8
IPEX Type A	Rating	0	0				Vortex ICD 40		0.9
IPEX Type A		0.1	5.7				Vortex ICD 40		1
IPEX Type A		0.2	8.1				Vortex ICD 40		1.2
IPEX Type A		0.3	9.9				Vortex ICD 40		1.4
IPEX Type A		0.4	11.4				Vortex ICD 40		1.6
IPEX Type A		0.5	12.8				Vortex ICD 40		1.7
IPEX Type A		0.6	14				Vortex ICD 40		1.8
IPEX Type A		0.7	15.1				Vortex ICD 40		1.9
IPEX Type A		0.8	16.2				Vortex ICD 40		2.2
IPEX Type A		0.9	17.2				Vortex ICD 40		2.4
IPEX Type A		1	18.1						
IPEX Type A		1.2	19.8						
IPEX Type A		1.4	21.4						
IPEX Type A		1.6	22.9						
IPEX Type A		1.8	24.3						
IPEX Type A		2	25.6						
IPEX Type A		2.5	28.6						
IPEX Type A		3	31.3						
IPEX Type B ICD Rating Curve									
IPEX Type B	Rating	0	0						
IPEX Type B		0.1	8.1						
IPEX Type B		0.2	11.5						
IPEX Type B		0.3	14.1						
IPEX Type B		0.4	16.2						
IPEX Type B		0.5	18.2						
IPEX Type B		0.6	19.9						
IPEX Type B		0.7	21.5						
IPEX Type B		0.8	23						
IPEX Type B		0.9	24.4						
IPEX Type B		1	25.7						
IPEX Type B		1.2	28.1						
IPEX Type B		1.4	30.4						
IPEX Type B		1.6	32.5						
IPEX Type B		1.8	34.4						
IPEX Type B		2	36.3						
IPEX Type B		2.5	40.6						
IPEX Type B		3	44.5						
IPEX Type C ICD Rating Curve									
IPEX Type C	Rating	0	0						
IPEX Type C		0.1	10.6						
IPEX Type C		0.2	15						
IPEX Type C		0.3	18.3						
IPEX Type C		0.4	21.2						
IPEX Type C		0.5	23.7						
IPEX Type C		0.6	25.9						
IPEX Type C		0.7	28						
IPEX Type C		0.8	29.9						
IPEX Type C		0.9	31.7						
IPEX Type C		1	33.5						
IPEX Type C		1.2	36.6						
IPEX Type C		1.4	39.6						
IPEX Type C		1.6	42.3						
IPEX Type C		1.8	44.9						
IPEX Type C		2	47.3						
IPEX Type C		2.5	52.9						
IPEX Type C		3	57.9						
IPEX Type AA ICD Rating Curve									
IPEX Type D	Rating	0	0						
IPEX Type D		0.1	15.4						
IPEX Type D		0.2	21.7						
IPEX Type D		0.3	26.6						
IPEX Type D		0.4	30.7						
IPEX Type D		0.5	34.3						
IPEX Type D		0.6	37.6						
IPEX Type D		0.7	40.6						
IPEX Type D		0.8	43.4						
IPEX Type D		0.9	46.1						
IPEX Type D		1	48.5						
IPEX Type D		1.2	53.2						
IPEX Type D		1.4	57.4						
IPEX Type D		1.6	61.4						
IPEX Type D		1.8	65.1						
IPEX Type D		2	68.7						
IPEX Type D		2.5	76.8						
IPEX Type D		3	84.1						
IPEX Type E ICD Rating Curve									
IPEX Type E	Rating	0	0						
IPEX Type E		0.1	20.5						
IPEX Type E		0.2	26.9						
IPEX Type E		0.3	35.5						
IPEX Type E		0.4	40.9						
IPEX Type E		0.5	45.8						
IPEX Type E		0.6	50.1						
IPEX Type E		0.7	54.2						
IPEX Type E		0.8	57.9						
IPEX Type E		0.9	61.4						
IPEX Type E		1	64.7						
IPEX Type E		1.2	70.9						
IPEX Type E		1.4	76.6						
IPEX Type E		1.6	81.9						
IPEX Type E		1.8	86.8						
IPEX Type E		2	91.5						
IPEX Type E		2.5	102.3						
IPEX Type E		3	112.1						
;Tempest Rating Curve for Vortex ICD 100, No grate allowance									
Vortex ICD 100	Rating	0	0						
Vortex ICD 100		0.1	2.8						
Vortex ICD 100		0.2	4						
Vortex ICD 100		0.3	4.9						
;Tempest Rating Curve for Vortex ICD 65, No grate allowance									
Vortex ICD 65	Rating	0	0						
Vortex ICD 65		0.1	1.2						
Vortex ICD 65		0.2	1.6						
Vortex ICD 65		0.3	2						
Vortex ICD 65		0.4	2.3						
Vortex ICD 65		0.5	2.5						
Vortex ICD 65		0.6	2.8						
Vortex ICD 65		0.7	3						
Vortex ICD 65		0.8	3.2						
Vortex ICD 65		0.9	3.4						
Vortex ICD 65		1	3.6						
Vortex ICD 65		1.2	4						
Vortex ICD 65		1.4	4.3						
Vortex ICD 65		1.6	4.6						
Vortex ICD 65		1.8	4.8						
Vortex ICD 65		2	5.1						
Vortex ICD 65		2.5	5.6						
Vortex ICD 65		3	5.6						

Post-Development 3-hour Chicago 1:100-year Event

January 2025

Vortex ICD 65 1.6 4.6
 Vortex ICD 65 1.8 4.9
 Vortex ICD 65 2 5.1
 Vortex ICD 65 2.5 5.7
 Vortex ICD 65 3 6.3

;Tempest Rating Curve for Vortex ICD 70, No grate allowance

Vortex ICD 70	Rating	0
Vortex ICD 70	0.1	1.3
Vortex ICD 70	0.2	1.9
Vortex ICD 70	0.3	2.3
Vortex ICD 70	0.4	2.7
Vortex ICD 70	0.5	3
Vortex ICD 70	0.6	3.3
Vortex ICD 70	0.7	3.6
Vortex ICD 70	0.8	3.8
Vortex ICD 70	0.9	4.1
Vortex ICD 70	1	4.3
Vortex ICD 70	1.2	4.7
Vortex ICD 70	1.4	5.1
Vortex ICD 70	1.6	5.5
Vortex ICD 70	1.8	5.8
Vortex ICD 70	2	6.1
Vortex ICD 70	2.5	6.8
Vortex ICD 70	3	7.5

;Tempest Rating Curve for Vortex ICD 75, No grate allowance

Vortex ICD 75	Rating	0
Vortex ICD 75	0.1	1.6
Vortex ICD 75	0.2	2.2
Vortex ICD 75	0.3	2.7
Vortex ICD 75	0.4	3.2
Vortex ICD 75	0.5	3.5
Vortex ICD 75	0.6	3.9
Vortex ICD 75	0.7	4.2
Vortex ICD 75	0.8	4.5
Vortex ICD 75	0.9	4.8
Vortex ICD 75	1	5
Vortex ICD 75	1.2	5.5
Vortex ICD 75	1.4	5.9
Vortex ICD 75	1.6	6.3
Vortex ICD 75	1.8	6.7
Vortex ICD 75	2	7.1
Vortex ICD 75	2.5	7.9
Vortex ICD 75	3	8.7

;Tempest Rating Curve for Vortex ICD 80, No grate allowance

Vortex ICD 80	Rating	0
Vortex ICD 80	0.1	1.8
Vortex ICD 80	0.2	2.6
Vortex ICD 80	0.3	3.1
Vortex ICD 80	0.4	3.6
Vortex ICD 80	0.5	4
Vortex ICD 80	0.6	4.4
Vortex ICD 80	0.7	4.8
Vortex ICD 80	0.8	5.1
Vortex ICD 80	0.9	5.4
Vortex ICD 80	1	5.7
Vortex ICD 80	1.2	6.3
Vortex ICD 80	1.4	6.8
Vortex ICD 80	1.6	7.2
Vortex ICD 80	1.8	7.7
Vortex ICD 80	2	8.1
Vortex ICD 80	2.5	9
Vortex ICD 80	3	9.9

;Tempest Rating Curve for Vortex ICD 85, No grate allowance

Vortex ICD 85	Rating	0
Vortex ICD 85	0.1	2
Vortex ICD 85	0.2	2.9
Vortex ICD 85	0.3	3.5
Vortex ICD 85	0.4	4.1
Vortex ICD 85	0.5	4.5
Vortex ICD 85	0.6	5
Vortex ICD 85	0.7	5.4
Vortex ICD 85	0.8	5.7
Vortex ICD 85	0.9	6.1
Vortex ICD 85	1	6.4
Vortex ICD 85	1.2	7
Vortex ICD 85	1.4	7.6
Vortex ICD 85	1.6	8.1
Vortex ICD 85	1.8	8.6
Vortex ICD 85	2	9.1
Vortex ICD 85	2.5	10.1
Vortex ICD 85	3	11.1

;Tempest Rating Curve for Vortex ICD 90, No grate allowance

Vortex ICD 90	Rating	0
Vortex ICD 90	0.1	2.2
Vortex ICD 90	0.2	3.2
Vortex ICD 90	0.3	3.9
Vortex ICD 90	0.4	4.5
Vortex ICD 90	0.5	5.1
Vortex ICD 90	0.6	5.5
Vortex ICD 90	0.7	6
Vortex ICD 90	0.8	6.4
Vortex ICD 90	0.9	6.8
Vortex ICD 90	1	7.2
Vortex ICD 90	1.2	7.9
Vortex ICD 90	1.4	8.5
Vortex ICD 90	1.6	9.1
Vortex ICD 90	1.8	9.6
Vortex ICD 90	2	10.2
Vortex ICD 90	2.5	11.4
Vortex ICD 90	3	12.5

;Tempest Rating Curve for Vortex ICD 95, No grate allowance

Vortex ICD 95	Rating	0
Vortex ICD 95	0.1	2.6
Vortex ICD 95	0.2	3.6
Vortex ICD 95	0.3	4.4
Vortex ICD 95	0.4	5.1
Vortex ICD 95	0.5	5.7
Vortex ICD 95	0.6	6.2
Vortex ICD 95	0.7	6.7
Vortex ICD 95	0.8	7.1
Vortex ICD 95	0.9	7.6
Vortex ICD 95	1	8
Vortex ICD 95	1.2	8.7
Vortex ICD 95	1.4	9.4
Vortex ICD 95	1.6	10.1
Vortex ICD 95	1.8	10.7
Vortex ICD 95	2	11.3
Vortex ICD 95	2.5	12.6
Vortex ICD 95	3	13.8

CB200 Storage 0 0.36
 CB200 2 0.66
 CB200 2.24 217.87
 CB200 2.32 217.87

CB201 Storage 0 0.36
 CB201 2.41 0.36
 CB201 2.56 169.64
 CB201 2.66 169.64

CB202 Storage 0 0.36
 CB202 2.6 0.36
 CB202 2.79 273.92
 CB202 2.89 273.92

CB203 Storage 0 0.36
 CB203 2.6 0.36
 CB203 2.9 178.09

CB204 Storage 0 0.36
 CB204 2.6 0.36
 CB204 2.75 146.08

Post-Development 3-hour Chicago 1:100-year Event

January 2025

```
;;Storage Node X-Coord Y-Coord
;;
[SYMBOLS]
;;Gage X-Coord Y-Coord
;;
***** ELEMENT COUNT *****
Element Count
*****
Number of rain gages ..... 1
Number of subcatchments .... 17
Number of nodes ..... 23
Number of links ..... 29
Number of pollutants ..... 0
Number of land uses ..... 0

***** RAINGAGE SUMMARY *****
Raingage Summary
*****
Name Data Source Data Type Recording Interval
----- 3CHI100 3CHI100 INTENSITY 10 min.

***** SUBCATCHMENT SUMMARY *****
Subcatchment Summary
*****
Name Area Width %Imperv %Slope Rain Gage Outlet
-----
S1 0.02 29.61 0.06 2.2000 3CHI100 CB208
S10 0.03 55.32 99.62 2.2000 3CHI100 CB204
S11 0.13 65.66 86.66 2.2000 3CHI100 CB202
S12 0.01 6.44 0.25 2.2000 3CHI100 CB213
S13 0.01 22.18 52.76 2.2000 3CHI100 CB211
S14_1 0.02 68.12 31.75 2.2000 3CHI100 CB212
S14_2 0.04 108.74 25.77 2.2000 3CHI100 CB210B
S15 0.07 33.61 63.05 2.2000 3CHI100 CB209
S2 0.07 45.79 96.63 2.2000 3CHI100 CB207
S3 0.07 29.70 14.29 2.2000 3CHI100 CB214
S32 0.05 24.67 99.97 2.2000 3CHI100 CB206
S4 0.04 12.32 99.76 2.2000 3CHI100 CB203
S45 0.02 12.32 99.76 2.2000 3CHI100 CB200
S5 0.09 122.16 89.90 2.2000 3CHI100 CB214
S6 0.02 40.30 0.00 2.2000 3CHI100 CB214
S7 0.07 25.95 100.00 2.2000 3CHI100 520_(P-)
Stm) S8 0.09 35.06 80.12 2.2000 3CHI100 CB201
S9 0.03 19.08 76.83 2.2000 3CHI100 CB205

***** NODE SUMMARY *****
Node Summary
*****
Name Type Invert Elev. Max. Depth Ponded Area External Inflow
-----
518 Orifice JUNCTION 81.36 -0.11 0.0
518A_(P-Stm) OUTFALL 80.65 1.13 0.0
518_(P-Stm) STORAGE 81.06 4.41 0.0
519_(P-Stm) STORAGE 82.20 3.51 0.0
520_(P-Stm) STORAGE 82.49 2.89 0.0
521_(P-Stm) STORAGE 81.96 3.67 0.0
522_(P-Stm) STORAGE 82.18 3.32 0.0
CB200 STORAGE 83.16 2.32 0.0
CB201 STORAGE 83.09 2.66 0.0
CB202 STORAGE 82.76 2.89 0.0
CB203 STORAGE 82.75 2.90 0.0
CB204 STORAGE 82.75 2.75 0.0
CB205 STORAGE 82.85 2.75 0.0
CB206 STORAGE 82.77 2.73 0.0
CB207 STORAGE 83.15 2.30 0.0
CB208 STORAGE 83.30 2.04 0.0
CB209 STORAGE 83.20 1.90 0.0
CB210B STORAGE 82.65 3.00 0.0
CB211 STORAGE 83.70 1.90 0.0
CB212 STORAGE 83.20 2.42 0.0
CB212A STORAGE 83.62 2.00 0.0
CB213 STORAGE 83.15 1.75 0.0
CB214 STORAGE 82.95 1.90 0.0

***** LINK SUMMARY *****
Link Summary
*****
Name From Node To Node Type Length %Slope
Roughness
-----
- C2 CB208 CB207 CONDUIT 9.7 1.0346
0.0130 0.0130 CB212A CB212 CONDUIT 18.5 2.0031
0.0130 C5 CB211 CB212 CONDUIT 22.3 2.0142
0.0130 CB213 CB213 522_(P-Stm) CONDUIT 29.3 1.3396
0.0130 CB214 CB214 522_(P-Stm) CONDUIT 21.6 0.8915
0.0130 Pipe_-(104)_ (P-Stm)_2 518_Orifice 518A_(P-Stm) CONDUIT 15.6 0.2496
0.0130 Pipe_-(110)_ (P-Stm) 521_(P-Stm) 518_(P-Stm) CONDUIT 27.2 0.3528
0.0130 Pipe_-(111)_ (P-Stm) 522_(P-Stm) 521_(P-Stm) CONDUIT 45.1 0.4990
0.0130 Pipe_-(71)_ (P-Stm) 520_(P-Stm) 519_(P-Stm) CONDUIT 57.1 0.4025
0.0130 Pipe_-(72)_ (P-Stm) 519_(P-Stm) 518_(P-Stm) CONDUIT 32.0 0.5005
0.0130 OR1 518_(P-Stm) 518 Orifice ORIFICE
W1 CB208 CB209 WEIR
W2 CB210B CB211 WEIR
W3 CB210B CB212 WEIR
W4 CB202 CB204 WEIR
W5 CB206 CB207 WEIR
W6 CB201 CB200 WEIR
W7 CB200 CB209 WEIR
CB200 CB200 520_(P-Stm) OUTLET
CB201 CB201 520_(P-Stm) OUTLET
CB202 CB202 521_(P-Stm) OUTLET
CB203 CB203 521_(P-Stm) OUTLET
CB204 CB204 522_(P-Stm) OUTLET
CB205 CB205 522_(P-Stm) OUTLET
CB206 CB206 522_(P-Stm) OUTLET
CB207 CB207 522_(P-Stm) OUTLET
CB209 CB209 520_(P-Stm) OUTLET
CB210B CB210B 518_(P-Stm) OUTLET
CB212 CB212 521_(P-Stm) OUTLET

***** CROSS SECTION SUMMARY *****
Cross Section Summary
*****
Conduit Shape Full Depth Full Area Hyd. Rad. Max. Width No. of Barrels Full Flow
-----
C2 CIRCULAR 0.25 0.05 0.06 0.25 1 60.49
C4 CIRCULAR 0.25 0.05 0.06 0.25 1 84.17
C5 CIRCULAR 0.25 0.05 0.06 0.25 1 84.40
CB213 CIRCULAR 0.25 0.05 0.06 0.25 1 68.83
CB214 CIRCULAR 0.25 0.05 0.06 0.25 1 56.15
142_46 Pipe_-(104)_ (P-Stm)_2 CIRCULAR 0.45 0.16 0.11 0.45 1
Pipe_-(110)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 255.47
Pipe_-(111)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 303.80
Pipe_-(71)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 272.85
Pipe_-(72)_ (P-Stm) CIRCULAR 0.53 0.22 0.13 0.53 1 304.28
```

 Analysis Options

 Flow Units LPS
 Process Models:
 Rainfall/Runoff YES
 RDI NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
 Infiltration Method HORTON
 Flow Routing Method DYNWAVE
 Surcharge Method EXTRAN
 Starting Date 01/01/2000 00:00:00
 Ending Date 01/01/2000 06:00:00
 Antecedent Dry Days 0.0
 Report Time Step 00:01:00
 Wet Time Step 00:01:00
 Dry Time Step 00:01:00
 Routing Time Step 0.00 sec
 Variable Time Step YES
 Maximum Trials 8
 Number of Threads 1
 Head Tolerance 0.001500 m

 Runoff Quantity Continuity Volume hectare-m Depth mm

 Total Precipitation 0.059 71.708
 Evaporation Loss 0.000 0.000
 Infiltration Loss 0.010 12.469
 Surface Runoff 0.048 58.202
 Final Storage 0.001 1.137
 Continuity Error (%) -0.141

 Flow Routing Continuity Volume hectare-m Volume 10^6 ltr

 Dry Weather Inflow 0.000 0.000
 Wet Weather Inflow 0.048 0.479
 Groundwater Inflow 0.000 0.000
 RDI Inflow 0.000 0.000
 External Inflow 0.000 0.000
 External Outflow 0.048 0.477
 Flooding Loss 0.000 0.000
 Evaporation Loss 0.000 0.000
 Extraction Loss 0.000 0.000
 Initial Stored Volume 0.000 0.000
 Final Stored Volume 0.000 0.002
 Continuity Error (%) -0.030

 Time-Step Critical Elements

 None

 Highest Flow Instability Indexes

 Link W3 (I)
 Convergence obtained at all time steps.

 Most Frequent Nonconverging Nodes

 Convergence obtained at all time steps.

 Routing Time Step Summary

 Minimum Time Step 0.50 sec
 Average Time Step 1.00 sec
 Maximum Time Step 1.00 sec
 % of Time in Steady State 0.00
 Average Iterations per Step 2.00
 % of Steps Not Converging 0.00
 Time Step Frequencies
 1.000 - 0.875 sec 100.00 %
 0.771 - 0.758 sec 0.00 %
 0.758 - 0.660 sec 0.00 %
 0.660 - 0.574 sec 0.00 %
 0.574 - 0.500 sec 0.00 %

 Subcatchment Runoff Summary

Total	Total	Peak	Total	Total	Total	Imperv	Perv
Runoff	Runoff	Runoff	Precip	Runon	Evap	Infil	Runoff
Subcatchment				mm	mm	mm	mm
mm	10^6 ltr	LPS					
S1		71.71	0.00	0.00	43.70	0.04	28.05
28.09	0.01	7.47	0.392				
S10		71.71	0.00	0.00	0.16	69.98	0.12
70.09	0.02	15.18	0.977				
S11		71.71	0.00	0.00	5.78	60.87	3.80
64.67	0.08	61.68	0.902				
S12		71.71	0.00	0.00	45.10	0.18	26.46
26.64	0.00	3.78	0.371				
S13		71.71	0.00	0.00	24.62	37.03	46.38
46.38 ⁻¹	0.01	5.46	0.647				
S14_2		71.71	0.00	0.00	32.72	22.28	38.63
38.63 ⁻²	0.01	8.14	0.539				
S15		71.71	0.00	0.00	34.87	18.08	36.59
36.59	0.01	16.73	0.510				
S2		71.71	0.00	0.00	16.22	44.29	10.30
54.59	0.04	33.11	0.261				
S3		71.71	0.00	0.00	1.46	67.87	0.98
68.85	0.05	34.97	0.960				
S32		71.71	0.00	0.00	39.41	10.03	30.12
32.13	0.02	18.19	0.448				
S4		71.71	0.00	0.00	0.01	70.21	0.01
70.22	0.03	22.26	0.979				
S5		71.71	0.00	0.00	0.02	70.22	0.01
70.22 ⁻²	0.02	10.98	0.979				
S5		71.71	0.00	0.00	4.36	66.05	2.90
66.05	0.06	42.36	0.921				
S6		71.71	0.00	0.00	43.69	0.00	28.10
28.10	0.01	9.63	0.392				
S7		71.71	0.00	0.00	0.00	70.22	0.00
70.22 ⁻¹	0.05	33.94	0.979				
S8		71.71	0.00	0.00	8.68	61.86	5.60
61.86	0.06	44.54	0.863				
S9		71.71	0.00	0.00	10.06	53.97	6.58
60.55	0.02	13.15	0.844				

 Node Depth Summary

Node	Type	Average Depth Meters	Maximum Depth Meters	Maximum HGL Meters	Time of Max Occurrence days hr:min	Reported Max Depth Meters
------	------	----------------------	----------------------	--------------------	------------------------------------	---------------------------

518 Orifice	JUNCTION	0.08	0.20	81.56	0	01:37	0.20
518A (P-Stm)	OUTFALL	0.63	0.63	81.28	0	00:00	0.63
518 (P-Stm)	STORAGE	1.27	3.78	84.84	0	01:37	3.78
519 (P-Stm)	STORAGE	0.81	2.65	84.84	0	01:37	2.65
520 (P-Stm)	STORAGE	0.72	2.36	84.85	0	01:37	2.36
521 (P-Stm)	STORAGE	0.90	2.89	84.84	0	01:37	2.89
522 (P-Stm)	STORAGE	0.81	2.66	84.85	0	01:37	2.66
CB200	STORAGE	0.43	2.15	85.33	0	01:20	2.15
CB201	STORAGE	0.58	2.15	85.66	0	01:11	2.57
CB202	STORAGE	0.60	2.74	85.50	0	01:20	2.74
CB203	STORAGE	0.54	2.66	85.41	0	01:11	2.65
CB204	STORAGE	0.65	2.70	85.45	0	01:20	2.70
CB205	STORAGE	0.56	2.69	85.54	0	01:20	2.69
CB206	STORAGE	0.63	2.70	85.47	0	01:20	2.70
CB207	STORAGE	0.58	2.18	85.33	0	01:20	2.17
CB208	STORAGE	0.52	2.03	85.33	0	01:21	2.03
CB209	STORAGE	0.37	1.79	84.99	0	01:25	1.79
CB210B	STORAGE	0.64	2.85	85.50	0	01:20	2.85
CB211	STORAGE	0.19	1.18	84.88	0	01:36	1.18
CB212	STORAGE	0.32	1.67	84.87	0	01:35	1.67
CB212A	STORAGE	0.21	1.26	84.88	0	01:35	1.25
CB213	STORAGE	0.32	1.70	84.85	0	01:38	1.70
CB214	STORAGE	0.37	1.90	84.85	0	01:36	1.90

 Node Inflow Summary

Flow Balance Error Node Percent	Type	Maximum	Maximum	Lateral	Total
		Lateral	Total	Time of Max Inflow	Inflow
518 Orifice	JUNCTION	0.00	66.10	0 01:37	0
518A (P-Stm)	OUTFALL	0.00	66.10	0 01:37	0
518 (P-Stm)	STORAGE	0.00	84.12	0 01:07	0
519 (P-Stm)	STORAGE	0.00	92.47	0 01:03	0
520 (P-Stm)	STORAGE	33.94	96.71	0 01:05	0.0482
521 (P-Stm)	STORAGE	0.00	78.54	0 01:05	0
522 (P-Stm)	STORAGE	0.00	60.78	0 01:06	0
CB200	STORAGE	42.36	43.45	0 01:10	0.0573
CB201	STORAGE	44.54	44.54	0 01:10	0.0582
CB202	STORAGE	61.68	61.68	0 01:10	0.0821
CB203	STORAGE	10.98	10.98	0 01:10	0.0156
CB204	STORAGE	15.18	15.18	0 01:10	0.0215
CB205	STORAGE	13.15	13.15	0 01:10	0.0167
CB206	STORAGE	22.26	22.26	0 01:10	0.0316
CB207	STORAGE	34.97	51.81	0 01:10	0.0489
CB208	STORAGE	7.47	26.09	0 01:03	0.00525
CB209	STORAGE	33.11	33.11	0 01:10	0.0399
CB210B	STORAGE	16.73	37.44	0 01:09	0.0136
CB211	STORAGE	5.46	7.13	0 01:08	0.00538
CB212	STORAGE	8.14	13.45	0 01:06	0.00691
CB212A	STORAGE	0.00	5.30	0 01:09	0
CB213	STORAGE	3.78	20.64	0 01:06	0.00397
CB214	STORAGE	27.81	27.81	0 01:10	0.0234

 Node Surcharge Summary

No nodes were surcharged.

 Node Flooding Summary

No nodes were flooded.

Storage Unit LPS	Average	Avg	Evap	Exfil	Maximum	Max	Time of Max
	Volume	Pcnt	Pcnt	Pcnt	Volume	Pcnt	Occurrence
518 (P-Stm)	0.001	28.9	0.0	0.0	0.004	85.8	0 01:37
66.09 (P-Stm)	0.001	23.0	0.0	0.0	0.003	75.4	0 01:37
519 (P-Stm)	0.001	24.9	0.0	0.0	0.003	81.7	0 01:37
520 (P-Stm)	0.001	24.9	0.0	0.0	0.003	78.6	0 01:37
521 (P-Stm)	0.001	24.5	0.0	0.0	0.003	80.1	0 01:37
522 (P-Stm)	0.001	24.5	0.0	0.0	0.003	80.1	0 01:37
CB200	0.001	2.0	0.0	0.0	0.011	25.0	0 01:20
CB201	0.002	6.1	0.0	0.0	0.015	49.8	0 01:11
CB202	0.001	2.7	0.0	0.0	0.015	28.0	0 01:20
CB203	0.000	0.8	0.0	0.0	0.002	6.7	0 01:11
CB204	0.001	6.4	0.0	0.0	0.006	46.3	0 01:20
CB205	0.000	4.7	0.0	0.0	0.003	42.4	0 01:20
CB206	0.001	8.4	0.0	0.0	0.004	67.6	0 01:10
CB207	0.002	6.2	0.0	0.0	0.012	40.2	0 01:20
CB208	0.002	15.2	0.0	0.0	0.010	91.1	0 01:21
CB209	0.000	3.6	0.0	0.0	0.005	39.9	0 01:25

Post-Development 3-hour Chicago 1:100-year Event

January 2025

CB210B	0.001	4.8	0.0	0.0	0.008	42.5	0	01:20
7.22								
CB211	0.000	0.5	0.0	0.0	0.000	3.0	0	01:36
5.42								
CB212	0.000	1.7	0.0	0.0	0.001	8.7	0	01:35
10.15								
CB212A	0.000	10.6	0.0	0.0	0.000	62.8	0	01:35
1.32								
CB213	0.000	4.6	0.0	0.0	0.000	49.4	0	01:38
7.52								
CB214	0.000	8.1	0.0	0.0	0.005	97.2	0	01:36
25.87								

Outfall Loading Summary

Outfall Node	Flow Freq Pcnt	Avg Flow LPS	Max Flow LPS	Total Volume 10^6 ltr
518A (P-Stm)	67.75	32.60	66.10	0.477
System	67.75	32.60	66.10	0.477

Link Flow Summary

Link	Type	Maximum Flow LPS	Time of Occurrence days hr:min	Maximum Veloc m/sec	Max/ Full Flow	Max/ Full Depth
C2	CONDUIT	24.70	0 01:03	0.50	0.41	1.00
C4	CONDUIT	5.30	0 01:09	0.15	0.06	1.00
C5	CONDUIT	5.42	0 01:06	0.66	0.06	1.00
CB213	CONDUIT	18.57	0 01:06	0.38	0.27	1.00
CB214	CONDUIT	25.87	0 01:09	0.53	0.46	1.00
Pipe_-(104)_-(P-Stm)	CONDUIT	66.10	0 01:37	1.05	0.46	0.42
Pipe_-(110)_-(P-Stm)	CONDUIT	64.19	0 01:08	0.72	0.40	1.00
Pipe_-(111)_-(P-Stm)	CONDUIT	40.32	0 01:05	0.49	0.13	1.00
Pipe_-(71)_-(P-Stm)	CONDUIT	92.47	0 01:03	1.04	0.34	1.00
Pipe_-(72)_-(P-Stm)	CONDUIT	65.69	0 01:06	0.89	0.22	1.00
OR1	ORIFICE	66.10	0 01:37			1.00
W1	WEIR	5.11	0 01:21			0.50
W2	WEIR	0.00	0 01:00			0.00
W3	WEIR	20.32	0 01:09			0.25
W4	WEIR	0.00	0 00:00			0.00
W5	WEIR	16.85	0 01:10			0.31
W6	WEIR	10.31	0 01:11			0.10
W7	WEIR	0.00	0 00:00			0.00
CB200	DUMMY	26.02	0 01:05			
CB201	DUMMY	0.08	0 01:04			
CB202	DUMMY	24.19	0 01:02			
CB203	DUMMY	5.70	0 01:07			
CB204	DUMMY	5.52	0 01:03			
CB205	DUMMY	5.18	0 01:06			
CB206	DUMMY	6.86	0 01:02			
CB207	DUMMY	12.67	0 01:04			
CB209	DUMMY	23.04	0 01:05			
CB210B	DUMMY	5.01	0 01:06			
CB212	DUMMY	5.95	0 01:05			

Flow Classification Summary

Conduit	Adjusted /Actual Length	Fraction of Time in Flow Class							
		Dry	Dry	Up Dry	Down Dry	Sub Crit	Up Crit	Down Crit	Norm Ctrl
C2	1.00	0.05	0.01	0.00	0.39	0.00	0.00	0.56	0.07
C4	1.00	0.17	0.01	0.00	0.47	0.00	0.00	0.03	0.00
C5	1.00	0.15	0.00	0.00	0.28	0.00	0.00	0.56	0.05
CB213	1.00	0.05	0.00	0.00	0.32	0.00	0.00	0.63	0.05
CB214	1.00	0.05	0.00	0.00	0.32	0.00	0.00	0.63	0.03
Pipe_-(104)_-(P-Stm)_-2	1.00	0.07	0.00	0.00	0.00	0.00	0.00	0.93	0.00
Pipe_-(110)_-(P-Stm)	1.00	0.06	0.00	0.00	0.38	0.00	0.00	0.56	0.00
Pipe_-(111)_-(P-Stm)	1.00	0.06	0.00	0.00	0.94	0.00	0.00	0.00	0.58
Pipe_-(71)_-(P-Stm)	1.00	0.06	0.00	0.00	0.34	0.00	0.00	0.60	0.03
Pipe_-(72)_-(P-Stm)	1.00	0.07	0.00	0.00	0.37	0.00	0.00	0.57	0.02

Conduit Surcharge Summary

Conduit	Hours Full				Hours Above Full Normal Flow	Hours Capacity Limited
	Both Ends	Upstream	Dnstream			
C2	1.5	1.76	1.80	0.01	0.01	
C4	1.23	1.32	1.44	0.01	0.01	
C5	1.23	1.23	1.55	0.01	0.01	
CB213	1.50	1.50	1.74	0.01	0.01	
CB214	1.63	1.63	1.74	0.01	0.01	
Pipe_-(110)_-(P-Stm)	1.90	1.90	1.98	0.01	0.01	
Pipe_-(111)_-(P-Stm)	1.74	1.74	1.90	0.01	0.01	
Pipe_-(71)_-(P-Stm)	1.56	1.56	1.69	0.01	0.01	
Pipe_-(72)_-(P-Stm)	1.73	1.73	1.85	0.01	0.01	

Analysis begun on: Tue Jan 28 12:44:03 2025
 Analysis ended on: Tue Jan 28 12:44:04 2025
 Total elapsed time: 00:00:01

Post-Development 24-hour SCS 1:100-year Event

[TITLE]
;;Project Title/Notes

[OPTIONS]
;;Option Value
FLOW_UNITS LPS
INFILTRATION HORTON
FLOW_ROUTING DYNWAVE
LINK_OFFSETS ELEVATION
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO

START_DATE 01/01/2000
START_TIME 00:00:00
REPORT_START_DATE 01/01/2000
REPORT_START_TIME 00:00:00
END_DATE 01/01/2000
END_TIME 06:00:00
SWEEP_START 01/01
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 00:01:00
WET_STEP 00:01:00
DRY_STEP 00:01:00
ROUTING_STEP 00:00:00
RULE_STEP 00:00:00

INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_MAIN_EQNATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SLOPE 0
MAX_TRIALS 8
HEAD_TOLERANCE 0.0015
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINIMUM_STEP 0.5
THREADS 12

[EVAPORATION]
;;Data Source Parameters
CONSTANT 0.0
DRY_ONLY NO

[RAINGAGES]
;;Name Format Interval SCF Source
3CHI100 INTENSITY 0:10 1.0 TIMESERIES 3CHI100

[SUBCATCHMENTS]
;;Name Rain Gage Outlet Area %Imperv Width %Slope Curblen
ShowPack -----
S1 3CHI100 CB208 0.0187 0.061 29.61 2.2 0
S10 3CHI100 CB204 0.0307 99.617 55.32 2.2 0
S11 3CHI100 CB202 0.127 86.66 65.66 2.2 0
S12 3CHI100 CB213 0.0149 0.253 6.44 2.2 0
S14_1 3CHI100 CB211 0.0156 52.17 22.78 2.2 0
S14_2 3CHI100 CB212 0.0179 31.754 58.2 2.2 0
S15 3CHI100 CB210B 0.0372 25.766 108.74 2.2 0
S2 3CHI100 CB209 0.0731 63.05 33.61 2.2 0
S3 3CHI100 CB207 0.071 96.627 45.79 2.2 0
S32 3CHI100 CB214 0.052 14.286 29.7 2.2 0
S4 3CHI100 CB206 0.045 99.974 24.67 2.2 0
S45 3CHI100 CB203 0.062 99.961 14.32 2.2 0
S5 3CHI100 CB200 0.0868 99.897 82.96 2.2 0
S6 3CHI100 CB214 0.0239 0.002 40.1 2.2 0
S7 3CHI100 520_(P-Stm) 0.0681 100 25.95 2.2 0
S8 3CHI100 CB201 0.0941 80.117 35.06 2.2 0
S9 3CHI100 CB205 0.0275 76.829 19.08 2.2 0

[SUBAREAS]
;;Subcatchment N-Imperv N-Perv S-Imperv S-Perv PctZero RouteTo PctRouted
S1 0.013 0.25 1.57 4.67 0 OUTLET
S10 0.013 0.25 1.57 4.67 0 OUTLET
S11 0.013 0.25 1.57 4.67 0 OUTLET
S12 0.013 0.25 1.57 4.67 0 OUTLET
S14_1 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S14_2 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S15 0.013 0.25 1.57 4.67 0 PREVIOUS 100
S2 0.013 0.25 1.57 4.67 0 OUTLET
S3 0.013 0.25 1.57 4.67 0 OUTLET
S32 0.013 0.25 1.57 4.67 0 PREVIOUS 80
S4 0.013 0.25 1.57 4.67 0 OUTLET
S45 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S5 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S6 0.013 0.25 1.57 4.67 0 OUTLET
S7 0.013 0.25 1.57 4.67 0 OUTLET
S8 0.013 0.25 1.57 4.67 0 IMPERVIOUS 100
S9 0.013 0.25 1.57 4.67 0 OUTLET

[INFILTRATION]
;;Subcatchment Param1 Param2 Param3 Param4 Param5
S1 76.2 13.2 4.14 7 0
S10 76.2 13.2 4.14 7 0
S11 76.2 13.2 4.14 7 0
S12 76.2 13.2 4.14 7 0
S14_1 76.2 13.2 4.14 7 0
S14_2 76.2 13.2 4.14 7 0
S15 76.2 13.2 4.14 7 0
S2 76.2 13.2 4.14 7 0
S3 76.2 13.2 4.14 7 0
S32 76.2 13.2 4.14 7 0
S4 76.2 13.2 4.14 7 0
S45 76.2 13.2 4.14 7 0
S5 76.2 13.2 4.14 7 0
S6 76.2 13.2 4.14 7 0
S7 76.2 13.2 4.14 7 0
S8 76.2 13.2 4.14 7 0
S9 76.2 13.2 4.14 7 0

[JUNCTIONS]
;;Name Elevation MaxDepth InitDepth SurDepth Apended
518_Orifice 81.361 4.106 0 0 0

[OUTFALLS]
;;Name Elevation Type Stage Data Gated Route To
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 80.646 FIXED 81.28 NO

[STORAGE]
;;Name Elev. MaxDepth InitDepth Shape Curve Name/Params
;Cylindrical Structure Slab Top Circular Frame SI
518_(P-Stm) 81.061 4.406 0.219 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
519_(P-Stm) 82.197 3.512 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI

520_(P-Stm) 82.487 2.888 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
521_(P-Stm) 81.957 3.673 0 FUNCTIONAL 0 0 1.13 0
;Cylindrical Structure Slab Top Circular Frame SI
522_(P-Stm) 82.182 3.323 0 FUNCTIONAL 0 0 1.13 0
;85.1800000001676
CB200 83.18 2.32 0 TABULAR CB200 0
;85.5000000001435
CB201 83.09 2.66 0 TABULAR CB201 0
;85.36
CB202 82.76 2.89 0 TABULAR CB202 0
;85.3500000000931
CB203 82.75 2.9 0 TABULAR CB203 0
;85.3500008022731
CB204 82.75 2.75 0 TABULAR CB204 0
;85.45000080823662
CB205 82.85 2.75 0 TABULAR CB205 0
;85.48
CB206 82.77 2.73 0 TABULAR CB206 0
;85.05
CB207 83.15 2.3 0 TABULAR CB207 0
;84.9000080821652
CB208 83.3 2.04 0 TABULAR CB208 0
;84.8
CB209 83.2 1.9 0 TABULAR CB209 0
;85.25
CB210B 82.65 3 0 TABULAR CB210B 0
;85.35
CB211 83.7 1.9 0 TABULAR CB211 0
;85.4
CB212 83.2 2.42 0 TABULAR CB212 0
;85.1500000000554
CB212A 83.62 2 0 TABULAR CB212A 0
;84.75
CB213 83.15 1.75 0 TABULAR CB213 0
;84.55
CB214 82.95 1.9 0 TABULAR CB214 0

[CONDUITS]
;;Name From Node To Node Length Roughness InOffset OutOffset
InitFlow MaxFlow
C2 CB208 CB207 9.666 0.013 83.3 83.2
C4 CB212A CB212 18.475 0.013 83.62 83.25
C5 CB211 CB212 22.346 0.013 83.7 83.25
CB213 522_(P-Stm) 29.34 0.013 83.15 82.757
CB214 522_(P-Stm) 21.65 0.013 82.95 82.757
;PVC Pipes
Pipe_-(104)_-(P-Stm)_2 518_Orifice 518A_(P-Stm) 15.623 0.013 81.361 81.322
;PVC Pipes
Pipe_-(110)_-(P-Stm) 521_(P-Stm) 518_(P-Stm) 27.209 0.013 82.257 82.161
;PVC Pipes
Pipe_-(111)_-(P-Stm) 522_(P-Stm) 521_(P-Stm) 45.094 0.013 82.482 82.257
;Concrete Pipes 100-D
Pipe_-(71)_-(P-Stm) 520_(P-Stm) 519_(P-Stm) 57.146 0.013 82.787 82.557
;Concrete Pipes 100-D
Pipe_-(72)_-(P-Stm) 519_(P-Stm) 518_(P-Stm) 31.967 0.013 82.497 82.337
;ORIFICES
;;Name From Node To Node Type Offset Qcoeff Gated
CloseTime
OR1 518_(P-Stm) 518_Orifice SIDE 81.361 0.65 NO
;WEIRS
;;Name From Node To Node Type CrestHt Qcoeff Gated
EndCon EndCoeff Surcharge RoadWidth RoadSurf Coeff. Curve
W1 CB208 CB209 TRANSVERSE 85.31 1.84 NO
W2 CB210B CB211 TRANSVERSE 85.6 1.84 NO
W3 CB210B CB202 TRANSVERSE 85.45 1.84 NO
W4 CB202 CB204 TRANSVERSE 85.55 1.84 NO
W5 CB206 CB207 TRANSVERSE 85.45 1.84 NO
W6 CB201 CB200 TRANSVERSE 85.65 1.84 NO
W7 CB200 CB209 TRANSVERSE 85.42 1.84 NO
;OUTLETS
;;Name From Node To Node Offset Type QTable/Qcoeff
Qexpon Gated
CB200 CB200 520_(P-Stm) 83.18 TABULAR/HEAD IPEX_Type_A
;Critical
CB201 CB201 520_(P-Stm) 83.09 TABULAR/HEAD Vortex_ICD_100
;critical
CB202 CB202 521_(P-Stm) 82.76 TABULAR/HEAD IPEX_Type_A
CB203 CB203 521_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_70
CB204 CB204 522_(P-Stm) 82.75 TABULAR/HEAD Vortex_ICD_65
CB205 CB205 522_(P-Stm) 82.85 TABULAR/HEAD Vortex_ICD_65
CB206 CB206 522_(P-Stm) 82.77 TABULAR/HEAD Vortex_ICD_70
CB207 CB207 522_(P-Stm) 83.15 TABULAR/HEAD Vortex_ICD_100
CB209 CB209 520_(P-Stm) 83.2 TABULAR/HEAD IPEX_Type_A
CB210B CB210B 518_(P-Stm) 82.65 TABULAR/HEAD Vortex_ICD_65
CB212 CB212 521_(P-Stm) 83.2 TABULAR/HEAD Vortex_ICD_100
;XSCTIONS
;;Link Culvert Shape Geom1 Geom2 Geom3 Geom4 Barrels

```

;-----
;-----[C2] CIRCULAR 0.25 0 0 0 1
;-----[C4] CIRCULAR 0.25 0 0 0 1
;-----[C5] CIRCULAR 0.25 0 0 0 1
;-----[CB213] CIRCULAR 0.25 0 0 0 1
;-----[CB214] CIRCULAR 0.25 0 0 0 1
;-----[Pipe_-(104)-(P-Stm)] CIRCULAR 0.925 0 0 0 1
;-----[Pipe_-(110)-(P-Stm)] CIRCULAR 0.525 0 0 0 1
;-----[Pipe_-(111)-(P-Stm)] CIRCULAR 0.525 0 0 0 1
;-----[Pipe_-(71)-(P-Stm)] CIRCULAR 0.525 0 0 0 1
;-----[Pipe_-(72)-(P-Stm)] CIRCULAR 0.525 0 0 0 1
;-----[OR1] CIRCULAR 0.127 0 0 0 1
;-----[W1] RECT OPEN 0.03 1.5 0 0 0
;-----[W2] RECT OPEN 0.05 2.59 0 0 0
;-----[W3] RECT OPEN 0.2 1.34 0 0 0
;-----[W4] RECT OPEN 0.1 4.9 0 0 0
;-----[W5] RECT OPEN 0.05 4.725 0 0 0
;-----[W6] RECT OPEN 0.1 6 0 0 0
;-----[W7] RECT OPEN 0.08 10.5 0 0 0
;-----[LOSSES]
;-----[Link] Kentry Kexit Kavg Flap Gate Seepage
;-----[CURVES]
;-----[Name] Type X-Value Y-Value
;-----[CB210-OUT85.5] Rating 0 0
;-----[CB210-OUT85.5] 85.5 0.04
;-----[CB210-OUT85.5] 100 0.04
;-----[CB210-OUT-85.6] Rating 0 0
;-----[CB210-OUT-85.6] 85.6 0.08
;-----[CB210-OUT-85.6] 100 0.08
;-----[IPEX Type A ICD Rating Curve]
;-----[IPEX Type A] Rating 0 0
;-----[IPEX Type_A] 0.1 5.7
;-----[IPEX Type_A] 0.2 8.1
;-----[IPEX Type_A] 0.3 9.9
;-----[IPEX Type_A] 0.4 11.4
;-----[IPEX Type_A] 0.5 12.8
;-----[IPEX Type_A] 0.6 14
;-----[IPEX Type_A] 0.7 15.1
;-----[IPEX Type_A] 0.8 16.2
;-----[IPEX Type_A] 0.9 17.2
;-----[IPEX Type_A] 1 18.1
;-----[IPEX Type_A] 1.2 19.8
;-----[IPEX Type_A] 1.4 21.4
;-----[IPEX Type_A] 1.6 22.9
;-----[IPEX Type_A] 1.8 24.3
;-----[IPEX Type_A] 2 25.6
;-----[IPEX Type_A] 2.5 28.6
;-----[IPEX Type_A] 3 31.3
;-----[IPEX Type B ICD Rating Curve]
;-----[IPEX Type B] Rating 0 0
;-----[IPEX Type_B] 0.1 8.1
;-----[IPEX Type_B] 0.2 11.5
;-----[IPEX Type_B] 0.3 14.1
;-----[IPEX Type_B] 0.4 16.2
;-----[IPEX Type_B] 0.5 18.2
;-----[IPEX Type_B] 0.6 19.9
;-----[IPEX Type_B] 0.7 21.5
;-----[IPEX Type_B] 0.8 23
;-----[IPEX Type_B] 0.9 24.4
;-----[IPEX Type_B] 1 25.7
;-----[IPEX Type_B] 1.2 28.1
;-----[IPEX Type_B] 1.4 30.4
;-----[IPEX Type_B] 1.6 32.5
;-----[IPEX Type_B] 1.8 34.4
;-----[IPEX Type_B] 2 36.3
;-----[IPEX Type_B] 2.5 40.6
;-----[IPEX Type_B] 3 44.5
;-----[IPEX Type C ICD Rating Curve]
;-----[IPEX Type_C] Rating 0 0
;-----[IPEX Type_C] 0.1 10.6
;-----[IPEX Type_C] 0.2 15
;-----[IPEX Type_C] 0.3 18.3
;-----[IPEX Type_C] 0.4 21.2
;-----[IPEX Type_C] 0.5 23.7
;-----[IPEX Type_C] 0.6 25.9
;-----[IPEX Type_C] 0.7 28
;-----[IPEX Type_C] 0.8 29.9
;-----[IPEX Type_C] 0.9 31.7
;-----[IPEX Type_C] 1 33.5
;-----[IPEX Type_C] 1.2 36.6
;-----[IPEX Type_C] 1.4 39.6
;-----[IPEX Type_C] 1.6 42.3
;-----[IPEX Type_C] 1.8 44.9
;-----[IPEX Type_C] 2 47.3
;-----[IPEX Type_C] 2.5 55.9
;-----[IPEX Type_C] 3 57.9
;-----[IPEX Type AA ICD Rating Curve]
;-----[IPEX Type_D] Rating 0 0
;-----[IPEX Type_D] 0.1 15.4
;-----[IPEX Type_D] 0.2 21.7
;-----[IPEX Type_D] 0.3 26.6
;-----[IPEX Type_D] 0.4 30.7
;-----[IPEX Type_D] 0.5 34.3
;-----[IPEX Type_D] 0.6 37.6
;-----[IPEX Type_D] 0.7 40.6
;-----[IPEX Type_D] 0.8 43.4
;-----[IPEX Type_D] 0.9 46.1
;-----[IPEX Type_D] 1 48.5
;-----[IPEX Type_D] 1.2 53.2
;-----[IPEX Type_D] 1.4 57.4
;-----[IPEX Type_D] 1.6 61.4
;-----[IPEX Type_D] 1.8 65.1
;-----[IPEX Type_D] 2 68.7
;-----[IPEX Type_D] 2.5 76.8
;-----[IPEX Type_D] 3 84.1
;-----[IPEX Type E ICD Rating Curve]
;-----[IPEX Type_E] Rating 0 0
;-----[IPEX Type_E] 0.1 20.5
;-----[IPEX Type_E] 0.2 28.9
;-----[IPEX Type_E] 0.3 35.5
;-----[IPEX Type_E] 0.4 40.9
;-----[IPEX Type_E] 0.5 45.8
;-----[IPEX Type_E] 0.6 50.1
;-----[IPEX Type_E] 0.7 54.2
;-----[IPEX Type_E] 0.8 57.9
;-----[IPEX Type_E] 0.9 61.4
;-----[IPEX Type_E] 1 64.7
;-----[IPEX Type_E] 1.2 70.9
;-----[IPEX Type_E] 1.4 76.6
;-----[IPEX Type_E] 1.6 81.9
;-----[IPEX Type_E] 1.8 86.8
;-----[IPEX Type_E] 2 91.5
;-----[IPEX Type_E] 2.5 102.3
;-----[IPEX Type_E] 3 112.1
;-----[Tempest Rating Curve for Vortex ICD 100, No grate allowance]
;-----[Vortex ICD 100] Rating 0 0
;-----[Vortex ICD 100] 0.1 2.8
;-----[Vortex ICD 100] 0.2 4
;-----[Vortex ICD 100] 0.3 4.9
;-----[Vortex ICD 100] 0.4 5.6
;-----[Vortex ICD 100] 0.5 6.3
;-----[Vortex ICD 100] 0.6 6.9
;-----[Vortex ICD 100] 0.7 7.5
;-----[Vortex ICD 100] 0.8 8
;-----[Vortex ICD 100] 0.9 8.5
;-----[Vortex ICD 100] 1 8.9
;-----[Vortex ICD 100] 1.2 9.8
;-----[Tempest Rating Curve for Vortex ICD 105, No grate allowance]
;-----[Vortex ICD 105] Rating 0 0
;-----[Vortex ICD 105] 0.1 0.1
;-----[Vortex ICD 105] 0.2 0.2
;-----[Vortex ICD 105] 0.3 0.3
;-----[Vortex ICD 105] 0.4 0.4
;-----[Vortex ICD 105] 0.5 0.5
;-----[Vortex ICD 105] 0.6 0.6
;-----[Vortex ICD 105] 0.7 0.7
;-----[Vortex ICD 105] 0.8 0.8
;-----[Vortex ICD 105] 0.9 0.9
;-----[Vortex ICD 105] 1 0.9
;-----[Vortex ICD 105] 1.2 1.2
;-----[Vortex ICD 105] 1.4 1.4
;-----[Vortex ICD 105] 1.6 1.6
;-----[Vortex ICD 105] 1.8 1.8
;-----[Vortex ICD 105] 2 2
;-----[Vortex ICD 105] 2.5 2.5
;-----[Vortex ICD 105] 3 3
;-----[Tempest Rating Curve for Vortex ICD 40, No grate allowance]
;-----[Vortex ICD 40] Rating 0 0
;-----[Vortex ICD 40] 0.1 0.1
;-----[Vortex ICD 40] 0.2 0.2
;-----[Vortex ICD 40] 0.3 0.3
;-----[Vortex ICD 40] 0.4 0.4
;-----[Vortex ICD 40] 0.5 0.5
;-----[Vortex ICD 40] 0.6 0.6
;-----[Vortex ICD 40] 0.7 0.7
;-----[Vortex ICD 40] 0.8 0.8
;-----[Vortex ICD 40] 0.9 0.9
;-----[Vortex ICD 40] 1 1
;-----[Vortex ICD 40] 1.2 1.2
;-----[Vortex ICD 40] 1.4 1.4
;-----[Vortex ICD 40] 1.6 1.6
;-----[Vortex ICD 40] 1.8 1.8
;-----[Vortex ICD 40] 2 2
;-----[Vortex ICD 40] 2.5 2.5
;-----[Vortex ICD 40] 3 3
;-----[Tempest Rating Curve for Vortex ICD 45, No grate allowance]
;-----[Vortex ICD 45] Rating 0 0
;-----[Vortex ICD 45] 0.1 0.1
;-----[Vortex ICD 45] 0.2 0.2
;-----[Vortex ICD 45] 0.3 0.3
;-----[Vortex ICD 45] 0.4 0.4
;-----[Vortex ICD 45] 0.5 0.5
;-----[Vortex ICD 45] 0.6 0.6
;-----[Vortex ICD 45] 0.7 0.7
;-----[Vortex ICD 45] 0.8 0.8
;-----[Vortex ICD 45] 0.9 0.9
;-----[Vortex ICD 45] 1 1
;-----[Vortex ICD 45] 1.2 1.2
;-----[Vortex ICD 45] 1.4 1.4
;-----[Vortex ICD 45] 1.6 1.6
;-----[Vortex ICD 45] 1.8 1.8
;-----[Vortex ICD 45] 2 2
;-----[Vortex ICD 45] 2.5 2.5
;-----[Vortex ICD 45] 3 3
;-----[Tempest Rating Curve for Vortex ICD 50, No grate allowance]
;-----[Vortex ICD 50] Rating 0 0
;-----[Vortex ICD 50] 0.1 0.1
;-----[Vortex ICD 50] 0.2 0.2
;-----[Vortex ICD 50] 0.3 0.3
;-----[Vortex ICD 50] 0.4 0.4
;-----[Vortex ICD 50] 0.5 0.5
;-----[Vortex ICD 50] 0.6 0.6
;-----[Vortex ICD 50] 0.7 0.7
;-----[Vortex ICD 50] 0.8 0.8
;-----[Vortex ICD 50] 0.9 0.9
;-----[Vortex ICD 50] 1 1
;-----[Vortex ICD 50] 1.2 1.2
;-----[Vortex ICD 50] 1.4 1.4
;-----[Vortex ICD 50] 1.6 1.6
;-----[Vortex ICD 50] 1.8 1.8
;-----[Vortex ICD 50] 2 2
;-----[Vortex ICD 50] 2.5 2.5
;-----[Vortex ICD 50] 3 3
;-----[Tempest Rating Curve for Vortex ICD 55, No grate allowance]
;-----[Vortex ICD 55] Rating 0 0
;-----[Vortex ICD 55] 0.1 0.1
;-----[Vortex ICD 55] 0.2 0.2
;-----[Vortex ICD 55] 0.3 0.3
;-----[Vortex ICD 55] 0.4 0.4
;-----[Vortex ICD 55] 0.5 0.5
;-----[Vortex ICD 55] 0.6 0.6
;-----[Vortex ICD 55] 0.7 0.7
;-----[Vortex ICD 55] 0.8 0.8
;-----[Vortex ICD 55] 0.9 0.9
;-----[Vortex ICD 55] 1 1
;-----[Vortex ICD 55] 1.2 1.2
;-----[Vortex ICD 55] 1.4 1.4
;-----[Vortex ICD 55] 1.6 1.6
;-----[Vortex ICD 55] 1.8 1.8
;-----[Vortex ICD 55] 2 2
;-----[Vortex ICD 55] 2.5 2.5
;-----[Vortex ICD 55] 3 3
;-----[Tempest Rating Curve for Vortex ICD 60, No grate allowance]
;-----[Vortex ICD 60] Rating 0 0
;-----[Vortex ICD 60] 0.1 0.1
;-----[Vortex ICD 60] 0.2 0.2
;-----[Vortex ICD 60] 0.3 0.3
;-----[Vortex ICD 60] 0.4 0.4
;-----[Vortex ICD 60] 0.5 0.5
;-----[Vortex ICD 60] 0.6 0.6
;-----[Vortex ICD 60] 0.7 0.7
;-----[Vortex ICD 60] 0.8 0.8
;-----[Vortex ICD 60] 0.9 0.9
;-----[Vortex ICD 60] 1 1
;-----[Vortex ICD 60] 1.2 1.2
;-----[Vortex ICD 60] 1.4 1.4
;-----[Vortex ICD 60] 1.6 1.6
;-----[Vortex ICD 60] 1.8 1.8
;-----[Vortex ICD 60] 2 2
;-----[Vortex ICD 60] 2.5 2.5
;-----[Vortex ICD 60] 3 3
;-----[Tempest Rating Curve for Vortex ICD 65, No grate allowance]
;-----[Vortex ICD 65] Rating 0 0
;-----[Vortex ICD 65] 0.1 0.1
;-----[Vortex ICD 65] 0.2 0.2
;-----[Vortex ICD 65] 0.3 0.3
;-----[Vortex ICD 65] 0.4 0.4
;-----[Vortex ICD 65] 0.5 0.5
;-----[Vortex ICD 65] 0.6 0.6
;-----[Vortex ICD 65] 0.7 0.7
;-----[Vortex ICD 65] 0.8 0.8
;-----[Vortex ICD 65] 0.9 0.9
;-----[Vortex ICD 65] 1 1
;-----[Vortex ICD 65] 1.2 1.2
;-----[Vortex ICD 65] 1.4 1.4
;-----[Vortex ICD 65] 1.6 1.6
;-----[Vortex ICD 65] 1.8 1.8
;-----[Vortex ICD 65] 2 2
;-----[Vortex ICD 65] 2.5 2.5
;-----[Vortex ICD 65] 3 3
;-----[Tempest Rating Curve for Vortex ICD 70, No grate allowance]
;-----[Vortex ICD 70] Rating 0 0

```

Vortex ICD-70 0.1 1.3
Vortex ICD-70 0.2 1.9
Vortex ICD-70 0.3 2.3
Vortex ICD-70 0.4 2.7
Vortex ICD-70 0.5 3
Vortex ICD-70 0.6 3.3
Vortex ICD-70 0.7 3.6
Vortex ICD-70 0.8 3.8
Vortex ICD-70 0.9 4.1
Vortex ICD-70 1 4.3
Vortex ICD-70 1.2 4.7
Vortex ICD-70 1.4 5.1
Vortex ICD-70 1.6 5.5
Vortex ICD-70 1.8 5.8
Vortex ICD-70 2 6.1
Vortex ICD-70 2.5 6.8
Vortex ICD-70 3 7.5

;Tempest Rating Curve for Vortex ICD 75, No grate allowance
Vortex ICD 75 Rating 0 0
Vortex ICD 75 0.1 1.6
Vortex ICD 75 0.2 2.2
Vortex ICD 75 0.3 2.7
Vortex ICD 75 0.4 3.2
Vortex ICD 75 0.5 3.5
Vortex ICD 75 0.6 3.9
Vortex ICD 75 0.7 4.2
Vortex ICD 75 0.8 4.5
Vortex ICD 75 0.9 4.8
Vortex ICD 75 1 5
Vortex ICD 75 1.2 5.5
Vortex ICD 75 1.4 5.9
Vortex ICD 75 1.6 6.3
Vortex ICD 75 1.8 6.7
Vortex ICD 75 2 7.1
Vortex ICD 75 2.5 7.9
Vortex ICD 75 3 8.7

;Tempest Rating Curve for Vortex ICD 80, No grate allowance
Vortex ICD 80 Rating 0 0
Vortex ICD 80 0.1 1.8
Vortex ICD 80 0.2 2.6
Vortex ICD 80 0.3 3.1
Vortex ICD 80 0.4 3.6
Vortex ICD 80 0.5 4
Vortex ICD 80 0.6 4.4
Vortex ICD 80 0.7 4.8
Vortex ICD 80 0.8 5.1
Vortex ICD 80 0.9 5.4
Vortex ICD 80 1 5.7
Vortex ICD 80 1.2 6.3
Vortex ICD 80 1.4 6.8
Vortex ICD 80 1.6 7.2
Vortex ICD 80 1.8 7.7
Vortex ICD 80 2 8.1
Vortex ICD 80 2.5 9
Vortex ICD 80 3 9.9

;Tempest Rating Curve for Vortex ICD 85, No grate allowance
Vortex ICD 85 Rating 0 0
Vortex ICD 85 0.1 2
Vortex ICD 85 0.2 2.9
Vortex ICD 85 0.3 3.5
Vortex ICD 85 0.4 4.1
Vortex ICD 85 0.5 4.5
Vortex ICD 85 0.6 5
Vortex ICD 85 0.7 5.4
Vortex ICD 85 0.8 5.7
Vortex ICD 85 0.9 6.1
Vortex ICD 85 1 6.4
Vortex ICD 85 1.2 7
Vortex ICD 85 1.4 7.6
Vortex ICD 85 1.6 8.1
Vortex ICD 85 1.8 8.6
Vortex ICD 85 2 9.1
Vortex ICD 85 2.5 10.1
Vortex ICD 85 3 11.1

;Tempest Rating Curve for Vortex ICD 90, No grate allowance
Vortex ICD 90 Rating 0 0
Vortex ICD 90 0.1 2.2
Vortex ICD 90 0.2 3.2
Vortex ICD 90 0.3 3.9
Vortex ICD 90 0.4 4.5
Vortex ICD 90 0.5 5.1
Vortex ICD 90 0.6 5.5
Vortex ICD 90 0.7 6
Vortex ICD 90 0.8 6.4
Vortex ICD 90 0.9 6.8
Vortex ICD 90 1 7.2
Vortex ICD 90 1.2 7.9
Vortex ICD 90 1.4 8.5
Vortex ICD 90 1.6 9.1
Vortex ICD 90 1.8 9.6
Vortex ICD 90 2 10.2
Vortex ICD 90 2.5 11.4
Vortex ICD 90 3 12.5

;Tempest Rating Curve for Vortex ICD 95, No grate allowance
Vortex ICD 95 Rating 0 0
Vortex ICD 95 0.1 2.6
Vortex ICD 95 0.2 3.6
Vortex ICD 95 0.3 4.4
Vortex ICD 95 0.4 5.1
Vortex ICD 95 0.5 5.7
Vortex ICD 95 0.6 6.2
Vortex ICD 95 0.7 6.7
Vortex ICD 95 0.8 7.1
Vortex ICD 95 0.9 7.6
Vortex ICD 95 1 8
Vortex ICD 95 1.2 8.7
Vortex ICD 95 1.4 9.4
Vortex ICD 95 1.6 10.1
Vortex ICD 95 1.8 10.7
Vortex ICD 95 2 11.3
Vortex ICD 95 2.5 12.6
Vortex ICD 95 3 13.8

CB200 Storage 0 0.36
CB200 2 0.36
CB200 2.24 217.87
CB200 2.32 217.87

CB201 Storage 0 0.36
CB201 2.41 0.36
CB201 2.56 169.64
CB201 2.66 169.64

CB202 Storage 0 0.36
CB202 2.6 0.36
CB202 2.79 273.92
CB202 2.89 273.92

CB203 Storage 0 0.36
CB203 2.6 0.36
CB203 2.9 178.09

CB204 Storage 0 0.36
CB204 2.6 0.36
CB204 2.75 146.08

CB205 Storage 0 0.36
CB205 2.6 0.36
CB205 2.75 86.52

CB206 Storage 0 0.36
CB206 2.6 0.36
CB206 2.68 57.95
CB206 2.73 57.95

CB207 Storage 0 0.36
CB207 1.97 0.36
CB207 2.3 178.5

CB208 Storage 0 0.073
CB208 1.74 0.073
CB208 2.01 67.88
CB208 2.04 67.88

CB209 Storage 0 0.073
CB209 1.6 0.073
CB209 1.9 84.87

CB210B Storage 0 0.073
CB210B 2.6 0.073
CB210B 2.9 70.98
CB210B 3 70.98

CB211 Storage 0 0.073
CB211 1.65 0.073
CB211 1.9 21.99

CB212 Storage 0 0.36
CB212 2.2 0.36
CB212 2.42 55.12

CB212A Storage 0 0.073
CB212A 2 0.073

CB213 Storage 0 0.073
CB213 1.6 0.073
CB213 1.75 9.05

CB214 Storage 0 0.073
CB214 1.6 0.073
CB214 1.9 34.75

[TIMESERIES]
;Name Date Time Value
;-----
;Rainfall (mm/hr)
3CH1100 01/01/2000 00:00:00 5.339
3CH1100 01/01/2000 00:10:00 6.376
3CH1100 01/01/2000 00:20:00 7.977
3CH1100 01/01/2000 00:30:00 10.797
3CH1100 01/01/2000 00:40:00 17.136
3CH1100 01/01/2000 00:50:00 45.128
3CH1100 01/01/2000 01:00:00 178.107
3CH1100 01/01/2000 01:10:00 51.166
3CH1100 01/01/2000 01:20:00 20.163
3CH1100 01/01/2000 01:30:00 17.571
3CH1100 01/01/2000 01:40:00 13.277
3CH1100 01/01/2000 01:50:00 10.712
3CH1100 01/01/2000 02:00:00 9.008
3CH1100 01/01/2000 02:10:00 7.793
3CH1100 01/01/2000 02:20:00 6.883
3CH1100 01/01/2000 02:30:00 6.174
3CH1100 01/01/2000 02:40:00 5.607
3CH1100 01/01/2000 02:50:00 5.142
3CH1100 01/01/2000 03:00:00 0

[REPORT]
;Reporting Options
INPUT YES
CONTROLS NO
SUBCATCHMENTS ALL
NODES ALL
LINKS ALL

[TAGS]
Node 518 Orifice RY_Manhole
Node CB200 RY_Manhole
Node CB201 RY_Manhole
Node CB202 RY_Manhole
Node CB203 RY_Manhole
Node CB204 RY_Manhole
Node CB205 RY_Manhole
Node CB206 RY_Manhole
Node CB207 RY_Manhole
Node CB208 RY_Manhole
Node CB209 RY_Manhole
Node CB210B RY_Manhole
Node CB211 RY_Manhole
Node CB212 RY_Manhole
Node CB213 RY_Manhole
Node CB214 RY_Manhole
Link C2 RY_Sewer
Link C4 RY_Sewer
Link C5 RY_Sewer

[MAP]
DIMENSIONS 381219.0294 5032865.6782 381334.8286 5033009.9278
UNITS Meters

[COORDINATES]
;Node X-Coord Y-Coord
;-----
518 Orifice 381302.7 5032953.108
518 (P-Stm) 381317.029 5032855.797
518 (P-Stm) 381301.695 5032952.807
519 (P-Stm) 381278.558 5032974.866
520 (P-Stm) 381240.562 5032932.182
521 (P-Stm) 381309.324 5032926.69
522 (P-Stm) 381212.739 5032919.232
CB200 381246.119 5032941.333
CB201 381266.142 5032969.504
CB202 381305.816 5032949.229
CB203 381314.519 5032914.342
CB204 381291.187 5032921.779
CB205 381286.939 5032925.282
CB206 381270.233 5032923.017
CB207 381254.811 5032913.556
CB208 381248.314 5032902.406
CB209 381228.288 5032926.78
CB210B 381314.246 5032963.095
CB211 381319.351 5032951.771
CB212 381328.283 5032931.288
CB212A 381326.507 5032912.9
CB213 381296.875 5032912.718
CB214 381282.831 5032893.727

[VERTICES]
;Link X-Coord Y-Coord
;-----
W2 381318.013 5032956.452
W4 381305.808 5032934.267
W4 381304.151 5032928.843

[POLYGONS]
;Subcatchment X-Coord Y-Coord
;-----
S1 381237.464 5032904.825
S1 381240.329 5032905.467
S1 381240.224 5032906.884

S9 381278.399 5032931.986
S9 381281.347 5032929.355
S9 381290.74 5032939.886

;Storage Node X-Coord Y-Coord
;-----

[SYMBOLS]
;Gage X-Coord Y-Coord
;-----

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 1
 Number of subcatchments 17
 Number of nodes 23
 Number of links 29
 Number of pollutants 0
 Number of land uses 0

Rainage Summary

Name	Data Source	Data Type	Recording Interval
3CHI100	3CHI100	INTENSITY	10 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet	Runoff Quantity Continuity	Volume hectare-m	Depth mm
S1	0.02	29.61	0.06	2.2000	3CHI100	CB208	Total Precipitation	0.059	71.708
S10	0.03	55.32	99.62	2.2000	3CHI100	CB204	Evaporation Loss	0.000	0.000
S11	0.13	65.66	86.66	2.2000	3CHI100	CB202	Infiltration Loss	0.010	12.469
S12	0.01	6.44	0.25	2.2000	3CHI100	CB213	Surface Runoff	0.048	58.202
S14_1	0.01	22.78	52.75	2.2000	3CHI100	CB211	Final Storage	0.001	1.137
S14_2	0.02	51.32	38.61	2.2000	3CHI100	CB212	Continuity Error (%)	-0.141	
S15	0.04	108.74	25.77	2.2000	3CHI100	CB210B			
S2	0.07	33.61	63.05	2.2000	3CHI100	CB209			
S3	0.07	45.79	96.63	2.2000	3CHI100	CB207			
S32	0.05	29.70	14.29	2.2000	3CHI100	CB214			
S4	0.04	24.67	99.97	2.2000	3CHI100	CB206			
S45	0.02	14.32	99.96	2.2000	3CHI100	CB203			
S5	0.09	82.96	89.31	2.2000	3CHI100	CB224			
S6	0.02	40.30	0.00	2.2000	3CHI100	CB214			
S7	0.07	25.95	100.00	2.2000	3CHI100	S20_(P-			
Stm									
S8	0.09	35.06	80.12	2.2000	3CHI100	CB201			
S9	0.03	19.08	76.83	2.2000	3CHI100	CB205			

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
518_Orifice	JUNCTION	81.86	4.11	0.0	
518_(P-Stm)	OUTFALL	80.65	1.13	0.0	
518_(P-Stm)	STORAGE	81.06	4.41	0.0	
519_(P-Stm)	STORAGE	82.20	3.51	0.0	
520_(P-Stm)	STORAGE	82.49	2.89	0.0	
521_(P-Stm)	STORAGE	81.96	3.67	0.0	
522_(P-Stm)	STORAGE	82.18	3.32	0.0	
CB20	STORAGE	83.13	2.32	0.0	
CB201	STORAGE	83.09	2.66	0.0	
CB202	STORAGE	82.76	2.89	0.0	
CB203	STORAGE	82.75	2.90	0.0	
CB204	STORAGE	82.75	2.75	0.0	
CB205	STORAGE	82.85	2.75	0.0	
CB206	STORAGE	82.77	2.73	0.0	
CB207	STORAGE	83.15	2.30	0.0	
CB208	STORAGE	83.01	2.04	0.0	
CB209	STORAGE	83.20	1.90	0.0	
CB210B	STORAGE	82.65	3.00	0.0	
CB211	STORAGE	83.70	1.90	0.0	
CB212	STORAGE	83.20	2.42	0.0	
CB212A	STORAGE	83.62	2.00	0.0	
CB213	STORAGE	83.15	1.75	0.0	
CB214	STORAGE	82.95	1.90	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope
-					
C2	CB208	CB207	CONDUIT	9.7	1.0346
C4	CB212A	CB212	CONDUIT	18.5	2.0031
C5	CB211	CB212	CONDUIT	22.3	2.0142
CB213	CB213	522_(P-Stm)	CONDUIT	29.3	1.3396
CB214	CB214	522_(P-Stm)	CONDUIT	21.6	0.8915
0.0130	Pipe_-(104)_-(P-Stm)_2 518_Orifice	518A_(P-Stm)	CONDUIT	15.6	0.2496
0.0130	Pipe_-(110)_-(P-Stm) 521_(P-Stm)	518_(P-Stm)	CONDUIT	27.2	0.3528
0.0130	Pipe_-(111)_-(P-Stm) 522_(P-Stm)	521_(P-Stm)	CONDUIT	45.1	0.4990
0.0130	Pipe_-(71)_-(P-Stm) 520_(P-Stm)	519_(P-Stm)	CONDUIT	57.1	0.4025
0.0130	Pipe_-(72)_-(P-Stm) 519_(P-Stm)	518_(P-Stm)	CONDUIT	32.0	0.5005
0.0130	OR1 518_(P-Stm)	518_Orifice	ORIFICE		
W1	CB208	CB207	OUTLET		
W2	CB210B	CB211	WEIR		
W3	CB210B	CB202	WEIR		
W4	CB202	CB204	WEIR		
W5	CB204	CB07	WEIR		
W6	CB201	CB200	WEIR		
W7	CB200	CB209	WEIR		
CB200	CB200	520_(P-Stm)	OUTLET		
CB201	CB201	520_(P-Stm)	OUTLET		
CB202	CB202	521_(P-Stm)	OUTLET		
CB203	CB203	521_(P-Stm)	OUTLET		
CB204	CB204	522_(P-Stm)	OUTLET		
CB205	CB205	522_(P-Stm)	OUTLET		
CB206	CB206	522_(P-Stm)	OUTLET		
CB207	CB207	522_(P-Stm)	OUTLET		
CB209	CB209	520_(P-Stm)	OUTLET		
CB210B	CB210B	518_(P-Stm)	OUTLET		
CB212	CB212	521_(P-Stm)	OUTLET		

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C2	CIRCULAR	0.25	0.05	0.06	0.25	1	60.49
C4	CIRCULAR	0.25	0.05	0.06	0.25	1	84.17
C5	CIRCULAR	0.25	0.05	0.06	0.25	1	84.40
CB213	CIRCULAR	0.25	0.05	0.06	0.25	1	68.83
CB214	CIRCULAR	0.25	0.05	0.06	0.25	1	56.15
Pipe_-(104)_-(P-Stm)_2 CIRCULAR	CIRCULAR	0.45	0.16	0.11	0.45	1	
Pipe_-(110)_-(P-Stm) CIRCULAR	CIRCULAR	0.53	0.22	0.13	0.53	1	255.47
Pipe_-(111)_-(P-Stm) CIRCULAR	CIRCULAR	0.53	0.22	0.13	0.53	1	303.80
Pipe_-(71)_-(P-Stm) CIRCULAR	CIRCULAR	0.53	0.22	0.13	0.53	1	272.85
Pipe_-(72)_-(P-Stm) CIRCULAR	CIRCULAR	0.53	0.22	0.13	0.53	1	304.28

Post-Development 24-hour SCS 1:100-year Event

January 2025

518 Orifice	JUNCTION	0.08	0.20	81.56	0	01:37	0.20		CB211	0.000	0.5	0.0	0.0	0.000	3.0	0	01:36	
518A (P-Stm)	OUTFALL	0.63	0.63	81.28	0	00:00	0.63		CB212	5.42	0.000	1.7	0.0	0.0	0.001	8.7	0	01:35
518 (P-Stm)	STORAGE	1.27	3.78	84.84	0	01:37	3.78		CB212A	10.15	0.000	10.6	0.0	0.0	0.000	62.8	0	01:35
520 (P-Stm)	STORAGE	0.81	2.65	84.84	0	01:37	2.65		CB212A	2.36	0.000	2.36	0.0	0.0	0.000	62.8	0	01:35
521 (P-Stm)	STORAGE	0.72	2.36	84.85	0	01:37	2.36		CB212A	1.32	0.000	4.6	0.0	0.0	0.000	49.4	0	01:38
522 (P-Stm)	STORAGE	0.90	2.89	84.84	0	01:37	2.89		CB213	7.52	0.000	8.1	0.0	0.0	0.005	97.2	0	01:36
CB201	STORAGE	0.43	2.19	83.33	0	01:20	2.19		CB214	25.87	0.000	2.66	0.0	0.0	0.005	97.2	0	01:36
CB202	STORAGE	0.60	2.57	85.66	0	01:20	2.57											
CB203	STORAGE	0.54	2.66	85.41	0	01:11	2.65											
CB204	STORAGE	0.65	2.70	85.45	0	01:20	2.70											
CB205	STORAGE	0.56	2.69	85.54	0	01:20	2.69											
CB206	STORAGE	0.63	2.17	85.47	0	01:10	2.17											
CB207	STORAGE	0.58	2.18	85.53	0	01:20	2.18											
CB208	STORAGE	0.52	2.03	85.33	0	01:21	2.03											
CB209	STORAGE	0.37	1.79	84.99	0	01:25	1.79											
CB210B	STORAGE	0.64	2.85	85.50	0	01:20	2.85											
CB211	STORAGE	0.19	1.18	84.88	0	01:36	1.18											
CB212	STORAGE	0.32	1.67	84.87	0	01:35	1.67											
CB212A	STORAGE	0.21	1.26	84.88	0	01:35	1.26											
CB213	STORAGE	0.32	1.70	84.85	0	01:38	1.70											
CB214	STORAGE	0.37	1.90	84.85	0	01:36	1.90											

Outfall Loading Summary

Outfall Node	Flow Freq Pcnt	Avg Flow LPS	Max Flow LPS	Total Volume 10^6 ltr
518A (P-Stm)	67.75	32.60	66.10	0.477
System	67.75	32.60	66.10	0.477

Node Inflow Summary

Flow Balance Error Node Percent	Link Type	Maximum Lateral		Lateral Total		Inflow Inflow		
		Lateral	Total	Time of Max	Inflow		Inflow	Inflow
		Inflow	Inflow	Occurrence	Volume		Volume	Volume
518 Orifice	JUNCTION	0.00	66.10	0	01:37	0	0.477	-
0.018	OUTFALL	0.00	66.10	0	01:37	0	0.477	-
0.000	STORAGE	0.00	84.12	0	01:07	0	0.477	-
0.111	STORAGE	0.00	92.47	0	01:03	0	0.206	-
0.377	STORAGE	33.94	96.71	0	01:05	0.0482	0.207	-
0.489	STORAGE	0.00	78.54	0	01:05	0	0.256	-
0.083	STORAGE	0.00	60.78	0	01:06	0	0.15	-
0.029	STORAGE	42.36	43.45	0	01:10	0.0573	0.0621	-
0.008	STORAGE	44.54	44.54	0	01:10	0.0582	0.0582	-
0.013	STORAGE	61.68	61.68	0	01:10	0.0821	0.0834	-
0.024	STORAGE	10.98	10.98	0	01:10	0.0156	0.0156	-
0.003	STORAGE	15.18	15.18	0	01:10	0.0215	0.0215	-
0.014	STORAGE	13.15	13.15	0	01:10	0.0167	0.0167	-
0.009	STORAGE	22.26	22.26	0	01:10	0.0316	0.0316	-
0.029	STORAGE	34.97	51.81	0	01:10	0.0489	0.068	-
0.003	STORAGE	7.47	26.09	0	01:03	0.00525	0.0156	-
0.021	STORAGE	33.11	33.11	0	01:10	0.0399	0.0434	-
0.001	STORAGE	16.73	37.44	0	01:09	0.0136	0.0176	-
0.083	STORAGE	5.46	7.13	0	01:08	0.00538	0.00544	-
0.053	STORAGE	8.14	13.45	0	01:06	0.00691	0.0143	-
0.123	STORAGE	0.00	5.30	0	01:09	0	0.00175	-
0.096	STORAGE	3.78	20.64	0	01:06	0.00397	0.00517	-
0.056	STORAGE	27.81	27.81	0	01:10	0.0234	0.0235	-

Flow Classification Summary

Conduit	Adjusted Length	Fraction of Time in Flow Class	Actual Length	Dry Up Down Sub Sup Up Down Norm Crit Crit Crit Ltd Ctrl	Flow Class
C2	1.00	0.05	0.01	0.00 0.39 0.00 0.00 0.00 0.56 0.07 0.00	1.00
C4	1.00	0.17	0.01	0.00 0.27 0.00 0.00 0.00 0.55 0.03 0.00	1.00
C5	1.00	0.15	0.01	0.00 0.28 0.00 0.00 0.00 0.56 0.05 0.00	1.00
CB213	1.00	0.00	0.00	0.00 0.00 0.00 0.00 0.00 0.62 0.00 0.00	1.00
CB214	1.00	0.05	0.00	0.00 0.32 0.00 0.00 0.00 0.93 0.03 0.00	1.00
Pipe_-(104)-(P-Stm)_2	1.00	0.07	0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.00
Pipe_-(110)-(P-Stm)	1.00	0.06	0.00	0.00 0.00 0.00 0.00 0.00 0.56 0.00 0.00	1.00
Pipe_-(111)-(P-Stm)	1.00	0.06	0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.00
Pipe_-(71)-(T-P-Stm)	1.00	0.06	0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.00
Pipe_-(72)-(P-Stm)	1.00	0.07	0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.00

Conduit Surcharge Summary

Conduit	Hours Both Ends	Hours Upstream	Hours Dnstream	Hours Above Normal Flow	Hours Capacity Limited
C2	1.76	1.76	1.80	0.01	0.01
C4	1.29	1.29	1.54	0.01	0.01
C5	1.23	1.23	1.55	0.01	0.01
CB213	1.50	1.50	1.44	0.01	0.01
CB214	1.63	1.63	1.74	0.01	0.01
Pipe_-(110)-(P-Stm)	1.90	1.90	1.98	0.01	0.01
Pipe_-(111)-(P-Stm)	1.74	1.74	1.90	0.01	0.01
Pipe_-(71)-(T-P-Stm)	1.56	1.56	1.69	0.01	0.01
Pipe_-(72)-(P-Stm)	1.73	1.73	1.85	0.01	0.01

Analysis begun on: Tue Jan 28 12:44:03 2025

Analysis ended on: Tue Jan 28 12:44:04 2025

Total elapsed time: 00:00:01

Maximum Outflow Storage Unit LPS	Average				Maximum Max Occurrence	
	Volume Pcnt	Pcnt	Loss	Loss		
518 (P-Stm)	0.001	28.9	0.0	0.0	0.004	85.8
66.10 ¹	0.001	23.0	0.0	0.0	0.003	75.4
518_(P-Stm)	0.001	24.9	0.0	0.0	0.003	81.7
520_(P-Stm)	0.001	24.5	0.0	0.0	0.003	78.6
521_(P-Stm)	0.001	24.5	0.0	0.0	0.003	80.1
522_(P-Stm)	0.001	24.5	0.0	0.0	0.003	25.0
43 ¹ CB200	0.001	2.0	0.0	0.0	0.011	49.8
26 ² CB201	0.002	6.1	0.0	0.0	0.015	49.8
21 ^{0.5} CB202	0.001	2.7	0.0	0.0	0.015	28.0
43 ¹⁸ CB203	0.000	0.8	0.0	0.0	0.002	6.7
5 ^{.70} CB204	0.001	6.4	0.0	0.0	0.006	46.3
5 ^{.52} CB205	0.000	4.7	0.0	0.0	0.003	42.4
5 ^{.18} CB206	0.001	8.4	0.0	0.0	0.004	67.6
22 ^{.01} CB207	0.002	6.2	0.0	0.0	0.012	40.2
37 ^{.16} CB208	0.002	15.2	0.0	0.0	0.010	91.1
9 ^{.56} CB209	0.000	3.6	0.0	0.0	0.005	39.9
23 ^{.04} CB210B	0.001	4.8	0.0	0.0	0.008	42.5
7 ^{.22}						

Stormceptor® EF Sizing Report

Imbrium® Systems

ESTIMATED NET ANNUAL SEDIMENT (TSS) LOAD REDUCTION

08/28/2024

Province:	Ontario
City:	Ottawa
Nearest Rainfall Station:	OTTAWA CDA RCS
Climate Station Id:	6105978
Years of Rainfall Data:	20
Site Name:	
Drainage Area (ha):	0.82
% Imperviousness:	73.64

Runoff Coefficient 'c': 0.74

Project Name:	Navan Gas Bar
Project Number:	29899-002
Designer Name:	Bobby Pettigrew
Designer Company:	J.L. Richards & Associates Ltd
Designer Email:	bpettigrew@jlrichards.ca
Designer Phone:	343-804-5381
EOR Name:	
EOR Company:	
EOR Email:	
EOR Phone:	

Particle Size Distribution:	Fine
Target TSS Removal (%):	80.0

Required Water Quality Runoff Volume Capture (%):	90.00
Estimated Water Quality Flow Rate (L/s):	19.63
Oil / Fuel Spill Risk Site?	Yes
Upstream Flow Control?	Yes
Upstream Orifice Control Flow Rate to Stormceptor (L/s):	66.00
Peak Conveyance (maximum) Flow Rate (L/s):	66.00
Influent TSS Concentration (mg/L):	200
Estimated Average Annual Sediment Load (kg/yr):	657
Estimated Average Annual Sediment Volume (L/yr):	534

**Net Annual Sediment
(TSS) Load Reduction
Sizing Summary**

Stormceptor Model	TSS Removal Provided (%)
EFO4	80
EFO6	90
EFO8	95
EFO10	97
EFO12	99

Recommended Stormceptor EFO Model: EFO4

Estimated Net Annual Sediment (TSS) Load Reduction (%): 80

Water Quality Runoff Volume Capture (%): > 90

Stormceptor® EF Sizing Report**THIRD-PARTY TESTING AND VERIFICATION**

► **Stormceptor® EF and Stormceptor® EFO** are the latest evolutions in the Stormceptor® oil-grit separator (OGS) technology series, and are designed to remove a wide variety of pollutants from stormwater and snowmelt runoff. These technologies have been third-party tested in accordance with the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators and performance has been third-party verified in accordance with the ISO 14034 Environmental Technology Verification (ETV) protocol.

PERFORMANCE

► **Stormceptor® EF and EFO** remove stormwater pollutants through gravity separation and floatation, and feature a patent-pending design that generates positive removal of total suspended solids (TSS) throughout each storm event, including high-intensity storms. Captured pollutants include sediment, free oils, and sediment-bound pollutants such as nutrients, heavy metals, and petroleum hydrocarbons. Stormceptor is sized to remove a high level of TSS from the frequent rainfall events that contribute the vast majority of annual runoff volume and pollutant load. The technology incorporates an internal bypass to convey excessive stormwater flows from high-intensity storms through the device without resuspension and washout (scour) of previously captured pollutants. Proper routine maintenance ensures high pollutant removal performance and protection of downstream waterways.

PARTICLE SIZE DISTRIBUTION (PSD)

► The **Canadian ETV PSD** shown in the table below was used, or in part, for this sizing. This is the identical PSD that is referenced in the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators for both sediment removal testing and scour testing. The Canadian ETV PSD contains a wide range of particle sizes in the sand and silt fractions, and is considered reasonably representative of the particle size fractions found in typical urban stormwater runoff.

Particle Size (μm)	Percent Less Than	Particle Size Fraction (μm)	Percent
1000	100	500-1000	5
500	95	250-500	5
250	90	150-250	15
150	75	100-150	15
100	60	75-100	10
75	50	50-75	5
50	45	20-50	10
20	35	8-20	15
8	20	5-8	10
5	10	2-5	5
2	5	<2	5

Stormceptor® EF Sizing Report


Upstream Flow Controlled Results

Rainfall Intensity (mm / hr)	Percent Rainfall Volume (%)	Cumulative Rainfall Volume (%)	Flow Rate (L/s)	Flow Rate (L/min)	Surface Loading Rate (L/min/m²)	Removal Efficiency (%)	Incremental Removal (%)	Cumulative Removal (%)
0.50	8.6	8.6	0.85	51.0	42.0	100	8.6	8.6
1.00	20.3	29.0	1.69	101.0	85.0	98	20.0	28.6
2.00	16.2	45.2	3.38	203.0	169.0	87	14.1	42.7
3.00	12.0	57.2	5.07	304.0	254.0	81	9.7	52.4
4.00	8.4	65.6	6.76	406.0	338.0	77	6.5	58.9
5.00	5.9	71.6	8.46	507.0	423.0	73	4.3	63.3
6.00	4.6	76.2	10.15	609.0	507.0	69	3.2	66.5
7.00	3.1	79.3	11.84	710.0	592.0	65	2.0	68.5
8.00	2.7	82.0	13.53	812.0	676.0	64	1.8	70.2
9.00	3.3	85.3	15.22	913.0	761.0	63	2.1	72.3
10.00	2.3	87.6	16.91	1015.0	846.0	63	1.4	73.8
11.00	1.6	89.2	18.60	1116.0	930.0	62	1.0	74.8
12.00	1.3	90.5	20.29	1218.0	1015.0	61	0.8	75.6
13.00	1.7	92.2	21.98	1319.0	1099.0	59	1.0	76.6
14.00	1.2	93.5	23.68	1421.0	1184.0	57	0.7	77.3
15.00	1.2	94.6	25.37	1522.0	1268.0	56	0.6	77.9
16.00	0.7	95.3	27.06	1623.0	1353.0	53	0.4	78.3
17.00	0.7	96.1	28.75	1725.0	1437.0	51	0.4	78.7
18.00	0.4	96.5	30.44	1826.0	1522.0	48	0.2	78.9
19.00	0.4	96.9	32.13	1928.0	1607.0	46	0.2	79.1
20.00	0.2	97.1	33.82	2029.0	1691.0	43	0.1	79.2
21.00	0.5	97.5	35.51	2131.0	1776.0	41	0.2	79.4
22.00	0.2	97.8	37.20	2232.0	1860.0	39	0.1	79.4
23.00	1.0	98.8	38.90	2334.0	1945.0	38	0.4	79.8
24.00	0.3	99.1	40.59	2435.0	2029.0	36	0.1	79.9
25.00	0.9	100.0	42.28	2537.0	2114.0	35	0.3	80.3
30.00	0.9	100.9	50.73	3044.0	2537.0	29	0.3	80.5
35.00	-0.9	100.0	59.19	3551.0	2959.0	25	N/A	80.3
40.00	0.0	100.0	66.00	3960.0	3300.0	22	0.0	80.3
45.00	0.0	100.0	66.00	3960.0	3300.0	22	0.0	80.3
Estimated Net Annual Sediment (TSS) Load Reduction =								80 %


Climate Station ID: 6105978 Years of Rainfall Data: 20

Stormceptor® EF Sizing Report

RAINFALL DATA FROM OTTAWA CDA RCS RAINFALL STATION



INCREMENTAL AND CUMULATIVE TSS REMOVAL FOR THE RECOMMENDED STORMCEPTOR® MODEL



Stormceptor® EF Sizing Report

Maximum Pipe Diameter / Peak Conveyance

Stormceptor EF / EFO	Model Diameter		Min Angle Inlet / Outlet Pipes	Max Inlet Pipe Diameter		Max Outlet Pipe Diameter		Peak Conveyance Flow Rate	
	(m)	(ft)		(mm)	(in)	(mm)	(in)	(L/s)	(cfs)
EF4 / EFO4	1.2	4	90	609	24	609	24	425	15
EF6 / EFO6	1.8	6	90	914	36	914	36	990	35
EF8 / EFO8	2.4	8	90	1219	48	1219	48	1700	60
EF10 / EFO10	3.0	10	90	1828	72	1828	72	2830	100
EF12 / EFO12	3.6	12	90	1828	72	1828	72	2830	100

SCOUR PREVENTION AND ONLINE CONFIGURATION


► Stormceptor® EF and EFO feature an internal bypass and superior scour prevention technology that have been demonstrated in third-party testing according to the scour testing provisions of the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators, and the exceptional scour test performance has been third-party verified in accordance with the ISO 14034 ETV protocol. As a result, Stormceptor EF and EFO are approved for online installation, eliminating the need for costly additional bypass structures, piping, and installation expense.

DESIGN FLEXIBILITY


► Stormceptor® EF and EFO offers design flexibility in one simplified platform, accepting stormwater flow from a single inlet pipe or multiple inlet pipes, and/or surface runoff through an inlet grate. The device can also serve as a junction structure, accommodate a 90-degree inlet-to-outlet bend angle, and can be modified to ensure performance in submerged conditions.

OIL CAPTURE AND RETENTION

► While Stormceptor® EF will capture and retain oil from dry weather spills and low intensity runoff, Stormceptor® EFO has demonstrated superior oil capture and greater than 99% oil retention in third-party testing according to the light liquid re-entrainment testing provisions of the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators. Stormceptor EFO is recommended for sites where oil capture and retention is a requirement.



Stormceptor® EF Sizing Report



INLET-TO-OUTLET DROP

Elevation differential between inlet and outlet pipe inverts is dictated by the angle at which the inlet pipe(s) enters the unit.

0° - 45° : The inlet pipe is 1-inch (25mm) higher than the outlet pipe.

45° - 90° : The inlet pipe is 2-inches (50mm) higher than the outlet pipe.

HEAD LOSS

The head loss through Stormceptor EF is similar to that of a 60-degree bend structure. The applicable K value for calculating minor losses through the unit is 1.1. For submerged conditions the applicable K value is 3.0.

Pollutant Capacity

Stormceptor EF / EFO	Model Diameter		Depth (Outlet Pipe Invert to Sump Floor)		Oil Volume		Recommended Sediment Maintenance Depth *		Maximum Sediment Volume *		Maximum Sediment Mass **	
	(m)	(ft)	(m)	(ft)	(L)	(Gal)	(mm)	(in)	(L)	(ft³)	(kg)	(lb)
EF4 / EFO4	1.2	4	1.52	5.0	265	70	203	8	1190	42	1904	5250
EF6 / EFO6	1.8	6	1.93	6.3	610	160	305	12	3470	123	5552	15375
EF8 / EFO8	2.4	8	2.59	8.5	1070	280	610	24	8780	310	14048	38750
EF10 / EFO10	3.0	10	3.25	10.7	1670	440	610	24	17790	628	28464	78500
EF12 / EFO12	3.6	12	3.89	12.8	2475	655	610	24	31220	1103	49952	137875

*Increased sump depth may be added to increase sediment storage capacity

** Average density of wet packed sediment in sump = 1.6 kg/L (100 lb/ft³)

Feature	Benefit	Feature Appeals To
Patent-pending enhanced flow treatment and scour prevention technology	Superior, verified third-party performance	Regulator, Specifying & Design Engineer
Third-party verified light liquid capture and retention for EFO version	Proven performance for fuel/oil hotspot locations	Regulator, Specifying & Design Engineer, Site Owner
Functions as bend, junction or inlet structure	Design flexibility	Specifying & Design Engineer
Minimal drop between inlet and outlet	Site installation ease	Contractor
Large diameter outlet riser for inspection and maintenance	Easy maintenance access from grade	Maintenance Contractor & Site Owner

STANDARD STORMCEPTOR EF/EFO DRAWINGS

For standard details, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

STANDARD STORMCEPTOR EF/EFO SPECIFICATION

For specifications, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

Stormceptor® EF Sizing Report**STANDARD PERFORMANCE SPECIFICATION FOR
“OIL GRIT SEPARATOR” (OGS) STORMWATER QUALITY TREATMENT DEVICE****PART 1 – GENERAL****1.1 WORK INCLUDED**

This section specifies requirements for selecting, sizing, and designing an underground Oil Grit Separator (OGS) device for stormwater quality treatment, with third-party testing results and a Statement of Verification in accordance with ISO 14034 Environmental Management – Environmental Technology Verification (ETV).

1.2 REFERENCE STANDARDS & PROCEDURES

ISO 14034:2016 Environmental management – Environmental technology verification (ETV)

Canadian Environmental Technology Verification (ETV) Program’s **Procedure for Laboratory Testing of Oil-Grit Separators**

1.3 SUBMITTALS

1.3.1 All submittals, including sizing reports & shop drawings, shall be submitted upon request with each order to the contractor then forwarded to the Engineer of Record for review and acceptance. Shop drawings shall detail all OGS components, elevations, and sequence of construction.

1.3.2 Alternative devices shall have features identical to or greater than the specified device, including: treatment chamber diameter, treatment chamber wet volume, sediment storage volume, and oil storage volume.

1.3.3 Unless directed otherwise by the Engineer of Record, OGS stormwater quality treatment product substitutions or alternatives submitted within ten days prior to project bid shall not be accepted. All alternatives or substitutions submitted shall be signed and sealed by a local registered Professional Engineer, based on the exact same criteria detailed in Section 3, in entirety, subject to review and approval by the Engineer of Record.

PART 2 – PRODUCTS**2.1 OGS POLLUTANT STORAGE**

The OGS device shall include a sump for sediment storage, and a protected volume for the capture and storage of petroleum hydrocarbons and buoyant gross pollutants. The minimum sediment & petroleum hydrocarbon storage capacity shall be as follows:

2.1.1	4 ft (1219 mm) Diameter OGS Units:	1.19 m ³ sediment / 265 L oil
	6 ft (1829 mm) Diameter OGS Units:	3.48 m ³ sediment / 609 L oil
	8 ft (2438 mm) Diameter OGS Units:	8.78 m ³ sediment / 1,071 L oil
	10 ft (3048 mm) Diameter OGS Units:	17.78 m ³ sediment / 1,673 L oil
	12 ft (3657 mm) Diameter OGS Units:	31.23 m ³ sediment / 2,476 L oil

PART 3 – PERFORMANCE & DESIGN**3.1 GENERAL**

The OGS stormwater quality treatment device shall be verified in accordance with ISO 14034:2016 Environmental management – Environmental technology verification (ETV). The OGS stormwater quality treatment device shall



Stormceptor® EF Sizing Report

remove oil, sediment and gross pollutants from stormwater runoff during frequent wet weather events, and retain these pollutants during less frequent high flow wet weather events below the insert within the OGS for later removal during maintenance. The Manufacturer shall have at least ten (10) years of local experience, history and success in engineering design, manufacturing and production and supply of OGS stormwater quality treatment device systems, acceptable to the Engineer of Record.

3.2 SIZING METHODOLOGY

The OGS device shall be engineered, designed and sized to provide stormwater quality treatment based on treating a minimum of 90 percent of the average annual runoff volume and a minimum removal of an annual average 60% of the sediment (TSS) load based on the Particle Size Distribution (PSD) specified in the sizing report for the specified device. Sizing of the OGS shall be determined by use of a minimum ten (10) years of local historical rainfall data provided by Environment Canada. Sizing shall also be determined by use of the sediment removal performance data derived from the ISO 14034 ETV third-party verified laboratory testing data from testing conducted in accordance with the Canadian ETV protocol Procedure for Laboratory Testing of Oil-Grit Separators, as follows:

3.2.1 Sediment removal efficiency for a given surface loading rate and its associated flow rate shall be based on sediment removal efficiency demonstrated at the seven (7) tested surface loading rates specified in the protocol, ranging 40 L/min/m² to 1400 L/min/m², and as stated in the ISO 14034 ETV Verification Statement for the OGS device.

3.2.2 Sediment removal efficiency for surface loading rates between 40 L/min/m² and 1400 L/min/m² shall be based on linear interpolation of data between consecutive tested surface loading rates.

3.2.3 Sediment removal efficiency for surface loading rates less than the lowest tested surface loading rate of 40 L/min/m² shall be assumed to be identical to the sediment removal efficiency at 40 L/min/m². No extrapolation shall be allowed that results in a sediment removal efficiency that is greater than that demonstrated at 40 L/min/m².

3.2.4 Sediment removal efficiency for surface loading rates greater than the highest tested surface loading rate of 1400 L/min/m² shall assume zero sediment removal for the portion of flow that exceeds 1400 L/min/m², and shall be calculated using a simple proportioning formula, with 1400 L/min/m² in the numerator and the higher surface loading rate in the denominator, and multiplying the resulting fraction times the sediment removal efficiency at 1400 L/min/m².

The OGS device shall also have sufficient annual sediment storage capacity as specified and calculated in Section 2.1.

3.3 CANADIAN ETV or ISO 14034 ETV VERIFICATION OF SCOUR TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of third-party scour testing conducted in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**.

3.3.1 To be acceptable for on-line installation, the OGS device must demonstrate an average scour test effluent concentration less than 10 mg/L at each surface loading rate tested, up to and including 2600 L/min/m².

3.4 LIGHT LIQUID RE-ENTRAINMENT SIMULATION TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of completed third-party Light Liquid Re-entrainment Simulation Testing in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**, with results reported within the Canadian ETV or ISO 14034 ETV verification. This re-entrainment testing is conducted with the device pre-loaded with low density polyethylene (LDPE) plastic beads as a surrogate for light liquids such as oil and fuel. Testing is conducted on the same OGS unit tested for sediment removal to



Stormceptor® EF Sizing Report

assess whether light liquids captured after a spill are effectively retained at high flow rates.

3.4.1 For an OGS device to be an acceptable stormwater treatment device on a site where vehicular traffic occurs and the potential for an oil or fuel spill exists, the OGS device must have reported verified performance results of greater than 99% cumulative retention of LDPE plastic beads for the five specified surface loading rates (ranging 200 L/min/m² to 2600 L/min/m²) in accordance with the Light Liquid Re-entrainment Simulation Testing within the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**. However, an OGS device shall not be allowed if the Light Liquid Re-entrainment Simulation Testing was performed with screening components within the OGS device that are effective at retaining the LDPE plastic beads, but would not be expected to retain light liquids such as oil and fuel.





Platinum
member

www.jlrichards.ca

Ottawa

343 Preston Street
Tower II, Suite 1000
Ottawa ON Canada
K1S 1N4
Tel: 613 728-3571
ottawa@jlrichards.ca

Kingston

203-863 Princess Street
Kingston ON Canada
K7L 5N4
Tel: 613 544-1424
kingston@jlrichards.ca

Sudbury

314 Countryside Drive
Sudbury ON Canada
P3E 6G2
Tel: 705 522-8174
sudbury@jlrichards.ca

Timmins

834 Mountjoy Street S
Timmins ON Canada
P4N 7C5
Tel: 705 360-1899
timmins@jlrichards.ca

North Bay

501-555 Oak Street E
North Bay ON Canada
P1B 8E3
Tel: 705 495-7597
northbay@jlrichards.ca

Hawkesbury

326 Bertha Street
Hawkesbury ON Canada
K6A 2A8
Tel: 613 632-0287
hawkesbury@jlrichards.ca

Guelph

107-450 Speedvale Ave. West
Guelph ON Canada
N1H 7Y6
Tel: 519 763-0713
guelph@jlrichards.ca

