

February 18, 2025



**PM15625-LET.01-Rev.01**

1818 Farm & Cidery  
1811 Richardson Side Road  
Ottawa (Carp), Ontario  
K0A 1L0

Attention: Ken Hoppner

Subject: **Hydrogeological Assessment and Terrain Analysis  
Zoning Bylaw Amendment and Site Plan Control  
Application  
1811 Richardson Side Road  
Ottawa (Carp), Ontario**

**Consulting Engineers**

9 Auriga Drive  
Ottawa, Ontario  
K2E 7T9  
Tel: (613) 226-7381

Geotechnical Engineering  
Environmental Engineering  
Hydrogeology  
Materials Testing  
Building Science  
Rural Development Design  
Retaining Wall Design  
Noise and Vibration Studies

[patersongroup.ca](http://patersongroup.ca)

## INTRODUCTION

Further to your request, Paterson has conducted a Hydrogeological Assessment and Terrain Analysis in support of a Re-Zoning Application and Site Plan Control Application for the proposed alteration to allow for a place of assembly as part of an on-farm diversified use (OFDU) and/or restaurant to be located at 1811 Richardson Side Road in Ottawa (Carp), Ontario.

The purpose of this work has been to determine the suitability of the water supply aquifer underlying the site as well as determine the capacity of the site to attenuate the sewage system impacts to support the Re-Zoning Application and Site Plan Control Application.

The Subject Site consists of a 11.68 ha lot and is currently occupied by a residential dwelling, located centrally near Bradley Side Road, a centrally located commercial building (Cidery), a commercial building to the south, and an agricultural area located on the northeastern portion of the property with an associated temporary tent-based greenhouse. The south-western portion of the site generally consists of treed areas. The ground surface generally slopes towards the east. There is a sharp slope from the central property to the northeastern agricultural area. The general direction of water flow is towards the Ottawa River to the north.

The Subject Site is bordered on all sides by agricultural lands, with a church and dwelling located to the south of the site. The site has frontage onto Bradley Side Road to the northwest, Huntmar Drive to the northeast and Richardson Side Road to the southeast.





The subject site itself and the surrounding commercial areas are zoned AG3 for Agricultural General Subzone 3 (GeoOttawa).

### **Hydrogeological Pre-consultation**

A Hydrogeological pre-consultation was completed with a City of Ottawa Hydrogeologist on June 23, 2024. The City Hydrogeologist noted that water quantity and quality may be an issue. Evidence was provided from the water well hydrofracking process to increase the quantity and was to be confirmed with the pumping test. An 8-hour pumping test with the standard Subdivision Package suite of parameters, trace metals and Volatile Organic Compounds (VOC's) required by the City of Ottawa Hydrogeological and Terrain Analysis Guidelines (HTAG) was determined to be acceptable.

### **Description of Subject Site**

The subject site is an approximately 11.68 ha lot and is currently occupied by a two-storey residential dwelling, a commercial building to the south with associated parking and storage, a commercial building (Cidery), and agricultural lands to the east, with an associated temporary tent-based greenhouse. The Re-zoning Application is for a zoning by-law amendment to increase the number of guests allowed at the OFDU and/or restaurant. Please refer to Figure-1 Key Plan, attached, for the proposed site location.

The residential dwelling is currently serviced by an onsite sewage system and an existing private drilled well. A newly drilled well was installed in 2022 to service the Cidery and a new sewage system will be required to service the proposed change of use . At this time no site plan has been completed.

The newly drilled well, hereafter referred to as Test Well 1 (TW1), is the well which is currently servicing the Cidery and will continue to service the building following the completion of construction. The property owner will need to ensure that protective measures are taken to protect the wellhead, such as the use of a barrier, during construction.

The suitability of the aquifer to supply the subject site was assessed using the methodology provided in City of Ottawa Hydrogeological and Terrain Analysis Guidelines (HTAG).

Based on available Ontario Geological Survey (OGS) mapping (GRS005), the subject site is not within an area of potential karst.

### **MISSISSIPPI-RIDEAU SOURCE PROTECTION PLAN**

The Mississippi-Rideau Source Protection Plan (MRSPP) provides guidance as to which policies apply to a given property, municipality or specific activity and if there are specific designations that apply to the area. The subject site and surrounding areas have not been



designated as a Significant Groundwater Recharge Area (SGRA), Highly Vulnerable Aquifer (HVA), or Intake Protection Zones (IPZ) Zone within the MRSPP.

There are no related requirements for this site relative to the MRSPP.

### **Karst Mapping**

As discussed in the City pre-consultation meeting, karst was not considered a concern at the site. Available Karst mapping (OGS GRS005) was reviewed as part of this assessment. The available mapping does not indicate the presence of any inferred or potential karstic features. Furthermore, no indication of karstic features was observed during the site visits completed by Paterson personnel.

## **FIELDWORK PROGRAM**

### **Well Inspection**

A visual inspection of TW1 was performed by Paterson personnel which confirmed that the well casing and cap are in good condition. The final grading around the well will be sufficiently graded to direct surface water away from the wellhead (as required by O.Reg 903) at the time of the new sewage system installation. The stick-up was measured to be 0.49 m above ground surface. Based on a visual inspection by Paterson personnel, the well was deemed to be in good condition.

### **Well Testing**

As a means to demonstrate the adequacy of the aquifer underlying the subject lands, with respect to water quality and quantity, TW1 was tested. TW1 has a Water Well Record (WWR) Well ID of A342224 with a 152.4 mm diameter steel casing that extends to 20.1 m below ground surface (bgs) and a 0.49 m stick-up. The well itself extends to a depth of 121.9 m bgs. Based on available geological mapping, the drift thickness at TW1 varies from 15 to 25 m.

As a means to evaluate the water supply aquifer intercepted by the well, the well was subjected to an 8-hour constant rate pumping test. The pumping test was conducted on June 25, 2024 under the full-time supervision of Paterson personnel. Prior to the pumping test the well was disinfected as per the MECP Disinfection Instruction Sheet, and a data-logger was installed to monitor the background groundwater levels.

The existing submersible pump was used for the 8-hour pumping test. A licensed water well technician (Air Rock) completed the necessary plumbing related activities. The discharge line was placed at a sufficient distance to ensure that the discharge water was being directed away from the well as well as any septic systems in the area. Upon completion of the test, the system was returned to its normal configuration.



The pumping test was carried out at a pumping rate of 30 L/min for a duration of 8 hours. During the pumping test, the pumping rate was periodically measured using the timed volume correlation method. The pumping rate was maintained within 5% of the selected pumping rate. The static water level was recorded manually and an electric datalogger (VanEssen TD-Diver) was installed in the test well prior to the start of the pumping test.

The selected rate of 30 L/min provides approximately 1.4 times (14,400 L) the maximum total daily design sanitary sewage flow (TDDSSF) of 10,000 L/day for the subject site during the 8-hour pumping test in support of the Re-zoning Application. The TDDSSF for the proposed development is 7,125 L/day (design by others) under the Site Plan Application. This provides greater than 2 times the TDDSSF proposed for the Site Plan Application. The total daily design sanitary sewage flows (TDDSSF) are proposed to remain below the limit of 10,000 L/day as set out by the Ontario Building Code (OBC) and does not require a large-scale subsurface sewage system.

The data logger recorded water levels at 30 second intervals. In addition, manual water level readings were taken at periodic intervals during the test.

Recovery data was collected from the well following the completion of the pumping. The well was noted to have achieved 95% recovery approximately 13 hours after the completion of pumping.

Groundwater samples were collected at 4 hours and 8 hours after the start of pumping. Prior to collection of the groundwater samples, the free chlorine residual was verified as non-detectable. The water samples were submitted for comprehensive testing of bacteriological, chemical, and physical water quality parameters consistent with the standard "Subdivision Supply" suite of parameters plus trace metals. VOCs were sampled 4 hours and 8 hours after the start of pumping.

All samples were collected unfiltered and unchlorinated and were placed directly into clean bottles supplied by the analytical laboratory. Samples were placed immediately into a cooler with ice and were transported directly to Environmental Testing Canada Inc.(Eurofins) laboratory in Ottawa. All samples were received by the laboratory within 24 hours of collection.

A series of field tests of the pumped water were carried out at the well head during the 8-hour pumping test. The parameters tested at the well head included: pH, total dissolved solids, conductivity, turbidity, apparent colour, hydrogen sulfide (olfactory only), and temperature. Calibration / confirmation of calibration of all field-testing equipment was performed in Paterson's laboratory the day prior to the pumping test. Values are then confirmed again onsite prior to the start of the pumping test.

Due to elevated measurements for turbidity, colour, and aluminum levels encountered during the pumping test, Paterson personnel returned to the site on July 19, 2024 to collect an additional untreated sample under normal operating conditions of TW1.



## Aquifer Analysis

### Water Quantity

Pumping test data was analyzed using AQTESOLV Pro Version 4 aquifer analysis software package by HydroSOLVE Inc. Drawdown data was measured using an electronic water level tape and an electronic datalogger unit.

<b>AQUIFER PARAMETER</b>	<b>RESULT OF ANALYSIS</b>
Transmissivity (m <sup>2</sup> /day)	1.68
Pumping Rate (L/min)	30
Pre-test Static Water Level (m)	4.25
Post-test Static Water Level (m)	19.47
Available Drawdown (m)	118.16
% Drawdown During Pumping Test (%)	13
Specific Capacity (L/min/m drawdown)	1.97

The drawdown data was analyzed using the Theis and Cooper Jacob methods of analysis. Aquifer transmissivity is estimated to be 1.68 m<sup>2</sup>/day. Refer to the Theis and Cooper Jacob methods of analysis data sheets attached to this report.

The pumping test results show that TW1 has a high yield to support the water demands that may be required. Overall maximum drawdown at a constant pumping rate for a period of 8 hours was approximately 15.22 m at approximately 8 hours into the pumping test (13% of the available drawdown). 95% recovery was achieved approximately 13 hours after the end of pumping.

The total volume of water pumped during the 8-hour pumping event was approximately 14,400 L. This is approximately 1.4 times the maximum total daily design volume of water (10,000 L/d) required to support the Re-Zoning Application for all uses on the property. This volume is more than twice the TDDSSF of 7,125 L/day for the Site Plan.

The suitability of the aquifer to support the proposed Re-Zoning Application and Site Plan Control Application for the proposed development was assessed using the methodology provided in the City of Ottawa HTAG. Based on the information summarized in Table 1, it is readily apparent that the water supply well has intercepted an adequately strong water supply aquifer which has sufficient quantity to service the maximum site requirements under OBC.

Given the analyses presented and summarized above, it is our opinion that there is an adequate supply of water to support the proposed Re-Zoning Application and Site Plan Control Application. Available water well records (WWR) of the neighboring properties on



the MECP Well Record mapping website indicated that the wells were screened in limestone. Surrounding WWR's are attached to this report.

## Water Quality

### Field Data

Turbidity, electrical conductivity, total dissolved solids (TDS), pH, true color and temperature were measured at the wellhead during the pumping test. The measurements and time intervals for each of these parameters are summarized in the graphical representation below. In addition, a HACH Pocket Colorimeter II chlorine reader was used to measure the free chlorine residual level. No chlorine residual was detected in the discharge water prior to the collection of the water samples.




Figure 1: Field Testing Results



## Laboratory Data

The Subdivision Package suite of parameters and trace metals laboratory water quality obtained from the pumping test of TW1 is provided in Table 2a and 2b below and the laboratory analyses reports can be found attached. VOC laboratory analytical testing was completed and measured to be non-detect in the sample results and is provided in Table 2c. All laboratory test results can be found attached to this report.

TABLE 2a: GROUNDWATER MICROBIOLOGY & GENERAL GEOCHEMISTRY						
PARAMETER	UNITS	ODWS		TW1		
		LIMIT	TYPE	TW1 GW1 (4 hr)	TW1 GW2 (8 hr)	TW1 GW-3
				6/25/2024	6/25/2024	7/19/2024
<b>MICROBIOLOGICAL</b>						
Escherichia Coli (E. Coli)	ct/100mL	0	MAC	0	0	-
Total Coliforms	ct/100mL	0	MAC	0	0	-
<b>GENERAL CHEMICAL - HEALTH RELATED</b>						
Fluoride (F)	mg/L	1.5	MAC	1.32	1.34	-
Ammonia (N-NH <sub>3</sub> )	mg/L	-	-	0.259	0.263	-
Nitrite (N-NO <sub>2</sub> )	mg/L	1	MAC	<0.5	<0.5	-
Nitrate (N-NO <sub>3</sub> )	mg/L	10	MAC	<0.5	<0.5	-
Total Kjeldahl Nitrogen	mg/L	-	-	1.460	0.483	-
Turbidity (Field)	NTU	1.0 (5.0)	MAC/AO	12.00	7.30	0.56
Turbidity (Laboratory)	NTU	1.0 (5.0)	MAC/AO	11.5	7.1	3.3
<b>GENERAL CHEMICAL - AESTHETIC RELATED</b>						
Alkalinity (as CaCO <sub>3</sub> )	mg/L	30-500	OG	225	225	-
Chloride (Cl)	mg/L	250	AO	85	86	-
Colour (Apparent-Lab)	TCU	5	AO	10	10	12
Colour (Apparent-Field)	TCU	5	AO	12	7	0
Conductivity	uS/cm	-	-	1,350	1,370	-
Dissolved Organic Carbon	mg/L	5	AO	1.3	1.0	-
Hardness (as CaCO <sub>3</sub> )	mg/L	100	OG	356	360	-
Ion Balance	unitless	-	-	1.01	1.02	-
pH	unitless	6.5-8.5	AO	7.97	8.04	-
Phenols	mg/L	-	-	<0.001	<0.001	-
Sulphate (SO <sub>4</sub> )	mg/L	500	AO	388	394	-
Sulphide (S <sub>2</sub> <sup>-</sup> )	mg/L	0.05	AO	0.95	1.16	-
Tannin & Lignin	mg/L	-	-	0.20	0.30	-
Total Dissolved Solids	mg/L	500	AO	944	959	-

1. ODWS identifies the following types of parameters:

MAC = Maximum Allowable Concentration

AO = Aesthetic Objective

OG = Operational Guideline

2. Shaded Concentration Indicates an Exceedance of the ODWS Objective





TABLE 2b: GROUNDWATER GEOCHEMISTRY - METALS						
PARAMETER	UNITS	ODWS		TW1		
		LIMIT	TYPE	TW1 GW1 (4 hr)	TW1 GW2 (8 hr)	TW1 GW-3
				6/25/2024	6/25/2024	7/19/2024
<b>METALS</b>						
Aluminum (Al)	mg/L	0.1	OG	0.43	0.34	0.02
Antimony (Sb)	mg/L	0.006	IMAC	<0.0005	<0.0005	-
Arsenic (As)	mg/L	0.01	IMAC	<0.001	<0.001	-
Barium (Ba)	mg/L	1.0	MAC	0.19	0.19	-
Beryllium (Be)	mg/L	-	-	<0.0005	<0.0005	-
Boron (B)	mg/L	5.0	IMAC	0.43	0.44	-
Cadmium (Cd)	mg/L	0.005	MAC	<0.0001	<0.0001	-
Calcium (Ca)	mg/L	-	-	74	75	-
Chromium (Cr)	mg/L	0.05	MAC	0.001	<0.001	-
Cobalt (Co)	mg/L	-	-	0.0002	<0.0002	-
Copper (Cu)	mg/L	1.0	AO	<0.001	<0.001	-
Iron (Fe)	mg/L	0.3	AO	0.68	0.44	-
Lead (Pb)	mg/L	0.01	MAC	<0.001	<0.001	-
Magnesium (Mg)	mg/L	-	-	42	42	-
Manganese (Mn)	mg/L	0.05	AO	0.02	0.02	-
Mercury (Hg)	mg/L	0.001	MAC	<0.0001	<0.0001	-
Molybdenum (Mo)	mg/L	-	-	<0.005	<0.005	-
Nickel (Ni)	mg/L	-	-	<0.005	<0.005	-
Potassium (K)	mg/L	-	-	6	6	-
Selenium (Se)	mg/L	0.05	MAC	<0.001	<0.001	-
Silver (Ag)	mg/L	-	-	<0.0001	<0.0001	-
Sodium (Na)	mg/L	200	AO	181	186	-
Strontium (Sr)	mg/L	-	-	2.64	2.72	-
Thallium (Tl)	mg/L	-	-	<0.0001	<0.0001	-
Uranium (U)	mg/L	0.02	MAC	<0.001	<0.001	-
Vanadium (V)	mg/L	-	-	0.001	<0.001	-
Zinc (Zn)	mg/L	5.0	AO	<0.01	<0.01	-

- ODWS identifies the following types of parameters:
  - MAC = Maximum Acceptable Concentration
  - IMAC = Interim Maximum Acceptable Concentration
  - AO = Aesthetic Objective
  - OG = Operational Guideline
- Shaded Concentration Indicates an Exceedance of the ODWS Objective





TABLE 2c: GROUNDWATER GEOCHEMISTRY - VOLATILES					
PARAMETER	UNITS	ODWS		TW1	
		LIMIT	TYPE	TW1 GW1 (4 hr)	TW1 GW2 (8 hr)
				6/25/2024	6/25/2024
<b>VOCs Surrogates</b>					
1,2-dichloroethane-d4	%	-	-	122	109
4-bromofluorobenzene	%	-	-	71	72
Toluene-d8	%	-	-	110	113
<b>Volatiles</b>					
1,1,1,2-tetrachloroethane	µg/L	-	-	<0.5	<0.5
1,1,1-trichloroethane	µg/L	-	-	<0.4	<0.4
1,1,2,2-tetrachloroethane	µg/L	-	-	<0.5	<0.5
1,1,2-trichloroethane	µg/L	-	-	<0.4	<0.4
1,1-dichloroethane	µg/L	-	-	<0.4	<0.4
1,1-dichloroethylene	µg/L	14.0	MAC	<0.5	<0.5
1,2-dichlorobenzene	µg/L	200.0	MAC	<0.4	<0.4
1,2-dichloroethane	µg/L	5.0	IMAC	<0.2	<0.2
1,2-dichloropropane	µg/L	-	-	<0.5	<0.5
1,3,5-trimethylbenzene	µg/L	-	-	<0.3	<0.3
1,3-dichlorobenzene	µg/L	-	-	<0.4	<0.4
1,3-Dichloropropylene (cis+trans)	µg/L	-	-	<0.3	<0.3
1,4-dichlorobenzene	µg/L	5.0	MAC	<0.4	<0.4
Acetone	µg/L	-	-	<30	<30
Benzene	µg/L	1.0	MAC	<0.5	<0.5
Bromodichloromethane	µg/L	-	-	<0.3	<0.3
Bromoform	µg/L	-	-	<0.4	<0.4
Bromomethane	µg/L	-	-	<0.5	<0.5
c-1,2-Dichloroethylene	µg/L	-	-	<0.4	<0.4
c-1,3-Dichloropropylene	µg/L	-	-	<0.2	<0.2
Carbon Tetrachloride	µg/L	2.0	MAC	<0.2	<0.2
Chloroethane	µg/L	-	-	<0.2	<0.2
Chloroform	µg/L	-	-	<0.5	<0.5
Dibromochloromethane	µg/L	-	-	<0.3	<0.3
Dichlorodifluoromethane	µg/L	-	-	<0.5	<0.5
Dichloromethane	µg/L	50	MAC	<4.0	<4.0
Ethylbenzene	µg/L	140	MAC	<0.5	<0.5
Ethylene Dibromide	µg/L	-	-	<0.2	<0.2
Hexane	µg/L	-	-	<5	<5
m/p-xylene	µg/L	-	-	<0.4	<0.4
Methyl Ethyl Ketone (MEK)	µg/L	-	-	<2	<2
Methyl Isobutyl Ketone (MIBK)	µg/L	-	-	<5	<5
Methyl Tert Butyl Ether (MTBE)	µg/L	15	AO	<2	<2
Monochlorobenzene	µg/L	80	MAC	<0.5	<0.5
o-xylene	µg/L	-	-	<0.4	<0.4
Styrene	µg/L	-	-	<0.5	<0.5
t-1,2-Dichloroethylene	µg/L	-	-	<0.4	<0.4
t-1,3-Dichloropropylene	µg/L	-	-	<0.2	<0.2
Tetrachloroethylene	µg/L	10	MAC	<0.3	<0.3
Toluene	µg/L	60	MAC	<0.4	<0.4
Trichloroethylene	µg/L	5	MAC	<0.3	<0.3
Trichlorofluoromethane	µg/L	-	-	<0.5	<0.5
Vinyl Chloride	µg/L	1	MAC	<0.2	<0.2
Xylene; total	µg/L	90	MAC	<0.5	<0.5

- ODWS identifies the following types of parameters:
  - MAC = Maximum Acceptable Concentration
  - IMAC = Interim Maximum Acceptable Concentration
  - AO = Aesthetic Objective
  - OG = Operational Guideline
- Shaded Concentration Indicates an Exceedance of the ODWS Objective



The bacteriological test results (Certificate of Analysis – Report No. 3966666) indicated that the test samples at the 4 and 8 hour interval were non-detect (0 ct/100 mL) for E.Coli and Total Coliforms.

The water quality of the subject water supply well meets all the Ontario Drinking Water Standards maximum acceptable concentrations (MAC). Furthermore, the water meets all of the Aesthetic Objectives (AO) and Operational Guidelines (OG) with the exception of the following.

- Hardness (as CaCO<sub>3</sub>)
- Total Dissolved Solids (TDS)
- Iron (Fe)
- Total Sulphides
- Aluminum (Al)
- Colour
- Turbidity

Exceedances of the above parameters are not uncommon of the water supply in the subject aquifer. Each of these groundwater parameters are discussed in detail below.

Should any water treatment be desired by the owner, it is recommended that a water treatment specialist be retained to ensure that water treatment occurs in a safe manner.

### **Hardness as CaCO<sub>3</sub>**

Hardness, expressed as calcium carbonate, is an operation guideline and does not appear in the ODWS. Rather, it appears in the Technical Support Documents for Ontario Drinking Water Standards, Objectives and Guidelines as a parameter with an operational guideline at 100 mg/L. At the measured concentrations of 356 and 360 mg/L, the water is considered to be very hard, however, it is below the reasonable treatable limit of 500 mg/L specified in Table 3 of the MOECC guidance document Procedure D-5-5 (1996).

The Langelier calculation provided an LSI of 0.0. Based on the evaluation of the result, the water is saturated and tends to precipitate a scale layer of calcium carbonate (scale forming and mildly corrosive). Based on the range of stability, there are no mitigative measures needed. See Langelier Saturation Index Calculation attached for calculation details.

It is recommended that water hardness be treated using conventional technologies such as water softening or reverse osmosis, if desired by the owner. Without treating hardness, scaling can occur which can result in discolouration and residue build-up on water fixtures, or reduction in boiler efficiency due to scale build-up. According to Health Canada's *Guidelines for Canadian Drinking Water Quality - Summary Tables* "Although hardness may have significant aesthetic effects, a guideline has not been established because public acceptance of hardness may vary considerably according to the local conditions; major contributors to hardness (calcium and magnesium) are not of direct public health concern".



## Total Dissolved Solids (TDS)

TDS refers to the concentration of inorganic substances dissolved in water. The main constituents are typically chloride, sulphates, calcium, magnesium, and bicarbonates. The TDS concentration of 944 and 959 mg/L, at the 4- and 8-hour points, respectively, exceeds the Aesthetic Objective of 500 mg/L. At concentrations above 500 mg/L, some consumers may find the taste objectionable, however, as the objective is an aesthetic objective, no treatment is required. It is recommended that a point of use reverse osmosis unit be installed to remove taste issues, if the owner desires, for drinking purposes. As such, no taste problems will occur when the recommended treatment technology, or equivalent, is used.

The Langelier calculation provided an LSI of 0.0. Based on the evaluation of the result, the water is saturated and does not tend to precipitate a scale layer of calcium carbonate (non-scale forming and non-corrosive). Based on the range of stability in the positive direction, there are no mitigative measures needed. See Langelier Saturation Index Calculation attached for calculation details.

## Iron

Concentrations of iron above 0.3 mg/L can contribute to staining of fixtures and a metallic taste at higher concentrations. Precipitation of iron can promote the growth of iron bacteria in pipes. The concentration of iron in the groundwater in TW1 was measured to be 0.68 and 0.44 mg/L. The concentration of iron in the groundwater in the test well is considered to be reasonably treatable in accordance with Procedure D-5-5. It is recommended that a water softener or manganese greensand filter be used to reduce the levels of iron and reduce the potential for excessive precipitate occurring in the water supply system, if desired by the property owner. If treatment is not used, negative impacts such as discolouration of water fixtures, precipitation of iron and staining may occur.

## Total Sulphides

Total sulphides were reported to be present within the water supply aquifer at concentrations of 0.95 and 1.16 mg/L. These can present as compounds such as iron sulphide or hydrogen sulphide, but are not limited to these forms. The value noted is for the **total sulphides** within the sample as there is no laboratory test for only hydrogen sulphide. Total sulphides should **not** be equated to a result for hydrogen sulphide.

Hydrogen sulphide is a gas that is heavier than air and has a very distinct “rotten egg” odour. Through the latter portion of the test, a faint odour was detected periodically. The aesthetic objective for hydrogen sulphide, which is incidentally also the threshold of the average human olfactory detection, is 0.05 mg/L. Field testing (olfactory only) estimated values in the range of 0 to 0.1 mg/L, which is in line with the intermittent olfactory observation. MECP Procedure D-5-5 does not indicate a maximum treatable limit for sulphide. One method to remove hydrogen sulphide, if desired, is a chlorine feeder and filter through oxidation or equivalent method recommended by a water treatment professional.



## Aluminum

Aluminum was reported to be present within the water supply aquifer at concentrations of 0.43 and 0.32 mg/L at the 4- and 8-hour marks, respectively. Aluminum has an OG of 0.1 mg/L where an exceedance may cause coating of pipes in the distribution system and flocculation in the distribution system. Aluminum has a federal health related guideline MAC of 2.9 mg/L, which was not exceeded. During a revisit to the subject site and resample, the aluminum concentration was 0.02 mg/L, indicating that TW1 operating under normal usage meets the required guidelines.

## Colour

Colour may occur in drinking water for several reasons. It may be due to organic substances from the decay of vegetation, or the presence of metals such as iron, manganese, and copper, which are abundant in nature. The provincial aesthetic objective for colour in drinking water is 5 True Colour Units (TCU). The federal (Health Canada) guideline aesthetic objective limit for colour is 15 TCU (Guidelines for Canadian Drinking Water Quality, Health Canada June 2019). Procedure D-5-5 gives a maximum concentration considered reasonably treatable for colour as 7 TCU. As colour is a strictly aesthetic parameter, a manganese greensand filter or a carbon filter can be used to reduced manganese from the water supply, if desired by the owner.

During the field pumping test, a DR900 colorimeter was used to measure apparent colour in the groundwater at regular intervals. Field testing for colour had values of 12 and 7 TCU. Laboratory testing showed colour values of 10 TCU during the field test and 12 TCU from the revisit. Apparent colour in the groundwater was measured as 0 TCU during regular usage which is below the aesthetic objective of 5 TCU. The elevated apparent colour levels detected in the lab samples is attributed to the precipitation of iron and manganese out of the groundwater.

## Turbidity

Turbidity, which is generally an aesthetic parameter, was detected in the laboratory test samples at values of 11.5 and 7.1 NTU at the 4 hour and 8 h mark of the pumping test, and at 3.3 NTU during regular usage. Field testing of turbidity showed values of 12, and 7.3 NTU at the 4- and 8-hour mark of the pumping test and 0.56 NTU during regular usage. The test during regular usage was completed during the resample visit. Continued pumping showed a gradual decrease towards the end of the pumping test. The rented pump would have disturbed any precipitate in the water column during its installation and removal of the existing pump. This is demonstrated by the reduction in turbidity and iron during the pumping test, further corroborated by the reduction in turbidity under normal usage.

The ODWS maximum acceptable concentration for turbidity in drinking water entering the distribution system is 1 NTU. In accordance with Procedure D-5-5, Table 2 does not reflect a maximum concentration considered reasonably treatable for Turbidity. The Aesthetic Objective and Maximum Concentration Considered Reasonably Treatable



(MCCRT) for turbidity in drinking water reaching the consumer is 5 NTU (Procedure D-5-5, Table 3). Rather, Procedure D-5-5 indicated that “particular care must be taken during testing to ensure that the bacteria requirements of Table 1 are met.” Based on the test results, the bacteria requirements of Table 1 of D-5-5 have been met (E.Coli = 0 and Total Coliforms = 0).

### **Sodium**

Sodium (Na), an aesthetic parameter, was detected in the laboratory test sample at concentrations of 181 and 186 mg/L, which does not exceed the ODWS aesthetic objective of 200 mg/L. Although sodium is not toxic and no maximum acceptable concentration has been set, concentrations above 20 mg/L require that the Medical Officer of Health be notified of the water quality results, so that this information may be passed on to local physicians for use in treatment of those requiring a sodium-restricted diet. It should be noted that some water treatment technologies, such as water softeners, can increase the sodium concentration so care should be given if such treatment technologies are used.



## **Terrain Analysis**

### **Surficial Geology**

The subsurface conditions are mapped to be fine-textured glaciomarine deposits, mainly consisting of silt and clay, underlying the eastern side of the property; while the western side of the property is mapped to be underlain by stone-poor sandy-silt to silty-sand textured till (OGS MRD218, 2022). The bedrock geology is mapped to be limestone and shale of the Verulam formation of the Simcoe Group (OGS MRD219).

Drift thickness is mapped to be 15 to 25 m bgs, which coincides with neighbouring water well records. The WWR for TW1 showed an overburden thickness of 18m.

### **Hydrogeological Sensitivity of the Site**

The subject site currently contains a two-storey residential dwelling, a commercial building to the south with associated parking and storage, a commercial building (Cidery), and agricultural lands to the east. The subject site is bordered on all sides by agricultural lands, with a church and dwelling located to the south of the site. The site fronts onto Bradley Side Road to the north-west, Huntmar Drive to the north-east and Richardson Side Road to the south-east. All surrounding properties are on private services. The adjacent properties are serviced by private wells and septic systems.

According to available mapping and WWRs, the overburden thickness was observed to be greater than 2 m. As the proposed site does not have bedrock within 2 m of the ground surface, the site is not considered hydrogeologically sensitive. Separation distances are not required to be increased between the septic components and the onsite well.

To corroborate our position in this matter, the water quality of the bedrock aquifer accessed by the onsite drilled potable supply well shows no indication of surface water or surface impacts from sewage system effluent.

### **Conceptual Lot Development**

This Terrain Analysis is completed to support a Re-zoning Application and a Site Plan Control Application. See the attached Site Plan titled “1818 Farm and Cidery – Site Plan” by Vandenberg & Wildeboer Architects, dated March 20, 2024. The place of assembly will consist of a cidery and open air assembly area along with associated parking.

### **Sewage System Design and Total Daily Design Sewage Flow**

This Terrain Analysis has been completed to support a Re-zoning Application and Site Plan Control Application. The associated Ontario Septic System Office permit and sewage treatment system design by D.B. Grey Engineering Inc has been included in the



overall application submission. The TDDSSF for the place of assembly was provided to be 7,125 L/day. A maximum predicted nitrate concentration will be determined for the site as a whole, and the current assessment will be completed based on existing conditions that include the existing residence. Any associated flows with the residence will be counted towards the total site capacity in the site plan application. The total volumes for the site, including the place of assembly and on-site residence, are less than 10,000 L/day per review and design by others.

The proposed property will be analysed as part of the Re-zoning Application and Site Plan Control Application to ensure the theoretical impacts are below the Ontario Drinking Water Objective maximum allowable concentration of 10 mg/L of nitrate in the groundwater prior to the property line.

### **Predictive Nitrate Impact Assessment**

Nitrate is considered to be a critical parameter of concern when assessing impacts to groundwater quality downgradient of an onsite sewage system. The City of Ottawa annotated MECP Procedure D-5-4 in the Hydrogeological and Terrain Analysis Guidelines (HTAG) applies for the proposed development. For the purpose of this guideline, the Ontario Drinking Water Objective of 10 mg/L of nitrate is the maximum allowable concentration detectable in the groundwater prior to the property line.

A detailed impact assessment is required due to the proposed zoning of the site. In order to demonstrate that private services would adequately support the proposed Re-zoning Application, a predictive nitrate impact assessment for the subject site was completed. This calculation was completed to determine the maximum sewage flow volume which could be applied to the subject site with the current site conditions and without the use of tertiary treatment systems (nitrate reducing systems). Furthermore, to support the Site Plan Control Application, a maximum TDDSSF of 10,000 L/day will be examined to determine the nitrate concentration at the property boundary. The values shown in the Predictive Nitrate Impact Assessment calculation attached to this report are summarized below:

- |   |           |
|---|-----------|
| <input type="checkbox"/> Site area  | 11.68 ha  |
| <input type="checkbox"/> Impervious area (%)  | 7 %       |
| <input type="checkbox"/> Concentration of nitrate in effluent<br>(Value based on typical effluent concentration)  | 40 mg/L   |
| <input type="checkbox"/> Surplus Water<br>(The surplus water value was estimated based on Environment Canada Climate Office values with a soil type comprised of a mixture between clay loam (Urban Lawns), fine sandy loam (Mature Forest) and anthropogenic sources.) | 329 mm/yr |





- |  |      |
|--|------|
| ☐ Combined infiltration factor based on: | 0.45 |
| • Topography infiltration factor         | 0.10 |
| • Soil texture infiltration factor       | 0.20 |
| • Cover infiltration factor              | 0.15 |

The topography infiltration factor of 0.10 is based upon a hilly land with an average slope of 28 to 47 m/km. The soil texture infiltration factor was based upon “medium combinations of clay and loam” with a value of 0.2 which is a reasonable generalization based upon the site investigations and available geological mapping. The “cover infiltration factor” was calculated at 0.15 based upon the mix of tree cover and cultivated land.

The predicted nitrate concentration calculation for a conventional sewage system (system without nitrate reduction) results in a maximum of **14.16 m<sup>3</sup>/day** of an effluent using a nitrate concentration of 40 mg/L. This maximum is significantly more than the proposed maximum daily usage of 10 m<sup>3</sup>/d. Therefore, using a conventional sewage system, the maximum TDDSSF of 10,000 L/day (10 m<sup>3</sup>/d) is less than the maximum volumes that the site can support.

Based on the results of the predicted nitrate impact assessment, it is our opinion that the property can adequately support the proposed re-zoning and development without having an adverse impact on the underlying bedrock aquifer.





## CONCLUSIONS

Based on the information contained within the body of this report the following conclusions can be drawn:

1. The water supply aquifer intercepted by the existing well is considered to be adequate to support the water quantity demands for the proposed building usage.
2. Based on a visual inspection performed by Paterson personnel of TW1, the well casing, stickup, and well cap are in compliance with O.Reg 903. The final grading around the well will be sufficiently graded to direct surface water away from the wellhead at the time of the new sewage system installation. The water supply well should be protected from traffic.
3. The preferred water supply intercepted by TW1 contains a water supply that is potable, and contains only elevated concentrations of hardness, TDS, total sulphides, and iron. The noted parameters can be treated with current readily available water conditioning equipment and a water treatment specialist can be retained by the owner, if desired.
4. Colour, turbidity, and aluminum were measured to be elevated in initial laboratory testing. A resample was completed at a later date. The field testing of the re-sample showed 0 TCU for colour and 0.56 NTU for turbidity. Laboratory testing for aluminum was under the operational guideline at the resample. These values represent typical usage of TW1.
5. If desired by the property owner, a residential grade water softener can be used to facilitate the reduction of the hardness concentration and reduce scaling. If a water softener is used for the proposed development, the owner should be made aware that additional sodium will be added to the water to reduce hardness. If desired, a point-of-use reverse osmosis system can be used to provide a drinking tap source without increasing sodium levels.
6. The sodium concentration was measured to be above the 20 mg/L reporting limit and, as such, the Medical Officer of Health for the City of Ottawa should be informed to assist area physicians in the treatment of local residents on sodium reduced diets. It should be noted that some water treatment equipment may further increase the sodium concentration.
7. The predicted nitrate concentrations at the property boundary is calculated to be below the required 10 mg/L threshold when a conventional treatment system is used for greater than 10,000 L/day.



8. A Sewage System Permit and Building Permit need to be issued prior to the commencement of construction.
9. The results of the Hydrogeological Assessment and Terrain Analysis have provided satisfactory evidence that the subject site can support the proposed Re-Zoning Application and Site Plan Control Application with respect to water quality, quantity and sewage system effluent (>10k L/day) attenuation within the property boundary.

We trust that the current submission satisfies your immediate requirements.

Best Regards,

**Paterson Group Inc.**

Alexander Schopf, PhD, EIT

Michael S. Killam, P.Eng.

**Attachments:**

- Key Plan
- MECP Water Well Records
- Eurofins Certificate of Analysis
- AQTESOLV - Pumping Test Analysis Reports
- Nitrate Impact Assessment Calculations
- Langelier Saturation Index (LSI) Calculation





# FIGURE 1

## KEY PLAN



Measurements recorded in:  Metric  Imperial

Page \_\_\_\_\_ of \_\_\_\_\_

Well Owner's Information

First Name \_\_\_\_\_ Last Name/Organization **1818 Bradley Side Road Inc (Ken Hoppner)** E-mail Address \_\_\_\_\_  Well Constructed by Well Owner

Mailing Address (Street Number/Name) **1818 Bradley Side Road** Municipality **Carp** Province **On** Postal Code **K0A 1L0** Telephone No. (inc. area code) \_\_\_\_\_

Well Location

Address of Well Location (Street Number/Name) **1818 Bradley Side Road** Township **West Carleton** Lot **P/L 6** Concession **1**

County/District/Municipality **Ottawa Carleton** City/Town/Village **Carp** Province **Ontario** Postal Code \_\_\_\_\_

UTM Coordinates: Zone **18** Easting **425440** Northing **5017793** Municipal Plan and Sublot Number **4R-1805** Other **Part 1**

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m)
				From To
	Gravel	Boulders	Hard Pan	0' 80'
Grey & Black	Limestone	(Soft)		80' 390'
Grey & Black	Limestone	(Soft)		390' 400'

**Annular Space**

Depth Set at (m)	To (m)	Type of Sealant Used (Material and Type)	Volume Placed (m <sup>3</sup> )
66'	56'	Neat cement	10.92
56'	0'	Bentonite slurry	21

**Results of Well Yield Testing**

Time (min)	Water Level (m)	Time (min)	Water Level (m)
Static Level	14'5"		112'
1	17.6	1	104
2	21	2	102
3	24	3	100
4	26.9	4	98
5	29.7	5	95.9
10	41.8	10	86.1
15	52	15	77.4
20	61.1	20	68.5
25	69.3	25	65.3
30	76.7	30	62.7
40	90	40	58.2
50	101	50	55.4
60	112'	60	53.4'

After test of well yield, water was:  Clear and sand free  Other, specify **Not tested**

If pumping discontinued, give reason: \_\_\_\_\_

Pump intake set at (m) **300**

Pumping rate (l/min/GPM) **4**

Duration of pumping **1** hrs + **0** min

Final water level end of pumping (m) **112'**

If flowing give rate (l/min/GPM) \_\_\_\_\_

Recommended pump depth (m) **380'**

Recommended pump rate (l/min/GPM) **5**

Well production (l/min/GPM) **4**

Disinfected?  Yes  No

**Method of Construction**

Cable Tool  Diamond  Public  Commercial  Not used

Rotary (Conventional)  Jetting  Domestic  Municipal  Dewatering

Rotary (Reverse)  Driving  Livestock  Test Hole  Monitoring

Sporing  Digging  Irrigation  Cooling & Air Conditioning

Percussion **SUGGED**  Industrial  Other, specify \_\_\_\_\_

**Construction Record - Casing**

Inside Diameter (cm)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm)	Depth (m)		Status of Well
			From	To	
6 1/4"	Steel	.188"	+2'	66'	<input checked="" type="checkbox"/> Water Supply
6"	Open Hole		66'	400'	<input type="checkbox"/> Replacement Well

Test Hole  Recharge Well  Dewatering Well  Observation and/or Monitoring Hole  Alteration (Construction)  Abandoned, Insufficient Supply  Abandoned, Poor Water Quality  Abandoned, other, specify \_\_\_\_\_  Other, specify \_\_\_\_\_

**Construction Record - Screen**

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m)	
			From	To

**Water Details**

Water found at Depth (m)	Kind of Water: <input type="checkbox"/> Fresh <input checked="" type="checkbox"/> Untested
390' (m) <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify _____	
(m) <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify _____	
(m) <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify _____	

**Hole Diameter**

Depth (m)	Diameter (cm/in)
0' 66'	9 3/4"
66' 400'	6"

**Well Contractor and Well Technician Information**


Business Name of Well Contractor **Air Rock Drilling Co. Ltd.** Well Contractor's Licence No. **C7681**

Business Address (Street Number/Name) **6859 Franktown Road** Municipality **Richmond**

Province **ON** Postal Code **K0A, 2Z0** Business E-mail Address **air-rock@sympatico.ca**

Bus. Telephone No. (inc. area code) **8138382170** Name of Well Technician (Last Name, First Name) **Hanna, Jeremy**

Well Technician's Licence No. **T3632** Signature of Technician and/or Contractor \_\_\_\_\_ Date Issued **03 31**



Comments: **1 HP 5 GPM SET AT 380 FEET**

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
<input checked="" type="checkbox"/> Yes	<b>2022 03 16</b>	Audit No. <b>2379220</b>
<input type="checkbox"/> No	<b>2022 02 16</b>	Received _____



GROUND WATER BRANCH  
 158 No 3022  
 JUL 3 1962  
 ONTARIO WATER RESOURCES COMMISSION

UTM 18Z 425455E  
 5R 5017205IN  
 Elev. 4R 0355

The Ontario Water Resources Commission Act

# WATER WELL RECORD

Basin 25  
 County or District CARLETON Township, Village, Town or City Huntley  
 Con. 1 County rd #31 Lot NW 1/2 E 5 Date completed 30th June 1962  
 Address Corp. St.

### Casing and Screen Record

Inside diameter of casing 6 1/4"  
 Total length of casing 71'  
 Type of screen  
 Length of screen  
 Depth to top of screen  
 Diameter of finished hole 5 3/4"

### Pumping Test

Static level 30'  
 Test-pumping rate 15' G.P.M.  
 Pumping level 75'  
 Duration of test pumping 45 min.  
 Water clear or cloudy at end of test clear  
 Recommended pumping rate 5' G.P.M.  
 with pump setting of 95' feet below ground surface

### Well Log


### Water Record

Overburden and Bedrock Record	From ft.	To ft.	Depth(s) at which water(s) found	Kind of water (fresh, salty, sulphur)
<u>clay</u>	<u>0</u>	<u>15'</u>		
<u>gravel</u>	<u>15'</u>	<u>30</u>		
<u>sand → gravel</u>	<u>30</u>	<u>40</u>		
<u>quik sand.</u>	<u>40</u>	<u>55'</u>		
<u>limestone</u>	<u>55'</u>	<u>105'</u>		
<u>sandstone</u>	<u>105'</u>	<u>125'</u>	<u>100</u>	<u>fresh.</u>

For what purpose(s) is the water to be used? house  
 Is well on upland, in valley, or on hillside? upland  
 Drilling or Boring Firm Mel M. Laughlin  
 Address Ashton St.  
 Licence Number 593  
 Name of Driller or Borer Melville M. Laughlin  
 Address Ashton St.  
 Date June 30 1962.  
Melville M. Laughlin  
 (Signature of Licensed Drilling or Boring Contractor)

### Location of Well

In diagram below show distances of well from road and lot line. Indicate north by arrow.



6.6

UTM 18 215 425 460 E



3165d

GROUND WATER BRANCH  
No. 3028  
DEC 7 1962  
ONTARIO WATER RESOURCES COMMISSION

5R 5017460 N

The Ontario Water Resources Commission Act

Elev. 4R 2345

# WATER WELL RECORD

Basin 25 Carleton  
County or District

Township, Village, Town or City Huntley

Con. ~~I~~ I Lot SE 1/4 6

Date completed 7<sup>th</sup> November 1962  
(day month year)

Address Corp. Ont.

### Casing and Screen Record

Inside diameter of casing 6 1/4"  
Total length of casing 74'  
Type of screen  
Length of screen  
Depth to top of screen  
Diameter of finished hole 6"

### Pumping Test

Static level 24'  
Test-pumping rate 10 G.P.M.  
Pumping level 40'  
Duration of test pumping 30 min  
Water clear or cloudy at end of test clear  
Recommended pumping rate 5' G.P.M.  
with pump setting of 100' feet below ground surface

### Well Log

#### Overburden and Bedrock Record

clay & boulders  
gravel  
gumbo sand  
limestone rock

#### Water Record

From ft.	To ft.	Depth(s) at which water(s) found	Kind of water (fresh, salty, sulphur)
0	20		
20	40		
40	58	98	fresh
58	120		

For what purpose(s) is the water to be used? farm

Is well on upland, in valley, or on hillside? upland

Drilling or Boring Firm Mel M. Laughlin

Address Ashton Ont

Licence Number 593

Name of Driller or Borer Melville M. Laughlin


Address Ashton Ont

Date November 7, 1962

Melville M. Laughlin  
(Signature of Licensed Drilling or Boring Contractor)

### Location of Well

In diagram below show distances of well from road and lot line. Indicate north by arrow.







Ontario

MINISTRY OF THE ENVIRONMENT  
The Ontario Water Resources Act

# WATER WELL RECORD

319/50

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1514699

MUNICIPALITY 15005 CON. Cdn 01

COUNTY OR DISTRICT	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE	CON., BLOCK, TRACT, SURVEY, ETC.	LOT
	West Carleton Huntley	1	006

R. # 3 Carp, Ontario	DATE COMPLETED
	48-53 DAY 02 NO. 05 YR. 75

1514699	18	425353	5017358	4	360	4	26	JUL 08, 1977	301
---------	----	--------	---------	---	-----	---	----	--------------	-----

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
brown	sand	stones	packed	0	15
grey	harpen	boulders	packed	15	45
grey	sand	boulders	packed	45	64
grey	limestone		soft	64	80
	limestone		soft	80	94

31	00156281279	00452141379	00642281379	008021585	0094 1585
----	-------------	-------------	-------------	-----------	-----------

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
10-13	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
15-18	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
20-23	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
25-28	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
30-33	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL

51 CASING & OPEN HOLE RECORD

INSIDE DIAM. INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/2	1 <input checked="" type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE	188	0	0066
6	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE		66	80
6	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE		80	94
5	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input checked="" type="checkbox"/> OPEN HOLE			0094

SCREEN


SIZE(S) OF OPENING (SLOT NO.)	DIAMETER	LENGTH
	INCHES	FEET
MATERIAL AND TYPE	DEPTH TO TOP OF SCREEN	
	41-44	80
	FEET	

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET	MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)
FROM TO	
10-13 14-17	
18-21 22-25	
26-29 30-33	

71 PUMPING TEST

PUMPING TEST METHOD	1 <input type="checkbox"/> PUMP 2 <input checked="" type="checkbox"/> BAILER
PUMPING RATE	0006 GPM.
DURATION OF PUMPING	02 HOURS 00 MINS.
STATIC LEVEL	060 FEET
WATER LEVEL END OF PUMPING	060 FEET
WATER LEVELS DURING	15 MINUTES: 060 FEET 30 MINUTES: 060 FEET 45 MINUTES: 060 FEET 60 MINUTES: 060 FEET
IF FLOWING, GIVE RATE	
PUMP INTAKE SET AT	080 FEET
WATER AT END OF TEST	0005 GPM.
RECOMMENDED PUMP TYPE	<input type="checkbox"/> SHALLOW <input checked="" type="checkbox"/> DEEP
RECOMMENDED PUMP SETTING	080 FEET
RECOMMENDED PUMPING RATE	0005 GPM.



FINAL STATUS OF WELL

1  WATER SUPPLY  
2  OBSERVATION WELL  
3  TEST HOLE  
4  RECHARGE WELL  
5  ABANDONED, INSUFFICIENT SUPPLY  
6  ABANDONED, POOR QUALITY  
7  UNFINISHED

WATER USE

1  DOMESTIC  
2  STOCK  
3  IRRIGATION  
4  INDUSTRIAL  
5  OTHER  
6  COMMERCIAL  
7  MUNICIPAL  
8  PUBLIC SUPPLY  
9  COOLING OR AIR CONDITIONING  
10  NOT USED

METHOD OF DRILLING

1  CABLE TOOL  
2  ROTARY (CONVENTIONAL)  
3  ROTARY (REVERSE)  
4  ROTARY (AIR)  
5  AIR PERCUSSION  
6  BORING  
7  DIAMOND  
8  JETTING  
9  DRIVING

CONTRACTOR

NAME OF WELL CONTRACTOR: Capital Water Supply Ltd. LICENCE NUMBER: 1558

ADDRESS: Box 490 Stitteville, Ontario

NAME OF DRILLER OR BORER: M. Hamilton LICENCE NUMBER: [blank]

SIGNATURE OF CONTRACTOR: [Signature] SUBMISSION DATE: DAY 8 NO. 5 YR. 75

OFFICE USE ONLY

DATA SOURCE: 1 CONTRACTOR: 1558 DATE RECEIVED: 05 06 75

DATE OF INSPECTION: 9 Apr 74 INSPECTOR: P/R. Dough

REMARKS: [blank]

P

WI



31G5d

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1516709

MUNICIPALITY 15006 CON. C6N LOT 01

COUNTY OR DISTRICT: Carleton Place TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: March CON., BLOCK, TRACT, SURVEY, ETC: 1 LOT: 006

DATE COMPLETED: DAY 21 MO 09 YR 78

WELL NO: 017660 RC: 4 ELEVATION: 0325 RC: 4 BASIN CODE: 26

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	clay	sand	loose	0	3
brown	clay		packed	3	20
grey	clay	stones		20	46
grey	sand	clay + boulders	packed	46	55
grey	limestone		med soft	55	200

31 00036052877 002060579 004620512 0052280513 020021585

32

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
10-13	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERAL
15-18	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERAL
20-23	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERAL
25-28	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERAL
30-33	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERAL

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET
4 1/4	STEEL	188	0 to 56
6	STEEL		56 to 200

SCREEN

SIZE(S) OF OPENING (SLOT NO.)	DIAMETER	LENGTH
	INCHES	FEET

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET	MATERIAL AND TYPE
10-13	14-17
18-21	22-25
26-29	30-33

71 PUMPING TEST

PUMPING TEST METHOD: 1  PUMP 2  BAILER

PUMPING RATE: 0007 GPM


DURATION OF PUMPING: 01 HOURS 30 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING PUMPING
015 FEET	075 FEET	15 MINUTES: 065 FEET 30 MINUTES: 075 FEET 45 MINUTES: 075 FEET 60 MINUTES: 075 FEET

RECOMMENDED PUMP TYPE:  SHALLOW  DEEP

RECOMMENDED PUMP SETTING: 080 FEET

RECOMMENDED PUMPING RATE: 0005 GPM



FINAL STATUS OF WELL: 1  WATER SUPPLY

WATER USE: 1  DOMESTIC

METHOD OF DRILLING: 1  CABLE TOOL

CONTRACTOR: CAPITAL WATER SUPPLY LTD LICENCE NUMBER: 1558

ADDRESS: Box 490, STITTSVILLE ONT.

NAME OF DRILLER OR BORER: J. Moore LICENCE NUMBER: [blank]

SIGNATURE OF CONTRACTOR: [Signature] SUBMISSION DATE: DAY 27 MO 9 YR 78

OFFICE USE ONLY

DATA SOURCE: 1 CONTRACTOR: 1558 DATE RECEIVED: 30/10/78

DATE OF INSPECTION: 22/05/79 INSPECTOR: [Signature]

REMARKS: [blank]



Ministry of the Environment

The Ontario Water Resources Act

31G5d

# WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

01516743

MUNICIPALITY 15005

CON. CQN

01

COUNTY OR DISTRICT: North York TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: West Carleton (Huntley) CON., BLOCK, TRACT, SURVEY, ETC.: 1

DATE COMPLETED: DAY 23 MO 10 YEAR 78

GRID: 10-12 017160 13-15 4 16-18 0355 19-21 4 22-24 26

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Haulpan	Boulders		0	21
Grey	Haulpan	boulders		21	32
Grey	limestone		broken	32	34
Grey	limestone		medium	34	115
Black	limestone		medium	115	250
Black	limestone		medium	250	260

31 002161413 003221413 003421571 0115215 0250815

**41 WATER RECORD**

WATER FOUND AT - FEET	KIND OF WATER
10-13	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY <input type="checkbox"/> MINERAL
15-18	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY <input type="checkbox"/> MINERAL
20-23	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY <input type="checkbox"/> MINERAL
25-28	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY <input type="checkbox"/> MINERAL
30-33	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY <input type="checkbox"/> MINERAL

**51 CASING & OPEN HOLE RECORD**

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/4	STEEL	188	0	34
6	STEEL		34	250
5 3/4	STEEL		250	260

**SCREEN**

SIZE(S) OF OPENING (SLOT NO)	DIAMETER	LENGTH
	INCHES	FEET

**61 PLUGGING & SEALING RECORD**

DEPTH SET AT - FEET	MATERIAL AND TYPE	CEMENT GROUT LEAD PACKER, ETC.)
10-13		
18-21		
26-29		

**71 PUMPING TEST**

PUMPING TEST METHOD: 1  PUMP 2  BAILER

PUMPING RATE: 0.024 GPM


DURATION OF PUMPING: 01 HOURS 00 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING
020 FEET	050 FEET	15 MINUTES: 050 FEET 30 MINUTES: 050 FEET 45 MINUTES: 050 FEET 60 MINUTES: 050 FEET

RECOMMENDED PUMP TYPE:  SHALLOW  DEEP

RECOMMENDED PUMP SETTING: 060 FEET

RECOMMENDED PUMPING RATE: 0005 GPM



**FINAL STATUS OF WELL**

1  WATER SUPPLY 5  ABANDONED, INSUFFICIENT SUPPLY  
2  OBSERVATION WELL 6  ABANDONED, POOR QUALITY  
3  TEST HOLE 7  UNFINISHED  
4  RECHARGE WELL

**WATER USE**

1  DOMESTIC 5  COMMERCIAL  
2  STOCK 6  MUNICIPAL  
3  IRRIGATION 7  PUBLIC SUPPLY  
4  INDUSTRIAL 8  COOLING OR AIR CONDITIONING  
9  NOT USED

**METHOD OF DRILLING**

1  CABLE TOOL 250-260 6  BORING  
2  ROTARY (CONVENTIONAL) 7  DIAMOND  
3  ROTARY (REVERSE) 8  JETTING  
4  ROTARY (AIR) 9  DRIVING  
5  AIR PERCUSSION

**CONTRACTOR**

NAME OF WELL CONTRACTOR: CAPITAL WATER SUPPLY LTD LICENCE NUMBER: 1558

ADDRESS: Box 490, STITTSVILLE ONT.

NAME OF DRILLER OR BORER: S Miller & J Moore

SIGNATURE OF CONTRACTOR: Kalter Kwanuk SUBMISSION DATE: DAY 26 MO 10 YEAR 78

**OFFICE USE ONLY**

DATA SOURCE: 1 CONTRACTOR: 1558 DATE RECEIVED: 281178

DATE OF INSPECTION: 17/05/79 INSPECTOR: km ll



# WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1516888 MUNICIPAL 15.006 CON. C6N 01

COUNTY OR DISTRICT: Carleton Place TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: March CON., BLOCK, TRACT, SURVEY, ETC.: 1 LOT: 006

DATE COMPLETED: 48-53 DAY: 22 MO: 12 YR: 78

RC: 017680 ELEVATION: 4 BASIN CODE: 0325 RC: 4 BASIN CODE: 26

### LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Hardpan	Boulders		0	10
Brown	Clay			10	25
Blue	Clay			25	29
Grey	Gabbro			29	90
Grey	Granite			90	130
White + green	granite		med hard	130	175
grey	granite		very hard	175	200

31 001061413 0025605 0029305 0130221 017512173 02002219073

32

#### 41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
10-13	1 <input checked="" type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
15-18	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
20-23	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
25-28	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
30-33	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL

#### 51 CASING & OPEN HOLE RECORD

INSIDE DIAM. INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET
			FROM TO
10-13	1 <input checked="" type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE	1.88	0 0030
17-18	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input checked="" type="checkbox"/> OPEN HOLE		30 0090
24-25	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input checked="" type="checkbox"/> OPEN HOLE		90 0200

#### SCREEN

SIZES OF OPENING (SLOT NO.)	DIAMETER INCHES	LENGTH FEET
		DEPTH TO TOP OF SCREEN
		41-44
		FEET

#### 61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET	MATERIAL AND TYPE (CEMENT GROUT LEAD PACKER, ETC.)
FROM TO	
10-13	14-17
18-21	22-25
26-29	30-33

#### 71 PUMPING TEST

PUMPING TEST METHOD: 1  PUMP 2  BAILER

PUMPING RATE: 0003 2 1/2 GPM


DURATION OF PUMPING: 01 15-16 HOURS 00 17-18 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING	1 <input checked="" type="checkbox"/> PUMPING 2 <input type="checkbox"/> RECOVERY
19-21	22-24	15 MINUTES 26-28	30 MINUTES 29-31
FEET	FEET	FEET	FEET
012	175	175	175
		175	175

RECOMMENDED PUMP TYPE:  SHALLOW  DEEP

RECOMMENDED PUMP SETTING: 0190 FEET

RECOMMENDED PUMPING RATE: 0002 GPM



#### FINAL STATUS OF WELL

1  WATER SUPPLY 5  ABANDONED, INSUFFICIENT SUPPLY  
2  OBSERVATION WELL 6  ABANDONED, POOR QUALITY  
3  TEST HOLE 7  UNFINISHED  
4  RECHARGE WELL

#### WATER USE

1  DOMESTIC 5  COMMERCIAL  
2  STOCK 6  MUNICIPAL  
3  IRRIGATION 7  PUBLIC SUPPLY  
4  INDUSTRIAL 8  COOLING OR AIR CONDITIONING  
9  OTHER 9  NOT USED

#### METHOD OF DRILLING

1  CABLE TOOL 6  BORING  
2  ROTARY (CONVENTIONAL) 7  DIAMOND  
3  ROTARY (REVERSE) 8  JETTING  
4  ROTARY (AIR) 9  DRIVING  
5  AIR PERCUSSION

#### CONTRACTOR

NAME OF WELL CONTRACTOR: CAPITAL WATER SUPPLY LTD 1558 LICENCE NUMBER: 1558

ADDRESS: Box 490 STITTVILLE ONTARIO

NAME OF DRILLER OR BORER: S Miller - J Moore LICENCE NUMBER:

SIGNATURE OF CONTRACTOR: H Koeneck SUBMISSION DATE: 22 MO: 12 YR: 78

#### OFFICE USE ONLY

DATA SOURCE: 1 CONTRACTOR: 1558 DATE RECEIVED: 220179

DATE OF INSPECTION: 22/05/79 INSPECTOR: K H

REMARKS:



Ontario

# WATER WELL RECORD

3165d

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1516900

MUNICIPALITY 15.005 CON. CQN LOT 01

COUNTY OR DISTRICT: CARLETON TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: WEST CARLETON CON. BLOCK, TRACT, SURVEY, ETC.: 1 LOT: 25-27

OWNER (SURNAME FIRST): [REDACTED] DATE COMPLETED: 25 MO 09 YR 78

STWAY TANK) 1995 MERIVALE RD

HING: 017140 ELEVATION: 6355 BASIN CODE: 26

## LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
BROWN	CLAY LOAM		LOOSE	0	8
BLUE	CLAY	MARINE CLAY	"	8	21
BLUE	CLAY	HARD TAN	PACKED	21	44
BROWN	GRAVEL	STONES	OVERBURDEN	44	38
BLUE	LIMESTONE		SHALEY	58	188

32 00086050277 00213050577 00443051479 0058611225 018831517

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
10-13	1 <input type="checkbox"/> FRESH 3 <input checked="" type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY 4 <input checked="" type="checkbox"/> MINERAL
15-18	1 <input checked="" type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
20-23	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
25-28	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL
30-33	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERAL

51 CASING & OPEN HOLE RECORD

INSIDE DIAM. INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET
			FROM TO
10-11	1 <input checked="" type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE	.188	0 0060
17-18	1 <input checked="" type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE		60 0188
22-25	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE		

SCREEN

SIZE(S) OF OPENING (SLOT NO.)	DIAMETER INCHES	LENGTH FEET
31-33	34-38	39-40
MATERIAL AND TYPE		DEPTH TO TOP OF SCREEN 41-44 80 FEET

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET	MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)
FROM TO	
10-13	14-17
18-21	22-25
26-29	30-33 80

71 PUMPING TEST

PUMPING TEST METHOD: 1  PUMP 2  BAILER

PUMPING RATE: 0015 GPM


DURATION OF PUMPING: 01 HOURS 00 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING	RECOVERY
018 FEET	187 FEET	15 MINUTES: 187 FEET 20 MINUTES: 187 FEET 25 MINUTES: 187 FEET 30 MINUTES: 187 FEET	1 <input checked="" type="checkbox"/> PUMPING 2 <input type="checkbox"/> RECOVERY

RECOMMENDED PUMP TYPE:  SHALLOW  DEEP

RECOMMENDED PUMP SETTING: 180 FEET

RECOMMENDED PUMPING RATE: 0010 GPM



54 FINAL STATUS OF WELL

1  WATER SUPPLY 5  ABANDONED, INSUFFICIENT SUPPLY  
2  OBSERVATION WELL 6  ABANDONED, POOR QUALITY  
3  TEST HOLE 7  UNFINISHED  
4  RECHARGE WELL

55-56 WATER USE

1  DOMESTIC 5  COMMERCIAL  
2  STOCK 6  MUNICIPAL  
3  IRRIGATION 7  PUBLIC SUPPLY  
4  INDUSTRIAL 8  COOLING OR AIR CONDITIONING  
9  NOT USED

57 METHOD OF DRILLING

1  CABLE TOOL 6  BORING  
2  ROTARY (CONVENTIONAL) 7  DIAMOND  
3  ROTARY (REVERSE) 8  JETTING  
4  ROTARY (AIR) 9  DRIVING  
5  AIR PERCUSSION

CONTRACTOR

NAME OF WELL CONTRACTOR: GIFFIN Well Drilling Ltd. LICENCE NUMBER: 2307

ADDRESS: RR#2 RENEW ONTARIO

NAME OF DRILLER OR BORER: Paul Daniels LICENCE NUMBER: 1746

SIGNATURE OF CONTRACTOR: [Signature] SUBMISSION DATE: [Blank]

OFFICE USE ONLY

DATA SOURCE: 1 CONTRACTOR: 2307 DATE RECEIVED: 21 02 79

DATE OF INSPECTION: 17/05/78 INSPECTOR: [Signature]

REMARKS: [Blank]

P  
WI



Ministry  
of the  
Environment  
Ontario

The Ontario Water Resources Act

# WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11

1522259

MUNICIPALITY: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24  
CON. NO.: 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40

COUNTY OR DISTRICT: **Ontario Carleton Place** TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: **West Carleton - Huntley** CON. BLOCK, TRACT, SURVEY ETC: **Conc. 1** LOT: **25-27 6**

DATE COMPLETED: **48-53** DAY: **04** MO: **02** YR: **88**

R. # **3; Carp, Ontario, KOA 110**

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)					
GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Clay	Boulders	Packed	0	20
Gray	Clay	Boulders	Packed	20	34
Gray	Sand	Clay and Boulders	Loose	34	55
Gray	Hardpan	Boulders, Sand	Packed	55	64 1/2
Gray	Limestone		Medium Hard	64 1/2	83

31 32


41 WATER RECORD	
WATER FOUND AT - FEET	KIND OF WATER
66	1 <input checked="" type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS
79	1 <input checked="" type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS

51 CASING & OPEN HOLE RECORD				
INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/4	1 <input checked="" type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC	.188	0	65
5 15/16	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC		65	83

SCREEN	SIZE(S) OF OPENING (SLOT NO.)	DIAMETER INCHES	LENGTH FEET

61 PLUGGING & SEALING RECORD		
DEPTH SET AT - FEET	MATERIAL AND TYPE	(CEMENT GROUT LEAD PACKER, ETC.)
10-13		
18-21		
26-29		

71 PUMPING TEST	PUMPING TEST METHOD		PUMPING RATE		DURATION OF PUMPING		
	1 <input checked="" type="checkbox"/> PUMP	2 <input type="checkbox"/> BAILER	8	GPM	16	HOURS	17-18
	19-21	22-24	25-28	29-31	32-34	35-37	
	20	30	30	30	30	30	



84 FINAL STATUS OF WELL	
1 <input checked="" type="checkbox"/> WATER SUPPLY	8 <input type="checkbox"/> ABANDONED, INSUFFICIENT SUPPLY
2 <input type="checkbox"/> OBSERVATION WELL	9 <input type="checkbox"/> ABANDONED POOR QUALITY
3 <input type="checkbox"/> TEST HOLE	10 <input type="checkbox"/> UNFINISHED
4 <input type="checkbox"/> RECHARGE WELL	11 <input type="checkbox"/> DEWATERING

85-86 WATER USE	
1 <input checked="" type="checkbox"/> DOMESTIC	5 <input type="checkbox"/> COMMERCIAL
2 <input type="checkbox"/> STOCK	6 <input type="checkbox"/> MUNICIPAL
3 <input type="checkbox"/> IRRIGATION	7 <input type="checkbox"/> PUBLIC SUPPLY
4 <input type="checkbox"/> INDUSTRIAL	8 <input type="checkbox"/> COOLING OR AIR CONDITIONING
9 <input type="checkbox"/> OTHER	12 <input type="checkbox"/> NOT USED

87 METHOD OF CONSTRUCTION	
1 <input checked="" type="checkbox"/> CABLE TOOL	6 <input type="checkbox"/> BORING
2 <input type="checkbox"/> ROTARY (CONVENTIONAL)	7 <input type="checkbox"/> DIAMOND
3 <input type="checkbox"/> ROTARY (REVERSE)	8 <input type="checkbox"/> JETTING
4 <input type="checkbox"/> ROTARY (AIR)	9 <input type="checkbox"/> DRIVING
5 <input type="checkbox"/> AIR PERCUSSION	10 <input type="checkbox"/> DIGGING
	11 <input type="checkbox"/> OTHER

CONTRACTOR		OFFICE USE ONLY	
NAME OF WELL CONTRACTOR: <b>Capital Water Supply Ltd.</b>	WELL CONTRACTOR'S LICENCE NUMBER: <b>1558</b>	DATE RECEIVED: <b>APR 11 1988</b>	CONTRACTOR: <b>58</b>
ADDRESS: <b>Box 490; Stittsville, Ont. KOA 3G0</b>	WELL TECHNICIAN'S LICENCE NUMBER: <b>J. Moore</b>	DATE OF INSPECTION:	INSPECTOR:
SIGNATURE OF TECHNICIAN/CONTRACTOR: <i>J. Moore</i>	SUBMISSION DATE: <b>APR 02 1988</b>	REMARKS:	



# WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11

1526023

MUNICIPALITY 150.05

CON. CON.

01

COUNTY OR DISTRICT <b>Ottawa Carleton</b>	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE <b>West Carleton</b>	CON. BLOCK, TRACT, SURVEY ETC <b>1</b>	LOT <b>6</b>
OWNER (SURNAME FIRST) <b>Jacques Whitford Ltd.</b>	ADDRESS <b>C-20 2285 St. Laurent Blvd. Ottawa, Ontario</b>	DATE COMPLETED DAY <b>21</b> MO <b>10</b> YR <b>91</b>	

ZONE <b>21</b>	EASTING <b>K46 476</b>	RC <b>25</b>	ELEVATION <b>30</b>	RC <b>31</b>	BASIN CODE <b>II</b>	III <b>IV</b>
-------------------	---------------------------	-----------------	------------------------	-----------------	-------------------------	------------------

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)					
GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Clay			0	10
Gray	Clay	Stones & Gravel		10	33
Gray	Limestone			33	300

31	32	33	34	35	36	37	38	39	40
----	----	----	----	----	----	----	----	----	----

41 WATER RECORD			
WATER FOUND AT - FEET	KIND OF WATER		
10-13 <b>243</b>	1 <input type="checkbox"/> FRESH 2 <input type="checkbox"/> SALTY	3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS	14
15-18	1 <input type="checkbox"/> FRESH 2 <input type="checkbox"/> SALTY	3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS	19
20-23	1 <input type="checkbox"/> FRESH 2 <input type="checkbox"/> SALTY	3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS	24
25-28	1 <input type="checkbox"/> FRESH 2 <input type="checkbox"/> SALTY	3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS	29
30-33	1 <input type="checkbox"/> FRESH 2 <input type="checkbox"/> SALTY	3 <input type="checkbox"/> SULPHUR 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS	34-80

51 CASING & OPEN HOLE RECORD				
INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/4	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC	.188	0	34
6 1/16	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC		34	200
6	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC		200	300

SCREEN	SIZE(S) OF OPENING (SLOT NO)	DIAMETER	LENGTH
		INCHES	FEET
MATERIAL AND TYPE		DEPTH TO TOP OF SCREEN	
		41-44	50

61 PLUGGING & SEALING RECORD			
DEPTH SET AT - FEET		MATERIAL AND TYPE (CEMENT GROUT LEAD PACKER, ETC)	
FROM	TO		
10-13	14-17	Grouted Cement	
18-21	22-25		
26-29	30-33	80	

71 PUMPING TEST	PUMPING TEST METHOD 1 <input checked="" type="checkbox"/> PUMP 2 <input type="checkbox"/> BAILER	PUMPING RATE <b>2.5</b> GPM	DURATION OF PUMPING 15-16 HOURS 17-18 MIN.			
	STATIC LEVEL <b>25</b> FEET	WATER LEVEL END OF PUMPING <b>200</b> FEET	WATER LEVELS DURING 1 <input checked="" type="checkbox"/> PUMPING 2 <input type="checkbox"/> RECOVERY			
	19-21	22-24	25-28	29-31	32-34	35-37
	<b>200</b> FEET	<b>200</b> FEET	<b>200</b> FEET	<b>200</b> FEET	<b>200</b> FEET	<b>200</b> FEET
	IF FLOWING, GIVE RATE	PUMP INTAKE SET AT	WATER AT END OF TEST	1 <input type="checkbox"/> CLEAR 2 <input type="checkbox"/> CLOUDY		
RECOMMENDED PUMP TYPE <input type="checkbox"/> SHALLOW <input type="checkbox"/> DEEP	RECOMMENDED PUMP SETTING <b>225</b> FEET	RECOMMENDED PUMPING RATE <b>2.5</b> GPM				

LOCATION OF WELL	
IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE INDICATE NORTH BY ARROW.	
DRILLERS REMARKS	<b>100188</b>

74 FINAL STATUS OF WELL	1 <input checked="" type="checkbox"/> WATER SUPPLY 2 <input type="checkbox"/> OBSERVATION WELL 3 <input type="checkbox"/> TEST HOLE 4 <input type="checkbox"/> RECHARGE WELL	5 <input checked="" type="checkbox"/> ABANDONED, INSUFFICIENT SUPPLY 6 <input type="checkbox"/> ABANDONED POOR QUALITY 7 <input type="checkbox"/> UNFINISHED 8 <input type="checkbox"/> DEWATERING
75-76 WATER USE	1 <input checked="" type="checkbox"/> DOMESTIC 2 <input type="checkbox"/> STOCK 3 <input type="checkbox"/> IRRIGATION 4 <input type="checkbox"/> INDUSTRIAL 5 <input type="checkbox"/> OTHER	6 <input type="checkbox"/> COMMERCIAL 7 <input type="checkbox"/> MUNICIPAL 8 <input type="checkbox"/> PUBLIC SUPPLY 9 <input type="checkbox"/> COOLING OR AIR CONDITIONING 10 <input type="checkbox"/> NOT USED
77 METHOD OF CONSTRUCTION	1 <input type="checkbox"/> CABLE TOOL 2 <input type="checkbox"/> ROTARY (CONVENTIONAL) 3 <input type="checkbox"/> ROTARY (REVERSE) 4 <input type="checkbox"/> ROTARY (AIR) 5 <input checked="" type="checkbox"/> AIR PERCUSSION	6 <input type="checkbox"/> BORING 7 <input type="checkbox"/> DIAMOND 8 <input type="checkbox"/> JETTING 9 <input type="checkbox"/> DRIVING 10 <input type="checkbox"/> DIGGING <input type="checkbox"/> OTHER

CONTRACTOR	NAME OF WELL CONTRACTOR <b>Capital Water Supply Ltd.</b>	WELL CONTRACTOR'S LICENCE NUMBER <b>1558</b>
	ADDRESS <b>Box 490 Stittsville, Ontario K2S 1A6</b>	
	NAME OF WELL TECHNICIAN <b>S. Miller</b>	WELL TECHNICIAN'S LICENCE NUMBER <b>T0096</b>
	SIGNATURE OF TECHNICIAN/CONTRACTOR 	SUBMISSION DATE DAY <b>25</b> MO <b>10</b> YR <b>91</b>

OFFICE USE ONLY	DATA SOURCE	CONTRACTOR <b>1558</b>	DATE RECEIVED <b>JAN 13 1992</b>
	DATE OF INSPECTION	INSPECTOR	
	REMARKS <b>CSSE</b>		



1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1526122 15005 CON. 01

COUNTY OR DISTRICT: **Ottawa Carleton** TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: **west Carleton - Huntley** CON. BLOCK, TRACT, SURVEY ETC: **1** LOT: **6**

OWNER (SURNAME FIRST): **Jacques Whitford Ltd.** ADDRESS: **C-20 2285 St. Laurent Blvd Ottawa, Ontario** DATE COMPLETED: **19 11 91**

U ZONE: **21** EASTING: **K19 426** RC. ELEVATION: **30** BASIN CODE: **11** III: **11** IV: **91**

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)					
GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Clay	Stones		0	14
Gray	Clay	Stones		14	24
Gray	Limestone			24	175
Gray	Limestone			175	205

31  
32

**41 WATER RECORD**

WATER FOUND AT - FEET	KIND OF WATER					
60	<input type="checkbox"/> FRESH	<input type="checkbox"/> SALTY	<input type="checkbox"/> SULPHUR	<input type="checkbox"/> MINERALS	<input type="checkbox"/> GAS	
195	<input type="checkbox"/> FRESH	<input type="checkbox"/> SALTY	<input type="checkbox"/> SULPHUR	<input type="checkbox"/> MINERALS	<input type="checkbox"/> GAS	
	<input type="checkbox"/> FRESH	<input type="checkbox"/> SALTY	<input type="checkbox"/> SULPHUR	<input type="checkbox"/> MINERALS	<input type="checkbox"/> GAS	
	<input type="checkbox"/> FRESH	<input type="checkbox"/> SALTY	<input type="checkbox"/> SULPHUR	<input type="checkbox"/> MINERALS	<input type="checkbox"/> GAS	
	<input type="checkbox"/> FRESH	<input type="checkbox"/> SALTY	<input type="checkbox"/> SULPHUR	<input type="checkbox"/> MINERALS	<input type="checkbox"/> GAS	

**51 CASING & OPEN HOLE RECORD**

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/4	STEEL GALVANIZED CONCRETE OPEN HOLE PLASTIC	.188	0	26
6 1/8	STEEL GALVANIZED CONCRETE OPEN HOLE PLASTIC		26	205
	STEEL GALVANIZED CONCRETE OPEN HOLE PLASTIC			27-30

**SCREEN**


SIZE(S) OF OPENING (SLOT NO 1)	DIAMETER	LENGTH
	INCHES	FEET
		DEPTH TO TOP OF SCREEN
		FEET

**61 PLUGGING & SEALING RECORD**

DEPTH SET AT - FEET	MATERIAL AND TYPE
FROM TO	(CEMENT GROUT, LEAD PACKER, ETC.)
10-13	14-17
18-21	22-25
26-29	30-33

**71 PUMPING TEST**

PUMPING TEST METHOD	PUMPING RATE	DURATION OF PUMPING
<input checked="" type="checkbox"/> PUMP <input type="checkbox"/> BAILER	20 GPM	1 15-16 HOURS 17-18 MINS
STATIC LEVEL	WATER LEVELS DURING	<input checked="" type="checkbox"/> PUMPING <input type="checkbox"/> RECOVERY
19-21 FEET	15 MINUTES 20-28 FEET 30 MINUTES 29-31 FEET 45 MINUTES 32-34 FEET 60 MINUTES 35-37 FEET	
IF FLOWING, GIVE RATE	PUMP INTAKE SET AT	WATER AT END OF TEST
	45 GPM	<input checked="" type="checkbox"/> CLEAR <input type="checkbox"/> CLOUDY
RECOMMENDED PUMP TYPE	RECOMMENDED PUMP SETTING	RECOMMENDED PUMPING RATE
<input type="checkbox"/> SHALLOW <input checked="" type="checkbox"/> DEEP	100 FEET	5 GPM



**FINAL STATUS OF WELL**

WATER SUPPLY  ABANDONED, INSUFFICIENT SUPPLY  
 OBSERVATION WELL  ABANDONED, POOR QUALITY  
 TEST HOLE  UNFINISHED  
 RECHARGE WELL  DEWATERING

**WATER USE**

DOMESTIC  COMMERCIAL  
 STOCK  MUNICIPAL  
 IRRIGATION  PUBLIC SUPPLY  
 INDUSTRIAL  COOLING OR AIR CONDITIONING  
 OTHER  NOT USED

**METHOD OF CONSTRUCTION**

CABLE TOOL 175-205  BORING  
 ROTARY (CONVENTIONAL)  DIAMOND  
 ROTARY (REVERSE)  JETTING  
 ROTARY (AIR)  DRIVING  
 AIR PERCUSSION 0-175  DIGGING  OTHER

**CONTRACTOR**

NAME OF WELL CONTRACTOR: **Capital Water Supply Ltd.** WELL CONTRACTOR'S LICENCE NUMBER: **1558**

ADDRESS: **Box 490 Stittsville, Ontario K2S 1A6**

NAME OF WELL TECHNICIAN: **S. Miller/ J. Moore** WELL TECHNICIAN'S LICENCE NUMBER: **T0097/T0096**

SIGNATURE OF TECHNICIAN/CONTRACTOR: *[Signature]* SUBMISSION DATE: **28 11 91**

**OFFICE USE ONLY**

DATA SOURCE: **1558** CONTRACTOR: **1558** DATE RECEIVED: **APR 30 1992**

DATE OF INSPECTION: \_\_\_\_\_ INSPECTOR: \_\_\_\_\_

REMARKS: \_\_\_\_\_

*CSG.E3*

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11 1527008 15005 CON 01

COUNTY OR DISTRICT: **Ottawa Carleton** TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: **West Carleton - Huntley** CON. BLOCK, TRACT, SURVEY, ETC.: **1** LOT: **6**

OWNER (SURNAME FIRST): [REDACTED] ADDRESS: **c/o Thunderbird Golf & Athletic Club Carp, Ontario** DATE COMPLETED: **14 MO 01 YR 93**

21 UTM ZONE: [REDACTED] EASTING: [REDACTED] NORTHING: **KOA 1L** ELEVATION: [REDACTED] BASIN CODE: [REDACTED]

**LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)**

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET	
				FROM	TO
Brown	Clay	Sand and Stones	Packed	0	8
Brown	Sand	Stones	Loose	8	13
Gray	Hardpan	Boulders	Hard	13	36
Gray	Limestone	Black Layers	Medium	36	90

31 [REDACTED] 32 [REDACTED]

**41 WATER RECORD**

WATER FOUND AT - FEET	KIND OF WATER
54	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS
66	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS
NOT TESTED	1 <input type="checkbox"/> FRESH 3 <input type="checkbox"/> SULPHUR 2 <input type="checkbox"/> SALTY 4 <input type="checkbox"/> MINERALS 6 <input type="checkbox"/> GAS

**51 CASING & OPEN HOLE RECORD**

INSIDE DIAM. INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET	
			FROM	TO
6 1/4	1 <input checked="" type="checkbox"/> STEEL 2 <input checked="" type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC	.188	0	40
6 1/8	1 <input type="checkbox"/> STEEL 2 <input type="checkbox"/> GALVANIZED 3 <input type="checkbox"/> CONCRETE 4 <input type="checkbox"/> OPEN HOLE 5 <input type="checkbox"/> PLASTIC		40	90

**SCREEN**

SIZE (S) OF OPENING (SLOT NO.)	DIAMETER INCHES	LENGTH FEET

MATERIAL AND TYPE: [REDACTED] DEPTH TO TOP OF SCREEN: [REDACTED] FEET

**61 PLUGGING & SEALING RECORD**

DEPTH SET AT - FEET	MATERIAL AND TYPE (CEMENT GROUT LEAD PACKER, ETC.)
40	2 Grouted Cement (7)

**71 PUMPING TEST**

PUMPING TEST METHOD: 1  PUMP 2  BAILER

PUMPING RATE: **5** GPM DURATION OF PUMPING: **1** HOURS

STATIC LEVEL: **20** FEET WATER LEVEL END OF PUMPING: **70** FEET

WATER LEVELS DURING PUMPING RECOVERY:

15 MINUTES: <b>55</b> FEET	30 MINUTES: <b>70</b> FEET	45 MINUTES: <b>70</b> FEET	60 MINUTES: <b>70</b> FEET
----------------------------	----------------------------	----------------------------	----------------------------

RECOMMENDED PUMP TYPE:  SHALLOW  DEEP

RECOMMENDED PUMP SETTING: **80** FEET

RECOMMENDED PUMPING RATE: **5** GPM

**LOCATION OF WELL**

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE INDICATE NORTH BY ARROW.

House \* 1948

Richardson Side Rd  
**130012**

**FINAL STATUS OF WELL**

1  WATER SUPPLY 5  ABANDONED INSUFFICIENT SUPPLY  
2  OBSERVATION WELL 6  ABANDONED POOR QUALITY  
3  TEST HOLE 7  UNFINISHED  
4  RECHARGE WELL  DEWATERING

**WATER USE**

1  DOMESTIC 5  COMMERCIAL  
2  STOCK 6  MUNICIPAL  
3  IRRIGATION 7  PUBLIC SUPPLY  
4  INDUSTRIAL 8  COOLING OR AIR CONDITIONING  
 OTHER 9  NOT USED

**METHOD OF CONSTRUCTION**

1  CABLE TOOL 6  BORING  
2  ROTARY (CONVENTIONAL) 7  DIAMOND  
3  ROTARY (REVERSE) 8  JETTING  
4  ROTARY (AIR) 9  DRIVING  
5  AIR PERCUSSION  DIGGING  OTHER

**CONTRACTOR**

NAME OF WELL CONTRACTOR: **Capital Water Supply Ltd.** WELL CONTRACTOR'S LICENCE NUMBER: **1558**

ADDRESS: **Box 490 Stittsville, Ontario K2S 1A6**

NAME OF WELL TECHNICIAN: **J. Moore** WELL TECHNICIAN'S LICENCE NUMBER: **T0096**

SIGNATURE OF TECHNICIAN/CONTRACTOR: [Signature] SUBMISSION DATE: **20 MO 01 YR 93**

**OFFICE USE ONLY**

DATA SOURCE: **1558** CONTRACTOR: **1558** DATE RECEIVED: **MAR 04 1993**

DATE OF INSPECTION: [REDACTED] INSPECTOR: [REDACTED]

REMARKS: [REDACTED]

A 054566

A 054566

**Instructions for Completing Form**

- For use in the Province of Ontario only. This document is a permanent legal document. Please retain for future reference.
- All Sections must be completed in full to avoid delays in processing. Further instructions and explanations are available on the back of this form.
- Questions regarding completing this application can be directed to the Water Well Management Coordinator at 416-235-6203.
- All metre measurements shall be reported to 1/10<sup>th</sup> of a metre.
- Please print clearly in blue or black ink only.

Well Owner's Information and Location of Well Information				Ministry Use Only			
First Name		Last Name		Mailing Address (Street Number/Name, RR, Lot, Concession)			
		TRINITY PRESBYTERIAN CHURCH		110 McCURDY DR.			
County/District/Municipality		Township/City/Town/Village		Province	Postal Code	Telephone Number (include area code)	
OTTAWA CARELTON		OTTAWA		Ontario	K2L2Z6	613-836-1429	
Address of Well Location (County/District/Municipality)				Township	Lot PT	Concession	
OTTAWA CARELTON				WEST CARELTON	116	1	
RR#/Street Number/Name				City/Town/Village		Site/Compartment/Block/Tract etc.	
1817 RICHARDSON SIDE RD.				OTTAWA			
GPS Reading	NAD	Zone	Easting	Northing	Unit Make/Model	Mode of Operation:	
	83	18	425510	5017649	MAGELLAN	<input type="checkbox"/> Undifferentiated <input checked="" type="checkbox"/> Averaged <input type="checkbox"/> Differentiated, specify	

**Log of Overburden and Bedrock Materials (see instructions)**

General Colour	Most common material	Other Materials	General Description	Depth Metres	
				From	To
BROWN	SAND	CLAY, STONES, BOULDERS		0	2.43
GREY	CLAY	SAND, STONES, BOULDERS		2.43	15.84
GREY	LIMESTONE	BROWN LIMESTONE		15.84	46.63

Hole Diameter		
Depth	Metres	Diameter
From	To	Centimetres
0	16.91	24.77
16.91	46.63	15.23

Water Record	
Water found at Metres	Kind of Water
22.8	<input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other: UNTESTED
26.8 m	<input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other: UNTESTED
43.5	<input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other: UNTESTED
After test of well yield, water was	
<input type="checkbox"/> Clear and sediment free <input type="checkbox"/> Other, specify: CLEARING	
Chlorinated	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

Construction Record			
Inside diam centimetres	Material	Wall thickness centimetres	Depth Metres
From			From To
15.87	<input checked="" type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized	0.48	0 + 1.52 16.91
Casing			
<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized			
Screen			
Outside diam	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized	Slot No.	
No Casing or Screen			
<input checked="" type="checkbox"/> Open hole		16.91	46.63

Test of Well Yield				
Pumping test method	Draw Down	Recovery		
SUB. PUMP	Time min	Water Level Metres	Time min	Water Level Metres
Pump intake set at (metres)	Static Level			
43.5	0			
Pumping rate - (litres/min)	1	2.04	1	16.91
36.4				
Duration of pumping	2	3.96	2	15.94
1 hrs + 0 min				
Final water level end of pumping	3	5.27	3	14.96
18.47 metres				
Recommended pump type	4	6.33	4	14.08
<input type="checkbox"/> Shallow <input checked="" type="checkbox"/> Deep				
Recommended pump depth	5	7.31	5	13.16
43.5 metres				
Recommended pump rate	10	10.82	10	9.02
36.4 (litres/min)				
If flowing give rate - (litres/min)	15	12.58	15	6.46
	20	14.38	20	5.51
	25	16.0	25	3.56
If pumping discontinued, give reason.	30	17.03	30	2.62
	40	18.44	40	1.57
	50	18.47	50	1.03
	60	18.47	60	0.88

Plugging and Sealing Record		
Depth set at - Metres	Material and type (bentonite slurry, neat cement slurry) etc.	Volume Placed (cubic metres)
From To		
0 16.91	BENTONITE SLURRY	1.15
Method of Construction		
<input type="checkbox"/> Cable Tool <input type="checkbox"/> Rotary (conventional) <input type="checkbox"/> Rotary (reverse)	<input type="checkbox"/> Rotary (air) <input checked="" type="checkbox"/> Air percussion <input type="checkbox"/> Boring	<input type="checkbox"/> Diamond <input type="checkbox"/> Jetting <input type="checkbox"/> Driving
Water Use		
<input type="checkbox"/> Domestic <input type="checkbox"/> Stock <input type="checkbox"/> Irrigation	<input type="checkbox"/> Industrial <input type="checkbox"/> Commercial <input type="checkbox"/> Municipal	<input checked="" type="checkbox"/> Public Supply <input type="checkbox"/> Not used <input type="checkbox"/> Cooling & air conditioning
Final Status of Well		
<input checked="" type="checkbox"/> Water Supply <input type="checkbox"/> Observation well <input type="checkbox"/> Test Hole	<input type="checkbox"/> Recharge well <input type="checkbox"/> Abandoned, insufficient supply <input type="checkbox"/> Abandoned, poor quality	<input type="checkbox"/> Unfinished <input type="checkbox"/> Dewatering <input type="checkbox"/> Replacement well <input type="checkbox"/> Abandoned, (Other)

Location of Well	
In diagram below show distances of well from road, lot line, and building. Indicate north by arrow.	
Audit No.	Date Well Completed
Z 44855	06 12 19
Was the well owner's information package delivered?	Date Delivered
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	06 12 19

Well Contractor/Technician Information	
Name of Well Contractor	Well Contractor's Licence No.
T. SAUNDERS DRILLING LTD	4879
Business Address (street name, number, city etc.)	
RR#1 BRASIDE ONT. K0A 1G0	
Name of Well Technician (last name, first name)	Well Technician's Licence No.
SAUNDERS TROY	T-517
Signature of Technician/Contractor	Date Submitted
<i>Troy Saunders</i>	07 01 19

Ministry Use Only	
Data Source	Contractor
	4879
Date Received	Date of Inspection
FEB 21 2007	
Remarks	Well Record Number

**OFFICIAL CERTIFICATE OF ANALYSIS : 3966666**

**WORK REQUEST : 100292480**

**Report Date : 2024-07-03**

**Paterson Group**

9 Auriga Dr  
Nepean, Ontario  
K2E 7T9  
Attention : Alex Schopf

Reception Date : 2024-06-26

Project : PM15625

Sampler : NA

PO Number : 60535

Temperature : 6 °C

Analysis	Quantity	External Method
Alkalinity (Water, Automated)	2	Modified from SM 2320 B
Ammonia, Total (Water, Colorimetry)	2	Modified from EPA 350.1
Chloride (Water, IC)	2	Modified from SM 4110 B and C
Colour, Apparent (Water, Spectrophotometry)	2	Modified from SM 2120 C
Conductivity (Water, Automated)	2	Modified from SM 2510 B
DOC (Water, IR)	2	Modified from SM 5310 B
Escherichia coli (DC Plate)	2	Modified from MECP E3407
Fluoride (Water, Auto/ISE)	2	Modified from SM 4500-F A and 4500-F C
Hardness (Water, Calculation Only)	2	SM 2340 B
Ion Balance (Water, Calculation)	2	Modified from SM1030 E
Metals Scan (Water, ICP/MS)	2	Modified from EPA 200.8
Metals Scan (Water, ICP/OES)	2	Modified from SM 3120 B
Nitrate (Water, IC)	2	Modified from SM 4110 B and C
Nitrite (Water, IC)	2	Modified from SM 4110 B and C
pH (25°C) (Water, Automated)	2	Modified from SM 4500-H+ B
Phenols (Water, Colorimetry)	2	Modified from EPA 420.2
Sulphate (Water, IC)	2	Modified from SM 4110 B and C
Sulphide (Water, Colorimetry)	2	Modified from SM 4500-S2 D
Tannin and Lignin (Water, Spec)	2	Modified from SM 5550 B
TDS (Estimated)	2	Modified from SM 2510 A
Total Coliforms (DC Plate)	2	Modified from MECP E3407
Total Kjeldahl Nitrogen (Water, Colorimetry)	2	Modified from EPA 351.2
Turbidity (Water, Turbidimeter)	2	Modified from SM 2130 B
VOCs (Water, GC/MS)	2	Modified from EPA 8260

**Criteria :**

**A :** Ontario Regulation 169/03 (Non-Regulated Drinking Water)

**Sample status upon receipt :**

7802343 7802344

**Compliant**

**Certificate Comments :**

7802344

**Anions MRL increase due to matrix interference. B spike not available due to high native analyte concentration in the mother sample. B results were verified for this sample. DOC analyzed from plastic sample bottle.**

7802343

**Anions MRLs increased due to matrix interferences. B spike not available due to high native analyte concentration in the mother sample. B results were verified for this sample.**

**Notes :**

- All analysis is completed at Eurofins Environment Testing Canada Inc. (Ottawa, Ontario) unless otherwise stated.

- Eurofins Environment Testing Canada Inc. is accredited by CALA, Canadian Association for Laboratory Accreditation to ISO/IEC 17025 for tests which appear on the scope of accreditation. The scope is available at <https://directory.cala.ca/>
- Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only. Guideline or regulatory limits listed on this report are provided for ease of use (informational purposes) only. Eurofins recommends consulting the official guideline or regulation as required. Unless otherwise stated, measurement uncertainty is not taken into account when determining guideline or regulatory exceedances.

<b>Legend :</b>		
RL : Reporting limit	N/A : Not applicable	* : Analysis conducted by external subcontracting
QC : Reference material (QC)	1 : Results in annex	^ : Analysis not accredited

## OFFICIAL CERTIFICATE OF ANALYSIS - EXCEEDENCE SUMMARY

Client : Paterson Group  
Project : PM15625

Reception Date : 2024-06-26

Eurofins Sample No	Client Sample Identification	Analyte	Result	Units	Exceeded Criteria		
					A	B	C
<b>Colour, Apparent (Water, Spectrophotometry)</b>							
7802343	TW1 - GW1	Colour (Apparent)	10	TCU	5		
7802344	TW1 - GW2	Colour (Apparent)	10	TCU	5		
<b>Hardness (Water, Calculation Only)</b>							
7802343	TW1 - GW1	Hardness as CaCO3 (Calculation)	356	mg/L	80-100		
7802344	TW1 - GW2	Hardness as CaCO3 (Calculation)	360	mg/L	80-100		
<b>Metals Scan (Water, ICP/MS)</b>							
7802343	TW1 - GW1	Aluminum	0.43	mg/L	0.1		
7802344	TW1 - GW2	Aluminum	0.34	mg/L	0.1		
7802343	TW1 - GW1	Iron	0.68	mg/L	0.3		
7802344	TW1 - GW2	Iron	0.44	mg/L	0.3		
<b>Sulphide (Water, Colorimetry)</b>							
7802343	TW1 - GW1	Sulphide (S2-)	0.95	mg/L	0.05		
7802344	TW1 - GW2	Sulphide (S2-)	1.16	mg/L	0.05		
<b>TDS (Estimated)</b>							
7802343	TW1 - GW1	TDS (Estimated)^	944	mg/L	500		
7802344	TW1 - GW2	TDS (Estimated)^	959	mg/L	500		
<b>Turbidity (Water, Turbidimeter)</b>							
7802343	TW1 - GW1	Turbidity	11.5	NTU	5		
7802344	TW1 - GW2	Turbidity	7.10	NTU	5		

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

						Eurofins Sample No :		7802343		7802344	
						Matrix :		Drinking water		Drinking water	
						Sampling Date :		2024-06-25		2024-06-25	
						Client Sample Identification :		TW1 - GW1		TW1 - GW2	
Anions			Criteria								
	RL	Unit	A	B	C						
Chloride	0.5	mg/L	250			84.9		86.4			
Nitrate (as Nitrogen)	0.1	mg/L	10.0			<0.5		<0.5			
Nitrite (as Nitrogen)	0.1	mg/L	1.0			<0.5		<0.5			
Sulphate	1	mg/L	500			388		394			

						Eurofins Sample No :		7802343		7802344	
						Matrix :		Drinking water		Drinking water	
						Sampling Date :		2024-06-25		2024-06-25	
						Client Sample Identification :		TW1 - GW1		TW1 - GW2	
Calculations											
	RL	Unit									
Ion Balance (Calculation)^	0.1		1.01		1.02						

						Eurofins Sample No :		7802343		7802344	
						Matrix :		Drinking water		Drinking water	
						Sampling Date :		2024-06-25		2024-06-25	
						Client Sample Identification :		TW1 - GW1		TW1 - GW2	
General Chemistry			Criteria								
	RL	Unit	A	B	C						
Alkalinity (as CaCO3)	5	mg/L	500			225		225			
Colour (Apparent)	2	TCU	5			10		10			
Conductivity @ 25°C	5	µS/cm				1350		1370			
Dissolved Organic Carbon	0.5	mg/L	5			1.3		1.0			
Fluoride	0.1	mg/L	1.5			1.32		1.34			
Hardness as CaCO3 (Calculation)	1	mg/L	80-100			356		360			
pH @ 25°C	1		6.5-8.5			7.97		8.04			
Phenols-4AAP	0.001	mg/L				<0.001		<0.001			
Sulphide (S2-)	0.01	mg/L	0.05			0.95		1.16			
Tannin and Lignin	0.1	mg/L				0.2		0.3			
TDS (Estimated)^	5	mg/L	500			944		959			
Turbidity	0.1	NTU	5			11.5		7.10			

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

		Eurofins Sample No :		7802343	7802344			
		Matrix :		Drinking water	Drinking water			
		Sampling Date :		2024-06-25	2024-06-25			
		Client Sample Identification :		TW1 - GW1	TW1 - GW2			
Metals	RL	Unit	Criteria					
			A	B	C			
<b>Metals Scan (Water, ICP/MS)</b>								
Aluminum	0.01	mg/L	0.1			0.43	0.34	
Antimony	0.0005	mg/L	0.006			<0.0005	<0.0005	
Arsenic	0.001	mg/L	0.01			<0.001	<0.001	
Barium	0.001	mg/L	1			0.191	0.190	
Beryllium	0.0005	mg/L				<0.0005	<0.0005	
Boron	0.01	mg/L	5			0.43	0.44	
Cadmium	0.0001	mg/L	0.005			<0.0001	<0.0001	
Chromium	0.001	mg/L	0.05			0.001	<0.001	
Cobalt	0.0002	mg/L				0.0002	<0.0002	
Copper	0.001	mg/L	1			<0.001	<0.001	
Iron	0.03	mg/L	0.3			0.68	0.44	
Lead	0.001	mg/L	0.01			<0.001	<0.001	
Manganese	0.01	mg/L	0.05			0.02	0.02	
Mercury	0.0001	mg/L	0.001			<0.0001	<0.0001	
Molybdenum	0.005	mg/L				<0.005	<0.005	
Nickel	0.005	mg/L				<0.005	<0.005	
Selenium	0.001	mg/L	0.05			<0.001	<0.001	
Silver	0.0001	mg/L				<0.0001	<0.0001	
Strontium	0.001	mg/L				2.64	2.72	
Thallium	0.0001	mg/L				<0.0001	<0.0001	
Uranium	0.001	mg/L	0.02			<0.001	<0.001	
Vanadium	0.001	mg/L				0.001	<0.001	
Zinc	0.01	mg/L	5			<0.01	<0.01	
<b>Metals Scan (Water, ICP/OES)</b>								
Calcium	1	mg/L				74	75	
Magnesium	1	mg/L				42	42	
Potassium	1	mg/L				6	6	
Sodium	1	mg/L	200			181	186	

		Eurofins Sample No :		7802343	7802344			
		Matrix :		Drinking water	Drinking water			
		Sampling Date :		2024-06-25	2024-06-25			
		Client Sample Identification :		TW1 - GW1	TW1 - GW2			
Microbiology	RL	Unit	Criteria					
			A	B	C			
Escherichia coli (DC)	0	CFU/100mL	0			0	0	
Total Coliforms (DC)	0	CFU/100mL	0			0	0	



## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-06-26

Eurofins Sample No :			<b>7802343</b>	<b>7802344</b>				
Matrix :			Drinking water	Drinking water				
Sampling Date :			2024-06-25	2024-06-25				
Client Sample Identification :			TW1 - GW1	TW1 - GW2				
<b>Nutrients</b>	<b>RL</b>	<b>Unit</b>						
Ammonia (Total, as Nitrogen)	0.02	mg/L	0.259	0.263				
Total Kjeldahl Nitrogen	0.1	mg/L	1.46	0.483				

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26


						Eurofins Sample No :		7802343	7802344			
						Matrix :		Drinking water	Drinking water			
						Sampling Date :		2024-06-25	2024-06-25			
						Client Sample Identification :		TW1 - GW1	TW1 - GW2			
Volatile Organic Compounds			Criteria									
	RL	Unit	A	B	C							
<b>VOCs (Water, GC/MS)</b>												
1,1,1,2-Tetrachloroethane	0.5	ug/L				<0.5	<0.5					
1,1,1-Trichloroethane	0.4	ug/L				<0.4	<0.4					
1,1,2,2-Tetrachloroethane	0.5	ug/L				<0.5	<0.5					
1,1,2-Trichloroethane	0.4	ug/L				<0.4	<0.4					
1,1-Dichloroethane	0.4	ug/L				<0.4	<0.4					
1,1-Dichloroethene	0.4	ug/L	14			<0.4	<0.4					
1,2-Dibromoethane	0.2	ug/L				<0.2	<0.2					
1,2-Dichlorobenzene	0.4	ug/L	200			<0.4	<0.4					
1,2-Dichloroethane	0.2	ug/L	5			<0.2	<0.2					
1,2-Dichloropropane	0.5	ug/L				<0.5	<0.5					
1,3,5-Trimethylbenzene	0.3	ug/L				<0.3	<0.3					
1,3-Dichlorobenzene	0.4	ug/L				<0.4	<0.4					
1,4-Dichlorobenzene	0.4	ug/L	5			<0.4	<0.4					
Acetone	5	ug/L				<5.0	<5.0					
Benzene	0.5	ug/L	1			<0.5	<0.5					
Bromodichloromethane	0.3	ug/L				<0.3	<0.3					
Bromoform	0.4	ug/L				<0.4	<0.4					
Bromomethane	0.5	ug/L				<0.5	<0.5					
Carbon tetrachloride	0.2	ug/L	2			<0.2	<0.2					
Chloroethane	0.2	ug/L				<0.2	<0.2					
Chloroform	0.5	ug/L				<0.5	<0.5					
Chloromethane	0.2	ug/L				<0.2	<0.2					
cis-1,2-Dichloroethene	0.4	ug/L				<0.4	<0.4					
cis-1,3-Dichloropropene	0.2	ug/L				<0.2	<0.2					
Dibromochloromethane	0.3	ug/L				<0.3	<0.3					
Dichloromethane	4	ug/L	50			<4.0	<4.0					
Diethyl ether	5	ug/L				<5	<5					
Ethylbenzene	0.5	ug/L	140			<0.5	<0.5					
m/p-Xylene	0.4	ug/L				<0.4	<0.4					
Methyl ethyl ketone (MEK)	2	ug/L				<2.0	<2.0					
Methyl isobutyl ketone (MIBK)	5	ug/L				<5.0	<5.0					
Methyl tert-butyl ether (MTBE)	2	ug/L				<2	<2					
Monochlorobenzene	0.5	ug/L	80			<0.5	<0.5					
o-Xylene	0.4	ug/L				<0.4	<0.4					
Styrene	0.5	ug/L				<0.5	<0.5					
Tetrachloroethylene (PCE)	0.3	ug/L	10			<0.3	<0.3					
Toluene	0.4	ug/L	60			<0.4	<0.4					
trans-1,2-dichloroethene	0.4	ug/L				<0.4	<0.4					
trans-1,3-dichloropropene	0.2	ug/L				<0.2	<0.2					
Trichloroethylene (TCE)	0.3	ug/L	5			<0.3	<0.3					
Trichlorofluoromethane	0.5	ug/L				<0.5	<0.5					

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

						Eurofins Sample No :		7802343		7802344					
						Matrix :		Drinking water		Drinking water					
						Sampling Date :		2024-06-25		2024-06-25					
						Client Sample Identification :		TW1 - GW1		TW1 - GW2					
Volatile Organic Compounds			Criteria												
	RL	Unit	A	B	C										
Vinyl chloride	0.2	ug/L	1			<0.2		<0.2							
Xylene (Total)	0.5	ug/L	90			<0.5		<0.5							
1,2-dichloroethane-d4 (surrogate)	0	%				122		109							
4-bromofluorobenzene (surrogate)	0	%				71		72							
Toluene-d8 (surrogate)	0	%				110		113							

Approved by :   
Emma-Dawn Ferguson, M.Sc.  
Environmental Chemist

Approved by :   
Jason Kennedy,  
Project Manager

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Alkalinity (Water, Automated)</b>									
<i>Method : Alkalinity (water, titration to pH 4.5, automated). Internal method: OTT-I-AT-WI45398.</i>									
Alkalinity (as CaCO <sub>3</sub> )	mg/L	5	<5	100	95-105			-	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	
<b>Ammonia, Total (Water, Colorimetry)</b>									
<i>Method : Ammonia (Water, Colorimetry). Internal method: OTT-I-NUT-WI46201.</i>									
Ammonia (Total, as Nitrogen)	mg/L	0.02	<0.020	104	80-120	112	80-120	3	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-27	
<b>Chloride (Water, IC)</b>									
<i>Method : Anions (Water, Ion Chromatography). Internal method: OTT-I-IC-WI45985.</i>									
Chloride	mg/L	0.5	<0.5	96	80-120	101	80-120	-	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	
<b>Colour, Apparent (Water, Spectrophotometry)</b>									
<i>Method : Colour (Water, Spectrophotometric). Internal method: OTT-I-SPEC-WI45980.</i>									
Colour (Apparent)	TCU	2	<2	110	39-159			2	0-40
Associated Samples : 7802343, 7802344								Prep Date: 2024-07-03 Analysis Date: 2024-07-03	
<b>Conductivity (Water, Automated)</b>									
<i>Method : Conductivity (Water, Autotitrator). Internal Method: OTT-I-AT-WI45398.</i>									
Conductivity @ 25°C	uS/cm	5	<5	98	98-102			2	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	
<b>DOC (Water, IR)</b>									
<i>Method : Organic carbon (water, IR, combustion). Internal method: OTT-I-DEM-WI46148.</i>									
Dissolved Organic Carbon	mg/L	0.5	<0.5	89	84-116	99	80-120	-	0-15
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	
<b>Escherichia coli (DC Plate)</b>									
<i>Method : Total Coliforms and E.Coli by MF (Water, DC plate). Internal method: OTT-M-BAC-WI45296.</i>									
Escherichia coli (DC)	CFU/100mL	0	0					-	0-30
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-26 Analysis Date: 2024-06-27	
<b>Fluoride (Water, Auto/ISE)</b>									
<i>Method : Fluoride by autotitrator, ion selective electrode. Internal method: OTT-I-AT-WI45398.</i>									
Fluoride	mg/L	0.1	<0.10	100	90-110				
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-06-26

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Metals Scan (Water, ICP/MS)</b>									
<i>Method : Metals (Water, ICP/MS). Internal method: AMMTFQE1.</i>									
Aluminum	mg/L	0.01	<0.01	100	80-120	-	70-130	-	0-20
Antimony	mg/L	0.0005	<0.0005	89	80-120	95	70-130	-	0-20
Arsenic	mg/L	0.001	<0.001	100	80-120	100	70-130	-	0-20
Barium	mg/L	0.001	<0.001	100	80-120	-	70-130	-	0-20
Beryllium	mg/L	0.0005	<0.0005	112	80-120	113	70-130	-	0-20
Boron	mg/L	0.01	<0.01	110	80-120	119	70-130	-	0-20
Cadmium	mg/L	0.0001	<0.0001	103	80-120	-	70-130	-	0-20
Chromium	mg/L	0.001	<0.001	110	80-120	-	70-130	-	0-20
Cobalt	mg/L	0.0002	<0.0002	105	80-120	-	70-130	-	0-20
Copper	mg/L	0.001	<0.001	110	80-120	-	70-130	-	0-20
Iron	mg/L	0.03	<0.03	90	80-120	101	70-130	-	0-20
Lead	mg/L	0.001	<0.001	100	80-120	-	70-130	-	0-20
Manganese	mg/L	0.01	<0.01	100	80-120	-	70-130	-	0-20
Mercury	mg/L	0.0001	<0.0001	110	80-120	-	70-130	-	0-20
Molybdenum	mg/L	0.005	<0.005	100	80-120	95	70-130	-	0-20
Nickel	mg/L	0.005	<0.005	110	80-120	-	70-130	-	0-20
Selenium	mg/L	0.001	<0.001	105	80-120	114	70-130	-	0-20
Silver	mg/L	0.0001	<0.0001	113	80-120	-	70-130	-	0-20
Strontium	mg/L	0.001	<0.001	100	80-120	-	70-130	-	0-20
Thallium	mg/L	0.0001	<0.0001	99	80-120	-	70-130	-	0-20
Uranium	mg/L	0.001	<0.001	90	80-120	90	70-130	-	0-20
Vanadium	mg/L	0.001	<0.001	100	80-120	-	70-130	-	0-20
Zinc	mg/L	0.01	<0.01	110	80-120	-	70-130	-	0-20

Associated Samples : 7802343

Prep Date: 2024-07-02  
 Analysis Date: 2024-07-03

<i>Method : Metals (Water, ICP/MS). Internal method: AMMTFQE1.</i>									
Aluminum	mg/L	0.01	<0.01	100	80-120	117	70-130	8	0-20
Antimony	mg/L	0.0005	<0.0005	89	80-120	-	70-130	-	0-20
Arsenic	mg/L	0.001	<0.001	100	80-120	104	70-130	-	0-20
Barium	mg/L	0.001	<0.001	100	80-120	83	70-130	1	0-20
Beryllium	mg/L	0.0005	<0.0005	112	80-120	-	70-130	-	0-20
Boron	mg/L	0.01	<0.01	110	80-120	-	-	1	0-20
Cadmium	mg/L	0.0001	<0.0001	103	80-120	-	70-130	-	0-20
Chromium	mg/L	0.001	<0.001	110	80-120	99	70-130	-	0-20
Cobalt	mg/L	0.0002	<0.0002	105	80-120	103	70-130	-	0-20
Copper	mg/L	0.001	<0.001	110	80-120	93	70-130	-	0-20
Iron	mg/L	0.03	<0.03	90	80-120	100	70-130	4	0-20
Lead	mg/L	0.001	<0.001	100	80-120	89	70-130	-	0-20
Manganese	mg/L	0.01	<0.01	100	80-120	103	70-130	-	0-20
Mercury	mg/L	0.0001	<0.0001	110	80-120	103	70-130	-	0-20
Molybdenum	mg/L	0.005	<0.005	100	80-120	109	70-130	-	0-20
Nickel	mg/L	0.005	<0.005	110	80-120	101	70-130	-	0-20
Selenium	mg/L	0.001	<0.001	105	80-120	-	70-130	-	0-20
Silver	mg/L	0.0001	<0.0001	113	80-120	-	70-130	-	0-20
Strontium	mg/L	0.001	<0.001	100	80-120	73	70-130	1	0-20
Thallium	mg/L	0.0001	<0.0001	99	80-120	-	70-130	-	0-20
Uranium	mg/L	0.001	<0.001	90	80-120	94	70-130	-	0-20

# Environment Testing

146 Colonnade Rd, Unit 8, Ottawa, ON K2E 7Y1 (613) 727-5692

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Metals Scan (Water, ICP/MS)</b>									
<i>Method : Metals (Water, ICP/MS). Internal method: AMMTFQE1.</i>									
Vanadium	mg/L	0.001	<0.001	100	80-120	100	70-130	-	0-20
Zinc	mg/L	0.01	<0.01	110	80-120	-	70-130	-	0-20
Associated Samples : 7802344								Prep Date: 2024-07-02 Analysis Date: 2024-07-03	
<b>Metals Scan (Water, ICP/OES)</b>									
<i>Method : Metals (Water, ICP/OES). Internal method: OTT-I-MET-WI48491.</i>									
Calcium	mg/L	1	<1	107	86-115	100	70-130	0	0-20
Magnesium	mg/L	1	<1	105	91-109	104	70-130	0	0-20
Potassium	mg/L	1	<1	106	87-113	116	70-130	-	0-20
Sodium	mg/L	1	<1	104	85-115	108	70-130	0	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-07-02 Analysis Date: 2024-06-26	
<b>Nitrate (Water, IC)</b>									
<i>Method : Anions (Water, Ion Chromatography). Internal method: OTT-I-IC-WI45985.</i>									
Nitrate (as Nitrogen)	mg/L	0.1	<0.1	97	80-120	101	80-120		
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	
<b>Nitrite (Water, IC)</b>									
<i>Method : Anions (Water, Ion Chromatography). Internal method: OTT-I-IC-WI45985.</i>									
Nitrite (as Nitrogen)	mg/L	0.1	<0.1	93	80-120	100	80-120		
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	
<b>pH (25°C) (Water, Automated)</b>									
<i>Method : pH (Water, Automated Meter). Internal method: OTT-I-AT-WI45398.</i>									
pH @ 25°C		1	5.78	100	97-103			0	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	
<b>Phenols (Water, Colorimetry)</b>									
<i>Method : Phenols (Water, Colorimetry). Internal method: OTT-I-4AAP-WI46150.</i>									
Phenols-4AAP	mg/L	0.001	<0.001	114	75-125	111	70-130	-	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-28 Analysis Date: 2024-07-02	
<b>Sulphate (Water, IC)</b>									
<i>Method : Anions (Water, Ion Chromatography). Internal method: OTT-I-IC-WI45985.</i>									
Sulphate	mg/L	1	<1	95	90-110	95	80-120		
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	
<b>Sulphide (Water, Colorimetry)</b>									
<i>Method : Sulphide, S2- (Water, Colorimetry). Internal method: OTT-I-SPEC-WI45931.</i>									
Sulphide (S2-)	mg/L	0.01	<0.01	96	80-120			-	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-07-02 Analysis Date: 2024-07-02	
<b>Tannin and Lignin (Water, Spec)</b>									
<i>Method : Tannin and Lignin (Water, Spec), Internal method: OTT-I-SPEC-WI57693.</i>									
Tannin and Lignin	mg/L	0.1	<0.1	96	80-120			-	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	

# Environment Testing

146 Colonnade Rd, Unit 8, Ottawa, ON K2E 7Y1 (613) 727-5692

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-06-26

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Total Coliforms (DC Plate)</b>									
<i>Method : Total Coliforms and E.Coli by MF (Water, DC plate). Internal method: OTT-M-BAC-WI45296.</i>									
Total Coliforms (DC)	CFU/100mL	0	0					-	0-30
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-26 Analysis Date: 2024-06-27	
<b>Total Kjeldahl Nitrogen (Water, Colorimetry)</b>									
<i>Method : TKN (Water, colorimetry). Internal method: OTT-I-NUT-WI46201.</i>									
Total Kjeldahl Nitrogen	mg/L	0.1	<0.100	95	70-130	102	70-130	1	0-20
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	
<b>Turbidity (Water, Turbidimeter)</b>									
<i>Method : Turbidity (Water, Turbidimeter). Internal method: OTT-I-TUR-WI46288.</i>									
Turbidity	NTU	0.1	<0.1	100	80-120			2	0-30
Associated Samples : 7802343, 7802344								Prep Date: 2024-06-27 Analysis Date: 2024-06-28	



## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
Project : PM15625

Reception Date: 2024-06-26

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>VOCs (Water, GC/MS)</b>									
<i>Method : Volatile Organic Compounds (Water, GC/MS). Internal method: AMVOMSE8.</i>									
1,1,1,2-Tetrachloroethane	ug/L	0.5	<0.5	109	70-130	91	70-130	-	0-30
1,1,1-Trichloroethane	ug/L	0.4	<0.4	92	70-130	114	70-130	-	0-30
1,1,2,2-Tetrachloroethane	ug/L	0.5	<0.5	119	70-130	86	70-130	-	0-30
1,1,2-Trichloroethane	ug/L	0.4	<0.4	118	70-130	104	70-130	-	0-30
1,1-Dichloroethane	ug/L	0.4	<0.4	97	70-130	110	70-130	-	0-30
1,1-Dichloroethene	ug/L	0.4	<0.4	99	70-130	113	70-130	-	0-30
1,2-Dibromoethane	ug/L	0.2	<0.2	96	70-130	108	70-130	-	0-30
1,2-Dichlorobenzene	ug/L	0.4	<0.4	111	70-130	87	70-130	-	0-30
1,2-Dichloroethane	ug/L	0.2	<0.2	106	70-130	100	70-130	-	0-30
1,2-Dichloropropane	ug/L	0.5	<0.5	100	70-130	94	70-130	-	0-30
1,3,5-Trimethylbenzene	ug/L	0.3	<0.3	111	70-130	103	70-130	-	0-30
1,3-Dichlorobenzene	ug/L	0.4	<0.4	110	70-130	104	70-130	-	0-30
1,4-Dichlorobenzene	ug/L	0.4	<0.4	110	70-130	107	70-130	-	0-30
Acetone	ug/L	5	<5.0	74	70-130	114	70-130	-	0-30
Benzene	ug/L	0.5	<0.5	97	70-130	107	70-130	-	0-30
Bromodichloromethane	ug/L	0.3	<0.3	96	70-130	106	70-130	-	0-30
Bromoform	ug/L	0.4	<0.4	96	70-130	106	70-130	-	0-30
Bromomethane	ug/L	0.5	<0.5	104	70-130	83	70-130	-	0-30
Carbon tetrachloride	ug/L	0.2	<0.2	97	70-130	105	70-130	-	0-30
Chloroethane	ug/L	0.2	<0.2	100	70-130	97	70-130	-	0-30
Chloroform	ug/L	0.5	<0.5	83	70-130	91	70-130	-	0-30
Chloromethane	ug/L	0.2	<0.2	83	70-130	91	70-130	-	0-30
cis-1,2-Dichloroethene	ug/L	0.4	<0.4	97	70-130	105	70-130	-	0-30
cis-1,3-Dichloropropene	ug/L	0.2	<0.2	79	70-130	119	70-130	-	0-30
Dibromochloromethane	ug/L	0.3	<0.3	95	70-130	100	70-130	-	0-30
Dichloromethane	ug/L	4	<4.0	90	70-130	91	70-130	-	0-30
Diethyl ether	ug/L	5	<5	100	70-130	100	70-130	-	0-30
Ethylbenzene	ug/L	0.5	<0.5	117	70-130	117	70-130	-	0-30
m/p-Xylene	ug/L	0.4	<0.4	94	70-130	98	70-130	-	0-30
Methyl ethyl ketone (MEK)	ug/L	2	<2.0	74	70-130	93	70-130	-	0-30
Methyl isobutyl ketone (MIBK)	ug/L	5	<5.0	90	70-130	119	70-130	-	0-30
Methyl tert-butyl ether (MTBE)	ug/L	2	<2	90	70-130	90	70-130	-	0-30
Monochlorobenzene	ug/L	0.5	<0.5	104	70-130	100	70-130	-	0-30
o-Xylene	ug/L	0.4	<0.4	117	70-130	96	70-130	-	0-30
Styrene	ug/L	0.5	<0.5	107	70-130	100	70-130	-	0-30
Tetrachloroethylene (PCE)	ug/L	0.3	<0.3	95	70-130	112	70-130	-	0-30
Toluene	ug/L	0.4	<0.4	109	70-130	92	70-130	-	0-30
trans-1,2-dichloroethene	ug/L	0.4	<0.4	90	70-130	104	70-130	-	0-30
trans-1,3-dichloropropene	ug/L	0.2	<0.2	83	70-130	113	70-130	-	0-30
Trichloroethylene (TCE)	ug/L	0.3	<0.3	102	70-130	104	70-130	-	0-30
Trichlorofluoromethane	ug/L	0.5	<0.5	97	70-130	117	70-130	-	0-30
Vinyl chloride	ug/L	0.2	<0.2	83	70-130	117	70-130	-	0-30
Xylene (Total)	ug/L	0.5	<0.5					-	-

Associated Samples : 7802343, 7802344

Prep Date: 2024-07-02  
Analysis Date: 2024-07-03

Where RPD % is reported as "-" the calculation is not available because one or both of the duplicates is within 5 times the RL.

100292480

FORMATION: YES  NO

**CLIENT INFORMATION**

Company: Paterson Group  
 Contact: Alex Schopf  
 Address: 9 Auriga Drive  
 Telephone: 613-218-3444 Cell: \_\_\_\_\_

**INVOICE INFO**

Company: \_\_\_\_\_  
 Contact: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Telephone: \_\_\_\_\_



Printed On: 2024-06-26 17:07:06

PO #: 60535

Email: #1: eardley@patersongroup.ca, mlaflamme@patersongroup.ca  
 Email: #2: aschopi@patersongroup.ca;  
 Project: PM15625 Quote #: \_\_\_\_\_

**TURN-AROUND TIME (Business Days)**

1 Day\* (100%)  2 Day\*\* (50%)  3-5 Days (25%)  5-7 Days (Standard)

Please contact Lab in advance to determine rush availability.  
 \*For results reported after rush due date, surcharges will apply: before 12:00 - 100%, after 12:00 - 50%.  
 \*\*For results reported after rush due date, surcharges will apply: before 12:00 - 50%, after 12:00 - 25%.

**REGULATION/GUIDELINE REQUIRED**

Sanitary Sewer, City: Ottawa  
 Storm Sewer, City: Ottawa  
 ODWSOG  
 PWQO  
 O. Reg 347/558  
 Other: \_\_\_\_\_  
 None

O. Reg 153  
 Table # \_\_\_\_\_ Course / Fine, Surface / subsurface.  
 Type: Com-Ind / Res-Park / Agri / GW / All Other / Sediment  
 Excess Soil, Table: \_\_\_\_\_ Type: \_\_\_\_\_

The sample results from this submission will form part of a formal Record of Site Condition (RSC) under O.Reg. 153/04  
 Yes  No

The optimal temperature conditions during transport should be less than 10°C. Sample(s) cannot be frozen, unless otherwise indicated or agreed upon with the Laboratory. Note that this COC is not to be used for drinking water samples. The COC must be complete upon submission of the samples, there will be a \$25 surcharge if required information is missing (required fields are shaded in grey).

Sample Details		Sample Analysis Required												RN# (Lab Use Only)					
Field Filtered →		O.Reg.153 parameters								See attached paper	Subdivision Supply Batch 2 (E/C TC only)	TSS	pH		Total Metals	Hg			
Sample Matrix	# of Containers	PHC F4 - F4	BTEX	VOCs	PAHs	PCBs	Metals + Inorganics	Metals only											
TW1-GW1	June 25, 2024	GW	10	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7802343
TW1-GW2	June 25, 2024	GW	10	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	44
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

**PRINT**

Sampled By: Alex Schopf  
 Relinquished By: Alex Schopf  
 Received By: \_\_\_\_\_

**SIGN**

DATE/TIME

June 25, 2024  
 June 26, 2024

TEMP (°C)  
 6.2

**COMMENTS:**

Total and Trace Metals

CUSTODY SEAL:  YES  NO Ice packs submitted:  Yes  No

**OFFICIAL CERTIFICATE OF ANALYSIS : 3991228**

**WORK REQUEST : 100298583**

**Report Date : 2024-07-22**

**Paterson Group**  
 9 Auriga Dr  
 Nepean, Ontario  
 K2E 7T9  
 Attention : Alex Schopf

Reception Date : 2024-07-19  
 Project : PM15625  
 Sampler : NA  
 PO Number : 60753  
 Temperature : 14 °C

Analysis	Quantity	External Method
Colour, Apparent (Water, Spectrophotometry)	1	Modified from SM 2120 C
Turbidity (Water, Turbidimeter)	1	Modified from SM 2130 B

**Criteria :**

**A :** Ontario Regulation 169/03 (Non-Regulated Drinking Water)

**Sample status upon receipt :**

7872590

**Compliant**

**Notes :**

- All analysis is completed at Eurofins Environment Testing Canada Inc. (Ottawa, Ontario) unless otherwise stated.
- Eurofins Environment Testing Canada Inc. is accredited by CALA, Canadian Association for Laboratory Accreditation to ISO/IEC 17025 for tests which appear on the scope of accreditation. The scope is available at <https://directory.cala.ca/>
- Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only. Guideline or regulatory limits listed on this report are provided for ease of use (informational purposes) only. Eurofins recommends consulting the official guideline or regulation as required. Unless otherwise stated, measurement uncertainty is not taken into account when determining guideline or regulatory exceedances.

**Legend :**

RL : Reporting limit  
 QC : Reference material (QC)  
 N/A : Not applicable  
 1 : Results in annex  
 \* : Analysis conducted by external subcontracting  
 ^ : Analysis not accredited

## OFFICIAL CERTIFICATE OF ANALYSIS - EXCEEDENCE SUMMARY

Client : Paterson Group  
 Project : PM15625

Reception Date : 2024-07-19

Eurofins Sample No	Client Sample Identification	Analyte	Result	Units	Exceeded Criteria		
					A	B	C
<b>Colour, Apparent (Water, Spectrophotometry)</b>							
7872590	TW1 - GW - 3	Colour (Apparent)	12	TCU	5		

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-07-19

			Eurofins Sample No :			<b>7872590</b>				
			Matrix :			Groundwater				
			Sampling Date :			2024-07-19				
			Client Sample Identification :			TW1 - GW - 3				
<b>General Chemistry</b>	<b>RL</b>	<b>Unit</b>	<b>Criteria</b>							
			<b>A</b>	<b>B</b>	<b>C</b>					
Colour (Apparent)	2	TCU	5			12				
Turbidity	0.1	NTU	5			3.29				

Approved by :   
 Emma-Dawn Ferguson, M.Sc.  
 Environmental Chemist

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-07-19

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Colour, Apparent (Water, Spectrophotometry)</b>									
<i>Method : Colour (Water, Spectrophotometric). Internal method: OTT-I-SPEC-WI45980.</i>									
Colour (Apparent)	TCU	2	<2	102	39-159			-	0-40
Associated Samples : 7872590								Prep Date: 2024-07-22 Analysis Date: 2024-07-22	
<b>Turbidity (Water, Turbidimeter)</b>									
<i>Method : Turbidity (Water, Turbidimeter). Internal method: OTT-I-TUR-WI46288.</i>									
Turbidity	NTU	0.1	<0.1	102	80-120			2	0-30
Associated Samples : 7872590								Prep Date: 2024-07-20 Analysis Date: 2024-07-20	

Where RPD % is reported as "-" the calculation is not available because one or both of the duplicates is within 5 times the RL.

CLIENT INFORMATION

INVOICE INFORMATION

100298583

IN: YES  NO

Company: Paterson Group

Contact: Alex Schopf

Address: 9 Auriga Drive

Telephone: 613-218-3444 Cell: \_\_\_\_\_

Email: #1: leardley@patersongroup.ca, mkillam@patersongroup.ca

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Address: \_\_\_\_\_

Telephone: \_\_\_\_\_

PO #: 60753



Printed On: 2024-07-19 17:13:38

Email: #2: aschopf@patersongroup.ca;

Project: PM15625 Quote #: \_\_\_\_\_

REGULATION/GUIDELINE REQUIRED

Sanitary Sewer, City: Ottawa \_\_\_\_\_

Storm Sewer, City: Ottawa \_\_\_\_\_

ODWSOG

PWQO

O. Reg 347/558

Other: \_\_\_\_\_

None

O. Reg 153

Table # \_\_\_\_\_, Course / Fine, Surface / subsurface.

Type: Com-Ind / Res-Park / Agri / GW / All Other / Sediment

Excess Soil, Table: \_\_\_\_\_ Type: \_\_\_\_\_

The sample results from this submission will form part of a formal Record of Site Condition (RSC) under O.Reg. 153/04

Yes  No

TURN-AROUND TIME (Business Days)

1 Day\* (100%)  2 Day\*\* (50%)  3-5 Days (25%)  5-7 Days (Standard)

Please contact Lab in advance to determine rush availability. \*For results reported after rush due date, surcharges will apply: before 12:00 - 100%, after 12:00 - 50%.

\*\*For results reported after rush due date, surcharges will apply: before 12:00 - 50%, after 12:00 - 25%.

The optimal temperature conditions during transport should be less than 10°C. Sample(s) cannot be frozen, unless otherwise indicated or agreed upon with the Laboratory. Note that this COC is not to be used for drinking water samples. The COC must be complete upon submission of the samples, there will be a \$25 surcharge if required information is missing (required fields are shaded in grey).

Sample Details

Sample Analysis Required

Sample ID	Date/Time Collected	Sample Matrix	# of Containers	PHC F1 - F4	BTEX	VOCs	PAHs	PCBs	Metals + Inorganics	Metals only	See attached paper	Subdivision Supply Batch 2 (Ec/TC only)	TSS	pH	Total Metals	Hg	Turbidity	Colour	Aluminum
TW1 - GW - 3	July 19, 2024	GW	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Sample Details				Sample Analysis Required																RN# (Lab Use Only)
Field Filtered -->				O.Reg.153 parameters																

RN# (Lab Use Only)

7872590

PRINT

Sampled By: Alex Schopf

Relinquished By: Alex Schopf

Received By: \_\_\_\_\_

SIGN

*Alex Schopf*

*Alex Schopf*

DATE/TIME

July 19, 2024

July 19, 2024

July 19/24

TEMP (°C)

14

COMMENTS:

CUSTODY SEAL:  YES  NO Ice packs submitted:  Yes  No



**OFFICIAL CERTIFICATE OF ANALYSIS : 3993095**

**WORK REQUEST : 100298584**

**Report Date : 2024-07-24**

**Paterson Group**  
9 Auriga Dr  
Nepean, Ontario  
K2E 7T9  
Attention : Alex Schopf

Reception Date : 2024-07-19  
Project : PM15625  
Sampler : NA  
PO Number : 60753  
Temperature : 14 °C

Analysis	Quantity	External Method
Metals Scan (Water, ICP/MS)	1	Modified from EPA 200.8

**Criteria :**

A : Ontario Regulation 169/03 (Non-Regulated Drinking Water)

**Sample status upon receipt :**

7872596

**Compliant**

**Notes :**

- All analysis is completed at Eurofins Environment Testing Canada Inc. (Ottawa, Ontario) unless otherwise stated.
- Eurofins Environment Testing Canada Inc. is accredited by CALA, Canadian Association for Laboratory Accreditation to ISO/IEC 17025 for tests which appear on the scope of accreditation. The scope is available at <https://directory.cala.ca/>
- Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only. Guideline or regulatory limits listed on this report are provided for ease of use (informational purposes) only. Eurofins recommends consulting the official guideline or regulation as required. Unless otherwise stated, measurement uncertainty is not taken into account when determining guideline or regulatory exceedances.

**Legend :**

RL : Reporting limit  
QC : Reference material (QC)

N/A : Not applicable  
1 : Results in annex

\* : Analysis conducted by external subcontracting  
^ : Analysis not accredited

## OFFICIAL CERTIFICATE OF ANALYSIS - RESULTS

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-07-19

			Eurofins Sample No :			7872596					
			Matrix :			Groundwater					
			Sampling Date :			2024-07-19					
			Client Sample Identification :			TW1 - GW - 3					
Metals	RL	Unit	Criteria			0.02					
			A	B	C						
Aluminum	0.01	mg/L	0.1								

Approved by :   
 Emma-Dawn Ferguson, M.Sc.  
 Environmental Chemist

# Environment Testing

146 Colonnade Rd, Unit 8, Ottawa, ON K2E 7Y1 (613) 727-5692

## OFFICIAL CERTIFICATE OF ANALYSIS - QUALITY CONTROL

Client : Paterson Group  
 Project : PM15625

Reception Date: 2024-07-19

Parameter	Unit	RL	Blank	QC		Matrix Spike		Duplicate	
				Recovery %	Range %	Recovery %	Range %	RPD %	Range %
<b>Metals Scan (Water, ICP/MS)</b>									
<i>Method : Metals (Water, ICP/MS). Internal method: AMMTFQE1.</i>									
Aluminum	mg/L	0.01	<0.01	100	80-120	106	70-130	0	0-20
Associated Samples : 7872596								Prep Date: 2024-07-21 Analysis Date: 2024-07-23	

Where RPD % is reported as "-" the calculation is not available because one or both of the duplicates is within 5 times the RL.

CLIENT INFORMATION

INVOICE INFORMATION (\$)

100298584

YES  NO

Company: Paterson Group  
 Contact: Alex Schopf  
 Address: 9 Auriga Drive  
 Telephone: 613-218-3444  
 Cell: \_\_\_\_\_  
 Email: #1: heardley@patersongroup.ca, mkillam@patersongroup.ca

Company: \_\_\_\_\_  
 Contact: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Telephone: \_\_\_\_\_  
 PO #: 60753



Printed On: 2024-07-19 17:15:49

Email: #2: aschopf@patersongroup.ca;  
 Project: PM15625 Quote #: \_\_\_\_\_  
**TURN-AROUND TIME (Business Days)**  
 1 Day\* (100%)  2 Day\*\* (50%)  3-5 Days (25%)  5-7 Days (Standard)  
 Please contact Lab in advance to determine rush availability.  
 \*For results reported after rush due date, surcharges will apply: before 12:00 - 100%, after 12:00 - 50%.  
 \*\*For results reported after rush due date, surcharges will apply: before 12:00 - 50%, after 12:00 - 25%.

REGULATION/GUIDELINE REQUIRED

Sanitary Sewer, City: Ottawa  
 Storm Sewer, City: Ottawa  
 ODWSOG  
 PWQO  
 O. Reg 347/558  
 Other: \_\_\_\_\_  
 None

O. Reg 153  
 Table # \_\_\_\_\_, Course / Fine, Surface / subsurface.  
 Type: Com-Ind / Res-Park / Agri / GW / All Other / Sediment  
 Excess Soil, Table: \_\_\_\_\_ Type: \_\_\_\_\_  
 The sample results from this submission will form part of a formal Record of Site Condition (RSC) under O.Reg. 153/04  
 Yes  No


The optimal temperature conditions during transport should be less than 10°C. Sample(s) cannot be frozen, unless otherwise indicated or agreed upon with the Laboratory. Note that this COC is not to be used for drinking water samples. The COC must be complete upon submission of the samples, there will be a \$25 surcharge if required information is missing (required fields are shaded in grey).

Sample ID	Date/Time Collected	Sample Details		Sample Analysis Required														RN# (Lab Use Only)					
		Sample Matrix	# of Containers	O.Reg.153 parameters										See attached paper	Subdivision Supply Batch 2 (Eo/TC only)	TSS	pH		Total Metals	Hg	Turbidity	Colour	Aluminum
				PHCEI - F4	BTEX	VOCs	PAHs	PCBs	Metals + Inorganics	Metals only													
TW1 - GW - 3	July 19, 2024	GW	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	7872596	
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		

PRINT	SIGN	DATE/TIME	TEMP (°C)	COMMENTS:
Sampled By: Alex Schopf		July 19, 2024		
Relinquished By: Alex Schopf		July 19, 2024		
Received By:		July 19, 2024	14	CUSTODY SEAL: <input type="checkbox"/> YES <input type="checkbox"/> NO Ice packs submitted: <input type="checkbox"/> Yes <input type="checkbox"/> No


**Pumping Test Analysis Report**

File No.	PM15625	Well ID:	TW1
Date:	Tuesday, June 25, 2024	Solution Method:	<b>Theis</b>
Client:	Ken Hoppner	Transmissivity (m <sup>2</sup> /day):	1.7
Site Address:	1811 Richardson Side Road	Discharge Rate (L/min)	30
Project:	Re-zoning Application	Analysis performed by:	AS



**Pumping Test Analysis Report**

File No.	PM15625	Well ID:	TW1
Date:	Tuesday, June 25, 2024	Solution Method:	<b>Cooper-Jacob</b>
Client:	Ken Hoppner	Transmissivity (m <sup>2</sup> /day):	1.65
Site Address:	1811 Richardson Side Road	Discharge Rate (L/min)	30
Project:	Re-zoning Application	Analysis performed by:	AS



**Pumping Test Analysis Report**

File No. PM15625  
Date: Tuesday, June 25, 2024  
Client: Ken Hoppner  
Site Address: 1811 Richardson Side Road  
Project: Re-zoning Application

Summary Table:		
Solution Method:	Well ID:	Transmissivity (m <sup>2</sup> /day):
Theis	TW1	1.7
Cooper-Jacob	TW1	1.65
Average:		<b>1.68</b>



## PREDICTIVE NITRATE IMPACT ASSESSEMENT

### Infiltration Factors

Topography	0.10
Soil	0.20
Cover	0.15
<b>Total</b>	<b>0.45</b>

### Site Characteristics

Area of Site :	116782	m <sup>2</sup>
Total of roof areas:	2500	m <sup>2</sup>
Total area of paved driveway areas:	6215	m <sup>2</sup>
Roof + paved driveway areas	8715	m <sup>2</sup>
Impervious Area	8715	m <sup>2</sup>
Percent Impervious Area =	7	%
Infiltration Area =	108067	m <sup>2</sup>

### Septic Effluent

Concentration of Effluent (Cs) =	40	mg/L
----------------------------------	----	------

### Infiltration Calculation

Nitrate concentration in precipitation (C <sub>i</sub> ) =	0	mg/L
Surplus Water (Environment Canada)	329	mm/yr
Factored Water Surplus =	148	mm/yr
Infiltration % due to stormwater management measures	-	%
Infiltration rate from stormwater management measures =	0	mm/yr
Infiltration Flow Entering the System (Q <sub>i</sub> ) =	44	m <sup>3</sup> /day

### Mass Balance Model (MOEE, 1995)

$$C_T = (Q_b C_b + Q_e C_e + Q_i C_i) / (Q_b + Q_e + Q_i) = \text{Cumulative Nitrate Concentration}$$

Q <sub>b</sub> = flow entering the system across the upgradient area	0	m <sup>3</sup> /day
C <sub>b</sub> = background nitrate concentration	0	mg/L
C <sub>s</sub> = concentration of nitrates in the septic effluent	40	mg/L
Q <sub>i</sub> = flow entering the system from infiltration	44	m <sup>3</sup> /day
C <sub>i</sub> = Concentration of nitrates in the infiltrate	0	mg/L
<b>C<sub>T</sub> =</b>	<b>10.00</b>	<b>mg/L</b>

### Maximum Allowable Sewage Flow Volume

Daily Sewage Flow (Q <sub>s</sub> )=	14.61122351	m <sup>3</sup>
--------------------------------------	-------------	----------------

*Notes: Site characteristic values were measured as approximate values from the available site plans and GeoOttawa.*

MW1 inputs			
pH	8	A	0.20
TDS	952	B	2.36
Calcium	75	C	1.48
Alkalinity	225	D	2.35
Temp.	11		
		pHs =	8.03

Langelier Saturation Index (LSI) Calculation		(Langelier, 1936)
LSI = pH - pHs	A = (Log10 [TDS] - 1) / 10	
pHs = (9.3 + A + B) - (C + D)	B = -13.12 x Log10 (oC + 273) + 34.55	
Where:	C = Log10 [Ca2+ as CaCO3] - 0.4	
	D = Log10 [alkalinity as CaCO3]	
	<b>LSI =</b>	<b>0.0</b>
LSI	Effect	
0.5 to 2	Water is super saturated and tends to precipitate a scale layer of calcium carbonate (scale forming but non-corrosive)	
0 to 0.5	<b>Water is super saturated and tends to precipitate a scale layer of calcium carbonate (slightly scale forming and corrosive).</b>	
0	Water is saturated (in equilibrium) with calcium carbonate. A scale layer of calcium carbonate is neither precipitated nor dissolved.	
0 to -0.5	Water is under saturated and tends to dissolve solid calcium carbonate (slightly corrosivebut non-scale forming).	
-0.5 to -2	Water is under saturated and tends to dissolve solid calcium carbonate (seriously corrosive).	