


**NOTES:**


1. REFER TO PARKING LOT STRIPING SPECIFICATION
2. CROSSWALK ALONG AN ACCESSIBLE ROUTE SHALL MAINTAIN A CROSS SLOPE OF 1.5% MAX AND A RUNNING SLOPE OF 5% MAX.

**C9.0** SCALE 1:50



**NOTES:**  
1. TACTILE WALKING SURFACE TO COMPLY WITH O.B.C. 3.8.3.18 AND OPSP 310.039 - "CONCRETE SIDEWALK RAMPS TACTILE WALKING SURFACE INDICATOR COMPONENTS"

**C9.0** SCALE 1:10



**NOTES:**

1. ACCESSIBLE PARKING AND ACCESSIBLE SHELTERS SHALL NOT EXIST IN OR IN CLOSE IN ANY DISCREET, IF ON ONE ACCESS AREA IS INSTALLED, IT IS TO BE A VAN SIZE.
2. PARKING STALL DIMENSIONING SHALL BE IN ACCORDANCE WITH APPLICABLE GOVERNING AUTHORITY'S AND ADA STANDARDS AND IF DIFFERENT THAN THIS DETAIL SHALL BE THE DIMENSIONING SHOWN ON THE SITE LAYOUT PLAN.
3. GENERAL CONTRACTOR SHALL REFER TO CHECK-FIL-A PARKING LOT STRIPING SPECIFICATIONS.
4. CONTRACTOR SHALL USE 100mm WIDE WHITE REFLECTIVE PAINT FOR STRIPING ON ASPHALT PARKING LOTS.
5. CONTRACTOR SHALL USE 100mm WIDE YELLOW REFLECTIVE PAINT FOR STRIPING ON CONCRETE PARKING LOTS.
6. NO WHEEL STOPS TO BE INSTALLED WHEN PARKING IS ADJACENT TO SIDEWALK.
7. ACCESSIBLE SIGNS IN BOLLARDS AND BOLLARDS SHALL BE INSTALLED WHEN PARKING IS ADJACENT TO FLUSH CURB OR A RAMP.

Technical drawing of a light pole base showing dimensions and components. The drawing is a cross-section view of the base, showing the concrete foundation and the steel structure. The overall width of the base is 610. The height of the base is 1676. The base is divided into three sections: a top section of 305, a middle section of 305, and a bottom section of 305. The top section contains 3 ties at 76mm O.C. at the top. The middle section contains 6 - #6 VERT. The bottom section contains #3 closed ties at 305mm O.C. with 305mm min. lap (TYP. U.N.). The base is supported by a concrete foundation. The drawing includes labels for the light pole, light pole base plate & anchor bolts, pole base cover, and 18mm chamfer. The drawing also includes a note: 'LIGHT POLE. SEE ELECT. DWGS.' and 'LIGHT POLE BASE PLATE & ANCHOR BOLTS. MATERIAL & DESIGN BY LIGHT POLE SUPPLIER'.

Labels and dimensions:

- LIGHT POLE. SEE ELECT. DWGS.
- LIGHT POLE BASE PLATE & ANCHOR BOLTS. MATERIAL & DESIGN BY LIGHT POLE SUPPLIER
- POLE BASE COVER
- 18mm CHAMFER
- 3 TIES @ 76mm O.C. AT TOP
- 6 - #6 VERT.
- #3 CLOSED TIES @ 305mm O.C. W/ 305mm MIN. LAP (TYP. U.N.)
- FIN. GRADE
- 305
- 305
- 305
- 610
- 1676
- 810
- 32
- 38

C9.0 SCALE 1:20



13 September 2024