# 120 Lusk Street



## **TIA Plan Reports - Certification**

On 14 June 2017, the Council of the City of Ottawa adopted new Transportation Impact Assessment (TIA) Guidelines. In adopting the guidelines, Council established a requirement for those preparing and delivering transportation impact assessments and reports to sign a letter of certification.

Individuals submitting TIA reports will be responsible for all aspects of development-related transportation assessment and reporting, and undertaking such work, in accordance and compliance with the City of Ottawa's Official Plan, the Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines.

By submitting the attached TIA report (and any associate documents) and signing this document, the individual acknowledges that s/he meets the four criteria listed below:

### CERTIFICATION

- 1. I have reviewed and have a sound understanding of the objectives, needs and requirements of the City of Ottawa's Official Plan, Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines;
- 2. I have a sound knowledge of industry standard practice with respect to the preparation of transportation impact assessment reports, including multi modal level of service review:
- I have substantial experience (more than 5 years) in undertaking and delivering transportation impact studies (analysis, reporting and geometric design) with strong background knowledge in transportation planning, engineering or traffic operations; and
- 4. I am either a licensed<sup>1</sup> or registered<sup>1</sup> professional in good standing, whose field of expertise [check  $\sqrt{\ }$  appropriate field(s)] is either transportation engineering  $\square$  or transportation planning  $\square$ .

License or registration body that oversees the profession is required to have a code of conduct and ethics guidelines that will ensure appropriate conduct and representation for transportation planning and/or transportation engineering works.

Dated at Ottawa this 14<sup>th</sup> day of October, 2025. (City)

Name: Ben Pascolo-Neveu, P.Eng.

Professional Title: Project Engineer

Ben Pascolo Neven

Signature of Individual certifier that she/he meets the above four criteria

## **Office Contact Information (Please Print)**


Address: 500-333 Preston Street

City / Postal Code: K1S 5N4

Telephone / Extension: 613-225-1311 ext. 64074

E-Mail Address: ben.pascoloneveu@arcadis.com

## Stamp



# **Document Control Page**

CLIENT:	NESCA Holdings Corp.
PROJECT NAME:	120 Lusk Street
REPORT TITLE:	Transportation Impact Assessment
IBI REFERENCE:	143412
VERSION:	1.0 DRAFT Submission
DIGITAL MASTER:	143412 120 Lusk Street - Internal Documents\6.0_Technical\6.23_Traffic\03_Reports\TTR_120_lusk_st_TIA_M ASTER_2023-05-23.docx
ORIGINATOR:	Ben Pascolo-Neveu
REVIEWER:	Ben Pascolo-Neveu
AUTHORIZATION:	David Hook
CIRCULATION LIST:	Josiane Gervais - City of Ottawa Transportation Project Manager
HISTORY:	1.0 – TIA Steps 1,2 & 3 Submitted for City Review – June 16, 2023 2.0 – TIA Step 4 Submitted for City Review – February 13, 2025 3.0 – TIA Step 4 Reissued for City Review – October 14, 2025

Exe	cutive S	Summary	y	1
1	Intro	duction.		1
2	TIA S	creenin	g	2
3	Proje	ct Scopi	ing	2
	3.1	Descri	iption of Proposed Development	2
		3.1.1	Site Location	2
		3.1.2	Land Use Details	4
		3.1.3	Development Phasing & Date of Occupancy	4
	3.2	Existin	ng Conditions	6
		3.2.1	Existing Road Network	6
		3.2.2	Existing Bicycle and Pedestrian Facilities	7
		3.2.3	Existing Transit Facilities and Service	8
		3.2.4	Collision History	8
	3.3	Planne	ed Conditions	9
		3.3.1	Transportation Network	9
		3.3.2	Future Adjacent Developments	10
		3.3.3	Network Concept Screenline	13
	3.4	Study	Area	13
	3.5	Time F	Periods	13
	3.6	Existin	ng Lane Configurations and Traffic Volumes	14
		3.6.1	Existing Lane Configurations	14
		3.6.2	Existing Traffic Volumes	14
	3.7	Study	Horizon Year	17
	3.8	Exem	ptions Review	17
4	Fore	casting .		18
	4.1	Dema	nd Rationalization	18
		4.1.1	Description of Capacity Issues	18

		4.1.2	Adjustment to Development Generated Demands	18
		4.1.3	Adjustment to Background Network Demands	19
	4.2	Develo	opment Generated Traffic	19
		4.2.1	Trip Generation Methodology	19
		4.2.2	Trip Generation Results	20
		4.2.3	Trip Distribution and Assignment	23
	4.3	Backg	round Network Traffic	25
		4.3.1	Changes to the Background Transportation Network	25
		4.3.2	General Background Growth Rates	25
		4.3.3	Other Area Development	25
	4.4	Traffic	: Volume Summary	26
		4.4.1	Future Background Traffic Volumes	26
		4.4.2	Future Total Traffic Volumes	26
5	Analy	sis		31
	5.1	Develo	opment Design	31
		5.1.1	Design for Sustainable Modes	31
		5.1.2	Circulation and Access	31
		5.1.3	New Street Networks	31
	5.2	Parkin	ng	32
		5.2.1	Parking Supply	32
	5.3	Bound	dary Streets	32
		5.3.1	Mobility	32
		5.3.2	Road Safety	33
	5.4	Acces	s Intersections	33
		5.4.1	Location and Design of Access	33
		5.4.2	Access Intersection Control	34
		5.4.3	Intersection Design (MMLOS)	34
	5.5	Transp	portation Demand Management (TDM) Program	34
		5.5.1	Context for TDM	34

		5.5.2	Need and Opportunity	34
		5.5.3	TDM Program	34
	5.6	Neighb	ourhood Traffic Management	35
		5.6.1	Adjacent Neighbourhoods	35
	5.7	Transit		35
		5.7.1	Route Capacity	35
		5.7.1	Transit Priority Measures	35
	5.8	Review	of Network Concept	35
	5.9	Interse	ction Design	35
		5.9.1	Intersection Control	35
		5.9.2	Intersection Analysis Criteria (Automobile)	36
		5.9.3	Intersection Capacity Analysis	36
		5.9.4	Intersection Design (MMLOS)	39
	5.10	Geome	tric Review	40
		Sight D	sistance and Corner Clearances	40
		5.10.2	Auxiliary Lane Analyses	40
	5.11	Summa	ary of Improvements Indicated and Modification Options	43
		5.11.1	Fallowfield Road & O'Keefe Court/Cobble Hill Drive	43
		5.11.2	O'Keefe Court & Lusk Street	43
		5.11.3	Fallowfield Road & Forager Street	43
6	Conclu	ısion		44

## **List of Tables**

Table 1 - Land Use Statistics	4
Table 2 - Reported Collisions within Vicinity of Proposed Development	8
Table 3 - Future Adjacent Developments	11
Table 4 - Exemptions Review	17
Table 5 - Intersection Capacity Analysis: Existing Traffic	18
Table 6 - Base Vehicular Trip Generation Results	20
Table 7 - Person-Trip Generation	20
Table 8 - 2011 O-D Survey Mode Shares and Proposed Mode Share Targets	21
Table 9 - Peak Hour Person Trips by Mode	22
Table 10 - Cumulative 4401 Fallowfield Road Trip Generation	23
Table 11 - Adjacent Development Vehicle Trip Generation	26
Table 12 – Segment-based MMLOS Results	32
Table 13 - LOS Criteria for Signalized and Unsignalized Intersections	36
Table 14 - Intersection Capacity Analysis: Future 2027 Background Traffic	37
Table 15 - Intersection Capacity Analysis: Future 2032 Background Traffic	37
Table 16 - Intersection Capacity Analysis: Future 2027 Total Traffic	38
Table 17 - Intersection Capacity Analysis: Future 2032 Total Traffic	38
Table 18 - Intersection MMLOS - Future Conditions	39
Table 19 - Auxiliary Left-Turn Storage Analysis at Signalized Intersections	41
Table 20 – Auxiliary Right-Turn Lane Storage Analysis at Signalized Intersections	42
List of Figures	
•	-
Figure 1 - Fallowfield Road & O'Keefe Court / Cobble Hill Drive intersection	
Figure 2 - Fallowfield Road & Forager Street	
Figure 3 - TMP Part 2 – Road Network - Priority (Map B2)	
Figure 4 - 2023 TMP Update (Part 1) Active Transportation Project List	
Figure 5 – South Nepean TAZ	19

## **List of Exhibits**

Exhibit 1 - Site Location	3
Exhibit 2 - Proposed Development	5
Exhibit 3 - Adjacent Developments	12
Exhibit 4 – Existing Lane Configurations and Intersection Controls	15
Exhibit 5 – Existing Traffic Volumes	16
Exhibit 6 - Site Generated AM & PM Peak Hour Traffic Volumes	24
Exhibit 7 - Future (2027) Background Traffic	27
Exhibit 8 - Future (2032) Background Traffic	28
Exhibit 9 - Future (2027) Total Traffic	29
Exhibit 10 - Future (2032) Total Traffic	30

# **List of Appendices**

Appendix A - TIA Screening Form

Appendix B – Proposed Development Site Plan

Appendix C - OC Transpo Routes

Appendix D - Collision Data

Appendix E – Traffic Count Data

Appendix F – Intersection Capacity Analyses

Appendix G - Trip Generation Data

Appendix H - TDM Checklists

Appendix I - Swept Path Analyses

Appendix J – MMLOS Analysis

Appendix K – Intersection Control Warrants

Appendix L – Auxiliary Lane Analyses

## **Executive Summary**

Arcadis was retained by NESCA Holdings Corp. to undertake a Transportation Impact Assessment (TIA) in support of a Site Plan Control application for a proposed medical facility, daycare, pharmacy and restaurant to be located at 120 Lusk Street, Ottawa. The subject development consists of an approximate 0.6-hectare, greenfield parcel included in the overall 4401 Fallowfield Road Plan of Subdivision which is gradually being transformed into a business park. The site is generally bound by O'Keefe Court to the north, Lusk Street to the south and undeveloped lands to the east and west.

The proposed development at 120 Lusk Street is expected to generate up to 117 and 133 two-way vehicular trips during the weekday morning and afternoon peak hours, respectively. The mode share targets were developed based on the South Nepean Traffic Assessment Zone (TAZ) and proportionally adjusted, in accordance with the Conditions of Approval for 4401 Fallowfield Road, to yield an 85% auto/15% non-auto mode share split.

Fallowfield & O'Keefe/Cobble Hill is presently operating as a two-way stop-controlled intersection. The results of the capacity analysis conducted for this study indicate that, by 2027, traffic signals will be operationally required and warranted under background traffic conditions. With traffic signals in place, the intersection would be expected to operate at LOS 'D' beyond the 2032 study horizon year. If traffic signals are not implemented by the study horizon year, delays of at least 5 minutes are expected at the Fallowfield & O'Keefe intersection with or without the inclusion of site-generated traffic. As site-generated traffic will not contribute significantly to any potential traffic operational issues at this intersection, it is recommended that the City continue monitoring this location on an annual basis to determine the appropriate timing for the introduction of traffic signals.

The results of the analysis indicate that the intersections of O'Keefe Court & Lusk Street and Fallowfield Road & Forager Street are expected to operate within acceptable standards (LOS 'D' or better) during the weekday morning and afternoon peak hours. Both are T-intersections that are configured with stop control on the minor road and are not expected to require additional auxiliary lanes or modifications within the timeframe of this study.

A multi-modal analysis identified deficiencies in the existing road network and potential remediation measures have been suggested which the City could consider to achieve these prescribed targets. It should be noted that, although these measures would provide improvements for a range of transportation modes, they are not required to safely accommodate the transportation demands of the proposed development.

Roadway modifications (RMA-2019-TPD-041B) were implemented in late 2021 to satisfy a conditional requirement for the Subdivision, including a right-in/right-out intersection at Fallowfield & Forager and a multi-use path along the west side of Fallowfield Road between O'Keefe Court to just south of Forager Street. It is understood that the southbound bus stop originally proposed as part of this RMA has been deferred until traffic signals are implemented at the Fallowfield & O'Keefe/Cobble Hill intersection.

All study area intersections were shown to operate well within the capacity constraints of the adjacent transportation network, with the appropriate modifications in place (i.e. signalization of Fallowfield & O'Keefe/Cobble Hill by 2027). Further, the proposed development will contribute a nominal increase in traffic on the adjacent road network. A Post-Development Monitoring Plan is, therefore, <u>not</u> a requirement of this study.

Based on the findings of this study, it is the overall opinion of Arcadis that the proposed development will integrate well with and can be safely accommodated by the adjacent transportation network with the recommended actions and modifications in place.

## 1 Introduction

Arcadis was retained by NESCA Holdings Corp. to undertake a Transportation Impact Assessment (TIA) in support of a Site Plan Control application for a proposed medical facility, daycare, pharmacy and restaurant to be located at 120 Lusk Street, Ottawa. The development represents a parcel of land in the original 4401 Fallowfield Road Plan of Subdivision.

In accordance with the City of Ottawa's Transportation Impact Assessment Guidelines, published in June 2017, the following report is divided into four major components:

- Screening Prior to the commencement of a TIA, an initial assessment of the proposed development is undertaken to establish the need for a comprehensive review of the site based on three triggers: Trip Generation, Location and Safety.
- Scoping This component of the TIA report describes both the existing and planned
  conditions in the vicinity of the development and defines study parameters such as the
  study area, analysis periods and analysis years of the development. It also provides an
  opportunity to identify any scope exemptions that would eliminate elements of scope
  described in the TIA Guidelines but not relevant to the development proposal, based on
  consultation with City staff.
- Forecasting The Forecasting component of the TIA is intended to review both the
  development-generated travel demand and the background network travel demand. It
  also provides an opportunity to rationalize this demand to ensure projections are within
  the capacity constraints of the transportation network.
- Analysis This component documents the results of any analyses undertaken to ensure
  that the transportation related features of the proposed development are in conformance
  with prescribed technical standards and that its impacts on the transportation network are
  both sustainable and effectively managed. It also identifies a development strategy to
  ensure that what is being proposed is aligned with the City of Ottawa's policies and citybuilding objectives.

Throughout the development of a TIA report, each of the four study components above are typically submitted in draft form to the City of Ottawa and undergo a review by a designated Transportation Project Manager (TPM). Any comments received are addressed to the satisfaction of the City's Transportation Project Manager before proceeding with subsequent components of the study. Based on email correspondence with the City TPM, dated May 25<sup>th</sup>, 2023, it was confirmed that a joint Screening, Scoping and Forecasting report would suffice for this study as a result of similarities between the subject site and the neighbouring properties at 135 and 140 Lusk Street, for which TIAs were conducted.

Roadway modifications proposed as part of RMA-2019-TPD-041B were implemented in late 2021 to satisfy a conditional requirement for the Subdivision. This RMA included a right-in/right-out intersection at Fallowfield Road & Forager Street and a multi-use pathway along the west side of Fallowfield Road. It is understood that the southbound bus stop originally proposed as part of this RMA has been deferred until traffic signals are implemented at the Fallowfield & O'Keefe/Cobble Hill intersection. The need for additional off-site road modifications or a Post-Development Monitoring Plan to track performance of the planned TIA Strategy will be confirmed through the analysis undertaken in this study.

## 2 TIA Screening

An initial screening was completed to confirm the need for a Transportation Impact Assessment (TIA) by reviewing the following three triggers:

- Trip Generation: The proposed development exceeds the 60-person trip threshold for each weekday peak hour, therefore the Trip Generation trigger is satisfied.
- Location: The proposed development will not be accessed from a boundary street that is
  designated as part of the City's Transit Priority, Rapid Transit network or Spine Bicycle
  Networks, nor is the subject site within a Design Priority Area or Transit-Oriented
  Development zone. As such, the Location trigger is not satisfied.
- **Safety**: A review of boundary street conditions did not identify an elevated potential for safety concerns adjacent the site, therefore the Safety trigger is <u>not</u> satisfied.

As the proposed development meets the Trip Generation trigger, the need to undertake a TIA is confirmed.

A copy of the TIA Screening Form is provided in **Appendix A**.

## 3 Project Scoping

## 3.1 Description of Proposed Development

## 3.1.1 Site Location

The subject property is presently an undeveloped, greenfield site located at 120 Lusk Street and is within the 4401 Fallowfield Road business park. The site occupies approximately 0.6 hectares and is generally bound by O'Keefe Court to the north, Lusk Street to the south and undeveloped lands to the east and west.

Based on GeoOttawa, the property is zoned IP[2265] H(12) – Business Park Industrial Zone.

The site location and its surrounding context are illustrated in Exhibit 1.



Exhibit 1: Site Location PROJECT No. 143412

SCALE:

## 3.1.2 Land Use Details

Table 1 summarizes the proposed land uses included in this development.

Table 1 - Land Use Statistics

LAND USE	SIZE – GFA <sup>1</sup>	
Medical Office	~1,375 m <sup>2</sup> (~14,801 ft <sup>2</sup> )	
Sit-down Restaurant	~187 m <sup>2</sup> (~2,010 ft <sup>2</sup> )	
General Office Building	~1,481 m² (~15,962 ft²)	
Pharmacy	~185 m <sup>2</sup> (~1,992 ft <sup>2</sup> )	
Daycare Centre	~374 m² (~4,022 ft²)	

Note: 1 GFA stands for 'Gross Floor Area'.

The proposed development is illustrated in **Exhibit 2** below and the full site plan, including additional details pertaining to site statistics, can be found in **Appendix B**.


The site will be accessed via a single all-movement private approach with a direct connection to Lusk Street.

With regards to parking, a total of 125 passenger vehicle spaces are proposed within the on-site surface parking lot, including 5 accessible parking stalls.

## 3.1.3 Development Phasing & Date of Occupancy

It is anticipated that the proposed development will be constructed and fully occupied in a single phase by the end of 2027.





## 3.2 Existing Conditions

## 3.2.1 Existing Road Network

### 3.2.1.1 Roadways

The proposed development is bound by the following street(s):

- Lusk Street is a two-lane local road under the jurisdiction of the City of Ottawa, extending from O'Keefe Court and terminates in a cul-de-sac approximately 250m to the southwest. Lusk Street has a 20m right-of-way, an unposted speed limit of 50 km/h and provides access to the 4401 Fallowfield Road business park.
- O'Keefe Court is a two-lane local road under the jurisdiction of the City of Ottawa, extending west from Fallowfield Road and terminating in a cul-de-sac approximately 800m west of the Fallowfield & O'Keefe intersection. The roadway has a rural cross-section with a posted speed limit of 50km/h. O'Keefe Court extends along the former Fallowfield Road alignment (prior to its realignment to Strandherd Drive). Its right-of-way (ROW) therefore varies and is generally 30m, however, additional ROW has been taken on a portion of the north side to accommodate a multi-use path.

Other streets within the vicinity of the proposed development are as follows:

- Fallowfield Road is a two-lane, undivided rural arterial roadway under the jurisdiction of the City of Ottawa with a right-of-way protection of 44.5m. Between Highway 416 and Strandherd Drive, Fallowfield Road has a posted speed of 80km/h, prior to its 90-degree realignment to the northeast through the context area with a reduced speed limit of 60 km/h.
- Forager Street is a two-lane local road under the jurisdiction of the City of Ottawa, linking Lusk Street to Fallowfield Road and provides access to the 4401 Fallowfield Road business park. Forager Street has a 20m right-of-way and an unposted speed limit of 50 km/h.
- **Strandherd Drive** is a four-lane, divided urban arterial road under the jurisdiction of the City of Ottawa with a posted speed limit of 80 km/h within the vicinity of the subject lands, and a right-of-way protection of 44.5m.
- Cedarview Road is a roadway under the jurisdiction of the City of Ottawa that extends from Strandherd Drive in the south to Baseline Road in the north. Cedarview Road is a two-lane, urban arterial road north of Fallowfield Road, with a 37.5m right-of-way protection. Between Fallowfield Road and Jockvale Road, it is a major collector with a 26m right-of-way. The posted speed limit on Cedarview Road is 60 km/h. South of Strandherd Drive and the VIA Rail corridor, Cedarview Road has been renamed Borrisokane Road and continues south to Barnsdale Road.
- **Foxtail Avenue** is a two-lane local road under the jurisdiction of the City of Ottawa, extending north from O'Keefe Court and provides access for the Orchard Estates residential community. The posted speed limit is 40 km/h.

#### 3.2.1.2 Intersections

The following existing intersections have been identified as having the greatest potential to be impacted by the proposed development:

Fallowfield Road & O'Keefe Court / Cobble Hill Drive presently exists as a four-legged unsignalized intersection with stop-control on the O'Keefe Court and Cobble Hill Drive approaches. Each leg of the intersection is configured with a single through lane and auxiliary left-turn lane. Auxiliary right-turn lanes are provided along Fallowfield Road, while the side streets are configured with shared through-right lanes. The City of Ottawa is currently monitoring this intersection for implementation of traffic signals, once warranted.

Figure 1 - Fallowfield Road & O'Keefe Court / Cobble Hill Drive intersection



Fallowfield Road & Forager Street is a three-legged intersection which has been modified with a raised diverter island to restrict turning movements to right-in/right-out and incorporate a multi-use path (MUP) on the west side of Fallowfield Road between Forager Street and Fallowfield Road. This MUP includes a bi-directional shared cross-ride on the west leg to achieve connectivity across Forager Street. The eastbound approach has a single right-turn lane. The north leg of the intersection consists of a single through lane, a shared through-right lane and the beginning taper of a single auxiliary left-turn lane for the intersection to the south within the confines of this intersection. The south leg is comprised of two through lanes.

Figure 2 - Fallowfield Road & Forager Street



## 3.2.1.3 Traffic Management Measures

There are currently no traffic management or traffic calming measures on the boundary streets within the vicinity of the proposed development.

#### 3.2.1.4 Nearby Driveways

The Hampton Inn and Suites Hotel is located to the south of the subject development and includes two full-movement private approaches on the south side of Lusk Street directly opposite the proposed development.

## 3.2.2 Existing Bicycle and Pedestrian Facilities

The section of Fallowfield Road was reconstructed in late 2021 to incorporate a multi-use path on the west side from just south of Forager Street to O'Keefe Court. An east-west multi-use path presently exists along the north side of O'Keefe Court from Lytle Park in the west to Cedarview Road in the east as well. There are also sidewalks on Forager Street and Lusk Street which

provide direct connections between active transportation facilities on Fallowfield Road and O'Keefe Court.

With respect to dedicated cycling infrastructure within the context area, a bike pocket exists along Fallowfield Road on the southbound approach to the Fallowfield Road & O'Keefe Court/Cobble Hill Drive intersection. Uni-directional cycle tracks are also provided on both sides of Strandherd Drive from Fallowfield Road to Maravista Drive with cross-rides, two-stage left-turn bike boxes and bicycle signals at key signalized intersections.

## 3.2.3 Existing Transit Facilities and Service

OC Transpo currently operates the following transit route within close proximity to the proposed development:

- Route #70 provides regular, all-day service 7 days a week between Fallowfield and Limebank, operating on an approximate 15-minute headway during weekday peak periods and 30-minute headway during off-peak periods and weekends.
- Route #110 provides regular service 7 days a week between Limebank and Innovation/Briarbrook. This route generally operates on 30-minute headways on weekdays. On the weekend, trips are limited to select trips in the morning and late afternoon/early evening time.
- Route #173 provides weekday peak period and peak direction service between Citigate
  and alternates between Fallowfield Station and Barrhaven Centre. This route operates on
  an approximate 30-minute headway on weekdays, with weekend frequencies reduced to
  provide service approximately once per hour.

The nearest bus stop pair to the proposed development are located at the CitiGate Drive and CrossKeys Place junction, just south of Fallowfield Road and represent an approximate 630-metre walking distance from the site, which serves all three of the above noted routes.

Transit service maps for the above noted transit routes are provided in **Appendix C**.

## 3.2.4 Collision History

A review of historical collision data has been conducted for the road network surrounding the proposed development. The TIA Guidelines require a safety review if at least six collisions for any one movement or of a discernible pattern, over a five-year period have occurred. **Table 2** summarizes all reported collisions between January 1, 2017 and December 31, 2021.

It should be noted that there were no recorded collisions on the internal segments/intersections of Forager Street or Lusk Street, or on Fallowfield Road between Strandherd and O'Keefe.

Table 2 - Reported Collisions within Vicinity of Proposed Development

LOCATION	# OF REPORTED COLLISIONS	
INTERSECTIONS		
Fallowfield Road & Strandherd Drive	52	
Fallowfield Road & O'Keefe Court / Cobble Hill Drive	2	

Based on the collision history summarized above, the Fallowfield Road & Strandherd Drive is the only intersection where the collisions are significant but as it is not within the study area, no further analysis is required.

Detailed collision records are provided in **Appendix D**.

## 3.3 Planned Conditions

## 3.3.1 Transportation Network

#### 3.3.1.1 Future Road Network Projects

The Transportation Master Plan (TMP) Part 2: Capital Infrastructure Plan outlines future road network modifications in the 2046 Road Network – Priority plan. The following projects of significance were noted within the vicinity of the site:

• Fallowfield Road – Planned urbanization on Fallowfield Road from Strandherd Drive to Cedarview Road. As part of the future Fallowfield Road urbanization project, new transportation facilities are proposed to enhance for all modes and support future development within the Barrhaven community.

**Figure 3** below illustrates the planned changes to the arterial road network projects in the broader context area, as per the TMP 'Road Network – Priority' plan.




Figure 3 - TMP Part 2 - Road Network - Priority (Map B2)

Source: TMP Part 2 Capital Infrastructure Plan – Map B2 Road Network Priority

#### 3.3.1.2 Future Transit Facilities and Services

The TMP – Capital Infrastructure Plan does not identify any planned transit priority projects within the vicinity of the proposed development as part of the '2046 Transit Network – Priority' or '2046 Transit Network – Needs-Based'.

The Roadway Modification Application (RMA) completed for the Fallowfield & Forager intersection originally included a new southbound bus stop on Fallowfield Road south of O'Keefe Court, however OC Transpo has deferred the installation of this bus stop until after the intersection becomes signalized.

#### 3.3.1.3 Future Cycling and Pedestrian Facilities

A 2.0-metre wide concrete sidewalk is planned as part of a future active transportation improvement for the ongoing subdivision development on the north side of Lusk Street and includes the site's frontage. This sidewalk will connect with a future 3.0-metre wide asphalt

pathway proposed to the west, and provide a direct pedestrian link to the western portion of the 4401 Fallowfield Road Subdivision.

The existing pathway north of O'Keefe Court form part of the Major Pathway network within the vicinity of the site. A multi-use path on the west side of Fallowfield Road was constructed in 2022 and provides connectivity from the site to the Fallowfield/O'Keefe Court intersection where a future signalized intersection and bus stops are planned. The signalization of the Fallowfield & O'Keefe/Cobble Hill intersection will facilitate connectivity to the existing pathway system immediately north of O'Keefe Court.

The 2023 TMP Update (Part 1) Active Transportation Project List includes a multi-use pathway on the west side of Fallowfield Road between Strandherd Drive and Forager Street labelled as the 'Fallowfield Road – Forager Street Pathway' project, as shown in **Figure 4** below. This initiative is identified as a 'Later Phase' project on Map C2 of the 'Cycling Projects within Prioritization' from the TMP Part 2 Capital Infrastructure Plan.

Strandherd Drive is identified as a Cross-town Bikeway in the 2046 TMP and was modified to include grade-separated sidewalks and cycle tracks on both sides of this arterial road as part of an urbanization initiative completed from 2015 to 2024.

Figure 4 below shows the future cycling network in the vicinity of the proposed development.

Figure 4 - 2023 TMP Update (Part 1) Active Transportation Project List



Source: GeoOttawa & Map C2 in TMP Part 2 Capital Infrastructure Plan

## 3.3.2 Future Adjacent Developments

The City of Ottawa Transportation Impact Assessment (TIA) Guidelines specify that all significant developments proposed within the surrounding area which are likely to occur within the study's horizon year must be identified and taken into consideration in the development of future background traffic projections.

The subject site forms part of the 4401 Fallowfield Road Plan of Subdivision (previously referred to as the Highway 416 Lands development). It is located in the northwest quadrant of the Fallowfield Road and Strandherd Drive intersection that will eventually consist of three hotels and an office park.

All current development applications within the context area of the proposed development have been summarized below in Table 3 below.

Table 3 - Future Adjacent Developments


DEVELOPMENT	TIA	LAND USE AND SIZE	TARGETED BUILD-OUT
100 Lusk Street <sup>2</sup> Stantec (2020)		• ~1,895 m <sup>2</sup> General Office	2021 <sup>1</sup>
115 Lusk Street <sup>2</sup>	IBI Group (2021)	<ul> <li>~280 m² Restaurant</li> <li>~560 m² Medical Office</li> </ul>	2023 <sup>1</sup>
135 Lusk Street <sup>2</sup>	IBI Group (2021)	• 99 Hotel Rooms	2023 <sup>1</sup>
140 Lusk Street <sup>2</sup>	Arcadis IBI Group (2022)	88 Hotel Rooms	2023 <sup>1</sup>
Gateway Industrial Centre (4497 O'Keefe Court)	Delcan (2008)	• ~25,981 m <sup>2</sup> General Light Industrial	Unknown <sup>1</sup>
4190, 4200, 4210, 4236 Fallowfield Road and 2740 Cedarview Road	Novatech (2018)	194 Residential Units	2023 <sup>1</sup>
CitiGate – 416 Novatech Employment Lands (2012)		<ul> <li>~32,526.1m² Shopping Centre</li> <li>200 Hotel Rooms</li> <li>Gas Station (8 fuel positions)</li> <li>~16.6 ha Business Park</li> <li>67.65 ha Office Park</li> <li>~10.5 ha New Car Sales</li> </ul>	2029
CitiGate Hotel (4433 Strandherd Drive) <sup>3</sup>	Novatech (2019)	• 99 Hotel Rooms	2020 <sup>1</sup>

### Notes:

- Occupancy assumed to coincide with full build-out of the proposed development in 2027.
- 2.
- Located within the Highway 416 Lands development.

  Located within the City Gate 416 Employment Lands development.

The locations of the adjacent developments described above are shown in **Exhibit 3** below.



**ARCADIS IBI GROUP** 

120 Lusk Street Transportation Impact Assessment

Exhibit 3: Adjacent Developments PROJECT No.

SCALE:

0m 125m 250m

## 3.3.3 Network Concept Screenline

A network screenline analysis is not expected to be necessary for this development, as the trip generation is anticipated to only slightly exceed the threshold prescribed in the TIA Guidelines of 200 person-trips or more during the weekday peak hours. Detailed trip generation calculations will be provided in the Forecasting section of the report.

## 3.4 Study Area

The information presented thus far provides a base level of information for the development's context. Based on preliminary estimates of trip generation completed for the TIA Screening Form, the proposed development is expected generate roughly 250 person-trips during the critical weekday afternoon peak hour. Travel demand will be subsequently stratified by mode share and further reduced by the variation in travel routes within the broader study area. As such, the proposed development is expected to contribute marginal downstream impacts to intersections at the periphery of the context area, including Cedarview & Fallowfield.

Strandherd Drive from Fallowfield Road to Maravista Drive was also exempt from the study area, as this segment of road was reconstructed in 2015 following the City's Complete Streets design philosophy to accommodate long-term multi-modal travel demands beyond the TMP's ultimate planning horizon of 2031. Consideration was given to the proposed development travel demands as part of the Highway 416 Lands Community Transportation Study (CTS), published In 2015.

With respect to the exemptions discussed above, this TIA will focus on site-specific impacts, integration with its boundary streets, including a functional review of the site access geometry and intersection control, on-site drive aisle requirements to accommodate proposed design vehicles and a review of the site's parking and loading requirements.

Consistent with numerous other TIAs conducted to support development applications within this industrial subdivision, a condensed study area is proposed for this TIA, which includes the following intersections:

- Fallowfield Road & O'Keefe Court/Cobble Hill Drive
- O'Keefe Court & Lusk Street
- Fallowfield Road & Forager Street

An intersection-based Multi-Modal Level of Service (MMLOS) analysis is only required for signalized intersections. Based on analysis conducted for previous TIAs within the 4401 Fallowfield Road subdivision, it is expected that the Fallowfield & O'Keefe/Cobble Hill intersection will require traffic signals operationally under Future Background conditions and therefore MMLOS will be limited to this intersection once signalization is required to achieve acceptable operating conditions. Segment-based MMLOS analysis will also be provided on Fallowfield Road between Forager Street and O'Keefe Court, as well as on the boundary streets, O'Keefe Court and Lusk Street.

## 3.5 Time Periods

Based on a preliminary review of trip generation rates associated with the proposed land uses, the peak weekly traffic generation is expected to occur during the weekday afternoon peak period. As such, consistent with other TIAs conducted for developments within the 4401 Fallowfield Road business park, the weekday morning and afternoon peak hours will constitute the critical analysis periods for this study.

## 3.6 Existing Lane Configurations and Traffic Volumes

## 3.6.1 Existing Lane Configurations

The existing lane configurations and traffic controls for the study area are shown in **Exhibit 4** below.


## 3.6.2 Existing Traffic Volumes

Weekday morning and afternoon peak hour turning movement counts were conducted on Tuesday, May 23, 2023 at the following intersection(s):

• Fallowfield Road and O'Keefe Court/Cobble Hill Drive

Weekday peak hour vehicular, pedestrian and cyclist traffic volumes representative of Existing conditions are shown in **Exhibit 5** below. Traffic count data is provided in **Appendix E**.











Exhibit 4: **Existing Lane Configurations** & Intersection Controls

PROJECT No. 143412

SCALE:

N.T.S.



120 Lusk Street

## 3.7 Study Horizon Year

It is expected that the proposed development will be constructed and fully occupied in a single phase by the end of 2027. The horizon year for this study is therefore 2032.

## 3.8 Exemptions Review

The TIA Guidelines provide exemption considerations for elements of the Design Review and Network Impact components. **Table 4** summarizes the TIA modules that are not applicable to this study.

Table 4 - Exemptions Review

TIA MODULE	ELEMENT	EXEMPTION CONISDERATIONS	REQUIRED
DESIGN REVIEW	COMPONENT		
4.1 Development Design	4.1.2 Circulation and Access	Only required for site plans	$\checkmark$
	4.1.3 New Street Networks	Only required for plans of subdivision	X
4.2 Parking	4.2.1 Parking Supply	Only required for site plans	✓
	4.2.2 Spillover Parking	Only required for site plans where parking supply is 15% below unconstrained demand	×
NETWORK IMPAC	T COMPONENT		
4.5 Transportation Demand Management	All Elements	Not required for site plans expected to have fewer than 60 employees and/or students on location at any given time	✓
4.6 Neighbourhood Traffic Management	4.6.1 Adjacent Neighbourhoods	Only required when the development relies on local or collector streets for access and total volumes exceed ATM capacity thresholds	×
4.8 Network Concept	n/a	Only required when proposed development generates more than 200 person-trips during the peak hour in excess of the equivalent volume permitted by established zoning	×

## 4 Forecasting

## 4.1 Demand Rationalization

The purpose of this section is to rationalize future travel demands within the study area to account for potential capacity limitations in the transportation network and its ability to effectively accommodate the additional demand generated by a new development.

## 4.1.1 Description of Capacity Issues

**Table 5** below summarizes the existing traffic operational performance at the study area intersections based on Existing Traffic volumes. The intersection capacity analysis is based on locally-specific parameters as described in the TIA Guidelines. As prescribed in the TIA Guidelines, a peak hour factor (PHF) of 0.90 has been considered in the analysis of existing conditions. The Synchro output files have been provided in **Appendix F**.

Table 5 -	Intersection	Capacity	Analysis:	<b>Existing Traffic</b>

		AM PEA	K HOUR	PM PEAK HOUR	
INTERSECTION	TRAFFIC CONTROL	OVERALL LOS	CRITICAL MOVEMENTS	OVERALL LOS	CRITICAL MOVEMENTS
		(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)
Fallowfield Road & O'Keefe Court / Cobble Hill Drive	Unsignalized	D (27.3s)	WBL (27.3s)	F (51.9s)	WBL (51.9s)
Lusk Street & O'Keefe Court	Unsignalized	A (8.4s)	NBRL (8.4s)	A (8.5s)	NBRL (8.5s)
Fallowfield Road & Forager Street	Unsignalized	B (10.2s)	EBR (10.2s)	B (11.2s)	EBR (11.2s)

As indicated above, the study area intersections are all operating at an acceptable Level of Service (i.e. LOS 'D' or better) with the exception of the Fallowfield & O'Keefe/Cobble Hill. This intersection is currently operating at LOS 'F' during the weekday afternoon peak period due to high conflicting north-south volumes on with the westbound left-turn movement. As the proposed development will not contribute to volumes at the westbound left-turn movement, no mitigation measures are proposed for existing conditions.

The intersection capacity analysis presented in Section 5.9 identifies potential capacity constraints (i.e. LOS 'F') under both weekday morning and afternoon peak hours by 2027 under Background and Total Traffic conditions, if its existing two-way stop-controlled configuration is retained. With traffic signals in place, the intersection capacity would be significantly improved to well within acceptable standards (i.e. LOS 'D' or better). If traffic signals are not implemented, long delays are expected at the Fallowfield & O'Keefe intersection with or without the inclusion of sitegenerated traffic.

## 4.1.2 Adjustment to Development Generated Demands

The proposed development is expected to contribute to demand on the adjacent road network with up to 133 additional two-way vehicle-trips during the critical weekday afternoon peak hour and therefore is unlikely to exacerbate any potential traffic operational issues, particularly because the majority of site-generated traffic is expected to use non-critical movements and therefore will

not contribute significantly to the overall intersection delay. The impacts on the Fallowfield & O'Keefe intersection are lessened by the completed Fallowfield & Forager intersection which provides a more direct connection to the arterial road network for right-turning traffic.

## 4.1.3 Adjustment to Background Network Demands

As prescribed in the TIA Guidelines, the effects of peak-hour spreading have been considered in in future analysis years of this study. It is anticipated that as traffic volumes continue to gradually increase, vehicular trips will have a natural tendency to be more evenly distributed across the peak hour (PHF = 1.0) and eventually increase demands in the shoulders of the peak as well. The impacts of peak hour spreading are accounted for in the Synchro modelling exercise, completed as part of the Analysis component of this study.

## 4.2 Development Generated Traffic


## 4.2.1 Trip Generation Methodology

Peak hour site-generated traffic volumes were developed using the Institute of Transportation Engineers (ITE) Trip Generation Manual (11<sup>th</sup> Edition). The TIA Guidelines indicate that vehicle-trip generation rates from the ITE Trip Generation Manual should be converted to person-trips through the application of a 1.28 vehicle-to-person-trip conversion factor.

Following the application of the vehicle-to-person-trip conversion factor, the person-trips were then subdivided based on representative mode share percentages applicable to the study area to determine the number of auto driver, auto passenger, transit, pedestrian, cycling and 'other' trip types.

Mode share targets were developed based on the local mode share distributions from the South Nepean Traffic Assessment Zone (TAZ) in the 2011 O-D Survey and adjusted to account for Condition 6b of the Conditions of Approval of the Draft Plan of Subdivision of 4401 Fallowfield Road. Condition 6b indicates that all TIAs prepared for Site Plan Applications within the 4401 Fallowfield Road subdivision must assume a maximum non-auto mode share (transit, walking, cycling and 'other') of 15%. Furthermore, Condition 6a indicates that the cumulative vehicle-trip generation of all sites within the 4401 Fallowfield Road subdivision shall not exceed 739 vehicles per hour during the weekday morning and afternoon peak periods.

The extents of the South Nepean TAZ are illustrated in Figure 5 below.



Source: 2011 O-D Survey

## 4.2.2 Trip Generation Results

## 4.2.2.1 Base Vehicle Trip Generation

Weekday peak hour vehicular traffic volumes associated with the proposed development were determined using appropriate trip generation rates from the ITE Trip Generation Manual.

The vehicular trip generation results for the proposed development have been summarized in **Table 6** below.

Table 6 - Base Vehicular Trip Generation Results

LAND USE	SIZE	DEDIOD	PERIOD GENERATED TRIPS (		
LAND USE	(GFA)	PERIOD	IN	OUT	TOTAL
720 – Medical Office	~3,124 m²	AM	36	10	46
building	0,124111	PM	17	41	58
932 – High-Turnover	~193 m²	AM	11	8	19
Sit-Down Restaurant	100 111	PM	11	7	18
710 – General Office	~1481 m²	AM	21	3	24
Building	1401111	PM	4	19	TOTAL 46 58 19 18
880 – Pharmacy	~185 m²	AM	4	2	6
without Drive-through	100 111	PM	8	9	17
565 – Daycare	~374 m²	AM	23	21	44
Centre	014111	PM	21	23	45
Total	AM	95	44	139	
rotai		PM	61	99	160

Notes: vph = vehicles per hour

### 4.2.2.2 Person Trip Generation

The TIA Guidelines indicate that a 1.28 vehicle-to-person-trip conversion rate should be utilized to convert the base vehicular trip generation results into person trips.

The resulting number of site-generated person-trips is summarized in **Table 7** below.

Table 7 - Person-Trip Generation

LAND USE	DEDIOD	PERSON TRIPS (PPH)			
LAND USE	PERIOD	IN	OUT	TOTAL	
Medical Office	AM	46	13	59	
Building	PM	22	52	74	
Restaurant	AM	14	11	25	
	PM	14	10	24	
General Office Building	AM	27	4	31	
	PM	5	24	29	

Dharmany	AM	5	3	8
Pharmacy	PM	10	12	22
	AM	29	27	56
Daycare	PM	27	29	56
	AM	122	56	178
Total	PM	78	127	205

Notes: pph = persons per hour

## 4.2.2.3 Mode Share Proportions

The 2011 TRANS Origin-Destination (O-D) Survey provides approximations of the existing modal share within the South Nepean Traffic Assessment Zone (TAZ). Relevant extracts from the 2011 O-D Survey are provided in **Appendix G**.

Of the available data, a weighted average of the weekday AM 'To', AM 'Within', PM 'From' and PM 'Within' mode share distributions were determined to be the most appropriate to develop a baseline mode share for the proposed development. These distributions were selected to best represent the travel characteristics of employees. The South Nepean TAZ also includes Barrhaven which provides a wide range of amenities and housing options for prospective employees and customers. As such, the internal (i.e. 'Within District') mode share proportions were also considered in the development of the modal targets for the proposed development.

It is acknowledged, however, that the subject development is located on the periphery of an autooriented suburb and therefore, it was determined that the mode share targets specific to this development may deviate from the average mode share experienced in the South Nepean TAZ. The following adjustments were made to the mode share distributions to better represent the travel characteristics of the proposed development:

> The vast majority of 'Other' trips were assumed to occur by taxi/rideshare services and therefore in order to quantify their vehicular impacts, these trips were reallocated to 'Auto Driver'.

Given the low probability of site-generated trips occurring by non-auto travel modes (transit, cycling, walking and other) within the horizon year of this study, the mode share targets of all non-auto travel modes were proportionally adjusted to yield a total non-auto mode share of 15% in accordance with the Conditions of Approval for 4401 Fallowfield Road. The difference in mode share was reallocated proportionally to the auto driver and auto passenger modes.

**Table 8** below summarizes the 2011 O-D Survey mode shares, as well as the mode share targets.

Table 8 - 2011 O-D Survey Mode Shares and Proposed Mode Share Targets

	2011 O	D SURVE	Y MODE S	SHARE	BLENDED BLENDED MO		
TRAVEL MODE	AM To District  AM PM PM PM Within From Within District District District	MODE	MODE SHAF	MODE SHARE TARGETS			
Auto Driver	71%	34%	72%	46%	49%	62%	65%
Auto Passenger	13%	19%	21%	21%	19%	19%	20%
Total Auto Mode Share	84%	53%	93%	67%	68%	81%	85%

Transit Cycling	5% 1%	4% 2%	4% 1%	4% 1%	4% 1%	4% 1%	3% 1%
Walking	0%	17%	0%	20%	14%	14%	11%
Other	10%	24%	2%	9%	13%	0%	0%
Total Non- Auto Mode Share	16%	47%	7%	34%	32%	19%	15%

#### Notes:

### 4.2.2.4 Trip Reduction Factors

## **Deduction of Existing Development Trips**

Not Applicable: The proposed development lands are currently undeveloped, and do not generate any traffic volumes.

## Pass-by Traffic

Based on survey data collected for the *ITE Trip Generation Handbook (11th Edition)*, the High-Turnover (Sit-Down) Restaurant land use was shown to generate an average of 43% pass-by trips, while the pharmacy has an average pass-by rate of about 53%. This study conservatively did not apply any pass-by reduction factors, as the vehicle trip generation associated with these land uses is anticipated to be nominal during the weekday perk hours and, as a consequence, the overall impact on the adjacent road network is expected to be minimal.

#### Synergy/Internalization

The proposed development will not generate internal person-trips of significance between the proposed land uses. Some non-auto trips are likely to occur to/from other sites within the 4401 Fallowfield Road subdivision, such as the adjacent Hampton Inn and Suites.

## 4.2.2.5 Trip Generation by Mode

The mode share targets summarized previously in **Table 8** were applied to the number of development-generated person-trips to establish the expected number of trips per travel mode, as shown in **Table 9** below.

Table 9 - Peak Hour Person Trips by Mode

MODE		AM		PM		
	IN	OUT	TOTAL	IN	OUT	TOTAL
Auto Driver	80	37	117	51	82	133
Auto Passenger	24	11	35	16	25	41
Transit	4	2	6	2	4	6
Cycling	1	1	2	1	1	2
Walking	13	6	19	9	14	23
Other	0	0	0	0	0	0

<sup>&</sup>lt;sup>1</sup> Adjustments to reallocate 'Other' mode share to 'Auto Driver'

Total	122	57	179	79	126	205

#### 4.2.2.6 Cumulative 4401 Fallowfield Road Trip Generation

Condition 6A of the Conditions of Approval of the Draft Plan of Subdivision of 4401 Fallowfield Road indicates that the total vehicle-trip generation of the subdivision shall not exceed 739 vehicle-trips per hour during the weekday morning and afternoon peak hours. **Table 10** below summarizes the total and cumulative number of vehicle-trips generated during the weekday morning and afternoon peak hours by all sub-developments within 4401 Fallowfield Road subdivision which have been approved or are currently undergoing the City's Site Plan Control application process.

Table 10 - Cumulative 4401 Fallowfield Road Trip Generation

SUB-DEVELOPMENT	TOTAL AM (PM) VEHICLE TRIPS	CUMULATIVE AM (PM) VEHICLE TRIPS
100 Lusk Street	23 (22)	23 (22)
115 Lusk Street	13 (32)	36 (54)
125 Lusk Street	56 (64)	92 (118)
135 Lusk Street	42 (53)	134 (171)
140 Lusk Street	36 (45)	170 (216)
120 Lusk Street	117 (125)	287 (349)
Total from Curren	287 (349)	
Total Allowa	739 (739)	
Percentage (	39% (47%)	

As indicated in **Table 10** above, the addition of the proposed development will not exceed the maximum permissible vehicular generation of the 4401 Fallowfield Road subdivision.

The developments listed above represent approximately 42% of the total developable area within the 4401 Fallowfield Road subdivision. Future developments as part of Phase 2 of the 4401 Fallowfield Road subdivision are anticipated to consist of land uses that will generate less trips during the weekday peak hour relative to the property parcel size and include uses such as auto dealerships.


## 4.2.3 Trip Distribution and Assignment

As the proposed development is expected to primarily draw traffic from Highway 416 and residential areas of Barrhaven, site-generated traffic has been distributed to the adjacent road network as follows:

- 40% to/from the north via Fallowfield Road
- 60% to/from the south via Fallowfield Road

Utilizing the estimated number of new auto trips and applying the above distribution, future site-generated traffic volumes are illustrated for each of the study area intersections in **Exhibit 6** below.







120 Lusk Street

**Transportation Impact Assessment** 

## 4.3 Background Network Traffic

## 4.3.1 Changes to the Background Transportation Network

To properly assess future traffic conditions, planned modifications to the transportation network that may impact travel patterns or demand within the study area must be considered. The TIA Scoping reviewed the anticipated changes to the study area transportation network based on the City of Ottawa Transportation Master Plan (TMP). Based on a review of these policy documents, it was determined that there are no major road, pedestrian or cycling network modifications planned within the study area prior to the 2032 TIA study horizon year.

It is worth noting that the intersection of Fallowfield & O'Keefe/Cobble Hill is being monitored by City staff for traffic signal warrants. Also, the intersection of Fallowfield & Forager was upgraded in 2022 which allows for an alternative means of accessing the arterial road network with right-in/right-out only movements permitted.

## 4.3.2 General Background Growth Rates

The background growth rate is intended to represent increases in regional travel demand from outside the study area that will contribute to traffic volumes on the adjacent road network. Consistent with the adjacent TIAs conducted for adjacent developments within the 4401 Fallowfield Road subdivision including 135 Lusk Street (IBI, 2021) and the 140 Lusk Street (Arcadis IBI, 2022), a 2.0% rate of linear growth per annum is proposed within the study area for the calculation of future background traffic.

The background growth rate has only been applied to the through movements on Fallowfield Road as traffic generation relating to all known future adjacent developments has been explicitly accounted for in the analysis.

### 4.3.3 Other Area Development

All current adjacent development applications within the study area were previously identified in **Table 3** above, all of which were accounted for explicitly in the assembly of future background volume projections. These developments represent specific areas of growth within the study area and are therefore considered in addition to the general background growth rate discussed previously. **Table 11** below summarizes the vehicle trip generation of all current adjacent background development applications.

Table 11 - Adjacent Development Vehicle Trip Generation

		V	VEHICLE TRIP GENERATION				
DEVELOPMENT	TIA	A	M	PM			
		IN	OUT	IN	OUT		
100 Lusk Street	Stantec (2020)	20	3	3	19		
115 Lusk Street	IBI (2021)	8	5	17	15		
135 Lusk Street	IBI (2021)	25	17	27	26		
140 Lusk Street	Arcadis IBI (2022)	20	16	23	22		
Gateway Industrial Centre (4497 O'Keefe Court)	Delcan (2008)	20	97	94	46		
4190, 4200, 4210, 4236 Fallowfield Road and 2740 Cedarview Road	Novatech (2018)	108	33	131	76		
		Interim (2019)					
CitiGate – 416	Novatech	741	216	664	1,015		
Employment Lands	(2012)		Ultimate	e (2029)			
		3,494	635	1,128	3,316		
CitiGate Hotel (4433 Strandherd Drive)	Novatech (2019)	29	20	27	26		

The CitiGate – 416 Employment Lands is a large multi-phase development which is currently under construction and is expected to be fully built out by 2029. The projected traffic volumes generated by this development at the 2027 analysis year were linearly interpolated and considered the development status at the time of the recorded traffic counts utilized in this study.

It was assumed that the Gateway Industrial Centre (4497 O'Keefe Court) development will be fully built out by the 2027 analysis year.

## 4.4 Traffic Volume Summary

## 4.4.1 Future Background Traffic Volumes


Future background traffic volumes projections have been established by combining the adjacent development traffic and background traffic derived through the application of a growth rate, as discussed previously. **Exhibit 7** and **Exhibit 8** present the future background traffic volumes anticipated for the 2027 build-out year, as well as the 2032 study horizon, respectively.

#### 4.4.2 Future Total Traffic Volumes

Future total volumes have been derived by combining the site-generated traffic from **Exhibit 6** with the future background volumes from **Exhibit 7** and **Exhibit 8**.

**Exhibit 9** and **Exhibit 10** present the future total traffic volumes anticipated for 2027 and 2032 analysis years, respectively.















Exhibit 8: Future (2032) Background Traffic








120 Lusk Street







120 Lusk Street

### 5 Analysis

#### 5.1 Development Design

#### 5.1.1 Design for Sustainable Modes

The proposed development is located an approximate 630-metre walking distance from the existing bus stops serving Routes 70, 110 and 173 near the Citigate Drive and CrossKeys Place roundabout. The facilities on Fallowfield Road are limited to paved shoulders which provide poor level of service for pedestrians. The RMA for the Fallowfield Road & Forager Street intersection originally included a new southbound bus stop on Fallowfield Road south of O'Keefe Court, which would ultimately reduce the walking distance to transit to approximately 350m, however a bus stop at this location has now been deferred until after the signalization of this intersection.

A direct pedestrian connection is provided from Lusk Street to the proposed building's primary pedestrian entrance, complete with TWSIs, curb depressions and 'ladder crossings' to support a more comfortable and safe experience for vulnerable road users. A 1.8-metre wide concrete sidewalk is proposed around the perimeter of the building to prioritize access for individuals with a range of mobility needs.

The Transportation Demand Management (TDM) Supportive Development Design and Infrastructure Checklist was completed and is provided in **Appendix H**. This checklist includes the following measures which are being considered in association with the proposed development to offset the vehicular impact on the adjacent road network:

- Providing a designated area for carpool drivers (plus taxi and ride-hailing services) to drop off or pick up passengers at the main entrance without blocking the proposed fire route. To this end, select parking stalls within close proximity to the main building entrance will be reserved for pick-up and drop-off activities to help reduce single vehicle occupancy trips to/from the site.
- Secured and anchored bicycle parking spaces provided in a highly visible and lighted area with curb depressions to facilitate access to the internal drive aisle.

These measures are similar to those provided by adjacent developments.

#### 5.1.2 Circulation and Access

The internal drive aisle generally provides at least 6.7 metres of clear width throughout the site, as indicated on the site plan presented in **Exhibit 2** and is therefore in compliance with the Zoning By-law (2008-250). Drive aisle widths adjacent to compact vehicle parking spaces are also proposed at 6.7-metres, which is expected to sufficiently accommodate maneuverability associated with small passenger vehicles. In accordance with the by-law, the proportion of compact parking stall will not exceed 50% of the total on-site supply and will be clearly signed for 'small cars only'.

Vehicle turning templates for a fire truck, waste collection vehicle, delivery truck and Light Single Unit (LSU) which are expected to be the largest vehicles requiring access to the site, are presented in **Appendix I**.

#### 5.1.3 New Street Networks

Not Applicable: The New Street Networks element is exempt from this TIA, as defined in the study scope. This element is not required for Site Plan Control applications.

#### 5.2 Parking

#### 5.2.1 Parking Supply

Based on the size of the proposed development, a minimum of 124 vehicle parking spaces are required to meet the Zoning Bylaw requirements to support the various uses proposed on-site. The proposed development indicates that 125 vehicle parking spaces will be provided, including 5 accessible parking spaces. There are also 2 loading spaces with dimensions, in accordance with the Zoning Bylaw requirements. As such, the parking supply is within the permissible range.

The Zoning By-law also requires a minimum number of bicycle parking spaces to support the proposed development. A total of 11 bicycle parking spaces will be provided, meeting the 10 required parking spaces. As indicated on the site plan presented in **Exhibit 2**, these bike parking stalls will be provided in the northeast and southeast corners of the proposed multi-use building with sidewalks leading to the primary entrance and therefore will provide easy access for visitors or staff.

#### 5.3 Boundary Streets

#### 5.3.1 Mobility

There are three existing boundary streets adjacent to or within close proximity to the proposed development: O'Keefe Court, Lusk Street and Fallowfield Road. As discussed in Section 3.4, Segment-based Multi-Modal Level of Service (MMLOS) results for each of these road segments are provided in **Table 12** below.

Details of the MMLOS analysis are provided in **Appendix J**. The policy area used to derive the MMLOS targets was 'Employment Area'.

Table 12 – Segment-based MMLOS Results
--

	LEVEL OF SERVICE BY MODE						
LOCATION	PEDESTRIAN	BICYCLE	TRANSIT	TRUCK			
	(PLOS)	(BLOS)	(TLOS)	(TkLOS)			
EXISTING & FUTURE CO	ONDITIONS						
O'Keefe – Fallowfield to terminus	<b>F</b> (Target: C)	D (Target: N/A)	N/A <sup>1</sup>	B (Target: E)			
Lusk (south side) –	A	D	N/A <sup>1</sup>	B			
O'Keefe to terminus	(Target: C)	(Target: N/A)		(Target: E)			
Lusk (north side) –	<b>F</b>	D	N/A <sup>1</sup>	B			
O'Keefe to terminus	(Target: C)	(Target: N/A)		(Target: E)			
Fallowfield – Forager to O'Keefe	<b>D</b>	A	D	B			
	(Target: C)	(Target: C)	(Target: N/A²)	(Target: B)			

#### Notes

All modes presented in **Table 12** meet their respective targets, with the exception of the PLOS for segments of O'Keefe Court and Fallowfield Road.

On O'Keefe Court, operating speed would have to be reduced to 50km/h or less and a 1.5m concrete sidewalk would be required with at least a 0.5m boulevard width to meet the PLOS target. At this time, there is no indication that O'Keefe Court will be urbanized and therefore this deficiency

<sup>&</sup>lt;sup>1</sup> Transit LOS (TLOS) is not required for streets that are not transit routes.

<sup>&</sup>lt;sup>2</sup> TLOS targets are not provided for routes that are not identified as transit priority routes or rapid transit corridors.

cannot be addressed. A multi-use path located along the north side of the roadway, however, provides a safe off-road link to the broader pedestrian and cycling network.

The MMLOS results are shown separately for the north and south sides of Lusk Street, given the significant difference in the PLOS scores. Ultimately, the north side of Lusk Street will also feature a concrete sidewalk on the north side as part of the overall plan of subdivision which should result in a high PLOS of 'A' similar to the south side, however, until such time, the PLOS score will remain at 'F'. It is important to note, however, that Lusk Street is a local street and therefore City policies do not require sidewalks on both sides of these lower-order streets.

Fallowfield Road operates slightly above its target of 'C', with a PLOS of 'D'. Operating speeds would have to be reduced to less than 60km/h to achieve this PLOS score.

#### 5.3.2 Road Safety

A summary of all reported collisions within the study area over the past 5 years was presented in the Scoping section of this TIA. The City requires a safety review if at least six collisions for any one movement or of a discernible pattern, over a five-year period have occurred. Based on the review of re-occurring events identified in the Scoping section of this report, none of the study area roadway segments or intersections require further analysis.

#### 5.4 Access Intersections

#### 5.4.1 Location and Design of Access

The proposed development will provide a new full-movement access on Lusk Street approximately 75m west of the existing cul-de-sac. The new vehicular connection is in conformance with the City of Ottawa Private Approach By-law 2003-447, with particular confirmation of the following items:

- Width: A private approach should have a minimum width of 2.4m and a maximum width of 9.0m.
  - The proposed site access driveway will have a width of approximately 9.8 metres at the property line, however the private approach narrows significantly to about 7.2m immediately to the north and therefore this configuration should be considered acceptable with respect to this item in the Private Approach Bylaw.
- Quantity and Spacing of Private Approaches: For sites with frontages between 46 and 150 metres, one (1) two-way private approach and two (2) one-way private approaches or two (2) two-way private approaches are permitted. Any two private approaches must be separated by at least 9.0m and can be reduced to 2.0m in the case of two one-way driveways. On lots that abut more than one roadway, these provisions apply to each frontage separately.
  - ➤ The frontage on Lusk Street is approximately 85m and therefore the single proposed two-way private approach is compliant with the by-law. ✓
- <u>Distance from Property Line</u>: Private approaches must be at least 3.0m from the abutting property line, however this requirement can be reduced to 0.3m provided that the access is a safe distance from the access serving the adjacent property, sight lines are adequate and that it does not create a traffic hazard.
  - ➤ The proposed site access driveway is located approximately 4.5m and 72m from the eastern and western property boundaries, respectively. ✓

The Transportation Association of Canada's (TAC) Geometric Design Guide for Canadian Roads (June 2017) does not suggest a minimum clear throat length for a site access driveway proposed on a local road. The clear throat length is provided to ensure that any queues that form due to on-

site circulation blockages do not spillback onto collector or higher-order roads. Given the low traffic volumes typically expected on local roads including Lusk Street, occasional queue spillback is not likely to result in traffic operational issues.

#### 5.4.2 Access Intersection Control

The proposed site access driveway on Lusk Street will be stop-controlled.

#### 5.4.3 Intersection Design (MMLOS)

Not Applicable – The proposed site access driveway will be unsignalized, therefore Intersection-based Multi-Modal Level of Service (MMLOS) analysis is not required.

This driveway connection will be designed as per City Standard Drawing SC7.1 (March 2021) to provide continuous sidewalks across the vehicular connection and prioritize pedestrians.

#### 5.5 Transportation Demand Management (TDM) Program

The City of Ottawa is committed to implementing Transportation Demand Management (TDM) measures on a City-wide basis in an effort to reduce automobile dependence, particularly during the weekday peak travel periods. TDM initiatives are aimed at encouraging individuals to use non-auto modes of travel during the peak periods.

#### 5.5.1 Context for TDM

As discussed previously, the proposed development is located adjacent to Lusk Street within the 4401 Fallowfield Road subdivision. Infrastructure for active transportation modes is planned with a 2.0-metre wide concrete sidewalk on the north side of Lusk Street that will connect to a future 3.0-metre wide asphalt pathway that will provide a pedestrian link to the western portion of the 4401 Fallowfield Road subdivision.

#### 5.5.2 Need and Opportunity

With the development of the 4401 Fallowfield Road subdivision, there is an opportunity to increase the overall proportion of sustainable transportation trips within the surrounding community.

Mode share targets applied in this TIA were consistent with the Fallowfield Road subdivision and although the sustainable mode share targets aim to achieve a lower active transportation target in comparison with a typical blended rate, given the development's context and the suite of TDM measures outlined in the following section, it is expected that these targets will be achievable.

#### 5.5.3 TDM Program

The proposed development conforms to the City's TDM principles by providing convenient and direct connections to adjacent pedestrian and cycling facilities.

The City of Ottawa's TDM Measures Checklist was completed for the proposed development and is provided in **Appendix E**. This checklist indicates measures that are being contemplated as part of this development, including the following:

- Display local area maps with walking/cycling access routes and key destinations at major entrances;
- Display relevant transit schedules and route maps at entrances;
- > Unbundle parking costs from purchase price and lease rates at multi-tenant sites; and
- Provide a multimodal travel option information package to new residents and employees.

#### 5.6 Neighbourhood Traffic Management

#### 5.6.1 Adjacent Neighbourhoods

Not Applicable – The proposed development is not reliant on residential local or collector streets to access the arterial road network.

#### 5.7 Transit

#### 5.7.1 Route Capacity

Not Applicable - Transit route capacity analysis is not required to support the projected sitegenerated transit demands which are expected to be nominal.

#### 5.7.1 Transit Priority Measures

Transit priority measures are not required specifically to support the projected site-generated transit demands which are expected to be nominal. Additionally, none of the boundary streets are included in the 2013 TMP future rapid transit and transit priority (RTTP) network therefore no transit priority measures are anticipated to be implemented within the study area during the study period.

#### 5.8 Review of Network Concept

Not Applicable – The Network Concept element is exempt from this TIA, as defined in the study scope. This element is not required for proposed developments expected to generate less than 200 person-trips during the weekday morning and afternoon peak hours in excess of current zoning permissions.

#### 5.9 Intersection Design

The following sections summarize the methodology and results of the intersection warrant and multi-modal intersection capacity analyses conducted within the study area.

#### 5.9.1 Intersection Control

#### 5.9.1.1 Traffic Signal Warrants

Traffic signal warrants were completed for the Fallowfield & O'Keefe/Cobble Hill intersection. Based on the results of the analysis, traffic signals are warranted at this intersection under Future (2027) Background Traffic conditions.

The results of the traffic signal warrant analysis are provided in **Appendix K**.

#### 5.9.1.2 Roundabout Analysis

The feasibility of implementing a roundabout was evaluated at the intersection of Fallowfield & O'Keefe/ Cobble Hill. It was determined that this form of traffic control would not be feasible, given that only one of the suitability factors had been met. Further, the implementation of a roundabout is not consistent with the City's long-term vision for this location which is planned to be upgraded to a signalized intersection once the appropriate warrants are met.

The results of the Roundabout Feasibility Screening Tool are provided in **Appendix K**.

#### 5.9.2 Intersection Analysis Criteria (Automobile)

The following section outlines the City of Ottawa's methodology for determining motor vehicle Level of Service (LOS) at signalized and unsignalized intersections.

#### 5.9.2.1 Signalized Intersections

The City of Ottawa has developed criteria as part of the TIA Guidelines, which directly relate the volume to capacity (v/c) ratio of a signalized intersection and the overall delay of an unsignalized intersection to a LOS designation. These criteria are as follows:

Table 13 - LOS Criteria for Signalized and Unsignalized Intersections

1.00	SIGNALIZED INTERSECTIONS	UNSIGNALIZED INTERSECTIONS
LOS	VOLUME TO CAPACITY RATIO (v/c)	DELAY (seconds)
А	0 to 0.60	<10
В	0.61 to 0.70	>10 and <15
С	0.71 to 0.80	>15 and <25
D	0.81 to 0.90	>25 and <35
E	0.91 to 1.00	>35 and <50
F	> 1.00	>50

The Level of Service calculation is based on locally-specific parameters as described in the TIA Guidelines and incorporates existing signal timing plans obtained from the City of Ottawa. The existing conditions analysis utilized a Peak Hour Factor (PHF) of 0.90, while future conditions consider optimized signal timing plans and use of a Peak Hour Factor (PHF) of 1.0 to recognize peak spreading beyond a 15-minute period in congested conditions.

#### 5.9.3 Intersection Capacity Analysis

Following the established intersection capacity analysis criteria described above, the future conditions were analysed during the weekday peak hour traffic volumes derived in this study.

The following section presents the results of the intersection capacity analysis. All tables summarize study area intersection LOS results during the weekday morning and afternoon peak hour periods.

The Synchro output files have been provided in **Appendix F**.

#### 5.9.3.1 Future (2027) Background Traffic

An intersection capacity analysis has been undertaken using the Future (2027) Background Traffic volumes presented in **Exhibit 7**, yielding the following results:

Table 14 - Intersection Capacity Analysis: Future 2027 Background Traffic

		AM PEA	K HOUR	PM PEA	K HOUR
INTERSECTION	TRAFFIC CONTROL	OVERALL LOS	CRITICAL MOVEMENTS	OVERALL LOS	CRITICAL MOVEMENTS
		(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)
Fallowfield Road	Unsignalized	F	WBTRL	F	EBL
& O'Keefe Court /	3	(168.0s)	(168.0s)	(422.2s)	(422.2s)
Cobble Hill Drive	Signalized	A (0.60)	SBT (0.60)	B (0.68)	SBT (0.68)
Lusk Street & O'Keefe Court	Unsignalized	A (8.5s)	NBRL (8.5s)	A (9.5s)	NBRL (9.5s)
Fallowfield Road & Forager Street	Unsignalized	C (15.0s)	EBR (15.0s)	C (18.6s)	EBR (18.6s)

As shown above, the Fallowfield & O'Keefe/Cobble Hill intersection is operating at an LOS 'F' as an unsignalized intersection under Future (2027) Background conditions. As the traffic signal warrants for this intersection were triggered under these conditions, the remaining intersection capacity analysis will only include an evaluation with traffic signals at this location.

With signalization, the Fallowfield & O'Keefe intersection is expected to operate at an acceptably (LOS 'D' or better), along with the other study area intersections without any modifications under Future (2027) Background Traffic conditions.

#### 5.9.3.2 Future (2032) Background Traffic

An intersection capacity analysis has been undertaken using the Future (2032) Background Traffic volumes presented in **Exhibit 8**, yielding the following results:

Table 15 - Intersection Capacity Analysis: Future 2032 Background Traffic

		AM PEA	K HOUR	PM PEA	K HOUR
INTERSECTION	TRAFFIC CONTROL	OVERALL LOS (V/C OR DELAY)	CRITICAL MOVEMENTS (V/C OR DELAY)	OVERALL LOS (V/C OR DELAY)	CRITICAL MOVEMENTS (V/C OR DELAY)
Fallowfield Road & O'Keefe Court / Cobble Hill Drive	Signalized	C (0.76)	SBT (0.76)	C (0.78)	NBT (0.78)
Lusk Street & O'Keefe Court	Unsignalized	A (8.5s)	NBRL (8.5s)	A (9.5s)	NBRL (9.5s)
Fallowfield Road & Forager Street	Unsignalized	C (18.7s)	EBR (18.7s)	C (20.8s)	EBR (20.8s)

All study area intersections are shown to operate acceptably (LOS 'D' or better) under Future (2032) Background Traffic conditions.

#### 5.9.3.3 Future (2027) Total Traffic

An intersection capacity analysis has been undertaken using the Future (2027) Total Traffic volumes presented in **Exhibit 9**, yielding the following results:

Table 16 - Intersection Capacity Analysis: Future 2027 Total Traffic

		AM PEA	K HOUR	PM PEAK HOUR	
INTERSECTION	TRAFFIC CONTROL	OVERALL LOS	CRITICAL MOVEMENTS	OVERALL LOS	CRITICAL MOVEMENTS
		(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)
Fallowfield Road & O'Keefe Court / Cobble Hill Drive	Signalized	B (0.62)	SBT (0.62)	C (0.77)	SBT (0.77)
Lusk Street & O'Keefe Court	Unsignalized	A (8.6s)	NBRL (8.6s)	A (9.7s)	NBRL (9.7s)
Fallowfield Road & Forager Street	Unsignalized	C (15.6s)	EBR (15.6s)	C (21.3s)	EBR (21.3s)

All study area intersections are shown to operate acceptably (LOS 'D' or better) under Future (2027) Total Traffic conditions.

#### 5.9.3.4 Future (2032) Total Traffic

An intersection capacity analysis has been undertaken using the Future (2032) Total Traffic volumes presented in **Exhibit 10**, yielding the following results:

Table 17 - Intersection Capacity Analysis: Future 2032 Total Traffic

		AM PEAK HOUR			PM PEAK HOUR	
INTERSECTION	TRAFFIC CONTROL	OVERALL LOS	CRITICAL MOVEMENTS	OVERALL LOS	CRITICAL MOVEMENTS	
		(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)	(V/C OR DELAY)	
Fallowfield Road & O'Keefe Court / Cobble Hill Drive	Signalized	C (0.78)	SBT (0.78)	D (0.85)	SBT (0.85)	
Lusk Street & O'Keefe Court	Unsignalized	A (8.6s)	NBRL (8.6s)	A (9.7s)	NBRL (9.7s)	
Fallowfield Road & Forager Street	Unsignalized	C (19.7s)	EBR (19.7s)	C (24.4s)	EBR (24.4s)	

All study area intersections are expected to continue operating at an acceptable Level of Service (LOS 'D' or better) under Future (2032) Total Traffic conditions, with traffic signals installed at the Fallowfield & O'Keefe/Cobble Hill intersection.

#### 5.9.4 Intersection Design (MMLOS)

An analysis of conditions for each mode has been conducted based on the methodology prescribed in the 2017 Multi-Modal Level of Service Guidelines. The Level of Service for each mode has been calculated for each intersection where traffic signals exist or are anticipated.

For the purposes of the MMLOS analysis undertaken for this study, the Fallowfield & O'Keefe Court intersection was assumed to maintain its existing vehicular lane geometry. The introduction of 'protected intersection' elements would greatly improve the overall MMLOS scores for actives modes.

The Future (2032) Total Traffic intersection MMLOS results have been summarized in **Table 18** below. Detailed analysis results are provided in **Appendix J**.

Table 18 - Intersection MMLOS - Future Conditions

	LEVEL OF SERVICE BY MODE					
LOCATION	PEDESTRIAN	BICYCLE	TRANSIT	TRUCK		
	(PLOS)	(BLOS)	(TLOS)	(TkLOS)		
INTERSECTION						
Fallowfield & O'Keefe/	<b>F</b>	<b>F</b>	D	<b>F</b>		
Cobble Hill	(Target: C)	(Target: C)	(Target: N/A¹)	(Target: B)		

Notes: <sup>1</sup> Not identified as a transit priority corridor in the TMP.

#### 5.9.4.1 Summary of Potential Improvements

Based on the MMLOS results outlined in **Table 18** above, the following measures have been identified which could improve conditions for each travel mode:

#### <u>Pedestrians</u>

The PLOS at intersections is based on several factors including the number of traffic lanes that pedestrians must cross, corner radii, and whether the crossing allows for permissive or protective right or left turns, among others. The City of Ottawa target for PLOS in an Employment Area is 'C'.

The results of the analysis indicate that the intersection of Fallowfield & O'Keefe/Cobble Hill is expected to operate at PLOS 'F', primarily as a result of the effective number of lanes required to cross (crossing distance/3.5m) in combination with expected pedestrian delays. Providing enhanced pedestrian features such as a median, pedestrian leading interval, zebra stripe high-visibility crosswalk markings on the north and south approaches would reduce the level of pedestrian exposure on those crossings. The above features in combination with a reduced pedestrian crossing width of no more than 14 metres would achieve a PLOS of 'C'. It should be noted, however, that a reduction in the cycle length may result in negative impacts to the vehicle level of service. Alternatively, a 'protected intersection' design would help achieve the PLOS target.

#### **Cyclists**

The BLOS at intersections is dependent on several factors: the number of lanes that the cyclist is required to cross to make a left-turn; the presence of a dedicated right-turn lane on the approach; and the operating speed of each approach. The City target for BLOS in the Employment Area on a 'Spine Route' is 'C'.

The results of the analysis indicate that cycling facilities at the Fallowfield & O'Keefe/Cobble Hill intersection are not sufficient to achieve the BLOS target. Given the high operating speeds at this location, only the provision of physically separated cycling facilities with two-stage, left-turn bike

boxes on all approaches will be sufficient to achieve the BLOS target. Alternatively, a 'protected intersection' design would help attain the BLOS target and would help to complement the future urbanization of Fallowfield Road.

#### **Transit**

Intersection TLOS is based on the average signal delay experienced by transit vehicles on each approach. According to the MMLOS Guidelines, there is no target for TLOS on roads that are not designated as either a rapid transit or transit priority corridors in the TMP.

The results of the analysis indicates that the Fallowfield & O'Keefe/Cobble Hill intersection is anticipated to operate with average delays ranging from about 10s to 25s during the weekday peak hours, however as there are no frequent transit routes that utilize either side street approach, neither is factored into the TLOS calculation. Both the northbound and southbound approaches currently are expected to also experience relatively minor delays of 15s to 25s or less upon signalization of the Fallowfield & O'Keefe/Cobble Hill intersection which results in an overall intersection TLOS of 'D'.

#### Trucks

The Truck LOS (TkLOS) is based on the right-turn radii, as well as the number of receiving lanes for vehicles making a right-turn from the traffic lane being analyzed. The TkLOS target for Truck Routes on arterial or collector roads in the General Urban Area is 'B'.

Overall, the intersection TkLOS target is not attainable as it would require an increased right-turn radius to 10-15m and/or an increase to more than two receiving lanes on departure from intersection. However, turning movement count data indicates that trucks infrequently utilize Cobble Hill Drive, which is consistent with its classification as a local road and non-truck route. Given that its primary function is to provide access to adjacent residential subdivisions with infrequent transit movements, the existing right-turn radii is considered acceptable in this context. It should be noted that the right-turn radii to/from O'Keefe Court meets the TkLOS target, which is appropriate given that the Highway 416 Lands development is expected to generate regular truck traffic.

The recommended measures listed above are intended only as suggestions to the City on how the MMLOS within the study area could be improved and do not identify measures to be implemented as a direct consequence of this development. The remediation measures described above would improve mobility and comfort for pedestrians and cyclists but are not required to accommodate the proposed development.

#### 5.10 Geometric Review

The following section provides a review of all geometric requirements for the study area intersections.

#### **Sight Distance and Corner Clearances**

The proposed site access driveway is being proposed on Lusk Street. This local road will have low vehicle volumes and operating speeds, given its classification and termination in a cul-de-sac west of the site. Further, there are no signalized or stop-controlled intersections within close proximity to the proposed site access driveway. As such, sightline visibility and corner clearance are not a concern with respect to the proposed access location.

#### 5.10.2 Auxiliary Lane Analyses

An evaluation of auxiliary turning lane requirements for all study area intersections is summarized in the following sub-sections:

#### 5.10.2.1 Auxiliary Left-Turn Lane Requirements (Unsignalized)

The intersection of O'Keefe Court & Lusk Street does not warrant an auxiliary left-turn lane based on the advancing and opposing volumes projected at this intersection under Future (2032) Total Traffic conditions.

The Fallowfield & Forager intersection is restricted to right-in/right-out movements, therefore it was not necessary to assess left-turn lane requirements at this intersection.

The results of the left-turn lane warrant analysis are provided in **Appendix L**.

#### 5.10.2.2 Auxiliary Left-Turn Lane Requirements (Signalized)

As the intersection of Fallowfield/O'Keefe has been shown to require signalization, a review of auxiliary left-turn lane storage requirements was completed under Future (2032) Total Traffic conditions, comparing the highest queue lengths on each intersection approach under weekday morning and afternoon peak hours. The review compared the projected 95th percentile queue lengths from Synchro operational results, and the standard queue length calculation based on the following equation:

Storage Length = 
$$\frac{NL}{C} \times 1.5$$

Where:

N = number of vehicles per hour

L = Length occupied by a vehicle in the queue = 7 m

C = number of traffic signal cycles per hour

The results of the auxiliary left-turn lane analysis are summarized below in **Table 19** below.

Table 19 - Auxiliary Left-Turn Storage Analysis at Signalized Intersections

INTERSECTION	APPROACH	95TH %ILE QUEUE LENGTH AM/PM (M)	CALCULATED QUEUE LENGTH AM/PM (M)	EXISTING PARALLEL LENGTH (M)	STORAGE DEFICIENCY (M)
	NB	40/35	45/25	140	Existing Storage Adequate
Fallowfield Road &	SB	5/15	5/10	60	Existing Storage Adequate
O'Keefe Court / Cobble Hill Drive	EB	15/30	10/35	50	Existing Storage Adequate
	WB	15/15 <sup>1</sup>	10/5	-	Existing Storage Adequate <sup>2</sup>

Notes: 1 Synchro queues were determined based on existing shared lane configuration

As per the results of the queue length analyses presented **Table 19** above, the existing parallel lanes have sufficient storage to accommodate the projected Future (2032) Total Traffic demand. As such, no modifications to the existing auxiliary lanes are required for signalization of this intersection within the timeframe of this study.

<sup>&</sup>lt;sup>2</sup> Through volumes are nominal during weekday peak hours (i.e. less than 10 veh/h)

#### 5.10.2.3 Auxiliary Right-Turn Lane Requirements (Unsignalized)

The Transportation Association of Canada (TAC) suggests that auxiliary right-turn lanes be considered "when the volume of decelerating or accelerating vehicles compared with through vehicles causes undue hazard." Consideration for auxiliary right-turn lanes is typically given when the right-turning traffic exceeds 10% of the through volume and is at least 60 vehicles per hour.

The Fallowfield & Forager intersection was constructed with a southbound auxiliary right-turn lane that includes sufficient lengths to accommodate vehicle storage requirements which are anticipated to be minimal, therefore no modifications are required to this lane within the timeframe of this study.

#### 5.10.2.4 Auxiliary Right-Turn Lane Requirements (Signalized)

Similarly for signalized intersections, Section 9.14 of TAC suggests that auxiliary right-turn lanes shall be considered when more than 10% of vehicles on an approach are turning right and when the peak hour demand exceeds 60 vehicles. The purpose of this guideline is to mitigate operational impacts to through-traffic, particularly on high-speed arterial roadways such as Fallowfield Road, and may not be applicable in all circumstances. The highest of the weekday morning and afternoon peak hour volumes under Future (2032) Total Traffic conditions were considered in this evaluation.

The results of the auxiliary right-turn lane analysis are summarized in Table 20 below.

Table 20 – Auxiliary Right-Turn Lane Storage Analysis at Signalized Intersections

INTERSECTION	APPROACH	RIGHT TURN VOLUME	APPROACH VEHICLES TURNING RIGHT (%)	95TH %ILE QUEUE LENGTH (M)	EXISTING PARALLEL LENGTH (M)	STORAGE DEFICIENCY (M)
	NB	47	4%	<10	115	Existing Storage Adequate
Fallowfield &	SB	111	10%	<10	25	Existing Storage Adequate
O'Keefe/Cobble Hill	EB	126	45%	15 <sup>1</sup>	-	Existing Storage Adequate <sup>2</sup>
	WB	69	62%	15 <sup>1</sup>	-	Existing Storage Adequate <sup>2</sup>

Notes: <sup>1</sup> Synchro queues were determined based on existing shared lane configuration

Based on the traffic volumes projections developed for this TIA and a review of the 95<sup>th</sup> percentile queue lengths on each approach, no additional right-turn facilities are expected to be required as a result of projected background or site-generated traffic volumes at the Fallowfield & O'Keefe/Cobble Hill intersection with traffic signals under Future (2032) Total Traffic conditions.

<sup>&</sup>lt;sup>2</sup> Through volumes are nominal during weekday peak hours (i.e. less than 10 veh/h)

## 5.11 Summary of Improvements Indicated and Modification Options

As per the intersection capacity, Multi-Modal Level of Service and auxiliary lane analyses results presented above, off-site improvements to the adjacent road network have been recommended in order to accommodate the transportation demands of both background and site-generated traffic. The MMLOS results indicate existing deficiencies with respect user comfort and safety that could be considered for implementation by the City but are not required to safely accommodate the proposed development.

#### 5.11.1 Fallowfield Road & O'Keefe Court/Cobble Hill Drive

Fallowfield & O'Keefe/Cobble Hill is presently operating as a two-way stop-controlled intersection. The results of the analysis indicate that, by 2027, traffic signals will be operationally required and warranted at this junction under background traffic conditions. As indicated in **Exhibit 6**, the proposed development is expected to contribute up to 133 vehicle trips to this intersection during the weekday peak hours. With traffic signals in place, the intersection would be expected to operate at an acceptable level of service (i.e. LOS 'D') under Future (2032) Total Traffic conditions. If traffic signals are not implemented by the 2027 study analysis year, the results of the analysis indicate that delays of at least 5 minutes are expected at the Fallowfield & O'Keefe intersection with or without the inclusion of site-generated traffic. It is recommended that the City monitor this intersection on an annual basis to determine the appropriate timing for its signalization.

An analysis of auxiliary lane requirements found available storage at this intersection is sufficient and can accommodate future travel demands within the context of this study.

As identified through intersection-based MMLOS analysis conducted for Fallowfield & O'Keefe, various measures would need to be implemented in order to achieve the PLOS an BLOS targets. To attain the PLOS target, zebra stripe high-visibility crosswalk markings, a Leading Pedestrian Interval (LPI) and a minimum 2.4-metre wide median on the northbound/southbound approaches are required in conjunction with a reduced pedestrian crossing width to no more than four effective lane widths. The implementation of bike lanes or higher-order cycling facilities on all approaches, along with two-stage, left-turn bike boxes are required to meet the BLOS targets. Alternatively, a 'protected intersection' design with fully-integrated pedestrian and cycling facilities will help attain the PLOS and BLOS targets. These features should be considered by the City upon signalization of this intersection but are not required to safely accommodate site-generated traffic.

#### 5.11.2 O'Keefe Court & Lusk Street

The O'Keefe & Lusk intersection is expected to operate at a high level of service (i.e. LOS 'A') beyond the 2032 horizon year of this study with stop control on Lusk Street and free-flow on O'Keefe Court.

The auxiliary lane analyses conducted as part of this study indicates that left- or right-turn auxiliary lanes are not required on any of the intersection approaches within the timeframe of this study.

#### 5.11.3 Fallowfield Road & Forager Street

The Fallowfield & Forager intersection was constructed with a diverter island to restrict turning movements to right-in/right-out. With these restrictions in place, the intersection is expected to operate at LOS 'C' or better within the timeframe of this study.

#### 6 Conclusion

The proposed development at 120 Lusk Street is expected to generate up to 117 and 133 two-way vehicular trips during the weekday morning and afternoon peak hours, respectively. The mode share targets were developed based on the South Nepean Traffic Assessment Zone (TAZ) and adjusted proportionally, in accordance with the Conditions of Approval for 4401 Fallowfield Road, to yield an 85% auto/15% non-auto mode share split.

Fallowfield & O'Keefe/Cobble Hill is presently configured as a two-way stop-controlled intersection and is operating at a LOS 'F' during the critical weekday afternoon peak hour, according to the capacity analysis conducted for this study. By 2027, traffic signals will be warranted under background traffic conditions in addition to being operationally required. With traffic signals in place, the intersection would be expected to operate at LOS 'D' under the critical weekday afternoon peak hour beyond the study horizon year. If traffic signals are not implemented by the 2032 study horizon year, delays of at least 5 minutes are expected at the Fallowfield & O'Keefe intersection with or without the inclusion of site-generated traffic. As site-generated traffic will not contribute significantly to any potential traffic operational issues at this intersection, it is recommended that the City continue monitoring this location on an annual basis to determine the appropriate timing for the introduction of traffic signals.

The results of the analysis indicate that the intersections of O'Keefe Court & Lusk Street and Fallowfield Road & Forager Street are expected to operate within acceptable standards (LOS 'D' or better) during the weekday morning and afternoon peak hours. Both are T-intersections that are configured with stop control on the minor road and are not expected to require additional auxiliary lanes or future modifications within the timeframe of this study.

A multi-modal analysis identified deficiencies in the existing road network and potential remediation measures have been suggested which the City could consider to meet these prescribed targets. It should be noted that, although these measures would improve for a range of transportation modes, they are not required to safely accommodate the transportation demands of the proposed development.

Roadway modifications (RMA-2019-TPD-041B) were implemented in 2021, including a right-in/right-out intersection at Fallowfield & Forager and a multi-use path along the west side of Fallowfield Road between O'Keefe Court to just south of Forager Street. It is understood that the southbound bus stop originally proposed as part of this RMA has been deferred until traffic signals are implemented at the Fallowfield & O'Keefe/Cobble Hill intersection.

All study area intersections were shown to operate well within the capacity constraints of the adjacent transportation network, with the signalization of the Fallowfield & O'Keefe/Cobble Hill intersection by 2027. Given that installation of traffic signals would be required to support existing and future background growth in travel demand and is the only mitigation measure recommended to accommodate Future (2032) Total Traffic conditions, a Post-Development Monitoring Plan is therefore not a requirement of this study.

Based on the findings of this study, it is the overall opinion of Arcadis that the proposed development will integrate well with and can be safely accommodated by the adjacent transportation network with the recommended actions and modifications in place.

## Appendix A – TIA Screening Form



## **City of Ottawa 2017 TIA Guidelines Screening Form**

1. Description of Proposed Develop	oment
Municipal Address	120 Lusk Street, Ottawa, Ontario.
Description of Location	The proposed development is located on the north side of the cul-desac at the end of Lusk Street. It is bordered by O'Keefe Court to the north and currently undeveloped lands to the east and west.
Land Use Classification	Sit-down Restaurant, Medical Uses, General Office, Pharmacy Daycare Centre
Development Size (units)	N/A
Development Size (m²)	Sit-down Restaurant - ~193 m <sup>2</sup> Medical Uses - ~1,375 m2 (~14,801 ft2)  General Office - ~1,481 m2 (~15,962 ft2)  Pharmacy - ~185 m2 (~1,992 ft2)  Daycare Centre - ~374 m2 (~4,022 ft2)
Number of Accesses and Locations	One (1) proposed full-movement site access driveway on Lusk Street
Phase of Development	Single Phase




#### Transportation Impact Assessment Screening Form

Buildout Year	2027	



If available, please attach a sketch of the development or site plan to this form.





#### 2. Trip Gen Trigger

Considering the Development's Land Use Type and Size (as filled out in the previous section), please refer to the Trip Generation Trigger checks below.

Land Use Type	Minimum De	evelopment Size
Single-family homes	40 units	
Townhomes or apartments	90 units	
Office	3,500 m <sup>2</sup>	
Industrial	5,000 m <sup>2</sup>	
Fast-food restaurant or coffee shop	100 m <sup>2</sup>	
Destination Retail	1,000 m <sup>2</sup>	
Gas Station or convenience market	75 m <sup>2</sup>	

The proposed development does not specifically trigger any of the minimum development sizes for the respective land uses presented in the Table above. Based on the Institute of Transportation Engineers' (ITE) Trip Generation Manual (11th Edition), the person-trip generation for the proposed development is expected to be in the range of 179 to 205 person trips per weekday peak hour. Since these person-trip estimates exceed the 60-person trip threshold established in the 2017 TIA Guidelines, the Trip Generation Trigger is satisfied.

\*If the development has a land use type other than what is presented in the table above, estimates of person trip generation may be made based on average trip generation characteristics represented in the current edition of the Institute of Transportation Engineers (ITE) Trip Generation Manual.

Based on the above, the Trip Generation Trigger is satisfied.



3. Location Triggers		
	Yes	No
Does the development propose a new driveway to a boundary street that is designated as part of the City's Transit Priority, Rapid Transit or Spine Bicycle Networks?		<b>√</b>
Is the development in a Design Priority Area (DPA) or Transit-oriented Development (TOD) zone?*		<b>√</b>

<sup>\*</sup>DPA and TOD are identified in the City of Ottawa Official Plan (DPA in Section 2.5.1 and Schedules A and B; TOD in Annex 6) See Chapter 4 for a list of City of Ottawa Planning and Engineering documents that support the completion of TIA.

#### Based on the above, the Location Trigger is not satisfied.

4. Safety Triggers		
	Yes	No
Are posted speed limits on a boundary street 80km/hr or greater?		✓
Are there any horizontal/vertical curvatures on a boundary street that limit sight lines at a proposed driveway?		<b>√</b>
Is the proposed driveway within the area of influence of an adjacent traffic signal or roundabout (i.e. within 300 m of intersection in rural conditions, or within 150 m of intersection in urban/suburban conditions?)		<b>√</b>
Is the proposed driveway within auxiliary lanes of an intersection?		✓
Does the proposed driveway make use of an existing median break that serves an existing site?		<b>√</b>
Is there a documented history of traffic operations or safety concerns on the boundary streets within 500 m of the development?		<b>√</b>
Does the development include a drive-thru facility?		<b>√</b>

Based on the above, the Safety Trigger is not satisfied.



5. Summary		
	Yes	No
Does the development satisfy the Trip Generation Trigger?	✓	
Does the development satisfy the Location Trigger?		✓
Does the development satisfy the Safety Trigger?		✓

Based on the results of the TIA Screening Form, the Trip Generation Trigger is satisfied. As such, a TIA is required for the proposed development.


## Appendix B – Proposed Development Site Plan


ZONING BY-LAW 2008-250 CONSOLIDATION				PARK INDUSTR
			2.100	(65]H(12)
ZONING MECHANISMS(TABLE 205)			REQ'D	PROVIDED
(a)LOT AREA			750 SQ/A	6040.28
(c)MAX. LOT COVERAGE			55%	22%
(d)MIN. FRONT YARD , O'KEEFE COURT			MIN 6m MIN 3m	6m 3m
(e)MIN. INTERIOR SIDE YARD			MIN3m	18.90m
(e)MIN, INTERIOR SIDE YARD			MIN 6m	50.57m
(f) MIN. REAR YARD , LUSK ST.			MAX 2	0.6
(g)MAX. FLOOR SPACE INDEX			12m	9.1 m
(h) MAX. BUILDING HEIGHT ((MEASURED FROM GRADE TO T/O ROOF DECK)  (I) MIN WIDTH OF LANDS CAPING			12111	7.( III
(ii)ABUTING A STREET			3m	3.06m
(iii) IN ALL OTHER CASES			NO MN.	1m
COVERAGE CALCULATION	SM	SF	ACRES	%
SITE AREA	6040.28	65,017	1.5	100%
BUILDING AREA	1,301	14,006	55873	22%
PAVED AREA	3.305.08	35,576		55%
LANDSCAPED AREA-INCL SIDEWALK AND PATIO	1,434	15,435		24%
TOTAL CONSTRUCTION AREA			SM	SF
BASEMENT FLOOR			474	5,102
BASEMENT FLOOR 1STFLOOR			1,288	13,864
2ND FLOOR			1,301	14,006
2ND FLOOR 3RD FLOOR			1,301	14,006
TOTAL CONSTRUCTION AREA			4,364	46,978
277778 10.27 10.20 10.27			SM	SF
GFA (LEASABLE SPACES) CALCULATIONS			187	2.010
GROUND FLOOR-RESTAURANT			371	3,991
GROUND FLOOR-MEDICAL OFFICES			185	1,992
GROUND FLOOR-PHARMACY			374	4.022
GROUND FLOOR-DAYCARE			502	5.405
2ND FLOOR-MEDICAL OFFICES			558	6,014
2ND FLOOR- OFFICES			502	5,405
3RD FLOOR-MEDICAL OFFICES			558	6.014
3RD FLOOR- OFFICES			365	3,934
BASEMENT-OFFICES			3.602	38.787
TOTAL GFA			3,802	38,787
PARKING REQUIREMENTS (BASED ON TABLE 101; AREA "C" ON SCHEDULE 1A) -SPACES @ 2.6W x 5.2L -50% of stalls are compact stalls (size at 2.4W x 4.6L per zoning standards)	GFA (M2)	PARKING RATE	REQ'D	PROVIDED
RESTAURANT: 10 PARKING SPACE PER 100m² OF GFA	187	0.100	18.7	
MEDICAL OFFICES (4 PARKING SPACE PER 100m² OF GFA)	1,375	0,040	55.0	
ACCESSORY TO THE MEDICAL FACILITIES (PHARMACY) (4 PARKING SPACE PER 100m²	185	0.040	7.4	
OF GFA)	374	0.020	7.5	
DAYCARE (2 PARKING SPACE PER 100 m² OF GFA)	1.481	0.024	35.5	
OFFICES (2.4 PARKING SPACE PER 100m <sup>a</sup> OF GFA.)	1,401	0.024	124.1	125
TOTAL NO. OF PARKING SPACES			124.1	1000
ACC. & STANDARD SPACES				63
COMPACT CAR SPACES			REQ'D	62 PROVIDED
ACCESSIBLE PARKING (CITY OF OTTAW A ACCESSIBILITY DESIGN STANDARDS)			REQ'D	PROVIDED 5
101-133 PARKING SPACES, THEN 5 ACCESSIBLE SPACES REQ/D			2	2
TYPE A (VAN), MIN WIDTH=3400			3	3
TYPEB, MIN WIDTH=2400	GFA		REQ'D	9 PROVIDED
BICYCLE PARKING (TABLE 111A)	2.042		REQ'D	PROVIDED
(e)RESTAURANT, DAYCARE, OFFICES, 1 BICYCLE PARKING/ 250 m² OF GFA	2,042		1.6	
(g)MEDICAL OFFICES,1 BICYCLE PARKING/ 1000m² OF GFA	1,560		CARBA	
TOTAL BICYCLE PARKING			9.7	11
			REQ'D (MIN)	PROVIDED
DRIVEWAYS AND AISLE REQUIREMENTS (SECTION 107)			(MIN)	6.7
TW O-W AY DRIVEW AY			6.7	6.7
TWO-W AY PARKING AISLE MINIMUM WIDTH IN METRES OF AISLE ACCESSING LOADING SPACE, BY ANGLE OF			(8.6.)	(2.5)
MINIMUM WIDH IN MEIRES OF AISLE ACCESSING LOADING SPACE, BY ANGLE OF LOADING SPACE			9.0	9.5
LOADING REQUIREMENTS (SECTION 113) (SIZE: 3.5Wx9.0L PARALLEL: 3.5Wx9.0 OTHER; 4.2M VERT.CLR)	GFA		REQ'D	PROVIDED
MEDICAL OFFICES (b) OFFICES, RESEARCH AND DEVELOPMENT CENTER, 1000-1999 m2,	1.560		1	
REGUIRE 1 LOADING SPACE OFFICES (b)OFFICES, RESEARCH AND DEVELOPMENT CENTER, 1000-1999 m2, REQUIRE 1 LOADING SPACE	1,481		i.	
	187		0	
(d) ALL OTHER NON-RESIDENTIAL USERS, <u>RESTAURANT</u> :350m <sup>2</sup> <gfa<999m<sup>2, REQUIRE 0 LOADING SPACE</gfa<999m<sup>	10/		"	



2 KEY PLAN ASP-1 N.T.S

		SITE PL	AN	LEC	GEND				]
	PROPERTY LINE				+	RECESSED EXTERIOR LIGHT FIXTURE @ -REFER TO ELECTRICAL DWGS	SOFFI	T & PROTE COCHERE	
	BUILDING SETBACK LINE				111:111	NEW HEAVY DUTY ASPHALT PAVING	(REMA	INDER OF THE SITE TO RECEIVE	
	LANDSCAPE BUFFER				7.41714	LIGHT DUTY ASPHALT PAVING)			
CD	CURB DEPRESSION					DECORATIVE NON-SLIP SURFACE PA	VING I	UNDER PORTE COCHERE	
	ENTRY/ EXIT ACCESS PO	INTS			111111111111111111111111111111111111111	(REFER TO LANDSCAPE DWGS)			
¤	EXISTING TOWN HYDRAN	NT			14/4/65	LANDSCAPED AREA			
	PROPOSED LOCATION O -REFER TO CIVIL DWGS	OF NEW FIRE HYDRANT W/ STEEL BOLLARD	DS		1944 - 1944 1944 - 1944	POURED CONCRETE PAD AT LOADIN	IG ARI	EA & WASTE COLLECTION	
\$≈	FIRE DEPARTMENT CONF	NECTION			N N NA NO.	STEEL BOLLARD (REFER TO DETAIL XX.	VI		
44	HOSE BIB (REFER TO MED	CHANICAL DWGS)			(x)	PARKING COUNT	.nj		
	PAD MOUNTED HYDRO	TRANSFORMER W/ STEEL BOLLARDS			104.04×	PROPOSED GRADING (REFER TO CIV	IL DW	GS)	
	DOUBLE HEADED LIGHT	FIXTURE ON CONCRETE BASE		-		CONDENSING UNIT ON 4" CONCRET	E PAD	(REFER TO MECH DWGS)	
<u>□</u> →□	-REFER TO ELECTRICAL	TATORE OT CONCRETE BYDE		_	<i>677777</i> 71	SNOW STORAGE AREA (OWNER TO I SNOW REMOVAL COMPANY)	AKE N	IECESSARY PRECAUTIONS W/	
₽	SINGLE HEADED LIGHT I -REFER TO ELECTRICAL E	FIXTURE ON CONCRETE BASE DWGS			i/////////////////////////////////////				
₽	SINGLE HEADED LIGHT I OUTLET -REFER TO ELECTRICAL D	FIXTURE ON CONCRETE BASE W/ ELECTRIC DWGS	CAL						
CREDIT NOTES	3:	CREDIT NOTES:	$\prod$			SITE PLAN- GENE	RAL	. NOTES	
READ IN CONJUNCTHIS PROPERTY, MA	SED UPON AND MUST BE CTION WITH THE SURVEY FOR LTAJ ARCHITECTS ACCEPTS FOR THE ACCURACY, OR	TOPO SURVEYORS INFO: ANNIS, O'SULLIVAN, VOLLEBEKK LTD.		1	AN DBOULEVARD AR CONSTRUCTION MUS	ENT, CURBS, SIDEWALKS, DRIVEWAYS EAS DISTURBED BY THE T BE REINSTATED TO THE	5	THE OWNER/ CONTRACTOR S AND BARRIER-FREE SIGNS AS S BY-LAWS AND DESIGN CRITER	SET OUT IN THE TOWN
COMPLETENESS OF	THE DATA SUPPLIED AND INCLUDED UNDER SEALS	14 Concourse Gate, Suite 500 Nepean, Ont. K2E 7S6 Phone: (613) 727-0850 PHONE: (519) 742-8371		2	PROPOSED DRIVEWA	OF 1.0m FROM STREET FURNITURE TO YS AND SIDEWALKS SHALL BE STING STREET FURNITURE TO BE	6	ALL EXTERIOR ILLUMINATION T AS WELL AS INWARD AND DES CUTOFF LIGHT DISTRIBUTION A	SIGNED TO MAINAIN ZERO
LEGAL LAND DESC	RIPTION:	Email: Népeán@aovltd.com			OF 1.0m. THE COST C	INTRACTOR/OWNER TO A SETBACK OF RELCOATION OF ANY UTILITY IS THE E DEVELOPER/OWNER	7	ALL DOWNSPOUTS TO BE CO DRAINAGE SYSTEM	ONNECTED TO THE STOR
Block 2 REGISTERED PLAN 4	IM-1634		lt	3		OWNER IS RESPONSIBLE FOR ALL DAMAGE/ DISTURBANCE DURING	8	ALL CONDENSING UNITS TO B GROUND FLOOR	E SCREENED ON THE
CITY OF OTTAWA				4	CONSTRUCTION.	TRANCES AND BARRIER FREE PATHS	9	SEPARATE PERMITS ARE RE ON THE PROPERY	QUIRED FOR ANY SIGNA
						MPLY WITH O.B.C. 3.8.	10	WHERE POSSIBLE TREES ARE TO CONSTRUCTION	D BE PROTECTED FROM





1 2024/11/29 Issued for SPA Date: Issue/Revision

**WORK IN PROGRESS** 





**LUSK MEDICAL** 

120 Lusk Street, Ottawa ON.

PROPOSED SITE PLAN

Design By: M.A./S.F. D.A. AS SHOWN 2024.05.16 Project No.: 22-043

ASP-1

A.M.

ARCHITECTURAL - SPA

## Appendix C – OC Transpo Routes




## 70

## LIMEBANK FALLOWFIELD


## Local

## 7 days a week / 7 jours par semaine All day service Service toute la journée





2025.05





# 110


## **LIMEBANK**

## INNOVATION BRIARBROOK

## Local


## 7 days a week / 7 jours par semaine

All day service Service toute la journée



2025.04

Limebank





## 173

## BARRHAVEN CENTRE CITIGATE

## Local

## 7 days a week / 7 jours par semaine

All day service Service toute la journée



0

Station

Park & Ride / Parc relais

**CC** Transpo

Shopping Centre / Centre commercial

04.2025

2025.04



octranspo.com

## Appendix D – Collision Data



### **Collision Details Report - Public Version**

**From:** January 1, 2017 **To:** December 31, 2021

Location: FALLOWFIELD RD @ O'KEEFE CRT

Traffic Control: Stop sign Total Collisions: 2

Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	r Vehicle type	First Event	No. Ped
2020-Jul-31, Fri,03:34	Clear	SMV other	Non-fatal injury	Dry	South	Going ahead	Automobile, station wagon	Ran off road	0
2021-Dec-24, Fri,09:39	Clear	SMV other	P.D. only	Dry	West	Going ahead	Automobile, station wagon	Ran off road	0

Location: FALLOWFIELD RD @ STRANDHERD DR

Traffic Control: Traffic signal Total Collisions: 52

Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	r Vehicle type	First Event	No. Ped
2017-Jan-12, Thu,06:25	Rain	Approaching	P.D. only	Wet	West	Unknown	Unknown	Other motor vehicle	0
					East	Going ahead	Pick-up truck	Other motor vehicle	
2017-Feb-26, Sun,14:09	Clear	Sideswipe	P.D. only	Dry	West	Changing lanes	Automobile, station wagon	Other motor vehicle	0
					West	Changing lanes	Pick-up truck	Other motor vehicle	
2017-Apr-20, Thu,08:40	Clear	Rear end	P.D. only	Dry	East	Turning left	Automobile, station wagon	Other motor vehicle	0
					East	Turning left	Pick-up truck	Other motor vehicle	
2017-Jun-05, Mon,14:45	Clear	Rear end	P.D. only	Dry	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2017-Jul-14, Fri,18:11	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Stopped	Automobile, station wagon	Other motor vehicle	
					South	Merging	Automobile, station wagon	Other motor vehicle	
2017-Jul-26, Wed,07:34	Clear	Sideswipe	P.D. only	Dry	West	Changing lanes	Automobile, station wagon	Other motor vehicle	0
					West	Going ahead	Automobile, station wagon	Other motor vehicle	
2017-Aug-12, Sat,18:56	Rain	Rear end	Non-fatal injury	Wet	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					West	Stopped	Automobile, station wagon	Other motor vehicle	
2017-Aug-15, Tue,14:45	Clear	Angle	Non-fatal injury	Dry	East	Going ahead	Passenger van	Other motor vehicle	0
					North	Turning left	Pick-up truck	Other motor vehicle	

June 02, 2023 Page 1 of 5



## **Collision Details Report - Public Version**

**From:** January 1, 2017 **To:** December 31, 2021

Location: FALLOWFIELD RD @ STRANDHERD DR

Traffic Control: Traffic signal Total Collisions: 52

	J								
Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	er Vehicle type	First Event	No. Ped
2017-Sep-20, Wed,20:10	Clear	Rear end	P.D. only	Dry	West	Turning right	Automobile, station wagon	Other motor vehicle	0
					West	Turning right	Automobile, station wagon	Other motor vehicle	
2017-Oct-17, Tue,17:28	Clear	Rear end	P.D. only	Dry	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					West	Stopped	Automobile, station wagon	Other motor vehicle	
2017-Nov-17, Fri,12:02	Clear	Rear end	P.D. only	Dry	West	Going ahead	Pick-up truck	Other motor vehicle	0
					West	Stopped	Passenger van	Other motor vehicle	
2018-Jan-08, Mon,12:55	Snow	Rear end	Non-fatal injury	Slush	East	Slowing or stoppin	g Pick-up truck	Skidding/sliding	0
					East	Stopped	Automobile, station wagon	Other motor vehicle	
2018-Feb-08, Thu,15:46	Clear	Angle	P.D. only	Dry	East	Going ahead	Automobile, station wagon	Other motor vehicle	0
					South	Going ahead	Pick-up truck	Other motor vehicle	
2018-Feb-09, Fri,17:45	Clear	Rear end	Non-fatal injury	Wet	West	Slowing or stoppin	g Automobile, station wagon	Skidding/sliding	0
					West	Slowing or stoppin	g Automobile, station wagon	Other motor vehicle	
2018-Feb-16, Fri,15:35	Clear	Rear end	P.D. only	Dry	East	Turning left	Automobile, station wagon	Other motor vehicle	0
					East	Turning left	Automobile, station wagon	Other motor vehicle	
2018-Mar-09, Fri,10:55	Snow	Angle	Non-fatal injury	Wet	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					South	Turning left	Pick-up truck	Other motor vehicle	
2018-Apr-26, Thu,16:11	Clear	Rear end	P.D. only	Dry	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Passenger van	Other motor vehicle	
2018-Jun-19, Tue,21:05	Clear	Angle	Non-fatal injury	Dry	South	Going ahead	Motorcycle	Other motor vehicle	0
					East	Going ahead	Automobile, station wagon	Other motor vehicle	
2018-Jun-24, Sun,14:01	Clear	Rear end	P.D. only	Dry	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2018-Aug-16, Thu,12:28	Clear	Rear end	P.D. only	Dry	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					West	Stopped	Automobile, station wagon	Other motor vehicle	

June 02, 2023 Page 2 of 5



### **Collision Details Report - Public Version**

**From:** January 1, 2017 **To:** December 31, 2021

Location: FALLOWFIELD RD @ STRANDHERD DR

Traffic Control: Traffic signal Total Collisions: 52

	3.9							02	
Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	r Vehicle type	First Event	No. Ped
2018-Sep-10, Mon,07:45	Clear	Sideswipe	P.D. only	Dry	West	Unknown	Unknown	Other motor vehicle	0
					West	Going ahead	Automobile, station wagon	Other motor vehicle	
2018-Sep-17, Mon,14:10	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2018-Oct-24, Wed,08:45	Clear	Rear end	Non-fatal injury	Dry	West	Changing lanes	Automobile, station wagon	Other motor vehicle	0
					West	Stopped	Automobile, station wagon	Other motor vehicle	
2018-Dec-22, Sat,08:04	Snow	Turning movement	P.D. only	Loose snow	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					East	Turning left	Automobile, station wagon	Other motor vehicle	
2019-Jan-01, Tue,19:29	Clear	Sideswipe	P.D. only	Dry	West	Turning left	Automobile, station wagon	Other motor vehicle	0
					West	Turning left	Municipal transit bus	Other motor vehicle	
2019-Jan-29, Tue,08:35	Clear	Rear end	P.D. only	Loose snow	East	Slowing or stoppin	g Truck - dump	Other motor vehicle	0
					East	Slowing or stopping	g Automobile, station wagon	Other motor vehicle	
					East	Stopped	Automobile, station wagon	Other motor vehicle	
2019-Jan-31, Thu,16:32	Clear	Rear end	P.D. only	Packed snow	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2019-Feb-25, Mon,21:05	Clear	Turning movement	P.D. only	Dry	East	Turning left	Automobile, station wagon	Other motor vehicle	0
					West	Going ahead	Pick-up truck	Other motor vehicle	
2019-Mar-05, Tue,16:30	Snow	Rear end	P.D. only	Loose snow	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2019-Apr-24, Wed,18:20	Clear	Rear end	P.D. only	Dry	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					West	Stopped	Pick-up truck	Other motor vehicle	
2019-May-04, Sat,10:30	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Turning right	Unknown	Other motor vehicle	

June 02, 2023 Page 3 of 5



## **Collision Details Report - Public Version**

**From:** January 1, 2017 **To:** December 31, 2021

Location: FALLOWFIELD RD @ STRANDHERD DR

Traffic Control: Traffic signal Total Collisions: 52

Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	r Vehicle type	First Event	No. Ped
2019-Jul-30, Tue,08:03	Clear	Sideswipe	P.D. only	Dry	East	Turning left	Truck and trailer	Other motor vehicle	0
					East	Turning left	Automobile, station wagon	Other motor vehicle	
2019-Sep-14, Sat,15:00	Clear	Rear end	P.D. only	Dry	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2019-Sep-16, Mon,08:35	Clear	Rear end	P.D. only	Dry	East	Going ahead	Automobile, station wagon	Other motor vehicle	0
					East	Stopped	Automobile, station wagon	Other motor vehicle	
2019-Nov-16, Sat,13:41	Clear	Rear end	P.D. only	Dry	West	Going ahead	Unknown	Other motor vehicle	0
					West	Slowing or stopping	g Automobile, station wagon	Other motor vehicle	
2020-Jan-31, Fri,11:01	Clear	Angle	Non-fatal injury	Dry	West	Going ahead	Automobile, station wagon	Other motor vehicle	0
					South	Going ahead	Pick-up truck	Other motor vehicle	
2020-Feb-20, Thu,07:15	Clear	Rear end	P.D. only	Dry	West	Turning right	Automobile, station wagon	Other motor vehicle	0
					West	Turning right	Automobile, station wagon	Other motor vehicle	
2020-Mar-08, Sun,10:29	Clear	Rear end	P.D. only	Dry	West	Slowing or stoppin	g Truck - dump	Other motor vehicle	0
					West	Slowing or stopping	g Automobile, station wagon	Other motor vehicle	
2020-Jun-05, Fri,15:10	Clear	Rear end	P.D. only	Dry	West	Going ahead	Pick-up truck	Other motor vehicle	0
					West	Stopped	Automobile, station wagon	Other motor vehicle	
2020-Jul-27, Mon,16:27	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2020-Oct-01, Thu,11:26	Clear	Rear end	P.D. only	Dry	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Pick-up truck	Other motor vehicle	
2020-Dec-28, Mon,18:51	Clear	Sideswipe	P.D. only	Wet	East	Changing lanes	Automobile, station wagon	Other motor vehicle	0
					East	Going ahead	Automobile, station wagon	Other motor vehicle	
					East	Going ahead	Automobile, station wagon	Other motor vehicle	

June 02, 2023 Page 4 of 5



### **Transportation Services - Traffic Services**

### **Collision Details Report - Public Version**

**From:** January 1, 2017 **To:** December 31, 2021

Location: FALLOWFIELD RD @ STRANDHERD DR

Traffic Control: Traffic signal Total Collisions: 52

Date/Day/Time	Environment	Impact Type	Classification	Surface Cond'n	Veh. Dir	Vehicle Manoeuve	r Vehicle type	First Event	No. Ped
2021-Jan-19, Tue,06:46	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Turning right	Pick-up truck	Other motor vehicle	
2021-Feb-18, Thu,08:20	Clear	Rear end	P.D. only	Ice	South	Turning right	Automobile, station wagon	Other motor vehicle	0
					South	Turning right	Automobile, station wagon	Other motor vehicle	
2021-Feb-27, Sat,14:21	Clear	SMV other	Non-fatal injury	Slush	East	Changing lanes	Automobile, station wagon	Skidding/sliding	0
2021-Mar-11, Thu,08:49	Clear	Rear end	P.D. only	Dry	South	Turning right	Pick-up truck	Other motor vehicle	0
					South	Turning right	Pick-up truck	Other motor vehicle	
2021-Jul-20, Tue,16:30	Rain	Sideswipe	P.D. only	Wet	East	Turning left	Other emergency vehicle	Other motor vehicle	0
					East	Turning left	Pick-up truck	Other motor vehicle	
2021-Aug-27, Fri,16:04	Clear	Sideswipe	P.D. only	Dry	East	Changing lanes	Automobile, station wagon	Other motor vehicle	0
					East	Stopped	Pick-up truck	Other motor vehicle	
2021-Oct-31, Sun,03:00	Clear	SMV other	P.D. only	Dry	West	Going ahead	Pick-up truck	Ran off road	0
2021-Oct-31, Sun,04:27	Clear	SMV other	P.D. only	Wet	East	Unknown	Unknown	Pole (utility, power)	0
2021-Nov-21, Sun,14:45	Clear	Rear end	P.D. only	Dry	East	Going ahead	Automobile, station wagon	Other motor vehicle	0
					East	Stopped	Pick-up truck	Other motor vehicle	
2021-Dec-15, Wed,11:55	Clear	Rear end	P.D. only	Dry	West	Going ahead	Pick-up truck	Other motor vehicle	0
					West	Slowing or stoppin	g Automobile, station wagon	Other motor vehicle	

June 02, 2023 Page 5 of 5

## Appendix E – Traffic Count Data




#### Turning Movement Count Summary, AM and PM Peak Hour Flow Diagrams

Flow Diagrams

All Vehicles Except Bicycles








# Turning Movement Count Heavy Vehicle Summary (FHWA Class 4-13) Flow Diagram





#### Comments:


Printed on: 6/5/2023

Transit buses, private buses and school buses comprise 18.24% of the heavy vehicle traffic. The Hampton Inn and Suites is the only business open in this area as all other building lots are not yet developed.



# Turning Movement Count Bicycle Summary Flow Diagram





#### Comments:

Printed on: 6/5/2023

Transit buses, private buses and school buses comprise 18.24% of the heavy vehicle traffic. The Hampton Inn and Suites is the only business open in this area as all other building lots are not yet developed.

## Appendix F – Intersection Capacity Analyses

Intersection												
Int Delay, s/veh	3.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	î,			4		ሻ	ħβ		ች	<b>1</b>	7
Traffic Vol, veh/h	8	5	13	37	6	69	13	519	13	12	487	8
Future Vol, veh/h	8	5	13	37	6	69	13	519	13	12	487	8
Conflicting Peds, #/hr	. 0	0	1	1	0	0	0	0	1	1	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	500	-	-	-	-	-	1400	-	-	600	-	250
Veh in Median Storag	je,# -	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	25	40	15	0	17	3	15	8	15	8	8	12
Mvmt Flow	9	6	14	41	7	77	14	577	14	13	541	9
Major/Minor	Minor2		ı	Minor1		ı	Major1		1	Major2		
Conflicting Flow All	887	1187	542	1196	1189	297	550	0	0	592	0	0
Stage 1	567	567	-	613	613	-	-	-	-	-	-	-
Stage 2	320	620	-	583	576	-	-	-	-	-	-	-
Critical Hdwy	7.675	7.1	6.425	7.3		6.945	4.325	-	-	4.22	-	-
Critical Hdwy Stg 1	6.475	6.1	-	6.5	5.755	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.875	6.1	-	6.1	5.755	-	-	-	-	-	-	-
Follow-up Hdwy	3.7375	4.38	3.4425	3.5	4.1615	3.32852	2.3425	-	-	2.276	-	-
Pot Cap-1 Maneuver	222	149	509	154	171	697	944	-	-	947	-	-
Stage 1	460	435	-	451	453	-	-	-	-	-	-	-
Stage 2	614	409	-	502	472	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver		145	509	142	166	696	944	-	-	946	-	-
Mov Cap-2 Maneuver		145	-	142	166	-	-	-	-	-	-	-
Stage 1	453	429	-	444	446	-	-	-	-	-	-	-
Stage 2	530	402	-	474	465	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	20.1			27.3			0.2			0.2		
HCM LOS	С			D								
Minor Lane/Major Mv	mt	NBL	NBT	NBR	EBLn1	EBLn2V	VBLn1	SBL	SBT	SBR		
Capacity (veh/h)		944			187	300	283	946		_		
HCM Lane V/C Ratio		0.015	_	_	0.048			0.014	_	_		
HCM Control Delay (s		8.9	-	_	25.2	17.9	27.3	8.9	_	_		
HCM Lane LOS	-,	Α	_	_	D	C	D	Α	-	_		
HCM 95th %tile Q(ve	h)	0	_	_	0.1	0.2	2.1	0	_	_		
	,	- 3			0.1	0.2	,					

Intersection						
Int Delay, s/veh	6.9					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	\$	LDIN	VVDL	<u>₩Ы</u>	₩.	ווטוז
Traffic Vol, veh/h	3	0	24	3	0	23
Future Vol, veh/h	3	0	24	3	0	23
<u>'</u>				0		
Conflicting Peds, #/hr	0	0	0		0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	3	0	27	3	0	26
Major/Minor M	lajor1	_ ^	Major2	ı	/linor1	
		0		0	60	3
Conflicting Flow All	0	U	3			
Stage 1	-	-	-	-	3	-
Stage 2	-	-	-	-	57	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1632	-	952	1087
Stage 1	-	-	-	-	1025	-
Stage 2	-	-	-	-	971	-
Platoon blocked, %	-	-		-		
Mov Cap-1 Maneuver	-	-	1632	-	936	1087
Mov Cap-2 Maneuver	-	_	-	-	936	-
Stage 1	_	_	_	-	1025	_
Stage 2	_	_	_	_	954	_
					50 r	
Approach	EB		WB		NB	
HCM Control Delay, s	0		6.4		8.4	
HCM LOS					Α	
Minor Lane/Major Mvmt	1	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	'	1087	-		1632	,,,,,,
HCM Lane V/C Ratio		0.024		-	0.016	-
HCM Control Delay (s)		8.4	-		7.2	0
HCM Lane LOS			-	-	7.2 A	
		Α	-	-	А	Α
HCM 95th %tile Q(veh)		0.1	_		0.1	-

Intersection						
Int Delay, s/veh	0.1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
	EDL		INDL			SDK
Lane Configurations	^	<b>7</b>	0	<b>^</b>	<b>↑</b> }	0
Traffic Vol, veh/h	0	13	0	545	529	8
Future Vol, veh/h	0	13	0	545	529	8
Conflicting Peds, #/hr	0	0	0	0	_ 0	_ 0
	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	-
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	14	0	606	588	9
Major/Minor M	inor2	N	Major1	N	/lajor2	
Conflicting Flow All	_	299	-	0	-	0
Stage 1	_	_	_	-	_	_
Stage 2	_	_	_	_	_	_
Critical Hdwy	_	6.9	_	_	_	_
Critical Hdwy Stg 1	_	0.5	_	_	_	_
Critical Hdwy Stg 2	_	_				
Follow-up Hdwy	_	3.3	_	_	_	_
Pot Cap-1 Maneuver	0	703	0			_
Stage 1	0	705	0	_	_	_
Stage 2	0	-	0	-		-
Platoon blocked, %	U	-	U	_	_	_
		702		-		-
Mov Cap-1 Maneuver	-	703	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	10.2		0		0	
HCM LOS	В				•	
	_					
N.C. 1 (N.C.) N.C. 1		NDT	-DI 4	ODT	000	
N/Inor Lang/N/Iaior N/Ivmt		NRIE	EBLn1	SBT	SBR	
Minor Lane/Major Mvmt			703	-	-	
Capacity (veh/h)		-				
Capacity (veh/h) HCM Lane V/C Ratio		-	0.021	-	-	
Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)		- -	0.021 10.2	- -	-	
Capacity (veh/h) HCM Lane V/C Ratio		-	0.021			

Intersection												
Int Delay, s/veh	3.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	f)			4		ሻ	<b>∱</b> }		ሻ	<u></u>	7
Traffic Vol, veh/h	8	7	22	23	5	50	15	559	47	48	684	12
Future Vol, veh/h	8	7	22	23	5	50	15	559	47	48	684	12
Conflicting Peds, #/hr	0	0	2	2	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	500	-	-	-	-	-	1400	-	-	600	-	250
Veh in Median Storage	е, # -	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	12	0	9	9	20	4	0	3	2	2	5	8
Mvmt Flow	9	8	24	26	6	56	17	621	52	53	760	13
Major/Minor	Minor2			Minor1		<u> </u>	Major1			Major2		
Conflicting Flow All	1214	1573	762	1572	1560	337	773	0	0	673	0	0
Stage 1	866	866	-	681	681	-	-	-	-	-	-	-
Stage 2	348	707	-	891	879	-	-	-	-	-	-	-
Critical Hdwy	7.48	6.5	6.335	7.435	6.8	6.96	4.1	-	-	4.13	-	-
Critical Hdwy Stg 1	6.28	5.5	-	6.635	5.8	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.68	5.5	-	6.235	5.8	-	-	-	-	-	-	-
Follow-up Hdwy	3.614	4	3.3855	3.5855	4.19	3.338	2.2	-	-	2.219	-	-
Pot Cap-1 Maneuver	138	111	390	77	98	655	851	-	-	916	-	-
Stage 1	329	373	-	394	415	-	-	-	-	-	-	-
Stage 2	619	441	-	324	333	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	113	102	389	64	90	655	851	-	-	916	-	-
Mov Cap-2 Maneuver	113	102	-	64	90	-	-	-	-	-	-	-
Stage 1	322	351	-	386	407	-	-	-	-	-	-	-
Stage 2	548	432	-	279	314	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	26.6			51.9			0.2			0.6		
HCM LOS	D			F								
Minor Lane/Major Mvn	nt	NBL	NBT	NBR	EBL <sub>n1</sub>	EBLn2V	VBLn1	SBL	SBT	SBR		
Capacity (veh/h)		851	-	_	113	232	159	916	-	-		
HCM Lane V/C Ratio		0.02	-	-		0.139			-	-		
HCM Control Delay (s)		9.3	-	-	39.6	23	51.9	9.2	-	-		
HCM Lane LOS		Α	-	-	Е	С	F	Α	-	-		
HCM 95th %tile Q(veh	)	0.1	-	-	0.3	0.5	2.8	0.2	-	-		
	,											

Intersection						
Int Delay, s/veh	4.3					
		EDD	WDI	WDT	NDI	NDD
	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	<b>\$</b>	•	0.4	र्	¥	
Traffic Vol, veh/h	23	0	24	8	0	14
Future Vol, veh/h	23	0	24	8	0	14
Conflicting Peds, #/hr	0	_ 0	_ 0	_ 0	0	0
	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	26	0	27	9	0	16
Major/Minor Ma	ajor1	N	//ajor2	N	Minor1	
Conflicting Flow All	0	0	26	0	89	26
Stage 1	-		-	-	26	-
Stage 2	_		_	-	63	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	_	-	4.1	-	5.4	0.2
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	_	-	1601		917	1056
	_	_	1001	-	1002	1000
Stage 1	-	-	-	-	965	-
Stage 2	-	-	-	-	900	-
Platoon blocked, %	-	-	1604	-	004	1056
Mov Cap-1 Maneuver	-	-	1601	-	901	1056
Mov Cap-2 Maneuver	-	-	-	-	901	-
Stage 1	-	-	-	-	1002	-
Stage 2	-	-	-		949	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		5.5		8.5	
HCM LOS	•		3.0		A	
NA:		IDL 4	EDT	EDD	\A/DI	MOT
Minor Lane/Major Mvmt	N	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)		1056	-		1601	-
HCM Lane V/C Ratio		0.015	-	-	0.017	-
LIOMA O ( I D . I / . )		8.5	_	_	7.3	0
HCM Control Delay (s)						
HCM Control Delay (s) HCM Lane LOS HCM 95th %tile Q(veh)		A 0	-	-	A 0.1	A

Intersection						
Int Delay, s/veh	0.1					
		<b>ED D</b>	NDI	NET	ODT	000
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations		7		<b>^</b>	ħβ	
Traffic Vol, veh/h	0	17	0	621	722	7
Future Vol, veh/h	0	17	0	621	722	7
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	-
Veh in Median Storage,	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	19	0	690	802	8
N. 4 . ' (N. 4)'	ı. o				4 : 0	
	1inor2		/lajor1		/lajor2	_
Conflicting Flow All	-	405	-	0	-	0
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Critical Hdwy	-	6.9	-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	601	0	-	-	
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	_	601	-	_	_	_
Mov Cap-2 Maneuver	_	-	_	_	_	_
Stage 1	_	_	_	_	_	_
Stage 2	_	_	_	_	_	_
Olayo Z	_	_			_	_
Approach	EB		NB		SB	
HCM Control Delay, s	11.2		0		0	
HCM LOS	В					
Minor Lang/Major Muset		NDT	EDI 51	SBT	CDD	
Minor Lane/Major Mvmt		NBT E		OBI	SBR	
Capacity (veh/h)		-	• • •	-	-	
HCM Lane V/C Ratio			0.031	-	-	
HCM Control Delay (s)		-		-	-	
HCM Lane LOS		-	В	-	-	
HCM 95th %tile Q(veh)		-	0.1	-	-	

Intersection												
Int Delay, s/veh	13.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		₽			4		- ሽ	ΦÞ				7
Traffic Vol, veh/h	33	5	28	37	6	69	151	602	13	12	742	95
Future Vol, veh/h	33	5	28	37	6	69	151	602	13	12	742	95
Conflicting Peds, #/hr		0	1	1	0	0	0	0	1	1	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	50	-	-	-	-	-	140	-	-	60	-	25
Veh in Median Storag	je,# -	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	100	100	100	100	100	100	100	100	100	100	100	100
Heavy Vehicles, %	25	40	15	0	17	3	15	8	15	8	8	12
Mvmt Flow	33	5	28	37	6	69	151	602	13	12	742	95
Major/Minor	Minor2		ı	Minor1			Major1		N	Major2		
Conflicting Flow All	1372	1684	743	1743	1773	309	837	0	0	616	0	0
	766	766	143	912		309	03/	U	U	010		
Stage 1 Stage 2	606	918	-	831	912 861			-	=	-	-	-
	7.675	7.1	6.425	7.3	6.755	6.945	4.325	-	-	4.22	-	-
Critical Hdwy Critical Hdwy Stg 1	6.475	6.1	0.425	6.5	5.755	0.943	4.323	-	=	4.22	-	-
	6.875	6.1	-	6.1		-	-	-	<del>-</del>	-	-	<del>-</del>
Critical Hdwy Stg 2			3.4425			- 3.3285 <i>2</i>	2/105	-	-	2.276	-	-
Follow-up Hdwy	3.7375							-	<del>-</del>	928	-	<del>-</del>
Pot Cap-1 Maneuver	97 352	70 345	388	62 299	73 326	685	729	-	-	920	-	-
Stage 1		288	-	367	345	-	-	-	<del>-</del>	-	-	<del>-</del>
Stage 2	408	200	-	307	343	-	-	-	-	-	-	-
Platoon blocked, %	. 67	EE	200	10	<b>57</b>	601	700	-	<del>-</del>	927	-	-
Mov Cap 2 Manager		55 55	388	45 45	57 57	684	729	-	-	921	-	-
Mov Cap-2 Maneuver			-			-	-	-	-	-	-	-
Stage 1	279	341	-	237	258 341	-	-	-	-	-	-	-
Stage 2	284	228	-	331	341	-	-	-	<del>-</del>	-	-	<del>-</del>
Approach	EB			WB			NB			SB		
HCM Control Delay, s	64.4			168			2.2			0.1		
HCM LOS	F			F								
Minor Lane/Major Mv	mt	NBL	NBT	NRR	FRI n1	EBLn2V	VRI n1	SBL	SBT	SBR		
	1110		HUI			202		927	ODT	ODIX		
Capacity (veh/h)		729	-	-	67	0.163	109		-	-		
HCM Control Dolov (		0.207	-				1.028		-	-		
HCM Long LOS	5)	11.2	-		102.5	26.3	168	8.9	-	-		
HCM Lane LOS	<b>b</b> \	В	-	-	F	D	F	A	-	-		
HCM 95th %tile Q(ve	11)	0.8	-	-	2	0.6	6.7	0	-	-		

HCM 2010 TWSC Synchro 11 Report September 2025

		۶	<b>→</b>	*	1	•	•	1	<b>†</b>	-	-	ţ	1
Traffic Volume (vph)	Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Traffic Volume (vph)	Lane Configurations	*	T <sub>a</sub>			43		*	<b>*</b>	7	*	<b>^</b>	7
Future Volume (vph)				28	37		69	151		13			
Idea   Flow (ryphpi)   1800		33	5	28	37	6	69	151	602	13	12	742	
Storage Langth (m)		1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Lanes	,	50.0		0.0	0.0		0.0	140.0		0.0	60.0		
Lane Util. Factor		1		0	0		0	1		1	1		1
Lane Unil. Factor		7.6			7.6			7.6			7.6		
Fith		1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected   0.950   0.984   0.950   0.500   0.950   0.831   0.831   0.831   0.831   0.831   0.831   0.832   0.837   0.321   0.402   0.40	Ped Bike Factor		0.98			1.00				0.98	1.00		
Satd. Flow (prot)   1383   1313   0   0   1598   0   1503   1685   1345   1601   1685   1381   Flit Permitted   0.823   0.877   0.321   0.321   0.002     Satd. Flow (perm)   1198   1313   0   0   1424   0   508   1685   1316   677   1685   1381     Right Turn on Red   Yes	Frt		0.873			0.917				0.850			0.850
Fit Permitted	Flt Protected	0.950				0.984		0.950			0.950		
Satd. Flow (perm)   1198	Satd. Flow (prot)	1383	1313	0	0	1598	0	1503	1685	1345	1601	1685	1381
Right Turn on Red	Flt Permitted	0.823				0.877		0.321			0.402		
Satd. Flow (RTOR)	Satd. Flow (perm)	1198	1313	0	0	1424	0	508	1685	1316	677	1685	1381
Link Speed (k/h)				Yes			Yes			Yes			Yes
Link Distance (m)	Satd. Flow (RTOR)		28			69				36			51
Link Distance (m)			50			50			60			60	
Confil Peds. (#hr)			187.0			55.0			184.6			116.3	
Peak Hour Factor	Travel Time (s)		13.5			4.0			11.1			7.0	
Heavy Vehicles (%)	Confl. Peds. (#/hr)			1	1					1	1		
Adj. Flow (vph)         33         5         28         37         6         69         151         602         13         12         742         95           Shared Lane Traffic (%)         Lane Group Flow (vph)         33         33         0         0         112         0         151         602         13         12         742         95           Turn Type         Perm         NA         Perm         NA         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         Perm         NA         Perm         Perm <td>Peak Hour Factor</td> <td>1.00</td>	Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj. Flow (vph)         33         5         28         37         6         69         151         602         13         12         742         95           Shared Lane Traffic (%)         Lane Group Flow (vph)         33         33         0         0         112         0         151         602         13         12         742         95           Turn Type         Perm         NA         Perm         NA<	Heavy Vehicles (%)	25%	40%	15%	0%	17%	3%	15%	8%	15%	8%	8%	12%
Lane Group Flow (vph)   33   33   0   0   112   0   151   602   13   12   742   95     Turn Type		33	5	28	37	6	69	151	602	13	12	742	95
Turn Type         Perm         NA         Perm         NA         Perm         NA         Perm         Perm <td>Shared Lane Traffic (%)</td> <td></td>	Shared Lane Traffic (%)												
Protected Phases	Lane Group Flow (vph)	33	33	0	0	112	0	151	602	13	12	742	95
Permitted Phases	Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Detector Phase   4	Protected Phases		4			8			2			6	
Switch Phase         Minimum Initial (s)         5.0         5.3         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%	Permitted Phases	4			8			2		2	6		6
Minimum Initial (s)         5.0         4.1         27.4 </td <td>Detector Phase</td> <td>4</td> <td>4</td> <td></td> <td>8</td> <td>8</td> <td></td> <td>2</td> <td>2</td> <td>2</td> <td>6</td> <td>6</td> <td>6</td>	Detector Phase	4	4		8	8		2	2	2	6	6	6
Minimum Split (s)         33.5         33.5         33.5         33.5         27.4 <td>Switch Phase</td> <td></td>	Switch Phase												
Total Split (s)         33.5         33.5         33.5         33.5         41.5	Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Total Split (%)         44.7%         44.7%         44.7%         44.7%         55.3%	Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Maximum Green (s)         28.0         28.0         28.0         28.0         28.0         36.1         4.1	Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Yellow Time (s)         3.6         3.6         3.6         3.6         4.1	Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
All-Red Time (s) 1.9 1.9 1.9 1.9 1.0 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3	Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Lost Time Adjust (s)         0.0	Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
Total Lost Time (s)         5.5         5.5         5.5         5.5         5.4	All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lead/Lag         Lead-Lag Optimize?         Vehicle Extension (s)       3.0	Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Lead-Lag Optimize?         Vehicle Extension (s)       3.0	Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Vehicle Extension (s)         3.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0	Lead/Lag												
Recall Mode         None         None         None         None         Min	Lead-Lag Optimize?												
Walk Time (s)       7.0	Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Flash Dont Walk (s)       21.0       21.0       21.0       21.0       15.0       16.0       16.0       16.0       10.0       10.0       10.0       10.0	Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Pedestrian Calls (#/hr)       0 <td>Walk Time (s)</td> <td>7.0</td> <td>7.0</td> <td></td> <td>7.0</td> <td>7.0</td> <td></td> <td>7.0</td> <td>7.0</td> <td>7.0</td> <td>7.0</td> <td>7.0</td> <td>7.0</td>	Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Pedestrian Calls (#/hr)       0 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>15.0</td> <td></td> <td></td> <td></td> <td></td>									15.0				
Act Effct Green (s)       7.7       7.7       7.7       43.1       43.					0	0			0				
Actuated g/C Ratio 0.13 0.13 0.13 0.74 0.74 0.74 0.74 0.74	,												
·	. ,					0.13		0.74	0.74			0.74	
	•												

	•	<b>→</b>	*	1	<b>←</b>	*	1	<b>†</b>	-	-	ļ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	24.3	12.0			16.7		9.1	6.5	0.6	4.0	8.2	2.5
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.3	12.0			16.7		9.1	6.5	0.6	4.0	8.2	2.5
LOS	С	В			В		Α	Α	Α	Α	Α	Α
Approach Delay		18.2			16.7			6.9			7.5	
Approach LOS		В			В			Α			Α	
Queue Length 50th (m)	3.0	0.5			4.0		5.5	23.8	0.0	0.3	33.8	1.2
Queue Length 95th (m)	9.2	6.3			15.1		20.7	54.2	0.6	1.8	79.0	5.6
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	578	648			722		375	1244	981	499	1244	1033
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.06	0.05			0.16		0.40	0.48	0.01	0.02	0.60	0.09
Intersection Summary												
Area Type:	Other											

Cycle Length: 75

Actuated Cycle Length: 58.3

Natural Cycle: 90

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.60

Intersection Signal Delay: 8.2
Intersection Capacity Utilization 77.3%

Intersection LOS: A ICU Level of Service D

Analysis Period (min) 15

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Intersection						
Int Delay, s/veh	2.9					
	EBT	EBR	WBL	WBT	NBL	NBR
		EDK	VVDL			INDIX
Lane Configurations	<b>}</b>	٥	00	472	Y	11
Traffic Vol, veh/h	26	0	80	172	0	41
Future Vol, veh/h	26	0	80	172	0	41
Conflicting Peds, #/hr	0	0	0	0	0	0
3	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None		None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	26	0	80	172	0	41
Major/Minor Ma	ajor1	ı	Major2	N	/linor1	
			26			26
Conflicting Flow All	0	0		0	358	
Stage 1	-	-	-	-	26	-
Stage 2	-	-	-	-	332	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1601	-	644	1056
Stage 1	-	-	-	-	1002	-
Stage 2	-	-	-	-	731	-
Platoon blocked, %	-	-		-		
Mov Cap-1 Maneuver	-	-	1601	-	609	1056
Mov Cap-2 Maneuver	-	-	-	-	609	-
Stage 1	-	_	-	-	1002	-
Stage 2	_	_	_	_	691	_
5 g =						
Approach	EB		WB		NB	
HCM Control Delay, s	0		2.3		8.5	
HCM LOS					Α	
						MOT
Minor Lane/Major Mymt	N	JRI n1	FRT	FRR	\M/RI	WRI
Minor Lane/Major Mvmt	1	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	1	1056	-	-	1601	-
Capacity (veh/h) HCM Lane V/C Ratio	١	1056 0.039	-	- -	1601 0.05	-
Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	1	1056 0.039 8.5	- - -	- - -	1601 0.05 7.4	- - 0
Capacity (veh/h) HCM Lane V/C Ratio	1	1056 0.039	-	- -	1601 0.05	-

HCM 2010 TWSC

Intersection						
Int Delay, s/veh	0.3					
	EDI	EDD	NDI	NDT	CDT	CDD
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	_	7		<b>^</b>	<b>^</b>	7
Traffic Vol, veh/h	0	36	0	768	787	25
Future Vol, veh/h	0	36	0	768	787	25
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage,	# 0	_	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mymt Flow	0	36	0	768	787	25
IVIVIIIL FIUW	U	30	U	100	101	20
Major/Minor M	linor2	N	Major1	Λ	/lajor2	
Conflicting Flow All	_	787		0		0
Stage 1	_	-	_	-	_	-
Stage 2	_	<u>-</u>	_	_	_	_
	-	6.2	_	_	-	_
Critical Hdwy						
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	395	0	-	-	-
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	-	395	-	-	-	-
Mov Cap-2 Maneuver	_	-	-	-	-	-
Stage 1	_	_	_	_	_	_
Stage 2	_	_	_	_	_	_
Olage Z	_					_
Approach	EB		NB		SB	
HCM Control Delay, s	15		0		0	
HCM LOS	C					
Minor Lane/Major Mvmt		NBT E	EBLn1	SBT	SBR	
Capacity (veh/h)		-	395	-	-	
HCM Lane V/C Ratio		_	0.091	-	-	
HCM Control Delay (s)		-	15	-	_	
HCM Lane LOS		_	C	_	_	
HCM 95th %tile Q(veh)		_	0.3	_	_	
Holvi Jour Joure Q(Veri)			0.0			

HCM 2010 TWSC Synchro 11 Report September 2025

Intersection													
	35.2												
	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	
Lane Configurations	T T		EDI	WDL		WDN	NDL T	<b>↑</b>	NDI	SBL Š	<u>361</u>	JDK 7	
Traffic Vol, veh/h	117	<b>1→</b> 7	118	23	<b>↔</b> 5	50	70	<b>T №</b> 768	47	48	<b>T</b> 807	28	
Future Vol, veh/h	117	7	118	23	5	50	70	768	47	48	807	28	
Conflicting Peds, #/hr	0	0	2	23	0	0	0	0	0	0	007	0	
	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free	
RT Channelized	- -	Stop	None	Stop -	Stop -	None	-	-	None	-	-	None	
Storage Length	50	_	INUITE	_	_	-	140		-	60	_	25	
Veh in Median Storage, #		0	_	_	0	_	-	0	_	-	0	-	
Grade, %	т - -	0	_	_	0	_	_	0	_	_	0	_	
Peak Hour Factor	100	100	100	100	100	100	100	100	100	100	100	100	
Heavy Vehicles, %	12	0	9	9	20	4	0	3	2	2	5	8	
Mvmt Flow	117	7	118	23	5	50	70	768	47	48	807	28	
IVIVIII I IOW	117	1	110	20	3	50	10	700	71	70	001	20	
	inor2	10		Minor1	1000		Major1			Major2			
	1430	1858	809	1914	1863	408	835	0	0	815	0	0	
Stage 1	903	903	-	932	932	-	-	-	-	-	-	-	
Stage 2	527	955	-	982	931	-	-	-	-	-	-	-	
•	7.48	6.5	6.335		6.8	6.96	4.1	-	-	4.13	-	-	
, ,	6.28	5.5		6.635	5.8	-	-	-	-	-	-	-	
, ,	6.68	5.5		6.235	5.8	-	-	-	-	-	-	-	
	3.614		3.38553		4.19	3.338	2.2	-	-	2.219	-	-	
	~ 96	74	366	43	62	589	807	-	-	810	-	-	
Stage 1	314	359	-	277	314	-	-	-	-	-	-	-	
Stage 2	482	339	-	287	314	-	-	-	-	-	-	-	
Platoon blocked, %	70	0.4	005	0.4		500	007	-	-	040	-	-	
	~ 73	64	365	24	53	589	807	-	-	810	-	-	
	~ 73	64	-	24	53	-	-	-	-	-	-	-	
Stage 1	287	338	-	253	287	-	-	-	-	-	-	-	
Stage 2	396	310	-	179	295	-	-	-	-	-	-	-	
Approach	EB			WB			NB			SB			
HCM Control Delay, s 2	217.9			252.1			0.8			0.5			
HCM LOS	F			F									
Minor Lang/Major Muset		NIDI	NIDT	NIDD	EDI n1	EBLn2V	MDI 51	CDI	CDT	SBR			
Minor Lane/Major Mvmt		NBL	NBT	ואסוו				SBL	SBT	SDK			
Capacity (veh/h)		807	-	-	73	289	69	810	-	-			
HCM Cantral Dalay (a)		0.087	-			0.433			-	-			
HCM Control Delay (s)		9.9	-	-\$	422.2		252.1	9.7	-	-			
HCM Lore LOC				_	F	D	F	Α	-	-			
HCM Lane LOS		A	-			0.4	^	0.0					
HCM Lane LOS HCM 95th %tile Q(veh)		0.3	-	-	9.9	2.1	6	0.2	-	-			
			-	-		2.1	6	0.2	-	-			

	۶	<b>→</b>	*	•	<b>←</b>	•	1	<b>†</b>	~	/	Ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1			4		×	<b>^</b>	7	7	<b>↑</b>	7
Traffic Volume (vph)	117	7	118	23	5	50	70	768	47	48	807	28
Future Volume (vph)	117	7	118	23	5	50	70	768	47	48	807	28
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Storage Lanes	1		0	0		0	1		1	1		1
Taper Length (m)	7.6			7.6			7.6			7.6		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped Bike Factor		0.98			0.99							
Frt		0.858			0.913				0.850			0.850
Flt Protected	0.950				0.985		0.950			0.950		
Satd. Flow (prot)	1544	1409	0	0	1516	0	1729	1767	1517	1695	1733	1432
Flt Permitted	0.706				0.863		0.249			0.273		
Satd. Flow (perm)	1147	1409	0	0	1327	0	453	1767	1517	487	1733	1432
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		118			50				47			36
Link Speed (k/h)		50			50			60			80	
Link Distance (m)		187.0			55.0			184.6			116.3	
Travel Time (s)		13.5			4.0			11.1			5.2	
Confl. Peds. (#/hr)			2	2								
Confl. Bikes (#/hr)						1						
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	12%	0%	9%	9%	20%	4%	0%	3%	2%	2%	5%	8%
Adj. Flow (vph)	117	7	118	23	5	50	70	768	47	48	807	28
Shared Lane Traffic (%)												
Lane Group Flow (vph)	117	125	0	0	78	0	70	768	47	48	807	28
Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2		2	6		6
Detector Phase	4	4		8	8		2	2	2	6	6	6
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	15.0
Pedestrian Calls (#/hr)	0	0		0	0		0	0	0	0	0	0
Act Effct Green (s)	11.0	11.0			10.8		37.1	37.1	37.1	37.1	37.1	37.1
Actuated g/C Ratio	0.20	0.20			0.20		0.68	0.68	0.68	0.68	0.68	0.68
- 1000000 9, 0 1 1000	0.20	V.20			0.20		0.00	3.00	0.00	3.00	3.00	<del></del>

	•	<b>→</b>	*	1	←	*	1	<b>†</b>	1	1	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
v/c Ratio	0.50	0.33			0.26		0.23	0.64	0.04	0.15	0.68	0.03
Control Delay	28.7	7.8			12.0		8.7	11.6	2.3	7.2	13.3	2.1
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	28.7	7.8			12.0		8.7	11.6	2.3	7.2	13.3	2.1
LOS	С	Α			В		Α	В	Α	Α	В	Α
Approach Delay		17.9			12.0			10.9			12.6	
Approach LOS		В			В			В			В	
Queue Length 50th (m)	11.3	0.6			2.5		2.8	46.0	0.0	1.8	51.0	0.0
Queue Length 95th (m)	24.4	11.2			11.2		10.9	105.2	3.5	7.4	#139.0	2.3
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	606	800			724		308	1203	1048	331	1180	986
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.19	0.16			0.11		0.23	0.64	0.04	0.15	0.68	0.03

#### Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 54.6

Natural Cycle: 80

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.68

Intersection Signal Delay: 12.5 Intersection LOS: B Intersection Capacity Utilization 81.3% ICU Level of Service D

Analysis Period (min) 15

#### # 95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Synchro 11 Report Lanes, Volumes, Timings

Intersection						
Int Delay, s/veh	2.9					
		EDD	\\/DI	WPT	NDI	NDD
	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	104	^	7.4	4	¥	40
Traffic Vol, veh/h	194	0	71	31	0	48
Future Vol, veh/h	194	0	71	31	0	48
Conflicting Peds, #/hr	0	0	0	0	0	0
•	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	194	0	71	31	0	48
M - ' - /M'			4 0		A'	
	ajor1		/lajor2		/linor1	
Conflicting Flow All	0	0	194	0	367	194
Stage 1	-	-	-	-	194	-
Stage 2	-	-	-	-	173	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1391	-	637	853
Stage 1	-	-	-	-	844	-
Stage 2	_	-	_	-	862	-
Platoon blocked, %	_	_		_		
Mov Cap-1 Maneuver	_	_	1391	_	604	853
Mov Cap-2 Maneuver	_	_	-	<u>-</u>	604	-
Stage 1	_				844	_
•	_	-		-	817	
Stage 2	-	-	-	-	017	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		5.4		9.5	
					Α	
HCM LOS						
HCM LOS						
		IDL 4	EDT	EDD	VA/DI	MDT
Minor Lane/Major Mvmt	N	NBLn1	EBT	EBR	WBL	WBT
Minor Lane/Major Mvmt Capacity (veh/h)	N	853	EBT -	-	1391	WBT -
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	N	853 0.056	EBT -	-	1391 0.051	-
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	N	853 0.056 9.5	-	-	1391 0.051 7.7	- - 0
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	N	853 0.056	-	-	1391 0.051	-

Intersection						
Int Delay, s/veh	0.6					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations		7		<b>^</b>	<b>^</b>	7
Traffic Vol, veh/h	0	65	0	890	924	30
Future Vol, veh/h	0	65	0	890	924	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage	, # 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	65	0	890	924	30
					<b>V</b> = .	
	Minor2		Major1	N	//ajor2	
Conflicting Flow All	-	924	-	0	-	0
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Critical Hdwy	-	6.2	-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	329	0	-	-	_
Stage 1	0	-	0	_	_	-
Stage 2	0	_	0	-	_	-
Platoon blocked, %	•			_	_	_
Mov Cap-1 Maneuver	_	329	_	_	_	_
Mov Cap-2 Maneuver	_	020	_	_	_	
Stage 1	_	_		_		
Stage 2	_	_	_	-	_	_
Staye 2	-		-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	18.6		0		0	
HCM LOS	С					
NA' I /NA - ! NA !	•	NDT	-DL 4	ODT	000	
Minor Lane/Major Mvm	ıt	NBT E		SBT	SBR	
Capacity (veh/h)		-		-	-	
HCM Lane V/C Ratio			0.198	-	-	
HCM Control Delay (s)		-	18.6	-	-	
		_	С	-	_	
HCM Lane LOS HCM 95th %tile Q(veh)			0.7			

HCM 2010 TWSC Synchro 11 Report September 2025

	۶	<b>→</b>	*	•	<b>—</b>	•	1	<b>†</b>	~	1	Ţ	-√
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1>			4		*	<b>↑</b>	7	*	<b>^</b>	7
Traffic Volume (vph)	33	5	28	37	6	69	151	674	13	12	946	95
Future Volume (vph)	33	5	28	37	6	69	151	674	13	12	946	95
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Storage Lanes	1		0	0		0	1		1	1		1
Taper Length (m)	7.6			7.6			7.6			7.6		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped Bike Factor		0.98			1.00				0.98	1.00		
Frt		0.873			0.917				0.850			0.850
Flt Protected	0.950				0.984		0.950			0.950		
Satd. Flow (prot)	1383	1313	0	0	1598	0	1503	1685	1345	1601	1685	1381
Flt Permitted	0.823				0.877		0.212			0.360		
Satd. Flow (perm)	1198	1313	0	0	1424	0	336	1685	1316	606	1685	1381
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		28			69				36			40
Link Speed (k/h)		50			50			60			80	
Link Distance (m)		187.0			55.0			184.6			116.3	
Travel Time (s)		13.5			4.0			11.1			5.2	
Confl. Peds. (#/hr)			1	1					1	1		
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	25%	40%	15%	0%	17%	3%	15%	8%	15%	8%	8%	12%
Adj. Flow (vph)	33	5	28	37	6	69	151	674	13	12	946	95
Shared Lane Traffic (%)												
Lane Group Flow (vph)	33	33	0	0	112	0	151	674	13	12	946	95
Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2		2	6		6
Detector Phase	4	4		8	8		2	2	2	6	6	6
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	15.0
Pedestrian Calls (#/hr)	0	0		0	0		0	0	0	0	0	0
Act Effct Green (s)	7.7	7.7			7.7		43.1	43.1	43.1	43.1	43.1	43.1
Actuated g/C Ratio	0.13	0.13			0.13		0.74	0.74	0.74	0.74	0.74	0.74
v/c Ratio	0.21	0.17			0.45		0.61	0.54	0.01	0.03	0.76	0.09
	V I	Ţ			50		0.0.	0.01	5.0.	3.00	3 3	

	•	-	*	-	←	*	1	<b>†</b>	-	1	Ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	24.3	12.0			16.7		22.7	7.2	0.6	4.1	13.6	2.8
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.3	12.0			16.7		22.7	7.2	0.6	4.1	13.6	2.8
LOS	С	В			В		С	Α	Α	Α	В	Α
Approach Delay		18.2			16.7			9.9			12.5	
Approach LOS		В			В			Α			В	
Queue Length 50th (m)	3.0	0.5			4.0		7.0	28.7	0.0	0.3	54.8	1.5
Queue Length 95th (m)	9.2	6.3			15.1		#39.8	65.8	0.6	1.9	#155.7	6.0
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	578	648			722		248	1244	981	447	1244	1030
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.06	0.05			0.16		0.61	0.54	0.01	0.03	0.76	0.09

#### Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 58.3

Natural Cycle: 110

Control Type: Actuated-Uncoordinated


Maximum v/c Ratio: 0.76

Intersection Signal Delay: 11.9 Intersection LOS: B
Intersection Capacity Utilization 88.6% ICU Level of Service E

Analysis Period (min) 15

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



<sup># 95</sup>th percentile volume exceeds capacity, queue may be longer.

Intersection						
Int Delay, s/veh	2.9					
		EDD	WDI	WDT	NIDI	NDD
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	<b>1</b>	^	00	470	¥	.4.4
Traffic Vol, veh/h	26	0	80	172	0	41
Future Vol, veh/h	26	0	80	172	0	41
Conflicting Peds, #/hr	_ 0	_ 0	_ 0	_ 0	0	0
•	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	26	0	80	172	0	41
Major/Minor M	lajor1	N	Major2	N	/linor1	
Conflicting Flow All	0	0	26	0	358	26
Stage 1	-	-	-	-	26	-
Stage 2	_	_	_	_	332	_
Critical Hdwy	_	_	4.1	_	6.4	6.2
Critical Hdwy Stg 1	_	_	-T. I	_	5.4	-
Critical Hdwy Stg 2	_		_	_	5.4	_
Follow-up Hdwy	_	_	2.2	_	3.5	3.3
Pot Cap-1 Maneuver	_		1601	_	644	1056
Stage 1	_	-	1001	_	1002	1030
Stage 2		-	-		731	
Platoon blocked, %	-	-	-	-	131	-
	-	-	1001	-	600	1056
Mov Cap-1 Maneuver	-	-	1601	-	609	1056
Mov Cap-2 Maneuver	-	-	-	-	609	-
Stage 1	-	-	-	-	1002	-
Stage 2	-	-	-	-	691	-
					NB	
Approach	EB		WB			
Approach HCM Control Delay, s						
HCM Control Delay, s	EB 0		2.3		8.5	
HCM Control Delay, s HCM LOS	0	IDI 4	2.3	EDD	8.5 A	WDT
HCM Control Delay, s HCM LOS Minor Lane/Major Mvmt	0	NBLn1		EBR	8.5 A WBL	WBT
HCM Control Delay, s HCM LOS  Minor Lane/Major Mvmt Capacity (veh/h)	0	1056	2.3	-	8.5 A WBL 1601	WBT -
HCM Control Delay, s HCM LOS  Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	0	1056 0.039	2.3 EBT		8.5 A WBL 1601 0.05	-
HCM Control Delay, s HCM LOS  Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	0	1056 0.039 8.5	2.3 EBT	-	8.5 A WBL 1601 0.05 7.4	- - 0
HCM Control Delay, s HCM LOS  Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	0	1056 0.039	2.3 EBT -	-	8.5 A WBL 1601 0.05	-

Intersection						
Int Delay, s/veh	0.4					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
	LDL	EDK	INDL			
Lane Configurations	٥		٥	<b>^</b>	<b>^</b>	75
Traffic Vol, veh/h	0	36	0	842	996	25
Future Vol, veh/h	0	36	0	842	996	25
Conflicting Peds, #/hr	0	0	_ 0	_ 0	_ 0	_ 0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	36	0	842	996	25
Major/Minor	linar?		Anier1		/oicr2	
	linor2		Major1		/lajor2	
Conflicting Flow All	-	996	-	0	-	0
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Critical Hdwy	-	6.2	-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	299	0	-	-	-
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	_	-
Platoon blocked, %				-	-	_
Mov Cap-1 Maneuver	_	299	_	_	_	_
Mov Cap-2 Maneuver	_	-	_	_	_	_
Stage 1			_	_	_	_
Stage 2	_	_		_	_	-
Stage 2	-	-	-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	18.7		0		0	
HCM LOS	С					
Minor Long/Maiar M		NDT	TDL 4	CDT	CDD	
Minor Lane/Major Mvmt		NBT E		SBT	SBR	
Capacity (veh/h)		-	299	-	-	
HCM Lane V/C Ratio		-	0.12	-	-	
HCM Control Delay (s)		-	18.7	-	-	
HCM Lane LOS		-	С	-	-	
		-	0.4	-	-	

Lane Configurations		۶	<b>→</b>	*	•	<b>←</b>	•	1	<b>†</b>	~	/	<b>↓</b>	4
Traffic Volume (vph)	Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Traffic Volume (vph)	Lane Configurations	*	1			43		*	<b>^</b>	7	*	<b>^</b>	7
Ideal Flow (ryph.ph)		117		118	23		50	70		47	48	890	
Storage Length (m)	Future Volume (vph)	117	7	118	23	5	50	70	942	47	48	890	28
Storage Length (m)   50.0   0.0   0.0   0.0   140.0   0.0   60.0   25.0	Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Lanes	Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		
Lane UNI. Factor		1		0	0		0	1		1	1		1
Lane UNI. Factor	Taper Length (m)	7.6			7.6			7.6			7.6		
Firth	Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected	Ped Bike Factor		0.98			0.99							
Satd. Flow (prot)   1544   1409   0   0   1516   0   1729   1767   1517   1695   1733   1432     Fil Permitted	Frt		0.858			0.913				0.850			0.850
Fit Permitted	Flt Protected	0.950				0.985		0.950			0.950		
Satd. Flow (perm)	Satd. Flow (prot)	1544	1409	0	0	1516	0	1729	1767	1517	1695	1733	1432
Right Turn on Red   Satd. Flow (RTOR)	Flt Permitted	0.706				0.865		0.208			0.178		
Satd. Flow (RTOR)	Satd. Flow (perm)	1147	1409	0	0	1331	0	379	1767	1517	318	1733	1432
Link Speed (k/h)	Right Turn on Red			Yes			Yes			Yes			
Link Distance (m)	Satd. Flow (RTOR)		94			50				47			36
Travel Time (s)	Link Speed (k/h)		50			50			80			60	
Confi. Peds. (#/hr)	Link Distance (m)		187.0			55.0			184.6			116.3	
Confl. Bikes (#/hr)	Travel Time (s)		13.5			4.0			8.3			7.0	
Peak Hour Factor	Confl. Peds. (#/hr)			2	2								
Heavy Vehicles (%)	Confl. Bikes (#/hr)						1						
Adj. Flow (vph)         117         7         118         23         5         50         70         942         47         48         890         28           Shared Lane Traffic (%)         Lane Group Flow (vph)         117         125         0         0         78         0         70         942         47         48         890         28           Turn Type         Perm         NA         Perm	Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Shared Lane Traffic (%)   Lane Group Flow (vph)   117   125   0   0   78   0   70   942   47   48   890   28   28   28   28   29   6   6   6   6   6   6   6   6   6	Heavy Vehicles (%)	12%	0%	9%	9%	20%	4%	0%	3%	2%	2%	5%	8%
Lane Group Flow (vph)	Adj. Flow (vph)	117	7	118	23	5	50	70	942	47	48	890	28
Turn Type         Perm         NA         Perm         NA         Perm         NA         Perm         Perm         Perm         NA         Perm         Perm         Perm         NA         Perm         Perm         Perm         NA         Perm	Shared Lane Traffic (%)												
Protected Phases         4         8         2         2         6         6           Permitted Phases         4         4         8         8         2         2         2         6         6           Switch Phase         Winimum Initial (s)         5.0 <td< td=""><td>Lane Group Flow (vph)</td><td>117</td><td>125</td><td>0</td><td>0</td><td>78</td><td>0</td><td>70</td><td>942</td><td>47</td><td>48</td><td>890</td><td>28</td></td<>	Lane Group Flow (vph)	117	125	0	0	78	0	70	942	47	48	890	28
Permitted Phases	Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Detector Phase   4	Protected Phases		4			8			2			6	
Switch Phase         Minimum Initial (s)         5.0         4.1	Permitted Phases	4			8			2			6		
Minimum Initial (s)         5.0         4.1         2.1         2.1         27.4	Detector Phase	4	4		8	8		2	2	2	6	6	6
Minimum Split (s)         33.5         33.5         33.5         33.5         33.5         27.4 <td>Switch Phase</td> <td></td>	Switch Phase												
Total Split (s)         33.5         33.5         33.5         33.5         41.5	Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Total Split (%)         44.7%         44.7%         44.7%         55.3%	Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Maximum Green (s)         28.0         28.0         28.0         28.0         36.1         4.1	Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Yellow Time (s)       3.6       3.6       3.6       3.6       3.6       4.1 <td>Total Split (%)</td> <td>44.7%</td> <td>44.7%</td> <td></td> <td>44.7%</td> <td>44.7%</td> <td></td> <td>55.3%</td> <td>55.3%</td> <td>55.3%</td> <td>55.3%</td> <td>55.3%</td> <td>55.3%</td>	Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
All-Red Time (s) 1.9 1.9 1.9 1.9 1.9 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3	Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Lost Time Adjust (s)         0.0	Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
Total Lost Time (s) 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.	All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lead/Lag         Lead-Lag Optimize?         Vehicle Extension (s)       3.0	Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Lead-Lag Optimize?         Vehicle Extension (s)       3.0 <td>Total Lost Time (s)</td> <td>5.5</td> <td>5.5</td> <td></td> <td></td> <td>5.5</td> <td></td> <td>5.4</td> <td>5.4</td> <td>5.4</td> <td>5.4</td> <td>5.4</td> <td>5.4</td>	Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Vehicle Extension (s)         3.0	Lead/Lag												
Recall Mode         None         None         None         None         Min	Lead-Lag Optimize?												
Walk Time (s)       7.0	Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Walk Time (s)       7.0		None	None		None	None		Min	Min	Min	Min	Min	Min
Flash Dont Walk (s)       21.0       21.0       21.0       21.0       15.0													
Pedestrian Calls (#/hr)       0 <td></td> <td>21.0</td> <td></td> <td></td> <td>21.0</td> <td>21.0</td> <td></td> <td>15.0</td> <td>15.0</td> <td>15.0</td> <td>15.0</td> <td></td> <td></td>		21.0			21.0	21.0		15.0	15.0	15.0	15.0		
Act Effct Green (s) 11.2 11.2 11.0 40.4 40.4 40.4 40.4 40.4 40.4	` ,												
												40.4	40.4
	Actuated g/C Ratio					0.19		0.69	0.69	0.69	0.69	0.69	

	•	-	*	1	<b>←</b>	*	1	<b>†</b>	-	1	<b>↓</b>	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
v/c Ratio	0.54	0.36			0.27		0.27	0.78	0.04	0.22	0.75	0.03
Control Delay	30.6	10.7			12.2		10.0	16.7	2.3	9.5	15.5	2.1
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	30.6	10.7			12.2		10.0	16.7	2.3	9.5	15.5	2.1
LOS	С	В			В		Α	В	Α	Α	В	Α
Approach Delay		20.3			12.2			15.6			14.8	
Approach LOS		С			В			В			В	
Queue Length 50th (m)	11.3	2.8			2.5		2.9	68.3	0.0	1.9	61.9	0.0
Queue Length 95th (m)	24.4	13.8			11.2		12.1	#173.9	3.5	8.9	#161.9	2.3
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	546	720			660		260	1212	1055	218	1189	994
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.21	0.17			0.12		0.27	0.78	0.04	0.22	0.75	0.03

#### Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 58.9

Natural Cycle: 90

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.78

Intersection Signal Delay: 15.6 Intersection LOS: B
Intersection Capacity Utilization 88.8% ICU Level of Service E

Analysis Period (min) 15

# 95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Intersection						
Int Delay, s/veh	2.9					
		EDD	\\/DI	WPT	NDI	NDD
	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	104	^	7.4	4	¥	40
Traffic Vol, veh/h	194	0	71	31	0	48
Future Vol, veh/h	194	0	71	31	0	48
Conflicting Peds, #/hr	0	0	0	0	0	0
•	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	194	0	71	31	0	48
M - ' - /M'			4 0		A'	
	ajor1		/lajor2		/linor1	
Conflicting Flow All	0	0	194	0	367	194
Stage 1	-	-	-	-	194	-
Stage 2	-	-	-	-	173	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1391	-	637	853
Stage 1	-	-	-	-	844	-
Stage 2	_	-	_	-	862	-
Platoon blocked, %	_	_		_		
Mov Cap-1 Maneuver	_	_	1391	_	604	853
Mov Cap-2 Maneuver	_	_	-	<u>-</u>	604	-
Stage 1	_				844	_
•	_	-		-	817	
Stage 2	-	-	-	-	017	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		5.4		9.5	
					Α	
HCM LOS						
HCM LOS						
		IDL 4	EDT	EDD	VA/DI	MDT
Minor Lane/Major Mvmt	N	NBLn1	EBT	EBR	WBL	WBT
Minor Lane/Major Mvmt Capacity (veh/h)	N	853	EBT -	-	1391	WBT -
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	N	853 0.056	EBT -	-	1391 0.051	-
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	N	853 0.056 9.5	-	-	1391 0.051 7.7	- - 0
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	N	853 0.056	-	-	1391 0.051	-

Intersection						
Int Delay, s/veh	0.6					
		EDD	NDI	NDT	CDT	CDD
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	^	7	^	<b>^</b>	1011	70
Traffic Vol, veh/h	0	65	0	1070	1011	30
Future Vol, veh/h	0	65	0	1070	1011	30
Conflicting Peds, #/hr	0	0	_ 0	_ 0	0	_ 0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	65	0	1070	1011	30
Major/Minor M	inor2	N	//ajor1	N	Major2	
Conflicting Flow All	-	1011	-	0	-	0
Stage 1	_	-	_	-	_	-
Stage 2	_	_	_	_	_	_
Critical Hdwy		6.2	_		_	_
Critical Hdwy Stg 1		- 0.2	_	_	_	
Critical Hdwy Stg 2	_		_	_	_	
Follow-up Hdwy	_	3.3	_	_	_	-
Pot Cap-1 Maneuver	0	293	0	-	_	
	0	293	0	-	-	-
Stage 1	0	-	0	-		-
Stage 2	U	-	U	-	-	-
Platoon blocked, %		000		-	-	-
Mov Cap-1 Maneuver	-	293	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	20.8		0		0	
HCM LOS	C					
		NET	-DL 4	ODT	000	
		NRIF	EBLn1	SBT	SBR	
Minor Lane/Major Mvmt						
Capacity (veh/h)		-	293	-	-	
Capacity (veh/h) HCM Lane V/C Ratio		-	293 0.222	-	-	
Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)		-	293 0.222 20.8	-	- - -	
Capacity (veh/h) HCM Lane V/C Ratio		-	293 0.222	-		

HCM 2010 TWSC Synchro 11 Report September 2025

Intersection						
Int Delay, s/veh	1.2					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥	11511	1	11511	UDL	<u>स</u>
Traffic Vol, veh/h	9	3	41	28	12	68
Future Vol, veh/h	9	3	41	28	12	68
Conflicting Peds, #/hr	0	0	0	0	0	0
	Stop	Stop	Free	Free	Free	Free
RT Channelized	Stop -	None	-		-	None
Storage Length	0	NOHE -		NULLE	_	110116
Veh in Median Storage, #		_	0			0
Grade, %	# 0	_	0	_	_	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	9	3	41	28	12	68
Major/Minor Mi	inor1	N	Major1		Major2	
Conflicting Flow All	147	55	0	0	69	0
Stage 1	55	-	_	_	_	_
Stage 2	92	_	_	_	_	_
Critical Hdwy	6.4	6.2	_	_	4.1	_
Critical Hdwy Stg 1	5.4	-	_	_	- '	_
Critical Hdwy Stg 2	5.4	_	_		_	_
Follow-up Hdwy	3.5	3.3	_		2.2	_
Pot Cap-1 Maneuver	850	1018	_		1545	_
Stage 1	973	1010	-		1040	_
Stage 2	937	_	_	_		-
Platoon blocked, %	331	-			_	-
	843	1018	-		1545	-
Mov Cap-1 Maneuver			-	-		
Mov Cap-2 Maneuver	843	-	-	-	-	-
Stage 1	973	-	-	-	-	-
Stage 2	930	-	-	-	-	-
Approach	WB		NB		SB	
HCM Control Delay, s	9.1		0		1.1	
HCM LOS	Α					
112.11.200	,,					
Minor Long/Major Marest		NDT	NDDV	MDI ~1	CDI	CDT
Minor Lane/Major Mvmt		NBT	NDKV	VBLn1	SBL	SBT
Capacity (veh/h)		-	-	881	1545	-
		-	-	0.014	บ.บบช	-
HCM Lane V/C Ratio				0.4	7.0	^
HCM Lane V/C Ratio HCM Control Delay (s)		-	-	9.1	7.3	0
HCM Lane V/C Ratio				9.1 A 0	7.3 A 0	0 A

	٠	<b>→</b>	*	•	•	•	1	<b>†</b>	~	-	ļ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	1			4		*	<b>†</b>	7	7	<b>†</b>	7
Traffic Volume (vph)	48	5	31	37	6	69	199	602	13	12	758	111
Future Volume (vph)	48	5	31	37	6	69	199	602	13	12	758	111
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Storage Lanes	1		0	0		0	1		1	1		1
Taper Length (m)	7.6			7.6			7.6			7.6		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped Bike Factor		0.98			1.00				0.98	1.00		
Frt		0.871			0.917				0.850			0.850
Flt Protected	0.950				0.984		0.950			0.950		
Satd. Flow (prot)	1383	1313	0	0	1598	0	1503	1685	1345	1601	1685	1381
Flt Permitted	0.821				0.876		0.309			0.399		
Satd. Flow (perm)	1195	1313	0	0	1422	0	489	1685	1316	672	1685	1381
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		31			69				36			58
Link Speed (k/h)		50			50			80			60	
Link Distance (m)		187.0			55.0			184.6			116.3	
Travel Time (s)		13.5			4.0			8.3			7.0	
Confl. Peds. (#/hr)			1	1					1	1		
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	25%	40%	15%	0%	17%	3%	15%	8%	15%	8%	8%	12%
Adj. Flow (vph)	48	5	31	37	6	69	199	602	13	12	758	111
Shared Lane Traffic (%)												
Lane Group Flow (vph)	48	36	0	0	112	0	199	602	13	12	758	111
Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2		2	6		6
Detector Phase	4	4		8	8		2	2	2	6	6	6
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	15.0
Pedestrian Calls (#/hr)	0	0		0	0		0	0	0	0	0	0
Act Effct Green (s)	8.1	8.1			8.1		42.3	42.3	42.3	42.3	42.3	42.3
Actuated g/C Ratio	0.14	0.14			0.14		0.73	0.73	0.73	0.73	0.73	0.73
v/c Ratio	0.14	0.17			0.14		0.76	0.49	0.73	0.02	0.62	0.13
- Tallo	0.23	V. 17			٧.٣٦		0.00	0.70	0.01	0.02	0.02	V. 1 1

	•	-	*	1	<b>←</b>	*	1	<b>†</b>	1	1	Ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	25.8	11.6			15.9		15.3	6.8	0.6	4.2	8.8	2.6
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	25.8	11.6			15.9		15.3	6.8	0.6	4.2	8.8	2.6
LOS	С	В			В		В	Α	Α	Α	Α	Α
Approach Delay		19.7			15.9			8.8			8.0	
Approach LOS		В			В			Α			Α	
Queue Length 50th (m)	4.4	0.4			3.9		9.1	25.1	0.0	0.3	36.9	1.5
Queue Length 95th (m)	12.0	6.6			15.1		#43.9	55.2	0.6	1.9	84.1	6.3
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	579	652			724		356	1230	970	490	1230	1023
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.06			0.15		0.56	0.49	0.01	0.02	0.62	0.11

Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 57.9

Natural Cycle: 90

Control Type: Actuated-Uncoordinated


Maximum v/c Ratio: 0.62

Intersection Signal Delay: 9.3 Intersection LOS: A Intersection Capacity Utilization 81.0% ICU Level of Service D

Analysis Period (min) 15

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



<sup># 95</sup>th percentile volume exceeds capacity, queue may be longer.

Intersection						
Int Delay, s/veh	4					
		EDD	\A/\;\	MOT	NE	NDD
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	f)			र्स	Y	
Traffic Vol, veh/h	26	0	144	172	0	60
Future Vol, veh/h	26	0	144	172	0	60
Conflicting Peds, #/hr	0	0	0	0	0	0
0	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage,	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	26	0	144	172	0	60
NA : /NA:			4		P	
	ajor1		Major2		/linor1	
Conflicting Flow All	0	0	26	0	486	26
Stage 1	-	-	-	-	26	-
Stage 2	-	-	-	-	460	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1601	-	544	1056
Stage 1	-	-	-	-	1002	-
Stage 2	-	-	-	-	640	-
Platoon blocked, %	-	_		-		
Mov Cap-1 Maneuver	-	_	1601	-	490	1056
Mov Cap-2 Maneuver	_	_	-	_	490	-
Stage 1	_	_	_	_	1002	_
Stage 2			_	_	577	_
Olaye Z	_	_	_	-	311	_
Approach	EB		WB		NB	
HCM Control Delay, s	0		3.4		8.6	
					Α	
HCM LOS						
HCM LOS						
		JDI 4	ГРТ	FDD	WDI	WDT
Minor Lane/Major Mvmt	1	NBLn1	EBT	EBR	WBL	WBT
Minor Lane/Major Mvmt Capacity (veh/h)	1	1056	-	-	1601	-
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	1	1056 0.057		-	1601 0.09	-
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	1	1056 0.057 8.6	-	-	1601 0.09 7.5	- - 0
Minor Lane/Major Mvmt Capacity (veh/h) HCM Lane V/C Ratio	1	1056 0.057	- -	-	1601 0.09	-

Intersection						
Int Delay, s/veh	0.5					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	LDL	LDIN	NDL	<b>†</b>	<u>361</u>	7
Traffic Vol, veh/h	0	54	0	816	<b>7</b> 91	41
Future Vol, veh/h	0	54	0	816	791	41
<u> </u>	0	0	0	010	0	0
Conflicting Peds, #/hr		Stop		Free	Free	Free
Sign Control	Stop		Free			
RT Channelized	-		-		-	None
Storage Length	<u>-</u>	0	-	-	-	25
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	54	0	816	791	41
Major/Minor N	1inor2	N	/lajor1	N	/lajor2	
Conflicting Flow All	-	791	-	0	-	0
Stage 1	-	791	-	-		-
Stage 1 Stage 2		-				-
	-	6.2	-	-	-	
Critical Hdwy	-		-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	393	0	-	-	-
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	-	393	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Annragah	ED		ND		CD	
Approach	EB		NB		SB	
HCM Control Delay, s	15.6		0		0	
HCM LOS	С					
Minor Lane/Major Mvmt		NBT E	EBL <sub>n1</sub>	SBT	SBR	
Capacity (veh/h)		-	393	-	-	
HCM Lane V/C Ratio		_	0.137	-	_	
HCM Control Delay (s)		-	15.6	-	_	
HCM Lane LOS		_	С	-	_	
HCM 95th %tile Q(veh)		_	0.5	_	-	
, , , , , , , , , , , , , , , ,			3.0			

	۶	<b>→</b>	•	•	<b>←</b>	•	1	<b>†</b>	~	/	ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1			4		×	<b>^</b>	7	¥	<b>↑</b>	7
Traffic Volume (vph)	150	7	126	23	5	50	100	768	47	48	818	38
Future Volume (vph)	150	7	126	23	5	50	100	768	47	48	818	38
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Storage Lanes	1		0	0		0	1		1	1		1
Taper Length (m)	7.6			7.6			7.6			7.6		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped Bike Factor		0.98			0.99							
Frt		0.858			0.913				0.850			0.850
Flt Protected	0.950				0.985		0.950			0.950		
Satd. Flow (prot)	1544	1408	0	0	1516	0	1729	1767	1517	1695	1733	1432
Flt Permitted	0.706				0.884		0.221			0.252		
Satd. Flow (perm)	1147	1408	0	0	1360	0	402	1767	1517	450	1733	1432
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		115			50				47			36
Link Speed (k/h)		50			50			60			60	
Link Distance (m)		187.0			55.0			184.6			116.3	
Travel Time (s)		13.5			4.0			11.1			7.0	
Confl. Peds. (#/hr)			2	2								
Confl. Bikes (#/hr)						1						
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	12%	0%	9%	9%	20%	4%	0%	3%	2%	2%	5%	8%
Adj. Flow (vph)	150	7	126	23	5	50	100	768	47	48	818	38
Shared Lane Traffic (%)												
Lane Group Flow (vph)	150	133	0	0	78	0	100	768	47	48	818	38
Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2		2	6		6
Detector Phase	4	4		8	8		2	2	2	6	6	6
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Lead/Lag	0.0	0.0			0.0		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	<b>U</b>
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	15.0
Pedestrian Calls (#/hr)	0	0		0	0		0	0	0	0	0	0.0
Act Effct Green (s)	13.5	13.5		<u> </u>	13.5		39.0	39.0	39.0	39.0	39.0	39.0
Actuated g/C Ratio	0.21	0.21			0.21		0.61	0.61	0.61	0.61	0.61	0.61
- Notation 9/0 Mail	V.Z I	V.Z I			V.Z I		0.01	0.01	0.01	0.01	0.01	0.01

	•	<b>-</b>	*	1	•	*	4	<b>†</b>	-	1	Ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
v/c Ratio	0.61	0.34			0.24		0.41	0.71	0.05	0.17	0.77	0.04
Control Delay	32.6	8.1			11.0		14.7	14.9	2.7	9.0	17.5	3.1
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	32.6	8.1			11.0		14.7	14.9	2.7	9.0	17.5	3.1
LOS	С	Α			В		В	В	Α	Α	В	Α
Approach Delay		21.1			11.0			14.3			16.5	
Approach LOS		С			В			В			В	
Queue Length 50th (m)	14.9	1.6			2.5		5.0	51.2	0.0	2.0	58.3	0.1
Queue Length 95th (m)	30.1	12.3			11.0		21.3	#140.5	3.9	8.8	#157.8	3.7
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	508	688			630		246	1085	950	276	1064	893
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.30	0.19			0.12		0.41	0.71	0.05	0.17	0.77	0.04

#### Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 63.5

Natural Cycle: 80

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.77


Intersection Signal Delay: 15.9 Intersection LOS: B
Intersection Capacity Utilization 84.1% ICU Level of Service E

Analysis Period (min) 15

# 95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Lanes, Volumes, Timings

Synchro 11 Report

September 2025

Intersection						
Int Delay, s/veh	4.1					
		EDD	MDI	MDT	NDI	NDE
	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1			4	Y	
Traffic Vol, veh/h	194	0	112	31	0	89
Future Vol, veh/h	194	0	112	31	0	89
Conflicting Peds, #/hr	0	0	0	0	0	0
	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage,	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	194	0	112	31	0	89
					*	
	ajor1		/lajor2		/linor1	
Conflicting Flow All	0	0	194	0	449	194
Stage 1	-	-	-	-	194	-
Stage 2	-	-	-	-	255	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	_	-	-	5.4	-
Follow-up Hdwy	_	-	2.2	_	3.5	3.3
Pot Cap-1 Maneuver	-	_	1391	_	571	853
Stage 1	_	_	_	_	844	-
Stage 2	_	_	_	_	792	_
Platoon blocked, %	_	<u>_</u>		_	102	
Mov Cap-1 Maneuver	_		1391		524	853
Mov Cap-1 Maneuver		_		-	524	- 000
	-	-	-			
Stage 1	-	-	-	-	844	-
Stage 2	-	-	-	-	727	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		6.1		9.7	
HCM LOS			0.1		A	
TIONI EOO					,,	
Minor Lane/Major Mvmt	1	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)		853	-	-	1391	-
HCM Lane V/C Ratio		0.104	-	-	0.081	-
HCM Control Delay (s)		9.7	-	-	7.8	0
HCM Lane LOS		Α	-	-	A	A
HCM 95th %tile Q(veh)		0.3	_	-	0.3	-
		3.0			3.5	

HCM 2010 TWSC Synchro 11 Report September 2025

Intersection						
Int Delay, s/veh	1.1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations		7		<b>^</b>	<b>^</b>	7
Traffic Vol, veh/h	0	106	0	921	933	40
Future Vol, veh/h	0	106	0	921	933	40
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-		-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage	, # 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	106	0	921	933	40
Major/Minor I	Minor2		/lajor1		/lajor2	
						0
Conflicting Flow All	-	933	-	0	-	0
Stage 1	-	-	-	-	-	-
Stage 2	-	6.2	-	-	-	-
Critical Hdwy	-		-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	325	0	-	-	-
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	-	-
Platoon blocked, %		005		-	-	-
Mov Cap-1 Maneuver	-	325	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	21.3		0		0	
HCM LOS	C		•		•	
. 10 200						
Minor Lane/Major Mvm	<u>it</u>	NBT E		SBT	SBR	
Capacity (veh/h)		-	325	-	-	
HCM Lane V/C Ratio			0.326	-	-	
HCM Control Delay (s)		-	21.3	-	-	
HCM Lane LOS		-	С	-	-	
HCM 95th %tile Q(veh)	١	_	1.4	_	_	

Synchro 11 Report September 2025 HCM 2010 TWSC

		۶	<b>→</b>	*	1	•	•	4	<b>†</b>	~	-	Ţ	1
Traffix (volume (vph)	Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Traffic Volume (vph)	Lane Configurations	*	13			4		*	<b>*</b>	7	*	<b>^</b>	7
Future Volume (vph)		48		31	37		69			13			
Idea   Flow (ryphpi)		48	5	31	37	6	69	199	674	13	12	962	
Storage Length (m)   50.0   0.0   0.0   0.0   140.0   0.0   60.0   25.0		1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Lanes	,	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Lane Util. Factor		1		0	0		0	1		1	1		1
Lane Unil. Factor		7.6			7.6			7.6			7.6		
Fith		1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fit Protected   0.950   0.984   0.950   0.500   0.981   0.981   0.980   0.980   0.981   0.980   0.98	Ped Bike Factor		0.98			1.00				0.98	1.00		
Satd. Flow (prot)   1383   1313   0   0   1598   0   1503   1685   1345   1601   1685   1381   Fli Permitted   0.821   0   0.876   0.198   0.375   0	Frt		0.871			0.917				0.850			0.850
Fit Permitted	Flt Protected	0.950				0.984		0.950			0.950		
Satd. Flow (perm)   1195	Satd. Flow (prot)	1383	1313	0	0	1598	0	1503	1685	1345	1601	1685	1381
Right Turn on Red	Flt Permitted	0.821				0.876		0.198			0.357		
Satd. Flow (RTOR)	Satd. Flow (perm)	1195	1313	0	0	1422	0	313	1685	1316	601	1685	1381
Link Speed (k/h)				Yes			Yes			Yes			Yes
Link Distance (m)	Satd. Flow (RTOR)		31			69				36			46
Link Distance (m)			50			50			60			60	
Confil Peds. (#hr)			187.0			55.0			184.6			116.3	
Peak Hour Factor	Travel Time (s)		13.5			4.0			11.1			7.0	
Heavy Vehicles (%)	Confl. Peds. (#/hr)			1	1					1	1		
Adj. Flow (vph)         48         5         31         37         6         69         199         674         13         12         962         111           Shared Lane Traffic (%)         Lane Group Flow (vph)         48         36         0         0         112         0         199         674         13         12         962         111           Turn Type         Perm         NA         Perm         NA         Perm         NA         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         NA         Perm         NA         Perm         Perm         NA         Perm         Perm         NA         Perm         Perm         Perm         NA         Perm         Perm         Perm         NA         Perm         Perm         Perm         NA         Perm         Perm         Perm         Perm         NA         Perm         Perm         Perm         Perm         NA         Perm         <	Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj. Flow (vph)   Ads   5   31   37   6   69   199   674   13   12   962   111	Heavy Vehicles (%)	25%	40%	15%	0%	17%	3%	15%	8%	15%	8%	8%	12%
Lane Group Flow (vph)		48	5	31	37	6	69	199	674	13	12	962	111
Turn Type         Perm         NA         Perm         NA         Perm         NA         Perm         Perm           A Particle All         4         4         8	Shared Lane Traffic (%)												
Turn Type         Perm         NA         Perm         NA         Perm            4         4         4         8	Lane Group Flow (vph)	48	36	0	0	112	0	199	674	13	12	962	111
Permitted Phases		Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Detector Phase   4	Protected Phases		4			8			2			6	
Switch Phase         Minimum Initial (s)         5.0         5.3         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%         55.3%	Permitted Phases	4			8			2		2	6		6
Minimum Initial (s)         5.0         4.1         27.4<	Detector Phase	4	4		8	8		2	2	2	6	6	6
Minimum Split (s)         33.5         33.5         33.5         33.5         27.4         27.8         27.8         27.8         27.8 <td>Switch Phase</td> <td></td>	Switch Phase												
Total Split (s)         33.5         33.5         33.5         33.5         41.1         41.1	Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Total Split (%)         44.7%         44.7%         44.7%         44.7%         55.3%	Minimum Split (s)	33.5	33.5		33.5	33.5		27.4	27.4	27.4	27.4	27.4	27.4
Maximum Green (s)         28.0         28.0         28.0         28.0         28.0         36.1         41.1         4.1 <t< td=""><td>Total Split (s)</td><td>33.5</td><td>33.5</td><td></td><td>33.5</td><td>33.5</td><td></td><td>41.5</td><td>41.5</td><td>41.5</td><td>41.5</td><td>41.5</td><td>41.5</td></t<>	Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Maximum Green (s)         28.0         28.0         28.0         28.0         36.1         4.1	Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
All-Red Time (s) 1.9 1.9 1.9 1.9 1.0 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3	Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Lost Time Adjust (s)         0.0	Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
Total Lost Time (s)         5.5         5.5         5.5         5.5         5.4	All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lead/Lag         Lead-Lag Optimize?         Vehicle Extension (s)       3.0	Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Lead-Lag Optimize?         Vehicle Extension (s)       3.0	Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Vehicle Extension (s)         3.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0         7.0	Lead/Lag												
Recall Mode         None         None         None         None         Min	Lead-Lag Optimize?												
Walk Time (s)       7.0	Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Flash Dont Walk (s)       21.0       21.0       21.0       21.0       15.0	Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Pedestrian Calls (#/hr)         0	Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Pedestrian Calls (#/hr)         0		21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	
Act Effct Green (s)       8.1       8.1       8.1       42.3       42.	, ,				0	0							
Actuated g/C Ratio 0.14 0.14 0.14 0.73 0.73 0.73 0.73 0.73 0.73	, ,	8.1	8.1					42.3			42.3		
· · · · ·	. ,												
	v/c Ratio	0.29	0.17			0.44		0.87	0.55	0.01		0.78	0.11

Lanes, Volumes, Timings

Synchro 11 Report

September 2025

	۶	<b>→</b>	*	1	<b>←</b>	*	1	<b>†</b>	1	1	ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	25.8	11.6			15.9		52.8	7.6	0.6	4.2	14.9	2.9
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	25.8	11.6			15.9		52.8	7.6	0.6	4.2	14.9	2.9
LOS	С	В			В		D	Α	Α	Α	В	Α
Approach Delay		19.7			15.9			17.6			13.6	
Approach LOS		В			В			В			В	
Queue Length 50th (m)	4.4	0.4			3.9		14.7	30.3	0.0	0.3	60.2	1.8
Queue Length 95th (m)	12.0	6.6			15.1		#36.4	66.9	0.6	1.9	#161.1	6.8
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	579	652			724		228	1230	970	438	1230	1020
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.06			0.15		0.87	0.55	0.01	0.03	0.78	0.11

Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 57.9

Natural Cycle: 130

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.87

Intersection Signal Delay: 15.6 Intersection LOS: B
Intersection Capacity Utilization 92.3% ICU Level of Service F

Analysis Period (min) 15

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Lanes, Volumes, Timings

Synchro 11 Report

September 2025

<sup># 95</sup>th percentile volume exceeds capacity, queue may be longer.

Intersection						
Int Delay, s/veh	4					
		<b>ED</b> 5	14/5	MOT	NE	NES
	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	₽			र्स	Y	
Traffic Vol, veh/h	26	0	144	172	0	60
Future Vol, veh/h	26	0	144	172	0	60
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	# 0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	26	0	144	172	0	60
					•	
	ajor1		Major2	<b>N</b>	/linor1	
Conflicting Flow All	0	0	26	0	486	26
Stage 1	-	-	-	-	26	-
Stage 2	-	-	-	-	460	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1601	-	544	1056
Stage 1	-	_	-	-	1002	-
Stage 2	_	_	_	-	640	-
Platoon blocked, %	_	_		_	010	
Mov Cap-1 Maneuver		_	1601	_	490	1056
Mov Cap-2 Maneuver	_	_	-		490	-
Stage 1		_	_	_	1002	_
•		-	-	-	577	
Stage 2	-	-	-	<del>-</del>	5//	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		3.4		8.6	
HCM LOS					Α	
1.0		IDL 4	EST	ED.5	14/51	MAIST
Minor Lane/Major Mvmt		NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)		1056	-	-	1601	-
HCM Lane V/C Ratio		0.057	-	-	0.09	-
HCM Control Delay (s)		8.6	-	-	7.5	0
HCM Lane LOS		Α	-	-	Α	Α
HCM 95th %tile Q(veh)		0.2	-	-	0.3	-

HCM 2010 TWSC Synchro 11 Report September 2025

Intersection						
Int Delay, s/veh	0.5					
		EDD	NDI	NDT	CDT	CDD
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations		7		<b>^</b>	<b>↑</b>	7
Traffic Vol, veh/h	0	54	0	890	999	41
Future Vol, veh/h	0	54	0	890	999	41
Conflicting Peds, #/hr	0	0	0	_ 0	0	_ 0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage	-	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	54	0	890	999	41
Major/Minor I	Minor2	N	//ajor1	N	//ajor2	
Conflicting Flow All	-	999	-	0	-	0
Stage 1	_	-		-	_	-
Stage 2	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	_	_
Critical Hdwy	_	6.2	_	_	_	_
Critical Hdwy Stg 1	_	- 0.2	_		_	
Critical Hdwy Stg 1		_		_	_	_
Follow-up Hdwy	_	3.3	_	_	_	
Pot Cap-1 Maneuver	0	298	0	_	_	_
•	0	290	0	-	-	-
Stage 1	0		0	-		-
Stage 2	U	-	U	-	-	-
Platoon blocked, %		200		-	-	-
Mov Cap-1 Maneuver	-	298	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
O		-	-	-	-	-
Stage 2	-					
Stage 2	-					
	EB		NB		SB	
Approach	EB 19 7		NB 0		SB 0	
Approach HCM Control Delay, s	19.7		NB 0		SB 0	
Approach						
Approach HCM Control Delay, s HCM LOS	19.7 C		0		0	
Approach HCM Control Delay, s HCM LOS Minor Lane/Major Mvm	19.7 C	NBT E	0 EBLn1	SBT		
Approach HCM Control Delay, s HCM LOS  Minor Lane/Major Mvm Capacity (veh/h)	19.7 C	-	0 EBLn1 298	SBT	0	
Approach HCM Control Delay, s HCM LOS  Minor Lane/Major Mvm Capacity (veh/h) HCM Lane V/C Ratio	19.7 C	-	0 EBLn1 298 0.181		0 SBR	
Approach HCM Control Delay, s HCM LOS  Minor Lane/Major Mvm Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	19.7 C	-	0 EBLn1 298 0.181 19.7	-	0 SBR	
Approach HCM Control Delay, s HCM LOS  Minor Lane/Major Mvm Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s) HCM Lane LOS	19.7 C	-	0 EBLn1 298 0.181 19.7 C	-	0 SBR -	
Approach HCM Control Delay, s HCM LOS  Minor Lane/Major Mvm Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (s)	19.7 C	-	0 EBLn1 298 0.181 19.7	- - -	0 SBR - -	

Synchro 11 Report September 2025 HCM 2010 TWSC

	•	<b>→</b>	*	1	•	•	1	Ť	~	-	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1			4		×	<b>†</b>	7	7	<b>↑</b>	7
Traffic Volume (vph)	150	7	126	23	5	50	100	942	47	48	900	38
Future Volume (vph)	150	7	126	23	5	50	100	942	47	48	900	38
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Storage Length (m)	50.0		0.0	0.0		0.0	140.0		0.0	60.0		25.0
Storage Lanes	1		0	0		0	1		1	1		1
Taper Length (m)	7.6			7.6			7.6			7.6		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped Bike Factor		0.98			0.99							
Frt		0.858			0.913				0.850			0.850
Flt Protected	0.950				0.985		0.950			0.950		
Satd. Flow (prot)	1544	1408	0	0	1516	0	1729	1767	1517	1695	1733	1432
Flt Permitted	0.706				0.884		0.170			0.144		
Satd. Flow (perm)	1147	1408	0	0	1360	0	309	1767	1517	257	1733	1432
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		91			50				47			36
Link Speed (k/h)		50			50			60			60	
Link Distance (m)		187.0			55.0			184.6			116.3	
Travel Time (s)		13.5			4.0			11.1			7.0	
Confl. Peds. (#/hr)			2	2								
Confl. Bikes (#/hr)						1						
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	12%	0%	9%	9%	20%	4%	0%	3%	2%	2%	5%	8%
Adj. Flow (vph)	150	7	126	23	5	50	100	942	47	48	900	38
Shared Lane Traffic (%)												
Lane Group Flow (vph)	150	133	0	0	78	0	100	942	47	48	900	38
Turn Type	Perm	NA		Perm	NA		Perm	NA	Perm	Perm	NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2		2	6		6
Detector Phase	4	4		8	8		2	2	2	6	6	6
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	33.5	33.5		33.5	33.5		33.4	33.4	33.4	33.4	33.4	33.4
Total Split (s)	33.5	33.5		33.5	33.5		41.5	41.5	41.5	41.5	41.5	41.5
Total Split (%)	44.7%	44.7%		44.7%	44.7%		55.3%	55.3%	55.3%	55.3%	55.3%	55.3%
Maximum Green (s)	28.0	28.0		28.0	28.0		36.1	36.1	36.1	36.1	36.1	36.1
Yellow Time (s)	3.6	3.6		3.6	3.6		4.1	4.1	4.1	4.1	4.1	4.1
All-Red Time (s)	1.9	1.9		1.9	1.9		1.3	1.3	1.3	1.3	1.3	1.3
Lost Time Adjust (s)	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5			5.5		5.4	5.4	5.4	5.4	5.4	5.4
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None		None	None		Min	Min	Min	Min	Min	Min
Walk Time (s)	7.0	7.0		7.0	7.0		7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	21.0	21.0		21.0	21.0		15.0	15.0	15.0	15.0	15.0	15.0
Pedestrian Calls (#/hr)	0	0		0	0		0	0	0	0	0	0
Act Effct Green (s)	13.5	13.5		J	13.5		39.0	39.0	39.0	39.0	39.0	39.0
Actuated g/C Ratio	0.21	0.21			0.21		0.61	0.61	0.61	0.61	0.61	0.61
- ioladioa g/o rialio	۷.۲۱	V.Z I			V.Z I		0.01	0.01	0.01	0.01	0.01	0.01

Lanes, Volumes, Timings

Synchro 11 Report

September 2025

	•	-	*	-	←	*	1	<b>†</b>	1	1	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
v/c Ratio	0.61	0.36			0.24		0.53	0.87	0.05	0.31	0.85	0.04
Control Delay	32.6	10.5			11.0		23.7	23.6	2.7	14.6	21.9	3.1
Queue Delay	0.0	0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	32.6	10.5			11.0		23.7	23.6	2.7	14.6	21.9	3.1
LOS	С	В			В		С	С	Α	В	С	Α
Approach Delay		22.2			11.0			22.7			20.8	
Approach LOS		С			В			С			С	
Queue Length 50th (m)	14.9	3.8			2.5		5.6	75.9	0.0	2.2	70.4	0.1
Queue Length 95th (m)	30.1	14.9			11.0		#31.3	#191.5	3.9	11.9	#181.5	3.7
Internal Link Dist (m)		163.0			31.0			160.6			92.3	
Turn Bay Length (m)	50.0						140.0			60.0		25.0
Base Capacity (vph)	508	674			630		190	1085	950	157	1064	893
Starvation Cap Reductn	0	0			0		0	0	0	0	0	0
Spillback Cap Reductn	0	0			0		0	0	0	0	0	0
Storage Cap Reductn	0	0			0		0	0	0	0	0	0
Reduced v/c Ratio	0.30	0.20			0.12		0.53	0.87	0.05	0.31	0.85	0.04

#### Intersection Summary

Area Type: Other

Cycle Length: 75

Actuated Cycle Length: 63.5

Natural Cycle: 90

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.87


Intersection Signal Delay: 21.5 Intersection LOS: C Intersection Capacity Utilization 89.3% ICU Level of Service E

Analysis Period (min) 15

# 95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: Fallowfield Road & O; Keefe Court/Cobble Hill Drive



Synchro 11 Report Lanes, Volumes, Timings

Intersection						
Int Delay, s/veh	4.1					
		EDD	///DI	WDT	NDI	NDD
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	104	^	440	<del>વ</del>	¥	00
Traffic Vol, veh/h	194	0	112	31	0	89
Future Vol, veh/h	194	0	112	31	0	89
Conflicting Peds, #/hr	_ 0	_ 0	_ 0	_ 0	0	0
3	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	194	0	112	31	0	89
Majay/Minay M	-:1		/aia#0		11:1	
	ajor1		Major2		Minor1	404
Conflicting Flow All	0	0	194	0	449	194
Stage 1	-	-	-	-	194	-
Stage 2	-	-	-	-	255	-
Critical Hdwy	-	-	4.1	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.2	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1391	-	571	853
Stage 1	-	-	-	-	844	-
Stage 2	-	_	-	-	792	-
Platoon blocked, %	-	-		-		
Mov Cap-1 Maneuver	-	_	1391	_	524	853
Mov Cap-2 Maneuver	_	_	_	_	524	-
Stage 1	_	_	_	_	844	_
Stage 2	_	_	_	_	727	_
Olago Z					121	
Approach	EB		WB		NB	
HCM Control Delay, s	0		6.1		9.7	
HCM LOS					Α	
Minor Long/Major Maret		VIDI ~1	EDT	EDD	WDI	WDT
Minor Lane/Major Mvmt	ſ	VBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)		853	-		1391	-
HCM Lane V/C Ratio		0.104	-		0.081	-
HCM Control Delay (s)		9.7	-	-	7.8	0
		Α	-	-	Α	Α
HCM Lane LOS						
HCM Lane LOS HCM 95th %tile Q(veh)		0.3	-	-	0.3	-

Synchro 11 Report September 2025 HCM 2010 TWSC

Intersection						
Int Delay, s/veh	1.1					
		EDD	NDI	NDT	CDT	CDD
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	^	100		<b>^</b>	1010	7
Traffic Vol, veh/h	0	106	0	1101	1019	40
Future Vol, veh/h	0	106	0	1101	1019	40
Conflicting Peds, #/hr	0	0	_ 0	_ 0	_ 0	_ 0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	-	0	-	-	-	25
Veh in Median Storage,		-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	0	106	0	1101	1019	40
Major/Minor	linor2	N	laior1	N	Major2	
			/lajor1		Major2	^
Conflicting Flow All	-	1019	-	0	-	0
Stage 1	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-
Critical Hdwy	-	6.2	-	-	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-
Follow-up Hdwy	-	3.3	-	-	-	-
Pot Cap-1 Maneuver	0	290	0	-	-	-
Stage 1	0	-	0	-	-	-
Stage 2	0	-	0	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	-	290	-	-	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-
Stage 2	-	-	_	_	-	-
					0.5	
Approach	EB		NB		SB	
HCM Control Delay, s	24.4		0		0	
HCM LOS	С					
Minor Lane/Major Mvmt		NBT E	-RI n1	SBT	SBR	
		-		ODT	ODIN	
Canacity (yeh/h)				-		
Capacity (veh/h)					-	
HCM Lane V/C Ratio			0.366			
HCM Lane V/C Ratio HCM Control Delay (s)		-	24.4	-	-	
HCM Lane V/C Ratio						

Synchro 11 Report September 2025 HCM 2010 TWSC

# Appendix G – Trip Generation Data

# Medical-Dental Office Building - Stand-Alone

(720)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 7 and 9 a.m.


Setting/Location: General Urban/Suburban

Number of Studies: 24 Avg. 1000 Sq. Ft. GFA: 25

Directional Distribution: 79% entering, 21% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
3.10	0.87 - 14.30	1.49



# Medical-Dental Office Building - Stand-Alone

(720)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 4 and 6 p.m.


Setting/Location: General Urban/Suburban

Number of Studies: 30 Avg. 1000 Sq. Ft. GFA: 23

Directional Distribution: 30% entering, 70% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	3.93	0.62 - 8.86	1.86	



## High-Turnover (Sit-Down) Restaurant

(932)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 7 and 9 a.m.


Setting/Location: General Urban/Suburban

Number of Studies: 37 Avg. 1000 Sq. Ft. GFA: 5

Directional Distribution: 55% entering, 45% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	9.57	0.76 - 102.39	11.61	



## High-Turnover (Sit-Down) Restaurant

(932)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 4 and 6 p.m.


Setting/Location: General Urban/Suburban

Number of Studies: 104 Avg. 1000 Sq. Ft. GFA: 6

Directional Distribution: 61% entering, 39% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	9.05	0.92 - 62.00	6.18	



## **General Office Building**

(710)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 7 and 9 a.m.


Setting/Location: General Urban/Suburban

Number of Studies: 221 Avg. 1000 Sq. Ft. GFA: 201

Directional Distribution: 88% entering, 12% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation	
1.52	0.32 - 4.93	0.58	



# **General Office Building**

(710)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 4 and 6 p.m.


Setting/Location: General Urban/Suburban

Number of Studies: 232 Avg. 1000 Sq. Ft. GFA: 199

Directional Distribution: 17% entering, 83% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	1.44	0.26 - 6.20	0.60	



# Pharmacy/Drugstore without Drive-Through Window (880)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 7 and 9 a.m.


Setting/Location: General Urban/Suburban

Number of Studies: 7 Avg. 1000 Sq. Ft. GFA: 10

Directional Distribution: 65% entering, 35% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	2.94	1.17 - 4.30	1.25	



# Pharmacy/Drugstore without Drive-Through Window (880)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 4 and 6 p.m.


Setting/Location: General Urban/Suburban

Number of Studies: 13 Avg. 1000 Sq. Ft. GFA: 11

Directional Distribution: 49% entering, 51% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
8.51	5.11 - 11.70	2.16



# **Day Care Center**

(565)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 7 and 9 a.m.


Setting/Location: General Urban/Suburban

Number of Studies: 89 Avg. 1000 Sq. Ft. GFA: 5

Directional Distribution: 53% entering, 47% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	11.00	1.79 - 57.02	6.08	



# **Day Care Center**

(565)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA

On a: Weekday,

Peak Hour of Adjacent Street Traffic, One Hour Between 4 and 6 p.m.


Setting/Location: General Urban/Suburban

Number of Studies: 90 Avg. 1000 Sq. Ft. GFA: 5

Directional Distribution: 47% entering, 53% exiting

#### Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate		Range of Rates	Standard Deviation	
	11.12	1.56 - 40.85	6.28	



# Appendix H – TDM Checklists

### **TDM-Supportive Development Design and Infrastructure Checklist:**

Non-Residential Developments (office, institutional, retail or industrial)

Legend		
REQUIRED	The Official Plan or Zoning By-law provides related guidance that must be followed	
BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users	
BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance	

TDM-supportive design & infrastructure measures:  Non-residential developments			Check if completed & add descriptions, explanations or plan/drawing references
	1.	WALKING & CYCLING: ROUTES	
	1.1	Building location & access points	
BASIC	1.1.1	Locate building close to the street, and do not locate parking areas between the street and building entrances	
BASIC	1.1.2	Locate building entrances in order to minimize walking distances to sidewalks and transit stops/stations	
BASIC	1.1.3	Locate building doors and windows to ensure visibility of pedestrians from the building, for their security and comfort	$\overline{\square}$
	1.2	Facilities for walking & cycling	
REQUIRED	1.2.1	Provide convenient, direct access to stations or major stops along rapid transit routes within 600 metres; minimize walking distances from buildings to rapid transit; provide pedestrian-friendly, weather-protected (where possible) environment between rapid transit accesses and building entrances; ensure quality linkages from sidewalks through building entrances to integrated stops/stations (see Official Plan policy 4.3.3)	N/A
REQUIRED	1.2.2	Provide safe, direct and attractive pedestrian access from public sidewalks to building entrances through such measures as: reducing distances between public sidewalks and major building entrances; providing walkways from public streets to major building entrances; within a site, providing walkways along the front of adjoining buildings, between adjacent buildings, and connecting areas where people may congregate, such as courtyards and transit stops; and providing weather protection through canopies, colonnades, and other design elements wherever possible (see Official Plan policy 4.3.12)	

	TDM-s	supportive design & infrastructure measures:  Non-residential developments	Check if completed & add descriptions, explanations or plan/drawing references
REQUIRED	1.2.3	Provide sidewalks of smooth, well-drained walking surfaces of contrasting materials or treatments to differentiate pedestrian areas from vehicle areas, and provide marked pedestrian crosswalks at intersection sidewalks (see Official Plan policy 4.3.10)	
REQUIRED	1.2.4	Make sidewalks and open space areas easily accessible through features such as gradual grade transition, depressed curbs at street corners and convenient access to extra-wide parking spaces and ramps (see Official Plan policy 4.3.10)	Sidewalks around building
REQUIRED	1.2.5	Include adequately spaced inter-block/street cycling and pedestrian connections to facilitate travel by active transportation. Provide links to the existing or planned network of public sidewalks, multi-use pathways and onroad cycle routes. Where public sidewalks and multi-use pathways intersect with roads, consider providing traffic control devices to give priority to cyclists and pedestrians (see Official Plan policy 4.3.11)	
BASIC	1.2.6	Provide safe, direct and attractive walking routes from building entrances to nearby transit stops	$\square$
BASIC	1.2.7	Ensure that walking routes to transit stops are secure, visible, lighted, shaded and wind-protected wherever possible	lacksquare
BASIC	1.2.8	Design roads used for access or circulation by cyclists using a target operating speed of no more than 30 km/h, or provide a separated cycling facility	$\square$
	1.3	Amenities for walking & cycling	_
BASIC	1.3.1	Provide lighting, landscaping and benches along walking and cycling routes between building entrances and streets, sidewalks and trails	$\square$
BASIC	1.3.2	Provide wayfinding signage for site access (where required, e.g. when multiple buildings or entrances exist) and egress (where warranted, such as when directions to reach transit stops/stations, trails or other common destinations are not obvious)	

	TDM-s	supportive design & infrastructure measures:  Non-residential developments	Check if completed & add descriptions, explanations or plan/drawing references
	2.	WALKING & CYCLING: END-OF-TRIP FACILITY	TIES
	2.1	Bicycle parking	
REQUIRED	2.1.1	Provide bicycle parking in highly visible and lighted areas, sheltered from the weather wherever possible (see Official Plan policy 4.3.6)	curb depression provided to facilitate access to internal drive aisle
REQUIRED	2.1.2	Provide the number of bicycle parking spaces specified for various land uses in different parts of Ottawa; provide convenient access to main entrances or well-used areas (see Zoning By-law Section 111)	
REQUIRED	2.1.3	Ensure that bicycle parking spaces and access aisles meet minimum dimensions; that no more than 50% of spaces are vertical spaces; and that parking racks are securely anchored (see Zoning By-law Section 111)	✓ racks to be secured and anchored
BASIC	2.1.4	Provide bicycle parking spaces equivalent to the expected number of commuter cyclists (assuming the cycling mode share target is met), plus the expected peak number of customer/visitor cyclists	
BETTER	2.1.5	Provide bicycle parking spaces equivalent to the expected number of commuter and customer/visitor cyclists, plus an additional buffer (e.g. 25 percent extra) to encourage other cyclists and ensure adequate capacity in peak cycling season	
	2.2	Secure bicycle parking	
REQUIRED	, i		□ <sub>N/A</sub>
BETTER			
	2.3	Shower & change facilities	
BASIC	2.3.1	Provide shower and change facilities for the use of active commuters	
BETTER	2.3.2	In addition to shower and change facilities, provide dedicated lockers, grooming stations, drying racks and laundry facilities for the use of active commuters	
	2.4	Bicycle repair station	
BETTER	2.4.1	Provide a permanent bike repair station, with commonly used tools and an air pump, adjacent to the main bicycle parking area (or secure bicycle parking area, if provided)	

	TDM-s	supportive design & infrastructure measures:  Non-residential developments	Check if completed & add descriptions, explanations or plan/drawing references			
	3.	TRANSIT				
	3.1	Customer amenities				
BASIC	3.1.1	Provide shelters, lighting and benches at any on-site transit stops	□ <sub>N/A</sub>			
BASIC	3.1.2	Where the site abuts an off-site transit stop and insufficient space exists for a transit shelter in the public right-of-way, protect land for a shelter and/or install a shelter	N/A			
BETTER	3.1.3	Provide a secure and comfortable interior waiting area by integrating any on-site transit stops into the building				
	4.	RIDESHARING				
	4.1	Pick-up & drop-off facilities				
BASIC	4.1.1	Provide a designated area for carpool drivers (plus taxis and ride-hailing services) to drop off or pick up passengers without using fire lanes or other no-stopping zones	Pick-up/drop-off at main entrance			
	4.2	Carpool parking				
BASIC	4.2.1	Provide signed parking spaces for carpools in a priority location close to a major building entrance, sufficient in number to accommodate the mode share target for carpools				
BETTER	4.2.2	At large developments, provide spaces for carpools in a separate, access-controlled parking area to simplify enforcement				
	5.	CARSHARING & BIKESHARING				
	5.1	Carshare parking spaces				
BETTER	5.1.1	Provide carshare parking spaces in permitted non-residential zones, occupying either required or provided parking spaces (see Zoning By-law Section 94)				
	5.2	Bikeshare station location				
BETTER	5.2.1	Provide a designated bikeshare station area near a major building entrance, preferably lighted and sheltered with a direct walkway connection				

TDM-s	supportive design & infrastructure measures:  Non-residential developments	Check if completed & add descriptions, explanations or plan/drawing references			
6.	PARKING				
6.1	Number of parking spaces				
6.1.1	Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for	Parking meets and does not exceed Zoning By-law requirements			
6.1.2	Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking				
6.1.3	Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (see Zoning By-law Section 104)				
6.1.4	Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (see Zoning By-law Section 111)				
6.2	Separate long-term & short-term parking areas				
6.2.1	Separate short-term and long-term parking areas using signage or physical barriers, to permit access controls and simplify enforcement (i.e. to discourage employees from parking in visitor spaces, and vice versa)				
7.	OTHER				
7.1	On-site amenities to minimize off-site trips				
7.1.1	Provide on-site amenities to minimize mid-day or mid-commute errands				
	6.1.2 6.1.3 6.1.4 6.1.4 7.7.1	<ul> <li>6. PARKING</li> <li>6.1 Number of parking spaces</li> <li>6.1.1 Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for</li> <li>6.1.2 Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking</li> <li>6.1.3 Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (see Zoning By-law Section 104)</li> <li>6.1.4 Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (see Zoning By-law Section 111)</li> <li>6.2 Separate long-term &amp; short-term parking areas</li> <li>6.2.1 Separate short-term and long-term parking areas using signage or physical barriers, to permit access controls and simplify enforcement (i.e. to discourage employees from parking in visitor spaces, and vice versa)</li> <li>7. OTHER</li> <li>7.1 On-site amenities to minimize off-site trips</li> <li>7.1.1 Provide on-site amenities to minimize mid-day or</li> </ul>			

#### **TDM Measures Checklist:**

Non-Residential Developments (office, institutional, retail or industrial)

# BASIC The measure is generally feasible and effective, and in most cases would benefit the development and its users The measure could maximize support for users of sustainable modes, and optimize development performance The measure is one of the most dependably effective tools to encourage the use of sustainable modes

	TDM	measures: Non-residential developments	Check if proposed & add descriptions
	1.	TDM PROGRAM MANAGEMENT	
	1.1	Program coordinator	
BASIC	★ 1.1.1	Designate an internal coordinator, or contract with an external coordinator	
	1.2	Travel surveys	
BETTER	1.2.1	Conduct periodic surveys to identify travel-related behaviours, attitudes, challenges and solutions, and to track progress	
	2.	WALKING AND CYCLING	
	2.1	Information on walking/cycling routes & destin	ations
BASIC	2.1.1	Display local area maps with walking/cycling access routes and key destinations at major entrances	under consideration
	2.2	Bicycle skills training	
		Commuter travel	
BETTER	★ 2.2.1	Offer on-site cycling courses for commuters, or subsidize off-site courses	
	2.3	Valet bike parking	
		Visitor travel	
BETTER	2.3.1	Offer secure valet bike parking during public events when demand exceeds fixed supply (e.g. for festivals, concerts, games)	

	TDM	measures: Non-residential developments	Check if proposed & add descriptions
	3.	TRANSIT	
	3.1	Transit information	
BASIC	3.1.1	Display relevant transit schedules and route maps at entrances	under consideration
BASIC	3.1.2	Provide online links to OC Transpo and STO information	
BETTER	3.1.3	Provide real-time arrival information display at entrances	
	3.2	Transit fare incentives	
		Commuter travel	
BETTER	3.2.1	Offer preloaded PRESTO cards to encourage commuters to use transit	
BETTER ★	3.2.2	Subsidize or reimburse monthly transit pass purchases by employees	
		Visitor travel	
BETTER	3.2.3	Arrange inclusion of same-day transit fare in price of tickets (e.g. for festivals, concerts, games)	
	3.3	Enhanced public transit service	
		Commuter travel	
BETTER	3.3.1	Contract with OC Transpo to provide enhanced transit services (e.g. for shift changes, weekends)	
		Visitor travel	
BETTER	3.3.2	Contract with OC Transpo to provide enhanced transit services (e.g. for festivals, concerts, games)	
	3.4	Private transit service	
		Commuter travel	
BETTER	3.4.1	Provide shuttle service when OC Transpo cannot offer sufficient quality or capacity to serve demand (e.g. for shift changes, weekends)	
		Visitor travel	
BETTER	3.4.2	Provide shuttle service when OC Transpo cannot offer sufficient quality or capacity to serve demand (e.g. for festivals, concerts, games)	

	TDM	measures: Non-residential developments	Check if proposed & add descriptions			
	4.	RIDESHARING				
	4.1	Ridematching service				
		Commuter travel				
BASIC	4.1.1	Provide a dedicated ridematching portal at OttawaRideMatch.com				
	4.2	Carpool parking price incentives				
		Commuter travel				
BETTER	4.2.1	Provide discounts on parking costs for registered carpools				
	4.3	Vanpool service				
		Commuter travel				
BETTER	4.3.1	Provide a vanpooling service for long-distance commuters				
	5.	CARSHARING & BIKESHARING				
	5.1	Bikeshare stations & memberships				
BETTER	5.1.1	Contract with provider to install on-site bikeshare station for use by commuters and visitors				
		Commuter travel				
BETTER	5.1.2	Provide employees with bikeshare memberships for local business travel				
	5.2	Carshare vehicles & memberships				
		Commuter travel				
BETTER	5.2.1	Contract with provider to install on-site carshare vehicles and promote their use by tenants				
BETTER	5.2.2	Provide employees with carshare memberships for local business travel				
	6.	PARKING				
	6.1	Priced parking				
		Commuter travel				
BASIC	6.1.1	Charge for long-term parking (daily, weekly, monthly)				
BASIC	6.1.2		☑	under consideration		
		Visitor travel				
BETTER	6.1.3	Charge for short-term parking (hourly)				

	TDM	measures: Non-residential developments	Check if proposed & add descriptions					
	7.	TDM MARKETING & COMMUNICATIONS						
	7.1	Multimodal travel information						
		Commuter travel						
BASIC ★	7.1.1	Provide a multimodal travel option information package to new/relocating employees and students	under consideration					
		Visitor travel						
BETTER ★	7.1.2	Include multimodal travel option information in invitations or advertising that attract visitors or customers (e.g. for festivals, concerts, games)						
	7.2	Personalized trip planning						
		Commuter travel						
BETTER ★	7.2.1	Offer personalized trip planning to new/relocating employees						
	7.3	Promotions						
		Commuter travel						
BETTER	7.3.1	Deliver promotions and incentives to maintain awareness, build understanding, and encourage trial of sustainable modes						
	8.	OTHER INCENTIVES & AMENITIES						
	8.1	Emergency ride home						
		Commuter travel						
BETTER ★	8.1.1	Provide emergency ride home service to non-driving commuters						
	8.2	Alternative work arrangements						
		Commuter travel						
BASIC ★	8.2.1	Encourage flexible work hours						
BETTER	8.2.2	Encourage compressed workweeks						
BETTER ★	8.2.3	Encourage telework						
	8.3	Local business travel options						
		Commuter travel						
BASIC *	8.3.1	Provide local business travel options that minimize the need for employees to bring a personal car to work						
	8.4	Commuter incentives						
		Commuter travel						
BETTER	8.4.1	Offer employees a taxable, mode-neutral commuting allowance						
	8.5	On-site amenities						
	8.5	On-site amenities  Commuter travel						


# Appendix I – Swept Path Analyses





#### SITE STAT VM1 N.T.S

	BUILDING SETBACK LINE			1//:///	NEW HEAVY DUTY ASPHALT PAVING (REMAINDER OF THE SITE TO RECEIVE				
	LANDSCAPE BUFFER			7.4/11/6	LIGHT DUTY ASPHALT PAVING)				
CD	CURB DEPRESSION				DECORATIVE NON-SLIP SURFACE PAVING		INDER PORTE COCHERE		
	ENTRY/ EXIT ACCESS PO	INTS		(REFER TO LANDSCAPE DWGS)					
¤	EXISTING TOWN HYDRANT				LANDSCAPED AREA				
٥	PROPOSED LOCATION OF NEW FIRE HYDRANT W/ STEEL BOLLARDS -REFER TO CIVIL DWGS			(XAV) 101	POURED CONCRETE PAD AT LOADIN	G ARE	FA & WASTE COLLECTION		
	FIRE DEPARTMENT CONF	NECTION			STEEL BOLLARD (REFER TO DETAIL XX.	10			
44	MOSE BIR IRESER TO ME	SHANICAL DWGS		-	STEEL BOLLAND (REFER TO DETAIL XX.	^)			
	HOSE BIB (REFER TO MECHANICAL DWGS)			×	PARKING COUNT				
	PAD MOUNTED HYDRO TRANSFORMER W/ STEEL BOLLARDS			104.04×	PROPOSED GRADING (REFER TO CIVIL DWGS)				
	DOUBLE HEADED LIGHT FIXTURE ON CONCRETE BASE				CONDENSING UNIT ON 4" CONCRETE PAD (REFER TO MECH DWGS)				
	-REFER TO ELECTRICAL				SNOW STORAGE AREA (OWNER TO TAKE NECESSARY PRECAUTIONS W/ SNOW REMOVAL COMPANY)				
□ <del>-</del> •	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE -REFER TO ELECTRICAL DWGS			SNOW REMOVAL COMPANY					
□₽	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE W/ ELECTRICAL OUTLET -REFER TO ELECTRICAL DWGS								
CREDIT NOTES:		CREDIT NOTES:			SITE PLAN- GENE	RAL	NOTES		
THIS SITEPLAN IS BASED UPON AND MUST BE READ IN CONJUNCTION WITH THE SURVEY FOR THIS PROPERTY, MATAJ ARCHITECTS ACCEPTS NO RESPONSIBILITY FOR THE ACCURACY, OR				ALL EXISTING PAVEMENT, CURBS, SIDEWALKS, DRIVEWAYS AN DBOULEVARD AREAS DISTURBED BY THE CONSTRUCTION MUST BE REINSTATED TO THE SATISFACTION OF THE TOWN			THE OWNER/ CONTRACTOR SHALL SUPPLY ALL FIRE ROUTE AND BARRIER-FREE SIGNS AS SET OUT IN THE TOWN BY-LAWS AND DESIGN CRITERIA		
COMPLETENESS OF THE DATA SUPPLIED AND SUCH DATA IS NOT INCLUDED UNDER SEALS OF CERTIFICATION, IF ANY.			2	A MINIMUM SETBACK PROPOSED DRIVEWA MAINTAINED, ALL EXI	THE TOWN  ICK OF 1.0m FROM STREET FURNTIURE TO WAYS AND SIDEWALKS SHALL BE EXISTING STREET FURNITURE TO BE		ALL EXTERIOR ILLUMINATION TO BE DIRECTED DOWNW. AS WELL AS INWARD AND DESIGNED TO MARNAIN ZERO CUTOFF LIGHT DISTRIBUTION AT THE PROPERTY LINE		
LEGAL LAND DESCRIPTION:				OF 1.0m. THE COST C	ONTRACTOR/OWNER TO A SETBACK OF RELCOATION OF ANY UTILITY IS THE IE DEVELOPER/ OWNER		ALL DOWNSPOUTS TO BE CO DRAINAGE SYSTEM	NSPOUTS TO BE CONNECTED TO THE STORM E SYSTEM	
Block 2 REGISTERED PLAN 4M-1634 CITY OF OTTAWA			3	THE CONTRACTOR/ OWNER IS RESPONSIBLE FOR ALL UTILITY LOCATES AND DAMAGE/ DISTURBANCE DURING		8	ALL CONDENSING UNITS TO B GROUND FLOOR	TO BE SCREENED ON THE	
			4	CONSTRUCTION.	NTRANCES AND BARRIER FREE PATHS		SEPARATE PERMITS ARE REQUIRED FOR ANY SIGNAG ON THE PROPERY		
					MIRANCES AND BARRIER FREE PAIRS DMPLY WITH O.B.C. 3.8.		WHERE POSSIBLE TREES ARE TO BE PROTECTED FROM CONSTRUCTION		





PROPOSED SITE PLAN

D.A.

AS SHOWN 2024.05.16








## SITE STAT N.T.S

				_'///////			INDER OF THE SITE TO RECEIVE	
	LANDSCAPE BUFFER		7//////	LIGHT DUTY ASPHALT PAVING)				
CD	CURB DEPRESSION				DECORATIVE NON-SLIP SURFACE PAVING UNDER PORTE COCHERE (REFER TO LANDSCAPE DWGS)			
	ENTRY/ EXIT ACCESS PO	INTS	74747	(KEPEK TO EXNESSEATE ENVISS)				
¤	EXISTING TOWN HYDRANT				LANDSCAPED AREA			
101	PROPOSED LOCATION OF REFER TO CIVIL DWGS	OF NEW FIRE HYDRANT W/ STEEL BOLLAR	(0.74. y 3).3	POURED CONCRETE PAD AT LOADING AREA & WASTE COLLECTION				
↑c	FIRE DEPARTMENT CONI	NECTION						
				•	STEEL BOLLARD (REFER TO DETAIL XX	.XJ		
•	HOSE BIB (REFER TO MED	CHANICAL DWGS)		×	PARKING COUNT			
	PAD MOUNTED HYDRO TRANSFORMER W/ STEEL BOLLARDS			104.04×	PROPOSED GRADING (REFER TO CIV	PROPOSED GRADING (REFER TO CIVIL DWGS)		
ПюП	DOUBLE HEADED LIGHT FIXTURE ON CONCRETE BASE				CONDENSING UNIT ON 4" CONCRETE PAD (REFER TO MECH DWGS)			
	-REFER TO ELECTRICAL			P777777	SNOW STORAGE AREA (OWNER TO SNOW REMOVAL COMPANY)		ECESSARY PRECAUTIONS W/	
□⊷	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE -REFER TO ELECTRICAL DWGS							
□₽°	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE W/ ELECTRICAL OUTLET -REFER TO ELECTRICAL DWGS							
CREDIT NOTES:		CREDIT NOTES:			SITE PLAN- GENE	RAL	. NOTES	
	D UPON AND MUST BE ON WITH THE SURVEY FOR ALL ARCHITECTS ACCEPTS	PTS ANNIS, O'SULLIVAN, VOLLEBEKK LTD.		AN DBOULEVARD AF	NENT, CURBS, SIDEWALKS, DRIVEWAYS REAS DISTURBED BY THE ST BE REINSTATED TO THE HE TOWN		THE OWNER/ CONTRACTOR S AND BARRIER-FREE SIGNS AS S BY-LAWS AND DESIGN CRITER	
	OR THE ACCURACY, OR			SATISFACTION OF TH				JMINATION TO BE DIRECTED DOWNWARD
COMPLETENESS OF THE DATA SUPPLIED AND SUCH DATA IS NOT INCLUDED UNDER SEALS OF CERTIFICATION, IF ANY.		Manage Oat V2E 707		PROPOSED DRIVEWA MAINTAINED. ALL EX	K OF 1.0m FROM STREET FURNITURE TO AYS AND SIDEWALKS SHALL BE ISTING STREET FURNITURE TO BE		AS WELL AS INWARD AND DES CUTOFF LIGHT DISTRIBUTION A	
LEGAL LAND DESCRIPTION:				OF 1.0m. THE COST O	ONTRACTOR/OWNER TO A SETBACK OF RELCOATION OF ANY UTILITY IS THE IE DEVELOPER/OWNER		ALL DOWNSPOUTS TO BE CONNECTED TO THE STOR DRAINAGE SYSTEM	
Block 2 REGISTERED PLAN 4M-1634 CITY OF OTTAWA			1	UTILITY LOCATES AND	OWNER IS RESPONSIBLE FOR ALL D DAMAGE/ DISTURBANCE DURING	8	ALL CONDENSING UNITS TO B GROUND FLOOR	E SCREENED ON THE
CITOFOIIAWA			-		NTRANCES AND BARRIER FREE PATHS		SEPARATE PERMITS ARE RE ON THE PROPERY	EQUIRED FOR ANY SIGNAGE
			ŀ	OF TRAVEL MUST CO	MPLY WITH O.B.C. 3.8.	10	WHERE POSSIBLE TREES ARE TO CONSTRUCTION	BE PROTECTED FROM
						_		



PROPOSED SITE PLAN

D.A.

AS SHOWN 2024.05.16








## SITE STAT N.T.S

	LANDSCAPE BUFFER		1//////	UGHT DUTY ASPHALT PAVING)					
CD	CURB DEPRESSION				DECORATIVE NON-SLIP SURFACE PA' (REFER TO LANDSCAPE DWGS)	VING L	UNDER PORTE COCHERE		
	ENTRY/ EXIT ACCESS POINTS			74747	(KEFEK TO EARBSCAFE BWGS)				
¤	EXISTING TOWN HYDRANT				LANDSCAPED AREA				
:01	PROPOSED LOCATION OF NEW FIRE HYDRANT W/ STEEL BOLLARDS -REFER TO CIVIL DWGS			OUALY FOR	POURED CONCRETE PAD AT LOADING AREA & WASTE COLLECTION				
≸t	FIRE DEPARTMENT CONF	NECTION		20.00					
44	HOSE BIB (REFER TO MEC	CHANICAL DWGS)		•	STEEL BOLLARD (REFER TO DETAIL XX.	.XJ			
				(x)	PARKING COUNT				
	PAD MOUNTED HYDRO 1	TRANSFORMER W/ STEEL BOLLARDS		104.04×	PROPOSED GRADING (REFER TO CIV	IL DW			
ПюП	DOUBLE HEADED LIGHT FIXTURE ON CONCRETE BASE				CONDENSING UNIT ON 4" CONCRETE PAD (REFER TO MECH DWGS)				
	-REFER TO ELECTRICAL			P777777	SNOW STORAGE AREA (OWNER TO T	TAKE NECESSARY PRECAUTIONS W/			
□⊷	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE -REFER TO ELECTRICAL DWGS								
□₽	SINGLE HEADED LIGHT FIXTURE ON CONCRETE BASE W/ ELECTRICAL OUTLET -REFER TO ELECTRICAL DWGS								
CREDIT NOTES:		CREDIT NOTES:			SITE PLAN- GENE	RAL	. NOTES		
	ON WITH THE SURVEY FOR	FOR EPTS OR ANNIS, O'SULLIVAN, VOLLEBEKK LTD.			ENT, CURBS, SIDEWALKS, DRIVEWAYS REAS DISTURBED BY THE		THE OWNER/ CONTRACTOR SHALL SUPPLY ALL FIRE ROUT AND BARRIER-FREE SIGNS AS SET OUT IN THE TOWN		
NO RESPONSIBILITY FO	JI ARCHITECTS ACCEPTS OR THE ACCURACY, OR			CONSTRUCTION MUS SATISFACTION OF TH	IT BE REINSTATED TO THE E TOWN	6	BY-LAWS AND DESIGN CRITERIA		
COMPLETENESS OF THE DATA SUPPLIED AND SUCH DATA IS NOT INCLUDED UNDER SEALS OF CERTIFICATION, IF ANY.		Nepean, Ont. K2E 7S6 Phone: (613) 727-0850 PHONE: (519) 742-8371		PROPOSED DRIVEWA MAINTAINED, ALL EX	IK OF 1.0m FROM STREET FURNTIURE TO AYS AND SIDEWALKS SHALL BE GSTING STREET FURNITURE TO BE			IINATION TO BE DIRECTED DOWNWARD D AND DESIGNED TO MAINAIN ZERO RIBUTION AT THE PROPERTY LINE	
LEGAL LAND DESCRIPTION:		Emait Nepean@oovltd.com		OF 1.0m. THE COST O	ONTRACTOR/OWNER TO A SETBACK OF RELCOATION OF ANY UTILITY IS THE HE DEVELOPER/ OWNER		ALL DOWNSPOUTS TO BE CONNECTED TO THE STORI DRAINAGE SYSTEM		
Block 2 REGISTERED PLAN 4M-1634 CITY OF OTTAWA			3	THE CONTRACTOR/ OWNER IS RESPONSIBLE FOR ALL UTILITY LOCATES AND DAMAGE/ DISTURBANCE DURI		8	ALL CONDENSING UNITS TO B GROUND FLOOR	E SCREENED ON THE	
				CONSTRUCTION.	ITDANICES AND BADDIED EDGE CONTO		SEPARATE PERMITS ARE RE ON THE PROPERY	ITS ARE REQUIRED FOR ANY SIGNAGE	
			4		ITRANCES AND BARRIER FREE PATHS IMPLY WITH O.B.C. 3.8.		WHERE POSSIBLE TREES ARE TO CONSTRUCTION	) BE PROTECTED FROM	





PROPOSED SITE PLAN

D.A.


AS SHOWN 2024.05.16





## SITE STAT N.T.S

	BUILDING SETBACK LINE			111:111	NEW HEAVY DUTY ASPHALT PAVING		INDER OF THE SITE TO RECEIVE			
	LANDSCAPE BUFFER			7.4/11.6	LIGHT DUTY ASPHALT PAVING)					
CD	CURB DEPRESSION				DECORATIVE NON-SLIP SURFACE PA' (REFER TO LANDSCAPE DWGS)	VING L	INDER PORTE COCHERE			
	ENTRY/ EXIT ACCESS PO	INTS			(KEEK TO BUILDION					
¤	EXISTING TOWN HYDRAI				LANDSCAPED AREA					
0	PROPOSED LOCATION OF REFER TO CIVIL DWGS	OF NEW FIRE HYDRANT W/ STEEL BOLLARD	os	(1.4×3).	POURED CONCRETE PAD AT LOADIN	A & WASTE COLLECTION				
\$c	FIRE DEPARTMENT CONF	NECTION		10 43 43 43 43	STEEL BOLLARD (REFER TO DETAIL XX	XI				
4⋈	HOSE BIB (REFER TO MED	CHANICAL DWGS)		(x)	PARKING COUNT					
				$\vdash$	PARKING COUNT					
	PAD MOUNTED HYDRO	TRANSFORMER W/ STEEL BOLLARDS		104.04×	PROPOSED GRADING (REFER TO CIV	IL DW				
Поп		FIXTURE ON CONCRETE BASE			CONDENSING UNIT ON 4" CONCRET	DENSING UNIT ON 4" CONCRETE PAD (REFER TO MECH DWGS)				
	-REFER TO ELECTRICAL			SNOW STORAGE AREA (OWNER TO TAK SNOW REMOVAL COMPANY)			TAKE NECESSARY PRECAUTIONS W/			
□⊷	SINGLE HEADED LIGHT I -REFER TO ELECTRICAL E	FIXTURE ON CONCRETE BASE DWGS								
□₽°	SINGLE HEADED LIGHT I OUTLET -REFER TO ELECTRICAL D	FIXTURE ON CONCRETE BASE W/ ELECTRIC DWGS	CAL							
CREDIT NOTES:		CREDIT NOTES:		SITE PLAN- GENERAL NOTES						
READ IN CONJUNCTI THIS PROPERTY, MATA	D UPON AND MUST BE ON WITH THE SURVEY FOR AJ ARCHITECTS ACCEPTS OR THE ACCURACY, OR	S ANNIS, O'SULLIVAN, VOLLEBEKK LTD. 14 Concourse Gate, Suite 500 Nepean, Ont. K2E 756 Phone: (613) 727-0850 PHONE: (519) 742-8371		ANNIS, O'SULLIVAN, VOLLEBEKK LTD.		AN DBOULEVARD AR CONSTRUCTION MUS	ENT, CURBS, SIDEWALKS, DRIVEWAYS EAS DISTURBED BY THE T BE REINSTATED TO THE	5	THE OWNER/ CONTRACTOR S AND BARRIER-FREE SIGNS AS S BY-LAWS AND DESIGN CRITER	SET OUT IN THE TOWN
COMPLETENESS OF TI	HE DATA SUPPLIED AND ICLUDED UNDER SEALS			SATISFACTION OF THE TOWN  A MINIMUM SETBACK OF 1.0m FROM STREET FURNITURE TO PROPOSED DRIVEWAYS AND SIDEWALKS SHALL BE MAINTAINED, ALL EXISTING STREET FURNITURE TO BE			ALL EXTERIOR ILLUMINATION TO BE DIRECTED DOWNWAI AS WELL AS INWARD AND DESIGNED TO MAINAIN ZERO CUTOFF LIGHT DISTRIBUTION AT THE PROPERTY LINE			
LEGAL LAND DESCRI	GAL LAND DESCRIPTION:			OF 1.0m. THE COST C	INTRACTOR/OWNER TO A SETBACK OF RELCOATION OF ANY UTILITY IS THE E DEVELOPER/ OWNER	7	ALL DOWNSPOUTS TO BE CONNECTED TO THE STOR DRAINAGE SYSTEM			
Block 2 REGISTERED PLAN 4M CITY OF OTTAWA	1-1634			THE CONTRACTOR/ OWNER IS RESPONSIBLE FOR ALL UTILITY LOCATES AND DAMAGE/ DISTURBANCE DURING			ALL CONDENSING UNITS TO B GROUND FLOOR	E SCREENED ON THE		
	FORDIAWA			CONSTRUCTION.	TRANCES AND BARRIER FREE PATHS	9	SEPARATE PERMITS ARE REQUIRED FOR ANY SIGN ON THE PROPERY			
			١Ľ		MPLY WITH O.B.C. 3.8.	10	<u> </u>			



PROPOSED SITE PLAN

AS SHOWN 2024.05.16

ASP-3

D.A.

# Appendix J – MMLOS Analysis

## Multi-Modal Level of Service - Segments Form

Consultant	Arcadis	Project	143412 120 Lus
Scenario	Existing and Future Conditions	Date	2023-06-15
Comments			

OF OMENIES			O'Keefe Court	Lusk Street (south	Lusk Street	Fallowfield	Section	Section	Section	Section	Section
SEGMENTS		Segment	1	side) 2	(north side) 3	4	5	6	7	 8	9
	Sidewalk Width Boulevard Width		no sidewalk n/a	≥ 2 m 0.5 - 2 m	no sidewalk n/a	≥ 2 m > 2 m					
	Avg Daily Curb Lane Traffic Volume		≤ 3000	≤ 3000	> 3000	> 3001					
Pedestrian	Operating Speed On-Street Parking		> 50 to 60 km/h no	> 50 to 60 km/h no	> 60 km/h no	> 60 km/h no					
est	Exposure to Traffic PLoS	-	F	Α	F	D	-	-	-	-	-
bed	Effective Sidewalk Width				2.0 m	3.0 m					
т.	Pedestrian Volume  Crowding PLoS		-	-	-	-	-	-	-	-	-
	Level of Service		-	-	-	-	-	-	-	-	-
	Type of Cycling Facility		Mixed Traffic	Mixed Traffic	Physically Separated	Physically Separated					
	Number of Travel Lanes		≤ 2 (no centreline)	≤ 2 (no centreline)							
	Operating Speed		≥ 50 to 60 km/h	≥ 50 to 60 km/h							
	# of Lanes & Operating Speed LoS		D	D	-	-	-	-	-	-	-
Bicycle	Bike Lane (+ Parking Lane) Width	D									
Š	Bike Lane Width LoS		-	-	-	-	-	-	-	-	-
蓝	Bike Lane Blockages										
	Blockage LoS		- 110	4.4.0 ma mafeuma	-	-	-	-	-	-	-
	Median Refuge Width (no median = < 1.8 m)		< 1.8 m refuge	< 1.8 m refuge							
	No. of Lanes at Unsignalized Crossing Sidestreet Operating Speed		≤ 3 lanes >40 to 50 km/h	≤ 3 lanes >40 to 50 km/h							
	Unsignalized Crossing - Lowest LoS		B	B	A	A	-	-	-	-	-
	Level of Service		D	D	A	A	-	-	-	-	-
.=	Facility Type					Mixed Traffic					
Transit	Friction or Ratio Transit:Posted Speed	D				Vt/Vp ≥ 0.8					
Tra	Level of Service		-	-	-	D	-	-	-	-	-
	Truck Lane Width		> 3.7 m	> 3.7 m	> 3.7 m	> 3.7 m					
S S S S S S S S S S S S S S S S S S S	Travel Lanes per Direction	В	1	1	1	1					
Truck	Level of Service	В	В	В	В	В	-	-	-	-	-

## Multi-Modal Level of Service - Intersections Form


Consultant	
Scenario	
Comments	

rcadis	Project
uture Conditions	Date

143412	120 Lusk St
2025-10-14	

To add intersections
Select columns LMNO, right-click and Copy;
Then select column P, right-click and Insert Copied Cells

											, <b>g</b>		
	INTERSECTIONS	F	allowfield & O'K	eefe / Cobble Hi	II		Interse	ection B			Interse	ection C	
	Crossing Side	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
	Lanes	7	6	5	3								
	Median	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m								
	Conflicting Left Turns	Permissive	Permissive	Permissive	Permissive								
	Conflicting Right Turns	Permissive or yield control	Permissive or yield control	Permissive or yield control	Permissive or yield control								
	Right Turns on Red (RToR) ?	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed								
	Ped Signal Leading Interval?	Yes	Yes	Yes	Yes								
trian	Right Turn Channel	No Channel	No Channel	No Channel	No Channel								
esti	Corner Radius	10-15m	10-15m	10-15m	10-15m								
Pede	Crosswalk Type	Std transverse markings	Std transverse markings	Std transverse markings	Std transverse markings								
	PETSI Score	6	22	39	72								
	Ped. Exposure to Traffic LoS	F	F	E	С	-	-	-	-	-	-	-	-
	Cycle Length	75	75	75	75								
	Effective Walk Time	22	22	7	7								
	Average Pedestrian Delay	19 B	19 B	31	31								
	Pedestrian Delay LoS	В	В	D	D				•				
	Level of Service	F	F	E	D	-	-	-	-	-	-	-	-
	Level of Service		ı	=				-				-	
	Approach From	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
	Bicycle Lane Arrangement on Approach	Pocket Bike Lane	Mixed Traffic	Mixed Traffic	Mixed Traffic								
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank></blank>	≤ 50 m Introduced right turn lane	> 50 m										
	Dedicated Right Turning Speed	≤ 25 km/h	≤ 25 km/h										
<u> </u>	Cyclist Through Movement	В	F			-	-	-	-	-	•	•	-
) S	Separated or Mixed Traffic	Separated	Mixed Traffic	Mixed Traffic	Mixed Traffic	-	-	-	-	-	-	-	-
Bicycle	Left Turn Approach	1 lane crossed	2-stage, LT box	No lane crossed	One lane crossed								
	Operating Speed	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h								
	Left Turning Cyclist	D	A	С	E	-	•	-	•	-	•	•	-
		D	F	С	E	-	-	-	-	-	-	-	-
	Level of Service		1	=				-				-	
<u>.</u>	Average Signal Delay	≤ 20 sec	≤ 30 sec	≤ 20 sec	≤ 30 sec								
nsit		С	D	С	D	-	-	-	-	-	-	-	-
Tra	Level of Service			)				-				-	
	Effective Corner Radius	10 - 15 m	< 10 m	< 10 m	10 - 15 m								
×	Number of Receiving Lanes on Departure from Intersection	1	1	≥ 2	1								
Truc		E	F	D	Е	-	-	-	-	-	-	-	-
	Level of Service			=				-				-	
0	Volume to Capacity Ratio												
Aut	Level of Service							-				-	





### OTM BOOK 12\* - TRAFFIC SIGNAL WARRANT

Project:	120 Lusi	Street		Date	: October 13, 2025
Project #:	143412				
Location:	Fallowfield Road	at	O'Keefe Court/Cobble Hill Drive		
Orientation:	(Major Roadway) North/South		(Minor Roadway) East/West		
Municipality:	Ottawa		Scenario:	Future (2027) Background Traffic	

## **Justification 1 - Minimum Vehicle Volume**

	MINIMUM REQUIREMENT				COMPLIANCE								
WARRANT	FREE FLOW	RESTR. FLOW	ADJUST. FREE FLOW	ADJUST. RESTR. FLOW	7:00 AM	8:00 AM	9:00 AM	10:00 AM	3:00 PM	4:00 PM	5:00 PM	6:00 PM	SECTIONAL PERCENT
A. Vehicle volumes, all	400	700	000	000	1905	952	952	952	2166	1083	1083	1083	4000/
approaches	480	720	600	900	100%	100%	100%	100%	100%	100%	100%	100%	100%
B. Vehicle volume along minor		470	400	470	290	145	145	145	398	199	199	199	0.40/
roads	120	170	120	170	100%	85%	85%	85%	100%	100%	100%	100%	94%

## Justification 2 - Delay to Cross Traffic

	N	MINIMUM REQUIREMENT				COMPLIANCE								
WARRANT	FREE FLOW	RESTR. FLOW	ADJUST. FREE FLOW	ADJUST. RESTR. FLOW	7:00 AM	8:00 AM	9:00 AM	10:00 AM	3:00 PM	4:00 PM	5:00 PM	6:00 PM	SECTIONAL PERCENT	
A. Vehicle volumes, along	480	720	600	900	1615	807	807	807	1768	884	884	884	95%	
artery	460	720	000	900	100%	90%	90%	90%	100%	98%	98%	98%	95%	
B. Combined vehicle and pedestrian volume crossing	50	70	50	70	196	60	60	60	175	87	87	87	95%	
artery from minor roads	30	50 70	50	20 /0	100%	86%	86%	86%	100%	100%	100%	100%	9370	

## Justification 3 - Volume/Delay Combination

JUSTIFICATION	SATISFIED TO 80% OR MORE?	BOTH SATISFIED TO 80% OR MORE?
Justification 1 - Minimum Vehicular Volume	YES	YES
Justification 2 - Delay to Cross Traffic	YES	163

## Justification 7 - Projected Volumes

			MINIMUM RE	QUIREMENT			COMPLIANCE		
WARRANT	DESCRIPTION	FREE FLOW	RESTRICTED	ADJUSTED	ADJUSTED RESTRICTED	SECT	ENTIRE %		
		TREETEOW	FLOW	FREE FLOW	FLOW	AHV	%	LINITINE /0	
1. MINIMUM VEHICULAR VOLUME	A. Vehicle volumes, all approaches (Average Hour)	480	720	720	1080	1018	94%	84%	
	B. Vehicle volume along minor roads (Average Hour)	120	170	144	204	172	84%		
2. DELAY TO CROSS TRAFFIC	A. Vehicle volumes, along artery (Average Hour)	480	720	720	1080	846	78%	700/	
	B. Combined vehicle and pedestrian volume crossing artery from minor roads (Average Hour)	50	75	60	90	75	83%	78%	

Projected Traffic Volumes:									je Hou	rly Vo	olume	(AHV	Α	AHV = (amPHV + pmPHV)/4						
		AM P	eak H	our Vo	lumes				PM P	eak H	our Vo	lumes	Av	Average Hourly Volumes (AHV)						
	95 ⊭	742 ↓	12 צ	K ← ∠	138 12 74			28 ⊭	807 ↓	48 \	K ← ∠	100 10 46		31 ∠	387 ↓	15 צ	K ← ∠	60 6 30		
		33 5	<i>7</i> 1 →	√ 151	↑ 602	71 13			117 7	<i>⊼</i>	70	↑ 768	71 47		38 3	<i>7</i> 1 →	<b>下</b> 55	↑ 343	7 15	
		28	Я						118	Я					36	Я				



#### Eight Hour Traffic Volumes\*\*:

Hann	l		Major	Road			l		Minor	Road	ı		D = 4+
Hour	NBL	NBT	NBR	SBL	SBT	SBR	EBL	EBT	EBR	WBL	WBT	WBR	Ped*
7:00 AM	151	602	13	12	742	95	33	5	28	74	12	138	1
8:00 AM	76	301	7	6	371	48	17	3	14	37	6	69	1
9:00 AM	76	301	7	6	371	48	17	3	14	37	6	69	1
10:00 AM	76	301	7	6	371	48	17	3	14	37	6	69	1
3:00 PM	70	768	47	48	807	28	117	7	118	46	10	100	2
4:00 PM	35	384	24	24	404	14	58	4	59	23	5	50	1
5:00 PM	35	384	24	24	404	14	58	4	59	23	5	50	1
6:00 PM	35	384	24	24	404	14	58	4	59	23	5	50	1
* Number o	f nada	otrion	0.000	ina th	a mai	or room	,						

<sup>\*\*</sup> These are projected 8-hour traffic volumes.

#### Notes:

CONCLUSION:

1. Vehicle volume warrant (1A) and (2A) for intersections of roadways having two or more moving lanes in one direction should be 25% higher than the

2+ Lanes per Direction

Restricted Flow

2. Warrant values for free flow apply when the 85th percentile speed of artery traffic equals or exceeds 70 km/h or when the intersection lies within the built-up area of an isolated community having a population of less than 10,000. Warrant values for restricted flow apply to large urban communities when the 85th percentile speed of artery traffic does not exceed 70 km/h.

4-legged Intersection

3. The lowest sectional percentage governs the entire warrant.

4. For "T" intersections the warrant values for the minor road should be increased by 50% (Warrant 1B only).

5. All flow values for Justification 1 and 2 are to be increased by 20% in the case of new intersections, Justification 3 is to only be used for existing intersections and all flow values for Warrant 1 and Warrant 2 of Justification 7 are to be increased by 20% for existing intersections and by 50% in the case of new intersections.

Existing Intersection

6. The crossing volumes are defined as the sum of:

- (a) Left-turns from both minor road approaches.
- (b) The heaviest through volume from the minor road.
- (c) 50% of the heavier left turn movement from major road when both of the following are met:
  - (i) the left-turn volume >120 vph
  - (ii) the left-turn volume plus the opposing volume >720 vph
- (d) Pedestrians crossing the main road.

Based on Justification 3, the intersection meets the minimum warrants for traffic control signals.

<sup>\* &</sup>quot;Ontario Traffic Manual, Book 12 (March 2012)", Ontario Ministry of Transportation.



### OTM BOOK 12\* - TRAFFIC SIGNAL WARRANT

Project:	120 Lus	k Street		Di	ate:	October 13, 2025
Project #:	143412					
Location:	Fallowfield Road	at	O'Keefe Court/Cobble Hill Drive			
Orientation:	(Major Roadway) North/South		(Minor Roadway) East/West			
Municipality:	Ottawa		Scenario:	Future (2027) Total Traffic		

## Justification 1 - Minimum Vehicle Volume

	N	IINIMUM RE	QUIREMEN	T				COMPL	LIANCE				
WARRANT	FREE FLOW	RESTR. FLOW	ADJUST. FREE FLOW	ADJUST. RESTR. FLOW	7:00 AM	8:00 AM	9:00 AM	10:00 AM	3:00 PM	4:00 PM	5:00 PM	6:00 PM	SECTIONAL PERCENT
A. Vehicle volumes, all	400	700	000	000	2115	1058	1058	1058	2336	1168	1168	1168	4000/
approaches	480	720	600	900	100%	100%	100%	100%	100%	100%	100%	100%	100%
B. Vehicle volume along minor		470	400	470	421	210	210	210	517	259	259	259	4000/
roads	120	170	120	170	100%	100%	100%	100%	100%	100%	100%	100%	100%

## Justification 2 - Delay to Cross Traffic

	N	IINIMUM RE	QUIREMEN	Т				COMPI	JANCE				
WARRANT	FREE FLOW	RESTR. FLOW	ADJUST. FREE FLOW	ADJUST. RESTR. FLOW	7:00 AM	8:00 AM	9:00 AM	10:00 AM	3:00 PM	4:00 PM	5:00 PM	6:00 PM	SECTIONAL PERCENT
A. Vehicle volumes, along artery	480	720	600	900	1695	847	847	847	1819	910	910	910	98%
artor y	400	120	600	900	100%	94%	94%	94%	100%	100%	100%	100%	3070
B. Combined vehicle and pedestrian volume crossing	50	70	50	70	278	89	89	89	236	118	118	118	100%
artery from minor roads	30	70	70 50		100%	100%	100%	100%	100%	100%	100%	100%	10070

## Justification 3 - Volume/Delay Combination

JUSTIFICATION	SATISFIED TO 80% OR MORE?	BOTH SATISFIED TO 80% OR MORE?
Justification 1 - Minimum Vehicular Volume	YES	YES
Justification 2 - Delay to Cross Traffic	YES	163

## Justification 7 - Projected Volumes

			MINIMUM RE	QUIREMENT		COMPLIANCE			
WARRANT	DESCRIPTION	FREE FLOW	RESTRICTED	ADJUSTED	ADJUSTED RESTRICTED	SECT	IONAL	ENTIRE %	
		TREE FLOW	FLOW	FREE FLOW	FLOW	AHV	%	LINTINE /0	
1. MINIMUM VEHICULAR VOLUME	A. Vehicle volumes, all approaches (Average Hour)	480	720	720	1080	1113	100%		
	B. Vehicle volume along minor roads (Average Hour)	120	170	144	204	235	100%	100%	
2. DELAY TO CROSS TRAFFIC	A. Vehicle volumes, along artery (Average Hour)	480	720	720	1080	878	81%	040/	
	B. Combined vehicle and pedestrian volume crossing artery from minor roads (Average Hour)	50	75	60	90	103	100%	81%	

Projected Traffic Volumes:								veraç	ge Hou	rly V	olume	(AHV	AHV = (amPHV + pmPHV)/4							
•	AM Peak Hour Volumes							PM Peak Hour Volumes							Average Hourly Volumes (AHV)					
	111 758 12 <del>C</del>			207 18 111			38 ⊭	818 ↓	48 ≽u	K + Y	150 15 69		37 ∠	394 ↓	15 \	K + Y	89 8 45			
•		48	7	K	1	7			150	7	K	1	71		49	7	Γ.	1	7	
		5 31	<sub>7</sub>	199	602	13			7 126	<sub>7</sub>	100	768	47		3 39	, Э	75	343	15	



#### Eight Hour Traffic Volumes\*\*:

Hour	l		Major	Road	l				Minor	Road	ı		D-4*
nour	NBL	NBT	NBR	SBL	SBT	SBR	EBL	EBT	EBR	WBL	WBT	WBR	Ped*
7:00 AM	199	602	13	12	758	111	48	5	31	111	18	207	1
8:00 AM	100	301	7	6	379	56	24	3	16	56	9	104	1
9:00 AM	100	301	7	6	379	56	24	3	16	56	9	104	1
10:00 AM	100	301	7	6	379	56	24	3	16	56	9	104	1
3:00 PM	100	768	47	48	818	38	150	7	126	69	15	150	2
4:00 PM	50	384	24	24	409	19	75	4	63	35	8	75	1
5:00 PM	50	384	24	24	409	19	75	4	63	35	8	75	1
6:00 PM	50	384	24	24	409	19	75	4	63	35	8	75	1
* * 1	£! .	-4-4		41-			,						

<sup>\*</sup> Number of pedestrians crossing the major road \*\* These are projected 8-hour traffic volumes.

#### Notes:

CONCLUSION:

1. Vehicle volume warrant (1A) and (2A) for intersections of roadways having two or more moving lanes in one direction should be 25% higher than the values given above.

2+ Lanes per Direction

2. Warrant values for free flow apply when the 85th percentile speed of artery traffic equals or exceeds 70 km/h or when the intersection lies within the built-up area of an isolated community having a population of less than 10,000. Warrant values for restricted flow apply to large urban communities when the 85th percentile speed of artery traffic does not exceed 70 km/h.

Restricted Flow

- 3. The lowest sectional percentage governs the entire warrant.
- 4. For "T" intersections the warrant values for the minor road should be increased by 50% (Warrant 1B only).
- 5. All flow values for Justification 1 and 2 are to be increased by 20% in the case of new intersections, Justification 3 is to only be used for existing intersections and all flow values for Warrant 1 and Warrant 2 of Justification 7 are to be increased by 20% for existing intersections and by 50% in the case of new intersections.

4-legged Intersection

Existing Intersection

- 6. The crossing volumes are defined as the sum of:
  - (a) Left-turns from both minor road approaches.
  - (b) The heaviest through volume from the minor road.
  - (c) 50% of the heavier left turn movement from major road when both of the following are met:
    - (i) the left-turn volume >120 vph
    - (ii) the left-turn volume plus the opposing volume >720 vph
  - (d) Pedestrians crossing the main road.

Based on Justification 1, 3 & 7, the intersection meets the minimum warrants for traffic control signals.

<sup>\* &</sup>quot;Ontario Traffic Manual, Book 12 (March 2012)", Ontario Ministry of Transportation.



