

SITE DATA LL ZONING DEFINITIONS AND REQUIREMENTS AS PER CITY OF OTTA	AWA ZONING BY-LAW, 2008-250	
DDRESS:	5431 FERNBANK ROAD, OTTA	Δ\Λ/Δ
REA	C SUBURBAN	
VARD	6 STITTSVILLE (COUNC. GLEN GOWER)	
ONING	I1A	1 COWLIN
ONNO	110	
OT AREA	73,967 m2 (18.27 ACRES)	
UILDING FOOTPRINT	±6,987 m2 (75,205 s.f.)	
OTAL FLOOR AREAS (GROSS)	±14,776 m2 (159,600 s.f.)	
UTURE PORTABLES (72 m2 EACH)	2,160 M2 (23,250 SF.)	
,	, , , ,	
ONING MECHANISMS	PROVISIONS (I1A SUBZONE)	PROVIDED
a) MINIMUM LOT AREA (m2)	400	73967
o) MINIMUM LOT WIDTH (m)	15	239.30
c) MINIMUM FRONT YARD SETBACK (m)	7.5	±13
d) MINIMUM INTERIOR SIDE YARD SETBACK (m)	7.5	±20
e) MINIMUM CORNER SIDE YARD SETBACK (m)	4.5	
) MINIMUM REAR YARD SETBACK (m)	7.5	
g) MAXIMUM BUILDING HEIGHT (m)	15	±13
A DIVINIC CALCULATION		
ARKING CALCULATION	46.V.4.5. 24	
RADE 7&8 CLASSROOMS (1.5 PS/CLASS)	16 X 1.5 = 24 46 X 2 = 92	
RADES 9-12 CLASSROOMS (2 PS/CLASS) ORTABLE CLASSROOMS	46 X Z = 9Z	
GRADE 7&8 CLASSROOMS (1.5 PS/CLASS)	10 X 1.5 = 15	
GRADES 9-12 CLASSROOMS (2 PS/CLASS)	20 X 2 = 40	
ARRIER FREE PARKING SPACES (3.1.2, TABLE 3)	7 (3 TYPE A + 4 TYPE B)	8 (4A + 4B)
TANDARD PARKING SPACES (5.1.2, TABLE 5)	5.2mx2.6mx6.7 m AISLE	0 (4A + 4D)
TANDARD FARRING SPACE	J.ZIIIXZ.OIIIXO.7 III AISEE	
OTAL REQUIRED	171	197
ICYCLE PARKING CALCULATION		
MAIN SCHOOL (1 PER 100 m2)	14,766 / 100 = 148	
UTURE PORTABLES (1 PER 100 m2)	2,160 / 100 = 22	
OTAL REQUIRED	170	170
TANDARD BICYCLE PARKING SPACE	1.8x0.6 m	
OADING SPACES		
ABLE 113A(a) (±10000 m2)	2 REQUIRED (3.5 X 7m)	2
	· · · · · ·	
ANDSCAPED BUFFER		
BUTTING THE STREET (PARKING LOT 100+ SPACES	•	
OT ABUTTING THE STREET (PARKING LOT 100+ SPA	ACES) 3m	
BUILDING CODE DATA		
LL REQUIREMENTS AS PER ONTARIO BUILDING CODE OBC 2024		
MA IOD OCCUDANCY		
	OUP A, DIVISION 2	
·	987 m2 (75,205 s.f.)	
1	,776 m2 (159,600 s.f.)	
UMBER OF STOREYS 3		
O OF STREETS FOR FIRE FIGHTING 1	2.24	
	2.24,	LEBED
	AREA, UP TO 6 STOREYS, SPRINK	LEKEU
PRINKLERED BUILDING YES		
ONSTRUCTION TYPE NON	N-COMBUSTIBLE	
LOOR ASSEMBLIES & F.R.R 1 HO		

EXISTING FIRE HYDRANT

EXISTING LIGHT STANDARD

EXISTING CATCH BASIN

CATCH BASIN - REFER TO CIVIL

FLAG POLE - SEE DETAIL 16/A002

RELOCATED EXISTING LIGHT STANDARD

LIGHT STANDARD - REFER TO ELECTRICAL

CATCH BASIN/MANHOLE - REFER TO CIVIL

WATER METER (IN WATER ENTRY ROOM)

NEW BARRIER- FREE DEPRESSED CURB -

NEW DEPRESSED CURB - REFER TO CIVIL

KNOCK-DOWN BOLLARD - SEE DETAILS 14/A002

TESTPIT LOCATION, REFER TO GEOTECHNICAL

BO BUSES ONLY

VP VISITOR PARKING SP STAFF PARKING

TACTILE WALKING SURFACE INDICATOR,

SANITARY MANHOLE - REFER TO CIVIL

STORM MANHOLE - REFER TO CIVIL

FIRE DEPARTMENT CONNECTION

WATER METER REMOTE READOUT

BUILDING ENTRANCE/EXIT

NEW FIRE HYDRANT

SEE DETAIL 15/A002

PROPERTY LINE

NEW CHAIN LINK FENCE

REFER TO LANDSCAPE

GEOTECHNICAL REPORT

REPORT

BOLLARD - SEE DETAIL 8/A002

BOREHOLE LOCATION, REFER TO

NO ENTRY

FR FIRE ROUTE

SPECIFIC CONSTRUCTION NOTES:

- PROVIDE PERIMETER FOUNDATION DRAINAGE; 100 TO 150mm Ø, GEOTEXTILE-WRAPPED, PERFORATED, CORRUGATED, PLASTIC PIPE SURROUNDED ON ALL SIDES BY 150mm OF 10mm CLEAR CRUSHED STONE. PLACE AT THE FOOTING LEVEL AROUND THE EXTERIOR OF THE STRUCTURE. THE PIPE TO HAVE A POSITIVE GRAVITY CONNECTION TO THE STORM SEWER OUTLET. SEE CIVIL.
- GAS METER CHAIN LINK FENCE: - ±4000 LONG x 2135 HIGH ALONG BACK OF GAS METER STATION - TOP: CHAIN LINK FENCE INSTALLED ACROSS THE
 - FENCE FABRIC; 6 GAUGE, VINYL COATED, BLACK - LOCKING DOUBLE GATES @ 1220 WIDE EACH - LOCKING DEVICE; ENBRIDGE TO SUPPLY MASTER X2268 LOCK UPON COMPLETION - FENCE POSTS - 100mm, SCHEDULE 80, IN CONCRETE
 - COORDINATE WITH MECHANICAL
 - DEPRESSED CURB 6m WIDE REFER TO CIVIL AND LANSCAPING
- PROVIDE TRENCHES FOR POWER, PA/SECURITY, COMMUNICATIONS, AND FIRE ALARM. REFER TO
- PROVIDE MANHOLE TO SERVICE FUTURE
- PORTABLES. REFER TO ELECTRICAL. PROVIDE 8000x4500mm GENERATOR ENCLOSURE &
- J GENERATOR. REFER TO ELECTRICAL. 1880x3760mm TRANSFORMER PAD MOUNT
- WITH 8 BOLLARDS
- BIKE RACKS SEE LANDSCAPING (SEE 2/A002)
- EARTH BINS (SEE 3/A002)

VEHICULAR GATE (SEE 8/A002)

GROUNDCOVER LEGEND:

GRASS

ASPHALT

CONCRETE

PAVERS

- SENERAL NOTES: ALL CONCRETE CURBS AND CONCRETE DEPRESSED CURBS TO BE CONSTRUCTED AS PER CITY OF OTTAWA
- STANDARD DETAIL SC1.1 ALL SITE ENTRANCES TO BE CONSTRUCTED AS PER CITY OF OTTAWA STANDARD DETAIL SC7.1 ALL BARRIER FREE DEPRESSED CURBS TO BE
- CONSTRUCTED AS PER CITY OF OTTAWA ACCESSIBILITY DESIGN STANDARDS (SECTION 3.4)

ALL TWSI INSTALLATIONS ARE TO CONFORM TO ONE OF FIGURES 33a, 33b, 34, OR 35 OF THE CITY OF OTTAWA ACCESSIBILITY STANDARDS.

ISSUED FOR SPC APPLICATION 15OCT25 33% CLIENT REVIEW 19SEP25 ISSUED FOR SITE PLAN PRE-CONSULT 05SEP25

revision

SCHOOL BOARD



date


N45 ARCHITECTURE INC.

71 Bank Street, 7th Floor - Ottawa, Ontario, K1P 5N2 tel. 613.224.0095 fax 613.224.9811

FERNBANK CATHOLIC HIGH SCHOOL

5431 FERNBANK ROAD OTTAWA, ONTARIO K2S OT7

PROJECT NORTH





	drawing title SITE PLAN	
	scale AS NOTED	drawn by x.x.
ľ	date SEPT. 2025	checked by V.P.
	project number	drawing number
	24-835	AUU1

revision CONTRACTOR TO VERIFY ALL DIMENSIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES BEFORE WORK COMMENCES.

DO NOT SCALE DRAWINGS