

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.

— RUNOFF COEFFICIENT

STORM DRAINAGE BOUNDARY MAXIMUM PONDING LIMITS

DIRECTION OF OVERLAND FLOW PROPOSED STORM SEWER PROPOSED CATCHBASIN MANHOLE PROPOSED CATCHBASIN PROPOSED DITCH INLET CATCHBASIN PROPOSED DOUBLE CATCH BASIN PROPOSED SUB DRAIN CATCH BASIN AS PER CITY OF OTTAWA STANDARD DETAIL DRAWINGS L10

PROPOSED PERFORATED SUBDRAIN — — EXISTING STORM SEWER — — EXISTING CATCHBASIN MANHOLE — — — — EXISTING CATCHBASIN 

> THERMAL INSULATION ON STORM SEWER WHERE COVER IS LESS THAN 1.5m. THERMAL INSULATION ON WATERMAIN WHERE COVER IS LESS THAN 2.4m AS PER W22.

768, BOUL. ST-JOSEPH, SUITE 100, GATINEAU (QUEBEC) CANADA, J8Y 4B8

1740 ST. LAURENT BOULEVARD

7 of 7