



File: 119351 - 5.2.2

Design Brief

Bank Street Development

4836 Bank Street



Prepared for Leitrim Home Hardware
by IBI Group
APRIL 2019
REVISED APRIL 2020

Table of Contents

| | | |
|----------|---|----------|
| 1 | INTRODUCTION | 1 |
| 1.1 | Scope | 1 |
| 1.2 | Subject Site | 1 |
| 1.3 | Previous Studies | 1 |
| 1.4 | Pre-Consultation | 1 |
| 1.5 | Geotechnical Investigation..... | 2 |
| 2 | WATER SUPPLY | 3 |
| 2.1 | Existing Conditions | 3 |
| 2.2 | Design Criteria | 3 |
| | 2.2.1 Water Demands | 3 |
| | 2.2.2 System Pressure | 3 |
| | 2.2.3 Fire Flow Rates | 4 |
| | 2.2.4 Boundary Conditions | 4 |
| | 2.2.5 Hydraulic Model | 4 |
| 2.3 | Proposed Water Plan | 4 |
| | 2.3.1 Modelling Results | 4 |
| | 2.3.2 Watermain Layout | 5 |
| 3 | WASTEWATER DISPOSAL | 6 |
| 3.1 | Existing Conditions | 6 |
| 3.2 | Design Criteria | 6 |
| 3.3 | Recommended Wastewater Plan | 6 |
| 4 | SITE STORMWATER MANAGEMENT | 7 |
| 4.1 | Existing Conditions | 7 |
| 4.2 | Phasing | 7 |
| 4.3 | Design Criteria | 7 |
| 4.4 | Proposed Minor System | 8 |

Table of Contents (continued)

| | | |
|----------|---|-----------|
| 4.5 | Stormwater Management | 8 |
| 4.6 | Inlet Controls | 8 |
| 4.7 | On-Site Detention | 9 |
| 4.7.1 | Site Inlet Control..... | 9 |
| 4.7.2 | Roof Inlet Controls | 10 |
| 4.7.3 | Overall Release Rate | 10 |
| 5 | SEDIMENT AND EROSION CONTROL PLAN..... | 11 |
| 5.1 | General | 11 |
| 5.2 | Trench Dewatering..... | 11 |
| 5.3 | Bulkhead Barriers | 11 |
| 5.4 | Seepage Barriers | 11 |
| 5.5 | Surface Structure Filters | 12 |
| 6 | APPROVALS AND CITY REQUIREMENTS..... | 13 |
| 6.1 | City of Ottawa | 13 |
| 6.2 | Province of Ontario | 13 |
| 6.3 | Conservation Authority..... | 13 |
| 6.4 | Federal Government..... | 13 |
| 7 | CONCLUSIONS & RECOMMENDATIONS..... | 14 |
| 7.1 | Conclusions | 14 |
| 7.2 | Recommendations | 14 |

Table of Contents (continued)

List of Figures

| | |
|-------------------|----------------------|
| Figure 1.1 | Site Location |
| Figure 1.2 | Site Plan |
| Figure 4.1 | Phasing Plan |

Table of Contents (continued)

List of Appendices

- Appendix A** City Pre-Consultation Meeting Notes (October 24, 2018 e-mail)
April 15, 2019 e-mail from the South Nation Conservation
- Appendix B** Figure 2.2, Preferred Water Distribution Plan, 2016 Updated Serviceability Report
Correspondence from the City of Ottawa
Watermain Demand Calculation Sheets
FUS Calculation
Hydraulic Model Out
- Appendix C** Pathways Phase 1 Sanitary Sewer Design Sheet
Drawing 33956-501A – Pathways Phase 1 Sanitary Drainage Area Plan
Sanitary Sewer Design Sheet
Drawing 119351-400 – Sanitary Drainage Area Plan
- Appendix D** Pathways Phase 1 Storm Sewer Design Sheet
Drawing 33956-500A – Pathways Phase 1 Storm Drainage Area Plan
Drawing 33956-700 – DDSWMM Schematic from Pathways Phase 1
Excerpts from *Design Brief Pathways at Findlay Creek 4800 Bank Street (Remer Lands) Phase 1 Leitrim Development Area* (IBI Group, August 2017)
Storm Sewer Design Sheet
Drawing 119351-500 – Storm Drainage Area Plan
Manufacturer's information for ICDs
- Appendix E** Stormwater Management Calculations
- Appendix F** Drawing 119351-001 – Site Servicing Plan
Drawing 119351-010 – Details and Notes
Drawing 119351-200 – Site Grading Plan
Drawing 119351-600 – Ponding Plan
Drawing 119351-900 – Erosion and Sedimentation Control Plan

1 INTRODUCTION

1.1 Scope

IBI Group has been retained by Leitrim Home Hardware to prepare the necessary engineering plans, specifications and documents to support a proposed Site Plan Application for the subject lands in accordance with the policies set out by the Planning and Development Branch of the City of Ottawa. This Brief will present a detailed servicing scheme to support development of the property, and will include sections that will review water supply, wastewater disposal, minor and major stormwater management along with erosion and sediment control.

1.2 Subject Site

The Leitrim Home Hardware site is located at the southwest corner of the Bank Street and Dun Skipper Drive intersection. The proposed development is approximately 2.5 hectares in size and is also bounded by the Idone subdivision to the south and east. Please refer to **Figure 1.1** for more information regarding the site location.

The subject property is presently improved with a Home Hardware retail outlet and associated out buildings. The proposed re-development of the site will include a new Home Hardware building; three other buildings; two vehicular accesses; dedicated parking spaces and landscaping areas. A current concept of the envisioned development is shown on **Figure 1.2**.

1.3 Previous Studies

Design of this project has been undertaken in accordance with the following reports:


- **2016 Updated Serviceability Report (Class EA OPA 76 Areas 8a, 9a & 9b) Leitrim Development Area (IBI Group, September 2016)** – The report is an update to an earlier servicing report completed in 2007. The updated report was needed to review the impacts on existing major infrastructure by developing an additional 87 ha in the LDA. IN 2012, under OPA 76, the City of Ottawa increased its urban envelope by over 900 ha including expansion areas 8a, 9a, and 9b in the LDA. The subject site is included in the OPA 76 Expansion Area. The report included a high level review of the development requirements of the subject site. The design of the subject site is based on the report recommendations.
- **Design Brief Pathways at Findlay Creek 4800 Bank Street (Remer Lands) Phase 1 (IBI Group July 2017)** – The report provides detail design criteria for adjacent developments including the subject site and identifies capacity for a water supply and both storm and sanitary sewers for the subject site.

1.4 Pre-Consultation

A pre-consultation meeting with the Owner and City Staff was held on October 18, 2018. Attached in **Appendix A** is an October 24, 2018 e-mail which includes some meeting notes from that meeting. Some of the items discussed during the meeting dealt with the following subjects:

- Policies
- Engineering
- Planning
- Transportation
- Forestry
- SNCA
- Required Plans and Studies

J:\119351_4836BankSt\5.9 Drawings\59civil\current\Figures\FIGURE 1.1.dwg Layout Name: FIGURE 1.1



Scale

Project Title

Drawing Title

Sheet No.

BANK STREET DEVELOPMENT
4836 BANK STREET

SITE LOCATION

FIGURE 1.1

NTS

N.T.S.

BANK STREET DEVELOPMENT
4836 BANK STREET

SITE PLAN

FIGURE 1.2

There is a small drainage ditch on the subject property which outlets to the Bank Street side road ditch. That ditch will need to be filled to support the proposed development. The South Nation Conservation (SNC) was contacted to confirm if a permit was needed to fill the ditch. In an April 15, 2019 e-mail, the SNC confirmed that a permit from that agency would not be required to fill the on-site ditch. A copy of that e-mail is included in **Appendix A**.

1.5 Geotechnical Investigation

A geotechnical report entitled "Geotechnical Investigation, Proposed Commercial Development, 4836 Bank Street, Ottawa, Ontario" by Paterson Group has been prepared for the subject site.

The objective of the investigation report include:

- Determination of the subsoil and groundwater conditions;
- Provision of geotechnical recommendations pertaining to the design and development of the subject site including construction considerations.

Among other items, the report comments on the following:

- Site grading and grade raises;
- Foundation design;
- Pavement structure;
- Infrastructure construction;
- Groundwater control;
- Contamination/corrosive environment.

2 WATER SUPPLY

2.1 Existing Conditions

As previously noted, the 2.5 hectare Home Hardware site is located west of Bank Street and south of Dun Skipper Drive. The subject site is flanked on both the north and east sides by existing watermain. Existing 400 diameter watermain are included in both Bank Street and Dun Skipper Drive. Both watermain fall within the City of Ottawa's pressure district Zone 4C which will provide the water supply to the site.

2.2 Design Criteria

2.2.1 Water Demands

Water demands have been calculated for the development using consumption rates from Table 4.2 of the Ottawa Design Guidelines – Water Distribution. Buildings A, C and D are one or two storey retail buildings while Building B is a 4 storey hotel with an estimated 500 beds. A summary of the water consumption rates is as follows:

Basic Demand:

- Shopping Centre (Retail) 2500 l/1000m²/day
- Hotels 225 l/bed/day

Maximum Daily Demand: 1.5 x Basic Day

Maximum Hourly Demand: 1.8 x Maximum Day

A watermain demand calculation sheet is included in **Appendix B** and the total water demands are summarized as follows:

- Average Day 1.41 l/s
- Maximum Day 2.12 l/s
- Peak Hour 3.83 l/s

2.2.2 System Pressure

The Ottawa Design Guidelines – Water Distribution (WDG001), July 2010, City of Ottawa, Clause 4.2.2 states that the preferred practice for design of a new distribution system is to have normal operating pressures range between 345 kPa (50 psi) and 480 kPa (80 psi) under maximum daily flow conditions. Other pressure criteria identified in Clause 4.2.2 of the guidelines are as follows:

| | |
|------------------|---|
| Minimum Pressure | Minimum system pressure under peak hour demand conditions shall not be less than 276 kPa (40 psi) |
| Fire Flow | During the period of maximum day demand, the system pressure shall not be less than 140 kPa (20 psi) during a fire flow event. |
| Maximum Pressure | In accordance with the Ontario Building/Plumbing Code, the maximum pressure should not exceed 552 kPa (80 psi). Pressure reduction controls will be required for buildings where it is not possible/feasible to maintain the system pressure below 552 kPa. |

2.2.3 Fire Flow Rates

The subject site plan will contain 4 commercial building pads. Calculations using the Fire Underwriter Survey (FUS) method were conducted to determine the fire flow requirement for the site for the two largest Buildings 'A' and 'B'. The FUS method considers building floor area, type of building construction, type of occupancy, availability of sprinkler systems and separations from adjacent buildings. Without detailed architectural drawings for the buildings, the building construction is assumed to be non-combustible as defined by the FUS. As we do not have details of the sprinkler systems at this time, a reduction of 30% has been assumed in accordance with the FUS. No reduction or increase has been required for the occupancy as is common with commercial buildings. Results of the calculations show a fire demand of 11,000 l/min (183.3 l/s) for Building 'A' and 13,000 l/min for Building 'B'. A copy of the FUS calculations is included in **Appendix B**.

2.2.4 Boundary Conditions

The City of Ottawa has provided hydraulic boundary conditions at two locations, one at the existing main on Dun Skipper Drive at the entrance to the site and the other is on the existing Bank Street main at the Bank Street entrance. Boundary conditions have been supplied for the 2019 existing conditions and for the future SUC zone reconfiguration in which the HGL will be reduced. Therefore the existing condition Max HGL is used for the basic day analysis to determine the maximum pressure as it represents the highest HGL elevation. For the peak hour and max day plus fire analysis the SUC zone reconfiguration is used in the analysis as these represent the lowest HGL elevations. The boundary conditions are included in Appendix B and are summarized as follows;

| SCENARIO | CONDITION 1 DUN SKIPPER DRIVE | CONDITION 2 BANK STREET |
|-------------------------------|----------------------------------|----------------------------|
| Max HGL (Basic Day) | 155.6m | 155.6m |
| Peak Hour | 145.1m | 145.1m |
| Max Day + Fire (11,000 l/min) | 139.6m | 139.6m |
| Max Day + Fire (13,000 l/min) | 137.8m | 137.9m |

2.2.5 Hydraulic Model

A computer model for the site has been developed using the Infowater 12.4 program by Innovyze. The model includes the proposed and existing watermain on Bank Street and Dun Skipper Drive and the boundary conditions provided by the City.

2.3 Proposed Water Plan

2.3.1 Modelling Results

The site will be serviced by two connections to the existing 400 mm watermain on Dun Skipper Drive and Bank Street. All watermain are 200 mm diameter except for a 150 mm diameter stub which services Buildings 'A' and 'D'. There are four fire hydrants proposed, nodes TH-010 to TH-040 in the model. Nodes TH-010 and TH-030 are adjacent to Buildings 'A' and 'D' with a fire demand of 11,000 l/min per Section 2.3.3. Nodes TH-020 and TH-040 are adjacent to Buildings 'B' and 'C' with a fire demand of 13,000 l/min. An existing hydrant on Dun Skipper Drive also

provides fire protection to Building 'B' and is represented by Node S15-300 in the water model. Results of the hydraulic analysis for the Site is included in **Appendix B** and is summarized as follows:

| SCENARIO | |
|--|---------------|
| Basic Day (Max HGL) Pressure (kPa) | 530.3 – 539.0 |
| Basic Day Water Age (hrs.) | 1.0 – 7.5 |
| Peak Hour Pressure (kPa) | 417.4 – 436.0 |
| Design Fire flow @ 140 kPa Residual Pressure (l/s) | |
| - Retail (183.3 l/s) | 434.0 & 686.0 |
| - Hotel (216.7 l/s) | 425.4 – 486.4 |

A comparison of the results and design criteria is summarized as follows:

| | |
|------------------|---|
| Maximum Pressure | Under Basic Day there are no nodes in which the pressure exceeds 552 kPa (80 psi), thus no pressure reducing control is required. There is also no area where the pressure exceeds the maximum level of 689 kPa (100 psi) in unoccupied areas. |
| Water Age | The water age under basic day conditions has been calculated for the site. The water age is calculated from the boundary. The highest water age is 7.5 hours from the boundary conditions. While the water age is adequate under basic day conditions, the age may be a concern during the early stage of construction due to low demand. Should water quality become a concern an automatic flushing unit in accordance with City Detail W3.2 can be installed on the water system in order to increase circulation. |
| Minimum Pressure | The lowest minimum pressure during peak hour conditions is 417.4 kPa which exceeds the minimum 276 kPa (40 psi) requirement. |
| Fire Flow | The minimum design fire flow under maximum day conditions with minimum system pressure of 140 kPa (20 psi) is 434.0 l/s for retail which exceeds the requirement of 183.3 l/s (11,000 l/min) from Section 2.3.3. For the hotel, the minimum fire flow is 425.4 l/s which practically meets the 216.7 l/s (13,000 l/min) requirement. |

2.3.2 Watermain Layout

In order to provide additional reliability to the system in case of a watermain break, two connections to the City's watermain system are proposed. One proposed connection is to the existing 400 mm watermain within the Dun Skipper Drive right of way and the other proposed connection is to the 400 mm watermain in Bank Street. The proposed water plan is shown on Drawing 119351-001, the Site Servicing Plan, a copy of which is included in **Appendix F**. An accompanying Drawing 010, Details and Notes is also included in **Appendix F**. The proposed fire hydrant layout also includes an unobstructed path of no more than 45m between the hydrant and Siamese connections as required by the Ontario Building Code.

3 WASTEWATER DISPOSAL

3.1 Existing Conditions

The Leitrim Home Hardware site at 4836 Bank Street is located within the Leitrim Development Area where sanitary flows ultimately outlet to the Leitrim Sanitary Pumping Station. As part of the adjacent downstream developments, the outlet sanitary sewer system for the subject site was completed. Those sewers were installed as per the recommendations of the 2016 Updated Serviceability Report. In particular, a 200 mm diameter sanitary sewer in Dun Skipper Drive was constructed as part of the Pathways Phase 1 project. That sewer (at MH1A) was also sized for the upstream Idone commercial lands. A highlighted copy of the sanitary sewer design sheet from the Pathways Phase 1 design, together with the related Sanitary Drainage Area Plan (drawing 33956-501A) are included in **Appendix C**.

3.2 Design Criteria

The sanitary sewers for the subject site will be based on the City of Ottawa design criteria. It should be noted that the sanitary sewer design for this study incorporates the latest City of Ottawa design parameters identified in Technical Bulletin ISTB-2018-01. Some of the key criteria will include the following:

- Commercial/Institutional flow 28,000 l/ha/d
- Peaking factor 1.5 if ICI in contributing area >20%
1.0 if ICI in contributing area <20%
- Infiltration allowance 0.33 l/s/ha
- Velocities 0.60 m/s min. to 3.0 m/s max.

3.3 Recommended Wastewater Plan

The on-site sanitary system will consist of a network of 200mm PVC sewers installed at normal depth and slope and will provide a single service connection to each commercial building. The sewers have been designed using the criteria noted above in Section 3.2 and outlet via a connection to the sanitary sewer within the Dun Skipper Drive right of way. A copy of the sanitary drainage area plan 119351-400 and the sanitary sewer design sheet can be found in **Appendix C**. Please refer to the site servicing plan 119351-001 for further details. No off site construction or sewer improvements are needed for the subject site. As noted previously, the proposed wastewater plan includes capacity at MH 1A for the upstream Idone commercial property.

4 SITE STORMWATER MANAGEMENT

4.1 Existing Conditions

The 2016 Updated Serviceability Report recommended that the subject site and the upstream Idone commercial site be serviced with a 1350 mm diameter minor storm sewer. That sewer was constructed in 2017 as part of the downstream Pathways Phase 1 development and is presently terminated near the north-east corner on the subject site. It is noted that the 1350 mm diameter storm sewer was also sized to provide a minor storm outlet for a portion of the future Earl Armstrong Road. The City of Ottawa requested the latter capacity in the event that the future road was located adjacent to the Idone commercial property. For reference, a highlighted copy of the Pathways Phase 1 storm sewer design sheet together with a copy of Drawing 33956-500A, Pathways Phase 1 Storm Drainage Area Plan are included in **Appendix D**.

The City of Ottawa is presently undertaking the Earl Armstrong Road Environmental Assessment and the preferred location of the road at Bank Street is not adjacent to the Idone property but about 200 m south of that location. Therefore the development of the subject site, as well as the adjacent Idone commercial property, will no longer need to provide a minor storm outlet for the future Earl Armstrong Road.

4.2 Phasing

Although the subject site will eventually include four buildings, the property owner plans to phase the site development. The first phase will include only Building A, associated parking, and vehicular connection to both Bank Street and Dun Skipper Drive. **Figure 4.1** shows the approximate limits for Phase 1. The existing Home Hardware retail outlet will remain open while the new store is under construction. As a consequence of this development plan, the existing 1350 mm diameter storm sewer, which is presently terminated behind Building B near Dun Skipper Drive, can no longer be the minor storm outlet for the commercial site. Instead, it is now proposed to service the site with a new 750 mm diameter storm sewer under the Don Skipper Drive driveway access location.

4.3 Design Criteria


IBI Group recently completed the municipal infrastructure design for the Pathways Phase 1 development. That design included a review of the allowable flow from the subject site including the adjacent Idone commercial property. The "Pathways" design assumed that the allowable minor storm release rate for the two commercial sites was 760 l/s and that the 1:100 year storm event would be self-contained with no overflow to adjacent properties. The emergency overflow for events greater than the 1:100 year event (stress test) would be to Bank Street. A copy of drawing 33956-700 DDSWMM Schematic from the former report along with an excerpt from the report identifying the previously mentioned release rate are included in **Appendix D**. The subject site and adjacent commercial property are outlined in the red and identified as area EXT4.

The stormwater system was designed following the principles of dual drainage, making accommodations for both major and minor flow.

Some of the key criteria include the following:

- | | |
|---------------------------------|--------------------------|
| • Design Storm | 1:2 year return (Ottawa) |
| • Rational Method Sewer Sizing | 1:2 year return (Ottawa) |
| • Initial Time of Concentration | 10 minutes |
| • Runoff Coefficients | |
| • Pipe Velocities | 0.80 m/s to 6.0 m/s |

J:\119351_4836BankSt\5.9 Drawings\59civil\current\Figures\FIGURE 4.1.dwg Layout Name: FIGURE 4.1



Scale

Project Title

Drawing Title

Sheet No.

N.T.S.

BANK STREET DEVELOPMENT
4836 BANK STREET

PHASING PLAN

FIGURE 4.1

4.4 Proposed Minor System

Using the criteria identified in Section 4.3, the proposed on-site storm sewers were sized accordingly. A detailed storm sewer design sheet and the associated Storm Sewer Drainage Area plan (drawing 119351-500) are both included in **Appendix D**. The Site Servicing Plan, depicting all on-site storm sewers can be found in **Appendix G**.

The proposed minor storm sewer will range in size between 200 mm diameter and 750 mm diameter. Catchbasin lead pipes will mostly be 200 mm diameter with some 250 mm diameter exceptions. The minor storm sewer outlet will be via the 750 mm diameter pipe which is proposed to connect to the existing 1350 mm diameter storm sewer in Dun Skipper Drive. The existing 1350 mm diameter storm sewer behind building B will be terminated with a manhole and will receive some minor storm flow from the landscaped areas behind Building B. The proposed design has also provided minor storm sewer capacity for the future Idone commercial site near MH1.

The 1350 mm diameter storm sewer in Dun Skipper Drive ultimately outlets to the Findlay Creek Village SWMF. This facility provides 80% TSS removal, as such no additional on-site stormwater quality control is required within the subject lands.

4.5 Stormwater Management

The subject site will be limited to a release rate established using the criteria described in section 4.2. This will be achieved through a combination of inlet control devices (ICD's) at inlet locations and surface storage.

Flows generated that are in excess of the site's allowable release rate will be stored on site in strategic surface storage areas or by the use of roof top storage and gradually released into the minor system so as not to exceed the site's allocation.

The maximum surface retention depth located within the developed areas will be limited to 300mm during a 1:100 year event as shown on the ponding and grading plans located in **Appendix G**.

Overland flow routes will be provided in the grading to permit emergency overland flow, in excess of the 100 year event, from the site.

At a single location within the site, west of building D, the opportunity to store runoff is limited due to grading constraints and building geometry, this area will flow uncontrolled to the Dun Skipper right-of-way. This uncontrolled areas – 0.01 hectares in total, have an average C value of 0.6250. Based on 1:100 year storm uncontrolled flows, the uncontrolled areas generate 3.10 l/s runoff (refer to Section 4.6 for the calculation).

The site grading and ponding has been designed to control water generated during the 1:100-year event, with no overflow leaving the site. Please refer to the SWM calculations in **Appendix E**.

4.6 Inlet Controls

The allowable release rate for the 2.49 Ha site can be calculated as follows:

$$\begin{aligned} Q_{\text{allowable}} &= 760 \text{ L/s as per IBI Pathways Phase 1 Report – EXT 4 drainage area} \\ \text{Area Total EXT4} &= 4.04 \text{ Ha} \\ \text{Subject lands share} &= 62\% \text{ of EXT4 release rate } (2.5 \text{ Ha} / 4.04 \text{ Ha} = 0.62) \\ Q_{\text{Subject Lands}} &= 468.42 \text{ L/s} \end{aligned}$$

As noted in Section 4.5, a small portion of the site just west of Building D will be left to discharge to the Dun Skipper Drive boulevard at an uncontrolled rate.

Based on a 1:100 year event, the flow from the 0.01 Ha uncontrolled areas can be determined as:

$$\begin{aligned}
 Q_{\text{uncontrolled}} &= 2.78 \times C \times i_{100\text{yr}} \times A \quad \text{where:} \\
 C &= \text{Average runoff coefficient of uncontrolled area} = 0.625 \\
 i_{100\text{yr}} &= \text{Intensity of 100-year storm event (mm/hr)} \\
 &= 1735.688 \times (T_c + 6.014)^{0.820} = 178.56 \text{ mm/hr; where } T_c = 10 \text{ minutes} \\
 A &= \text{Uncontrolled Area} = 0.01 \text{ Ha}
 \end{aligned}$$

Therefore, the uncontrolled release rate can be determined as:

$$\begin{aligned}
 Q_{\text{uncontrolled}} &= 2.78 \times C \times i_{100\text{yr}} \times A \\
 &= 2.78 \times 0.625 \times 178.56 \times 0.01 \\
 &= 3.10 \text{ L/s}
 \end{aligned}$$

The maximum allowable release rate from the remainder of the site can then be determined as:

$$\begin{aligned}
 Q_{\text{max allowable}} &= Q_{\text{restricted}} - Q_{\text{uncontrolled}} \\
 &= 468.42 \text{ L/s} - 3.10 \text{ L/s} \\
 &= 465.31 \text{ L/s}
 \end{aligned}$$

Based on the flow allowance at the various inlet locations, a combination of various sizes of inlet control devices (ICDs) were chosen for the design. The design of the inlet control devices is unique to each drainage area and is determined based on a number of factors, including hydraulic head and allowable release rate. The inlet control devices were sized according to the manufacturer's design charts. The restrictions will cause the on-site catchbasins and manholes to surcharge, generating surface ponding in the parking and landscaped areas. Ponding locations and elevations are summarized on drawing 119351-600, Ponding Plan 119351-600 which is included in **Appendix G**.

4.7 On-Site Detention

Any excess storm water up to the 100-year event is to be stored on-site in order to not surcharge the downstream municipal storm sewer system. Detention will be provided in parking and landscape areas and building rooftops, where feasible. As previously noted, the volume of storage is dependent on the characteristics of each individual drainage area and the ICD's were chosen accordingly. It should be noted that 0.30m of vertical separation has been provided from all maximum ponding elevations to lowest building openings.

4.7.1 Site Inlet Control

The following Table summarizes the on-site storage requirements during both the 1:5-year and 1:100-year events.

| DRAINAGE AREA(s) | TRIBUTARY AREA | AVAILABLE STORAGE (M ³) | 100-YEAR STORM | | 5-YEAR STORM | |
|------------------|----------------|-------------------------------------|-----------------------|------------------------------------|-----------------------|------------------------------------|
| | | | RESTRICTED FLOW (L/S) | REQUIRED STORAGE (M ³) | RESTRICTED FLOW (L/S) | REQUIRED STORAGE (M ³) |
| MH9/MH9B | 0.14 | 20.64 | 10 | 44.84 | 10 | 13.85 |
| CB1 | 0.17 | 50.59 | 16 | 38.68 | 16 | 10.47 |
| CB16 | 0.01 | 0.31 | 6 | 1.56 | 6 | 0.48 |
| CB17 | 0.09 | 0.84 | 9 | 25.47 | 9 | 8.90 |
| CB15 | 0.09 | 66.27 | 6 | 28.06 | 6 | 8.73 |
| CBMH3 | 0.02 | 4.17 | 6 | 1.52 | 6 | 0.42 |
| CB11 | 0.03 | 0.93 | 15 | 1.65 | 15 | 0.02 |
| CB12/13/14 | 0.33 | 54.36 | 73 | 54.70 | 73 | 13.07 |
| CB10 | 0.13 | 6.81 | 45 | 13.23 | 45 | 1.73 |
| CBMH2 | 0.08 | 6.21 | 20 | 11.83 | 20 | 2.53 |
| CB7 | 0.08 | 6.97 | 30 | 7.30 | 30 | 0.79 |
| CB6 | 0.07 | 13.66 | 20 | 9.01 | 20 | 2.53 |
| CB5 | 0.06 | 3.41 | 15 | 8.87 | 15 | 1.89 |
| CB8 | 0.17 | 24.90 | 47 | 22.66 | 47 | 4.29 |
| CB4 | 0.03 | 10.62 | 6 | 5.42 | 6 | 1.40 |
| CBMH1 | 0.08 | 0.00 | 20 | 11.83 | 20 | 2.53 |
| CB9 | 0.15 | 10.83 | 43 | 19.23 | 43 | 0.00 |
| CB18 | 0.16 | 13.76 | 15 | 3.65 | 15 | 0.19 |
| TOTAL | 1.89 | 295.28 | 402 | 309.51 | 402 | 73.82 |

In all instances within the parking lot areas the required storage is met with surface ponds and underground in structure/pipe storage which retain the stormwater and discharge at the restricted flow rate to the sewer system. Additionally, available storage in the landscaped area at CB18 has been calculated including the volume capacity of the perforated pipe subdrain as well as the City standard S29 clear stone trench. Refer to the SWM calculations in **Appendix E** for storage information and Drawing 119351-600, Ponding Plan located in **Appendix G**.

4.7.2 Roof Inlet Controls

The proposed buildings will have roof ICD's that help to control the amount of stormwater being released into the system. The restricted flow rate for the proposed building is shown below.

| ICD AREA | TRIBUTARY AREA | 100-YEAR STORM | | 5-YEAR STORM | |
|--------------|----------------|-----------------------|------------------------------------|-----------------------|------------------------------------|
| | | RESTRICTED FLOW (L/S) | REQUIRED STORAGE (M ³) | RESTRICTED FLOW (L/S) | REQUIRED STORAGE (M ³) |
| Bldg A | 0.30 | 27.0 | 89.56 | 27.0 | 32.15 |
| Bldg B | 0.22 | 20.0 | 65.35 | 20.0 | 23.40 |
| Bldg C | 0.05 | 8.0 | 10.68 | 8.0 | 3.13 |
| Bldg D | 0.05 | 8.0 | 10.68 | 8.0 | 3.13 |
| TOTAL | 0.62 | 63.0 | 176.27 | 63.0 | 61.81 |

4.7.3 Overall Release Rate

As noted above, the site uses ICDs to restrict the 100 year storm event to the criteria approved by the City of Ottawa. Restricted stormwater will be contained onsite by utilizing surface ponding, in structure/pipe and rooftop storage. In the 100 year event, there will be no off-site overflow.

The sum of restrictions on the site, rooftops and uncontrolled flows is 468.10 l/s (402 l/s + 63.00 l/s + 3.10 L/S), which is less than the allowable release of 468.42 l/s noted in section 4.6.

5 SEDIMENT AND EROSION CONTROL PLAN

5.1 General

During construction, existing stream and conveyance systems can be exposed to significant sediment loadings. Although construction is only a temporary situation, it is proposed to possibly introduce a number of mitigative construction techniques to reduce unnecessary construction sediment loadings. These may include:

- Until the local storm sewer is constructed, groundwater in trenches will be pumped into a filter mechanism prior to release to the environment. One half diameter bulkhead barriers will be installed at the nearest downstream manhole in each sewer which connects to an existing downstream sewers.
- Seepage barriers will be constructed in any temporary drainage ditches (where applicable);
- Sediment capture filter socks will remain on open surface structures such as maintenance holes and catchbasins until these structures are commissioned and put into use.
- Silt fence on the site perimeter will be installed.

5.2 Trench Dewatering

Any trench dewatering using pumps will be discharged into a filter trap made up of geotextile filters and straw bales similar in design to the OPSD 219.240 Dewatering Trap. These will be constructed in a bowl shape with the fabric forming the bottom and the straw bales forming the sides. Any pumped groundwater will be filtered prior to release to the existing surface runoff. The contractor will inspect and maintain the filters as needed, including sediment removal and disposal and material replacement as needed. It should be noted that the contractor will be responsible for the design and management of the trap(s).

5.3 Bulkhead Barriers

To further reduce downstream sediment loading, ½ diameter bulkheads will be constructed over the lower half of the outletting sewers during construction. These bulkheads will trap any sediment laden flows, thus preventing any construction-related contamination into existing sewers. The bulkheads will be inspected and maintained including periodic sediment removal as needed.

5.4 Seepage Barriers

In order to further reduce sediment loading to the surrounding area such as the Bank Street roadside ditch, seepage barriers will be installed on any surface water courses at appropriate locations that may become evident during construction. These barriers will be Light Duty Straw Bale Barriers per OPSD 219.100 and Heavy Duty Silt Fence Barriers per OPSD 219.130; locations are shown on the Erosion and Sedimentation Control Plan included in **Appendix G**. They are typically made of layers of straw bales or geotextile fabric staked in place. All seepage barriers will be inspected and maintained as needed.

5.5 Surface Structure Filters

All catchbasins, and to a lesser degree, manholes, convey surface water to sewers. Until streets are asphalted and curbed, all catchbasins and manholes will be constructed with sediment capture inserts or equivalent located between the structure frame and cover. These will stay in place and be maintained during construction and build until it is appropriate to remove same.

6 APPROVALS AND CITY REQUIREMENTS

6.1 City of Ottawa

The City of Ottawa reviews all development documents including this report and working drawings. Upon completion, the City will approve the local watermains under Permit No. 008-202, submit the sewer ECA application to the province, and eventually issue a Commence Work Notification.

6.2 Province of Ontario

The Ministry of Environment, Conservation and Parks (MECP) will approve the local sewers under Section 53 of the Ontario Water Resources Act and issue an Environmental Compliance Approval. The Ministry will also issue a Permit to Take Water.

6.3 Conservation Authority

The South Nation Conservation has confirmed no permits are required from the agency. Email correspondence with SNC is included in **Appendix A**.

6.4 Federal Government

There are no required permits, authorizations or approvals needed expressly for this development from the federal government.

7 CONCLUSIONS & RECOMMENDATIONS


7.1 Conclusions

This report and the accompanying working drawings clearly indicate that the proposed development meets the requirements of the stakeholder regulators, including the City of Ottawa, provincial MECP and SNC. The proposed development is in general conformance with the recommendations of both the 2016 Updated Serviceability Report and the Pathways Phase 1 design.

There is a reliable water supply available adjacent to the proposed development; a wastewater outlet is available adjacent to the site, local storm sewers have been installed adjacent to the site and an expansion to the existing Findlay Creek Village Stormwater Facility has been constructed to collect and treat runoff from the subject site.

7.2 Recommendations

It is recommended that the regulators review this submission with an aim of providing the requisite approvals to permit the owners to proceed to the construction stage of the subject site.



"J:\119351_4836BankSt\5.2 Reports\5.2.2 Civil\3rd Submission\CTR-Design Brief-2020-04-20.docx"

APPENDIX A

- **City Pre-Consultation Meeting Notes (October 24, 2018 e-mail)**
- **April 15, 2019 e-mail from the South Nation Conservation**

From: Walker, Max
To: [Nico Church](#)
Cc: [Brian Casagrande](#)
Subject: 4836 Bank Street - Comments
Date: October-24-18 3:07:35 PM
Attachments: [Pre-application Consultation Servicing Memo \(2\).pdf](#)
[4836_Plan and Study list.pdf](#)

Nico,

-

As a follow-up to our meeting on October 18, 2018, please find below information regarding the development of the noted site. I have identified the plans and studies required for an application for a [Site Plan Control](#) (Manager Approval, Public Consultation) and a [Zoning By-law](#) amendment. Should the proposed development/use change, another pre-consultation should be scheduled to discuss.

-

Policies/designations of the site:

- Official Plan – designated [Developing Community \(Expansion Area\)](#) and [General Urban Area](#)
 - Official Plan [Amendment 150](#) was adopted by Council in December 2013. The application will be reviewed under the Official Plan with regard for the Council approved amendments contained within Official Plan Amendment (OPA) 150. An annotated version of the Official Plan, showing the proposed changes within the context of existing policies, can be found [here](#).
- Please consider section 4.8.6 - [Land-Use Constraints Due to Airport and Aircraft Operations](#)
- [Leitrim Community Design Plan](#)
- [Building Better and Smarter Suburbs](#)
- [Urban Design Guidelines for Large-Format Retail](#)

Engineering Comments:

-

As per the pre-application memo, attached.

-

Planning Comments:

Buildings should be oriented to front, face, and feature public streets, especially with buildings at corners, as shown on the concept plan.

Building façades along the public streets should be articulated with colour, material variations, windows, and other treatments of the wall plane to provide a high quality of design, detail, and variety. The design treatment of flanking façades visible from the street should be similar to that of the front facade.

Building fronts should be treated as pedestrian areas and public spaces.

The side and rear of buildings abutting low to medium density residential properties should be of similar height as the residential dwellings or should be stepped above 4 storeys to maintain an appropriate scale in relation to adjacent residential uses.

- E.g., where the building height is greater than 4 storeys the second, third or fourth storey could be stepped back a further 2.5 metres from the front wall of the storey below.
- Locate loading areas away from adjacent sensitive uses, such as residential and outdoor amenity areas, to reduce the impacts of noise and pollution that could be caused by such uses. Use landscaping and fencing to help buffer potential impacts.

Orient the front façade to face the public street and locate front doors to be visible, and directly accessible, from the public street.

- Please consider adjustments to the building center building with a view on orienting it towards the streets to re-inforce the street edge with active frontages and entrances directly from ROW and parking located behind the building.

Base new development on an internal circulation pattern that allows logical movement throughout the site that will accommodate, and not preclude, intensification over time. Design the internal circulation pattern with direct connections to the surrounding streets.

- The subject property does not have access to Dunskipper Dr. Please outline the framework that will facilitate the proposed access, e.g. easement.
 - Consider locating the access over the future services for the most efficient and effective use of space.
- The proposed access to Bank Street overlaps with the lands to the south. Please clarify how this access will be built, e.g., agreements, if any, between the Owner of the subject site and of the abutting lands.

Design the site circulation to minimize the conflicts between pedestrians and vehicles. This can be achieved by orienting car parking spaces to minimize the number of traffic aisles that pedestrians must cross. Overall, the development should

be designed for pedestrians and the public realm first, vehicles second.

Divide large parking areas into smaller and well-defined sections using soft and hard landscaping in order to minimize the amount of paved areas

Enclose all utility equipment within buildings or screen it from both the public street and private properties to the rear and ensure that noise is attenuated. This includes utility boxes, garbage and recycling container storage, loading docks and ramps and air conditioner compressors

Outdoor loading and refuse collection - incorporating all building services, including disposal bins, into the architectural fabric of the building

- Ensure that the wall height is sufficient to completely conceal garbage dumpsters in order to avoid conflict of uses. We find that the Ecologia refuse bins meets this objective.
- Consider Molak and/or Earthbins.

The site has approximately 300 parking spaces, whereas the By-law requires only 176 parking space @ a rate of 3.4 per 100 m² of GFA for retail. Shopping Centre is 3.6 per 100 m² of GFA. Please provide a strong rational for the excessive parking spaces.

Provide opportunities for pedestrian connections between the subject site and remainder of the Idone lands. Section 4.11 (c) of the Official Plan states that we should pursue opportunities to reduce parking requirements and promote increased usage of walking, cycling and transit, where appropriate. We are creating a connected development which works in favor of permeability and improved opportunities for active transportation. Disconnected neighborhoods with isolated land uses result in longer trip distances, which favor vehicular mode choices.

With respect to the turning movements, the applicant should demonstrate that all operational characteristics of the site could be self-contained.

The site is outside of the area envisioned for the mixed-use centre designation per the Leitrim Community Design Plan. It is suggested to make a case for why the expansion of the mixed-use area further south is reasonable and why this property should be analogous to the other mixed use areas.

Section 3.13 -Developing Community Expansions Area- of the Official Plan requires a Plan of Subdivision to determine how the land will be serviced and developed. Because the Owner is not party to the plan of subdivision for the surrounding lands, a site plan application, together with a zoning amendment application, is required to the identify distribution of land uses, how the site is to be serviced and how traffic will be addressed.

The site is located within the Ottawa Airport Operating Influence Zone. The

landscape plan should not include plants known to be attractive to birds. The landscape plan should conform to Transport Canada's TP 11500 table c4 'Ornamental Trees and Shrubs Attractive to Birds'.

Transportation Comments:

A Transportation Impact Assessment (TIA) would be required in support of the Zoning By-law application. The TIA should be in accordance to the City's TIA Guidelines.

Bank Street is an urban arterial road in this section with a ROW protection of 44.5m per the City OP. Road widening will be required to achieve the ROW width, i.e. 22.25m from the existing centreline of the road to the property line.

There is a plan to improve the Intersection of Bank Street and Dunskipper Drive. This will include turning lanes and traffic signals. The intersection is currently in the 2014 DC By-law, subject to approval by Council.

Note that per the transportation impact study completed for the subdivision to the north, the traffic signals are not warranted for the intersection until 2025.

Ensure that Dunskipper access on Bank Street is reviewed for safety if road modifications are not in place or keep this access closed until intersection modifications and signalization can be completed.

A 5X5 sight triangle will be required at the Dunskipper Drive access

New TIA guidelines:

The TIA (Transportation Impact Assessment) Guidelines (2017) were approved by Transportation Committee and City Council on June 14, 2017. The new version of the TIA Guidelines (2017) that are posted on the web are now to be used for the TIA Submission for development applications.

The following list highlights the significant changes to the 2006 TIA Guidelines

- A recent revisit of all steps in the TIA Guidelines has retained the first three steps as required for our review and or sign off. Only step 4, which is the strategy report, is optional. You may or may not forward the strategy report to staff for review and can move on to assemble all documentation (including strategy report) into step 5 for submission of the application.

Please provide 3 copies of the Traffic Impact Assessment, if required.

-

Forestry Comments:

- A Tree Conservation Report (TCR) must be supplied for review along with the suite of other plans/reports required by the City; an approved TCR is a requirement of Site Plan approval.
- Any removal of privately-owned trees 10cm or larger in diameter requires a tree permit issued under the Urban Tree Conservation Bylaw; the permit is based on the approved TCR.
- The removal of City-owned trees will require the permission of Forestry Services who will also review the submitted TCR.
- In this case, the TCR may be combined with the Environmental Impact Statement.

- TCR shall addresses butternut trees.

- The TCR must list all trees on site by species, diameter and health condition – separate stands of trees may be combined using averages.
- The TCR must address all trees with a critical root zone that extends into the developable area – all trees that could be impacted by the construction that are outside the developable area need to be addressed.
- Trees with a trunk that crosses/touches a property line are considered co-owned by both property owners; permission from the adjoining property owner must be obtained prior to the removal of co-owned trees.

If trees are to be removed, the TCR must clearly show where they are, and document the reason they can not be retained – please provide a plan showing retained and removed treed areas.

- All retained trees must be shown and all retained trees within the area impacted by the development process must be protected as per City guidelines listed on Ottawa.ca.
- The City encourages the retention of healthy trees; if possible, please seek opportunities for retention of trees that will contribute to the design/function of the site.
- Please ensure all planted trees have a sufficient soil volume to support them at maturity. Please ensure salt tolerant trees are planted in high salt areas.
- For more information on the process or help with tree retention options, contact Mark Richardson mark.richardson@ottawa.ca.

-

SNCA Comments:

-

SNC recommends a storm water report, or an update to an existing report. It should demonstrate that storm water runoff post development will equal pre development for the 2 or 5 and the 100 year storm event. Treatment should achieve a 80% TSS removal. The following plans should also be provided: storm water, drainage and grading, sediment and erosion control.

GeoOttawa shows roadside ditches and a watercourse that starts on the property flowing east into the ditch. These features should be been confirmed.

Note that any interference with a watercourse may require a permit under Ontario Regulation 170/06 and restrictions may apply. The applicant should contact South Nation Conservation before commencing any work that may interfere with a watercourse.

-

Required plans and studies:

As per the Study and Plan identification List

For information and guidance on preparing required studies and plans refer to <http://ottawa.ca/en/city-hall/planning-and-development/how-develop-property/development-application-review-process-2/guide-preparing-studies-and-plans>

Fees

The fees are detailed in Table 1 and 2, below. Please note that where two or more planning applications are submitted at the same time for the same property, the planning fee imposed for such applications shall be reduced by 10%.

Table 1: Site Plan Fees

| | |
|---|--|
| Manager Approval, Public Consultation Fee: | \$ 21,508.66 |
| <i>Includes:</i> | Planning Fee: \$ 18,478 |
| | On-Site Sign Fee: \$576.30 |
| | Legal Fee: \$2,454.36 (\$2,172 + \$282.36 HST) |
| <i>Plus</i> | |
| Initial Engineering Design Review | \$10,000 (includes HST) (value of Hard |

| | |
|------------------------------------|--|
| and Inspection Fee: | and Soft Servicing >\$300,000) |
| <i>Plus</i> | |
| Conservation Authority Fee: | \$975 |

Table 2: Zoning Amendment Fees

| Zoning By-Law Amendments | |
|---------------------------------|---|
| Major Zoning Amendment: | \$16,545.30 |
| <i>Includes:</i> | Planning Fee: \$15,969 |
| | On-Site Sign Fee: \$576.30 (<i>incl. HST</i>) |

Prior to making a complete submission, I also encourage you to discuss the proposal with the area Councillor and local community associations. Please note that these pre-consultation comments are valid for one year. If you submit a development application after this time, you may be required to meet for another pre-consultation meeting and/or the submission requirements may change.

If you have any questions regarding the foregoing, please do not hesitate to contact me.

Regards,

-Max

Max Walker, RPP

Planner I | Urbaniste I

Development Review (South Services) | Examen des projets d'aménagement (services sud)

Planning, Infrastructure and Economic Development | Services de planification, d'infrastructure et de développement économique

City of Ottawa | Ville d'Ottawa

☎ 613.580.2424 ext./poste 23947

ottawa.ca/planning / ottawa.ca/urbanisme

APPLICANT'S STUDY AND PLAN IDENTIFICATION LIST

Legend: **S** indicates that the study or plan is required with application submission.

A indicates that the study or plan may be required to satisfy a condition of approval/draft approval.

For information and guidance on preparing required studies and plans refer to:

<http://ottawa.ca/en/development-application-review-process-0/guide-preparing-studies-and-plans>

| S/A | Number of copies | ENGINEERING | | S/A | Number of copies |
|----------|------------------|---|---|----------|------------------|
| S | 5 | 1. Site Servicing Plan | 2. Assessment of Adequacy of Public Services / Site Servicing Study / Brief | S | 3 |
| S | 5 | 3. Grade Control and Drainage Plan | 4. Geotechnical Study | S | 3 |
| | | 5. Composite Utility Plan | 6. Groundwater Impact Study | | |
| | | 7. Servicing Options Report | 8. Wellhead Protection Study | | |
| S | 9 | 9. Transportation Impact Brief | 10. Erosion and Sediment Control Plan / Brief | S | 3 |
| S | 3 | 11. Storm water Management Report / Brief | 12. Hydro geological and Terrain Analysis | | |
| S | 3 | 13. Hydraulic Water main Analysis | 14. Noise / Vibration Study | S | 3 |
| | | 15. Roadway Modification Design Plan | 16. Confederation Line Proximity Study | | |

| S/A | Number of copies | PLANNING / DESIGN / SURVEY | | S/A | Number of copies |
|----------|------------------|---|---|----------|------------------|
| | | 17. Draft Plan of Subdivision | 18. Plan Showing Layout of Parking Garage | | |
| | | 19. Draft Plan of Condominium | 20. Planning Rationale/ Design Brief | S | 2 |
| S | 10 | 21. Site Plan | 22. Minimum Distance Separation (MDS) | | |
| S | 10 | 23. Concept Plan Showing Proposed Land Uses and Landscaping | 24. Agrology and Soil Capability Study | | |
| | | 25. Concept Plan Showing Ultimate Use of Land | 26. Cultural Heritage Impact Statement | | |
| S | 10 | 27. Landscape Plan | 28. Archaeological Resource Assessment Requirements: S (site plan) A (subdivision, condo) | S | 2 |
| S | 1 | 29. Survey Plan | 30. Shadow Analysis | | |
| S | 3 | 31. Architectural Building Elevation Drawings (dimensioned) | 32. Design Brief | | |
| | | 33. Wind Analysis | | | |

| S/A | Number of copies | ENVIRONMENTAL | | S/A | Number of copies |
|----------|------------------|---|--|-----|------------------|
| S | 3 | 34. Phase 1 Environmental Site Assessment | 35. Impact Assessment of Adjacent Waste Disposal/Former Landfill Site | | |
| A | 3 | 36. Phase 2 Environmental Site Assessment (depends on the outcome of Phase 1) | 37. Assessment of Landform Features | | |
| | | 38. Record of Site Condition | 39. Mineral Resource Impact Assessment | | |
| S | 3 | 40. Tree Conservation Report | 41. Environmental Impact Statement / Impact Assessment of Endangered Species | | |
| | | 42. Mine Hazard Study / Abandoned Pit or Quarry Study | | | |

| S/A | Number of copies | ADDITIONAL REQUIREMENTS | | S/A | Number of copies |
|----------|------------------|---|-----|-----|------------------|
| S | 1 | 43. Electronic Copy of All reports/drawings | 44. | | |

Meeting Date: October 18, 2018

File Lead (Assigned Planner): Max Walker

City Architect:

Site Address 4836 Bank Street

Application Type: Site Plan Control / Zoning Amendment

Infrastructure Approvals Project Manager: Natasha Baird

Transportation Project Manager: Amira Shehata

*Preliminary Assessment: 1 ☒ 2 ☐ 3 ☐ 4 ☐ 5 ☐

*One (1) indicates that considerable major revisions are required before a planning application is submitted, while five (5) suggests that proposal appears to meet the City's key land use policies and guidelines. **This assessment is purely advisory and does not consider technical aspects of the proposal or in any way guarantee application approval.**

It is important to note that the need for additional studies and plans may result during application review. If following the submission of your application, it is determined that material that is not identified in this checklist is required to achieve complete application status, in accordance with the Planning Act and Official Plan requirements, the Planning and Growth Management Department will notify you of outstanding material required within the required 30 day period. Mandatory pre-application consultation will not shorten the City's standard processing timelines, or guarantee that an application will be approved. It is intended to help educate and inform the applicant about submission requirements as well as municipal processes, policies, and key issues in advance of submitting a formal development application. This list is valid for one year following the meeting date. If the application is not submitted within this timeframe the applicant must again pre-consult with the Planning and Growth Management Department.

MEMO

Date:

| | | |
|----------------------|--|----------------------|
| To / Destinataire | Max Walker, Planner | |
| From / Expéditeur | Natasha Baird, Project Manager, Infrastructure Approvals | |
| Subject / Objet | Pre-Application Consultation 4836 Bank and Ward No. 22, | File No. PC2018-0257 |

Please note the following information regarding the engineering design submission for the above noted site:

1. The Servicing Study Guidelines for Development Applications are available at the following address: <http://ottawa.ca/en/development-application-review-process-0/servicing-study-guidelines-development-applications>
2. Servicing and site works shall be in accordance with the following documents:
 - ⇒ Ottawa Sewer Design Guidelines (October 2012)
 - ⇒ Ottawa Design Guidelines – Water Distribution (2010)
 - ⇒ Geotechnical Investigation and Reporting Guidelines for Development Applications in the City of Ottawa (2007)
 - ⇒ City of Ottawa Slope Stability Guidelines for Development Applications (revised 2012)
 - ⇒ City of Ottawa Environmental Noise Control Guidelines (January, 2016)
 - ⇒ City of Ottawa Park and Pathway Development Manual (2012)
 - ⇒ City of Ottawa Accessibility Design Standards (2012)
 - ⇒ Ottawa Standard Tender Documents (latest version)
 - ⇒ Ontario Provincial Standards for Roads & Public Works (2013)

3. Record drawings and utility plans are also available for purchase from the City (Contact the City's Information Centre by email at InformationCentre@ottawa.ca or by phone at (613) 580-2424 x.44455).
4. The Stormwater Management Criteria, for the subject site, is based on the total allowable minor system outflow of 760L/s for 1:100 year storm. For further information please refer to the approved Design Brief, Pathways at Findlay Creek, 4800 Bank Street, Phase 1, prepared by IBI, revised August 2017.
5. Deep Services (Storm, Sanitary & Water Supply)
 - i. The monitoring manhole should be located in an accessible location on private property near the property line (ie. Not in a parking area).

Sewer connections to be made above the springline of the sewermain as per:

 - a. Std Dwg S11.1 for flexible main sewers – connections made using approved tee or wye fittings.
 - b. Std Dwg S11 (For rigid main sewers) – lateral must be less than 50% the diameter of the sewermain,
 - c. Std Dwg S11.2 (for rigid main sewers using bell end insert method) – for larger diameter laterals where manufactured inserts are not available; lateral must be less than 50% the diameter of the sewermain,
 - d. Connections to manholes permitted when the connection is to rigid main sewers where the lateral exceeds 50% the diameter of the sewermain. – Connect obvert to obvert with the outlet pipe unless pipes are a similar size.
 - e. No submerged outlet connections.
6. Water Boundary condition requests must include the location of the service and the expected loads required by the proposed development. Please provide the following information:
 - i. Location of service

- ii. Type of development and the amount of fire flow required (as per FUS, 1999).
 - iii. Average daily demand: ____ l/s.
 - iv. Maximum daily demand: ____ l/s.
 - v. Maximum hourly daily demand: ____ l/s.
7. Provide a geotechnical report for the proposed development.
8. MOECC ECA Requirements

An MOECC Environmental Compliance Approval might be required for the proposed development. Please contact Ontario Ministry of the Environment and Climate Change, Ottawa District Office to arrange a pre-submission consultation:

For I/C/I applications: Emily Diamond

(613) 521-3450, ext. 238

Emily.Diamond@ontario.ca
9. Phase 1 ESAs and Phase 2 ESAs must conform to clause 4.8.4 of the Official Plan that requires that development applications conform to Ontario Regulation 153/04.
10. Location of Fire Hydrant:

If the proposed buildings will be sprinkled, an unobstructed path of 45 meters between the hydrant and siamese connection as required by the Ontario Building Code.
11. Noise Study Requirements:

Since the proposed site is within 100m from an arterial road, a noise study will be required.
12. Exterior Site Lighting:

If the exterior Site Lighting is used, provide a certification and plan by a qualified engineer confirming the design complies with the following criteria needs to be provided:

- i. It must be designed using only fixtures that meet the criteria for Full Cut-Off (Sharp cut-off) Classification, as recognized by the Illuminating Engineering Society of North America (IESNA or IES), and;
- ii. It must result in minimal light spillage onto adjacent properties. As a guideline, 0.5 foot-candle is normally the maximum allowable spillage.
- iii. The location of the fixtures, fixture types as in make, model and part number and the mounting heights must be shown on one of the approved plans.

Should you have any questions or require additional information, please contact me directly at (613) 580-2424, x 27995 or by email at natasha.baird@ottawa.ca.

Jim Moffatt

From: Samantha Labadie
Sent: Monday, April 15, 2019 9:45 AM
To: Jim Moffatt
Subject: FW: 4836 Bank Street - Ditch

From: Geoff Owens [mailto:GOwens@nation.on.ca]
Sent: Monday, April 15, 2019 8:28 AM
To: Samantha Labadie <Samantha.Labadie@ibigroup.com>
Subject: RE: 4836 Bank Street - Ditch

Good morning Samantha,

It does not appear to be something SNC's Regulations would consider requires a permit. However, it should be understood that drainage is a big issue in the area and current drainage patterns/flows should be maintained and no changes that impact any surrounding properties including the City of Ottawa should be made as this may constitute an issue under common law drainage.

Regards,
Geoff

From: Samantha Labadie <Samantha.Labadie@ibigroup.com>
Sent: April 2, 2019 10:12 AM
To: Geoff Owens <GOwens@nation.on.ca>
Subject: 4836 Bank Street - Ditch

Hi Geoff,

The Home Hardware property at 4836 Bank Street is proposed to be redeveloped and there is an existing ditch that would need to be filled in (sketch attached).

The existing ditch starts on the property and drains to a roadside ditch along Bank Street.

Would you be able to let us know if we need a permit to fill this ditch in?

Thank you,

Samantha Labadie

IBI GROUP
Suite 400, 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel +1 613 225 1311 ext 64062 fax +1 613 225 9868





NOTE: This email message/attachments may contain privileged and confidential information. If received in error, please notify the sender and delete this e-mail message.
NOTE: Ce courriel peut contenir de l'information privilégiée et confidentielle. Si vous avez reçu ce message par erreur, veuillez le mentionner immédiatement à l'expéditeur et effacer ce courriel.



Geoff Owens | Regulations Officer

38 Victoria Street, P. O. Box 29, Finch, ON K0C 1K0

Tel: 613-984-2948 or 1-877-984-2948 ext. 613) 984-2948 x.240 | Fax:

613-984- 2872

www.nation.on.ca ☐☐☐☐

[Book a Meeting Room](#) | [Réservez une salle de réunion](#)

APPENDIX B

- **Boundary Conditions from the City of Ottawa**
- **Watermain Demand Calculation Sheets**
- **FUS Calculation**
- **Water model schematic and results**


Boundary Conditions for 4836 Bank St

Information Provided:

Date provided: December 2019

| Scenario | Demand | |
|----------------------|--------|--------|
| | L/min | L/s |
| Average Daily Demand | 84.6 | 1.41 |
| Maximum Daily Demand | 127.2 | 2.12 |
| Peak Hour | 229.8 | 3.83 |
| Fire Flow Demand #1 | 11000 | 183.3 |
| Fire Flow Demand #2 | 13000 | 216.67 |

Location:



Results: 2019 Existing Conditions

Connection 1 - Dun Skipper Dr.

| Demand Scenario | Head (m) | Pressure ¹ (psi) |
|----------------------------------|----------|-----------------------------|
| Maximum HGL | 155.6 | 79.7 |
| Peak Hour | 145.9 | 65.9 |
| Max Day plus Fire (11,000 l/min) | 146.0 | 66.0 |
| Max Day plus Fire (13,000 L/min) | 143.1 | 61.9 |

¹ Ground Elevation = 99.53m

Connection 2 - Bank St.

| Demand Scenario | Head (m) | Pressure ¹ (psi) |
|----------------------------------|----------|-----------------------------|
| Maximum HGL | 155.6 | 80.2 |
| Peak Hour | 145.9 | 66.4 |
| Max Day plus Fire (11,000 l/min) | 144.7 | 66.5 |
| Max Day plus Fire (13,000 L/min) | 143.1 | 62.4 |

¹ Ground Elevation = 99.19m

Results: SUC Zone Reconfiguration

Connection 1 - Dun Skipper Dr.

| Demand Scenario | Head (m) | Pressure ¹ (psi) |
|----------------------------------|----------|-----------------------------|
| Maximum HGL | 146.9 | 67.3 |
| Peak Hour | 145.1 | 64.8 |
| Max Day plus Fire (11,000 l/min) | 139.6 | 56.9 |
| Max Day plus Fire (13,000 L/min) | 137.8 | 54.5 |

¹ Ground Elevation = 99.53m

Connection 2 - Bank St.

| Demand Scenario | Head (m) | Pressure ¹ (psi) |
|----------------------------------|----------|-----------------------------|
| Maximum HGL | 146.8 | 67.7 |
| Peak Hour | 145.1 | 65.3 |
| Max Day plus Fire (11,000 l/min) | 139.6 | 57.4 |
| Max Day plus Fire (13,000 L/min) | 137.9 | 55.0 |

¹ Ground Elevation = 99.19m

Notes:

1) As per the Ontario Building Code in areas that may be occupied, the static pressure at any fixture shall not exceed 552 kPa (80 psi.) Pressure control measures to be considered are as follows, in order of preference:

- a) If possible, systems to be designed to residual pressures of 345 to 552 kPa (50 to 80 psi) in all occupied areas outside of the public right-of-way without special pressure control equipment.
- b) Pressure reducing valves to be installed immediately downstream of the isolation valve in the home/ building, located downstream of the meter so it is owner maintained.

Disclaimer

The boundary condition information is based on current operation of the city water distribution system. The computer model simulation is based on the best information available at the time. The operation of the water distribution system can change on a regular basis, resulting in a variation in boundary conditions. The physical properties of watermains deteriorate over time, as such must be assumed in the absence of actual field test data. The variation in physical watermain properties can therefore alter the results of the computer model simulation. Fire Flow analysis is a reflection of available flow in the watermain; there may be additional restrictions that occur between the watermain and the hydrant that the model cannot take into account.



IBI GROUP
333 PRESTON STREET
OTTAWA, ON
K1S 5N4

WATERMAIN DEMAND CALCULATION SHEET

PROJECT : 4836 Bank Street
LOCATION : Leitrim Development Area - City of Ottawa
DEVELOPER : Leitrim Home Hardware

FILE: 119351.5.7.3
DATE PRINTED: 16-Apr-19
DESIGN: LME
PAGE: 1 OF 1

| Node | Residential | | | | Non-Residential | | | Average Daily Demand (l/s) | | | Maximum Daily Demand (l/s) | | | Maximum Hourly | | | Fire Demand (l/min) |
|-----------------------------|-------------|-----|----|------------|-----------------|-------------|-------------|----------------------------|----------|-------|----------------------------|----------|-------|----------------|----------|-------|---------------------|
| | Units | | | Hotel Beds | Indtrl (ha.) | Inst. (ha.) | Retail (m²) | Res. | Non-res. | Total | Res. | Non-res. | Total | Res. | Non-res. | Total | |
| | SF | APT | ST | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| T-120 (Building A and D) | | | | | | | 3,490 | 0.00 | 0.10 | 0.10 | 0.00 | 0.15 | 0.15 | 0.00 | 0.27 | 0.27 | |
| | | | | | | | | | | | | | | | | | |
| T-150 (Building B) | | | | 500 | | | | 1.30 | 0.00 | 1.30 | 1.95 | 0.00 | 1.95 | 3.52 | 0.00 | 3.52 | |
| | | | | | | | | | | | | | | | | | |
| T-160 (Building C) | | | | | | | 502 | 0.00 | 0.01 | 0.01 | 0.00 | 0.02 | 0.02 | 0.00 | 0.04 | 0.04 | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| Fire Nodes | | | | | | | | | | | | | | | | | |
| TH-110, TH-030 | | | | | | | | | | | | | | | | | 11,000 |
| TH-020, TH-040 | | | | | | | | | | | | | | | | | 13,000 |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

ASSUMPTIONS

RESIDENTIAL DENSITIES

- Single Family (SF) 3.4 p / p / u
- Hotel Beds average 1.8 p / p / u
- Stacked Townhouse (ST) 2.3 p / p / u

AVG. DAILY DEMAND

- Hotel (Table 4.2) 225 l / cap / day
- Retail (Shopping Centre) 2,500 l / 1000m² / day

MAX. DAILY DEMAND

- Hotel (Table 4.2) 338 l / cap / day
- Retail (Shopping Centre) 3,750 l / 1000m² / day

MAX. HOURLY DEMAND

- Hotel (Table 4.2) 608 l / cap / day
- Retail (Shopping Centre) 6,750 l / 1000m² / day

FIRE FLOW

- Hotel 13,000 l / min
- Retail 11,000 l / min

Fire Flow Requirement from Fire Underwriters Survey

Building 'A' & Drive Thru- 1 Storey Retail

Building Floor Area 2,997 m²

Fire Flow

$$F = 220C\sqrt{A}$$

| | | | |
|-----|----------------------|-----|--------------------|
| C | 0.8 | C = | 1.5 wood frame |
| A | 2,997 m ² | | 1.0 ordinary |
| | | | 0.8 non-combustile |
| F | 9,635 l/min | | 0.6 fire-resistive |
| Use | 10,000 l/min | | |

Occupancy Adjustment

| | | |
|------------|--------------|-------------------------|
| | | -25% non-combustile |
| | | -15% limited combustile |
| Use | 0% | 0% combustile |
| | | +15% free burning |
| Adjustment | 0 l/min | +25% rapid burning |
| Fire flow | 10,000 l/min | |

Sprinkler Adjustment

| | | |
|------------|-------------|-----------------------------------|
| | | -30% system conforming to NFPA 13 |
| | | -50% complete automatic system |
| Use | -30% | |
| Adjustment | -3000 l/min | |

Exposure Adjustment

| | | | Separation Charge | |
|---------------|------------|--------|-------------------|------|
| | | | 0 to 3m | +25% |
| | | | 3.1 to 10m | +20% |
| | | | 10.1 to 20m | +15% |
| | | | 20.1 to 30m | +10% |
| | | | 30.1 to 45m | +5% |
| Building Face | Separation | Charge | | |
| north | 23 | 10% | | |
| east | > 45 | 0% | | |
| south | 20 | 15% | | |
| west | 20 | 15% | | |
| Total | | 40% | | |

Adjustment 4,000 l/min

Required Fire Flow

| | |
|-------------------|---------------------|
| Total adjustments | <u>1,000</u> l/min |
| Fire flow | 11,000 l/min |
| Use | 11,000 l/min |
| | 183.3 l/s |

Fire Flow Requirement from Fire Underwriters Survey

Building 'B' - 5 Storey Hotel Building

Building Floor Area (2 largest adjoining floors plus 50% of floors above up to eight)

| | |
|-------------------|----------------------------|
| Floor 1 & 2 | 4,318 m ² |
| 50% Floors 3 to 5 | <u>3,238 m²</u> |
| Total | 7,556 m ² |

Fire Flow

$$F = 220C\sqrt{A}$$

| | | | |
|-----|----------------------|-----|--------------------|
| C | 0.8 | C = | 1.5 wood frame |
| A | 7,556 m ² | | 1.0 ordinary |
| | | | 0.8 non-combustile |
| F | 15,299 l/min | | 0.6 fire-resistive |
| Use | 15,000 l/min | | |

Occupancy Adjustment

| | | |
|------------|--------------|-------------------------|
| | | -25% non-combustile |
| | | -15% limited combustile |
| Use | 0% | 0% combustile |
| | | +15% free burning |
| Adjustment | 0 l/min | +25% rapid burning |
| Fire flow | 15,000 l/min | |

Sprinkler Adjustment

| | | |
|------------|-------------|-----------------------------------|
| | | -30% system conforming to NFPA 13 |
| | | -50% complete automatic system |
| Use | -30% | |
| Adjustment | -4500 l/min | |


Exposure Adjustment

| | | | Separation Charge | |
|---------------|------------|-------------|-------------------|------|
| | | | 0 to 3m | +25% |
| | | | 3.1 to 10m | +20% |
| | | | 10.1 to 20m | +15% |
| | | | 20.1 to 30m | +10% |
| | | | 30.1 to 45m | +5% |
| Building Face | Separation | Charge | | |
| north | > 45 | 0% | | |
| east | > 45 | 0% | | |
| south | 12 | 15% | | |
| west | > 45 | 0% | | |
| Total | | 15% | | |
| Adjustment | | 2,250 l/min | | |

Required Fire Flow

| | |
|-------------------|----------------------|
| Total adjustments | <u>(2,250) l/min</u> |
| Fire flow | 12,750 l/min |
| Use | 13,000 l/min |
| | 216.7 l/s |

WATERMAIN MODEL SCHEMATIC



Basic Day (Max HGL) - Junction Report

| | | ID | Demand (L/s) | Elevation (m) | Head (m) | Pressure (kPa) | Water Age (hrs) |
|----|--------------------------|---------|-----------------|------------------|-------------|-------------------|--------------------|
| 1 | <input type="checkbox"/> | B-200 | 0.68 | 99.25 | 155.60 | 552.18 | 4.69 |
| 2 | <input type="checkbox"/> | S15-300 | 2.34 | 100.00 | 155.60 | 544.84 | 3.78 |
| 3 | <input type="checkbox"/> | T-100 | 0.00 | 101.50 | 155.60 | 530.14 | 1.00 |
| 4 | <input type="checkbox"/> | T-110 | 0.00 | 102.10 | 155.60 | 524.26 | 3.00 |
| 5 | <input type="checkbox"/> | T-120 | 0.10 | 102.25 | 155.60 | 522.79 | 4.43 |
| 6 | <input type="checkbox"/> | T-130 | 0.00 | 102.50 | 155.60 | 520.34 | 6.21 |
| 7 | <input type="checkbox"/> | T-140 | 0.00 | 102.50 | 155.60 | 520.34 | 6.13 |
| 8 | <input type="checkbox"/> | T-150 | 1.30 | 100.60 | 155.60 | 538.95 | 6.40 |
| 9 | <input type="checkbox"/> | T-160 | 0.01 | 101.00 | 155.60 | 535.04 | 3.00 |
| 10 | <input type="checkbox"/> | T-170 | 0.00 | 100.80 | 155.60 | 537.00 | 2.00 |
| 11 | <input type="checkbox"/> | T-180 | 0.00 | 101.10 | 155.60 | 534.06 | 1.00 |
| 12 | <input type="checkbox"/> | TH-010 | 0.00 | 101.90 | 155.60 | 526.22 | 2.00 |
| 13 | <input type="checkbox"/> | TH-020 | 0.00 | 100.70 | 155.60 | 537.97 | 7.21 |
| 14 | <input type="checkbox"/> | TH-030 | 0.00 | 100.90 | 155.60 | 536.02 | 7.54 |
| 15 | <input type="checkbox"/> | TH-040 | 0.00 | 100.70 | 155.60 | 537.97 | 4.00 |

Peak Hour - Junction Report

| | | ID | Demand (L/s) | Elevation (m) | Head (m) | Pressure (kPa) | Water Age (hrs) |
|----|--------------------------|---------|-----------------|------------------|-------------|-------------------|--------------------|
| 1 | <input type="checkbox"/> | B-200 | 1.02 | 99.25 | 145.10 | 449.29 | 0.00 |
| 2 | <input type="checkbox"/> | S15-300 | 6.31 | 100.00 | 145.10 | 441.94 | 0.00 |
| 3 | <input type="checkbox"/> | T-100 | 0.00 | 101.50 | 145.10 | 427.24 | 0.00 |
| 4 | <input type="checkbox"/> | T-110 | 0.00 | 102.10 | 145.10 | 421.36 | 0.00 |
| 5 | <input type="checkbox"/> | T-120 | 0.27 | 102.25 | 145.10 | 419.89 | 0.00 |
| 6 | <input type="checkbox"/> | T-130 | 0.00 | 102.50 | 145.10 | 417.44 | 0.00 |
| 7 | <input type="checkbox"/> | T-140 | 0.00 | 102.50 | 145.10 | 417.44 | 0.00 |
| 8 | <input type="checkbox"/> | T-150 | 3.52 | 100.60 | 145.10 | 436.03 | 0.00 |
| 9 | <input type="checkbox"/> | T-160 | 0.04 | 101.00 | 145.10 | 432.13 | 0.00 |
| 10 | <input type="checkbox"/> | T-170 | 0.00 | 100.80 | 145.10 | 434.10 | 0.00 |
| 11 | <input type="checkbox"/> | T-180 | 0.00 | 101.10 | 145.10 | 431.16 | 0.00 |
| 12 | <input type="checkbox"/> | TH-010 | 0.00 | 101.90 | 145.10 | 423.32 | 0.00 |
| 13 | <input type="checkbox"/> | TH-020 | 0.00 | 100.70 | 145.10 | 435.06 | 0.00 |
| 14 | <input type="checkbox"/> | TH-030 | 0.00 | 100.90 | 145.10 | 433.12 | 0.00 |
| 15 | <input type="checkbox"/> | TH-040 | 0.00 | 100.70 | 145.10 | 435.06 | 0.00 |

Peak Hour - Pipe Report

| | | ID | From Node | To Node | Length (m) | Diameter (mm) | Roughness | Flow (L/s) | Velocity (m/s) | Headloss (m) | HL/1000 (m/k-m) | Status | Flow Reversal Count |
|----|--------------------------|------|-----------|---------|---------------|------------------|-----------|---------------|-------------------|-----------------|--------------------|--------|---------------------|
| 1 | <input type="checkbox"/> | 2107 | S15-300 | B-200 | 84.75 | 393.00 | 120.00 | -1.70 | 0.01 | 0.00 | 0.00 | Open | 0 |
| 2 | <input type="checkbox"/> | 791 | B-200 | T-180 | 127.53 | 393.00 | 120.00 | -2.72 | 0.02 | 0.00 | 0.00 | Open | 0 |
| 3 | <input type="checkbox"/> | P13 | T-100 | TH-010 | 25.45 | 204.00 | 110.00 | 1.24 | 0.04 | 0.00 | 0.02 | Open | 0 |
| 4 | <input type="checkbox"/> | P15 | TH-010 | T-110 | 10.56 | 204.00 | 110.00 | 1.24 | 0.04 | 0.00 | 0.02 | Open | 0 |
| 5 | <input type="checkbox"/> | P17 | T-110 | T-120 | 27.22 | 155.00 | 100.00 | 0.27 | 0.01 | 0.00 | 0.00 | Open | 0 |
| 6 | <input type="checkbox"/> | P19 | T-130 | T-110 | 14.44 | 204.00 | 110.00 | -0.97 | 0.03 | 0.00 | 0.01 | Open | 0 |
| 7 | <input type="checkbox"/> | P21 | T-130 | TH-020 | 56.42 | 204.00 | 110.00 | 1.54 | 0.05 | 0.00 | 0.03 | Open | 0 |
| 8 | <input type="checkbox"/> | P23 | T-130 | TH-030 | 55.80 | 204.00 | 110.00 | -0.57 | 0.02 | 0.00 | 0.00 | Open | 0 |
| 9 | <input type="checkbox"/> | P25 | TH-030 | T-140 | 32.64 | 204.00 | 110.00 | -0.57 | 0.02 | 0.00 | 0.00 | Open | 0 |
| 10 | <input type="checkbox"/> | P27 | TH-020 | T-150 | 39.62 | 204.00 | 110.00 | 1.54 | 0.05 | 0.00 | 0.03 | Open | 0 |
| 11 | <input type="checkbox"/> | P29 | TH-040 | T-150 | 33.83 | 204.00 | 110.00 | 1.98 | 0.06 | 0.00 | 0.04 | Open | 0 |
| 12 | <input type="checkbox"/> | P31 | TH-040 | T-160 | 22.30 | 204.00 | 110.00 | -1.98 | 0.06 | 0.00 | 0.04 | Open | 0 |
| 13 | <input type="checkbox"/> | P33 | T-160 | T-170 | 21.12 | 204.00 | 110.00 | -2.02 | 0.06 | 0.00 | 0.04 | Open | 0 |
| 14 | <input type="checkbox"/> | P35 | T-140 | T-170 | 95.88 | 204.00 | 110.00 | -0.57 | 0.02 | 0.00 | 0.00 | Open | 0 |
| 15 | <input type="checkbox"/> | P39 | T-170 | T-180 | 1.00 | 204.00 | 110.00 | -2.59 | 0.08 | 0.00 | 0.07 | Open | 0 |
| 16 | <input type="checkbox"/> | P41 | T-100 | S15-300 | 54.54 | 393.00 | 120.00 | 4.61 | 0.04 | 0.00 | 0.01 | Open | 0 |
| 17 | <input type="checkbox"/> | P43 | C2 | T-180 | 1.00 | 204.00 | 110.00 | 5.32 | 0.16 | 0.00 | 0.25 | Open | 0 |
| 18 | <input type="checkbox"/> | P45 | C1 | T-100 | 1.00 | 204.00 | 110.00 | 5.84 | 0.18 | 0.00 | 0.30 | Open | 0 |

Max Day + Fire (11,000 l/min) - Fireflow Design Report

| | | ID | Total Demand (L/s) | Available Flow at Hydrant (L/s) | Critical Node ID | Critical Node Pressure (kPa) | Critical Node Head (m) | Design Flow (L/s) | Design Pressure (kPa) | Design Fire Node Pressure (kPa) |
|---|--------------------------|--------|-----------------------|------------------------------------|------------------|---------------------------------|---------------------------|----------------------|--------------------------|------------------------------------|
| 1 | <input type="checkbox"/> | TH-010 | 183.33 | 686.03 | TH-010 | 139.96 | 116.18 | 686.04 | 139.96 | 139.96 |
| 2 | <input type="checkbox"/> | TH-030 | 183.33 | 434.04 | TH-030 | 139.96 | 115.18 | 434.04 | 139.96 | 139.96 |

Max Day + Fire (13,000 l/min) - Fireflow Design Report


| | | ID | Total Demand (L/s) | Available Flow at Hydrant (L/s) | Critical Node ID | Critical Node Pressure (kPa) | Critical Node Head (m) | Design Flow (L/s) | Design Pressure (kPa) | Design Fire Node Pressure (kPa) |
|---|--------------------------|---------|-----------------------|------------------------------------|------------------|---------------------------------|---------------------------|----------------------|--------------------------|------------------------------------|
| 1 | <input type="checkbox"/> | S15-300 | 220.18 | 2,284.11 | S15-300 | 139.98 | 114.28 | 2,284.21 | 139.96 | 139.96 |
| 2 | <input type="checkbox"/> | TH-020 | 216.67 | 425.54 | TH-020 | 139.96 | 114.98 | 425.54 | 139.96 | 139.96 |
| 3 | <input type="checkbox"/> | TH-040 | 216.67 | 486.43 | TH-040 | 139.96 | 114.98 | 486.43 | 139.96 | 139.96 |

APPENDIX C

- **Pathways Phase 1 Sanitary Sewer Design Sheet**
- **Drawing 33956-501A – Pathways Phase 1 External Sanitary Drainage Area Plan**
- **Sanitary Sewer Design Sheet**
- **Drawing 119351-400 – Sanitary Drainage Area Plan**

| LOCATION | | | | RESIDENTIAL | | | | | | | | | | ICI AREAS | | | | | | | | | | INFILTRATION ALLOWANCE | | | | | | | | | | PROPOSED SEWER DESIGN | | | | | | | | | |
|--------------------|------------|-------------|------------|---------------------------------|----|----|----|-----|-----------------------------------|----------------|-----|-----------------|-----------------|-------------------|------|----------------|------|----------------|------|-----------------|-----------------------------|------|------------|-----------------------------|------|------------|------|------|------------------|----------------|------------|----------|-----------|-----------------------|------------------------|--------|--------|--|--|--|--|--|--|
| STREET | AREA ID | FROM MH | TO MH | AREA w/Units (ft ²) | SF | SD | TH | APT | AREA w/o Units (ft ²) | POPULATION IND | CUM | PEAK FLOW (L/s) | PEAK FLOW (L/s) | INSTITUTIONAL IND | CUM | COMMERCIAL IND | CUM | INDUSTRIAL IND | CUM | PEAK FLOW (L/s) | AREA (ft ²) IND | CUM | FLOW (L/s) | AREA (ft ²) IND | CUM | FLOW (L/s) | IND | CUM | TOTAL FLOW (L/s) | CAPACITY (L/s) | LENGTH (m) | DIA (mm) | SLOPE (%) | VELOCITY (ft/s) | AVAILABLE CAPACITY (%) | | | | | | | | |
| Dun Skipper Road | 6132Aa | MH6132A | MH6133A | 0.64 | 10 | | | | 32.0 | 32.0 | | 4.00 | 0.52 | | 0.00 | | | | 0.00 | | 0.00 | 0.64 | 0.64 | 0.64 | 0.18 | | | 0.00 | 0.70 | 43.28 | 82.00 | 200 | 1.60 | 1.335 | 42.58 | 98.39% | | | | | | | |
| Sheet No. 7 | EX12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sheet No. 7 | 6133Ab | BLK6133AS | MH6133A | 0.07 | | | | | 172.8 | 172.8 | | 4.00 | 2.80 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 2.88 | 2.88 | 0.81 | | | | 0.00 | 3.63 | 24.19 | 44.00 | 200 | 0.50 | 0.746 | 20.57 | 85.01% | | | | | | | |
| Dun Skipper Road | 6133Aa | MH6133A | MH6134A | 0.58 | 10 | | | | 32.0 | 236.8 | | 4.00 | 3.84 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.58 | 4.17 | 1.17 | | | | 0.00 | 5.00 | 37.48 | 72.14 | 200 | 1.20 | 1.156 | 32.48 | 86.65% | | | | | | | |
| Dun Skipper Road | 6134A | MH6134A | MH6135A | 0.68 | 12 | | | | 38.4 | 275.2 | | 4.00 | 4.46 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.68 | 4.83 | 1.35 | | | | 0.00 | 5.81 | 28.63 | 72.09 | 200 | 0.70 | 0.883 | 22.82 | 79.70% | | | | | | | |
| Dun Skipper Road | 6135A | MH6135A | MH6136A | 0.19 | 3 | | | | 9.6 | 284.8 | | 4.00 | 4.61 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.19 | 5.02 | 1.41 | | | | 0.00 | 6.02 | 28.63 | 24.81 | 200 | 0.70 | 0.883 | 22.61 | 78.97% | | | | | | | |
| Essement | EX13 | BLK6145A | MH6146A | 2.50 | | | | | 250.8 | 250.8 | | 4.00 | 4.06 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 2.50 | 2.50 | 0.70 | | | | 0.00 | 4.76 | 21.64 | 22.70 | 200 | 0.40 | 0.667 | 16.88 | 77.99% | | | | | | | |
| Essement | | MH6146A | MH6136A | | | | | | 0.0 | 250.8 | | 4.00 | 4.06 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.00 | 2.50 | 0.70 | | | | 0.00 | 4.76 | 21.64 | 46.46 | 200 | 0.40 | 0.667 | 16.88 | 77.99% | | | | | | | |
| Dun Skipper Road | EX14 | BLK6138A | MH6138A | 0.08 | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 4.07 | 4.07 | 1.14 | | | | 0.00 | 4.67 | 20.24 | 20.00 | 200 | 0.35 | 0.624 | 15.57 | 76.92% | | | | | | | |
| Dun Skipper Road | 6138A | MH6138A | MH6137A | | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 0.08 | 4.15 | 1.16 | | | | 0.00 | 4.69 | 20.24 | 32.25 | 200 | 0.35 | 0.624 | 15.55 | 76.81% | | | | | | | |
| Dun Skipper Road | 6137A | MH6137A | MH6136A | 0.10 | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 0.10 | 4.25 | 1.19 | | | | 0.00 | 4.72 | 20.24 | 44.44 | 200 | 0.35 | 0.624 | 15.52 | 76.67% | | | | | | | |
| Cedar Creek Drive | 6136A | MH6136A | MH6121A | 0.04 | | | | | 0.0 | 535.6 | | 3.96 | 8.59 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 0.04 | 11.81 | 3.31 | | | | 0.00 | 15.43 | 20.24 | 28.03 | 20.24 | 200 | 0.35 | 0.624 | 4.81 | 23.79% | | | | | | |
| Cedar Creek Drive | 6121A | MH6121A | MH6120A | 0.03 | | | | | 0.0 | 535.6 | | 3.96 | 8.59 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 0.03 | 11.84 | 3.32 | | | | 0.00 | 15.44 | 20.24 | 12.97 | 23.74% | 0.35 | 0.624 | 4.81 | 23.74% | | | | | | | |
| Cedar Creek Drive | 6120A | MH6120A | MH6119A | 0.10 | | | | | 0.0 | 535.6 | | 3.96 | 8.59 | | 0.00 | | 4.07 | | 0.00 | | 3.53 | 0.10 | 11.94 | 3.34 | | | | 0.00 | 15.47 | 20.24 | 53.29 | 200 | 0.35 | 0.624 | 4.78 | 23.60% | | | | | | | |
| Pingwi Place | 6132Ab | MH6132A | MH6161A | 0.25 | 3 | | | | 9.6 | 9.6 | | 4.00 | 0.16 | | 0.00 | | 0.00 | | 0.00 | | 0.25 | 0.25 | 0.25 | 0.07 | | | | 0.00 | 0.23 | 56.22 | 77.03 | 200 | 2.70 | 1.734 | 56.00 | 99.60% | | | | | | | |
| Pingwi Place | 6161A | MH6161A | MH6162A | 0.22 | 3 | | | | 9.6 | 19.2 | | 4.00 | 0.31 | | 0.00 | | 0.00 | | 0.00 | | 0.22 | 0.42 | 0.13 | 0.00 | | | | 0.00 | 0.44 | 24.19 | 11.41 | 200 | 0.50 | 0.746 | 23.75 | 98.17% | | | | | | | |
| Pingwi Place | 6162A | MH6162A | MH6163A | 0.62 | 14 | | | | 44.8 | 64.0 | | 4.00 | 1.04 | | 0.00 | | 0.00 | | 0.00 | | 0.62 | 1.09 | 0.31 | | | | 0.00 | 1.34 | 20.24 | 74.88 | 200 | 0.35 | 0.624 | 18.90 | 93.37% | | | | | | | | |
| Pingwi Place | 6163A | MH6163A | MH6164A | 0.44 | | | | | 28.8 | 92.8 | | 4.00 | 1.50 | | 0.00 | | 0.00 | | 0.00 | | 0.44 | 1.53 | 0.43 | | | | 0.00 | 1.93 | 20.24 | 86.35 | 200 | 0.35 | 0.624 | 18.31 | 90.46% | | | | | | | | |
| Pingwi Place | 6164A | MH6164A | MH6119A | 0.40 | | | | | 26.4 | 119.2 | | 4.00 | 1.93 | | 0.00 | | 0.00 | | 0.00 | | 0.40 | 1.93 | 0.54 | | | | 0.00 | 2.47 | 29.63 | 86.29 | 200 | 0.75 | 0.914 | 27.16 | 91.66% | | | | | | | | |
| Block 429 | COM | BLK6119A | MH6119A | | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 0.00 | | 3.01 | | 0.00 | | 2.61 | 3.01 | 3.01 | 0.84 | | | | 0.00 | 3.46 | 45.12 | 20.00 | 300 | 0.20 | 0.618 | 41.66 | 92.34% | | | | | | | |
| Cedar Creek Drive | 6119A | MH6119A | MH6118A | 0.05 | | | | | 0.0 | 654.8 | | 3.91 | 10.37 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.05 | 16.93 | 4.74 | | | | 0.00 | 21.26 | 45.12 | 28.01 | 300 | 0.20 | 0.618 | 23.86 | 92.88% | | | | | | | |
| Cedar Creek Drive | 6118A | MH6118A | MH6117A | 0.07 | | | | | 0.0 | 654.8 | | 3.91 | 10.37 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.07 | 17.00 | 4.76 | | | | 0.00 | 21.28 | 45.12 | 33.76 | 300 | 0.20 | 0.618 | 22.84 | 92.83% | | | | | | | |
| Block 443 | HD1 | BLK6117A | MH6117A | 1.03 | | | | | 129.6 | 129.6 | | 4.00 | 2.10 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 1.03 | 1.03 | 0.29 | | | | 0.00 | 2.39 | 20.24 | 20.00 | 200 | 0.35 | 0.624 | 17.85 | 86.20% | | | | | | | |
| Cedar Creek Drive | 6117A | MH6117A | MH6116A | 0.55 | 17 | | | | 40.8 | 825.2 | | 3.85 | 12.88 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.55 | 18.58 | 5.20 | | | | 0.00 | 24.23 | 45.12 | 75.05 | 300 | 0.20 | 0.618 | 20.89 | 46.30% | | | | | | | |
| Cedar Creek Drive | 6116A | MH6116A | MH6115A | 0.52 | 17 | | | | 40.8 | 866.0 | | 3.84 | 13.47 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.52 | 19.10 | 5.35 | | | | 0.00 | 24.96 | 59.68 | 67.16 | 300 | 0.35 | 0.818 | 34.72 | 58.17% | | | | | | | |
| Salamanca Way | 6156Aa | MH6156A | MH6157A | 0.29 | 3 | | | | 9.6 | 9.6 | | 4.00 | 0.16 | | 0.00 | | 0.00 | | 0.00 | | 0.29 | 0.29 | 0.29 | 0.08 | | | | 0.00 | 0.24 | 31.55 | 74.63 | 200 | 0.85 | 0.973 | 31.31 | 99.25% | | | | | | | |
| Salamanca Way | 6157A | MH6157A | MH6158A | 0.07 | | | | | 2.4 | 12.0 | | 4.00 | 0.19 | | 0.00 | | 0.00 | | 0.00 | | 0.07 | 0.36 | 0.10 | | | | 0.00 | 0.30 | 34.22 | 12.28 | 200 | 1.00 | 1.055 | 33.92 | 99.14% | | | | | | | | |
| Salamanca Way | 6158A | MH6158A | MH6153A | 0.54 | | | | | 33.6 | 45.6 | | 4.00 | 0.74 | | 0.00 | | 0.00 | | 0.00 | | 0.54 | 0.90 | 0.25 | | | | 0.00 | 0.99 | 56.22 | 106.46 | 200 | 2.70 | 1.734 | 55.23 | 98.24% | | | | | | | | |
| Block 436 | PARK | BLK6153C | MH6153A | | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.83 | 0.83 | 0.23 | | | | 0.00 | 0.23 | 24.19 | 13.25 | 200 | 0.50 | 0.746 | 23.96 | 99.04% | | | | | | | |
| Salamanca Way | 6153A | MH6153A | MH6154A | 0.03 | | | | | 0.0 | 45.6 | | 4.00 | 0.74 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.03 | 1.76 | 0.49 | | | | 0.00 | 1.23 | 28.63 | 10.53 | 200 | 0.70 | 0.883 | 27.40 | 95.70% | | | | | | | |
| Salamanca Way | 6154A | MH6154A | MH6115A | 0.13 | | | | | 0.0 | 45.6 | | 4.00 | 0.74 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.13 | 1.89 | 0.53 | | | | 0.00 | 1.27 | 24.19 | 76.18 | 200 | 0.50 | 0.746 | 22.93 | 94.76% | | | | | | | |
| Cedar Creek Drive | 6115A | MH6115A | MH6101A | 0.61 | 18 | | | | 43.2 | 954.8 | | 3.81 | 14.75 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.61 | 21.60 | 6.05 | | | | 0.00 | 26.94 | 59.68 | 87.15 | 300 | 0.35 | 0.818 | 32.74 | 54.86% | | | | | | | |
| Miliana Road | 6101A | MH6101A | MH6102A | 0.45 | 11 | | | | 26.4 | 981.2 | | 3.81 | 15.13 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.45 | 22.05 | 6.17 | | | | 0.00 | 27.45 | 59.68 | 91.17 | 300 | 0.35 | 0.818 | 32.24 | 54.01% | | | | | | | |
| Block 436 | HD2 | BLK6102AS | MH6102A | 0.94 | | | | | 115.2 | 115.2 | | 4.00 | 1.87 | | 0.00 | | 0.00 | | 0.00 | | 0.00 | 0.94 | 0.94 | 0.26 | | | | 0.00 | 2.13 | 20.24 | 20.00 | 200 | 0.35 | 0.624 | 18.11 | 89.48% | | | | | | | |
| Miliana Road | 6102A | MH6102A | MH6103A | 0.23 | | | | | 14.4 | 1110.8 | | 3.77 | 16.96 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.23 | 23.22 | 6.50 | | | | 0.00 | 29.61 | 59.68 | 41.44 | 300 | 0.35 | 0.818 | 30.07 | 50.38% | | | | | | | |
| Miliana Road | 6103A | MH6103A | MH6104A | 0.66 | | | | | 43.2 | 1154.0 | | 3.76 | 17.57 | | 0.00 | | 7.08 | | 0.00 | | 6.15 | 0.66 | 23.86 | 6.69 | | | | 0.00 | 30.40 | 59.68 | 120.00 | 300 | 0.35 | 0.818 | 29.28 | 49.06% | | | | | | | |
| Block 450 | INST | BLK6104AS | MH6104A | | | | | | 0.0 | 0.0 | | 4.00 | 0.00 | | 2.55 | | 0.00 | | 0.00 | | 2.21 | 2.55 | 0.71 | | | | 0.00 | 2.93 | 20.24 | 20.00 | 200 | 0.35 | 0.624 | 17.32 | 85.54% | | | | | | | | |
| Miliana Road | 6104A | MH6104A | MH6105B | 0.60 | | | | | 36.0 | 1190.0 | | 3.75 | 18.08 | | 2.55 | | 7.08 | | 0.00 | | 8.36 | 0.60 | 27.03 | 7.57 | | | | 0.00 | 34.01 | 59.68 | 114.40 | 300 | 0.35 | 0.818 | 26.68 | 43.02% | | | | | | | |
| Miliana Road | MH6105B | EX. MH647A | EX. MH647A | | | | | | 0.0 | 1190.0 | | 3.75 | 18.08 | | 2.55 | | 7.08 | | 0.00 | | 8.36 | 0.00 | 27.03 | 7.57 | | | | 0.00 | 34.01 | 45.12 | 8.00 | 300 | 0.20 | 0.618 | 11.11 | 24.63% | | | | | | | |
| Kelly Farm Drive | EX. MH647A | EX. MH742A | | 0.28 | | | | | 12.0 | 3587.6 | | 3.38 | 49.05 | | 2.55 | | 7.08 | | 0.00 | | 8.36 | 0.28 | 75.56 | 21.16 | | | | 0.00 | 78.57 | 101.84 | 80.31 | 375 | 0.37 | 0.893 | 23.27 | 22.85% | | | | | | | |
| Design Parameters: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Residential | ICI Areas | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SF 3.2 | pipu | INST 50,000 | U/h/day | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| THSD 2.4 | pipu | COM 50,000 | U/h/day | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| API 1.9 | pipu | IND 35,00 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

J:\33956-Remediation\5.9 Drawings\33956\501A EXTERNAL SANITARY DRAINAGE AREA PLAN.dwg Printed At: 8/11/2017 2:10 PM Last Saved By: DDOE Last Saved At: Aug. 11, 17



REVIEWED BY
DEVELOPMENT REVIEW SERVICES BRANCH

Signed _____

Date _____ 2017

Plan Number _____

LEGEND :

EXT3

2.50250.8

AREA NUMBER

RUNOFF COEFFICIENT

AREA IN HECTARES

FUTURE FLOW DIRECTION

| | | | |
|-----|---|--------|------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | REVISED BLOCK NUMBERS | J.I.M. | 2017.08.11 |
| 4 | RE-SUBMISSION FOR MOECC APPROVAL & REVISED STREET NAMES | J.I.M. | 2017.08.02 |
| 3 | SUBMISSION FOR MOECC APPROVAL | J.I.M. | 2017.07.07 |
| 2 | SUBMISSION No.2 FOR CITY REVIEW | J.I.M. | 2017.05.12 |
| 1 | SUBMISSION No.1 FOR CITY REVIEW | J.I.M. | 2016.11.23 |
| No. | REVISIONS | By | Date |

LEITRIM SOUTH HOLDINGS INC.

IBI

IBI GROUP
400 - 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

Project Title

pathways

at FINDLAY CREEK

LICENSÉ PROFESSIONNEL
J. I. MOFFATT
2017/08/02
PROVINCE OF ONTARIO

Drawing Title

EXTERNAL SANITARY DRAINAGE AREA PLAN

Scale

1 : 1000



| | | | |
|-------------|--------|-------------|----------|
| Design | J.I.M. | Date | NOV 2016 |
| Drawn | D.D. | Checked | ---- |
| Project No. | 33956 | Drawing No. | 501A |



4836 Bank Street
CITY OF OTTAWA
Home Hardware

J:\119351_4836BankSt\5.7 Calculations\5.7.1 Sewers & Grading\CCS_SanitarySewer Design_2019-04-15

\\11351_4338\dwg\53.9 Drawing\Sanitary\Area\119351-0001.dwg Plot Size: 125.4 Printed At: 4/27/2020 2:47 PM Last Saved By: Janna.Bellison Last Saved At: Dec. 6, 19



KEY PLAN
(NTS)

- NOTES:
- SEE DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.
 - SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR H.A. KEN SHIPMAN SURVEYING LTD.

- LEGEND :
- 6115A
0.81/43.2
EXISTING AREA NUMBER
EXISTING POPULATION
EXISTING AREA IN HECTARES
 - FUTURE FLOW DIRECTION
 - MH2A
0.37
EXISTING AREA NUMBER
EXISTING AREA IN HECTARES
 - MH2A
0.37
AREA NUMBER
AREA IN HECTARES

| | | | |
|-----|--|-----|------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | | | |
| 4 | REVISED AS PER CITY COMMENTS | JIM | 2020-04-20 |
| 3 | REVISED AS PER CITY COMMENTS | JIM | 2019-12-09 |
| 2 | REVISED AS PER NEW SITE PLAN AND CITY COMMENTS | JIM | 2019-10-11 |
| 1 | ISSUED FOR SPA | JIM | 2019-04-15 |
| No. | REVISIONS | By | Date |

IBI GROUP
400 – 333 Preston Street
Oshawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

Project Title

**BANK STREET
DEVELOPMENT**
4836 BANK STREET

Drawing Title

**SANITARY DRAINAGE
AREA PLAN**

Scale
1 : 500

| | | | |
|-------------|--------|-------------|-----------|
| Design | SEL | Date | FEB. 2019 |
| Drawn | DPS | Checked | JIM |
| Project No. | 119351 | Drawing No. | 400 |

APPENDIX D

- **Pathways Phase 1 Storm Sewer Design Sheet**
- **Drawing 33956-500A – Pathways Phase 1 External Storm Drainage Area Plan**
- **Drawing 33956-700 – DDSWMM Schematic from Pathways Phase 1**
- **Excerpts from Design Brief Pathways at Findlay Creek 4800 Bank Street (Remer Lands) Phase 1 Leitrim Development Area (IBI Group, August 2017)**
- **Storm Sewer Design Sheet**
- **Drawing 119351-500 – Storm Drainage Area Plan**

LEITRIM
WETLAND

PHASE 4B AND 4C

LEGEND:

- PHASE 1 EAST DRAINAGE AREA
MODELED IN DDSWMM
- PHASE 1 WEST DRAINAGE AREA
MODELED IN DDSWMM
- FUTURE DRAINAGE AREA
MODELED IN DDSWMM
- PHASE 1 DRAINAGE BOUNDARY
- DDSWMM MODELS DRAINAGE BOUNDARIES
- SUBCATCHMENT DRAINAGE BOUNDARY
- AREA ID
Imp. (%)/To (ft)
AREA (ha)
- MAJOR FLOW
- MAJOR FLOW TO WETLAND


| | | | |
|-----|--|------|-------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | REVISED BLOCK NUMBERS | D.D. | 2017: 08:11 |
| 4 | RE-SUBMISSION FOR MOECC APPROVAL & REVISED STREET NAMES | R.B. | 2017: 08:02 |
| 3 | SUBMISSION FOR MOECC APPROVAL | R.B. | 2017: 07:07 |
| 2 | SUBMISSION NO.2 FOR CITY REVIEW | R.B. | 2017: 05:12 |
| 1 | SUBMISSION NO.1 FOR CITY REVIEW | R.B. | 2016: 11:23 |
| No. | REVISIONS | By | Date |

LEITRIM SOUTH
HOLDINGS INC.

IBI GROUP
400 - 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

Project Title

pathways
at FINDLAY CREEK



Drawing Title

DDSWMM SCHEMATIC

Scale

1:1500

| | | | |
|-------------|-------|-------------|----------|
| Design | R.B. | Date | NOV 2016 |
| Drawn | J.F. | Checked | R.B. |
| Project No. | 33956 | Drawing No. | 700 |

EXT 1

RUNOFF COEFFICIENT

AREA IN HECTARES

UTURE MINOR
LOW DIRECTION



| | | | |
|-----|---|--------|------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | REVISED BLOCK NUMBERS | J.I.M. | 2017:08:11 |
| 4 | RE-SUBMISSION FOR MOECC APPROVAL & REVISED STREET NAMES | J.I.M. | 2017:08:02 |
| 3 | SUBMISSION FOR MOECC APPROVAL | J.I.M. | 2017:07:07 |
| 2 | SUBMISSION No.2 FOR CITY REVIEW | J.I.M. | 2017:05:12 |
| 1 | SUBMISSION No.1 FOR CITY REVIEW | J.I.M. | 2016:11:23 |
| No. | REVISIONS | By | Date |

LEITRIM SOUTH
HOLDINGS INC.





BI GROUP
400 – 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
bigroup.com

Project Title



pathways
at FINDLAY CREEK



Drawing Title

EXTERNAL STORM DRAINAGE AREA PLAN

ale

: 2000

sign

J.I.M.

NOV 2016

awn
B.D.

cked

Project No.

wing No

33956

00A



REPORT
Project: 33956-5.2.2

DESIGN BRIEF
PATHWAYS AT FINDLAY CREEK
4800 BANK STREET
(REMER LANDS)
PHASE 1
LEITRIM DEVELOPMENT AREA



Prepared for LEITRIM SOUTH HOLDINGS INC.
by IBI GROUP

REVISED: AUGUST, 2017

was not accounted for as available on-site storage. Inlet restriction was also proposed for rear yards and overflow from the rear yards cascades to a major system street segment via swales.

Major System Storage Attenuation and Routing (Double Routing)

For street segments, the cascading overflow to the next segment or low point, utilizes the static storage available plus an additional amount of storage equivalent to the depth required for the flow to carry over the high point. The attenuation in street sags was evaluated to account for static storage and, if overflow occurs, dynamic storage. Within this report it is referred to as double routing.

The DDSWMM model does not have a direct way of coding double routing since it does not allow the user to code dynamic storage over the high point. For this analysis, an alternative method was employed where the overflow from a street segment (regular static storage at a sag) is conveyed to a dummy segment. In other words, a regular low point segment was provided with a downstream dummy segment for further flow attenuation to account for the dynamic ponding during overflow.

The dummy segment does not have any drainage area attributes associated with it since it is a segment for routing. In addition, there is no inflow to the minor system from these dummy segments. The overflow hydrograph from the upstream catchment is routed in the dummy segment to the next "real" downstream segment. The dummy segments have specific characteristics which are noted below:

- Segment Length – equivalent to length of maximum static storage from the street segment contributing to it.
- Road Type – equivalent to appropriate right-of-way characteristics from the segment contributing to it, and with a minimum longitudinal slope of 0.01% (0.0001 m/m).

The double routing method noted above applied to DDSWMM, is a feasible method outlined in the February 2014 Technical Bulletin ISDTB 2014-01.

The dummy segments for major system routing were applied to the analysis of the subject site. The segments are referenced as D1, D2, D3, etc. within the DDSWMM modelling file. The DDSWMM schematic presented in **Drawing 700** does not show the dummy segments, but DDSWMM computer output file shows the dummy segments immediately following the corresponding major segment which cascades into that dummy segment.

Future Lands

In addition to the above noted assumptions with respect to Phase 1 Pathways at Findlay Creek, the following assumptions were used to model the minor and major system flow from the future areas which are tributary to and contribute flow (minor and major) to the subject site. A summary of the areas, storages, inflows and parameter assumptions are provided in **Table 4.4**.

- **Commercial Sites (DDSWMM ID: COM and EXT4)**

These commercial areas were assumed to be restricted to the 5 year modeled flow. It was also assumed that full on-site storage will be provided in both sites (all major flow contained on-site up to and including the 100 year event). Emergency overflow for both sites will be routed to Bank Street (DDSWMM ID BANK).

† Pathways at Findlay Creek Phase 1 West modeled flow is from the DDSWMM output file 33956-PH1W-3CHI2.out, 33956-PH1W-3CHI5.out and 33956-PH1W-3CHI100.out which are all presented on the CD in **Appendix E**.

The assigned size of the inlet control devices (ICDs) for the subject site was optimized using DDSWMM. ICDs are incorporated into the stormwater management design to protect the minor system from surcharge during major storm events. The ICDs used for Phase 1 are provided on **Drawing 010**. It should be noted that due to the increased minor system capture at low points flow, there were a few instances where the flow restriction into the minor system was the capacity of the CB inlet. These include one CB on S6115B, one CB on S6183A, one CB on S6107 (indicated in bold in **Table 4.4**). Calculations demonstrating the capacity of the CBs within a road sag is presented in **Appendix E**. In addition, there are two instances where the CB lead is the restriction for the inflow to the minor system. These include S6115B and S6155B. Calculations supporting the lead size for the inflow restriction are provided in **Appendix E**.

For those areas within Phase 1 which will require a separate site stormwater design and analysis, the following table summarizes the assumed inflow rate and minimum on-site storage required for their design.

Table 4.5 Summary of Minimum On-Site Storage and Minor System Inflow Rate for External Development Lands to Phase 1

| Drainage Area | | Land Use | IMP Ratio (%) | Minimum On-Site Storage Required (m ³)* | Minor System Inflow Rate (l/s) |
|---------------|-----------|--------------|---------------|---|--------------------------------|
| Segment ID | Area (ha) | | | | |
| EXT3 | 2.50 | High Density | 79 | 125.00 | 469 |
| HD1 | 1.02 | High Density | 86 | 100.00 | 206 |
| PARK1 | 0.83 | Park | 14 | 150.00 | 38 |
| HD2 | 0.94 | High Density | 86 | 115.00 | 190 |
| INST | 2.55 | School | 79 | 290.00 | 476 |
| EXT4 | 4.06 | Commercial | 79 | 462.00 | 760 |
| COM | 3.01 | Commercial | 79 | 345.00 | 562 |

* The on-site storage noted was used to evaluate Phase 1. As a minimum this on-site storage should be provided.

4.9.3 Simulation Results

Minor system hydrographs generated in DDSWMM were downloaded to the XPSWMM model for hydraulic grade line analysis (refer to **Section 4.10**).

The storage available on-site and its maximum depth and the results of the DDSWMM evaluation for the subject site are presented in **Table 4.6**. Also included in **Table 4.6**, is the duration of ponding and depth of ponding for the 2 year, 5 year, 100 year and July 1, 1979 historical storm events. The ponding plan for the subject site is presented on **Drawing 751**. The DDSWMM output files are presented in **Appendix E**.





IBI GROUP
400-333 Preston Street
Ottawa, Ontario K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

STORM SEWER DESIGN SHEET

4836 Bank Street
City of Ottawa
Home Hardware

| LOCATION | | | | AREA (Ha) | | | | | | | | | | RATIONAL DESIGN FLOW | | | | | | | | | | | | | | SEWER DATA | | | | | | | | | | | | | |
|------------------|---------|--------|-------------|-----------|------|------|------|------|------|------|------|------|------|----------------------|--------|-------|---------|-------|---------|---------|---------|---------|------------|------------|------------|------------|------------|------------|----------|--------|----------------|--------|--------|-------|----------|-----------------|--------|-------|-------|-------|--------|
| STREET | AREA ID | FROM | TO | C= | C= | C= | C= | C= | C= | C= | C= | C= | C= | IND | CUM | INLET | TIME | TOTAL | i (2) | i (5) | i (10) | i (100) | 2yr PEAK | 5yr PEAK | 10yr PEAK | 100yr PEAK | FIXED | DESIGN | CAPACITY | LENGTH | PIPE SIZE (mm) | | | SLOPE | VELOCITY | AVAIL CAP (2yr) | | | | | |
| | | | | 0.20 | 0.30 | 0.40 | 0.50 | 0.55 | 0.65 | 0.70 | 0.75 | 0.90 | 1.00 | 2.78AC | 2.78AC | (min) | IN PIPE | (min) | (mm/hr) | (mm/hr) | (mm/hr) | (mm/hr) | FLOW (L/s) | FLOW (L/s) | FLOW (L/s) | FLOW (L/s) | FLOW (L/s) | FLOW (L/s) | (L/s) | (m) | DIA | W | H | (%) | (m/s) | (L/s) | (%) | | | | |
| | | CB3 | MH9-MH8 | | | | | | | | | | 0.12 | | | | | 0.25 | 0.25 | 10.00 | 0.11 | 10.11 | 76.81 | 104.19 | 122.14 | 178.56 | 19.22 | 26.07 | 30.56 | 44.68 | | 19.22 | 34.22 | 6.73 | 200 | | | 1.00 | 1.055 | 15.00 | 43.84% |
| | | CB2 | MH9-MH8 | | | | | | | | | | | 0.05 | 0.05 | 10.00 | 0.12 | 10.12 | 76.81 | 104.19 | 122.14 | 178.56 | 3.84 | 5.21 | 6.11 | 8.94 | | 3.84 | 34.22 | 7.69 | 200 | | | 1.00 | 1.055 | 30.37 | 88.77% | | | | |
| | | MH9 | MH8 | | | | | | | | | | | 0.00 | 0.30 | 10.12 | 0.64 | 10.76 | 76.34 | 103.56 | 121.39 | 177.46 | 22.92 | 31.09 | 36.45 | 53.28 | | 22.92 | 158.41 | 53.17 | 375 | | | 0.75 | 1.389 | 135.48 | 85.53% | | | | |
| | | CB1 | MH8-MH7 | | | | | | | | | | 0.17 | | | | | 0.35 | 0.35 | 10.00 | 0.17 | 10.17 | 76.81 | 104.19 | 122.14 | 178.56 | 27.22 | 36.93 | 43.29 | 63.29 | | 27.22 | 34.22 | 10.80 | 200 | | | 1.00 | 1.055 | 6.99 | 20.44% |
| | | MH8 | MH7 | | | | | | | | | | | 0.00 | 0.65 | 10.76 | 0.41 | 11.17 | 74.01 | 100.35 | 117.61 | 171.90 | 48.45 | 65.70 | 77.00 | 112.54 | | 48.45 | 53.73 | 26.20 | 250 | | | 0.75 | 1.060 | 5.28 | 9.82% | | | | |
| | | BLDG D | MH7-MH5 | | | | | | | | | | | 0.13 | 0.13 | 10.00 | 0.20 | 10.20 | 76.81 | 104.19 | 122.14 | 178.56 | 9.61 | 13.03 | 15.28 | 22.34 | | 9.61 | 34.22 | 12.60 | 200 | | | 1.00 | 1.055 | 24.61 | 71.92% | | | | |
| | | BLDG A | MH7-MH5 | | | | | | | | | | | 0.30 | 0.75 | 0.75 | 10.00 | 0.18 | 10.18 | 76.81 | 104.19 | 122.14 | 178.56 | 57.65 | 78.21 | 91.68 | 134.03 | | 57.65 | 62.04 | 12.97 | 250 | | | 1.00 | 1.224 | 4.39 | 7.07% | | | |
| | | MH7 | MH5 | | | | | | | | | | | 0.00 | 1.53 | 11.17 | 0.46 | 11.63 | 72.58 | 98.39 | 115.31 | 168.52 | 111.08 | 150.57 | 176.46 | 257.90 | | 111.08 | 230.39 | 38.63 | 450 | | | 0.60 | 1.403 | 119.31 | 51.79% | | | | |
| | | CB4 | MH10-CBMH1 | | | | | | | | | | 0.03 | | | | | 0.08 | 0.08 | 10.00 | 0.12 | 10.12 | 76.81 | 104.19 | 122.14 | 178.56 | 5.76 | 7.82 | 9.17 | 13.40 | | 5.76 | 34.22 | 7.78 | 200 | | | 1.00 | 1.055 | 28.45 | 83.15% |
| | | MH10 | CBMH1 | | | | | | | | | | | 0.00 | 0.08 | 10.12 | 0.73 | 10.85 | 76.34 | 103.55 | 121.38 | 177.44 | 5.73 | 7.77 | 9.11 | 13.32 | | 5.73 | 48.06 | 41.57 | 250 | | | 0.60 | 0.948 | 42.33 | 88.08% | | | | |
| | | CB5 | CBMH1-CBMH2 | | | | | | | | | | 0.06 | | | | | 0.15 | 0.15 | 10.00 | 0.36 | 10.36 | 76.81 | 104.19 | 122.14 | 178.56 | 11.53 | 15.64 | 18.34 | 26.81 | | 11.53 | 34.22 | 22.72 | 200 | | | 1.00 | 1.055 | 22.69 | 66.30% |
| | | CB6 | CBMH1-CBMH2 | | | | | | | | | | 0.07 | | | | | 0.18 | 0.18 | 10.00 | 0.15 | 10.15 | 76.81 | 104.19 | 122.14 | 178.56 | 13.45 | 18.25 | 21.39 | 31.27 | | 13.45 | 34.22 | 9.78 | 200 | | | 1.00 | 1.055 | 20.76 | 60.69% |
| | | CB7 | CBMH1-CBMH2 | | | | | | | | | | 0.08 | | | | | 0.20 | 0.20 | 10.00 | 0.15 | 10.15 | 76.81 | 104.19 | 122.14 | 178.56 | 15.37 | 20.86 | 24.45 | 35.74 | | 15.37 | 34.22 | 9.59 | 200 | | | 1.00 | 1.055 | 18.84 | 55.07% |
| | | CBMH1 | CBMH2 | | | | | | | | | | 0.08 | | | | | 0.20 | 0.80 | 10.85 | 0.80 | 11.66 | 73.68 | 99.89 | 117.07 | 171.12 | 58.99 | 79.98 | 93.73 | 137.00 | | 58.99 | 66.53 | 63.40 | 250 | | | 1.15 | 1.313 | 7.54 | 11.33% |
| | | CBMH2 | MH4 | | | | | | | | | | | 0.00 | 0.80 | 11.66 | 0.68 | 12.33 | 70.98 | 96.18 | 112.71 | 164.70 | 56.83 | 77.01 | 90.24 | 131.87 | | 56.83 | 59.68 | 33.14 | 300 | | | 0.35 | 0.818 | 2.86 | 4.79% | | | | |
| | | CB9 | MH1-MH2 | | | | | | | | | | 0.15 | | | | | 0.38 | 0.38 | 10.00 | 0.28 | 10.28 | 76.81 | 104.19 | 122.14 | 178.56 | 28.82 | 39.10 | 45.84 | 67.01 | | 28.82 | 34.22 | 17.68 | 200 | | | 1.00 | 1.055 | 5.39 | 15.76% |
| | | CB8 | MH1-MH2 | | | | | | | | | | 0.17 | | | | | 0.43 | 0.43 | 10.00 | 0.24 | 10.24 | 76.81 | 104.19 | 122.14 | 178.56 | 32.67 | 44.32 | 51.95 | 75.95 | | 32.67 | 34.22 | 14.99 | 200 | | | 1.00 | 1.055 | 1.55 | 4.53% |
| | | BLDG C | MH1-MH2 | | | | | | | | | | 0.05 | | | | | 0.13 | 0.13 | 10.00 | 0.22 | 10.22 | 76.81 | 104.19 | 122.14 | 178.56 | 9.61 | 13.03 | 15.28 | 22.34 | | 9.61 | 34.22 | 14.20 | 200 | | | 1.00 | 1.055 | 24.61 | 71.92% |
| | | CB10 | MH1-MH2 | | | | | | | | | | 0.13 | | | | | 0.33 | 0.33 | 10.00 | 0.27 | 10.27 | 76.81 | 104.19 | 122.14 | 178.56 | 24.98 | 33.89 | 39.73 | 58.08 | | 24.98 | 34.22 | 17.04 | 200 | | | 1.00 | 1.055 | 9.23 | 26.99% |
| | | CB11 | MH1-MH2 | | | | | | | | | | 0.03 | | | | | 0.08 | 0.08 | 10.00 | 0.11 | 10.11 | 76.81 | 104.19 | 122.14 | 178.56 | 5.76 | 7.82 | 9.17 | 13.40 | | 5.76 | 34.22 | 6.75 | 200 | | | 1.00 | 1.055 | 28.45 | 83.15% |
| | | CB12 | CB13 | | | | | | | | | | 0.06 | | | | | 0.15 | 0.15 | 10.00 | 0.18 | 10.18 | 76.81 | 104.19 | 122.14 | 178.56 | 11.53 | 15.64 | 18.34 | 26.81 | | 11.53 | 34.22 | 11.50 | 200 | | | 1.00 | 1.055 | 22.69 | 66.30% |
| Idone Commercial | | MH1 | MH2 | | | | | | | | | 1.58 | | | | | | 3.29 | 4.77 | 10.28 | 0.87 | 11.15 | 75.75 | 102.74 | 120.43 | 176.05 | 361.36 | 490.12 | 574.51 | 839.82 | | 361.36 | 452.94 | 81.04 | 600 | | | 0.50 | 1.552 | 91.59 | 20.22% |
| | | CB13 | MH2-MH3 | | | | | | | | | | 0.18 | | | | | 0.45 | 0.45 | 10.00 | 0.01 | 10.01 | 76.81 | 104.19 | 122.14 | 178.56 | 34.59 | 46.92 | 55.01 | 80.42 | | 34.59 | 40.49 | 1.00 | 200 | | | 1.40 | 1.248 | 5.90 | 14.56% |
| | | BLDG B | MH2-MH3 | | | | | | | | | | 0.22 | | | | | 0.55 | 0.55 | 10.00 | 0.26 | 10.26 | 76.81 | 104.19 | 122.14 | 178.56 | 42.28 | 57.35 | 67.23 | 98.29 | | 42.28 | 62.04 | 19.00 | 250 | | | 1.00 | 1.224 | 19.76 | 31.85% |
| | | MH2 | MH3 | | | | | | | | | | | 0.00 | 5.77 | 11.15 | 0.14 | 11.29 | 72.66 | 98.49 | 115.42 | 168.69 | 419.32 | 568.41 | 666.14 | 973.56 | | 419.32 | 480.32 | 10.88 | 675 | | | 0.30 | 1.300 | 61.00 | 12.70% | | | | |
| | | CB14 | MH3-MH4 | | | | | | | | | | 0.15 | | | | | 0.38 | 0.38 | 10.00 | 0.03 | 10.03 | 76.81 | 104.19 | 122.14 | 178.56 | 28.82 | 39.10 | 45.84 | 67.01 | | 28.82 | 34.22 | 1.63 | 200 | | | 1.00 | 1.055 | 5.39 | 15.76% |
| | | CB15 | CBMH3 | | | | | | | | | 0.09 | | | | | | 0.19 | 0.19 | 10.00 | 0.31 | 10.31 | 76.81 | 104.19 | 122.14 | 178.56 | 14.41 | 19.55 | 22.92 | 33.51 | | 14.41 | 34.22 | 19.85 | 200 | | | 1.00 | 1.055 | 19.80 | 57.88% |
| | | CB18 | MH11 | | | 0.16 | | | | | | | | 0.13 | 0.13 | 10.00 | 0.27 | 10.27 | 76.81 | 104.19 | 122.14 | 178.56 | 10.25 | 13.90 | 16.30 | 23.83 | | 10.25 | 27.59 | 13.80 | 200 | | | 0.65 | 0.851 | 17.34 | 62.85% | | | | |
| | | MH11 | CBMH3 | | | | | | | | | | | 0.00 | 0.13 | 10.27 | 0.34 | 10.61 | 75.78 | 102.79 | 120.48 | 176.12 | 10.11 | 13.72 | 16.08 | 23.50 | | 10.11 | 27.59 | 17.50 | 200 | | | 0.65 | 0.851 | 17.47 | 63.34% | | | | |
| | | CBMH3 | MH3-MH4 | | | | | | | | | 0.02 | | | | | | 0.04 | 0.36 | 10.31 | 0.35 | 10.67 | 75.62 | 102.57 | 120.22 | 175.74 | 27.01 | 36.64 | 42.95 | 62.78 | | 27.01 | 27.59 | 17.94 | 200 | | | 0.65 | 0.851 | 0.57 | 2.07% |
| | | MH3 | MH4 | | | | | | | | | | | 0.00 | 6.50 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | |



KEY PLAN
(NTS)

- NOTES:
- SEE DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.
 - SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR H.A. KEN SHIPMAN SURVEYING LTD.

LEGEND:

| | |
|--|--|
| | DRAINAGE AREA LIMITS |
| | AREA ID RUNOFF COEFFICIENT AREA IN HECTARES |
| | EXISTING AREA ID EXISTING RUNOFF COEFFICIENT EXISTING AREA IN HECTARES |

| | | | |
|-----|--|-----|------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | REVISED AS PER CITY COMMENTS | JIM | 2020-04-20 |
| 4 | REVISED AS PER CITY COMMENTS | JIM | 2020-04-03 |
| 3 | REVISED AS PER NEW SITE PLAN AND CITY COMMENTS | JIM | 2019-12-09 |
| 2 | REVISED AS PER NEW SITE PLAN AND CITY COMMENTS | JIM | 2019-10-11 |
| 1 | ISSUED FOR SPA | JIM | 2019-04-15 |
| No. | REVISIONS | By | Date |

IBI GROUP
400 - 333 Preston Street
Ottawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

Project Title

BANK STREET DEVELOPMENT
4836 BANK STREET

Drawing Title


STORM DRAINAGE AREA PLAN

Scale

1 : 500

| | | | |
|-------------|--------|-------------|-----------|
| Design | SEL | Date | FEB. 2019 |
| Drawn | DPS | Checked | JIM |
| Project No. | 119351 | Drawing No. | 500 |

Chart 3: HF & MHF Preset Flow Curves



APPENDIX E

- **Stormwater Management Calculations**



IBI GROUP
333 PRESTON STREET
OTTAWA, ON
K1S 5N4

PROJECT: 4836 Bank St
DATE: 2019-10-08
FILE: 119351.5.7
REV #:
DESIGNED BY: JEB
CHECKED BY: JM

STORMWATER MANAGEMENT

Formulas and Descriptions

$i_{2yr} = 1:2 \text{ year Intensity} = 732.951 / (T_c + 6.199)^{0.810}$
 $i_{5yr} = 1:5 \text{ year Intensity} = 998.071 / (T_c + 6.053)^{0.814}$
 $i_{100yr} = 1:100 \text{ year Intensity} = 1735.688 / (T_c + 6.014)^{0.820}$
 T_c = Time of Concentration (min)
 C = Average Runoff Coefficient
 A = Area (Ha)
 Q = Flow = $2.78CiA$ (L/s)

Maximum Allowable Release Rate

Restricted Flowrate

Taken from City of Ottawa approved Design Brief "Pathways at Findlay Creek" (D07-16-13-0023) drainage area EXT 4

EXT 4 Release Rate 760.00 L/s
Area EXT 4 TOTAL = 4.04 Ha
Area Subject Lands 2.49
Percentage Share of release rate 62%

Q TOTAL = 468.42 L/s

Uncontrolled Release ($Q_{uncontrolled} = 2.78 \cdot C \cdot i_{100yr} \cdot A_{uncontrolled}$)

C = 0.625
 T_c = 10 min
 i_{100yr} = 178.56 mm/hr
 $A_{uncontrolled}$ = 0.01 Ha

Q uncontrolled = 3.10 L/s

Maximum Allowable Release Rate ($Q_{max \text{ allowable}} = Q_{restricted} - Q_{uncontrolled}$)

Q max allowable = 465.31 L/s

MODIFIED RATIONAL METHOD (100-Year & 5-Year Ponding)

Drainage Area MH9/MH9B

Area (Ha) 0.14
C = 0.98 Restricted Flow Q_r (L/s)= 10.00

| 100-Year Ponding | | | | | |
|----------------------------|--------------------------|---|----------------|----------------------|------------------------------|
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p = 2.78 \times C \times i_{100yr} \times A$ (L/s) | Q_r (L/s) | $Q_p - Q_r$ (L/s) | Volume 100yr (m^3) |
| 30 | 91.87 | 34.86 | 10.00 | 24.86 | 44.75 |
| 32 | 87.89 | 33.35 | 10.00 | 23.35 | 44.83 |
| 33 | 86.03 | 32.65 | 10.00 | 22.65 | 44.84 |
| 34 | 84.27 | 31.98 | 10.00 | 21.98 | 44.83 |
| 36 | 80.96 | 30.72 | 10.00 | 20.72 | 44.76 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 44.84 | 20.64 | 10.07 | 14.13 |

| Length (m) | Dia (m) | Area (m^2) | Volume (m^3) |
|------------|---------|----------------|------------------|
| 54.91 | 0.375 | 0.110 | 6.06 |
| 6.73 | 0.200 | 0.031 | 0.21 |
| 7.69 | 0.200 | 0.031 | 0.24 |
| | | | 6.51 |

Drainage Area MH9/MH9B

Area (Ha) 0.14
C = 0.78 Restricted Flow Q_r (L/s)= 10.00

| 5-Year Ponding | | | | | |
|----------------------------|------------------------|---|----------------|----------------------|----------------------------|
| T_c Variable (min) | i_{5yr} (mm/hour) | Peak Flow $Q_p = 2.78 \times C \times i_{5yr} \times A$ (L/s) | Q_r (L/s) | $Q_p - Q_r$ (L/s) | Volume 5yr (m^3) |
| 13 | 90.63 | 27.51 | 10.00 | 17.51 | 13.66 |
| 15 | 83.56 | 25.37 | 10.00 | 15.37 | 13.83 |
| 16 | 80.46 | 24.43 | 10.00 | 14.43 | 13.85 |
| 17 | 77.61 | 23.56 | 10.00 | 13.56 | 13.83 |
| 19 | 72.53 | 22.02 | 10.00 | 12.02 | 13.70 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 13.85 | 20.64 | 10.07 | 0.00 |

| Structure | Depth | Area (m^2) | Volume (m^3) |
|-----------------------|-------|----------------|------------------|
| CB3 (600mm x 600mm) | 1.80 | 0.36 | 0.65 |
| CB2 (600mm x 600mm) | 1.80 | 0.36 | 0.65 |
| CBMH10 (1200mm round) | 2.00 | 1.13 | 2.26 |
| | | | 3.56 |

overflows to: CB1

Drainage Area MH9/MH9B

Area (Ha) 0.140
C = 0.78 Restricted Flow Q_r (L/s)= 10.00

| 2-Year Ponding | | | | | |
|----------------------------|------------------------|---|----------------|----------------------|----------------------------|
| T_c Variable (min) | i_{2yr} (mm/hour) | Peak Flow $Q_p = 2.78 \times C \times i_{2yr} \times A$ (L/s) | Q_r (L/s) | $Q_p - Q_r$ (L/s) | Volume 2yr (m^3) |
| 10 | 76.81 | 23.32 | 10.00 | 13.32 | 7.99 |
| 11 | 73.17 | 22.21 | 10.00 | 12.21 | 8.06 |
| 12 | 69.89 | 21.22 | 10.00 | 11.22 | 8.08 |
| 13 | 66.93 | 20.32 | 10.00 | 10.32 | 8.05 |
| 15 | 61.77 | 18.75 | 10.00 | 8.75 | 7.88 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 8.08 | 20.64 | 10.07 | 0.00 |

overflows to: CB1

| Drainage Area | | CB1 | | | |
|----------------------------|--------------------------|---|----------------|----------------------|------------------------------|
| Area (Ha) | | 0.17 | | | |
| C = | | 0.88 | | | |
| | | Restricted Flow Q_r (L/s)= 16.00 | | | |
| 100-Year Ponding | | | | | |
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p \approx 2.78xCi_{100yr} A$ (L/s) | Q_r (L/s) | $Q_p - Q_r$ (L/s) | Volume 100yr (m^3) |
| 19 | 123.87 | 49.72 | 16.00 | 33.72 | 38.44 |
| 21 | 116.30 | 46.68 | 16.00 | 30.68 | 38.65 |
| 22 | 112.88 | 45.31 | 16.00 | 29.31 | 38.68 |
| 23 | 109.68 | 44.02 | 16.00 | 28.02 | 38.67 |
| 25 | 103.85 | 41.68 | 16.00 | 25.68 | 38.52 |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 14.13 | 52.82 | 50.59 | 5.58 | 0.00 |
| Length (m) | Dia (m) | Area (m ²) | Volume (m ³) | |
| 31.00 | 0.450 | 0.159 | 4.93 | 4.93 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB16 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.010 | | | |
| C = | | 0.38 | | | |
| | | Restricted Flow Q _r (L/s)= 6.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | I _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| -6 | 57497.20 | 599.41 | 16.00 | 583.41 | -210.03 |
| -4 | 977.56 | 10.19 | 16.00 | -5.81 | 1.39 |
| -3 | 702.38 | 7.32 | 16.00 | -8.68 | 1.56 |
| -2 | 555.31 | 5.79 | 16.00 | -10.21 | 1.23 |
| 0 | 398.62 | 4.16 | 16.00 | -11.84 | 0.00 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.56 | 0.31 | 0.00 | 1.25 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB17 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.090 | | | |
| C = | | 1.00 | | | |
| | | Restricted Flow Q _r (L/s)= 9.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 22 | 112.88 | 28.24 | 9.00 | 19.24 | 25.40 |
| 24 | 106.68 | 26.69 | 9.00 | 17.69 | 25.47 |
| 25 | 103.85 | 25.98 | 9.00 | 16.98 | 25.47 |
| 26 | 101.18 | 25.32 | 9.00 | 16.32 | 25.45 |
| 28 | 96.27 | 24.09 | 9.00 | 15.09 | 25.35 |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 1.25 | 26.73 | 0.84 | 5.10 | 20.79 |
| Length (m) | Dia (m) | Area (m ²) | Volume (m ³) | |
| 28.00 | 0.450 | 0.159 | 4.45 | 4.45 |
| overflows to: CB15 | | | | |

| Drainage Area | | CB1 | | | | |
|-------------------------------------|-------------------------------|--|---------------------------------------|---|------------------------------------|--|
| Area (Ha) | | 0.17 | | | | |
| C = | | 0.70 | Restricted Flow Q _r (L/s)= | | 16.00 | |
| 5-Year Ponding | | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) | |
| 7 | 123.30 | 39.59 | 16.00 | 23.59 | 9.91 | |
| 9 | 109.79 | 35.25 | 16.00 | 19.25 | 10.40 | |
| 10 | 104.19 | 33.46 | 16.00 | 17.46 | 10.47 | |
| 11 | 99.19 | 31.85 | 16.00 | 15.85 | 10.46 | |
| 13 | 90.63 | 29.10 | 16.00 | 13.10 | 10.22 | |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 10.47 | 50.59 | 5.58 | 0.00 |
| Structure | Depth | Area (m ²) | Volume (m ³) | |
| CB3 (600mm x 600mm) | 1.80 | 0.36 | 0.65 | 0.65 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB16 | | | | |
|-------------------------------------|-------------------------------|--|---------------------------------------|---|------------------------------------|--|
| Area (Ha) | | 0.010 | | | | |
| C = | | 0.30 | Restricted Flow Q _r (L/s)= | | 6.00 | |
| 5-Year Ponding | | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) | |
| -6 | 10904.38 | 90.94 | 6.00 | 84.94 | -30.58 | |
| -4 | 555.75 | 4.63 | 6.00 | -1.37 | 0.33 | |
| -3 | 402.34 | 3.36 | 6.00 | -2.64 | 0.48 | |
| -2 | 319.47 | 2.66 | 6.00 | -3.34 | 0.40 | |
| 0 | 230.48 | 1.92 | 6.00 | -4.08 | 0.00 | |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.48 | 0.31 | 0.00 | 0.17 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB17 | | | | |
|-------------------------------------|-------------------------------|--|---------------------------------------|---|------------------------------------|--|
| Area (Ha) | | 0.090 | | | | |
| C = | | 0.90 | Restricted Flow Q _r (L/s)= | | 9.00 | |
| 5-Year Ponding | | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) | |
| 10 | 104.19 | 23.46 | 9.00 | 14.46 | 8.68 | |
| 12 | 94.70 | 21.32 | 9.00 | 12.32 | 8.87 | |
| 13 | 90.63 | 20.41 | 9.00 | 11.41 | 8.90 | |
| 14 | 86.93 | 19.58 | 9.00 | 10.58 | 8.88 | |
| 16 | 80.46 | 18.12 | 9.00 | 9.12 | 8.75 | |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.17 | 9.06 | 0.84 | 5.10 | 3.13 |
| Structure | Depth | Area (m ²) | Volume (m ³) | |
| CB3 (600mm x 600mm) | 1.80 | 0.36 | 0.65 | 0.65 |
| overflows to: CB15 | | | | |

| Drainage Area | | CB1 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.165 | | | | |
| C = | 0.70 | Restricted Flow Q _r (L/s)= 16.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 4 | 111.72 | 35.87 | 16.00 | 19.87 | 4.77 |
| 6 | 96.64 | 31.03 | 16.00 | 15.03 | 5.41 |
| 7 | 90.66 | 29.11 | 16.00 | 13.11 | 5.51 |
| 8 | 85.46 | 27.44 | 16.00 | 11.44 | 5.49 |
| 10 | 76.81 | 24.66 | 16.00 | 8.66 | 5.20 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 5.51 | 50.59 | 5.58 | 0.00 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB16 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.010 | | | | |
| C = | 0.30 | Restricted Flow Q _r (L/s)= 6.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -7 | #NUM! | #NUM! | 6.00 | #NUM! | #NUM! |
| -5 | 632.75 | 5.28 | 6.00 | -0.72 | 0.22 |
| -4 | 387.14 | 3.23 | 6.00 | -2.77 | 0.67 |
| -3 | 285.77 | 2.38 | 6.00 | -3.62 | 0.65 |
| -1 | 192.83 | 1.61 | 6.00 | -4.39 | 0.26 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.67 | 0.31 | 0.00 | 0.36 |
| overflows to: CB17 | | | | |

| Drainage Area | | CB17 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.090 | | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= 9.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 7 | 90.66 | 20.42 | 9.00 | 11.42 | 4.79 |
| 9 | 80.87 | 18.21 | 9.00 | 9.21 | 4.97 |
| 10 | 76.81 | 17.29 | 9.00 | 8.29 | 4.98 |
| 11 | 73.17 | 16.48 | 9.00 | 7.48 | 4.93 |
| 13 | 66.93 | 15.07 | 9.00 | 6.07 | 4.74 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 4.98 | 0.84 | 5.10 | 0.00 |
| overflows to: CB15 | | | | |

| Drainage Area | | CB15 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|--|--------------------------------------|
| Area (Ha) | | 0.090 | | | |
| C = | | 0.94 | | Restricted Flow Q _r (L/s)= 6.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p ≈2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 33 | 86.03 | 20.18 | 6.00 | 14.18 | 28.08 |
| 35 | 82.58 | 19.37 | 6.00 | 13.37 | 28.08 |
| 36 | 80.96 | 18.99 | 6.00 | 12.99 | 28.06 |
| 37 | 79.42 | 18.63 | 6.00 | 12.63 | 28.03 |
| 39 | 76.51 | 17.95 | 6.00 | 11.95 | 27.96 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 20.79 | 48.85 | 66.27 | 5.10 | 0.00 |

| | | | |
|------------|---------|------------------------|--------------------------|
| Length (m) | Dia (m) | Area (m ²) | Volume (m ³) |
| 28.00 | 0.450 | 0.159 | 4.45 4.45 |

overflows to: out

| Drainage Area | | CB15 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.090 | | | |
| C = | | 0.75 | | | |
| | | Restricted Flow Q _r (L/s)= 6.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C i _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| 13 | 90.63 | 17.01 | 6.00 | 11.01 | 8.59 |
| 15 | 83.56 | 15.68 | 6.00 | 9.68 | 8.71 |
| 16 | 80.46 | 15.10 | 6.00 | 9.10 | 8.73 |
| 17 | 77.61 | 14.56 | 6.00 | 8.56 | 8.73 |
| 19 | 72.53 | 13.61 | 6.00 | 7.61 | 8.67 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 3.13 | 11.86 | 66.27 | 5.10 | 0.00 |

| | | | |
|---------------------|-------|------------------------|--------------------------|
| Structure | Depth | Area (m ²) | Volume (m ³) |
| CB3 (600mm x 600mm) | 1.80 | 0.36 | 0.65 0.65 |

overflows to: out

| Drainage Area | | CB15 | | | |
|-------------------------------------|-------------------------------|---|--|--|------------------------------------|
| Area (Ha) | 0.090 | | | | |
| C = | 0.75 | | Restricted Flow Q _r (L/s)= 6.00 | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 2yr (m ³) |
| 9 | 80.87 | 15.18 | 6.00 | 9.18 | 4.95 |
| 11 | 73.17 | 13.73 | 6.00 | 7.73 | 5.10 |
| 12 | 69.89 | 13.12 | 6.00 | 7.12 | 5.12 |
| 13 | 66.93 | 12.56 | 6.00 | 6.56 | 5.12 |
| 15 | 61.77 | 11.59 | 6.00 | 5.59 | 5.03 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 5.12 | 66.27 | 5.10 | 0.00 |

overflows to: out

| Drainage Area | | CBMH3 | | | |
|-------------------------------------|---------------------------------|---|-------------------------|--|--------------------------------------|
| Area (Ha) | 0.020 | | | | |
| C = | 0.81 | Restricted Flow Q _r (L/s)= | | | 6.00 |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p ≈ 2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 100yr (m ³) |
| 3 | 286.05 | 12.92 | 6.00 | 6.92 | 1.25 |
| 5 | 242.70 | 10.96 | 6.00 | 4.96 | 1.49 |
| 6 | 226.01 | 10.21 | 6.00 | 4.21 | 1.52 |
| 7 | 211.67 | 9.56 | 6.00 | 3.56 | 1.50 |
| 9 | 188.25 | 8.50 | 6.00 | 2.50 | 1.35 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.52 | 4.17 | 0 | 0.00 |

overflows to: CB12/13/14

| Drainage Area | | CBMH3 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.020 | | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= 6.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 0 | 230.48 | 11.53 | 6.00 | 5.53 | 0.00 |
| 2 | 182.69 | 9.14 | 6.00 | 3.14 | 0.38 |
| 3 | 166.09 | 8.31 | 6.00 | 2.31 | 0.42 |
| 4 | 152.51 | 7.63 | 6.00 | 1.63 | 0.39 |
| 6 | 131.57 | 6.58 | 6.00 | 0.58 | 0.21 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.42 | 4.17 | 0.00 | 0.00 |

overflows to: CB12/13/14

| Drainage Area | | CBMH3 | | | |
|-------------------------------------|-------------------------------|---|-------------------------|--|------------------------------------|
| Area (Ha) | 0.020 | | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= | | | 6.00 |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 2yr (m ³) |
| -2 | 229.26 | 11.47 | 6.00 | 5.47 | -0.66 |
| 0 | 167.22 | 8.37 | 6.00 | 2.37 | 0.00 |
| 1 | 148.14 | 7.41 | 6.00 | 1.41 | 0.08 |
| 2 | 133.33 | 6.67 | 6.00 | 0.67 | 0.08 |
| 4 | 111.72 | 5.59 | 6.00 | -0.41 | -0.10 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.08 | 4.17 | 0.00 | 0.00 |

overflows to: CB12/13/14

| Drainage Area | | CB11 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.030 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 15.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 1 | 351.38 | 29.31 | 15.00 | 14.31 | 0.86 |
| 3 | 286.05 | 23.86 | 15.00 | 8.86 | 1.59 |
| 4 | 262.41 | 21.88 | 15.00 | 6.88 | 1.65 |
| 5 | 242.70 | 20.24 | 15.00 | 5.24 | 1.57 |
| 7 | 211.67 | 17.65 | 15.00 | 2.65 | 1.11 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 5.62 | 7.27 | 0.93 | 0 | 6.34 |

overflows to: CB12/CB13/CB14

| Drainage Area | | CB11 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.030 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 15.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| -2 | 319.47 | 23.98 | 15.00 | 8.98 | -1.08 |
| 0 | 230.48 | 17.30 | 15.00 | 2.30 | 0.00 |
| 1 | 203.51 | 15.28 | 15.00 | 0.28 | 0.02 |
| 2 | 182.69 | 13.71 | 15.00 | -1.29 | -0.15 |
| 4 | 152.51 | 11.45 | 15.00 | -3.55 | -0.85 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.02 | 0.93 | 0.00 | 0.00 |

overflows to: CB12/CB13/CB14

| Drainage Area | | CB11 | | | |
|-------------------------------------|-------------------------------|--|---------------------------------------|---|------------------------------------|
| Area (Ha) | 0.030 | | | | |
| C = | 0.90 | | Restricted Flow Q _r (L/s)= | | 15.00 |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -4 | 387.14 | 29.06 | 15.00 | 14.06 | -3.37 |
| -2 | 229.26 | 17.21 | 15.00 | 2.21 | -0.26 |
| -1 | 192.83 | 14.47 | 15.00 | -0.53 | 0.03 |
| 0 | 167.22 | 12.55 | 15.00 | -2.45 | 0.00 |
| 2 | 133.33 | 10.01 | 15.00 | -4.99 | -0.60 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.03 | 0.93 | 0.00 | 0.00 |

overflows to: CB12/CB13/CB14

| Drainage Area | | CB12/CB13/CB14 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | 0.330 | Restricted Flow Q _r (L/s)= 73.00 | | | |
| C = | 1.00 | | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p ≈2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 9 | 188.25 | 172.70 | 73.00 | 99.70 | 53.84 |
| 10 | 178.56 | 163.81 | 73.00 | 90.81 | 54.49 |
| 11 | 169.91 | 155.87 | 73.00 | 82.87 | 54.70 |
| 12 | 162.13 | 148.74 | 73.00 | 75.74 | 54.53 |
| 14 | 148.72 | 136.44 | 73.00 | 63.44 | 53.29 |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 6.34 | 61.03 | 54.36 | 5.07 | 1.60 |
| | | | | |
| Length (m) | Dia (m) | Area (m ²) | Volume (m ³) | |
| 11.07 | 0.375 | 0.110 | 1.22 | |
| 12.00 | 0.450 | 0.159 | 1.91 | |
| | | | 3.13 | |

overflows to: CB10

| Drainage Area | | CB10 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.130 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 45.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 5 | 242.70 | 87.71 | 45.00 | 42.71 | 12.81 |
| 6 | 226.01 | 81.68 | 45.00 | 36.68 | 13.20 |
| 7 | 211.67 | 76.50 | 45.00 | 31.50 | 13.23 |
| 8 | 199.20 | 71.99 | 45.00 | 26.99 | 12.96 |
| 10 | 178.56 | 64.53 | 45.00 | 19.53 | 11.72 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 5.62 | 18.85 | 6.81 | 0.00 | 12.04 |

overflows to: CB18

| Drainage Area | | CB12/CB13/CB14 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | 0.330 | Restricted Flow Q _r (L/s)= 73.00 | | | |
| C = | 0.90 | | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C _i 5yr A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| 2 | 182.69 | 150.84 | 73.00 | 77.84 | 9.34 |
| 4 | 152.51 | 125.92 | 73.00 | 52.92 | 12.70 |
| 5 | 141.18 | 116.57 | 73.00 | 43.57 | 13.07 |
| 6 | 131.57 | 108.63 | 73.00 | 35.63 | 12.83 |
| 8 | 116.11 | 95.87 | 73.00 | 22.87 | 10.98 |

| Storage (m ³) | | | | |
|---------------------------|----------|------------------------|--------------------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 13.07 | 54.36 | 5.07 | 0.00 |
| | | | | |
| Structure | Depth | Area (m ²) | Volume (m ³) | |
| CB12 (600mm x 600mm) | 1.80 | 0.36 | 0.65 | |
| CB13 (600mm x 600mm) | 1.80 | 0.36 | 0.65 | |
| CB14 (600mm x 600mm) | 1.80 | 0.36 | 0.65 | |
| | | | 1.94 | |

overflows to: CB10

| Drainage Area | | CB10 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.130 | Restricted Flow Q _r (L/s)= 45.00 | | | |
| C = | 0.90 | | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| -1 | 266.98 | 86.84 | 45.00 | 41.84 | -2.51 |
| 1 | 203.51 | 66.19 | 45.00 | 21.19 | 1.27 |
| 2 | 182.69 | 59.42 | 45.00 | 14.42 | 1.73 |
| 3 | 166.09 | 54.02 | 45.00 | 9.02 | 1.62 |
| 5 | 141.18 | 45.92 | 45.00 | 0.92 | 0.28 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.73 | 6.81 | 0.00 | 0.00 |

overflows to: CB18

| Drainage Area 2/CB13/CB14 | | | | | |
|---|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.330 | | | | |
| C = | 0.90 | | | | |
| Restricted Flow Q _r (L/s)= 73.00 | | | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 0 | 167.22 | 138.07 | 73.00 | 65.07 | 0.00 |
| 2 | 133.33 | 110.09 | 73.00 | 37.09 | 4.45 |
| 3 | 121.46 | 100.29 | 73.00 | 27.29 | 4.91 |
| 4 | 111.72 | 92.25 | 73.00 | 19.25 | 4.62 |
| 6 | 96.64 | 79.79 | 73.00 | 6.79 | 2.44 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 4.91 | 54.36 | 5.07 | 0.00 |

overflows to: CB10

| Drainage Area | | CB10 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.130 | Restricted Flow Q _r (L/s)= 45.00 | | | |
| C = | 0.90 | | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -2 | 229.26 | 74.57 | 45.00 | 29.57 | -3.55 |
| 0 | 167.22 | 54.39 | 45.00 | 9.39 | 0.00 |
| 1 | 148.14 | 48.19 | 45.00 | 3.19 | 0.19 |
| 2 | 133.33 | 43.37 | 45.00 | -1.63 | -0.20 |
| 4 | 111.72 | 36.34 | 45.00 | -8.66 | -2.08 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| Balance | #VALUE! | 6.81 | 0.00 | #VALUE! |

overflows to: CB18

| Drainage Area | | CBMH2 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 1.00 | | | |
| | | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 7 | 211.67 | 47.07 | 20.00 | 27.07 | 11.37 |
| 9 | 188.25 | 41.87 | 20.00 | 21.87 | 11.81 |
| 10 | 178.56 | 39.71 | 20.00 | 19.71 | 11.83 |
| 11 | 169.91 | 37.79 | 20.00 | 17.79 | 11.74 |
| 13 | 155.11 | 34.50 | 20.00 | 14.50 | 11.31 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 11.83 | 6.21 | 0.00 | 5.62 |

overflows to: CB11

| Drainage Area | | CB7 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 30.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 3 | 286.05 | 63.62 | 30.00 | 33.62 | 6.05 |
| 5 | 242.70 | 53.98 | 30.00 | 23.98 | 7.19 |
| 6 | 226.01 | 50.26 | 30.00 | 20.26 | 7.30 |
| 7 | 211.67 | 47.07 | 30.00 | 17.07 | 7.17 |
| 9 | 188.25 | 41.87 | 30.00 | 11.87 | 6.41 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 5.62 | 12.91 | 6.97 | 0.00 | 5.94 |

overflows to: CB8

| Drainage Area | | CB6 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.070 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 20.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p ≈2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 5 | 242.70 | 47.23 | 20.00 | 27.23 | 8.17 |
| 7 | 211.67 | 41.19 | 20.00 | 21.19 | 8.90 |
| 8 | 199.20 | 38.76 | 20.00 | 18.76 | 9.01 |
| 9 | 188.25 | 36.63 | 20.00 | 16.63 | 8.98 |
| 11 | 169.91 | 33.06 | 20.00 | 13.06 | 8.62 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 9.01 | 13.66 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CB5 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.060 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 15.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 7 | 211.67 | 35.31 | 15.00 | 20.31 | 8.53 |
| 9 | 188.25 | 31.40 | 15.00 | 16.40 | 8.86 |
| 10 | 178.56 | 29.78 | 15.00 | 14.78 | 8.87 |
| 11 | 169.91 | 28.34 | 15.00 | 13.34 | 8.80 |
| 13 | 155.11 | 25.87 | 15.00 | 10.87 | 8.48 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 8.87 | 3.41 | 0.00 | 5.46 |

overflows to: CB8

| Drainage Area | | CBMH2 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C i _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| 1 | 203.51 | 40.73 | 20.00 | 20.73 | 1.24 |
| 3 | 166.09 | 33.24 | 20.00 | 13.24 | 2.38 |
| 4 | 152.51 | 30.53 | 20.00 | 10.53 | 2.53 |
| 5 | 141.18 | 28.26 | 20.00 | 8.26 | 2.48 |
| 7 | 123.30 | 24.68 | 20.00 | 4.68 | 1.97 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 2.53 | 6.21 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CB7 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 30.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C i _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| -1 | 266.98 | 53.44 | 30.00 | 23.44 | -1.41 |
| 1 | 203.51 | 40.73 | 30.00 | 10.73 | 0.64 |
| 2 | 182.69 | 36.57 | 30.00 | 6.57 | 0.79 |
| 3 | 166.09 | 33.24 | 30.00 | 3.24 | 0.58 |
| 5 | 141.18 | 28.26 | 30.00 | -1.74 | -0.52 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.79 | 6.97 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | P3/L3 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.160 | | | |
| C = | | 0.45 | | | |
| | | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 1 | 203.51 | 40.73 | 20.00 | 20.73 | 1.24 |
| 3 | 166.09 | 33.24 | 20.00 | 13.24 | 2.38 |
| 4 | 152.51 | 30.53 | 20.00 | 10.53 | 2.53 |
| 5 | 141.18 | 28.26 | 20.00 | 8.26 | 2.48 |
| 7 | 123.30 | 24.68 | 20.00 | 4.68 | 1.97 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 2.53 | 13.66 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CBMH2 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 0.90 | | Restricted Flow Q _r (L/s)= 20.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -1 | 192.83 | 38.60 | 20.00 | 18.60 | -1.12 |
| 1 | 148.14 | 29.65 | 20.00 | 9.65 | 0.58 |
| 2 | 133.33 | 26.69 | 20.00 | 6.69 | 0.80 |
| 3 | 121.46 | 24.31 | 20.00 | 4.31 | 0.78 |
| 5 | 103.57 | 20.73 | 20.00 | 0.73 | 0.22 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.80 | 6.21 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CB7 | | | |
|-------------------------------------|-------------------------------|---|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | | 0.90 | | Restricted Flow Q _r (L/s)= 30.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 2yr (m ³) |
| -3 | 285.77 | 57.20 | 30.00 | 27.20 | -4.90 |
| -1 | 192.83 | 38.60 | 30.00 | 8.60 | -0.52 |
| 0 | 167.22 | 33.47 | 30.00 | 3.47 | 0.00 |
| 1 | 148.14 | 29.65 | 30.00 | -0.35 | -0.02 |
| 3 | 121.46 | 24.31 | 30.00 | -5.69 | -1.02 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.00 | 6.97 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CB6 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.070 | | | | |
| C = | 0.45 | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -4 | 387.14 | 33.90 | 20.00 | 13.90 | -3.34 |
| -2 | 229.26 | 20.08 | 20.00 | 0.08 | -0.01 |
| -1 | 192.83 | 16.89 | 20.00 | -3.11 | 0.19 |
| 0 | 167.22 | 14.64 | 20.00 | -5.36 | 0.00 |
| 2 | 133.33 | 11.68 | 20.00 | -8.32 | -1.00 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.19 | 13.66 | 0.00 | 0.00 |

overflows to: CB8

| Drainage Area | | CB5 | | | |
|-------------------------------------|-------------------------------|---|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.060 | | | |
| C = | | 0.90 | | Restricted Flow Q _r (L/s)= 15.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78Ci _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -1 | 192.83 | 28.95 | 15.00 | 13.95 | -0.84 |
| 1 | 148.14 | 22.24 | 15.00 | 7.24 | 0.43 |
| 2 | 133.33 | 20.02 | 15.00 | 5.02 | 0.60 |
| 3 | 121.46 | 18.23 | 15.00 | 3.23 | 0.58 |
| 5 | 103.57 | 15.55 | 15.00 | 0.55 | 0.16 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| #VALUE! | #VALUE! | 3.41 | 0.00 | #VALUE! |

overflows to: CB8

| Drainage Area | | CB8 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.170 | | | |
| C = | | 1.00 | | | |
| | | Restricted Flow Q _r (L/s)= 47.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 6 | 226.01 | 106.81 | 47.00 | 59.81 | 21.53 |
| 8 | 199.20 | 94.14 | 47.00 | 47.14 | 22.63 |
| 9 | 188.25 | 88.97 | 47.00 | 41.97 | 22.66 |
| 10 | 178.56 | 84.39 | 47.00 | 37.39 | 22.43 |
| 12 | 162.13 | 76.62 | 47.00 | 29.62 | 21.33 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 11.40 | 34.07 | 24.90 | 1.60 | 7.57 |

| | | | |
|------------|---------|------------------------|--------------------------|
| Length (m) | Dia (m) | Area (m ²) | Volume (m ³) |
| 6.00 | 0.450 | 0.159 | 0.95 |

| Drainage Area | | CB8 | | | | |
|-------------------------------------|-------------------------------|---|---------------------------------------|--|------------------------------------|--|
| Area (Ha) | | 0.170 | | | | |
| C = | | 0.90 | Restricted Flow Q _r (L/s)= | | 47.00 | |
| 5-Year Ponding | | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) | |
| 1 | 203.51 | 86.56 | 47.00 | 39.56 | 2.37 | |
| 3 | 166.09 | 70.64 | 47.00 | 23.64 | 4.26 | |
| 4 | 152.51 | 64.87 | 47.00 | 17.87 | 4.29 | |
| 5 | 141.18 | 60.05 | 47.00 | 13.05 | 3.91 | |
| 7 | 123.30 | 52.45 | 47.00 | 5.45 | 2.29 | |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 4.29 | 24.90 | 1.60 | 0.00 |

| | | | |
|---------------------|-------|------------------------|--------------------------|
| Structure | Depth | Area (m ²) | Volume (m ³) |
| CB8 (600mm x 600mm) | 1.80 | 0.36 | 0.65 |

| Drainage Area | | CB8 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.170 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 47.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -1 | 192.83 | 82.02 | 47.00 | 35.02 | -2.10 |
| 1 | 148.14 | 63.01 | 47.00 | 16.01 | 0.96 |
| 2 | 133.33 | 56.71 | 47.00 | 9.71 | 1.17 |
| 3 | 121.46 | 51.66 | 47.00 | 4.66 | 0.84 |
| 5 | 103.57 | 44.05 | 47.00 | -2.95 | -0.88 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.17 | 24.90 | 1.60 | 0.00 |

overflows to: CB9

| Drainage Area | | CB4 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|--|--------------------------------------|
| Area (Ha) | | 0.030 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 6.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 9 | 188.25 | 15.70 | 6.00 | 9.70 | 5.24 |
| 11 | 169.91 | 14.17 | 6.00 | 8.17 | 5.39 |
| 12 | 162.13 | 13.52 | 6.00 | 7.52 | 5.42 |
| 13 | 155.11 | 12.94 | 6.00 | 6.94 | 5.41 |
| 15 | 142.89 | 11.92 | 6.00 | 5.92 | 5.33 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 7.57 | 12.98 | 10.62 | 0.00 | 2.36 |

overflows to: CBMH1

| Drainage Area | | CB4 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.030 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 6.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C i _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| 3 | 166.09 | 12.47 | 6.00 | 6.47 | 1.16 |
| 5 | 141.18 | 10.60 | 6.00 | 4.60 | 1.38 |
| 6 | 131.57 | 9.88 | 6.00 | 3.88 | 1.40 |
| 7 | 123.30 | 9.26 | 6.00 | 3.26 | 1.37 |
| 9 | 109.79 | 8.24 | 6.00 | 2.24 | 1.21 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.40 | 10.62 | 0.00 | 0.00 |

overflows to: CBMH1

| Drainage Area | | CB4 | | | |
|-------------------------------------|-------------------------------|--|---------------------------------------|---|------------------------------------|
| Area (Ha) | 0.030 | | | | |
| C = | 0.90 | | Restricted Flow Q _r (L/s)= | | 6.00 |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 1 | 148.14 | 11.12 | 6.00 | 5.12 | 0.31 |
| 3 | 121.46 | 9.12 | 6.00 | 3.12 | 0.56 |
| 4 | 111.72 | 8.39 | 6.00 | 2.39 | 0.57 |
| 5 | 103.57 | 7.77 | 6.00 | 1.77 | 0.53 |
| 7 | 90.66 | 6.81 | 6.00 | 0.81 | 0.34 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.57 | 10.62 | 0.00 | 0.00 |

overflows to: CBMH1

| Drainage Area | | CBMH1 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | 0.080 | | | | |
| C = | 1.00 | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 7 | 211.67 | 47.07 | 20.00 | 27.07 | 11.37 |
| 9 | 188.25 | 41.87 | 20.00 | 21.87 | 11.81 |
| 10 | 178.56 | 39.71 | 20.00 | 19.71 | 11.83 |
| 11 | 169.91 | 37.79 | 20.00 | 17.79 | 11.74 |
| 13 | 155.11 | 34.50 | 20.00 | 14.50 | 11.31 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 2.36 | 14.19 | 0.00 | 0.00 | 14.19 |

overflows to: CB9

| Drainage Area | | CBMH1 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.080 | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 1 | 203.51 | 40.73 | 20.00 | 20.73 | 1.24 |
| 3 | 166.09 | 33.24 | 20.00 | 13.24 | 2.38 |
| 4 | 152.51 | 30.53 | 20.00 | 10.53 | 2.53 |
| 5 | 141.18 | 28.26 | 20.00 | 8.26 | 2.48 |
| 7 | 123.30 | 24.68 | 20.00 | 4.68 | 1.97 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 2.53 | 0.00 | 0.00 | 2.53 |

overflows to: CB9

| Drainage Area | | CBMH1 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.080 | | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= | | 20.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -1 | 192.83 | 38.60 | 20.00 | 18.60 | -1.12 |
| 1 | 148.14 | 29.65 | 20.00 | 9.65 | 0.58 |
| 2 | 133.33 | 26.69 | 20.00 | 6.69 | 0.80 |
| 3 | 121.46 | 24.31 | 20.00 | 4.31 | 0.78 |
| 5 | 103.57 | 20.73 | 20.00 | 0.73 | 0.22 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.80 | 0.00 | 0.00 | 0.80 |

overflows to: CB9

| Drainage Area | | CB9 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.150 | | | |
| C = | | 1.00 | | | |
| | | Restricted Flow Q _r (L/s)= 43.00 | | | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 5 | 242.70 | 101.21 | 43.00 | 58.21 | 17.46 |
| 7 | 211.67 | 88.27 | 43.00 | 45.27 | 19.01 |
| 8 | 199.20 | 83.07 | 43.00 | 40.07 | 19.23 |
| 9 | 188.25 | 78.50 | 43.00 | 35.50 | 19.17 |
| 11 | 169.91 | 70.85 | 43.00 | 27.85 | 18.38 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 21.75 | 40.99 | 10.83 | 0.00 | 30.16 |

overflows to: CB18

| Drainage Area | | CB9 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.160 | | | |
| C = | | 0.45 | | Restricted Flow Q _r (L/s)= 43.00 | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78 x C i _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| -3 | 402.34 | 80.53 | 43.00 | 37.53 | -6.76 |
| -1 | 266.98 | 53.44 | 43.00 | 10.44 | -0.63 |
| 0 | 230.48 | 46.13 | 43.00 | 3.13 | 0.00 |
| 1 | 203.51 | 40.73 | 43.00 | -2.27 | -0.14 |
| 3 | 166.09 | 33.24 | 43.00 | -9.76 | -1.76 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 2.53 | 2.53 | 10.83 | 0.00 | 0.00 |

overflows to: CB18

| Drainage Area | | CB9 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.150 | | | | |
| C = | 0.45 | Restricted Flow Q _r (L/s)= | | 43.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -3 | 285.77 | 53.62 | 43.00 | 10.62 | -1.91 |
| -1 | 192.83 | 36.18 | 43.00 | -6.82 | 0.41 |
| 0 | 167.22 | 31.38 | 43.00 | -11.62 | 0.00 |
| 1 | 148.14 | 27.80 | 43.00 | -15.20 | -0.91 |
| 3 | 121.46 | 22.79 | 43.00 | -20.21 | -3.64 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.00 | 10.83 | 0.00 | 0.00 |

overflows to: CB18

| Drainage Area | | CB18 | | | |
|-------------------------------------|---------------------------------|--|-------------------------|---|--------------------------------------|
| Area (Ha) | 0.160 | | | | |
| C = | 0.25 | Restricted Flow Q _r (L/s)= | | 15.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 3 | 286.05 | 31.81 | 15.00 | 16.81 | 3.03 |
| 5 | 242.70 | 26.99 | 15.00 | 11.99 | 3.60 |
| 6 | 226.01 | 25.13 | 15.00 | 10.13 | 3.65 |
| 7 | 211.67 | 23.54 | 15.00 | 8.54 | 3.59 |
| 9 | 188.25 | 20.93 | 15.00 | 5.93 | 3.20 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 42.19 | 45.84 | 13.76 | 46.33 | 0.00 |

Subsurface storage calculation

| | |
|---|----------------------|
| 450mm subdrain @ 96m | 15.30 m ³ |
| Bottom of storage medium ave. grade | 98.00 m |
| width of S29 trench | 1.00 m |
| depth of S29 trench (below spill elev.) | 1.01 m |
| Volume of S29 trench | 96.96 m ³ |
| Volume of clear stone | 81.66 m ³ |
| 25mm clear stone per S29 | 0.38 void ratio |
| Stoage within clear stone | 31.03 m ³ |

overflows to: offsite

| Drainage Area | | RA | | | |
|-------------------------------------|---------------------------------|---|-------------------------|---|--------------------------------------|
| Area (Ha) | | 0.300 | | | |
| C = | | 1.00 | | Restricted Flow Q _r (L/s)= 27.00 | |
| 100-Year Ponding | | | | | |
| T _c Variable (min) | i _{100yr} (mm/hour) | Peak Flow Q _p ≈ 2.78xCi _{100yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 100yr (m ³) |
| 25 | 103.85 | 86.61 | 27.00 | 59.61 | 89.41 |
| 26 | 101.18 | 84.38 | 27.00 | 57.38 | 89.52 |
| 27 | 98.66 | 82.28 | 27.00 | 55.28 | 89.56 |
| 28 | 96.27 | 80.29 | 27.00 | 53.29 | 89.53 |
| 29 | 94.01 | 78.41 | 27.00 | 51.41 | 89.45 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 89.56 | 90.00 | 0.00 | 0.00 |

| Drainage Area | | CB18 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.160 | | | |
| C = | | 0.20 | | | |
| | | Restricted Flow Q _r (L/s)= 15.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| -2 | 319.47 | 28.42 | 15.00 | 13.42 | -1.61 |
| 0 | 230.48 | 20.50 | 15.00 | 5.50 | 0.00 |
| 1 | 203.51 | 18.10 | 15.00 | 3.10 | 0.19 |
| 2 | 182.69 | 16.25 | 15.00 | 1.25 | 0.15 |
| 4 | 152.51 | 13.57 | 15.00 | -1.43 | -0.34 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.19 | 13.76 | 46.33 | 0.00 |

overflows to: offsite

| Drainage Area | | RA | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.300 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 27.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 13 | 90.63 | 68.03 | 27.00 | 41.03 | 32.00 |
| 14 | 86.93 | 65.25 | 27.00 | 38.25 | 32.13 |
| 15 | 83.56 | 62.72 | 27.00 | 35.72 | 32.15 |
| 16 | 80.46 | 60.39 | 27.00 | 33.39 | 32.06 |
| 17 | 77.61 | 58.25 | 27.00 | 31.25 | 31.88 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 32.15 | 90.00 | 0.00 | 0.00 |

| Drainage Area | | CB18 | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.160 | | | |
| C = | | 0.20 | | Restricted Flow Q _r (L/s)= 15.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| -3 | 285.77 | 25.42 | 15.00 | 10.42 | -1.88 |
| -1 | 192.83 | 17.15 | 15.00 | 2.15 | -0.13 |
| 0 | 167.22 | 14.88 | 15.00 | -0.12 | 0.00 |
| 1 | 148.14 | 13.18 | 15.00 | -1.82 | -0.11 |
| 3 | 121.46 | 10.81 | 15.00 | -4.19 | -0.76 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 0.00 | 13.76 | 46.33 | 0.00 |

C

overflows to: offsite

| Drainage Area | | RA | | | |
|-------------------------------------|-------------------------------|---|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.300 | | | |
| C = | | 0.90 | | Restricted Flow Q _r (L/s)= 27.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 2yr (m ³) |
| 8 | 85.46 | 64.14 | 27.00 | 37.14 | 17.83 |
| 10 | 76.81 | 57.65 | 27.00 | 30.65 | 18.39 |
| 11 | 73.17 | 54.92 | 27.00 | 27.92 | 18.43 |
| 12 | 69.89 | 52.46 | 27.00 | 25.46 | 18.33 |
| 14 | 64.23 | 48.21 | 27.00 | 21.21 | 17.82 |

| Storage (m ³) | | | | |
|---------------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 18.43 | 90.00 | 0.00 | 0.00 |

| Drainage Area | | RB | | | |
|----------------------------|--------------------------|--|----------------|------------------------------------|------------------------------|
| Area (Ha) | | 0.220 | | | |
| C = | | 1.00 | | Restricted Flow Q_r (L/s)= 20.00 | |
| 100-Year Ponding | | | | | |
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p=2.78xCi_{100yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 100yr (m^3) |
| 24 | 106.68 | 65.24 | 20.00 | 45.24 | 65.15 |
| 26 | 101.18 | 61.88 | 20.00 | 41.88 | 65.34 |
| 27 | 98.66 | 60.34 | 20.00 | 40.34 | 65.35 |
| 28 | 96.27 | 58.88 | 20.00 | 38.88 | 65.32 |
| 30 | 91.87 | 56.19 | 20.00 | 36.19 | 65.14 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 65.35 | 66.00 | 0.00 | 0.00 |

| Drainage Area | | RC | | | |
|----------------------------|--------------------------|--|----------------|-----------------------------------|------------------------------|
| Area (Ha) | | 0.050 | | | |
| C = | | 1.00 | | Restricted Flow Q_r (L/s)= 8.00 | |
| 100-Year Ponding | | | | | |
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p \approx 2.78xCi_{100yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 100yr (m^3) |
| 12 | 162.13 | 22.54 | 8.00 | 14.54 | 10.47 |
| 14 | 148.72 | 20.67 | 8.00 | 12.67 | 10.64 |
| 15 | 142.89 | 19.86 | 8.00 | 11.86 | 10.68 |
| 16 | 137.55 | 19.12 | 8.00 | 11.12 | 10.67 |
| 18 | 128.08 | 17.80 | 8.00 | 9.80 | 10.59 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 10.68 | 13.50 | 1.00 | 0.00 |

| Drainage Area | | RD | | | |
|----------------------------|--------------------------|--|----------------|-----------------------------------|------------------------------|
| Area (Ha) | | 0.050 | | | |
| C = | | 1.00 | | Restricted Flow Q_r (L/s)= 8.00 | |
| 100-Year Ponding | | | | | |
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p=2.78xCi_{100yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 100yr (m^3) |
| 12 | 162.13 | 22.54 | 8.00 | 14.54 | 10.47 |
| 14 | 148.72 | 20.67 | 8.00 | 12.67 | 10.64 |
| 15 | 142.89 | 19.86 | 8.00 | 11.86 | 10.68 |
| 16 | 137.55 | 19.12 | 8.00 | 11.12 | 10.67 |
| 18 | 128.08 | 17.80 | 8.00 | 9.80 | 10.59 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 10.68 | 11.25 | 1.00 | 0.00 |

| Drainage Area | | EXTERNAL | | | |
|----------------------------|--------------------------|--|----------------|-------------------------------------|------------------------------|
| Area (Ha) | | 1.550 | | | |
| C = | | 1.00 | | Restricted Flow Q_r (L/s)= 291.58 | |
| 100-Year Ponding | | | | | |
| T_c Variable (min) | i_{100yr} (mm/hour) | Peak Flow $Q_p \approx 2.78xCi_{100yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 100yr (m^3) |
| 9 | 188.25 | 811.19 | 291.58 | 519.61 | 280.59 |
| 11 | 169.91 | 732.13 | 291.58 | 440.55 | 290.76 |
| 12 | 162.13 | 698.63 | 291.58 | 407.05 | 293.08 |
| 13 | 155.11 | 668.36 | 291.58 | 376.78 | 293.89 |
| 15 | 142.89 | 615.73 | 291.58 | 324.15 | 291.74 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 293.08 | 270.00 | 0.00 | 23.08 |

| Drainage Area | | RB | | | |
|-------------------------------------|-------------------------------|---|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.220 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 20.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78Ci _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 11 | 99.19 | 54.60 | 20.00 | 34.60 | 22.84 |
| 13 | 90.63 | 49.89 | 20.00 | 29.89 | 23.31 |
| 14 | 86.93 | 47.85 | 20.00 | 27.85 | 23.40 |
| 15 | 83.56 | 45.99 | 20.00 | 25.99 | 23.39 |
| 17 | 77.61 | 42.72 | 20.00 | 22.72 | 23.17 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 23.40 | 66.00 | 0.00 | 0.00 |

| Drainage Area | | RC | | | |
|-------------------------------------|-------------------------------|---|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.050 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 8.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p = 2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p - Q _r (L/s) | Volume 5yr (m ³) |
| 5 | 141.18 | 17.66 | 8.00 | 9.66 | 2.90 |
| 7 | 123.30 | 15.43 | 8.00 | 7.43 | 3.12 |
| 8 | 116.11 | 14.53 | 8.00 | 6.53 | 3.13 |
| 9 | 109.79 | 13.74 | 8.00 | 5.74 | 3.10 |
| 11 | 99.19 | 12.41 | 8.00 | 4.41 | 2.91 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 3.13 | 13.50 | 0.00 | 0.00 |

| Drainage Area | | RD | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | | 0.050 | | | |
| C = | | 0.90 | | | |
| | | Restricted Flow Q _r (L/s)= 8.00 | | | |
| 5-Year Ponding | | | | | |
| T _c Variable (min) | i _{5yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{5yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 5yr (m ³) |
| 5 | 141.18 | 17.66 | 8.00 | 9.66 | 2.90 |
| 7 | 123.30 | 15.43 | 8.00 | 7.43 | 3.12 |
| 8 | 116.11 | 14.53 | 8.00 | 6.53 | 3.13 |
| 9 | 109.79 | 13.74 | 8.00 | 5.74 | 3.10 |
| 11 | 99.19 | 12.41 | 8.00 | 4.41 | 2.91 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 3.13 | 11.25 | 0.00 | 0.00 |

| Drainage Area | | EXTERNAL | | | |
|----------------------------|------------------------|--|-------------------------------------|--------------------|----------------------------|
| Area (Ha) | | 1.550 | | | |
| C = | | 0.80 | Restricted Flow Q_r (L/s)= 291.58 | | |
| 5-Year Ponding | | | | | |
| T_c Variable (min) | i_{5yr} (mm/hour) | Peak Flow $Q_p=2.78xCi_{5yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 5yr (m^3) |
| 2 | 182.69 | 629.76 | 291.58 | 338.18 | 40.58 |
| 4 | 152.51 | 525.73 | 291.58 | 234.15 | 56.19 |
| 5 | 141.18 | 486.67 | 291.58 | 195.09 | 58.53 |
| 6 | 131.57 | 453.54 | 291.58 | 161.96 | 58.31 |
| 8 | 116.11 | 400.26 | 291.58 | 108.68 | 52.17 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 58.53 | 270.00 | 0.00 | 0.00 |

| Drainage Area | | RB | | | |
|----------------------------|------------------------|---|----------------|--------------------|----------------------------|
| Area (Ha) | | 0.220 | | | |
| C = | 0.90 | Restricted Flow Q_r (L/s)= 20.00 | | | |
| 2-Year Ponding | | | | | |
| T_c Variable (min) | i_{2yr} (mm/hour) | Peak Flow $Q_p=2.78 \times C i_{2yr} A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 2yr (m^3) |
| 8 | 85.46 | 47.04 | 20.00 | 27.04 | 12.98 |
| 10 | 76.81 | 42.28 | 20.00 | 22.28 | 13.37 |
| 11 | 73.17 | 40.27 | 20.00 | 20.27 | 13.38 |
| 12 | 69.89 | 38.47 | 20.00 | 18.47 | 13.30 |
| 14 | 64.23 | 35.36 | 20.00 | 15.36 | 12.90 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 13.38 | 66.00 | 0.00 | 0.00 |

| Drainage Area | | RC | | | |
|-------------------------------------|-------------------------------|--|-------------------------|---|------------------------------------|
| Area (Ha) | 0.050 | | | | |
| C = | 0.90 | Restricted Flow Q _r (L/s)= 8.00 | | | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 2 | 133.33 | 16.68 | 8.00 | 8.68 | 1.04 |
| 4 | 111.72 | 13.98 | 8.00 | 5.98 | 1.43 |
| 5 | 103.57 | 12.96 | 8.00 | 4.96 | 1.49 |
| 6 | 96.64 | 12.09 | 8.00 | 4.09 | 1.47 |
| 8 | 85.46 | 10.69 | 8.00 | 2.69 | 1.29 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.49 | 13.50 | 0.00 | 0.00 |

| Drainage Area | | RD | | | |
|-------------------------------------|-------------------------------|--|-------------------------|--|------------------------------------|
| Area (Ha) | | 0.050 | | | |
| C = | | 0.90 | | Restricted Flow Q _r (L/s)= 8.00 | |
| 2-Year Ponding | | | | | |
| T _c Variable (min) | i _{2yr} (mm/hour) | Peak Flow Q _p =2.78xCi _{2yr} A (L/s) | Q _r (L/s) | Q _p -Q _r (L/s) | Volume 2yr (m ³) |
| 2 | 133.33 | 16.68 | 8.00 | 8.68 | 1.04 |
| 4 | 111.72 | 13.98 | 8.00 | 5.98 | 1.43 |
| 5 | 103.57 | 12.96 | 8.00 | 4.96 | 1.49 |
| 6 | 96.64 | 12.09 | 8.00 | 4.09 | 1.47 |
| 8 | 85.46 | 10.69 | 8.00 | 2.69 | 1.29 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 1.49 | 11.25 | 0.00 | 0.00 |

| Drainage Area | | EXTERNAL | | | |
|----------------------------|------------------------|---|----------------|--------------------|----------------------------|
| Area (Ha) | 1.550 | | | | |
| C = | 0.80 | Restricted Flow Q_r (L/s)= | | 291.58 | |
| 2-Year Ponding | | | | | |
| T_c Variable (min) | i_{2yr} (mm/hour) | Peak Flow $Q_p=2.78Ci_{2yr}A$ (L/s) | Q_r (L/s) | Q_p-Q_r (L/s) | Volume 2yr (m^3) |
| 0 | 167.22 | 576.45 | 291.58 | 284.87 | 0.00 |
| 2 | 133.33 | 459.62 | 291.58 | 168.04 | 20.16 |
| 3 | 121.46 | 418.71 | 291.58 | 127.13 | 22.88 |
| 4 | 111.72 | 385.13 | 291.58 | 93.55 | 22.45 |
| 6 | 96.64 | 333.13 | 291.58 | 41.55 | 14.96 |

| Storage (m^3) | | | | |
|-------------------|----------|---------|-------------|---------|
| Overflow | Required | Surface | Sub-surface | Balance |
| 0.00 | 22.88 | 270.00 | 0.00 | 0.00 |

APPENDIX F

- **Drawing 119351-001 – Site Servicing Plan**
- **Drawing 119351-010 – Details and Notes**
- **Drawing 119351-200 – Site Grading Plan**
- **Drawing 119351-600 – Ponding Plan**
- **Drawing 119351-900 – Erosion and Sedimentation Control Plan**

DRAWING NOTES

1.0 GENERAL

- 1.1 CONTRACTOR TO VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION.
- 1.2 DO NOT SCALE DRAWINGS.
- 1.3 CONTRACTOR TO REPORT ALL DISCOVERIES OR OMISSIONS OR DISCREPANCIES TO THE ARCHITECT OR DESIGN ENGINEER AS APPLICABLE.
- 1.4 USE ONLY THE LATEST REVISED DRAWINGS OR THOSE THAT ARE MARKED "ISSUED FOR CONSTRUCTION".
- 1.5 ALL CONSTRUCTION SHALL COMPLY WITH CURRENT CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.
- 1.6 THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ALL RELEVANT DRAWINGS AND SPECIFICATIONS.
- 1.7 FOR LEGAL SURVEY INFORMATION REFER TO REGISTERED PLAN.
- 1.8 REFER TO SITE PLAN BY S. J. LAWRENCE ARCHITECT INCORPORATED.

1.9 CONTRACTOR TO IMPLEMENT EROSION AND SEDIMENT CONTROL MEASURES AS IDENTIFIED IN THE EROSION AND SEDIMENT CONTROL PLAN TO THE SATISFACTION OF THE CITY OF OTTAWA. PRIOR TO UNDERTAKING ANY SITE ALTERATIONS INCLUDING GRADING, REMOVAL OF VEGETATION, ETC., DURING ALL PHASES OF THE SITE PREPARATION AND CONSTRUCTION THE MEASURES ARE TO BE MAINTAINED TO THE SATISFACTION OF THE ENGINEER AND CITY OF OTTAWA IN ACCORDANCE WITH THE BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL. SHOULD ANY ADDITIONAL MEASURES BE REQUIRED TO ADDRESS FIELD CONDITIONS THEY SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER OR THE CITY OF OTTAWA. SUCH ADDITIONAL MEASURES MAY INCLUDE BUT NOT BE LIMITED TO INSTALLATION OF FILTER CLOTHS ACROSS MANHOLE AND CATCH-BASIN LIDS TO PREVENT SEDIMENT FROM ENTERING THE STRUCTURE AND INSTALLATION AND MAINTENANCE OF A LIGHT DUTY SILT FENCE BARRIER AS REQUIRED.

1.10 ALL IRON WORK ELEVATIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR ADJUSTMENTS AS DETERMINED BY THE ENGINEER.

1.11 ALL CONCRETE CURBS AND SIDEWALKS TO CONFORM TO CITY STANDARDS SC1.1 AND SC1.4. ALL ONSITE CURBS TO BE BARRIER TYPE, WITH DEPRESSIONS AS NOTED.

1.12 ALL CONCRETE SHALL BE "NORMAL PORTLAND CEMENT" IN ACCORDANCE WITH O.P.S.S. 1350 AND SHALL ACHIEVE A MINIMUM STRENGTH OF 30MPa AT 28 DAYS.

1.13 ALL CONSTRUCTION TRAFFIC TO ACCESS SITE FROM BANK STREET.

1.14 FOR GEOTECHNICAL REPORT SEE GEOTECHNICAL INVESTIGATION PROPOSED COMMERCIAL DEVELOPMENT - 4836 BANK STREET, OTTAWA, ON, REPORT NO. PG2934-LET.01 REVISION 1 BY PATERSON GROUP DATED NOV. 19, 2019. FOR GEOTECHNICAL REPORT ON DUN SKIPPER DRIVE SEE GEOTECHNICAL INVESTIGATION PROPOSED RESIDENTIAL DEVELOPMENT REMER LANDS OTTAWA, ONTARIO REPORT #13-121-0083 (10402945) PREPARED BY GOLDER ASSOCIATES.

1.15 CONTRACTOR TO PROTECT EXISTING INFRASTRUCTURE AND PROPERTY SUCH AS TREES, PARKING METERS, SIDEWALKS, CURBS, ASPHALT AND STREET SIGNS FROM DAMAGE DURING CONSTRUCTION. CONTRACTOR TO PAY THE COST TO REINSTATE OR REPLACE ANY DAMAGED INFRASTRUCTURE OR PROPERTY TO THE SATISFACTION OF THE CITY.

1.16 THE POSITION OF POLE LINES, CONDUITS, WATERMAIN, SEWERS, AND OTHER UNDERGROUND AND ABOVEGROUND UTILITIES AND STRUCTURES ARE NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK THE CONTRACTOR SHALL INFORM ITSELF OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, SHALL PROTECT ALL UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

1.17 CONTRACTOR TO SUPPLY SUTABLE FILL MATERIAL WHERE REQUIRED TO ROUGH GRADE THE SITE. ALL IMPORTED FILL MATERIAL TO BE CERTIFIED AS SPECIFIABLE BY THE GEOTECHNICAL ENGINEER.

1.18 CONTRACTOR TO HAIL EXCESS MATERIAL OFFSITE AS NECESSARY TO GRADE SITE TO MEET THE PROPOSED GRADES. ALL EXCESS MATERIAL TO BE HAILED OFFSITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY CONTAMINATED WATER, THE CONTRACTOR IS TO NOTIFY ENGINEER, ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.

1.19 FILL MATERIAL WITHIN THE PARKING LOT AND BUILDING PAD AREAS, AND SUPPORTING BUILDING FOUNDATIONS SHALL BE COMPACTED TO 98% STANDARD MODIFIED PROCTOR DENSITY AND TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER.

1.20 ALL COMPACTION METHODS TO BE PERFORMED TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO INCLUDE BUT NOT BE LIMITED TO THE THICKNESS OF LIFTS, AND COMPACTION EQUIPMENT USED.

1.21 ALL DISTURBED BOULEVARDS TO BE REINSTITED WITH SOD ON 100mm TOPSOIL.

1.22 UTILITY DUCTS TO BE INSTALLED PRIOR TO ROAD BASE CONSTRUCTION.

1.23 CLAY DIKES TO BE INSTALLED WHERE INDICATED ON THE DRAWINGS OR AS APPROVED AND DIRECTED BY THE GEOTECHNICAL ENGINEER. ALL IN ACCORDANCE WITH CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.

1.24 ALL UTILITY BOXES (i.e. PEDESTALS, TRANSFORMERS, ETC) ARE TO BE INSTALLED IN ACCORDANCE WITH THE LATEST EDITION OF THE CITY OF OTTAWA'S "GUIDELINES FOR UTILITY PEDESTALS WITHIN THE ROAD RIGHT OF WAY".

1.25 FOR SITE BENCH MARK SEE SURVEY BY H. A. KEN SHIPMAN SURVEYING LTD. REF. NO. GL-495.

2.0 SANITARY

2.1 ALL SANITARY SEWER MAINS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ONLY FACTORY FITTINGS TO BE USED. SEWER TO BE INSTALLED AS PER OSPS 1085.01. SANITARY SEWER MATERIALS TO BE: 200mm AND SMALLER - PVC DR 35

2.2 ALL SANITARY MAINTENANCE HOLES TO BE 1.2m DIAMETER AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, FRAME AND COVER, DROP PIPES AND LANDINGS WHERE NEEDED.

2.3 SANITARY MANHOLE COVERS TO BE CITY OF OTTAWA STD. S25 (MOD. OPSD 401.020). SANITARY MANHOLE COVER TO BE CLOSED COVER TYPE, AS PER CITY STANDARD S24.

2.4 SANITARY SEWER LEAKAGE TEST AND CCTV INSPECTION SHALL BE COMPLETED AS PER CITY SPECIFICATIONS PRIOR TO INSTALLATION OF BASE COURSE ASPHALT.

2.5 ANY STORM SEWER WITH LESS THAN 2.0m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

2.6 CONNECTION TO THE EXISTING SANITARY SEWER TO BE INCLUDED IN THE COST FOR SANITARY SEWER INSTALLATION. THIS INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARDS.

3.0 STORM

3.1 ALL STORM SEWERS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ALL STORM SEWERS TO BE INSTALLED PER MANUFACTURER'S INSTRUCTIONS. ONLY FACTORY FITTINGS TO BE USED. STORM SEWER MATERIALS TO BE: 375mm AND SMALLER - PVC DR 35 450mm AND LARGER - 100% REINFORCED CONCRETE.

3.2 ALL STORM MAINTENANCE HOLES TO BE SIZED IN ACCORDANCE WITH THE PLANS AND AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, FRAME AND COVER.

3.3 STORM MH COVERS TO BE OPEN TYPE, AS PER CITY STANDARD S24. FRAMES TO BE PER CITY OF OTTAWA STD. S25. CONTRACTOR TO INSTALL FLTER FABRIC UNDER STORM MH COVER UNTIL SODDING IS COMPLETE.

3.4 STORM MAINTENANCE HOLES TO BE OPSD, SIZE AS SPECIFIED, TAPER TOP.

3.5 ALL CATCH BASINS TO BE AS PER OPSD 705.010. FRAME & FISH TYPE GRATE AS PER CITY OF OTTAWA STD. S18.1.

3.6 150mm DIAMETER SOCK-WRAPPED PERFORATED PG SUBDRAINS TO BE INSTALLED AT THE LIMIT OF THE HEAVY DUTY ROAD STRUCTURE WHERE IT MEETS THE LIGHT DUTY ROAD STRUCTURE AND AT ALL C/S IN HEAVY DUTY ROADS AS IDENTIFIED ON PLAN. SUBDRAINS TO DISCHARGE TO C/S AS SHOWN.

3.7 ANY STORM SEWER WITH LESS THAN 2.0m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

3.8 CONNECTION TO THE EXISTING STORM SEWER TO BE INCLUDED IN THE COST FOR STORM SEWER INSTALLATION. THIS INCLUDES REINSTATEMENT OF ROAD CUT TO CITY STANDARDS.

3.9 CONTRACTOR TO PROVIDE IPX-TEMPEST MHF ICD'S SHOP DRAWINGS, OR EQUIVALENT, FOR ENGINEERS REVIEW PRIOR TO ORDERING ICD'S.

4.1 ALL WATERMANS TO BE PVC DR 18, WITH MINIMUM COVER OF 2.4m AND INSTALLED PER CITY OF OTTAWA STANDARDS. THIS INCLUDES REINSTATEMENT OF ROAD CUT TO CITY STANDARDS.

4.2 THRUST BLOCKS TO BE INSTALLED AT ALL BENDS, TEES, AND CAPS ALL TO CITY STANDARDS W25.3 AND W25.4.

4.3 CONTRACTOR TO CONDUCT PRESSURE AND LEAKAGE TESTING OF ALL WATERMANS AND DISINFECT AND CHLORINATE ALL WATERMANS TO THE SATISFACTION OF M.O.E. AND THE CITY OF OTTAWA.

4.4 TRACER WIRE TO BE INSTALLED ALONG THE FULL LENGTH OF WATERMAIN AND ATTACHED TO EACH MAIN STOP AS PER CITY OF OTTAWA STANDARD W36.

4.5 ALL COMPONENTS OF THE WATER DISTRIBUTION SYSTEM SHALL BE CATHODICALLY PROTECTED AS PER CITY OF OTTAWA STANDARD W46.

4.6 ALL VALVES & VALVE BOXES AND CHAMBERS, HYDRANTS, AND HYDRANT VALVES AND ASSEMBLIES SHALL BE INSTALLED AS PER CITY OF OTTAWA STANDARDS W19 & W24.

4.7 ANY WATERMAIN WITH LESS THAN 2.4m COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.

4.8 CONTRACTOR IS RESPONSIBLE FOR ACQUIRING THE WATER PERMIT FROM THE CITY OF OTTAWA AND PAYMENT OF ANY FEES ASSOCIATED WITH SECURING THE WATER PERMIT. OWNER IS RESPONSIBLE FOR REIMBURSING THE CONTRACTOR FOR THE ACTUAL COST OF ACQUIRING THE WATER PERMIT.

4.9 CONNECTION TO EXISTING WATERMAIN TO BE INCLUDED IN THE COST FOR THE WATERMAIN INSTALLATION. THIS COST INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARD R10.

5.0 PARKING LOT AND WORK IN PUBLIC RIGHTS OF WAY

5.1 CONTRACTOR TO REINSTATE ROAD CUTS PER CITY OF OTTAWA STANDARD R-10.

5.2 THE CONTRACTOR SHALL PREPARE A TRAFFIC MANAGEMENT PLAN FOR REVIEW AND APPROVAL BY THE CITY OF OTTAWA. CONTRACTOR TO MAINTAIN TRAFFIC FLOW DURING THE ENTIRE CONSTRUCTION PERIOD. MAINTENANCE OF ROAD CUTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. PROVISION OF FLAGMEN, DISCOURS AS NECESSARY, BARRICADES AND SIGNS TO THE FULL SATISFACTION OF THE ENGINEER AND ROAD AUTHORITY SHALL BE THE CONTRACTOR'S RESPONSIBILITY.

5.3 CONTRACTOR TO PREPARE SUBGRADE, INCLUDING PROOFROLLING, TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER PRIOR TO THE COMMENCEMENT OF PLACEMENT OF GRANULAR B MATERIAL.

5.4 FILL TO BE PLACED AND COMPACTED PER THE GEOTECHNICAL REPORT REQUIREMENTS.

5.5 CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR B MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR B MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

5.6 GRANULAR A MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR A PLACEMENT.

5.7 CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR A MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR A MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

5.8 ASPHALT MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR A PLACEMENT.

5.9 CONTRACTOR TO SUPPLY, PLACE AND COMPACT ASPHALT MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF ASPHALT MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.

5.10 CONTRACTOR IS RESPONSIBLE FOR ESTABLISHING LINE AND GRADE IN ACCORDANCE WITH THE PLANS, AND FOR PROVIDING THE ENGINEER WITH VERIFICATION PRIOR TO PLACEMENT.

5.11 DITCHES DISTURBED DURING CULVERT INSTALLATION AND GRADING OPERATIONS ARE TO BE REINSTITED TO THEIR ORIGINAL CONDITION AND FLOWLINE GRADES.

5.12 EXISTING EAST SIDE ROAD DITCH ALONG PALLADIUM DRIVE TO BE RE-OPENED AS PER THE GRADING PLAN. ADJACENT AREAS BETWEEN ROAD SIDE DITCH AND PARKING LOT TO BE RE-GRADED AS PER THE GRADING PLAN. ALL RE-GRADED AREAS IN EXISTING PUBLIC RIGHTS OF WAY AND ANY OTHER DISTURBED AREAS IN EXISTING PUBLIC RIGHTS OF WAY ARE TO BE FINISHED WITH SOD ON 100mm TOPSOIL.

5.13 ALL EXCESS MATERIAL TO BE HAILED OFFSITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY HAZARDOUS MATERIAL, CONTRACTOR IS TO NOTIFY ENGINEER, ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.


5.14 PAYMENT STRUCTURE (MATERIAL TYPES AND THICKNESSES) FOR HEAVY DUTY AND LIGHT DUTY AREAS TO BE AS SPECIFIED IN THE GEOTECHNICAL REPORT AND SHOWN ON THE PLANS.

| CATCH BASIN DATA TABLE | | | | | | | | | | |
|------------------------|---------|--------------|-------------|--------------|--------|---------|---------------|-----------|-------|-------|
| STRUCTURE ID | AREA ID | STRUCTURE | COVER | ELEVATION | | | OUTLET PIPE | | HEAD | FLOW |
| | | | | TOP OF GRATE | INVERT | OUTLET | DIAMETER (mm) | TYPE | | |
| CB1 | MH8 | OPSD 705.010 | S19 | 102.05 | | 100.570 | 200 | HDPE PERF | 1.65 | 13.00 |
| CB2 | MH9B | OPSD 705.010 | S19 | 101.75 | | 100.350 | 200 | HDPE PERF | | |
| CB3 | MH9 | OPSD 705.010 | S19 | 102.45 | | 100.950 | 200 | PVC DR-35 | 1.65 | 10.00 |
| CB4 | MH10A | OPSD 705.010 | S19 | 102.50 | | 101.200 | 200 | PVC DR-35 | 1.4 | 6.00 |
| CB5 | CBMH1A | OPSD 705.010 | S19 | 101.33 | | 99.980 | 200 | PVC DR-35 | 1.4 | 15.00 |
| CB6 | CBMH1B | OPSD 705.010 | S19 | 101.45 | | 100.200 | 200 | PVC DR-35 | 1.4 | 20.00 |
| CB7 | CBMH1C | OPSD 705.010 | S19 | 101.30 | | 100.050 | 200 | PVC DR-35 | 1.4 | 30.00 |
| CB8 | MH1B | OPSD 705.010 | S19 | 100.60 | | 99.400 | 200 | PVC DR-35 | 1.4 | 47.00 |
| CB9 | MH1A | OPSD 705.010 | S19 | 100.66 | | 99.420 | 200 | PVC DR-35 | 1.35 | 43.00 |
| CB10 | MH1D | OPSD 705.010 | S19 | 100.40 | | 98.850 | 200 | PVC DR-35 | 1.65 | 45.00 |
| CB11 | MH1E | OPSD 705.010 | S19 | 100.55 | | 98.930 | 200 | PVC DR-35 | 1.65 | 15.00 |
| CB12 | MH2B | OPSD 705.010 | S19 | 100.40 | | 99.100 | 200 | PVC DR-35 | | |
| CB13 | MH3 | OPSD 705.010 | S19 | 100.30 | 99.000 | 99.000 | 200 | PVC DR-35 | 1.5 | 36.00 |
| CB14 | MH4 | OPSD 705.010 | S19 | 100.45 | | 99.000 | 200 | PVC DR-35 | 1.5 | 37.00 |
| CB15 | CBMH3B | OPSD 705.010 | S19 | 100.92 | | 99.470 | 200 | PVC DR-35 | 1.65 | 6.00 |
| CB16 | MH5B | OPSD 705.010 | S19 | 100.65 | | 100.020 | 200 | PVC DR-35 | 1.65 | 6.00 |
| CB17 | MH5A | OPSD 705.010 | S19 | 101.35 | | 99.690 | 200 | PVC DR-35 | 1.65 | 6.00 |
| CB18 | MH11 | OPSD 705.010 | S19 | 100.03 | | 98.320 | 200 | PVC DR-35 | 1.65 | 15.00 |
| CBMH1 | MH10B | OPSD 701.010 | S25 & S28.1 | Open | 102.21 | 99.795 | 250 | PVC DR-35 | 2.54 | 20.0 |
| CBMH2 | CBMH2 | OPSD 701.010 | S25 & S28.1 | Open | 101.50 | 99.016 | 300 | PVC DR-35 | 2.834 | 20.0 |
| CBMH3 | CBMH3A | OPSD 701.010 | S25 & S28.1 | Open | 100.45 | 98.705 | 200 | PVC DR-35 | 2.045 | 6.0 |
| TCB1 | MH11 | CITY STD S29 | S30/S31 | 98.70 | | 97.700 | 450 | HDPE PERF | | |
| ECB2 | MH11 | CITY STD S29 | S30/S31 | 100.04 | | 98.300 | 450 | HDPE PERF | | |

Bold font indicates CB's with ICD's


Revision: 2020-04-20

| WATERMAIN SCHEDULE | | | | | | |
|--------------------|----------|--|--------------------|------------------|-----------------|--------------------|
| | STATION | DESCRIPTION | FINISHED GRADE (m) | TOP OF WATERMAIN | WATERMAIN COVER | AS-BUILT WATERMAIN |
| A | 0+000 | CONNECT TO EX. 400Ø W/M | 101.45 | 99.16 | 2.29 | |
| | 0+008.59 | 200Ø V&VB | 101.67 | 99.27 | 2.40 | |
| | 0+020 | -- | 101.57 | 99.17 | 2.40 | |
| | 0+024.72 | 200Ø x 150Ø HYDRANT TEE | 101.76 | 99.36 | 2.40 | |
| B | 0+034.70 | 150Ø x 200Ø TEE | 102.05 | 99.65 | 2.40 | |
| | 0+040 | -- | 102.21 | 99.81 | 2.40 | |
| | 0+048.82 | 200Ø -- 11 1/4" BEND | 102.42 | 100.02 | 2.40 | |
| | 0+050.57 | 200Ø x 200Ø TEE | 102.45 | 100.05 | 2.40 | |
| C | 0+052.57 | 200Ø V&VB | 102.46 | 100.06 | 2.40 | |
| | 0+060 | -- | 102.55 | 100.15 | 2.40 | |
| | 0+080 | -- | 102.65 | 100.25 | 2.40 | |
| | 0+97.676 | 200Ø x 150Ø HYDRANT TEE | 102.68 | 100.28 | 2.40 | |
| | 0+100 | -- | 102.68 | 100.28 | 2.40 | |
| | 0+100.58 | 200Ø x 200Ø TEE DOMESTIC WATER SERVICE | 102.70 | 100.30 | 2.40 | |
| | 0+120 | -- | 102.70 | 100.30 | 2.40 | |
| | 0+133.06 | 200Ø -- 11 1/4" BEND | 102.56 | 100.16 | 2.40 | |
| | 0+136.02 | -- | 102.56 | 100.16 | 2.40 | |
| | 0+142.04 | 200Ø x 200Ø TEE | 102.42 | 100.02 | 2.40 | |
| | 0+143.71 | 200Ø V&VB | 102.37 | 99.97 | 2.40 | |
| | 0+144.76 | 200Ø CAP | 102.33 | 99.93 | 2.40 | |
| E | | | | | | |
| | 0+000 | 200Ø x 200Ø TEE | 102.45 | 100.05 | 2.40 | |
| | 0+001.61 | 200Ø -- 11 1/4" BEND | 102.39 | 99.99 | 2.40 | |
| | 0+004.04 | 200Ø V&VB | 102.34 | 99.94 | 2.40 | |
| | 0+020 | -- | 101.91 | 99.51 | 2.40 | |
| | 0+040 | -- | 101.35 | 98.95 | 2.40 | |
| | 0+056.69 | 200Ø x 150Ø HYDRANT TEE | 100.90 | 98.50 | 2.40 | |
| | 0+060 | -- | 100.74 | 98.34 | 2.40 | |
| | 0+062.44 | -- | 100.66 | 98.26 | 2.40 | |
| | 0+081.06 | 200Ø -- 22 1/2" BEND | 100.47 | 98.07 | 2.40 | |
| | 0+084.95 | 200Ø -- 22 1/2" BEND | 100.44 | 98.04 | 2.40 | |
| | 0+088.64 | 200Ø -- 11 1/4" BEND | 100.40 | 98.00 | 2.40 | |
| | 0+093.48 | 200Ø x 200Ø TEE DOMESTIC WATER SERVICE | 100.41 | 98.01 | 2.40 | |
| | 0+096.06 | 200Ø -- 22 1/2" BEND | 100.44 | 98.04 | 2.40 | |
| | 0+099.51 | 200Ø -- 22 1/2" BEND | 100.47 | 98.07 | 2.40 | |
| | 0+120 | -- | 100.56 | 98.16 | 2.40 | |
| | 0+130.23 | 200Ø x 150Ø HYDRANT TEE | 100.66 | 98.26 | 2.40 | |
| | 0+136.32 | 200Ø x 200Ø TEE DOMESTIC WATER SERVICE | 100.82 | 98.42 | 2.40 | |
| | 0+140 | -- | 100.85 | 98.45 | 2.40 | |
| | 0+160 | -- | 100.88 | 98.48 | 2.40 | |
| | 0+171.94 | 200Ø -- 11 1/4" BEND | 100.97 | 98.57 | 2.40 | |
| | 0+174.66 | 200Ø V&VB | 100.98 | 98.58 | 2.40 | |
| | 0+177.30 | 200Ø x 200Ø CROSS | 101.03 | 98.63 | 2.40 | |
| | 0+179.04 | 200Ø V&VB | 101.01 | 98.61 | 2.40 | |
| G | 0+182.36 | 200Ø CAP | 100.89 | 98.49 | 2.40 | |
| H | 0+000 | CONNECT TO EX. 400Ø W/M | 101.05 | 97.80 | 3.25 | |
| | 0+008.79 | 200Ø V&VB | 101.06 | 98.66 | 2.40 | |
| | 0+012.26 | 200Ø -- 11 1/4" BEND | 101.04 | 98.64 | 2.40 | |
| | 0+020 | -- | 100.96 | 98.56 | 2.40 | |
| F | 0+043.52 | 200Ø x 200Ø CROSS | 101.03 | 98.63 | 2.40 | |
| | 0+048.81 | -- | 101.12 | 98.72 | 2.40 | |
| | 0+058.52 | 200Ø V&VB | 101.22 | 98.82 | 2.40 | |
| | 0+060 | -- | 101.23 | 98.83 | 2.40 | |
| | 0+080 | -- | 101.41 | 99.01 | 2.40 | |
| | 0+100 | -- | 101.73 | 99.33 | 2.40 | |
| | 0+120 | -- | 102.23 | 99.83 | 2.40 | |
| | 0+133.36 | 200Ø V&VB | 102.42 | 100.02 | 2.40 | |
| D | 0+137.59 | 200Ø x 200Ø TEE | 102.42 | 100.02 | 2.40 | |
| B | 0+000 | 150Ø x 200Ø TEE | 102.05 | 99.65 | 2.40 | |
| | 0+003 | 150Ø V&VB | 102.09 | 99.69 | 2.40 | |
| | 0+020 | -- | 102.33 | 99.93 | 2.40 | |
| | 0+025.62 | 150Ø x 150Ø TEE DOMESTIC WATER SERVICE | 102.31 | 99.91 | 2.40 | |
| I | 0+028.10 | 150Ø CAP | 102.29 | 99.89 | 2.40 | |




NOTES:
1. Number of bales varies to suit ditch.
2. Straw bales to be butted tightly against adjoining bales and shaped to conform to the sides of the ditch to prevent water flow through barrier.
A. All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING Nov 2006 Rev 1
STRAW BALE FLOW CHECK DAM
OPSD 219.180




NOTE:
A. All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING Nov 2006 Rev 1
LIGHT-DUTY SILT FENCE BARRIER
OPSD 219.110




NOTE:
A. All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING Nov 2006 Rev 1
ROCK FLOW CHECK DAM
V-DITCH
OPSD 219.210



- NOTES:
- SILT FENCE TO BE ERECTED PRIOR TO EARTH WORKS BEING COMMENCED. SILT FENCE TO BE MAINTAINED UNTIL VEGETATION IS ESTABLISHED OR UNTIL START OF SUBSEQUENT PHASE.
 - STRAW BALE SEDIMENT TRAPS TO BE CONSTRUCTED IN EXISTING ROAD SIDE DITCHES. TRAPS TO REMAIN AND BE MAINTAINED UNTIL VEGETATION IS ESTABLISHED.
 - SILT SACK TO BE PLACED AND MAINTAINED UNDER COVER OF ALL CATCHBASINS. GEOTEXTILE SILT SACK IN STREET C/S TO REMAIN UNTIL ALL CURBS ARE CONSTRUCTED. GEOTEXTILE FABRIC IN RYOBs TO REMAIN UNTIL VEGETATION IS ESTABLISHED. ALL CATCHBASINS TO BE REGULARLY INSPECTED AND CLEANED, AS NECESSARY, UNTIL SOD AND CURBS ARE CONSTRUCTED.
 - WORKS NOTED ABOVE ARE TO BE INSTALLED, INSPECTED, MAINTAINED AND ULTIMATELY REMOVED BY SERVICING CONTRACTOR.
 - THIS IS A "LIVING DOCUMENT" AND MAY BE MODIFIED IN THE EVENT THE PROPOSED CONTROL MEASURES ARE INSUFFICIENT.
 - THE CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES, TO PROVIDE FOR PROTECTION OF THE AREA DRAINAGE SYSTEM AND THE RECEIVING WATERCOURSE, DURING CONSTRUCTION ACTIVITIES. THE CONTRACTOR ACKNOWLEDGES THAT FAILURE TO IMPLEMENT APPROPRIATE EROSION AND SEDIMENT CONTROL MEASURES MAY BE SUBJECT TO PENALTIES IMPOSED BY ANY APPLICABLE REGULATORY AGENCY.



KEY PLAN
(NTS)


NOTES:
1. SEE DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.
2. SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR H.A. KEN SHIPMAN SURVEYING LTD.

- LEGEND:
- LIGHT DUTY SILT FENCE AS PER OPSD-219.110
 - SNOW FENCE
 - STRAW BALE CHECK DAM AS PER OPSD-219.180
 - ROCK CHECK DAM AS PER OPSD-219.210
 - SILT SACK PLACED UNDER EXISTING CB COVER
 - TEMPORARY MUD MAT 0.15m THICK 50mm CLEAR STONE ON NON WOVEN FILTER CLOTH

| | | | |
|-----|--|-----|------------|
| 14 | | | |
| 13 | | | |
| 12 | | | |
| 11 | | | |
| 10 | | | |
| 9 | | | |
| 8 | | | |
| 7 | | | |
| 6 | | | |
| 5 | | | |
| 4 | | | |
| 3 | REVISED AS PER CITY COMMENTS | JIM | 2020-04-20 |
| 2 | REVISED AS PER NEW SITE PLAN AND CITY COMMENTS | JIM | 2019-10-11 |
| 1 | ISSUED FOR SPA | JIM | 2019-04-15 |
| No. | REVISIONS | By | Date |

IBI GROUP
400 - 333 Preston Street
Oshawa ON K1S 5N4 Canada
tel 613 225 1311 fax 613 225 9868
ibigroup.com

Project Title
BANK STREET DEVELOPMENT
4836 BANK STREET



Drawing Title
EROSION AND SEDIMENTATION CONTROL PLAN

Scale
1 : 500

| | | | |
|-------------|--------|-------------|-----------|
| Design | SEL | Date | FEB. 2019 |
| Drawn | DPS | Checked | JIM |
| Project No. | 119351 | Drawing No. | 900 |