



NOT FOR  
CONSTRUCTION

[illegible]

# PLANTING NOTES

1. This drawing shall be read in conjunction with all relevant Engineering, and related drawings and documents.
2. Refer to Engineering Drawings for Grading. Provide drainage as indicated in grading plan. Round all tops and toes of slopes, smoothly. Contact all areas to 95% Standard Proctor Density unless otherwise noted.
3. Refer to Engineering Drawings for site servicing.
4. Contractor must contact utility companies for locates prior to excavation or planting.
5. It is essential to use the plans and details in conjunction with the specifications and notes.
6. Existing trees to be retained shall be protected according to the contract detail and specifications.
7. Plant material shall be No. 1 Grade and shall comply with Canadian Standards for Nursery Stock (latest edition) published by the Canadian Nursery Landscape Association.
8. Use plant material with strong fibrous root system free of disease, defects or injuries, and structurally sound. Use trees with straight trunks, well and characteristically branched for species. Obtain approval from consultant of plant material at source prior to digging. All trees and shrubs shall be container grown, potted, W/B or RB, as indicated on Plant List. Bare root planting will only be acceptable for certain species and as approved by the Landscape Architect.
9. Plant material substitutions shall not be permitted without the written approval from the consultant, **with 48 hours notice**, prior to shipping plant material.
10. Plant locations are schematic / approximate only. **Contractor shall stake out locations on site for approval by the Landscape Architect prior to installation.** The illustrated number of plants shown in the Planting Plan supersedes the estimated number in the Plant List. Contractor to report any discrepancies to the Landscape Architect prior to installation. Contractor will assume full responsibility if the Landscape Architect is not notified.
11. Shrubs, Perennials, Vines, and Groundcovers shall be planted in a continuous planting bed of **450mm** depth with approved topsoil covered with **75mm** depth shredded bark mulch.
12. Ensure trees are thoroughly watered following planting. Monitor material and ensure adequate moisture until acceptance.
13. In heavy clay or poorly drained soils, set root ball with root collar 75-100mm higher than finished grade.
14. Sod and/or seed areas to receive **150mm** depth topsoil as specified. Sod shall be No. 1 Kentucky Bluegrass Sod grown from minimum mixture of 3 cultivars and 3 seed sources. Quality and source shall comply with Canadian Standards for Nursery Stock, Section 17, (latest edition) published by the Canadian Nursery Landscape Nursery Landscape Association. Unless otherwise specified, turf to be maintained by the contractor until a second cutting is accepted by the Landscape Architect.
15. Apply the following minimum fertilizer unless soil tests show other requirements: Sodded areas - (8-32-16) 8% Nitrogen, 32% Phosphorus, 16% Potash at a rate of 350kg/ha. • Planting Beds - (8-32-16) - 8% Nitrogen, 32% Phosphorus, 16% Potash as per manufacturer specifications.
16. Reinststate all areas damaged or disturbed beyond the Limit of Work.
17. Refer to specifications:  
NOVA 8020 Imported Topsoil  
NOVA 8030 Sod  
NOVA 8040 Seed and Cover (Hydraulic Seeding)  
NOVA 8060 Trees, Shrubs and Groundcover Planting  
NOVA 8061 Maintenance of Planting

|   |                              |
|---|------------------------------|
| LOCATION<br>CITY OF OTTAWA<br>6793 HIRAM DRIVE                                  |                              |
| DRAWING NAME<br><br>PROPOSED HEAVY EQUIPMENT<br>REPAIR GARAGE<br>LANDSCAPE PLAN | PROJECT No.<br><br>119060-00 |
|   | REV<br><br>REV #4            |
|   | DRAWING No.<br><br>119060-1  |