

WALL ASSEMBLY NOTES:

- FW1** EXISTING RUBBLE / BLOCK FOUNDATION WALL
-CEMENT PARGING TO EXTEND 6" BELOW GRADE
-PLATON DAMPROOFING SYSTEM BELOW GRADE
-24" STONE FOUNDATION OR 8" CONCRETE BLOCK (SEE PLANS FOR THICKNESS)
-#15 BUILDING PAPER FROM FINISHED GRADE TO SLAB.
-1" AIR SPACE
-2x4 STUDS 16" o.c.
-SPRAY FOAM INSULATION 'POLYISO' MIN R10ci W/ R12
-6 mil. POLY VAPOUR BARRIER SEALED TO FOUNDATION WALL.
-1/2" GYPSUM BOARD
- W1** MASONRY VENEER EXTERIOR WALL
-EXISTING DOUBLE BRICK WALL c/w BRICK TIES PROVIDE WEEP/VENT HOLES AT 24" o.c.
-EXISTING BRICK COVERED WITH 1X3 STRAPPING & CORRUGATED STEEL SIDING WHERE SHOWN
-1" RIGID INSULATION - MIN R5 CI
-2x4 STUDS @16" o.c
-5 1/2" R24 BATT INSULATION
-6 mil. POLY VAPOUR BARRIER
-1/2" GYPSUM BOARD
- W2** MASONRY VENEER EXTERIOR WALL
-STONE VENEER c/w BRICK TIES PROVIDE WEEP/VENT HOLES AT 24" o.c.
-1" AIR SPACE
-1" RIGID INSULATION - MIN R5 CI
-TYVEK WEATHER AIR BARRIER
-7/16" O.S.B. SHEATHING
-2x6 STUDS @16" o.c
-5 1/2" R24 BATT INSULATION
-6 mil. POLY VAPOUR BARRIER
-1/2" GYPSUM BOARD
- W3** METAL SIDING EXTERIOR WALL
-METAL SIDING (AS PER CLIENT)
-1X3 STRAPPING @ 16" O/C
-1" RIGID INSULATION - MIN R5 CI
-TYVEK WEATHER AIR BARRIER
-7/16" O.S.B. SHEATHING
-2x6 STUDS @16" o.c
-5 1/2" R24 BATT INSULATION
-6 mil. POLY VAPOUR BARRIER
-1/2" GYPSUM BOARD
- W4** METAL SIDING EXTERIOR WALL - NON COMBUSTIBLE
-METAL SIDING (AS PER CLIENT)
-1X3 STRAPPING @ 16" O/C
-1" RIGID INSULATION - MIN R5 CI
-TYVEK WEATHER AIR BARRIER
-5/8" TYPE X DENSGLASS FIREGUARD SHEATHING
-2 LAYERS 5/8" TYPE X GYPSUM BOARD
-2x6 STEEL STUDS @16" O/C
-5 1/2" R24 ROXUL BATT INSULATION
-6 mil. POLY VAPOUR BARRIER
-2 LAYERS 5/8" TYPE X GYPSUM BOARD
- W5** 2x4 INTERIOR PARTITION
-1/2" GYPSUM BOARD
-2x4 STUDS @16" o.c. W/ SAFE N SOUND BATT INSULATION AROUND BATHS
-1/2" GYPSUM BOARD
- W6** INTERIOR PARTITION - SB-3 - W4B: FRR 1 HR, STC 54
-5/8" GYPSUM BOARD
-2x4 OR 2X6 STUDS @16" o.c. W/ ROXUL BATT INSULATION
-1/2" RESILIENT CHANNELS
-RESILIENT METAL CHANNELS @ 16" O/C
-2 LAYERS 5/8" TYPE X GYPSUM BOARD (CONTINUOUS)

FLOOR ASSEMBLY NOTES:

- F1** GROUND & SECOND FLOOR
-FLOOR FINISH (AS PER OWNER'S INSTRUCTION)
-EXISTING 2X10 OR 2X8 WD FLOOR JOISTS @ 20" O/C
-ROXUL BATT INSULATION
-RESILIENT METAL CHANNELS @ 16" O/C
-2 LAYERS 5/8" TYPE X GYPSUM BOARD (CONTINUOUS)
- F2** ADDITION GROUND FLOOR
-FLOOR FINISH (AS PER OWNER'S INSTRUCTION)
-5/8" T&G, G1S OSB SUBFLOOR
-PRE-ENGINEERED FLOOR JOISTS AS PER MANU. SPECS.
-SPRAY FOAM INSULATION 'POLYISO' min. 5 1/2" THICK R-30
-1/2" EXT. GRADE PLYWOOD
- F3** ADDITION FLOOR - SB-3 - F28C: 1 HR, FRR / STC 54
-FLOOR FINISH (AS PER OWNER'S INSTRUCTION)
-5/8" T&G, G1S OSB SUBFLOOR
-PRE-ENGINEERED FLOOR JOISTS AS PER MANU. SPECS.
-ROXUL BATT INSULATION
-RESILIENT METAL CHANNELS @ 16" O/C
-2 LAYERS 5/8" TYPE X GYPSUM BOARD (CONTINUOUS)

ROOF ASSEMBLY NOTES:

- R1** NEW FLAT ROOF
-2PLY MODIFIED BITUMEN MEMBRANE
-ICE / WATER SHIELD TO EXTEND 30" PAST OUTER WALL
-7/16" O.S.B. SHEATHING INSTALLED WITH "H CLIPS" BETWEEN TRUSSES
-PRE ENGINEERED STRUCTURAL ROOF TRUSS SYSTEM
-SPRAY FOAM INSULATION 'POLYISO' - R-40 MIN.
-INSULATION DEPRESSORS TO PROVIDE 2 1/2" OF VENTILATION ON ALL ROOF SLOPES
-6 MIL. POLYETHYLENE VAPOR BARRIER
-1"X3" STRAPPING @ 16" O.C.
-1/2" GYPSUM BOARD



#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/20/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



Layout Page Table	
Label	Title
A0	CONSTRUCTION NOTES, ASSEMBLIES & SITE PLAN
A3.0	PROPOSED BASEMENT FLOOR PLAN
A3.1	PROPOSED GROUND FLOOR PLAN
A3.2	PROPOSED SECOND FLOOR PLAN
A3.3	PROPOSED THIRD FLOOR PLAN
A4.0	EXTERIOR ELEVATION (FRONT)
A4.1	EXTERIOR ELEVATION (LEFT)
A4.2	EXTERIOR ELEVATION (RIGHT)
A4.3	EXTERIOR ELEVATION (REAR)
A5.0	BUILDING SECTION & DETAILS

The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.



DESIGNER	BCNL
DATE	O.G.
DATE	BCNL

87 STIRLING AVENUE

CONSTRUCTION NOTES,
ASSEMBLIES & SITE PLAN

AS SHOWN	A0
JAN 30, 2019	

#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



DOOR SCHEDULE					
NUMBER	QTY	FLOOR	WIDTH	HEIGHT	DIMENSIONS
D01	1	0	26"	80"	26"x80"x1 3/8" L IN
D02	1	0	34"	80"	34"x80"x1 3/8" R IN
D03	1	0	36"	80"	36"x80"x1 3/8" L IN
D04	1	0	36"	80"	36"x80"x1 3/8" R IN
D05	1	0	42"	80"	(4) 10 1/2"x80"x1 3/8" L/R
D06	1	1	28"	80"	28"x80"x1 3/8" L IN
D07	1	1	30"	80"	30"x80"x1 3/8" L IN
D08	1	1	30"	80"	30"x80"x1 3/8" R IN
D09	1	1	32"	80"	32"x80"x1 3/8" R IN
D10	2	1	34"	80"	34"x80"x1 3/4" L EX
D11	1	1	36"	80"	(2) 18"x80"x1 3/8" L
D12	1	1	36"	80"	36"x80"x1 3/8" R IN
D13	1	1	36"	80"	36"x80"x1 3/4" L EX
D14	1	1	36"	80"	36"x80"x1 3/8" L IN
D15	3	1	48"	80"	(4) 12"x80"x1 3/8" R IN
D16	1	2	28"	80"	28"x80"x1 3/8" R IN
D17	1	2	30"	80"	(2) 15"x80"x1 3/8" L
D18	2	2	30"	80"	30"x80"x1 3/8" L IN
D19	1	2	30"	80"	30"x80"x1 3/8" R IN
D20	1	2	32"	80"	32"x80"x1 3/8" L IN
D21	1	2	32"	80"	32"x80"x1 3/8" R IN
D22	1	2	34"	84"	34"x84"x1 3/4" L EX
D23	1	2	36"	84"	36"x84"x1 3/4" L EX
D24	1	2	36"	80"	36"x80"x1 3/8" L IN
D25	1	2	36"	80"	(2) 18"x80"x1 3/8" L
D26	3	2	36"	80"	(2) 18"x80"x1 3/8" R
D27	1	3	21"	80"	(2) 10 1/2"x80"x1 3/8" L
D28	1	3	28"	80"	28"x80"x1 3/8" R
D29	3	3	30"	80"	30"x80"x1 3/8" R IN
D30	1	3	32"	80"	32"x80"x1 3/8" L IN
D31	1	3	32"	80"	32"x80"x1 3/8" R IN
D32	1	3	34"	84"	34"x84"x1 3/4" L EX
D33	2	3	36"	80"	36"x80"x1 3/8" L IN
D34	1	3	36"	84"	36"x84"x1 3/4" L EX
D35	2	3	48"	80"	(4) 12"x80"x1 3/8" L/R

WINDOW SCHEDULE					
NUMBER	QTY	FLOOR	WIDTH	HEIGHT	TOP
W01	1	0	36"	24"	88"
W02	1	0	48"	24"	88"
W03	1	0	84"	36"	84 1/2"
W04	1	1	24"	22"	102"
W05	1	1	24"	18"	80"
W06	1	1	24"	80"	80"
W07	1	1	34"	18"	98"
W08	1	1	36"	22"	102"
W09	1	1	60"	66"	96"
W10	2	1	69 15/16"	66"	98"
W11	1	1	84"	60"	102"
W12	2	2	24"	84"	84"
W13	2	2	60"	66"	96"
W14	2	2	69 15/16"	66"	84"
W15	1	2	60"	80"	84"
W16	1	3	24"	18"	80"
W17	1	3	60"	66"	96"
W18	2	3	69 15/16"	66"	84"
W19	1	3	60"	80"	84"
W20	2	3	24"	84"	84"

DEMO NOTE:

ALL EXISTING INTERIOR WALLS TO BE REMOVED
EXISTING REAR ADDITION TO BE REMOVED
EXISTING STAIR TO SECOND FLOOR AND STAIR TO
THIRD FLOOR TO BE REMOVED AND REPLACED
EXISTING WINDOWS TO BE REMOVED AND FRAMED IN
OR REPLACED WITH NEW WINDOWS UNLESS NOTED
OTHERWISE
SHADED EXTERIOR WALLS REPRESENT EXISTING WALLS
TO REMAIN

BATHROOM NOTE: (TYP.)

FINAL BATHROOM LAYOUT TO BE CONFIRMED BY OWNER/
BATHROOM DESIGNER.

(F) EXHAUST FAN TO BE VENTED TO EXTERIOR.

-PROVIDE STUD WALL REINFORCING TO PERMIT THE FUTURE
INSTALLATION OF A GRAB BAR ON A WALL ADJACENT TO A
WATER CLOSET, BATHTUB AND A SHOWER AS PER OBC 9.5.2.3.(1)
-PROVIDE WATERPROOF WALL IN SHOWER STALLS (5'11") ABOVE
THE RIM OF BATHTUBS EQUIPPED WITH SHOWERS (3'11") AND
THE RIM OF BATHTUBS NOT EQUIPPED WITH SHOWERS (15 3/4")
IN ACCORDANCE TO OBC 9.29.2.1.

GENERAL NOTES:

- SMOKE DETECTORS TO HAVE A VISUAL SIGNALING
COMPONENT AND CONFORM TO NFPA 72 - 18.5.3
-ELECTRICAL OUTLET BOXES AND OTHER PARTY WALL
PENETRATIONS SHALL BE OFFSET TO MAINTAIN INTEGRITY
OF FIRE SEPARATION. TYPICAL ALL FLOORS.
-CERAMIC TILE REQUIRES 5/8" UNDERLAY
-WATER RESISTANT FLOORING REQUIRED IN BATHROOMS,
LAUNDRY ROOMS, KITCHENS, GENERAL STORAGE AREAS &
ENTRANCE (OBC 9.30.1.2.)

STAIR NOTE: (TYP.)

STAIRS TO CONFORM TO OBC 9.8.9.
MAX RISE = 7 7/8"
MIN RUN = 8 1/4"
MIN TREAD = 9 1/4"
MIN HEADROOM = 6'5"
HANDRAIL TO CONFORM TO OBC 9.8.7.
MIN HT = 2'10"
MAX HT = 3'0"
GUARDRAIL TO CONFORM TO OBC 9.8.8.
MIN HT = 2'11"

LEGEND

PT. PRESSURE TREATED LUMBER

PL POINT LOAD ABOVE

P1 3X9X1/4" HSS

P2 2 - 2X6

P3 3 - 2X6

P4 4 - 2X6

B1 1/2X5X101 STEEL BEAM

B2 1/2X10X39 STEEL BEAM

B3 1/2X5X28 STEEL BEAM

B4 1/2X5X13 STEEL BEAM

L1 2 - 2X10 WND LINTEL

L2 2 - 2X12 WND LINTEL

L3 2 - 1 3/4" X 9 1/2" LVL 2.0 OE

F1 48"X48"X12" CONC. FOOTING W/ 3-15M E.M.

KEY TO SYMBOLS

(F) EXHAUST FAN

(CO/SD) SMOKE DETECTOR/ CARBON

MONOXIDE DETECTOR

The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER BCIN

O.G.

BCIN


87 STIRLING AVENUE

PROPOSED BASEMENT FLOOR PLAN

AS SHOWN
JAN 30, 2019
A3.0



A circular professional seal for a Licensed Professional Engineer in the Province of Ontario. The outer ring contains the text "LICENSED PROFESSIONAL ENGINEER" at the top and "PROVINCE OF ONTARIO" at the bottom. The center of the seal features the name "D. R. CLARK" and the license number "4319" which is enclosed in a stylized oval shape.



PT. PRESSURE TREATED LUMBER
PL. POINT LOAD ABOVE
P1 3X3X1/4" H55
P2 2 - 2X6
P3 3 - 2X6
P4 4 - 2X6
B1 W250X101 STEEL BEAM
B2 W810X39 STEEL BEAM
B3 W250X26 STEEL BEAM
B4 W250X73 STEEL BEAM
L1 2 - 2X10 WID LINTEL
L2 2 - 2X12 WID LINTEL
L3 2 - 1 3/4" X 9 1/2" LVL 2.0 OE
F1 48"X48"X12 CONC. FOOTING W/ 3-15M EMB
KEY TO SYMBOLS
(F) EXHAUST FAN
(C) SMOKE DETECTOR/ CARBON MONOXIDE DETECTOR

0

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525</

A3.2

#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



LEGEND

PT.	PRESSURE TREATED LUMBER
PL	POINT LOAD ABOVE
P1	3X3X1/4" HSS
P2	2 - 2X6
P3	3 - 2X6
P4	4 - 2X6
B1	1/2X25X101 STEEL BEAM
B2	1/8X10X39 STEEL BEAM
B3	1/2X25X28 STEEL BEAM
B4	1/2X25X13 STEEL BEAM
L1	2 - 2X10 W/D LINTEL
L2	2 - 2X12 W/D LINTEL
L3	2 - 1 3/4" X 9 1/2" LVL 2.0 OE
F1	48"X48"X12" CONC. FOOTING W/ 3-15M E.M.
KEY TO SYMBOLS	
(F)	EXHAUST FAN
(CO/SD)	SMOKE DETECTOR/ CARBON MONOXIDE DETECTOR

The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER BCIN

O.G.

BCIN


87 STIRLING AVENUE

PROPOSED THIRD FLOOR PLAN

AS SHOWN
JAN 30, 2019

A3.3

EXISTING BUILDING	653.8 SQ.FT.
PROPOSED BUILDING	636.8 SQ.FT.



DEMO NOTE:
ALL EXISTING INTERIOR WALLS TO BE REMOVED
EXISTING REAR ADDITION TO BE REMOVED
EXISTING STAIR TO SECOND FLOOR AND STAIR TO THIRD FLOOR TO BE REMOVED AND REPLACED
EXISTING WINDOWS TO BE REMOVED AND FRAMED IN OR REPLACED WITH NEW WINDOWS UNLESS NOTED OTHERWISE
SHADED EXTERIOR WALLS REPRESENT EXISTING WALLS TO REMAIN

GENERAL NOTES:
- SMOKE DETECTORS TO HAVE A VISUAL SIGNALING COMPONENT AND CONFORM TO NFPA 72 - 18.5.3
- ELECTRICAL OUTLET BOXES AND OTHER PARTY WALL PENETRATIONS SHALL BE OFFSET TO MAINTAIN INTEGRITY OF FIRE SEPARATION. TYPICAL ALL FLOORS.
- CERAMIC TILE REQUIRES 5/8" UNDERLAY
- WATER RESISTANT FLOORING REQUIRED IN BATHROOMS, LAUNDRY ROOMS, KITCHENS, GENERAL STORAGE AREAS & ENTRANCE (OBC 9.30.1.2.)


BATHROOM NOTE: (TYP.)
FINAL BATHROOM LAYOUT TO BE CONFIRMED BY OWNER/ BATHROOM DESIGNER.
- EXHAUST FAN TO BE VENTED TO EXTERIOR.
- PROVIDE STUD WALL REINFORCING TO PERMIT THE FUTURE INSTALLATION OF A GRAB BAR ON A WALL ADJACENT TO A WATER CLOSET, BATHTUB AND A SHOWER AS PER OBC 9.5.2.3.(1)
- PROVIDE WATERPROOF WALL IN SHOWER STALLS (5'11") ABOVE THE RIM OF BATHTUBS EQUIPPED WITH SHOWERS (3'11") AND THE RIM OF BATHTUBS NOT EQUIPPED WITH SHOWERS (15 3/4") IN ACCORDANCE TO OBC 9.29.2.1.

LAUNDRY ROOM NOTE: (TYP.)
OWNER TO CONFIRM DOOR SWING OF APPLIANCES BEFORE ROUGH-IN.
PROVIDE GALV. METAL PAN OR EQUAL C/W DRAIN @ WASHER.
ENSURE PROPER DRYER VENTING TO EXTERIOR.

STAIR NOTE: (TYP.)
STAIRS TO CONFORM TO OBC 9.8.9.
MAX RISE = 7 7/8"
MIN RUN = 8 1/4"
MIN TREAD = 9 1/4"
MIN HEADROOM = 6'5"
HANDRAIL TO CONFORM TO OBC 9.8.7.
MIN HT = 2'10"
MAX HT = 3'0"
GUARDRAIL TO CONFORM TO OBC 9.8.8.
MIN HT = 2'11"

UPO CALCULATION
EBF AREA = 841 SQ.FT.
LIMITING DISTANCE = 12.5M
PERMITTED GLAZING = 100%

SEE DETAIL 03/A4.1



01
A4.0
EXTERIOR ELEVATION (FRONT)
SCALE: 1/4"=1'-0"

23

DEVELOPMENTS

#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER

O.G.

BCIN

87 STIRLING AVENUE

EXTERIOR ELEVATION
(FRONT)

AS SHOWN
JAN 30, 2019
A4.0

#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER: BCINL

O.G.

BCIN


87 STIRLING AVENUE

EXTERIOR ELEVATION (LEFT)

AS SHOWN
JAN 30, 2019

A4.1



UPO CALCULATION
EBF AREA = 1543 SQ.FT.
LIMITING DISTANCE = 2.73M
PERMITTED GLAZING = 9.46% = 146 SQ.FT.
PROPOSED GLAZING = 96.4 SQ.FT.




01
A4.1 EXTERIOR ELEVATION (LEFT)
SCALE: 1/4"=1' 0"




#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



01
A4.2 EXTERIOR ELEVATION (RIGHT)
SCALE: 1/4"=1' 0"



02
A4.2 STEEL STUD WALL DETAILS - TO BE CONFIRMED BY P.ENG.
SCALE: 1-1/2"=1' 0"



THICKNESS - STEEL COMPONENTS	MINIMUM THICKNESS (MILS)	DESIGN THICKNESS (IN)	DESIGN THICKNESS (MM)	REFERENCE ONLY GAUGE NO.
	18	0.0188	0.477	25
	27	0.0283	0.718	22
	30	0.0312	0.792	20 - DRYWALL
	33	0.0346	0.878	20 - STRUCTURAL
	43	0.0451	1.145	18
	54	0.0566	1.437	16
	68	0.0713	1.811	14
	97	0.1017	2.583	12

- 1. MATERIALS**
MATERIAL FOR COLD FORMED STEEL STUDS, BRACING, BRIDGING CHANNELS AND CLIPS, ETC. SHALL MEET THE REQUIREMENTS OF CAN/CSA-S136-01. FOR MATERIAL 1.15mm AND THINNER, GRADE A YIELD STRENGTH 228MPa (33 Ksi), FOR MATERIAL 1.52mm AND THICKER, GRADE D, 345 MPa (50 Ksi)

FOR STUDS & TRACKS, HOT DIPPED GALVANIZED COATING TO BE 2275 MINIMUM.
- 2. STUD SIZES & DESIGNATIONS**
STUDS - 8"x1 5/8"x5/8" - 0.0566" - (800s162-56) TYP.
EXT. WALL. REFER TO STUD DESIGNATION DEFINITION BELOW. STUDS TO BE SECURED AT TOP WITH DIETRICH FASTCLIPS.
- 3. STUDS & TRACKS**
UNLESS INDICATED, ALL TRACK IS TO BE SAME GAUGE AS STUDS, WITH A WIDTH TO MATCH STUD AND STANDARD LEGS. MATERIAL AS PER NOTE 1.
- 4. FASTENERS & CONNECTIONS**
ALL FASTENERS BETWEEN STUDS, STUDS & TRACK TO BE #8-18 WAFER HEAD SCREWS CORROSION RESISTANT ZINC OR CADMIUM COATING (0.008mm) THICK.

- 5. BRIDGING CHANNEL & CLIPS**
UNLESS INDICATED, BRIDGING REQUIRED ON CENTERLINE OF STUDS AS PER DETAIL AT 1200mm (48") O/C MAX. TO BE 38 (1.5")X13 (1/2")X1.15mm (0.045") "U" CHANNEL.

BRIDGING CLIPS TO BE 38 (1.5")X38 (1.5")X1.15mm (0.045") CONNECT WITH 2-#8-18 SCREWS TO BOTH STUD & BRIDGING CHANNEL MATERIAL AS PER NOTE 1.
- 6. VERTICAL DEFLECTION**
ATTACH BUILDING ANCHORS TO THE STRUCTURE ACCORDING TO THE MANUFACTURER'S INSTRUCTIONS. ANCHORS SHALL BE INSTALLED THROUGH THE EMBOSSEMENTS ON THE SCORED LINE OF THE CLIP AS SHOWN ON THE ATTACHED DRAWINGS. IN NO CASE SHALL ANCHORS BE INSTALLED MORE THAN 1" (25mm) FROM THE BEND ON THE SHORT LEG OF THE CLIP. IN CASE OF DISCREPANCY BETWEEN THIS INFORMATION AND THE DESIGN ENGINEER'S DETAILS, DESIGN ENGINEER'S DETAILS SHALL BE FOLLOWED. SCREWS SHALL BE DRIVEN THROUGH THE SLOTTED HOLES AND POSITIONED TO ALLOW FOR THE APPROPRIATE BUILDING DEFLECTION.
- 7. GENERAL NOTES**
THESE SPECIFICATIONS & ATTACHED SKETCHES MUST BE READ IN CONJUNCTION WITH ALL CONTRACT DOCUMENTS FOR THIS PROJECT.


ALL HEIGHTS OF WALLS TO BE CONFIRMED ON SITE, MAXIMUM HEIGHTS USED FOR DESIGN OF STUDS.

STEEL STUD CONTRACTOR SHALL REPORT ANY DISCREPANCIES TO ENGINEER PRIOR TO PROCEEDING WITH WORK.

The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER	BCIN
O.G.	
BCIN	

87 STIRLING AVENUE		
EXTERIOR ELEVATION (RIGHT)		
AS SHOWN	A4.2	
JAN 30, 2019		



UPO CALCULATION
EBF AREA = 841 SQ.FT.
LIMITING DISTANCE = 8.89M
PERMITTED GLAZING = 68.5% = 576 SQ.FT.
PROPOSED GLAZING = 230.6 SQ.FT.

01
A4.3 EXTERIOR ELEVATION (REAR)
SCALE: 1/4"=1' 0"



#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19



The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements setout in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER BCINL

O.G.

BCIN



87 STIRLING AVENUE

EXTERIOR ELEVATION (REAR)


AS SHOWN
JAN 30, 2019

A4.3


#	REVISION	DATE
01	ISSUED FOR CLIENT REVIEW	01/28/19
02	ISSUED FOR ENGINEERING REVIEW	01/29/19
03	ISSUED FOR BUILDING PERMIT	03/04/19
04	REVISED FOR DEFICIENCY LETTER	03/25/19




01 BUILDING SECTION
A5.0 SCALE: 1/4"=1' 0"



02 TYP. BASEMENT EGRESS WINDOW DETAIL
A5.0 SCALE: 1/2"=1' 0"



03 TYP. VENTING DETAIL
A5.0 SCALE: 1 1/2"=1' 0"



04 STANDARD REINFORCEMENT DETAIL
A5.0 SCALE: 1/2"=1' 0"

LEGEND

PT.	PRESSURE TREATED LUMBER
PL	POINT LOAD ABOVE
P1	3X3X1/4" HSS
P2	2 - 2X6
P3	3 - 2X6
P4	4 - 2X6
B1	W250X101 STEEL BEAM
B2	W810X39 STEEL BEAM
B3	W250X28 STEEL BEAM
B4	W250X13 STEEL BEAM
L1	2 - 2X10 WND LINTEL
L2	2 - 2X12 WND LINTEL
L3	2 - 1 3/4" X 9 1/2" LVL 2.0 OE
F1	48"X48"X12" CONC. FOOTING W/ 3-15M E.M.

KEY TO SYMBOLS

(F)	EXHAUST FAN
(CO/SD)	SMOKE DETECTOR / CARBON MONOXIDE DETECTOR

The undersigned has reviewed and takes responsibility for this design and has the qualifications and meets the requirements set out in the Ontario Building Code to design the work shown in the attached documents.

DESIGNER: BCIN

O.G.

BCIN

87 STIRLING AVENUE

BUILDING SECTION & DETAILS

AS SHOWN
JAN 30, 2019

A5.0