


Functional Servicing and Stormwater Management Report



Project: 400 Albert Street

Albert and Main Holdings Inc.

Lithos Group Inc.
150 Bermondsey Road
North York, ON M4A-1Y1
Tel: (416) 750-7769
Email: info@LithosGroup.ca

PREPARED BY:



Catherine Agiou, P.E., M.A.Sc.,
Project Designer

REVIEWED BY:



Matina Sakoutsou, M.A.Sc.
Project Design Manager

AUTHORIZED FOR ISSUE BY:

LITHOS GROUP INC.



Nick Moutzouris, P.Eng., M.A.Sc.
Principal

Issues and Revisions Registry

Identification	Date	Description of issued and/or revision
FSR/SWM Report	08-26-2019	Issued for 1 st Zoning Application
FSR/SWM Report	05-05-2020	Issued for 2 nd Zoning Application

Statement of Conditions

This Report / Study (the “Work”) has been prepared at the request of, and for the exclusive use of, the Owner / Client, the City of Ottawa and its affiliates (the “Intended User”). No one other than the Intended User has the right to use and rely on the Work without first obtaining the written authorization of Lithos Group Inc. and its Owner. Lithos Group Inc. expressly excludes liability to any party except the intended User for any use of, and/or reliance upon, the work.

Neither possession of the Work, nor a copy of it, carries the right of publication. All copyright in the Work is reserved to Lithos Group Inc. The Work shall not be disclosed, produced or reproduced, quoted from, or referred to, in whole or in part, or published in any manner, without the express written consent of Lithos Group Inc. and the Owner.

Executive Summary

Lithos Group Inc. (Lithos) was retained by Albert and Main Holdings Inc. (the “Owner”) to prepare a Functional Servicing and Stormwater Management Report in support of a Rezoning Application, for a proposed mixed-use development located north-west of the intersection between Slater Street and Lyon Street, at 400 Albert Street (K1R 5B2), in the City of Ottawa (the “City”). The following summarizes our conclusions:

Storm Drainage

A more detailed Stormwater Management report will be prepared at the Site Plan Application. The property’s existing drainage pattern is separated into two drainage areas (one flowing north towards Lyon Street and one flowing south-east towards Slater Street). Following that fact, our analysis assumes that the drainage pattern is maintained under Post-development conditions.

The site stormwater discharge will be controlled to the 5-year pre-development flows according to the City of Ottawa IDF curves. Two (2) proposed storm laterals will be connected to the existing 300 mm storm sewer on Lyon Street and to the existing 525 mm diameter storm sewer on Slater Street. In order to attain the target flows and meet the City’s guidelines, quantity controls will be utilized and up to 89.8 m³ and 84.9 m³ of storage will be required to meet the allowable flows towards Lyon Street and Slater Street, respectively.

The stormwater management (SWM) system will be designed to provide enhanced level (Level 1) protection as specified by the Ministry of the Environment, Conservation and Parks (MECP). During Site Plan Application, a detailed analysis will be provided to assess the water quality on site and determine additional measures in order to achieve a minimum total suspended solids (TSS) removal of 80%.

Sanitary Sewers

The flow from the proposed development will be directed to a proposed sanitary chamber to be located at the south side of the property and through a 250 mm lateral sanitary connection, will be finally discharged to the 375mm diameter sanitary sewer on Slater Street. The additional net discharge flow from the proposed development, is anticipated at approximately 19.86 L/s. According to our analysis, the existing infrastructure has the capacity to support the additional sanitary flow from the proposed development.

Water Supply

Water supply for the proposed development will be provided from two (2) separate water connections. More specifically, for domestic water, Towers A and C, along with the East and West Podium, will be connected to the existing 200 mm diameter watermain on the south side of Albert Street, while Tower B by the existing 375 mm diameter watermain on the north side of Slater Street. Moreover, as far as the fire service is concerned, the entire property will be serviced by the 375mm watermain along Slater Street. It is anticipated that a total design flow of 11.50 L/s, for the Albert Street connection, and 88.91 L/s, for the Slater Street connection, will be required to support the proposed development. Based on the boundary conditions received from the City, it is revealed that the existing water infrastructure can support the proposed development

Site Grading

The proposed grades will improve the existing drainage conditions to meet the City’s/Regional requirements. Grades will be maintained along the property line wherever feasible and emergency overland flow will be gravity driven to the adjacent right-of-way’s (ROW).

Table of Contents

1.0	Introduction	1
2.0	Site Description	1
3.0	Site Proposal	1
4.0	Terms of Reference and Methodology	2
4.1.	Terms of Reference	2
4.2.	Methodology: Stormwater Drainage and Management.....	2
4.3.	Methodology: Sanitary Discharge	2
4.4.	Methodology: Water Usage.....	3
5.0	Stormwater Management and Drainage	4
5.1.	Existing Conditions.....	4
5.2.	Proposed Conditions.....	5
5.2.1.	Quantity Controls.....	6
5.2.2.	Quality Controls	7
5.3.	Proposed Storm Connection	7
6.0	Sanitary Drainage System	7
6.1.	Existing Sanitary Drainage System	7
6.2.	Existing and Proposed Sanitary Flows	8
6.3.	Existing Downstream Capacity.....	8
6.3.1.	Dry-Weather Conditions	8
6.3.2.	Wet-Weather Conditions.....	8
6.4.	Proposed Sanitary Connection.....	9
7.0	Water Supply System	9
7.1.	Existing System	9
7.2.	Proposed Water Supply Requirements	9
7.3.	Watermain Analysis Results	10
7.4.	Proposed Watermain Connection	11
8.0	Erosion and Sediment Control	12
9.0	Site Grading	13
9.1.	Existing Grades	13
9.2.	Proposed Grades.....	13
10.0	Conclusions and Recommendations.....	13

LIST OF FIGURES

Figure 1 - Location Plan

Figure 2 - Aerial Plan

LIST OF TABLES

Table 4-1 – Sanitary Design Criteria	3
Table 4-2 – Water Usage.....	4
Table 5-1 – Target Input Parameters	5
Table 5-2 – Target Peak Flows	5
Table 5-3 – Post-development Input Parameters.....	6
Table 5-4 – Post-development Quantity Control as Per City Requirements	6
Table 7-1 – Water Demand.....	9
Table 7-2 – Fire Flow Input Parameters.....	10
Table 7-3 – Water Demand	10
Table 7-4– Boundary Conditions Provided by the City	11
Table 7-5- Watermain Analysis Results.....	11

APPENDICES

Appendix A – Site Photographs

Appendix B – Background Information

Appendix C – Storm Analysis

Appendix D – Sanitary Data Analysis

Appendix E – Water Data Analysis

Appendix F – Engineering Figures

1.0 Introduction

Lithos Group Inc. (Lithos) was retained by Albert and Main Holdings Inc. (the “Owner”) to prepare a Functional Servicing and Stormwater Management Report in support of a Zoning Application for a proposed mixed-use development located at 400 Albert Street in the City of Ottawa (the “City”).

The purpose of this report is to provide site-specific information for the City’s review with respect to infrastructure required to support the proposed development. More specifically, the report will present details on sanitary discharge, water supply and an outline of the storm drainage pattern.

We contacted the City’s engineering department to obtain existing information in preparation of this report. The following documents were available for our review:

- As built plans of:
 - Slater Street, drawing No. PP2 and No. PP3, dated June 30, 2016;
 - Slater Street, drawing No. E-35, dated September 1970;
 - Albert Street, drawing No. A-3-3;
 - Lyon Street, drawing No. H-36-f, dated October 7 1969;
 - Bay Street, drawing No. R430, dated February 6 1970
- Site Plan prepared by IBI GROUP, dated May 04, 2020;
- Statistics prepared by IBI GROUP, dated May 04, 2020;
- Topographical Survey prepared by Annis, O’Sullivan, Vollebakk Ltd., dated March 28, 2014;

2.0 Site Description

The existing site is approximately 0.615 hectares and is comprised of one (1) three-storey commercial building with outdoor parking area. The site is located on the north-west side of the intersection between Slater Street and Lyon Street and is bound by residential development and Bay Street to the west, Albert Street to the north, Lyon Street to the east and Slater Street to the south. Refer to **Figures 1 and 2** following this report and site photographs in **Appendix A**.

3.0 Site Proposal

Under post-development conditions, approximately 0.032 ha will be conveyed to the City due to the road widening along Albert Street, Lyon Street and Slater Street; therefore, the proposed site area will be 0.583 hectares. The proposed development will consist of one (1) three-storey podium with two (2) high-rise, 23-storey and 29-storey residential towers, and one (1) three-storey podium with one (1) high-rise, 35-storey residential tower. The proposed development will consist with a total of 930 residential units as well as 2,884 m² of retail space, facilitated by three (3) levels of underground parking. Please refer to **Appendix B** for site plan and building statistics.

4.0 Terms of Reference and Methodology

4.1. Terms of Reference

The following references and technical guidelines were consulted in the present study:

- **City of Ottawa Servicing Study Guidelines**, online edition,
- **City of Ottawa Sewer Design Guidelines**, (2012),
- **City of Ottawa Design Guidelines – Water Distribution**, (2010),
- **Ministry of Environment, Conservation and Parks (MECP) Guidelines for the Design of Water Systems** (2008)
- **MECP Guidelines for the Design of Sanitary Sewage Systems** (2008)
- **MECP Stormwater Planning and Design Manual** (2003)
- **Ontario Building Code** (2010)

4.2. Methodology: Stormwater Drainage and Management

This report provides a brief Stormwater Management (SWM) review of the pre-development and post-development conditions and comments on opportunities to reduce peak flows, as per the City of Ottawa guidelines. A detailed Stormwater Management (SWM) report will be prepared at the Site Plan Application stage.

The stormwater management criteria for this development are based on the City of Ottawa Sewer Design Guidelines, as well as the Ministry of Environment, Conservation and Parks (MECP) 2003 Stormwater Management Planning and Design Manual (SWMPD). The following design criteria will be reviewed:

- Post-development peak flow for the 100-year storm event from the site should be controlled to the 5-year target flow. A 20-minute time of concentration and a 10 min inlet time derived from City of Ottawa IDF curves, were considered for connection to a dedicated storm sewer;
- For connection to a dedicated storm sewer, when the imperviousness of the existing property is greater than 50%, the maximum value of the runoff coefficient, “c”, used in calculating the pre-development peak runoff rate is limited to 0.50;
- A safe overland flow will be provided for all flows in excess of the 100-year storm event.

4.3. Methodology: Sanitary Discharge

The sanitary sewage discharge from the site will be determined using sanitary sewer design sheets that incorporate the land use and building statistics as supplied by the design team. The calculated values provide peak sanitary flow discharge that considers infiltration.

The estimated sanitary discharge flows from the proposed site will be calculated based on the criteria shown **Table 4-1** below. (Sections 4 and 6 of the City of Ottawa Sewer Design Guidelines)

Table 4-1 – Sanitary Design Criteria

Design Parameter	Value
Residential Units (Average Apartment)	1.8 people/unit
Average Daily Residential Flow	280 L/person/day
Residential Peak Factor	$PF = 1 + (14/(4+(P/1000)^{1/2}))$
Commercial Floor Space	50000 L/ha/day
Commercial Peaking Factor	1.5 if commercial contribution >20%, otherwise 1.0
Infiltration and Inflow Allowance	0.28 L/s/ha
Sanitary sewers are to be sized employing the Manning's Equation	$Q = \frac{1}{n} AR^{2/3} S^{1/2}$
Minimum Manning's 'n'	0.013
Minimum Depth of Cover	1.5 m from crown of sewer to grade
Minimum Full Flowing Velocity	0.6 m/s
Maximum Full Flowing Velocity	3.0 m/s

4.4. Methodology: Water Usage

The fire flow requirements were estimated using the method prescribed by the Fire Underwriters Survey (FUS). This method is based on the floor area of the building to be protected, the type and combustibility of the structural frame and the separation distances with adjoining building units.

Section 4.3.22 of the City Design guidelines for water distribution provides guidance for determining the method for estimating Fire Demand. As indicated, the requirements for levels of fire protection on private property are covered in the Ontario Building Code. Section 7.2.11 of the OBC addresses the installation of water service pipes and fire service mains. Part 3 of the OBC outlines the requirement for Fire Protection, Occupant Safety, and Accessibility; and subsection A-3.2.5.7 provides the provisions for firefighting. Based on trained personnel responding to the emergency, and water supply being delivered through a municipal, the required minimum provision for water supply flow rates shall not be less than 2,700L/min or greater than 9,000L/min (OBC Section A.3.2.5.7, Table 2). The City of Ottawa was contacted in August 2019 to obtain boundary conditions based on an estimated water demand.

The domestic water usage was calculated based on the City of Ottawa Guidelines – Water Distribution outlined in **Table 4-2** that follows.

Table 4-2 – Water Usage

Design Parameter	Value
Average Residential Day Demand	350 L/person/day
Maximum Residential Day Demand	2.5 x Average Day Demand
Maximum Residential Hour Demand	2.2 x Max Day Demand
Average Commercial Day Demand	2.5 L/m ² /d
Maximum Commercial Day Demand	1.5 x Average Day Demand
Maximum Commercial Hour Demand	1.8 x Max Day Demand
Minimum Depth of Cover	2.4 m from top of watermain to finished grade
During Peak Hour Demand desired operating pressure is within	350kPa and 480KPa
Minimum pressure during normal operating conditions (average day to maximum hour demand)	275kPa
During normal operating conditions, pressure must not exceed	552kPa
Minimum pressure during fire flow plus maximum day demand	140kPa

5.0 Stormwater Management and Drainage

5.1. Existing Conditions

The existing site contains one (1) three-storey commercial development with outdoor parking area. The site drains towards Lyon Street and towards Slater Street. Moreover, no external areas drain towards the subject property.

According to available records, there are four (4) storm sewers abutting the subject property. More specifically:

- A 375mm diameter storm sewer on Bay Street flowing south;
- A 600mm diameter storm sewer on Albert Street flowing east;
- A 525mm diameter storm sewer on Slater Street flowing east; and
- A 300mm diameter storm sewer on Lyon Street flowing south.

Two (2) internal drainage areas were identified in the existing site:

1. A1 Pre – Storm runoff from the north-east portion of the site, which incorporates the runoff from the north outdoor parking area and the existing building's rooftop, being discharged into the City's storm network along Lyon Street;
2. A2 Pre – Storm runoff from the south parking area of the site facing Slater Street and a portion of the north-west corner of the site facing Albert Street, draining overland towards Slater Street. Those areas are captured by existing catch basins before being discharged into the City's storm network along Slater Street.

For details, please refer to **DAP-1** in **Appendix C**.

Moreover, the existing site is primarily covered by impermeable areas, thus there is no significant infiltration onsite. Although the existing run-off composite coefficient is estimated at 0.9, the City of Ottawa Guidelines require target flow calculations based on a run-off coefficient of 0.5. **Table 5-1** shows the input parameters which are illustrated on the pre-development drainage area plan in **Figure DAP-1** in **Appendix C**.

Table 5-1 – Target Input Parameters

Catchment	Drainage Area (ha)	Actual "C"	Design "C"	Tc (min.)
A1 Pre (Parking Area and Building-north-east)	0.123	0.90	0.50	20
A2 Pre (Parking Area – south and north-west)	0.460	0.90	0.50	20

Peak flows calculated for the existing conditions are shown in **Table 5-2** below. Detailed calculations are in **Appendix C**.

Table 5-2 – Target Peak Flows

Catchment	Peak Flow Rational Method (L/s)		
	2-year	5-year	100-year
A1 Pre (Lyon Street)	8.9	12.0	20.5
A2 Pre (Slater Street)	33.2	44.9	76.6

As shown in **Table 5-2**, post-development flows towards Lyon and Slater Street will need to be controlled to the target flows of 12.0 L/s and 44.9 L/s, respectively.

5.2. Proposed Conditions

In order to meet the City's Stormwater Management criteria, the development flow rate is to be controlled to the five (5)-year target flow established in **Section 5.1**. Overland flow from the site will be directed towards the adjacent right-of-ways.

The site consists of two (2) internal drainage areas:

1. A1 Post – Storm runoff from the rooftops of Tower A and from the East Podium's terraces, is controlled in the underground storage tank located in the north side of the property;
2. A2 Post – Storm runoff from the rooftop of Towers C & B, from the West Podium's terraces and from the south driveway area, is controlled in the underground storage tank located in the south side of the property;

The pre and post-development drainage areas and runoff coefficients are summarized in **Table 5-3** below.

The post-development drainage areas and runoff coefficients are indicated in **Figure DAP-2**, located in **Appendix C** and summarized in **Table 5-3** below.

Table 5-3 – Post-development Input Parameters

Drainage Area	Drainage Area (ha)	"C"	Tc (min.)
A1 Post (Tower A and East Podium)	0.236	0.90*	10
A2 Post (Towers C, B, West Podium and driveway area)	0.347	0.90*	10

* "C" value for the 100 year storm event is increased by 25%, with a maximum of 1.0 per City's Sewer Design Guidelines.

5.2.1. Quantity Controls

As mentioned in **Section 5.1** storm runoff from the existing property drains towards two (2) storm sewer networks, therefore, quantity control analysis has been prepared for each storm network adjacent to the site in order to assess the pre to post development impacts on each network.

5.2.1.1 Post-development flows towards Lyon and Slater Street

Using the City's intensity-duration-frequency (IDF) data, modified rational method calculations were undertaken to determine the maximum storage required during each storm event. Results for the 2, 5, and 100-year storm events are provided in **Table 5-4**. The detailed post-development quantity control calculations are provided in **Appendix C**.

Table 5-4 – Post-development Quantity Control as Per City Requirements

Storm Event	Storm Event	Target Flow (L/s)	Required Storage Tank Volume (m ³)
A1 Post- Towards Lyon Street (Controlled)	2-year	12.0	22.4
	5-year		35.9
	100-year		89.8
A2 Post- Towards Slater Street (Controlled)	2-year	44.9	13.0
	5-year		27.3
	100-year		84.9

As shown in **Table 5-4**, in order to control post-development flows to the 5-year pre-development conditions, a target flow of 12.0 L/s towards Lyon and of 44.9 L/s, towards Slater Street's storm network, is to be satisfied. The on site storage required in order to meet the allowable release rates for Lyon Street and Slater Street, is calculated at 89.8 m³ and 84.9 m³ respectively, for the 100-year storm event. This can be achieved through the design and installation of stormwater holding tanks, flow control devices and/or roof storage, details of which will be provided through the detailed design stage of Site Plan Application.

5.2.2. Quality Controls

Stormwater treatment must meet Enhanced Protection criteria as defined by the MECP 2003 SWMPD Manual, including the removal of at least 80% total suspended solids (TSS). Quality control and the need of additional measures is required, details of which will be discussed during Site Plan Application.

5.3. Proposed Storm Connection

The proposed development will have two (2) storm connections, on Lyon Street and on Slater Street.

Proposed storm connection on Lyon Street

Storm discharge from the rooftop of Tower A and from the East Podium's terraces will be connected to the existing manhole located at the north side of the property and through the existing 200 mm storm sewer will finally discharge at the 300 mm storm sewer on Lyon Street, with a minimum grade of 2.00% (or equivalent pipe design).

Proposed storm connection towards Slater Street

Storm discharge from the rooftop of Towers C & B, from the West Podium's terraces and from the south driveway area will be connected to the existing 525 mm diameter storm sewer along Slater Street, via a 200 mm storm sewer service connection, with a minimum grade of 2.00% (or equivalent pipe design).

Orifice controls, as required, will be designed to meet the allowable release rates to the municipal system and will be defined at the detailed design stage, of Site Plan Application. Therefore, since the post-development discharge rate will meet the 5-year pre-development rate, it is anticipated that this development will not adversely affect flow conditions downstream. Flows above the 100-year event will be conveyed both overland and within pipes to the adjacent municipal right-of-ways (ROW).

The 'Proposed Servicing Plan' Figure-3 in Appendix F indicates the stormwater service connections.

6.0 Sanitary Drainage System

6.1. Existing Sanitary Drainage System

The existing site is comprised of one (1) three-storey commercial building with parking area. According to available records, there are five (5) sanitary sewers abutting the subject property. More specifically:

- A 375mm diameter sanitary sewer on Albert Street flowing east;
- A 600mm diameter trunk sanitary sewer on Lyon Street flowing south;
- A 225mm diameter sanitary sewer on Bay Street flowing south;
- A 250mm diameter sanitary sewer on Bay Street flowing south; and
- A 375mm diameter sanitary sewer on Slater Street flowing east.

The sewers mentioned above connect to the 900 mm diameter sanitary trunk sewer located at the intersection between Lyon Street and Slater Street.

6.2. Existing and Proposed Sanitary Flows

The sanitary flow generated by the proposed development at 400 Albert Street was compared to the existing flow in order to quantify the net increase in the sanitary sewer.

Using the design criteria outlined in **Section 4.3** and existing site information, the sanitary discharge flow from the existing commercial building is estimated at 0.24 L/s.

Similarly, using the design criteria and the proposed development statistics, the new building will discharge 20.10 L/s into the City's infrastructure.

The additional flow will be considered within the sanitary discharge rate, therefore, there is an increase in sanitary flow of approximately 19.86 L/s within the City's sewer network.

A sanitary external analysis has been prepared in order to indicate that the new development will not adversely affect downstream flow conditions. For detailed calculations refer to the sanitary sewer design sheet in **Appendix D**.

6.3. Existing Downstream Capacity

The external sanitary analysis rely upon plans provided by the City, topographic information, and on-site investigation, which were conducted by our team, in order to determine the land use, the population density and the drainage areas towards each sewer segment. Based on the information above, we assessed the existing flow conditions downstream and upstream of the site. The sanitary flows were calculated using the sanitary sewer design sheets typically associated with the design of sanitary pipes for municipal design. The data was based on residential / commercial flows, extraneous infiltration quantities, and peaking factors.

Based on our review of the Sanitary Drainage Area Plan developed, we have identified all sewer segments upstream and downstream of the proposed development, up to the 900mm sanitary trunk sewer located at the intersection between Lyon Street and Slater Street. Please refer to the **Downstream Sanitary Network Drainage Area Plan (DAP-3)** and design sheet for the location of these sewer segments (found in **Appendix D**). The proposed development will connect to a proposed chamber to be located at the south side of the property and through the 250 mm lateral sanitary sewer connection will finally discharge at the 375mm diameter sanitary sewer on Slater Street. External Sanitary Analysis has been developed in order to review how the additional sanitary flows from the proposed development will affect the municipal network downstream.

6.3.1. Dry-Weather Conditions

Our analysis shows that under pre-development conditions, the capacity of the existing sanitary sewer network downstream of the proposed development does not carry more than 45.0% of it's full flow capacity. Refer to design sheet "**External Sanitary Sewer Segments (Dry Weather)**" in **Appendix D**.

The proposed development will increase the flow into the existing network, resulting to a maximum post-development design capacity of 68.6%, into the existing City's sewer network. Refer to design sheet "**External Sanitary Sewer Segments (Dry Weather)**" in **Appendix D**.

6.3.2. Wet-Weather Conditions

An external analysis under extreme wet weather flows including a WWF value has been incorporated into the design, according to the City's Sewer Design Guidelines. Under pre-development wet-weather conditions, the capacity of the existing sanitary sewer network upstream and downstream of the site, does not carry more than 63.4% of it's full flow capacity. Refer to design sheet "**External Sanitary Sewer Segments (Wet Weather)**" in **Appendix D**.

Our analysis shows that the proposed development will increase the flow into the existing network downstream, resulting to a maximum design capacity of 87.0%. Refer to design sheet “**External Sanitary Sewer Segments (Wet Weather)**” in **Appendix D**.

The proposed development will increase the sanitary flows into the downstream network; however, there is adequate capacity to the City’s network to accommodate the additional sanitary flow under both dry and wet-weather conditions

6.4. Proposed Sanitary Connection

The proposed development will connect to a proposed sanitary chamber to be located at the south side of the property, through the 250 mm lateral sanitary connection, at a minimum grade of 2.00% (or equivalent pipe design), and will finally discharge at the 375mm diameter sanitary sewer on Slater Street. Refer to ‘**Proposed Servicing Plan**’ **Figure-3** in **Appendix F**, for the proposed sanitary connection.

7.0 Water Supply System

7.1. Existing System

The subject property lies within the City of Ottawa 1W pressure zone. The existing watermain system consists of a 200 mm diameter watermain on the south side of Albert Street, a 375 mm diameter watermain on the north side of Slater Street and a 200 mm diameter watermain on the east side of Bay Street.

7.2. Proposed Water Supply Requirements

The estimated water consumption was calculated based on the occupancy rates shown on **Table 4-2**, according to the City’s watermain design criteria. Water supply for the site will be provided by the two (2) separate water connections for the proposed development. More specifically, for domestic water, Towers A and C, along with the East and West Podium, will be connected to the existing 200 mm diameter watermain on the south side of Albert Street, while Tower B by the existing 375 mm diameter watermain on the north side of Slater Street. Moreover, as far as the fire service is concerned, the entire property will be serviced by the 375mm watermain along Slater Street.

Albert Street Connection

It is anticipated that an average consumption of approximately 4.55 L/s (393,120 L/day), a maximum daily consumption of 11.50 L/s (993,600 L/day) and a peak hourly demand of 25.25 L/s (90,900 L/hr) will be required to service Towers A, C, the East and West Podiums with domestic water.

Table 7-1 summarizes the anticipated water demand for the proposed development based on the City of Ottawa Guidelines – Water Distribution.

Table 7-1 – Water Demand

Design Parameter	Anticipated Demand ¹ (L/min)
Average Day Demand	273
Max Day + Fire Flow	690 + 0.00 = 690
Max Hour Demand	1515
1. Water demand calculations per City of Ottawa Guidelines. See Appendix E for detailed calculations.	

Slater Street connection

According to our calculations based on the City's watermain design criteria, as far as the domestic water consumption for Tower B is concerned, it is anticipated that an average consumption of approximately 2.23 L/s (192,672 L/day), a maximum daily consumption of 5.58 L/s (482,112 L/day) and a peak hourly demand of 12.28 L/s (44,208 L/hr) will be required.

The fire flow requirements we estimated using the method prescribed by the Fire Underwriters Survey (FUS) be undertaken to assess the minimum requirement for fire suppression. The fire flow calculations is normally conducted for the largest storey, by area, and for the two immediately adjacent storeys. **Table 7-2** illustrates the input parameters used for the FUS calculations. According to our calculations, a minimum fire suppression flow of approximately 83.33 L/s (1,321 USGPM) will be required to service the entire site. Detailed calculations can be found in **Appendix E**.

Table 7-2 – Fire Flow Input Parameters

Parameter	Frame used for Building	Combustibility of Contents	Presence of Sprinklers	Separation Distance			
				North	East	South	West
Value according to FUS options	Fire-Resistive Construction	Limited-Combustible	Yes	Road	Road	Road	3.1m to 10.0 m
Surcharge/reduction from base flow	0.6	15%	30%	0%	0%	0%	20%

In summary, the required design flow is the sum of 'the minimum fire suppression flow' and 'maximum daily demand' ($83.33 + 5.58 = 88.91$ L/s, 1409 USGPM).

Table 7-3 summarizes the anticipated water demand for the proposed development based on the City of Ottawa Guidelines – Water Distribution.

Table 7-3 – Water Demand

Design Parameter	Anticipated Demand ¹ (L/min)
Average Day Demand	133.8
Max Day + Fire Flow	$334.8 + 5334.6 = 5669.4$
Max Hour Demand	736.8
1. Water demand calculations per City of Ottawa Guidelines. See Appendix E for detailed calculations.	

7.3. Watermain Analysis Results

Upon completion of the detailed calculations in order to determine the anticipated domestic water consumption and the required minimum fire flow for the proposed development, the calculation results were provided to the City of Ottawa. As a result, the above noted values were used to generate the municipal watermain network boundary conditions.

Table 7-4 below summarizes the boundary conditions provided by the City of Ottawa for the existing municipal watermain network along Slater and Albert Street.

Table 7-4– Boundary Conditions Provided by the City

Municipal Watermain Boundary Condition	Slater Street Connection	Albert Street Connection
Minimum HGL	106.5	106.5
Maximum HGL	116.5	116.5
Max Day + Fire Flow (100 L/s)	110.5	106.0

Table 7-5 below summarizes the calculated water demands for the proposed development under the various operating conditions and compares the anticipated operating pressures at the watermains to the normal operating pressures outlined in the City of Ottawa Design Guidelines. In addition, booster pumps will be used to increase the water pressure to the upper floors, in order the entire proposed development to function properly.

Table 7-5- Watermain Analysis Results

Watermain Connection	Design Parameter	Anticipated Demand (L/s)	Approximate Design Operating Pressures (psi) / Relative Head (m)	Normal Municipal Operating Pressures (psi)
Slater Street	Average Demand	2.23	63 psi (44.5m)	50-70 psi
	Peak Hour Demand	12.28	49 psi (34.5m)	40-70 psi
	Max Day + Fire Flow Demand	88.91	55 psi (38.5m)	20 psi (min)
Albert Street	Average Demand	4.55	61 psi (42.7m)	50-70 psi
	Peak Hour Demand	25.25	47 psi (32.7m)	40-70 psi
	Max Day + Fire Flow Demand	11.50	46 psi (32.2m)	20 psi (min)

As indicated in the **Table 7-5** above, the results of the watermain analysis based on boundary conditions provided by the City, along Slater and Albert Street, reveal that the existing water infrastructure will support the proposed development. The boundary conditions received by the City of Ottawa can be found in **Appendix E**.

7.4. Proposed Watermain Connection

Two (2) separate connections will be provided to the proposed development. The connections will be as follows:

Albert Street

The proposed development will be serviced by a 200 mm diameter waterline that will distribute the Towers A, C, along with the East and West podium with domestic water. The proposed water lateral will connect on the 200mm existing watermain on Albert Street.

Slater Street

The proposed development will be serviced by a 200 mm diameter waterline that will distribute the Tower B with domestic water and the entire site with fire service. The proposed water lateral will connect on the 375mm existing watermain on Slater Street.

According to City standards the watermains will be constructed with a minimum depth of cover of 2.4m. Refer to '**Proposed Servicing Plan**' **Figure-3** in **Appendix F**, for the proposed water connection.

8.0 Erosion and Sediment Control

Soil erosion occurs naturally and is a function of soil type, climate topography. The extent of erosion losses is exaggerated during construction where vegetation has been removed and the top layer of soil becomes agitated.

Prior to topsoil stripping, earthworks or underground construction, erosion and sediment controls will be implemented and will be maintained throughout construction.

Silt fence will be installed around the perimeter of the site and will be cleaned and maintained throughout construction.

Catch basins will have filter fabric installed under the grate during construction to protect from silt entering the storm sewer system.

A mud mat will be installed at the construction access in order to prevent mud tracking onto adjacent roads.

Erosion and sediment controls must be in place during construction. The following recommendations to the contractor will be included in contract documents.

- Limit extend of exposed soils at any given time.
- Re-vegetate exposed areas as soon as possible.
- Minimize the area to be cleared and grubbed.
- Protect exposed slopes with plastic or synthetic mulches.
- Install silt fence to prevent sediment from entering existing ditches.
- No refueling or cleaning of equipment near existing watercourses.
- Provide sediment traps and basins during dewatering.
- Install filter cloth between catch basins and frames.
- Plan construction at proper time to avoid flooding.

Establish material stockpiles away from watercourses, so that barriers and filters may be installed.

The contractor will, at every rainfall, complete inspections and guarantee proper performance. The inspection is to include:

- Verification that water is not following under silt barriers.
- Clean and change filter cloth at catch basins.

9.0 Site Grading

9.1. Existing Grades

The existing site is approximately 0.583 hectares and is currently occupied by one (1) three-storey commercial building and by outdoor parking area. Moreover, it is located between Lyon Street, Albert Street, Slater Street and Bay Street, in the City of Ottawa. The site drains into the existing stormwater system inside the property and overland towards the adjacent right of ways (ROW).

9.2. Proposed Grades

The proposed grades will improve the existing drainage conditions to meet the City's/Regional requirements. Grades will be maintained along the property line wherever feasible and emergency overland flow will be directed towards the intersection between Slater Street and Lyon Street. Existing drainage patterns on adjacent properties will not be altered and stormwater runoff from the subject development will not affect the adjacent properties.

10.0 Conclusions and Recommendations

Based on our investigations, we conclude the following:

Storm Drainage

A more detailed Stormwater Management report will be prepared at the Site Plan Application. The property's existing drainage pattern is separated into two drainage areas (one flowing north towards Lyon Street and one flowing south-east towards Slater Street). Following that fact, our analysis assumes that the drainage pattern is maintained under Post-development conditions.

The site stormwater discharge will be controlled to the 5-year pre-development flows according to the City of Ottawa IDF curves. Two (2) proposed storm laterals will be connected to the existing 300 mm storm sewer on Lyon Street and to the existing 525 mm diameter storm sewer on Slater Street. In order to attain the target flows and meet the City's guidelines, quantity controls will be utilized and up to 89.8 m³ and 84.9 m³ of storage will be required to meet the allowable flows towards Lyon Street and Slater Street, respectively.


The stormwater management (SWM) system will be designed to provide enhanced level (Level 1) protection as specified by the Ministry of the Environment, Conservation and Parks (MECP). During Site Plan Application, a detailed analysis will be provided to assess the water quality on site and determine additional measures in order to achieve a minimum total suspended solids (TSS) removal of 80%.

Sanitary Sewers

The flow from the proposed development will be directed to a proposed sanitary chamber to be located at the south side of the property and through a 250 mm lateral sanitary connection, will be finally discharged to the 375mm diameter sanitary sewer on Slater Street. The additional net discharge flow from the proposed development, is anticipated at approximately 19.86 L/s. According to our analysis, the existing infrastructure has the capacity to support the additional sanitary flow from the proposed development.

Water Supply

Water supply for the proposed development will be provided from two (2) separate water connections. More specifically, for domestic water, Towers A and C, along with the East and West Podium, will be connected to the existing 200 mm diameter watermain on the south side of Albert Street, while Tower B by the existing 375 mm diameter watermain on the north side of Slater Street. Moreover, as far as the fire service is concerned, the entire property will be serviced by the 375mm watermain along Slater Street. It is anticipated that a total design flow of 11.50 L/s, for the Albert Street connection, and 88.91 L/s, for the Slater Street connection, will be required to support the proposed development. Based on the boundary conditions received from the City, it is revealed that the existing water infrastructure can support the proposed development.



LOCATION PLAN
MIXED USE DEVELOPMENT
ALBERT STREET
TORONTO, ONTARIO

150 Bermondsey Road, North York, Ontario, M4A 1Y1

DATE: MAY 2020

PROJECT No: UD19-048

SCALE: N.T.S.

FIGURE No: FIG 1




AERIAL PLAN
MIXED USE DEVELOPMENT
ALBERT STREET
TORONTO, ONTARIO

DATE:	MAY 2020	PROJECT No:	UD19-048
SCALE:	N.T.S.	FIGURE No:	FIG 2


150 Bermondsey Road, North York, Ontario, M4A 1Y1

APPENDIX A

Site Photographs




North-East Corner of property facing South-East



North-East Corner of property facing South-West



North-West Corner of property facing North-East




North-West Corner of property facing South-East



South-East Corner of property facing North-West



South-East Corner of property facing South-West




South-West Corner of property facing North-East




South-West Corner of property facing North-West


APPENDIX B

Background Information





3 CONTEXT PLAN
Scale: NTS



2 SITE PLAN
Scale: 1 : 400

400 Albert Street - Ottawa

May 1, 2020

PROJECT STATISTICS

SUMMARY	TOTAL	
	SQ.M.	SQ.FT.
Site Area	6,156	66,233
Net Site Area	5,832	62,756
Total GCA	77,596	834,929
Total GFA	61,544	662,211
Total NSA (Residential + Retail)	67,476	726,037
Total Retail GFA (Ground and 2nd)	2,884	31,036
URBAN PARK Area	402	4,326
Total Number of Units	930	

PROJECT STATISTICS

Tower A (23 Storeys) - North	TOTAL	
	SQ.M.	SQ.FT.
Total Tower GCA	15,654	168,432
Total Tower GFA	12,616	135,743
Total Number of Units	231	
Tower B (29 Storeys) - SE	TOTAL	
	SQ.M.	SQ.FT.
Podium GCA (shared with Tower A)	7,798	83,908
Podium GFA (shared with Tower A)	5,364	57,720
Total Tower GCA	22,631	243,510
Total Tower GFA	18,559	199,695
Total GCA	30,429	327,417
Total GFA	23,923	257,415
Total Number of Units	306	
Tower C (35 Storeys) - SW	TOTAL	
	SQ.M.	SQ.FT.
Podium GCA	2,856	30,731
Total Tower GCA	28,657	308,349
Total GCA	31,513	339,080
Total GFA	25,005	269,054
Total Number of Units (tower)	393	

Notes

- GCA is Gross Constructible Area (includes everything inside building envelope).
NSA is Net Saleable Area (Includes the residential units measured to the exterior of the outside wall).
GFA is calculated based on the City of Ottawa Definition copied below.
*GFA is calculated based on the City of Ottawa Definition copied below.
Gross floor area (GFA) means the total area of each floor whether located above, at or below grade, measured from the interiors of outside walls and including floor area occupied by interior walls and floor area created by bay windows, but excluding;
(a) floor area occupied by shared mechanical, service and electrical equipment that serve the building; (By-law 2008-326)
(b) common hallways, corridors, stairwells, elevator shafts and other voids, steps and landings;
Part 1 – Administration, Interpretation and Definitions 1 - 24
City of Ottawa Zoning By-law 2008-250 Consolidation
(By-law 2008-326) (By-law 2017-302)
(c) bicycle parking, motor vehicle parking or loading facilities;
(d) common laundry, storage and washroom facilities that serve the building or tenants;
(e) common storage areas that are accessory to the principal use of the building; (By-law 2008-326)
(f) common amenity area and play areas accessory to a principal use on the lot; and (By-law 2008-326)
(g) living quarters for a caretaker of the building. (surface de plancher hors oeuvre brute)

CLIENT
5015218 Ontario Inc. and
Albert & Main
Developments Inc.

109 Atlantic Avenue, Toronto, ON, M6K 1X4

COPYRIGHT
This drawing has been prepared solely for the intended use. Thus any reproduction or distribution for any purpose other than authorized by IBI Group is forbidden. Written dimensions shall have precedence over scaled dimensions. Contractors shall verify and be responsible for all dimensions and conditions on the job, and IBI Group shall be informed of any variations from the dimensions and conditions shown on the drawing. Shop drawings shall be submitted to IBI Group for general concurrence before proceeding with fabrication.

ISSUES		
No.	DESCRIPTION	DATE
01	ISSUED FOR REZONING	2019-08-29
02	ISSUED FOR REZONING	2020-05-04




PRIME CONSULTANT
IBI GROUP
55 St. Clair Avenue West, 7th Floor,
Toronto, ON M4V 2Y7, Canada
Tel: 416 596 1500 Fax: 416 596 0644
ibigroup.com

PROJECT
400 Albert Street
383 Slater Street/400 Albert Street
Ottawa, Ontario



PROJECT NO:
120068
SCALE:
As indicated
DATE:
05/04/20

SHEET TITLE
CONTEXT, SITE PLAN AND
SITE STATISTICS

SHEET NUMBER
A100



Lyon Street
Part of H-36-f





MATCH LINE 13+50




SCALES

L.V.C. = 150'
P.I. = 9+75
ELEV. = 241.40








	BEFORE	AFTER
31 tons	235.1	234.8
32 tons	235.2	255.0
33 tons	245.7	255.38
40 tons	236.9	236.70
40 tons	237.5	237.80
41 tons	257.8	237.80



UTILITY CHECK			
DATE	UTILITY	REMARKS	CHECK BY
APR/17/70	BELL GAS HYDRO WATER	DRAWN FROM B.TCa PLANS AS PER OTTAWA GAS AS PER HYDRO AS PER W.W. DEPARTMENT	PATH

DATE	DESCRIPTION	DRAWN BY	APPR'D BY
R	E	V	I
S	I	O	N
S			

CITY OF OTTAWA ENGINEERING DEPARTMENT SEWER BRANCH	
SLATER STREET CHAINAGE 37+00 to CHAINAGE 43+00	
<i>E. Howard</i> DESIGN ENGINEER  ENGINEER (C. SEWER BRANCH) T. H. DORBIN CITY ENGINEER	DRAWN BY P. A. T. H. CHECKED BY DATE 3439, 3496 SURVEY BOOK 3439, 3496
SCALES HOR. 1" = 20' VERT. 1" = 6' PLAN No. C-35a SHEET 1 of 6	



OTTAWA COMBINED
SEWAGE STORAGE TUNNEL

CIVIL
PLAN AND PROFILE
STA 1+280 TO STA 1+580
EAST-WEST TUNNEL

W. Newell, P. Eng.
General Manager
Infrastructure Services

R. Dempsey, P. Eng.
Senior Engineer
Infrastructure Services

Contract No.
ISD14-2036

Dwg. No.
PP2

Asset No.

Asset Group

Stantec CH2MHILL.

Des.
C. Quintero

Chk'd.
P. Pitre

Dwn.
J. Arico

Utility Circ. No.
C. Quintero

Const. Inspector


Scale:
HORIZONTAL 500
0m 5 10 20
VERTICAL 100
0m 2 4

LICENSED PROFESSIONAL ENGINEER
C. QUINTERO
100112901
JUNE 30 2016
PROVINCE OF ONTARIO


LICENSED PROFESSIONAL ENGINEER
P. PITRE
100012758
JUNE 22 2016
PROVINCE OF ONTARIO


NOTE: The location of utilities is approximate only, the exact location should be determined by consulting the municipal authorities and utility companies concerned. The contractor shall prove the location of utilities and shall be responsible for adequate protection from damage.

No.	Description	By	Date (dd/mm/yy)
2	ISSUED FOR CONSTRUCTION	D.L.	2016/06/30
1	ISSUED FOR TENDER	J.A.	2015/10/01
C	ISSUED FOR 95% DESIGN	J.A.	2015/02/27
B	ISSUED FOR 70% DESIGN	M.D.	2014/08/29
A	ISSUED FOR PRELIMINARY DESIGN	M.D.	2014/04/18



- NOTE:
- SEE NOTES ON DRAWING PP1.





Source: City of Ottawa GIS infrastructure database

Figure 5.1: City of Ottawa Water Distribution System, Facilities and Feeder mains



Pre-application Consultation Meeting Minutes

Address: 400 Albert Street (388 & 400 Albert, 156 & 160 Lyon)

Formal Pre-consultation File No.: PC2019-0134

Date: May 27, 2019, 2:30pm – 4:00pm

Location: Room 4102E, City Hall, 110 Laurier Ave W

City Contact: Andrew McCreight

City of Ottawa Staff Present:

Andrew McCreight – File Lead, Planner, Development Review - Central

John Wu – Infrastructure Project Manager

Wally Dubyk – Transportation Project Manager

Christopher Moise – Urban Design

Jennifer Hemmings – Parks

Mark Gordon – Planning Student

Invitees Present:

Daniel Bryne – Main and Main, Applicant

Mansoor Kazerouni – IBI

Ron Jack – Parsons

Shawn Barber – Centretown Citizens Community Association

Jack Hanna - Centretown Citizens Community Association

Introductions and Acknowledgements

- Round table introductions
- Acknowledgement that a NDA has been signed by members of the community association

Overview of Proposal (Daniel Bryne & Mansoor Kazerouni)

- Current plan is for the majority of the site to be purpose built rental units. Could be all rental but have not completely ruled out ownership condominiums units.
- The guiding principles of the project come from the City of Ottawa and the Ottawa Lands Development Corporation with the purchase of 156 & 160 Lyon. These include making improvements to the public realm, iconic architecture (more notable than typical Ottawa high-rises), incorporating sustainable elements, and include affordable housing program. Closing on the lands in roughly 3 weeks.
- Main and Main aims for LEED standard but does not pursue the accreditation
- Interested in connecting to the Federal Government's District Energy heating tunnels. Unsure of who to contact, Feds, NCC, ROW?
- Affordable housing agreement to be negotiated, but the requirement through the Lyon property purchases is for seven units to be affordable housing.
- Three towers, 18-38 storeys. 38 storey building at the south west corner of the site on an individual three storey podium. 33 storey tower located at the south

east corner and 18 storey tower near the middle of the site on a shared 3 storey podium.

- Towers will have distinct curvilinear form, removes blunt corners and opens up space between the towers. Still refining details of the architecture.
- Design approach for block permeability.
- Separate podiums allow for a mid-block lane. Primarily for pedestrians but also for loading/deliveries to large retail store.
- Pulled the podium back at the corner of Albert and Lyon Street to create an urban park of around 400m².
- Large shared podium is targeting a grocery store. Has 20,000ft² floorplate. Planning on commercial second floor – some retail, possibly commercial on the third floor – office space. Lobbies for residential towers to be located on Lyon Street, Slater Street, and Albert Street. Design looking for synergy between food store and urban park.
- Single ramp from Bay Street to underground parking. One parking garage across entire site. Unsure about amount of parking. Will have to find the right balance of parking. Only looking to serve residents/workers on site, not to rent out excess spaces to other people. Preliminary estimate of 10-15% more parking spaces than previous proposal. Idea is to target active transportation and minimize parking to only satisfy demand. Car-sharing programs may be explored as well.
- Interested in commercial parking and visitor parking split.
- Phasing – dig out basement as one phase. Then build east towers at the same time while the other tower is capped. May end up building them all at one time given Ottawa's current population growth.
- City's requirement of outright ownership of parkland is problematic for the configuration of the parking garage. This may result in the park being located based on underground parking configuration rather than what is best from a urban design perspective.
- Previous building concept had “no back of house” looked great on paper but wasn't feasible so the lane had to be reconfigured.
- Podium rooftop greenspaces are for resident use only, not public space
- Targeting neighborhood commercial tenants not attempting to become a shopping destination within Ottawa.

Preliminary Comments from the City

Planning Comments (Andrew McCreight)

- Will look into how to reactivate the current applications and how to move them forward procedurally. Both the Zoning and Site Plan applications will be subject to a new circulation fee, but the existing file numbers can be kept. More details to be included in the e-mail follow-up.
- Will provide a legal template for sign over of the previous reports given the potential change in property ownership during an active application.

- New reports and plans will be required given that the site has expanded and the proposed use has changed. If the previous owner signs over the reports you may reuse relevant information in the new reports.
- Application process will effectively be starting over, with new signs posted on site and community circulations will be required as previous application only included 400 Albert proper.
- City requires minimum of 400m² parkland to be provided. This cannot include areas for road widening or otherwise designated.
- Mid-block connection should be more than a connection from A to B, should be an enhanced public space. Look at how this space will function at different times of day and seasons. Think about lighting, seating, public art etc.
- Revise midblock perspective to show the concept now that grocery store loading has been added to the lane. Same consideration for the urban park in the rendering details, which currently has the look of an entrance plaza.
- Would like to see successful examples for loading bays being included on a primarily pedestrian lane. Work this into the Planning Rationale with specific examples and photos.
- The building height causes some concern. The site covered by two height guidelines. One for views plane protection of parliament and another for the neighbourhood secondary plan.
- Anything above the parliament view plane will be hard to support. May want to lower the 38 and 33 storey towers and increase the 18 if you are looking to maintain the overall GFA.
- Want to see background silhouette analysis before the proposed height can be considered. Focus on view 8A and 8B in analysis. Look at other examples of view plane analysis.
- Would like to see a 1:1 ratio of bike parking to residential units to encourage active transportation.
- Floor plate of tower “C” is bulky, could be trimmed or better articulated to reduce the impact of the “slab” floorplate.
- Submission will need another section 37 analysis in the Planning Rationale to determine applicability.

Infrastructure Comments (John Wu)

- No major issues with previous proposal. Now that the new property has been acquired the reports will need to be redone and submitted using current standards/guidelines.
- Maintain current storm water runoff patterns.
- Would be beneficial if engineering consultant calls John Wu to have a quick conversation to verify number of connections, size etc.

Transportation Comments (Wally Dubyk)

- Albert Street and Slater Street are undergoing redesigns. Please include this consideration within your report.
- Update old reports.
- Screening report form with vehicles per hour generated by the site will be required. From this the City will identify intersections to be studied.
- Right of way protection must be identified on plans for all perimeter streets. Albert requires 1.5m.
- See the City's updated standards for modal splits in traffic studies.
- More details and comments provided in email follow-up.

Parks Comments (Jennifer Hemmings)

- Previous discussion on parks for the site. Interested in having the park and the mid-block lane connected.
- Strata parks are not feasible, too many issues around ownership of the park and structural maintenance. Therefore, the City will be looking for at least 400sq.m of parkland dedication and such land is to be unencumbered. Lands associated with road widening or sight triangles will not count towards size requirements.
- Need to look at setbacks from the property line.
- Need to look at the form of the buildings to ensure a successful public space/Urban plaza. Building overhanging raises concerns.
- The City has approximately \$61,000 in development charges for the park (based on proposal). This is not much given the hard surface required.
- Opportunity for the City and Developer to work together to ensure the space is successful and delivered early. Take on design and construction working with the City.
- Park can be used for staging during construction.
- Maintenance may not be to the level that the private development may expect. Private and City can work together on maintenance.
- See City resources such as [Park Development Manual](#).

Urban Design (Christopher Moise)

- There are street designs for Slater and Albert that should be addressed for compatibility and design;
- NW corner site should be massed in at development potential (use existing zoning ~37m) and address relationships to west 4th floor terrace tower adjacencies. Perhaps the east side of the tower would be a more appropriate location;
- Potential for loading conflict with mid-block pedestrian connection needs further description and design development.
- Strongly recommended that this proposal go to the Urban Design Review Panel for an informal presentation. This is a major project and the more time and think you spend with the city to fully participate and work through the design development the smoother the application should go

Community Association (Shawn Barber & Jack Hana)

- Previous application for the site had about half the number of units. There are concerns about how many vehicles the new proposal will bring.
- Traffic will go onto Bay Street which is a narrow street and a major cyclist connection with bike lanes.
- One way streets surrounding site create a circulation pattern around the block.
- Can support the increase in unit density on the site but have concerns about providing too much parking as it will generate more vehicle traffic.
- Including green elements, affordable housing, and quality architecture are all positives.
- Downtown is filling up, we are getting more small greenspaces but where are the new large public greenspaces? Rooftop could be that, and it should be publicly accessible.
- Could control delivery times on lane to reduce issues of conflict between pedestrians and deliveries.
- Discussed a temporary community garden at the site of tower three with the previous owner. Community is still interested in the possibility.
- People want a grocery store and a hardware store.
- Commercial (retail) could play on the proximity to the LRT station
- Concerned about the previous owner's application to extent the temporary use of a parking lot. Don't want to see the site sit as a parking lot for three years or more.
- Concerns about affordability. Want a social mix, not just wealthy young professionals; society does better with integration.
- Look at social studies, like the National Housing Strategy, and possibility of Inclusionary Zoning on the horizon.
- Need to have an open dialogue around affordable housing.
- This a big significant development – requires ample consultation.
- Need the public space and realm improvements throughout and around the site.
- Site offers good opportunity for bike rentals with proximity to the O-Train.
- Would like to discuss a development forum/partnership with the owner/applicant.

Next Steps

- Applicant to submit informal review with the City of Ottawa's Urban Design Review Panel.
- Have engineering consultant contact John Wu.
- Recommended to schedule a second pre-consultation with City staff to go over proposal details before submitting.
- It is recommended that the applicant team seek input from the Ward Councillor and neighbouring property owners, including the Centretown Citizens Community Association.

4.1 General Content

- ☒ Executive Summary (for larger reports only).

Comments: *Page iii*

- ☒ Date and revision number of the report.

Comments: *Page i*

- ☒ Location map and plan showing municipal address, boundary, and layout of proposed development.

Comments: *Figure 1 and Figure 3 in Appendix F*

- ☒ Plan showing the site and location of all existing services.

Comments: *Figure 3 in Appendix F*

- ☒ Development statistics, land use, density, adherence to zoning and official plan, and reference to applicable subwatershed and watershed plans that provide context to which individual developments must adhere.

Comments: *Appendix B*

- ☒ Summary of Pre-consultation Meetings with City and other approval agencies.

Comments: *Appendix B*

- ☒ Reference and confirm conformance to higher level studies and reports (Master Servicing Studies, Environmental Assessments, Community Design Plans), or in the case where it is not in conformance, the proponent must provide justification and develop a defensible design criteria.

Comments: *N/A. Reference to the City's guidelines are included in Section 4.0 pg. 2*

- ☒ Statement of objectives and servicing criteria.

Comments: *Section 4.2 (Stormwater Criteria), Section 4.3 (Sanitary Sewer Criteria), Section 4.4 (Water Usage Criteria)*

- ☒ Identification of existing and proposed infrastructure available in the immediate area.

Comments: *Section 5.1 (ex. storm sewers), Section 6.1 (ex. sanitary sewers), Section 7.1 (ex. water system)*

- ☐ Identification of Environmentally Significant Areas, watercourses and Municipal Drains potentially impacted by the proposed development (Reference can be made to the Natural Heritage Studies, if available).

Comments: N/A

- ☐ Concept level master grading plan to confirm existing and proposed grades in the development. This is required to confirm the feasibility of proposed stormwater management and drainage, soil removal and fill constraints, and potential impacts to neighbouring properties. This is also required to confirm that the proposed grading will not impede existing major system flow paths.

Comments: N/A during Zoning Application

- ☐ Identification of potential impacts of proposed piped services on private services (such as wells and septic fields on adjacent lands) and mitigation required to address potential impacts.

Comments: N/A

- ☐ Proposed phasing of the development, if applicable.

Comments: N/A

- ☐ Reference to geotechnical studies and recommendations concerning servicing.

Comments: N/A

- ☒ All preliminary and formal site plan submissions should have the following information:

- ☒ Metric scale
- ☒ North arrow (including construction North)
- ☒ Key plan
- ☒ Name and contact information of applicant and property owner
- ☒ Property limits including bearings and dimensions
- ☒ Existing and proposed structures and parking areas
- ☒ Easements, road widening and rights-of-way
- ☒ Adjacent street names

Comments: Existing and proposed structures and parking areas are included in topo survey and architectural dwgs. Name and owner info. can be found in zba cover letter.

4.2 Development Servicing Report: Water

- ☐ Confirm consistency with Master Servicing Study, if available
Comments: Not available
- ☒ Availability of public infrastructure to service proposed development
Comments: Section 5.2.1.1, Section 6.3
- ☒ Identification of system constraints
Comments: N/A
- ☒ Identify boundary conditions
Comments: Upon receipt of the City of Ottawa boundary conditions.
- ☒ Confirmation of adequate domestic supply and pressure
Comments: Upon receipt of the City of Ottawa boundary conditions.
- ☒ Confirmation of adequate fire flow protection and confirmation that fire flow is calculated as per the Fire Underwriter's Survey. Output should show available fire flow at locations throughout the development.
Comments: Section 7.2 and Appendix E
- ☒ Provide a check of high pressures. If pressure is found to be high, an assessment is required to confirm the application of pressure reducing valves.
Comments: N/A
- ☐ Definition of phasing constraints. Hydraulic modeling is required to confirm servicing for all defined phases of the project including the ultimate design
Comments: N/A
- ☐ Address reliability requirements such as appropriate location of shut-off valves
Comments: N/A
- ☐ Check on the necessity of a pressure zone boundary modification.
Comments: N/A

- ☒ Reference to water supply analysis to show that major infrastructure is capable of delivering sufficient water for the proposed land use. This includes data that shows that the expected demands under average day, peak hour and fire flow conditions provide water within the required pressure range

Comments: *Appendix E*

- ☒ Description of the proposed water distribution network, including locations of proposed connections to the existing system, provisions for necessary looping, and appurtenances (valves, pressure reducing valves, valve chambers, and fire hydrants) including special metering provisions.

Comments: *Appendix E and Figure-3 at Appendix F*

- ☐ Description of off-site required feeder mains, booster pumping stations, and other water infrastructure that will be ultimately required to service proposed development, including financing, interim facilities, and timing of implementation.

Comments: *N/A*

- ☒ Confirmation that water demands are calculated based on the City of Ottawa Design Guidelines.

Comments: *Section 4.4*

- ☐ Provision of a model schematic showing the boundary conditions locations, streets, parcels, and building locations for reference.

Comments: *Appendix B*

4.3 Development Servicing Report: Wastewater

- ☒ Summary of proposed design criteria (Note: Wet-weather flow criteria should not deviate from the City of Ottawa Sewer Design Guidelines. Monitored flow data from relatively new infrastructure cannot be used to justify capacity requirements for proposed infrastructure).

Comments: Section 4.3

- ☐ Confirm consistency with Master Servicing Study and/or justifications for deviations.

Comments: N/A

- ☐ Consideration of local conditions that may contribute to extraneous flows that are higher than the recommended flows in the guidelines. This includes groundwater and soil conditions, and age and condition of sewers.

Comments: N/A

- ☒ Description of existing sanitary sewer available for discharge of wastewater from proposed development.

Comments: Section 6.1

- ☒ Verify available capacity in downstream sanitary sewer and/or identification of upgrades necessary to service the proposed development. (Reference can be made to previously completed Master Servicing Study if applicable)

Comments: Section 6.3

- ☐ Identification and implementation of the emergency overflow from sanitary pumping stations in relation to the hydraulic grade line to protect against basement flooding.

Comments: N/A

- ☐ Special considerations such as contamination, corrosive environment etc.

Comments: N/A

4.4 Development Servicing Report: Stormwater

- ☒ Description of drainage outlets and downstream constraints including legality of outlets (i.e. municipal drain, right-of-way, watercourse, or private property)

Comments: N/A

- ☒ Analysis of available capacity in existing public infrastructure.

Comments: Section 5.3

- ☒ A drawing showing the subject lands, its surroundings, the receiving watercourse, existing drainage patterns, and proposed drainage pattern.

Comments: DAP1 and 2 in Appendix C

- ☒ Water quantity control objective (e.g. controlling post-development peak flows to pre-development level for storm events ranging from the 2 or 5 year event (dependent on the receiving sewer design) to 100 year return period); if other objectives are being applied, a rationale must be included with reference to hydrologic analyses of the potentially affected subwatersheds, taking into account long-term cumulative effects.

Comments: Section 5.2.2

- ☐ Water Quality control objective (basic, normal or enhanced level of protection based on the sensitivities of the receiving watercourse) and storage requirements.

Comments: N/A during Zoning Application Stage

- ☒ Description of the stormwater management concept with facility locations and descriptions with references and supporting information.

Comments: Section 5.3

- ☐ Set-back from private sewage disposal systems.

Comments: N/A

- ☐ Watercourse and hazard lands setbacks.

Comments: N/A

- ☐ Record of pre-consultation with the Ontario Ministry of Environment and the Conservation Authority that has jurisdiction on the affected watershed.

Comments: N/A

- ☐ Confirm consistency with sub-watershed and Master Servicing Study, if applicable study exists.

Comments: N/A

- ☒ Storage requirements (complete with calculations) and conveyance capacity for minor events (1:5 year return period) and major events (1:100 year return period).

Comments: Appendix C

- ☐ Identification of watercourses within the proposed development and how watercourses will be protected, or, if necessary, altered by the proposed development with applicable approvals.

Comments: N/A

- ☒ Calculate pre and post development peak flow rates including a description of existing site conditions and proposed impervious areas and drainage catchments in comparison to existing conditions.

Comments: Section 5.2 and Appendix C

- ☐ Any proposed diversion of drainage catchment areas from one outlet to another.

Comments: N/A

- ☒ Proposed minor and major systems including locations and sizes of stormwater trunk sewers, and stormwater management facilities.

Comments: Section 5.3 and Figure 3 in Appendix F

- ☒ If quantity control is not proposed, demonstration that downstream system has adequate capacity for the post-development flows up to and including the 100-year return period storm event.

Comments: Section 5.3 and Figure 3 in Appendix F

- ☒ Identification of potential impacts to receiving watercourses

Comments: Section 5.3 and Figure 3 in Appendix F

- ☒ Identification of municipal drains and related approval requirements.

Comments: Section 5.3 and Figure 3 in Appendix F

- ☒ Descriptions of how the conveyance and storage capacity will be achieved for the development.

Comments: Section 5.3 and Figure 3 in Appendix F

- ☐ 100 year flood levels and major flow routing to protect proposed development from flooding for establishing minimum building elevations (MBE) and overall grading.

Comments: N/A

- ☐ Inclusion of hydraulic analysis including hydraulic grade line elevations.

Comments: N/A

- ☒ Description of approach to erosion and sediment control during construction for the protection of receiving watercourse or drainage corridors.

Comments: Section 8.0

- ☐ Identification of floodplains - proponent to obtain relevant floodplain information from the appropriate Conservation Authority. The proponent may be required to delineate floodplain elevations to the satisfaction of the Conservation Authority if such information is not available or if information does not match current conditions.

Comments: N/A

- ☐ Identification of fill constraints related to floodplain and geotechnical investigation.

Comments: N/A

4.5 Approval and Permit Requirements: Checklist

The Servicing Study shall provide a list of applicable permits and regulatory approvals necessary for the proposed development as well as the relevant issues affecting each approval. The approval and permitting shall include but not be limited to the following:

- ☐ Conservation Authority as the designated approval agency for modification of floodplain, potential impact on fish habitat, proposed works in or adjacent to a watercourse, cut/fill permits and Approval under Lakes and Rivers Improvement Act. The Conservation Authority is not the approval authority for the Lakes and Rivers Improvement Act. Where there are Conservation Authority regulations in place, approval under the Lakes and Rivers Improvement Act is not required, except in cases of dams as defined in the Act.

Comments: N/A

- ☐ Application for Certificate of Approval (CofA) under the Ontario Water Resources Act.

Comments: N/A

- ☐ Changes to Municipal Drains.

Comments: N/A

- ☐ Other permits (National Capital Commission, Parks Canada, Public Works and Government Services Canada, Ministry of Transportation etc.)

Comments: N/A

4.6 Conclusion Checklist

- ☒ Clearly stated conclusions and recommendations

Comments: Section 9.0

- ☐ Comments received from review agencies including the City of Ottawa and information on how the comments were addressed. Final sign-off from the responsible reviewing agency.


Comments: N/A

- ☒ All draft and final reports shall be signed and stamped by a professional Engineer registered in Ontario

Comments: Signed and stamped by Ontario engineer

APPENDIX C

Storm Analysis



DRAINAGE AREA	AREA (ha)	TOTAL AREA (ha)
A1 PRE (towards Lyon Street)	0.123	0.583
A2 PRE (towards Slater Street)	0.460	



150 Bermondsey Road, North York, Ontario, M4A 1Y1

LEGEND

A1 pre
0.04 ha

A2 pre
0.50 ha

STORM DRAINAGE AREA NUMBER

DRAINAGE AREA (ha)

COMPOSITE RUNOFF COEFFICIENT

PRE-DEVELOPMENT STORM DRAINAGE AREA

PROPERTY LINE

PRE-DEVELOPMENT DRAINAGE AREA PLAN MIXED USE DEVELOPMENT 400 ALBERT STREET OTTAWA, ONTARIO	
DATE: MAY 2020	PROJECT No: UD19-048
SCALE: N.T.S.	FIGURE No: DAP1



Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed by: Nick Moutzouris, P.Eng., M.A.Sc.

Rational Method Pre-Development Flow Calculation

400 Albert Street
File No. UD19-048
City of Ottawa
Date: May 2020

Input Parameters

Area Number	Area (ha)	C	Tc (min.)
A1 pre (towards Lyon Street)	0.123	0.50	20

Rational Method Calculation

Event 2 yr
IDF Data Set City of Ottawa
a = 732.95
b = 6.199
c = 0.810

Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A1 pre (towards Lyon Street)	0.123	0.50	0.06	20	52.0	0.009	8.9

Event 5 yr
IDF Data Set City of Ottawa
a = 998.07
b = 6.053
c = 0.814

Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A1 pre (towards Lyon Street)	0.123	0.50	0.06	20	70.3	0.012	12.0

Event 100 yr
IDF Data Set City of Ottawa
a = 1735.69
b = 6.014
c = 0.820

Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A1 pre (towards Lyon Street)	0.123	0.50	0.06	20	120.0	0.021	20.5



Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed by: Nick Moutzouris, P.Eng., M.A.Sc.

Rational Method Pre-Development Flow Calculation

400 Albert Street
File No. UD19-048
City of Ottawa
Date: May 2020

Input Parameters

Area Number	Area (ha)	C	Tc (min.)
A2 pre (towards Slater Street)	0.460	0.50	20

Rational Method Calculation

Event 2 yr
IDF Data Set City of Ottawa
a = 732.95
b = 6.199
c = 0.810


Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A2 pre (towards Slater Street)	0.460	0.50	0.23	20	52.0	0.033	33.2

Event 5 yr
IDF Data Set City of Ottawa
a = 998.07
b = 6.053
c = 0.814

Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A2 pre (towards Slater Street)	0.460	0.50	0.23	20	70.3	0.045	44.9


Event 100 yr
IDF Data Set City of Ottawa
a = 1735.69
b = 6.014
c = 0.820

Area Number	A (ha)	C	AC	Tc (min.)	I (mm/h)	Q (m ³ /s)	Q (L/s)
A2 pre (towards Slater Street)	0.460	0.50	0.23	20	120.0	0.077	76.6




150 Bermondsey Road, North York, Ontario, M4A 1Y1

LEGEND



STORM DRAINAGE
AREA NUMBER
DRAINAGE AREA (ha)
COMPOSITE RUNOFF
COEFFICIENT



POST-DEVELOPMENT STORM
DRAINAGE AREA
PROPERTY LINE

POST-DEVELOPMENT DRAINAGE AREA PLAN MIXED USE DEVELOPMENT 400 ALBERT STREET OTTAWA, ONTARIO

DATE: MAY 2020
SCALE: N.T.S.
PROJECT No: UD19-048
FIGURE No: DAP2



Modified Rational Method - Two Year Storm Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa

Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

Drainage Area A1 Post - Towards Lyon Street

Drainage Areas **A1 Post**

Area = **0.236** ha

"C" = **0.90**

AC = **0.21**

Tc = **10.0** min

Time Increment = **5.0** min

Allowable Release Rate = **12.0** L/s

Min. Storage = **22.4** m³

2-Year Design Storm

a= 732.95

b= 6.199

c= 0.810

I = $a / (T_c + b)^c$

(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m ³ /s)	(m ³)	(m ³)	(m ³)
10.0	76.8	0.045	27.19	7.21	19.98
15.0	61.8	0.036	32.80	10.82	21.98
20.0	52.0	0.031	36.84	14.42	22.41
25.0	45.2	0.027	39.97	18.03	21.94
30.0	40.0	0.024	42.53	21.64	20.89
35.0	36.1	0.021	44.68	25.24	19.43
40.0	32.9	0.019	46.54	28.85	17.69
45.0	30.2	0.018	48.17	32.46	15.72
50.0	28.0	0.017	49.63	36.06	13.57
55.0	26.2	0.015	50.95	39.67	11.29
60.0	24.6	0.014	52.16	43.27	8.89
65.0	23.2	0.014	53.27	46.88	6.39
70.0	21.9	0.013	54.30	50.49	3.81
75.0	20.8	0.012	55.26	54.09	1.17
80.0	19.8	0.012	56.16	57.70	0.00
85.0	18.9	0.011	57.00	61.31	0.00
90.0	18.1	0.011	57.80	64.91	0.00
95.0	17.4	0.010	58.56	68.52	0.00
100.0	16.7	0.010	59.28	72.12	0.00
105.0	16.1	0.010	59.97	75.73	0.00
110.0	15.6	0.009	60.63	79.34	0.00
115.0	15.0	0.009	61.26	82.94	0.00
120.0	14.6	0.009	61.86	86.55	0.00
125.0	14.1	0.008	62.44	90.16	0.00
130.0	13.7	0.008	63.00	93.76	0.00
135.0	13.3	0.008	63.54	97.37	0.00
140.0	12.9	0.008	64.06	100.97	0.00
145.0	12.6	0.007	64.57	104.58	0.00
150.0	12.3	0.007	65.06	108.19	0.00
155.0	11.9	0.007	65.53	111.79	0.00
160.0	11.7	0.007	65.99	115.40	0.00
165.0	11.4	0.007	66.44	119.01	0.00



Modified Rational Method - Five Year Storm

Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa

Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

		Drainage Area A1 Post - Towards Lyon Street			
		Drainage Areas		A1 Post	
		Area =	0.236	ha	
		"C" =	0.90		
		AC =	0.21		
		T _c =	10.0	min	
		Time Increment =	5.0	min	
5-Year Design Storm		Allowable Release Rate =	12.0	L/s	
a= 998.07		Min. Storage =	35.9	m ³	
b= 6.053					
c= 0.814					
I = a / (T _c + b) ^c					
(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m ³ /s)	(m ³)	(m ³)	(m ³)
10.0	104.2	0.061	36.88	7.21	29.67
15.0	83.6	0.049	44.37	10.82	33.55
20.0	70.3	0.041	49.74	14.42	35.31
25.0	60.9	0.036	53.89	18.03	35.86
30.0	53.9	0.032	57.27	21.64	35.63
35.0	48.5	0.029	60.11	25.24	34.87
40.0	44.2	0.026	62.57	28.85	33.72
45.0	40.6	0.024	64.72	32.46	32.27
50.0	37.7	0.022	66.65	36.06	30.58
55.0	35.1	0.021	68.39	39.67	28.72
60.0	32.9	0.019	69.97	43.27	26.70
65.0	31.0	0.018	71.43	46.88	24.55
70.0	29.4	0.017	72.78	50.49	22.30
75.0	27.9	0.016	74.04	54.09	19.95
80.0	26.6	0.016	75.22	57.70	17.52
85.0	25.4	0.015	76.33	61.31	15.03
90.0	24.3	0.014	77.38	64.91	12.47
95.0	23.3	0.014	78.38	68.52	9.86
100.0	22.4	0.013	79.32	72.12	7.20
105.0	21.6	0.013	80.22	75.73	4.49
110.0	20.8	0.012	81.08	79.34	1.75
115.0	20.1	0.012	81.91	82.94	0.00
120.0	19.5	0.011	82.70	86.55	0.00
125.0	18.9	0.011	83.46	90.16	0.00
130.0	18.3	0.011	84.19	93.76	0.00
135.0	17.8	0.010	84.90	97.37	0.00
140.0	17.3	0.010	85.58	100.97	0.00
145.0	16.8	0.010	86.24	104.58	0.00
150.0	16.4	0.010	86.88	108.19	0.00
155.0	15.9	0.009	87.50	111.79	0.00
160.0	15.6	0.009	88.11	115.40	0.00
165.0	15.2	0.009	88.69	119.01	0.00



Modified Rational Method - Hundred Year Storm Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

Date: May 2020

		Drainage Area A1 Post - Towards Lyon Street			
		Drainage Areas		A1 Post	
		Area =		0.236	ha
		"C" * =		1.00	
		AC =		0.24	
		Tc =		10.0	min
		Time Increment =		5.0	min
100-Year Design Storm		Allowable Release Rate =		12.0	L/s
a=	1735.69	Min. Storage =		89.8	m³
b=	6.014	* C value for the 100 year storm event is increased by 25%, with a maximum of 1.0 per City's Sewer Design Guidelines			
c=	0.820				
I =	a / (T _c + b) ^c				
(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m³/s)	(m³)	(m³)	(m³)
10.0	178.6	0.117	70.23	7.21	63.02
15.0	142.9	0.094	84.31	10.82	73.49
20.0	120.0	0.079	94.36	14.42	79.94
25.0	103.8	0.068	102.12	18.03	84.09
30.0	91.9	0.060	108.40	21.64	86.77
35.0	82.6	0.054	113.68	25.24	88.44
40.0	75.1	0.049	118.23	28.85	89.38
45.0	69.1	0.045	122.22	32.46	89.76
50.0	64.0	0.042	125.78	36.06	89.71
55.0	59.6	0.039	128.99	39.67	89.32
60.0	55.9	0.037	131.91	43.27	88.64
65.0	52.6	0.035	134.60	46.88	87.72
70.0	49.8	0.033	137.09	50.49	86.60
75.0	47.3	0.031	139.40	54.09	85.31
80.0	45.0	0.029	141.57	57.70	83.87
85.0	43.0	0.028	143.61	61.31	82.30
90.0	41.1	0.027	145.53	64.91	80.62
95.0	39.4	0.026	147.35	68.52	78.84
100.0	37.9	0.025	149.09	72.12	76.96
105.0	36.5	0.024	150.73	75.73	75.00
110.0	35.2	0.023	152.31	79.34	72.97
115.0	34.0	0.022	153.82	82.94	70.87
120.0	32.9	0.022	155.26	86.55	68.71
125.0	31.9	0.021	156.65	90.16	66.50
130.0	30.9	0.020	157.99	93.76	64.23
135.0	30.0	0.020	159.28	97.37	61.92
140.0	29.2	0.019	160.53	100.97	59.56
145.0	28.4	0.019	161.74	104.58	57.16
150.0	27.6	0.018	162.90	108.19	54.72
155.0	26.9	0.018	164.03	111.79	52.24
160.0	26.2	0.017	165.13	115.40	49.73
165.0	25.6	0.017	166.20	119.01	47.19



Modified Rational Method - TwoYear Storm

Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa

Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

		Drainage Area A2 Post - Towards Slater Street			
		Drainage Areas		A2 post	
		Area =	0.347	ha	
		"C" =	0.90		
		AC =	0.31		
		Tc =	10.0	min	
		Time Increment =	5.0	min	
2-Year Design Storm		Allowable Release Rate =	44.9	L/s	
		Min. Storage =	13.0	m ³	
a=	732.95				
b=	6.199				
c=	0.810				
I =	$a / (T_c + b)^c$				
(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m ³ /s)	(m ³)	(m ³)	(m ³)
10.0	76.8	0.067	39.98	26.93	13.05
15.0	61.8	0.054	48.22	40.39	7.83
20.0	52.0	0.045	54.16	53.86	0.31
25.0	45.2	0.039	58.77	67.32	0.00
30.0	40.0	0.035	62.53	80.79	0.00
35.0	36.1	0.031	65.69	94.25	0.00
40.0	32.9	0.029	68.42	107.72	0.00
45.0	30.2	0.026	70.83	121.18	0.00
50.0	28.0	0.024	72.98	134.65	0.00
55.0	26.2	0.023	74.92	148.11	0.00
60.0	24.6	0.021	76.69	161.58	0.00
65.0	23.2	0.020	78.33	175.04	0.00
70.0	21.9	0.019	79.84	188.51	0.00
75.0	20.8	0.018	81.25	201.97	0.00
80.0	19.8	0.017	82.57	215.44	0.00
85.0	18.9	0.016	83.82	228.90	0.00
90.0	18.1	0.016	84.99	242.37	0.00
95.0	17.4	0.015	86.10	255.83	0.00
100.0	16.7	0.015	87.16	269.30	0.00
105.0	16.1	0.014	88.17	282.76	0.00
110.0	15.6	0.014	89.14	296.23	0.00
115.0	15.0	0.013	90.07	309.69	0.00
120.0	14.6	0.013	90.95	323.16	0.00
125.0	14.1	0.012	91.81	336.62	0.00
130.0	13.7	0.012	92.63	350.08	0.00
135.0	13.3	0.012	93.43	363.55	0.00
140.0	12.9	0.011	94.19	377.01	0.00
145.0	12.6	0.011	94.94	390.48	0.00
150.0	12.3	0.011	95.65	403.94	0.00
155.0	11.9	0.010	96.35	417.41	0.00
160.0	11.7	0.010	97.03	430.87	0.00
165.0	11.4	0.010	97.69	444.34	0.00



Modified Rational Method - Five Year Storm Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa

Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

		Drainage Area A2 Post - Towards Slater Street			
		Drainage Areas		A2 post	
		Area =	0.347	ha	
		"C" =	0.90		
		AC =	0.31		
		Tc =	10.0	min	
		Time Increment =	5.0	min	
5-Year Design Storm		Allowable Release Rate =	44.9	L/s	
		Min. Storage =	27.3	m ³	
a=	998.07				
b=	6.053				
c=	0.814				
I =	$a / (T_c + b)^c$				
(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m ³ /s)	(m ³)	(m ³)	(m ³)
10.0	104.2	0.090	54.23	26.93	27.30
15.0	83.6	0.072	65.24	40.39	24.84
20.0	70.3	0.061	73.13	53.86	19.27
25.0	60.9	0.053	79.24	67.32	11.92
30.0	53.9	0.047	84.21	80.79	3.42
35.0	48.5	0.042	88.39	94.25	0.00
40.0	44.2	0.038	91.99	107.72	0.00
45.0	40.6	0.035	95.16	121.18	0.00
50.0	37.7	0.033	97.99	134.65	0.00
55.0	35.1	0.030	100.55	148.11	0.00
60.0	32.9	0.029	102.88	161.58	0.00
65.0	31.0	0.027	105.03	175.04	0.00
70.0	29.4	0.025	107.02	188.51	0.00
75.0	27.9	0.024	108.87	201.97	0.00
80.0	26.6	0.023	110.60	215.44	0.00
85.0	25.4	0.022	112.24	228.90	0.00
90.0	24.3	0.021	113.78	242.37	0.00
95.0	23.3	0.020	115.24	255.83	0.00
100.0	22.4	0.019	116.63	269.30	0.00
105.0	21.6	0.019	117.95	282.76	0.00
110.0	20.8	0.018	119.22	296.23	0.00
115.0	20.1	0.017	120.43	309.69	0.00
120.0	19.5	0.017	121.59	323.16	0.00
125.0	18.9	0.016	122.71	336.62	0.00
130.0	18.3	0.016	123.79	350.08	0.00
135.0	17.8	0.015	124.83	363.55	0.00
140.0	17.3	0.015	125.83	377.01	0.00
145.0	16.8	0.015	126.81	390.48	0.00
150.0	16.4	0.014	127.75	403.94	0.00
155.0	15.9	0.014	128.66	417.41	0.00
160.0	15.6	0.013	129.55	430.87	0.00
165.0	15.2	0.013	130.41	444.34	0.00



Modified Rational Method - Hundred Year Storm Site Flow and Storage Summary Site Flow and Storage Summary

400 Albert Street, Ottawa


Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

		Drainage Area A2 Post - Towards Slater Street			
		Drainage Areas		A2 Post	
		Area =		0.347	ha
		"C" * =		1.00	
		AC =		0.35	
		Tc =		10.0	min
		Time Increment =		5.0	min
100-Year Design Storm		Allowable Release Rate =		44.9	L/s
a= 1735.69		Min. Storage =		84.9	m ³
b= 6.014					
c= 0.820					
I = a / (T _c + b) ^c					
		* C value for the 100 year storm event is increased by 25%, with a maximum of 1.0 per City's Sewer Design Guidelines			
(1)	(2)	(3)	(4)	(5)	(6)
Time	Rainfall	Storm	Runoff	Target Released	Released
	Intensity	Runoff	Volume	Volume	Volume (A1 Post)
(min)	(mm/hr)	(m ³ /s)	(m ³)	(m ³)	(m ³)
10.0	178.6	0.172	103.27	26.93	76.34
15.0	142.9	0.138	123.96	40.39	83.57
20.0	120.0	0.116	138.74	53.86	84.88
25.0	103.8	0.100	150.15	67.32	82.82
30.0	91.9	0.089	159.39	80.79	78.60
35.0	82.6	0.080	167.15	94.25	72.90
40.0	75.1	0.072	173.84	107.72	66.12
45.0	69.1	0.067	179.70	121.18	58.52
50.0	64.0	0.062	184.93	134.65	50.29
55.0	59.6	0.057	189.65	148.11	41.54
60.0	55.9	0.054	193.95	161.58	32.38
65.0	52.6	0.051	197.91	175.04	22.86
70.0	49.8	0.048	201.57	188.51	13.06
75.0	47.3	0.046	204.97	201.97	3.00
80.0	45.0	0.043	208.16	215.44	0.00
85.0	43.0	0.041	211.15	228.90	0.00
90.0	41.1	0.040	213.98	242.37	0.00
95.0	39.4	0.038	216.66	255.83	0.00
100.0	37.9	0.037	219.21	269.30	0.00
105.0	36.5	0.035	221.63	282.76	0.00
110.0	35.2	0.034	223.95	296.23	0.00
115.0	34.0	0.033	226.16	309.69	0.00
120.0	32.9	0.032	228.29	323.16	0.00
125.0	31.9	0.031	230.33	336.62	0.00
130.0	30.9	0.030	232.30	350.08	0.00
135.0	30.0	0.029	234.20	363.55	0.00
140.0	29.2	0.028	236.03	377.01	0.00
145.0	28.4	0.027	237.81	390.48	0.00
150.0	27.6	0.027	239.52	403.94	0.00
155.0	26.9	0.026	241.19	417.41	0.00
160.0	26.2	0.025	242.80	430.87	0.00
165.0	25.6	0.025	244.37	444.34	0.00

APPENDIX D


Sanitary Data Analysis



SANITARY SEWER DESIGN SHEET

400 Albert Street

CITY OF OTTAWA

LOCATION		RESIDENTIAL												COMMERCIAL			INFILTRATION			SEWER DESIGN					
	SECTION (ha.)	SINGLE FAMILY DWELLING @ 3.4 ppu	SEMI- DETACHED / DUPLEX / TOWNHOUSE @ 2.7 ppu	STACKED TOWNHOUSE @ 2.3 ppu	BACHELOR @1.4 ppu	1 BED @1.4 ppu	2 BED @2.1 ppu	3 BED @3.1 ppu	AVERAGE @1.8 ppu	TOTAL RESIDENTIAL POPULATION population	AVERAGE RES. FLOW @ 280 L/c/d (L/s)	HARMON PEAKING FACTOR	RES. PEAK FLOW (L/s)	COMMERCIAL AREA (ha.)	AVERAGE COMMERCIAL FLOW @50000L/ha/d (L/s)	COMMERCIAL PEAK FLOW (L/s)	TOTAL ACCUM. AREA (ha.)	INFILT. @ 0.28 L/s/ha. (L/s)	TOTAL DESIGN FLOW (L/s)	PIPE LENGTH (m)	PIPE DIA. (mm)	SLOPE (%)	FULL FLOW CAPACITY n = 0.013 (L/sec)	% of DESIGN CAPACITY (%)	
column number	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	(23)	(24)	
Existing Condition																									
Retail	0.583	0	0	0	0	0	0	0	0	0.00	0.00	4.00	0.00	0.09	0.05	0.08	0.58	0.163	0.24	-	-	-	-	-	
Proposed Condition																									
Mixed Use Development	0.583	0	0	0	0	0	0	0	930	1674	5	3.64	19.77	0.29	0.17	0.17	0.58	0.163	20.10	10.8	250	2.0%	84.10	23.90%	
																	Total Net Flow		19.86						
Average Residential Flow Rate - 280 Litres / capita / day					Infiltration Allowance (Dry Weather) - 0.05 Litres / s / grosss ha																				
Average Daily Flow Commercial - 50,000 Litres / gross ha / day					Infiltration Allowance (Wet Weather) - 0.28 Litres / s / grosss ha																				
Average Daily Flow Institutional - 50,000 Litres / gross ha / day					Infiltration Allowance (Total I/I) - 0.33 Litres / s / grosss ha																				
Average Daily Flow Industrial - 35,000 Litres / gross ha / day					Peaking Factor = 1 + [14 / (4 + P ^{0.5})], P=Population in thousands																				
Site Area: 0.583 Ha																									
<div><div></div></div>																	Prepared By: Catherine Agiou, P. E., M.A.Sc. Reviewed by: Nick Moutzouris, P.Eng., M.A.Sc. Date: May 2020		Project: 400 Albert Street Project: UD19-048 City of Ottawa					Sheet 1 OF 3	



DOWNSTREAM SANITARY SEWER SEGMENT INFORMATION				
SEWER SEGMENT	TYPE	SIZE (mm)	LENGTH (m)	SLOPE (%)
#1	CIRCULAR	375	51.44	0.23



150 Bermondsey Road, North York, Ontario, M4A 1Y1

LEGEND

- DRAINAGE AREA
- - - - - SANITARY TRUNK SEWER
- EXISTING SANITARY/ COMBINED SEWER

- EXISTING MANHOLE
- #1 NUMBERED SEGMENT AS INDICATED IN "EXTERNAL SANITARY SEWER SEGMENTS" DESIGN SHEET

- LAND-USE TYPE
- DRAINAGE AREA (ha)
- COMPOSITE RUNOFF COEFFICIENT

DOWNSTREAM
SANITARY NETWORK
MIXED USE DEVELOPMENT
400 ALBERT STREET
OTTAWA, ONTARIO

DATE: MAY 2020	PROJECT No: UD19-048
SCALE: N.T.S.	FIGURE No: DAP3



EXTERNAL SANITARY SEWER SEGMENTS
DRY WEATHER
400 Albert Street
CITY OF OTTAWA

280 L/gross ha/day - existing commercial
280 L/c/day - existing residential

M = Peaking Factor (residential) = $1 + 14/(4+P^{.5})$ where P = population in 1000's

q = average daily per capita flow (c.m./day)
Q (p) = peak population flow (L/s)
Q (I) = peak extraneous flow (L/s)
Q (C) = peak flow from commercial area (L/s)
Q (d) = peak design flow (L/s)

I = unit of peak extraneous flow
Q(p) = $PqM/86.4$ (L/s)
Q(I) = IA (L/s) where I = 0.05 L/s/ha, and A = drainage area - commercial area (ha)
Q(C) = based on Y L/p/day - residential equivalent (see below)
Q(d) = Q(p) + Q(I) + Q(C)

LOCATION					POPULATION			Peak Factor (residential) M (dimensionless)	Drainage Area (cumulative) (hectares)	F L O W S (CUMMULATIVE)						GRADE (used) (%) Max. Allowable Flow (L/s) PIPE SIZE (mm)			Pre-development % of DESIGN CAPACITY (%)	Post-development % of DESIGN CAPACITY (%)																
					RESIDENTIAL (@ 280 people/unit) (persons)	TOTAL RESIDENTIAL (cumulative) (persons)	TOTAL PEOPLE (cumulative) (persons)			RESIDENTIAL Q (p) (L/s)	INFILTRATION Q (I) (L/s)	COMMERCIAL Q (C) (L/s)	EXISTING PEAK FLOW (Cumulative) (L/s)	PROPOSED FLOW Q(prop.)* (L/s)	TOTAL PEAK DESIGN FLOW (Cumulative) (L/s)																					
DESCRIPTION	Sewer Segment	Drainage Area (hectares)	Homes (units)	Residential (hectares)	Commercial (hectares)																															
column number	1	2	3	4	5	6		7		8		9		10		11		12		13		14		15		16		17		18		19		20		21
DOWNSTREAM SEWER SEGMENTS																																				
Sewer Segment	# 1	0.49	0	2.65	0.88	742		742		742		3.88		0.49		9.33		0.02		28.49		37.85		19.86		57.7		0.23%		84.1		375		45.0%		68.6%
Trunk Sewer																																				

- NOTES:
- Calculated flows are estimated based on the existing development within the drainage area.
 - The population equivalent for medium density development (apartments) was assumed at 280 people/hectare.
 - The post development flow can be supported by the existing sanitary network, thus the sewers can support the proposed development.



Prepared By: Catherine Agiou, P. E., M.A.Sc.
Reviewed by: Nick Moutzouris, P.Eng., M.A.Sc.
Date: May 2020

Project: 400 Albert Street
Project: IUD19-048
City of Toronto

<div><div><div></div><div>Lithos</div></div><div><div>EXTERNAL SANITARY SEWER SEGMENTS</div><div>WET WEATHER</div><div>400 Albert Street</div><div>CITY OF OTTAWA</div></div></div>										<div><div>280 L/gross ha/day - existing commercial</div><div>280 L/c/day - existing residential</div></div> <div><div>q = average daily per capita flow (c.m./day)</div><div>Q (p) = peak population flow (L/s)</div><div>Q (I) = peak extraneous flow (L/s)</div><div>Q (C) = peak flow from commercial area (L/s)</div><div>Q (d) = peak design flow (L/s)</div></div> <div><div>M = Peaking Factor (residential) = 1 + 14/(4+P^0.5) where P = population in 1000's</div><div>I = unit of peak extraneous flow</div><div>Q(p) = PqM/86.4 (L/s)</div><div>Q(I) = IA (L/s) where I = 0.28 L/s/ha, and A = drainage area - commercial area (ha)</div><div>Q(C) = based on Y L/p/day - residential equivalent (see below)</div><div>Q(d) = Q(p) + Q(I) + Q(C)</div></div>																	
SANITARY FLOW																											
LOCATION					POPULATION			Peak Factor (residential) M	Drainage Area (cumulative)				2-Year Event Storm Flow														
DESCRIPTION	Sewer Segment based on HVM figure	Drainage Area (hectares)	Homes (units)	Residential (hectares)	Commercial (hectares)	RESIDENTIAL (@ 280 people/unit) (persons)	TOTAL RESIDENTIAL (cumulative) (persons)			TOTAL PEOPLE (cumulative) (persons)	RESIDENTIAL Q (p) (L/s)	INFILTRATION Q (I) (L/s)	COMMERCIAL Q (C) (L/s)	Commercial Area Coefficient		Road Area Coefficient		STORM Q (S) (L/s)	EXISTING PEAK FLOW (Cumulative) (L/s)	PROPOSED FLOW Q(prop.)* (L/s)	TOTAL PEAK DESIGN FLOW (Cumulative) (L/s)	GRADE (used) (%)	Max. Allowable Flow (L/s)	PIPE SIZE (mm)	Pre-development % of DESIGN CAPACITY (%)	Post-development % of DESIGN CAPACITY (%)	
column number	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	
DOWNSTREAM SEWER SEGMENTS																											
Sewer Segment	# 1	1.37	0	2.65	0.88	742	742	742	3.88	1.37	9.33	0.38	28.49	0.06	0.68	0.04	0.90	15.08	53.28	19.86	73.1	0.23%	84.1	375	63.4%	87.0%	
Trunk Sewer																											
NOTES:																											
1. Calculated flows are estimated based on the existing development within the drainage area.																											
2. The population equivalent for medium density development (appartments) was assumed at 280 people/hectare.																											
3. The post development flow can be supported by the existing sanitary network, thus the sewers can support the proposed development.																											
<div><div><div></div><div>Lithos</div></div></div>		Prepared By: Catherine Agiou, P. E., M.A.Sc. Reviewed by: Nick Moutzouris, P.Eng., M.A.Sc. Date: May 2020								Project: 400 Albert Street																	
										Project: IUD19-048																	
City of Toronto																											
Sheet 3 OF 3																											

APPENDIX E

Water Data Analysis



WATER DEMAND

400 Albert Street

File No: UD19-048

Date: May 2020

Prepared By: Catherine Agiou, P. E., M.A.Sc.

Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

Fire Flow Calculation

Slater Street

1 $F = 220 C (A)^{1/2}$

Where F = Fire flow in Lpm

C = construction type coefficient

= 0.6

A = total floor area in sq.m. excluding basements

		Area Applied
Level 1=	2317.00 m ²	100%
Level 2=	1390.00 m ²	25%
Level P1=	0.00 m ²	0%
=	2,664.5 sq.m.	
F =	6,813.68 L/min	$F(No. 1) = 200C\sqrt{A}$
F =	7,000 L/min	$F(No. 1)$ Round to nearest 1000 l/min

Note: The levels indicated, reference the floors with the largest areas (refer to architectural design)

2 Occupancy Reduction

15% reduction for limited-combustible occupancy

$F = 5950 \text{ L/min}$ $F(No. 2) = F(No. 1) \times \text{occupancy reduction/charge}(\%)$

3 Sprinkler Reduction

30% Reduction for NFPA Sprinkler System

$F = 4165 \text{ l/min}$ $F(No. 3) = F(No. 2) \times \text{sprinkler reduction}(\%)$

4 Separation Charge

20% West 3.1m to 10m

0% North 0m to 3.0m

0% South Road

0% East Road

20% Total Separation Charge

$F = 1,190.00 \text{ L/min}$ $F(No. 4) = F(No. 2) \times \text{separation charge}(\%)$

$F = 5,355.00 \text{ L/min}$ $F(tot) = F(No. 3) + F(No. 4)$

$F = 5,000 \text{ L/min}$ $F(tot)$ Round to nearest 1000 l/min

83.33 L/s

$F = 1321 \text{ US GPM}$

Domestic Flow Calculations

Population=	551 Persons	Tower B	
Office Area =	0.0 m ²		
Average Day Demand (Residential) =	350.0 L/person/day		
Average Day Demand (Commercial) =	2.5 L/m ² /day (OBC)		1 US Gallon=3.785 L
Average Residential Water Demand=	2.23 L/s		
	35 US GPM		1 US GPM=15.852L/s
Average Commercial Water Demand=	0.00 L/s		
	0 US GPM		

Max. Daily Residential Demand Peaking Factor= 2.5

Max. Daily Commercial Demand Peaking Factor = 1.5

Max. Daily Demand = 5.58 L/s = 88 US GPM

or

Max. Hourly Residential Demand Peaking Factor = 2.2

Max. Hourly Commercial Demand Peaking Factor = 1.8

Max. Hourly Demand = 12.28 L/s = 195 US GPM

Max Daily Demand = 5.58 L/s

Fire Flow = 83.33 L/s

Required 'Design' Flow = 88.91 L/s
1409 US GPM

Note: Required 'Design' Flow is the maximum of either:
1) Fire Flow + Maximum Daily Demand
2) Maximum Hourly Demand



WATER DEMAND

400 Albert Street

File No: UD19-048

Date: February 2020

Prepared by: Matina Sakoutsiou

Reviewed By: Nick Moutzouris, P.Eng., M.A.Sc.

Fire Flow Calculation

Albert Street

1 $F = 220 C (A)^{1/2}$

Where F= Fire flow in Lpm

C= construction type coefficient

= 0.6

A = total floor area in sq.m. excluding basements

		Area Applied
Level 2=	0.00 m ²	100%
Level 1=	0.00 m ²	25%
Level 3=	0.00 m ²	25%
=	0.0 sq.m.	
F =	0.00 L/min	$F(\text{No. 1}) = 200C\sqrt{A}$
F =	0 L/min	$F(\text{No. 1}) \text{ Round to nearest } 1000 \text{ l/min}$

Note: The levels indicated, reference the floors with the largest areas (refer to architectural design)

2 Occupancy Reduction

15% reduction for limited-combustible occupancy

$F = 0 \text{ L/min}$ $F(\text{No. 2}) = F(\text{No. 1}) \times \text{occupancy reduction/charge}(\%)$

3 Sprinkler Reduction

30% Reduction for NFPA Sprinkler System

$F = 0 \text{ l/min}$ $F(\text{No. 3}) = F(\text{No. 2}) \times \text{sprinkler reduction}(\%)$

4 Separation Charge

0% West Road

20% North 3.1m to 10m

0% South Road

15% East 10.1m to 20m

35% Total Separation Charge

$F = 0.00 \text{ L/min}$ $F(\text{No. 4}) = F(\text{No. 2}) \times \text{separation charge}(\%)$

$F = 0.00 \text{ L/min}$ $F(\text{tot}) = F(\text{No. 3}) + F(\text{No. 4})$

$F = 0 \text{ L/min}$ $F(\text{tot}) \text{ Round to nearest } 1000 \text{ l/min}$

$F = 0.00 \text{ L/s}$

$F = 0 \text{ US GPM}$

Domestic Flow Calculations

Population=	1123 Persons	Towers A + C
Office Area =	2884.0 m ²	
Average Day Demand (Residential) =	350.0 L/person/day	
Average Day Demand (Commercial) =	2.5 L/m ² /day (OBC)	1 US Gallon=3.785 L
Average Residential Water Demand=	4.55 L/s	
	72 US GPM	1 US GPM=15.852L/s
Average Commercial Water Demand=	0.08 L/s	
	1 US GPM	

Max. Daily Residential Demand Peaking Factor= 2.5

Max. Daily Commercial Demand Peaking Factor = 1.5

Max. Daily Demand = 11.50 L/s = 182 US GPM

or

Max. Hourly Residential Demand Peaking Factor = 2.2

Max. Hourly Commercial Demand Peaking Factor = 1.8

Max. Hourly Demand = 25.25 L/s = 400 US GPM

Max Daily Demand = 11.50 L/s

Fire Flow = 0.00 L/s

Required 'Design' Flow = 11.50 L/s
182 US GPM

Note: Required 'Design' Flow is the maximum of either:

- 1) Fire Flow + Maximum Daily Demand
- 2) Maximum Hourly Demand

From: Wu, John
To: catherine@lithosgroup.ca
Subject: RE: 400 Albert Street - Boundary conditions
Date: January 22, 2020 10:53:05 AM
Attachments: [image001.png](#)
[400 Albert Jan 2020.pdf](#)

The following are boundary conditions, HGL, for hydraulic analysis at 400 Albert (zone 1W) assumed to be connected to the 203mm on Albert and 381mm on Slater (see attached PDF for location).

Minimum HGL = 106.5m

Maximum HGL = 116.5m

MaxDay + FireFlow (100 L/s) = 110.5m, Slater connection

MaxDay + FireFlow (100 L/s) = 106.0m, Albert connection

These are for current conditions and are based on computer model simulation.

Disclaimer: The boundary condition information is based on current operation of the city water distribution system. The computer model simulation is based on the best information available at the time. The operation of the water distribution system can change on a regular basis, resulting in a variation in boundary conditions. The physical properties of watermain deteriorate over time, as such must be assumed in the absence of actual field test data. The variation in physical watermain properties can therefore alter the results of the computer model simulation.

John

From: catherine@lithosgroup.ca <catherine@lithosgroup.ca>
Sent: January 20, 2020 10:22 AM
To: Wu, John <John.Wu@ottawa.ca>
Cc: 'Matina Sakoutsiou' <matinas@lithosgroup.ca>
Subject: RE: 400 Albert Street - Boundary conditions

CAUTION: This email originated from an External Sender. Please do not click links or open attachments unless you recognize the source.

ATTENTION : Ce courriel provient d'un expéditeur externe. Ne cliquez sur aucun lien et n'ouvrez pas de pièce jointe, excepté si vous connaissez l'expéditeur.

Good Morning John,

Yes, the three towers share the same basement.

Thank you,

Catherine Agiou, P.E., M.A.Sc.
Project Designer / Coordinator



Lithos Group Inc.

150 Bermondsey Road, Unit #200
Toronto, Ontario M4A 1Y1
Direct: (437) 889-9950 T: (416) 750-7769
Catherine@LithosGroup.ca
www.LithosGroup.ca

CONFIDENTIALITY NOTE

This email may contain confidential information and any rights to privilege have not been waived.
If you have received this transmission in error, please notify us by telephone or e-mail. Thank you.

From: Wu, John <John.Wu@ottawa.ca>
Sent: January 20, 2020 9:37 AM
To: catherine@lithosgroup.ca
Subject: RE: 400 Albert Street - Boundary conditions

Is it internal connected? all three?

From: catherine@lithosgroup.ca <catherine@lithosgroup.ca>
Sent: January 17, 2020 1:24 PM
To: Wu, John <John.Wu@ottawa.ca>
Cc: 'Matina Sakoutsiou' <matinas@lithosgroup.ca>
Subject: 400 Albert Street - Boundary conditions

CAUTION: This email originated from an External Sender. Please do not click links or open attachments unless you recognize the source.

ATTENTION : Ce courriel provient d'un expéditeur externe. Ne cliquez sur aucun lien et n'ouvrez pas de pièce jointe, excepté si vous connaissez l'expéditeur.

I hope this email finds you well.

Kindly find attached the relative data in order to provide us the boundary conditions for the subject site.

Note that the connections will be as follows:

- Domestic Water : Tower A + C to the 200mm watermain along Albert Street
Tower B to the 375mm watermain along Slater Street.

- Fire Service : The entire property will be serviced by the 375mm watermain along Slater Street.

Thank you for your help.

Should you have any questions, please let us know.

Sincerely,

Catherine Agiou, P.E., M.A.Sc.
Project Designer / Coordinator



Lithos Group Inc.

150 Bermondsey Road, Unit #200

Toronto, Ontario M4A 1Y1

Direct: (437) 889-9950 T: (416) 750-7769

Catherine@LithosGroup.ca

www.LithosGroup.ca

CONFIDENTIALITY NOTE

This email may contain confidential information and any rights to privilege have not been waived.

If you have received this transmission in error, please notify us by telephone or e-mail. Thank you.

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.


Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.

Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

APPENDIX F

Engineering Drawings



150 Bermondsey Road, North York, Ontario, M4A 1Y1

LEGEND

- | | | | | | |
|--|-------------------|--|---------------------------|--|---------------------|
| | PROPERTY LINE | | PROPOSED SANITARY SEWER | | WATERMAIN ABANDONED |
| | EXISTING STORM | | PROPOSED WATERMAIN | | GASMAIN ABANDONED |
| | EXISTING SANITARY | | PROPOSED STORMWATER SEWER | | |
| | EXISTING WATER | | EXISTING GASMAIN | | |

PROPOSED SERVICING FIGURE
MIXED USE DEVELOPMENT
400 ALBERT STREET
OTTAWA, ONTARIO

DATE: MAY 2020

PROJECT No: UD19-048

SCALE: N.T.S.

FIGURE No: FIG-3