Phase Two Environmental Site Assessment

2829 Dumaurier Avenue Ottawa, Ontario

Prepared for: 3223701 Canada Inc.



June 11, 2021

Ref: LOP21-004C

Table of Contents

1.	1. Executive Summary				
2.	Intr	Introduction			
	i.	Site Description	3		
	ii.	Property Ownership	3		
	iii.	Current and Proposed Future Use	3		
	iv.	Applicable Site Condition Standard	4		
3.	Background Information				
	i.	Physical Setting	5		
	ii.	Past Investigations	5		
4.	Scope of Investigation				
	i.	Overview of Site Investigation	9		
	ii.	Media Investigation	11		
	iii.	Phase One Conceptual Site Model	12		
	iv.	Deviations from Sampling and Analysis Plan	13		
	V.	Impediments	14		
5.	Inve	14			
	i.	General	14		
	ii.	Drilling	15		
	iii.	Soil Sampling	15		
	iv.	Field Screening Measurements	16		
	V.	Groundwater: Monitoring Well Installation	16		
	vi.	Groundwater: Field Measurement of Water Quality Parameters	17		
	vii.	Groundwater: Sampling	18		
	viii.	Sediment: Sampling	18		
	ix.	Analytical Testing	18		
	x.	Residue Management Procedures	18		
	xi.	Elevation Surveying	19		
	xii.	Quality Assurance and Quality Control Measures	19		
6.	Rev	riew and Evaluation	21		

	i.	Geology	21
	ii.	Groundwater and Elevations and Flow Direction	23
	iii.	Groundwater: Hydraulic Gradients	25
	iv.	Fine-Medium Soil Texture	25
	V.	Soil Field Screening	25
	vi.	Soil Quality	26
	vii.	Groundwater Quality	27
	viii.	Sediment Quality	29
	ix.	Quality Assurance and Quality Control Results	30
	X.	Phase Two Conceptual Site Model	31
7.	Con	oclusions	33
	i.	Signatures	34
8.	Limi	itations	35
9.	Refe	erences	36
10.	App	pendices	37
Figu	re 1:		
Figu		Key Plan	
Figu Figu Lis	re 1: re 2: t of	Key Plan Site Plan Tables	
Figu Figu Lis Tabl Tabl Tabl Tabl	re 1: re 2: t of e 1: I e 2: 0 e 3: 3 e 4: 0 e 5: 3	Key Plan Site Plan	24 26 28 Following Text
Figu Figu Lis Tabl Tabl Tabl Tabl Tabl	re 1: re 2: t o1 e 1: I e 2: 0 e 3: 3 e 4: 0 e 5: 3 e 6: 0	Key Plan Site Plan F Tables Monitoring Well Construction Details	24 26 28 Following Text

1. Executive Summary

Lopers & Associates (Lopers) was retained by 3223701 Canada Inc. (Brigil) to complete a Phase Two Environmental Site Assessment (Phase Two ESA) of the commercial property with Civic address No. 2829 Dumaurier Avenue, Ottawa, Ontario ("Phase Two Property", "Property" or "Site").

This Phase Two ESA is being completed as part of due diligence requirements associated with the submission of a Development Application to the City of Ottawa Municipal Planning Department.

Lopers has previously completed a Phase One Environmental Site Assessment (Phase One ESA) (Reference No. LOP20-004A, dated January 8, 2021) for Brigil at the Property. The Phase One ESA identified the presence of one potentially contaminating activity (PCA) at the Property (and adjacent land to the north and east) which was interpreted to represent an area of potential environmental concern (APEC). The presence of a former waste disposal site on the north portion of the Phase One Property (PCA #1) is a significant PCA which represents APEC #1 for the Property. The contaminants of potential concern (CPCs) associated with the former waste disposal site are VOCs (for groundwater only), metals, PAHs and PHCs/BTEXs.

A recent (2019) GHD Phase Two ESA was completed by others (as supervised by Mr. Luke Lopers, author of this report) for Brigil; the subject of which was a larger parcel of land which includes the Phase Two Property as well as the adjacent commercial property to the south, including the entire Dumaurier Plaza. Lopers understands that because of information contained in this report that is not specific to only the Property a revised Phase Two ESA report, which is Site specific is required. This Phase Two ESA report includes reference to all available investigations completed at the Property.

As part of historical investigations, at least seven boreholes were drilled at the Phase Two Property. All seven of these boreholes were instrumented with groundwater monitoring wells with screens installed in either the overburden or bedrock.

As part of historical investigations, at least one soil sample was submitted for laboratory analysis for Polycyclic Aromatic Hydrocarbons (PAHs), metals and inorganics. One sample was also submitted for toxicity leaching characteristic procedure (TCLP) for waste characterization purposes.

Groundwater sampling was completed at the time of the 2019 GHD Phase Two ESA. An additional round of groundwater monitoring and sampling was completed of the viable monitoring wells at the Phase Two Property as part of this investigation in May of 2021. A total of nine groundwater samples, including two duplicate samples and two trip blanks, were

submitted for laboratory analysis for a combination of PHCs, BTEXs, VOCs, PAHs, metals and inorganics.

The applicable site condition standard was determined to be the full depth generic site condition standard, in a non-potable groundwater condition, with course textured soil, for residential property use, as specified in Table 3 of the MECP Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act, April 15, 2011.

The groundwater sample BH3S, collected in October of 2018 from a screen depth of approximately 2.2-3.7 m BGS, had reported concentrations of PHC F2 range (170 μ g/g vs. 150 μ g/g) and PHC F3 range (860 μ g/g vs. 500 μ g/g). All of the other soil and groundwater results for the Phase Two Property are in compliance with the applicable site condition standards. It should be noted that the monitoring well BH3D was installed for vertical delineation purposes for BH3S; BH3D had no detectable PHC concentrations in a sample collected the same date as the aforementioned sample from BH3S. The Phase Two Property is not in compliance with the site condition standards as of the certification date of May 17, 2021.

Historical environmental reports referenced the presence of a layer of buried refuse/waste at the Phase Two Property, however, the specific investigations (including associated borehole logs and laboratory analytical results) referenced were not available as part of this Phase Two ESA. Although there were no observations of refuse/waste or evidence of deleterious fill material identified in any of the boreholes drilled as part of the 2019 GHD Phase Two ESA or the 2019 Paterson Geotechnical Investigation, it is suspected that waste and/or poor environmental quality fill material may have been placed at the Property in locations not assessed as part of the aforementioned investigations.

There is suspected soil and/or groundwater contamination at the Phase Two Property. Additional investigation and confirmation of soil and groundwater quality in this area of the Property is recommended at the time of excavation for site redevelopment. It should be noted that the proposed redevelopment includes excavation for at least two to three levels of underground parking, which is expected to be sufficient for remediation of the aforementioned environmental contamination at the Phase Two Property.

An environmental remediation program, including the bulk removal and off-site disposal of soil and groundwater in excess of the site condition standards is required for the Phase Two Property. Further delineation and confirmation of remediation sampling will be required prior to confirmation of compliance with the site condition standards and prior to the submission of a Record of Site Condition (RSC); however, these tasks can be completed at the time decommissioning and demolition of existing structures at the Phase Two Property in conjunction with the proposed redevelopment. The submission and acknowledgment of an RSC would be required prior to occupancy of the Phase Two Property for residential purposes following redevelopment, however, these tasks can be completed following decommissioning

and demolition of existing structure at the Phase Two Property. The Phase Two ESA could be then updated at that time to show compliance with site condition standards.

Preparation of a soil management plan in accordance with O.Reg. 406/19 will be required as part of management of excess soil generated as part of construction activities. It is recommended that a remedial action plan be prepared to develop a strategy for remediation, including soil and groundwater management, during redevelopment.

2. Introduction

Lopers & Associates (Lopers) was retained by 3223701 Canada Inc. (Brigil) to complete a Phase Two Environmental Site Assessment (Phase Two ESA) of the commercial property with Civic address No. 2829 Dumaurier Avenue, Ottawa, Ontario ("Phase Two Property", "Property" or "Site"). The location of the Phase Two Property within the City of Ottawa is presented on Figure 1: Key Plan.

i. Site Description

The Phase Two Property has a Civic address of 2829 Dumaurier Avenue, Ottawa, Ontario. The Property is legally described as Part of Lot 20, Concession 2, Ottawa Front, Registered Plan 479600, Township of Nepean, now in the City of Ottawa and has a property identifier number of 03944-0237. The boundaries of the Phase Two Property are presented on Figure 2: Site Plan.

Based on approximate dimensions obtained from the City of Ottawa's GIS mapping tool, the Phase Two Property has an approximate area of 4,200 m2 (0.42 Hectares). The Phase Two Property is immediately surrounded by the adjoining south portion of Dumaurier Plaza to the south, a municipal Right-of-Way followed by Dumaurier Park to the east, by institutional properties to the north, and by residential properties to the west.

ii. Property Ownership

The Phase Two Property is currently owned by 3223701 Canada Inc., a subsidiary company of Brigil Construction ("Brigil"). This Phase Two ESA was commissioned by Mr. Jean-Luc Rivard, Director of Land Development and Infrastructure for Brigil Construction (Brigil), operating as 3223701 Canada Inc. Brigil has a business address of 98 Rue Lois, Gatineau, Quebec, J8Y 3R7 and a business telephone number of 819-243-7392.

iii. Current and Proposed Future Use

It is Lopers' understanding that Brigil intends to redevelop the Phase Two Property for mixed use (commercial and residential purposes), including the current concept for construction of one building, approximately 30 storeys in height, with subgrade parking, commercial ground floors and residential units above.

The redevelopment plan for the Phase Two Property includes mixed use (residential and commercial), which is the current zoning of the Phase Two Property. Given that the proposed redevelopment will involve a more stringent land use, a record of site condition (RSC) will be required to be filed with the Ministry of Environment, Conservation and Parks (MECP) for the Phase Two Property. An update to this Phase Two ESA (post-remediation) can be used as supporting documentation as part of filing of an RSC.

iv. Applicable Site Condition Standard

Through Ontario Regulation 153/04 (O.Reg. 153/04) the Ministry of Environment, Conservation and Parks (MECP) prescribes the conditions to determine the applicable site condition standard for a property.

The proposed future use of the Phase Two Property is for mixed ground floor commercial and residential use, however residential land use standards have been applied for the purposes of this report as they represent the more environmentally sensitive land use conditions.

The Phase Two Property and all other properties within 250 m of the property boundaries are supplied by the municipal drinking water system. There is no proposed agricultural use and there are no wells within 250 m of the property boundaries that are intended for use as a source of water for human consumption or agriculture. As such, the designation of non-potable groundwater setting is determined to be applicable [O.Reg. 153/04, section 35].

The soil and groundwater quality over the full depth of overburden was considered for this Phase Two ESA. The full depth generic site condition standards were selected for comparison for the Phase Two Property [O.Reg. 153/04, sections 36, 37, 38, 39 and 40].

The Phase Two Property is not situated within or adjacent to an area of natural significance and does not include any land within 30 m of an area of natural significance. The pH of the soil was analyzed as part of this Phase Two ESA and was reported at 7.44. As such, the Phase Two Property is not considered to be an environmentally sensitive area [O.Reg. 153/04, section 41].

A substantial layer of fill, consisting of silty sand and gravel, which would be classified as coarse grained soil, is present to near full depth to bedrock on the Phase Two Property. It is interpreted that greater than 1/3 of the Phase Two Property has coarse grained soil. For the purposes of this Phase Two ESA, the soil conditions are considered to be coarse grained, which provides a more conservative comparison to the MECP site condition standards than the fine-grained values [O.Req. 153/04, section 42].

Review of the borehole/monitoring well logs completed as part of previous investigations was completed. It was determined that greater than 2/3 of the Phase Two Property has greater than 2 m of overburden soil. The Phase Two Property is not considered a shallow soil property [O.Reg. 153/04, section 43.1].

The Phase Two Property does not include and does not have any land located within 30 m of a water body. The MECP site condition standards for use within 30 m of a water body do not apply [O.Reg. 153/04, section 43.1].

The full depth generic site condition standards, with non-potable groundwater, course textured soil, for residential/parkland/institutional property use, as specified in Table 3 of the MECP Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act, April 15, 2011 were determined to be the applicable site condition standards for the Phase Two Property as part of this Phase Two ESA.

3. Background Information

i. Physical Setting

No water bodies or areas of natural significance are located at the Phase Two Property or in the Phase One Study Area. There were no areas of natural and scientific interest (ANSIs) or areas of natural significance identified in the Phase One Study Area.

The local regional topography in the Phase One Study Area is undulating but generally slopes downward to the south. Regionally, the topography slopes downward to the northwest, toward the Ottawa River. The north portion of the Phase Two Property is elevated approximately 2 m with respect to the south portion of the Property. The Ottawa River is located approximately 1.3 km northwest of the Phase Two Property.

Surface water drainage at the Phase Two Property is by sheet drainage to catch basins located on the paved surfaces of the Property, which drain into the municipal stormwater sewer system.

No drinking water wells are located at the Phase Two Property and the Phase One Study Area are serviced by municipally treated drinking water. The Phase Two Property and Study Area are not located in the vicinity of any well-head protection areas or other designation identified by the City of Ottawa in its official plan for the protection of ground water. No private or agricultural water supply wells are located within the Phase One Study Area.

ii. Past Investigations

A Phase One ESA report was prepared prior to this Phase Two ESA: "Phase One Environmental Site Assessment, 2829 Dumaurier Avenue, Ottawa, Ontario" dated January 8, 2021 prepared for 3223701 Canada Inc. by Lopers & Associates. The Phase One ESA identified four potentially contaminating activities (PCAs) at the Phase One Property, which include:

• The presence of a former waste disposal site on the north portion of the Phase One Property is a significant PCA (PCA #1) which represents an APEC for the Property. Given that previous environmental reports and investigations have documented petroleum

hydrocarbon (PHC) groundwater contamination and that waste fill material has been observed in boreholes on the north portion of the Property, the Property is not in compliance with the Soil, Groundwater and Sediment Standards for use under Part XV.1 of the Environmental Protection Act, which are also for consideration of O.Reg. 153/04.

- The contaminants of potential concern (CPCs) associated with the former waste disposal site are volatile organic compounds (VOCs) (for groundwater only), metals, polycyclic aromatic hydrocarbons (PAHs) and PHCs/BTEXs. An investigation of the soil and groundwater quality with respect to these CPCs at the Property was completed by others in 2019.
- One active automotive service garage and a historical retail fuel outlet are located at
 properties in the Phase One Study Area and constitute PCA#2 and PCA#3, respectively.
 The PCAs at properties in the Phase One Study Area are located significant distances
 and/or at cross-gradient orientations with respect to the Phase One Property and are not
 considered to represent APECs for the Phase One Property.

Based on the identification of PCAs and APECs at the Phase One Property, a Phase Two Environmental Site Assessment was recommended to be completed to assess the soil groundwater quality in the vicinity of the APECs.

Brigil provided the following four reports for review prior to Lopers completing the Phase One ESA:

- 1. "Phase I Environmental Site Assessment, 2831, 2833, 2835, 2841 and 2865 Dumaurier Avenue, Ottawa, Ontario", dated August 16, 2018, completed by GHD Limited for 3223701 Canada Inc.
- 2. "Phase Two Environmental Site Assessment, 2831, 2833, 2835, 2841 and 2865 Dumaurier Avenue, Ottawa, Ontario", dated April 2, 2019, completed by GHD Limited for 3223701 Canada Inc.
- 3. "Geotechnical Investigation, Proposed Hi-Rise Building, 2829 Dumaurier Avenue, Ottawa, Ontario", dated December 18, 2019, completed by Paterson Group Inc. for 3223701 Canada Inc.
- 4. "Methane Gas Detection Monitoring Program (2015-2019), Dumaurier Plaza 2829 Dumaurier Avenue, Closed Pinecrest Landfill Site, Ottawa, Ontario", dated August 26, 2020, completed by Wood Canada Limited for 1248816 Ontario Inc.

2018 Phase I Environmental Site Assessment by GHD (2018 GHD Phase I ESA)

The 2018 GHD Phase I ESA was completed for a larger parcel of land which included that Phase One Property and the adjacent commercial land to the south, including the entire Dumaurier Plaza. The Phase One Property was occupied by the northern portion of the present-day commercial plaza building at the time of the 2018 GHD Phase I ESA. The occupants of the plaza

were retail commercial and did not include any operations which were interpreted as PCAs. The presence of a former waste disposal site was identified on the northeast portion of the Phase One Property and on adjacent land to the east. This former waste disposal site is associated with the PCA of "Waste Disposal and Waste Management, including thermal treatment, landfilling and transfer of waste, other than use of biosoils as soil conditioners" (PCA #1). This former waste disposal site is a significant PCA and is considered to represent APEC #1 for the Property. The location of this PCA and APEC is depicted on Figure 3: Surrounding Land Use and are summarized in Table 6 in Section 7. (b).

An additional PCA, "Importation of Fill material of Unknown Quality" was identified to south of the Phase One Property (O.Reg. PCA item #30). This fill placement occurred off-Site and interpreted down- or cross-gradient with respect to the Property and is not considered to represent an APEC for the Property.

Based on the identification of a PCA and APEC at the Phase One Property, a Phase Two Environmental Site Assessment was recommended to be completed to assess the soil and/or groundwater quality in the vicinity of the identified APEC #1. Investigation of the aforementioned fill material was also recommended as part of the Phase Two ESA.

2019 Phase Two Environmental Site Assessment by GHD (2019 Phase Two ESA)

The 2019 GHD Phase Two ESA was completed for a larger parcel of land which included the Phase One Property and the adjacent commercial land to the south, including the entire Dumaurier Plaza. Only the findings at the Phase One Property have been included in this report summary.

The 2019 GHD Phase Two Environmental Site Assessment (2019 GHD Phase Two ESA) was completed to assess the APECs identified through a review of the 2018 GHD Phase I ESA, namely, the potential for residual soil and groundwater contamination in the vicinity of the former waste disposal site on the north and east portions of the Phase One Property, as well as fill material on the commercial property adjacent to the south of the Property.

Five boreholes, each instrumented with a groundwater monitoring well, were drilled as part of the 2019 GHD Phase Two ESA, however, only two of these boreholes/monitoring wells were located at the Phase One Property. Soil conditions on the northeast portion of the Property were found to consist of a layer silty sand and gravel fill, underlain by peat, followed by fractured limestone bedrock at approximately 3.7 m below ground surface (m BGS). Black staining was observed in the fill material. Groundwater was encountered at depths ranging from approximately 1.3 to 1.4 m BGS.

Soil and groundwater samples were submitted from each of the borehole/monitoring well locations, which were analyzed for a combination of petroleum hydrocarbons (PHCs), volatile organic compounds (VOCs), polycyclic aromatic hydrocarbons (PAHs), metals and inorganics. The one analyzed soil sample from the Property was in compliance with the site condition

standards (MECP Table 3). One of the three analyzed groundwater samples from the Property had exceedances of the site condition standards, with respect to PHCs. The 2019 GHD Phase Two ESA report concluded that the Property would require remediation or a risk assessment to be in compliance with the site condition standards. It was recommended that a remedial action plan, including a soil and groundwater management program be completed prior to the construction phase of redevelopment.

The pertinent data, findings and interpretations from the 2019 GHD Phase Two ESA have been incorporated to this Phase Two ESA report, as they pertain to the Site specifically. The analytical data from BH1, BH2, BH4 and BH5 (duplicate of BH4), located at the adjacent commercial property to the south of the Phase Two Property, have been redacted from the laboratory certificates of analysis, which have been included in Appendix E.

2019 Geotechnical Investigation by Paterson Group Inc. (2019 Paterson Geotechnical Investigation)

The 2019 Paterson Geotechnical Investigation was completed for the Phase One Property. Three boreholes, each instrumented with a groundwater monitoring well, were drilled as part of the 2019 Paterson Geotechnical Investigation. Soil conditions at the Property were found to consist of a layer silty sand and gravel fill, underlain by glacial till, fine sand and/or silty clay, followed by limestone bedrock at depths ranging from approximately 3.9 to 5.3 m BGS. Each of the boreholes were cored into the bedrock and monitoring wells were installed with their screens set at approximately 15 to 18 m BGS. Groundwater was encountered at depths ranging from approximately 5.8 to 7.1 m BGS.

2020 Methane Gas Detection Monitoring Program by Wood (2020 Wood Methane Monitoring)

The 2020 Wood Methane Monitoring report was completed to assess methane presence as a result of a former waste disposal site¹. Monitoring data was collected from three gas probes at the Phase One Property over the period from 2015 to 2019 at approximately quarterly intervals. The results of the methane monitoring indicate that, while a decreasing trend in methane concentrations does appear evident from 2015 to 2019, several regulation criteria including concentration at the site boundary (2.5% volume methane/total volume), concentration of indoor air in an on-site building (1% volume methane/total volume) and concentration of indoor air in an off-site building (0.05% volume methane/total volume) were intermittently exceeded by observed methane concentrations in some of the gas probes.

It is noted that the regulation which applies to landfills is Ontario Regulation (O.Reg.) 232/98 (as amended in 2011); this regulation is not part of O.Reg. 153/04 for which this Phase One ESA has been prepared in accordance with. It should also be noted that the on-Site building and off-Site

¹ For the purposes of this review section only, the word 'site' references a landfill site.

building criteria is based on indoor air monitoring, and as such the gas probes may provide data which is a conservative approximation of what indoor conditions may exist; it is not known if any indoor air monitoring for methane has been completed at the Phase One Property. Based on the current concept for construction for redevelopment of the Property, it is expected that all waste on the Property will be excavated and sent off-Site for disposal. Subgrade design of the proposed building may also include construction features for methane risk mitigation.

There were no discrepancies identified in review of documentation, information or data from previous investigations. As such, previous investigations are considered to be of adequate quality such that they can be relied upon for the purposes of this Phase Two ESA.

4. Scope of Investigation

i. Overview of Site Investigation

This Phase Two ESA was designed to meet the general requirements of O.Reg. 153/04 as amended, with details of scope presented in Lopers' Letter entitled "Proposal for Phase One Environmental Site Assessment and Phase Two Environmental Site Assessment, Proposed Residential Re-development, 2829 Dumaurier Avenue, Ottawa, ON", dated April 8, 2021, reference, No. PRO-004B-20-BRIGIL V2.

In 2018, Brigil was considering purchase of the entire Dumaurier Plaza property, which includes the Phase Two Property, as well as the adjacent land to the south. The scope of work for a Phase Two ESA investigation was discussed with Brigil and sampling and analysis plan (SAP) was prepared to achieve the objectives of the Phase Two ESA; the SAP prepared by GHD in 2018 is provided in Appendix A. Lopers completed an additional surveying, groundwater monitoring/sampling event of the viable shallow overburden monitoring wells and deep bedrock groundwater monitoring wells in 2021. Several aspects of the scope of work for this Phase Two ESA have been completed by others as part of historical investigations, including previous drilling programs; these activities have been referenced throughout this Phase Two ESA report as they comprise a portion of the scope of work for this Phase Two ESA. In the event that an RSC is required for the Phase Two Property, additional effort, including delineation, remediation and reporting would be required in order to demonstrate that the Site meets the Standard for its intended land use at the time of filing the RSC.

Underground utility locates were completed through Ontario 1-Call by GHD in 2018 to identify any active public services on the Phase Two Property. Following the completion of the public locates, USL-1 Underground Service Locators completed scanning of the Phase Two Property proposed drilling locations to locate privately owned underground services prior to initiating the field program. Various underground utility services, including natural gas, electricity, water and sewers were identified at the Phase Two Property. The natural gas, water and sewer services are

present in underground trenches which enter the Property from Dumaurier Avenue to the east and lead to the commercial building. Electricity enters the property through an underground service trench to the west of the commercial building. Copies of the underground locates are provided in Appendix B.

On October 5, 2018, two boreholes/monitoring wells (BH3D and BH3S) were drilled at the Phase Two Property, as supervised by GHD. On November 10 and 11, 2019, three boreholes/monitoring wells (BH1, BH2 and BH3) were drilled at the Phase Two Property, as supervised by Paterson. The boreholes were drilled using a truck mounted CME 55 drill rig operated by George Downing Estate Drilling. Soil samples were collected using stainless steel split spoons. Soil samples recovered during the sampling program were screened in the field for volatile vapour concentrations, as well as visual and olfactory observations.

Two additional boreholes/monitoring wells (MW95-1 and MW95-2) were present at the Property during this Phase Two ESA. References for the monitoring well IDs were obtained from figures in historical reporting, but no reference to the investigation or findings were provided. It is suspected that these monitoring wells were installed as part of an environmental assessment in 1995.

No new groundwater monitoring wells were installed at the time of this investigation. Based on the aforementioned investigations, a total of seven groundwater monitoring wells (MW95-1, MW95-2, BH1, BH2, BH3, BH3D and BH3S) were installed on the Phase Two Property. Four of these historical monitoring wells (MW95-1, MW95-2, BH1 and BH3) were monitored and/or sampled at the time of this Phase Two ESA; the remaining three monitoring wells (BH2, BH3D and BH3S) could not be located and are presumed to be buried. Based on the provided borehole logs and the interpretation of field observations, the groundwater monitoring wells were drilled to the localized depths ranging from 2.9 to 18.2 m below ground surface (m BGS). The shallow monitoring wells (MW95-1, MW95-2 and BH3S) appear to have been screened to straddle the shallow groundwater table; BH4 is an additional shallow monitoring well, which straddles the south Property limit (but may be on the adjacent property to the south) and was monitored for hydrogeological assessment purposes. The deeper monitoring wells were screened to provide vertical delineation (BH3D) or to provide an assessment of hydrogeological groundwater conditions for the proposed redevelopment. When possible, these groundwater monitoring wells were developed on day of drilling by removing at least three well volumes or by purging the wells dry three times.

The locations of the previously existing boreholes/monitoring at the Phase Two Property are presented on Figure 2: Site Plan. The placement of the boreholes was to assess the quality of fill material and extent of the historical waste disposal site; several boreholes (BH1, BH2 and BH3) were placed for geotechnical Site coverage. Groundwater monitoring wells were installed in all of the aforementioned boreholes.

Soil samples were selected for laboratory analysis of select contaminants of potential concern (CPCs) based on APECs and CPCs identified in the Phase One ESA, as described in Section 3.ii. above as well as field screening observations.

Groundwater monitoring and sampling of the monitoring wells during this Phase Two ESA included the existing groundwater monitoring wells (MW95-1, MW95-2 and BH4, which were interpreted as being screened in overburden and BH1 and BH3, screened in the bedrock) was completed on May 17, 2021. Static groundwater levels were measured prior to disturbance of the water column. During purging, water quality parameters were measured at regular intervals to monitor groundwater quality stabilization; once groundwater quality parameters stabilized (were within approximately 10% on successive readings), groundwater samples were collected. Groundwater samples were selected for laboratory analysis of select CPCs based on APECs and CPCs identified in the Phase One ESA.

An elevation survey was completed of the existing boreholes/monitoring wells which could be located at the Phase Two Property as part of the Phase Two ESA. The boreholes/monitoring wells were surveyed relative to a temporary benchmark of the top of spindle of the City of Ottawa fire hydrant located to the northeast of the Property on the west side of Dumaurier Avenue; this benchmark was assigned a reference elevation of 100.000 m ("Site Datum") for the purposes of this Phase Two ESA.

ii. Media Investigation

Based on the findings of historical investigations, which were consistent with the findings in the Phase One ESA, the following APECs and CPCs were identified for the following media:

The presence of a former waste disposal site on the north portion of the Phase One Property (PCA #1) is a significant PCA which represents APEC #1 for the Property. The contaminants of potential concern (CPCs) associated with the former waste disposal site are VOCs (for groundwater only), metals, PAHs and PHCs/BTEXs. An investigation of the soil and groundwater quality with respect to these CPCs at the Property was completed at BH3S and BH3D by others in 2019. Lopers completed additional assessment of the groundwater quality at MW95-1, MW95-2 and BH1 with respect to the aforementioned CPCs as part of this Phase Two ESA.

Soil quality at the Phase Two Property was investigated by GHD in 2018 through the collection of soil samples at varying depths facilitated by drilling using a truck mounted CME drill rig with stainless steel split spoon sampling.

Groundwater quality at the Phase Two Property was investigated through the installation and sampling of groundwater monitoring wells. The monitoring wells installed at the Phase Two Property were drilled to the localized depths ranging from 2.9 to 18.2 m BGS. The shallow monitoring wells (MW95-1, MW95-2 and BH3S) appear to have been screened to straddle the shallow groundwater table; BH4 is an additional shallow monitoring well, which straddles the south Property limit (but may be on the adjacent property to the south) and was monitored for

hydrogeological assessment purposes. The deeper monitoring wells were screened to provide vertical delineation (BH3D) or to provide an assessment of hydrogeological groundwater conditions for the proposed redevelopment. A bentonite seal was installed above the monitoring well screen's sand pack in each of the monitoring wells to prevent surface and precipitation water influence. When possible, these groundwater monitoring wells were developed on day of drilling by removing at least three well volumes or by purging the wells dry three times. Groundwater monitoring wells were sampled using a peristaltic pump.

There were no natural surface water bodies at the Phase Two Property, and as such no sediment sampling was completed as part of the Phase Two ESA.

iii. Phase One Conceptual Site Model

The Phase One Property, which has the same location orientation and property boundaries as the Phase Two Property, is located at Civic No. 2829 Dumaurier Avenue, Ottawa, Ontario and has an approximate area of 0.42 Hectares.

The Phase One Property was unoccupied prior to the mid 1950's when it is reported that the City of Ottawa operated a waste disposal site on the north portion of the Phase One Property and adjacent lands to the north and east from approximately 1953 to 1957. The south portion of the Property was developed circa 1980, in conjunction with adjacent land to the south, with the present day commercial Dumaurier Plaza. The north portion of the Property, which is elevated approximately 1 to 2 meters above the south portion of the Property, is landscaped. The remaining undeveloped areas of the Phase One Property are paved with asphalt and used for access or parking.

The Property is currently used for commercial purposes and is zoned for mixed use. 1248816 Ontario Inc. is the current registered owner of the Property, with a vendor take back agreement signed in 2018 for ownership to transfer to 3223701 Canada Inc. (Brigil) by July 2023 and it is understood that the intended future use is for residential purposes, with possible commercial use on the ground floor. The Phase One Property is immediately surrounded by the adjoining south portion of Dumaurier Plaza to the south, a municipal Right-of-Way followed by Dumaurier Park to the east, by institutional properties to the north, and by residential properties to the west.

The Phase One Study Area includes the Phase One Property and properties with their boundaries within 250 m of the Phase One Property limits. Based on a review of the Phase One Property and properties in the Phase One Study Area, their associated historical and/or current uses and operations and physical characteristics of the Phase One Study Area, it was determined that an assessment of properties within 250 m of the Phase One property was sufficient to meet the objectives of the scope of this investigation for a Phase One ESA.

No water bodies or areas of natural significance are located at the Phase One Property or in the Phase One Study Area. No drinking water wells are located at the Phase One Property and the

Phase One Study Area is serviced by municipally treated non-potable water. Seven existing groundwater monitoring wells were reportedly drilled at the Phase One Property by others as part of historical investigations; the locations of these wells are presented on Figure 2.

The local regional topography in the Phase One Study Area is undulating but generally slopes downward to the south. Regionally, the topography slopes downward to the northwest, toward the Ottawa River. The north portion of the Phase One Property is elevated approximately 2 m with respect to the south portion of the Property. The Ottawa River is located approximately 1.3 km northwest of the Phase One Property.

Based on the historical research, the general stratigraphy of the Phase One Property and Phase One Study Area consists of sand and gravel fill, underlain by silty clay, followed by silty sand. The overburden soil is underlain by interbedded shale and dolostone bedrock. Groundwater is expected at a depth of approximately 2 to 6 m BGS and to flow in a predominantly south direction.

The presence of a former waste disposal site (PCA#1) on the north portion of the Phase One Property is a significant PCA which represents APEC #1 for the Property. Given that reports were provided which document PHC groundwater contamination and that waste fill material has reportedly been been observed in boreholes on the north portion of the Property, the Property is not in compliance with the Soil, Groundwater and Sediment Standards for use under Part XV.1 of the Environmental Protection Act, which are also for consideration of O.Reg. 153/04.

The contaminants of potential concern (CPCs) associated with the former waste disposal site are VOCs (for groundwater only), metals, PAHs and PHCs/BTEXs. An investigation of the soil and groundwater quality with respect to these CPCs at the Property was completed by others in 2019.

One active automotive service garage and a historical retail fuel outlet are located at neighbouring properties in the Phase One Study Area and constitute PCA#2 and PCA#3, respectively. The PCAs at neighbouring properties in the Phase One Study Area are located significant distances and/or at cross-gradient orientations with respect to the Phase One Property and are not considered to represent APECs for the Phase One Property.

Underground utility service trenches are present at the Phase One Property. The underground utility corridors have the potential to affect contaminant distribution and transport, as they would create preferential pathways for lateral migration. It should be noted that the groundwater table is expected to be present at greater depths than underground utility service trenches at the Property, therefore it is not suspected that significant migration of contaminants has occurred through underground utility corridors.

iv. Deviations from Sampling and Analysis Plan

The Sampling and Analysis Plan (SAP) was designed with the intent of collection groundwater elevation data and/or samples for laboratory analysis from all seven of the reported existing

groundwater monitoring wells at the Property. Since only four groundwater monitoring wells could be located at the property, BH4, an additional shallow monitoring well, which straddles the south Property limit (but may be on the adjacent property to the south) and was monitored for hydrogeological assessment purposes.

v. Impediments

Three of the known historical monitoring wells (BH3S, BH3D and BH2) could not be located and were not monitored or sampled as part of the 2021 field program for this Phase Two ESA.

5. Investigation Method

i. General

The investigation method for this Phase Two ESA involved an assessment and review of findings of historical investigations, which were consistent with the findings in the Phase One ESA for assessment of the soil and/or groundwater quality for the associated CPCs in the vicinity of the APECs identified during the Phase One ESA.

Investigation of soil was completed using a truck mounted CME drill rig, with stainless steel split spoons used to recover soil samples. Soil samples were screened in the field for volatile vapour concentrations, as well as visual and olfactory observations. Select soil samples were submitted based on all the indications mentioned above, as well as to capture representative soil and fill layers, for laboratory analysis for the CPCs.

Groundwater was assessed using groundwater monitoring wells which were installed at the Phase Two Property as part of historical previous investigations. The wells selected for monitoring/sampling were purged during the initial Site visit completed 3 days prior to sampling. Static groundwater levels were measured in the monitoring wells prior to disturbance of the water column during the initial Site visit and again on the day of sampling. Groundwater samples were collected using a peristaltic pump using low-flow procedures and were submitted for laboratory analysis for the CPCs.

An elevation survey was completed of the existing boreholes/monitoring wells which could be located at the Phase Two Property as part of the Phase Two ESA. The boreholes/monitoring wells were surveyed relative to a temporary benchmark of the top of spindle of the City of Ottawa fire hydrant located to the northeast of the Property on the west side of Dumaurier Avenue.

The following sections provide further detailed information regarding the investigation methodology completed to produce this Phase Two ESA.

ii. Drilling

The Phase Two ESA drilling field program was completed on October 5, 2018 under full time supervision of GHD personnel; it should be noted that Mr. Luke Lopers, P. Eng. acted as project manager for the 2019 GHD Phase Two ESA. The geotechnical drilling field program was completed on November 10 and 11, 2019 under full time supervision of Paterson personnel. Seven boreholes were drilled for the Phase Two ESA by the drilling subcontractor George Downing Estate Drilling, located at 410 Principale Rue, Grenville-Sur-la-Rouge, Quebec, J0V 1B0. The drill rig used for the Phase Two ESA was a truck mounted CME drill, equipped with hollow stem augers and stainless-steel split spoons. At least four of the seven boreholes were advanced to auger refusal on suspected bedrock and/or were cored into the dolostone bedrock.

Two additional boreholes/monitoring wells (MW95-1 and MW95-2) were present at the Property during this Phase Two ESA. References for the monitoring well IDs were obtained from figures in historical reporting, but no reference to the investigation or findings were provided. It is suspected that these monitoring wells were installed as part of an environmental assessment in 1995.

Samples were collected using stainless steel split spoons from the near surface to the full depth of drilling. Split spoon samples, collected in 0.6 m segments, were recovered at continuous 0.76 m intervals; the additional 0.16 m between split spoon samples was over-drilled to provide undisturbed field measurement of geotechnical parameters (blow counts) and to prevent cave in materials from stratigraphic units above the intended sampling intervals from being collected at unrepresentative depths during sampling.

The split spoons, which were the only media to come into contact with the soil samples, were washed using soap and water and a scrub brush between samples to minimize the potential for cross-contamination among samples. The field technician used sterile nitrile gloves, which were changed prior to the handling of each soil sample to further reduce the potential of cross-contamination. The flights of the hollow stem augers were cleaned manually following each borehole.

Bedrock core samples were recovered directly from the HQ core barrels, and were placed into wax coated rock core boxes for review. The recovery lengths, rock quality designation and other observations were recorded for each core length recovered.

iii. Soil Sampling

As described above, soil samples were recovered using stainless steel split spoons.

Soil samples were initially collected in Ziploc bags for initial screening as part of sample selection. Soil samples selected for laboratory analysis were collected in dedicated clear glass jars prepared and provided by the analytical laboratory. Soil samples collected for BTEXs/VOCs and the F1 range of PHCs analysis were collected using a dedicated graduated syringe provided by the laboratory and placed directly into a glass vial with a known quantity of methanol

preservative. Analytes and associated preservatives were specified on each jar/vial by the laboratory. Each jar/vial sample set was provided with a unique sample identifier, project number and date of sampling in the field.

Detailed soil descriptions of the stratigraphy for each borehole/monitoring completed as part of the 2019 GHD Phase Two ESA and 2019 Paterson Geotechnical Investigation are included on the borehole logs from those respective reports provided in Appendix C. No historical borehole logs were available for MW95-1 or MW95-2.

Based on the observations of soil samples collected during the 2019 GHD Phase Two ESA and 2019 Paterson Geotechnical Investigation, there were eight stratigraphic units identified at the Phase Two Property, which include: Asphalt, Topsoil, Silty Sand and Gravel (Fill), Sand, Silty Clay, Peat, Silty Sand and Gravel (Till) and Bedrock. Further details and observations of the stratigraphic units identified at the Phase Two Property is presented in Section 6.i.

Field Screening Measurements

Initial field screening of the soil samples consisted of visual and olfactory observations made at the time of sample collection during the drilling program.

Additional field screening of the soil samples was completed using Photo Ionization Detector (PID). The RKI Eagle is capable of measuring volatile vapours at concentrations ranging from 0 parts per million (PPM) to 50% of the lower explosive limit (LEL). The RKI Eagle is also capable of measuring VOC vapours at concentrations ranging from 0.1 ppm to 1000 ppm.

Where soil samples were selected in a borehole within an APEC and the SAP identified proposed soil analysis in that borehole, the field screening was used as follows to select the appropriate sample for laboratory analysis.

- 1. Select sample with evidence of visual and/or olfactory indications of suspected contamination, such as staining, PHC odours or deleterious fill material.
- 2. Select sample with most significant elevated soil vapour concentration.
- 3. Select sample based on stratigraphy and/or moisture content, as certain CPCs are generally expected to be found in these defined conditions (i.e. fill material at shallow depths or PHC impacts near the groundwater table interface).
- iv. Groundwater: Monitoring Well Installation

Installation of monitoring wells in BH1, BH2, BH3, BH3S and BH3D were completed by George Downing Estate Drilling. The wells were installed using slotted PVC No. 10 monitoring well screens, which were 51 mm in diameter. Based on the provided borehole logs and the interpretation of field observations, the groundwater monitoring wells were drilled to the localized depths ranging from 2.9 to 18.2 m below ground surface (m BGS). The shallow monitoring wells (MW95-1, MW95-2 and BH3S) appear to have been screened to straddle the shallow groundwater table; BH4 is an additional shallow monitoring well, which straddles the

south Property limit (but may be on the adjacent property to the south) and was monitored for hydrogeological assessment purposes. The deeper monitoring wells were screened to provide vertical delineation (BH3D) or to provide an assessment of hydrogeological groundwater conditions for the proposed redevelopment. Well screens were 1.5 m in length in the shallow overburden monitoring wells (MW95-1, MW95-2 and BH3S), 1.2 m in length in the shallow bedrock monitoring well (BH3D) or 3.1 m in length in all three of the deep monitoring wells (BH1, BH2 and BH3) installed at the Phase Two Property. The monitoring wells were extended to approximately 0.1 m below the surface grade with PVC riser, also 51 mm in diameter. A threaded PVC end cap was installed at the base of the screen to prevent sediment infiltration, while a J-Plug was installed at the top of the riser to present surface influence.

The annular space in each monitoring well was backfilled with clean silica sand to approximately 0.3 m above the monitoring well screens. A layer of bentonite chips was then used to make a hydraulic seal above the sand pack to near the ground surface. The monitoring wells were completed with aluminum flushmount protective casings, which were backfilled with sand to allow drainage of any surface water which may infiltrate into the casings. A steel stick-up casing was installed at BH1, and the PVC riser was extended to approximately 1.2 m above ground surface, while the steel casing was backfilled with sand.

Development of each of the monitoring wells to be monitored and/or sampled as part of this Phase Two ESA was completed using dedicated Waterra low density polyethylene (LDPE) tubing and a Waterra footvalve. The monitoring wells were developed on May 14, 2021 by purging the wells dry at least three times or removing up to 10 well volumes. The wells were left to stabilize for a period of three days prior to groundwater sampling.

v. Groundwater: Field Measurement of Water Quality Parameters

Measurements of the groundwater quality field parameters were completed to determine stabilization of these parameters prior to sampling. These measurements were completed using Horiba U-52 groundwater quality measurement device ("Horiba"). The Horiba used for groundwater quality parameter stabilization measurements as part of this Phase Two ESA was obtained from Maxim Environmental and Safety Inc. and was calibrated on May 14, 2021. The Horiba is capable of measuring temperature, pH, conductivity, turbidity, dissolved oxygen and oxidation reduction potential. Additional equipment and calibration information for the Horiba is provided on the certificate of calibration included in Appendix D.

Field measurement of water quality parameters were collected at regular intervals (0 L, 0.5 well volumes, 1 well volume, 2 well volumes, etc.) during purging of the monitoring wells prior to sampling. The Horiba was placed in a flow-through cell and water quality parameters were measured until they were found to stabilize to within approximately 10% of the previous measurements prior to sample collection.

vi. Groundwater: Sampling

Groundwater monitoring and sampling of the monitoring wells during this Phase Two ESA included the existing groundwater monitoring wells (MW95-1, MW95-2 and BH4, which were interpreted as being screened in overburden and BH1 and BH3, screened in the bedrock) was completed on May 17, 2021. Groundwater samples were selected for laboratory analysis of select CPCs based on APECs and CPCs identified in the Phase One ESA.

Stabilized groundwater levels were measured in each of the groundwater monitoring wells prior to disturbance of the water column prior to sampling. The dedicated Waterra LDPE tubing and footvalve was removed from each of the monitoring wells and 6 m Waterra LDPE tubing was placed in each of the monitoring wells. The LDPE tubing was connected to a dedicated length of silicon tubing, run through a peristaltic pump set to low flow (approximately 0.2-0.5 L/minute) during purging and sampling while monitoring groundwater level to minimize the drop in head. The monitoring wells were purged on the day of sampling while water quality parameters were measured as noted above.

Groundwater samples were collected in dedicated amber glass bottles and vials or plastic bottles prepared and provided by the analytical laboratory. Analytes and associated preservatives were specified on each bottle by the laboratory. Each bottle sample set was provided with a unique sample identifier, project number and date of sampling in the field. Samples for PHCs, BTEXs, VOCs, PAHs and general chemistry were unfiltered, while metals samples were field filtered using a dedicated 0.45 µm Waterra filter for each sample.

The field technician changed dedicated sterile nitrile gloves prior to initiating work at each monitoring well and changed gloves prior to sample collection to minimize the potential for cross-contamination.

vii. Sediment: Sampling

There were no natural surface water bodies at the Phase Two Property, and as such no sediment sampling was completed as part of the Phase Two ESA.

viii. Analytical Testing

Soil and groundwater analytical testing was conducted by AGAT Laboratories Ltd. (AGAT). AGAT is accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) and the National Institute of Standards and Technology (NIST), Standard Services Division, National Voluntary Laboratory Accreditation Program (NVLAP) for specific environmental and IAQ tests listed in the Scopes of Accreditation registered with each association. AGAT is accredited for all of the analysis performed as part of this Phase Two ESA.

ix. Residue Management Procedures

Excess soil cuttings from drilling and monitoring well installations were containerized in steel 205 L drums, which were stored in the in the southeast portion of the Property. These drums

were marked with a wax crayon indicating the origin location(s) of the cuttings containerized within each.

Groundwater from well development and purging was initially placed in a graduated plastic bucket for volume measurements and then was transferred to a dedicated plastic 205 L drum, which was stored in the northwest portion of the Property. This drum was marked with a wax crayon indicating the origin location(s) of the water containerized within.

Fluids from equipment cleaning and decontamination were containerized within the purge water drum.

x. Elevation Surveying

An elevation survey was completed of the existing boreholes/monitoring wells which could be located at the Phase Two Property as part of the Phase Two ESA. The boreholes/monitoring wells were surveyed relative to a temporary benchmark of the top of spindle of the City of Ottawa fire hydrant located to the northeast of the Property on the west side of Dumaurier Avenue; this benchmark was assigned a reference elevation of 100.000 m ("Site Datum") for the purposes of this Phase Two ESA. The reference elevations of each borehole/monitoring well, which could be located at the time of the fieldwork for this Phase Two ESA, are provided in Tables 1 and 2 in Section 6.ii.

xi. Quality Assurance and Quality Control Measures

Soil samples, recovered at the time of the 2019 GHD Phase Two ESA, were collected in dedicated clear glass jars prepared and provided by the analytical laboratory. Soil samples collected for BTEXs/VOCs and the F1 range of PHCs analysis were collected using dedicated graduated syringes provided by the laboratory and placed directly into a glass vial with methanol preservative. Analytes and associated preservatives were specified on each jar/vial by the laboratory. Each jar/vial sample set was provided with a unique sample identifier, project number and date of sampling in the field.

Groundwater samples were collected in dedicated amber glass bottles and vials or plastic bottles prepared and provided by the analytical laboratory. Analytes and associated preservatives were specified on each bottle by the laboratory. Each bottle sample set was provided with a unique sample identifier, project number and date of sampling in the field.

Following sample collection, the soil and groundwater samples were stored in an ice pack chilled cooler to minimize volatilization and begin the cooling process on the day of sampling. On each day of sample collection, following completion of the fieldwork, samples were delivered directly to the analytical laboratory. Standard chain of custody procedures were used to maintain a custody record of soil and groundwater samples between the field technician and the analytical laboratory.

During the 2019 GHD Phase Two ESA, the split spoons, which were the only media to come into contact with the soil samples, were washed using soap and water and a scrub brush between samples to minimize the potential for cross contamination among samples. The field technician used sterile nitrile gloves, which were changed prior to the handling of each soil sample to prevent cross-contamination. The field technician changed dedicated sterile nitrile gloves prior to initiating work at each monitoring well and changed gloves prior to groundwater sample collection to minimize the potential for cross-contamination.

Trip blank water samples for VOCs were submitted for laboratory analysis from the groundwater sampling event completed on October 19, 2018 by GHD and on May 17, 2021 by Lopers. No detectable VOC concentrations were reported in the trip blank water samples.

One soil sample was submitted to the laboratory as a blind field duplicate sample at the time of the 2019 GHD Phase Two ESA. The 2019 GHD Phase Two ESA was completed for the entire commercial property for Dumaurier Plaza, and the duplicate sample analyzed at the time was from BH4, interpreted to be immediately south of the Phase Two Property. The duplicate sample was noted to have relative percent differences (RPDs) which were generally less than 40%. It was also noted that the parameters which were detected above the laboratory method detection limits in the duplicate samples, were generally detected at low concentrations, which could be an explanation for the variability in results. Additionally, the high degree of heterogeneity in soil samples can attribute to higher levels of variability in analytical ratios.

The groundwater sample (Dup-1) was submitted to the laboratory as a blind field duplicate sample of MW95-1, which was collected during this Phase Two ESA. The ratio of groundwater duplicate results to original sample results was generally less than 1% to 15 or 26% which meets the required ratio.

One blind field duplicate groundwater sample (MW6) was submitted for laboratory analysis of VOCs, PHCs, metals and inorganics for the groundwater samples collected from BH3S at the time of the 2019 GHD Phase Two ESA. These duplicate results were observed to be generally consistent for the VOCs and metals and inorganics parameter sets, but had some observed variability with respect to the PHC analytical results, which reported exceedances of the Site Condition Standards in the original sample but concentrations less than the laboratory method detection limits in the duplicate sample. The variability in the PHC results from this groundwater duplicate sample is suspected to be associated with sampling procedures and/or the presence of sediment in the original sample; sediment in PHC samples has been shown in previous groundwater quality assessments at other properties to result in false positive analytical results for the heavier fractions of PHCs.

The level of variability generally observed in the laboratory analytical results is considered to meet the objectives of confirmation of consistency in the laboratory data.

No equipment blank of groundwater was required since the groundwater samples were collected using dedicated tubing.

6. Review and Evaluation

i. Geology

Based on the observations of soil samples collected during the 2019 GHD Phase Two ESA and 2019 Paterson Geotechnical Investigation, there were eight stratigraphic units identified at the Phase Two Property, which include:

Asphalt

A layer of asphalt, approximately 0.08 m in thickness, was encountered at the ground surface in BH1 and BH3.

Topsoil

A surface layer of topsoil and grass, approximately 0.08 m in thickness, was encountered at the ground surface in BH3D/3S. This material was described as silty sand with organics, loose, dark brown, and damp.

Silty Sand and Gravel (Fill)

A layer of silty sand and gravel fill material, ranging from approximately 0.9 to 2.7 m in thickness, was encountered immediately below the topsoil or the asphalt in all of the boreholes. This material was identified to consist of silty sand and gravel and generally grey. This layer was encountered at varying moisture conditions, and moisture conditions were not documented on the Paterson borehole logs, however, it was noted that the fill layer was generally present above the static water table at the Property.

Black staining, suspected to be associated with poor quality fill placement were observed in BH3S/BH3D in this unit from an approximate depth of 1.2 to 2.4 m BGS. No petroleum hydrocarbon odours were noted in the stained soil from BH3S/BH3D.

Sand

A layer of fine sand, ranging from approximately 0.9 to 1.0 m in thickness, was encountered at depths ranging from approximately 2.0 to 2.9 m BGS, immediately below a peat layer in borehole BH2 and below the fill layer in BH1. This material was identified to consist of fine sand with silt and clay, was loose and grey. Moisture conditions were not documented on the Paterson borehole logs, however, it was noted that the sand layer was present above the static water table in BH2.

Silty Clay

A layer of silty clay, approximately 1.3 m in thickness, was encountered below the sand layer in borehole BH2. This material was identified to consist of silty clay with trace sand, and grey.

Moisture conditions were not documented on the Paterson borehole logs, however, it was noted that the silty clay layer was present above the static water table in BH2.

Peat

A layer of peat, ranging from approximately 0.4 to 1.2 m in thickness, was encountered immediately below the fill layer in BH2 and BH3S/BH3D. This material was described as black, organics with an organic odour (not suspected to be associated with environmental contamination). This layer was encountered at wet moisture conditions.

Silty Sand and Gravel (Till)

A layer of silty sand and gravel, ranging from approximately 0.8 to 1.5 m in thickness, was encountered at depths ranging from approximately 3.1 to 3.8 m BGS, immediately below a sand layer in borehole BH1 and below the fill layer in BH3. This material was identified to consist of sandy silt with some clay and gravel and was grey. Moisture conditions were not documented on the Paterson borehole logs, however, it was noted that the till layer was present near the static water at the Property.

Interbedded Limestone, Shale, Dolomite and Dolostone Bedrock

Bedrock was observed at depths ranging from approximately 3.7 to 5.3 m BGS in borehole BH1, BH2, BH3 and BH3S/BH3D. The bedrock was cored using HQ diamond coring equipment and observations of the bedrock were recorded following recovery. The bedrock was observed to be grey limestone, or green shale interbedded with dolomite and dolostone at intermittent depths. Bedrock quality was observed to be poor to excellent in quality with some to moderate fracturing near the bedrock surface and was generally increasing in Rock Quality Designation (RQD) with depth.

Aquifer

The shallow overburden (unconfined) aquifer is the aquifer of interest based on the PCAs, APECs and CPCs identified for the Phase Two Property. The shallow overburden aquifer is present in the native silty sand and gravel (till) layer, as well as in the sand and/or silty sand and gravel fill layers (where present in the former areas of backfilling).

The shallow aquifer is expected to have moderate relative permeability in more porous stratigraphic units such as the silty sand and gravel, sand and/or potential refuse/waste fill, while the shallow aquifer in the silty sand or more clayey till layers are expected to have low permeability and restrict the movement of groundwater and associated contaminants.

Some investigation into the localized groundwater quality of the deep bedrock aquifer was also completed for vertical delineation purposes.

Based on moisture contents observed in the soil samples collected as part of this Phase Two ESA it is expected that seasonal and annual variability affect the groundwater table elevation in the shallow aquifer.

ii. Groundwater and Elevations and Flow Direction

Based on the nature of the primary CPCs identified for groundwater at the Phase Two Property (including light non-aqueous phase liquids (LNAPLs)), the screened intervals of the existing groundwater monitoring wells selected for monitoring and sampling as part of this Phase Two ESA were interpreted to straddle the shallow groundwater table within the overburden.

The boreholes/monitoring wells were surveyed relative to a temporary benchmark of the top of spindle of the City of Ottawa fire hydrant located to the northeast of the Property on the west side of Dumaurier Avenue; this benchmark was assigned a reference elevation of 100.000 m ("Site Datum") for the purposes of this Phase Two ESA.

The shallow groundwater aquifer was present within the overburden on central, east and north portions of the Phase Two Property. Although these monitoring wells were installed as part of separate historical investigations, it has been interpreted that the same shallow aquifer exists across these units and can be used for a determination of groundwater flow direction and hydraulic gradient. Monitoring well construction details, where they are known, are presented in Table 1 below.

Table 1: Monitoring Well Construction Details

Monitoring Well	Ground Surface Elevation	Top of Piezometer Elevation	Screen Elevation (m RSD)	Sand Pack Elevation (m RSD)	Bentonite Seal (m RSD)	
	(m RSD)	(m RSD)				
Shallow Overb	Shallow Overburden monitoring wells					
* MW95-1	98.51	98.43	95.51 – 97.03	Unknown	Unknown	
* MW95-2	98.28	98.31	95.04 – 96.56	Unknown	Unknown	
*** BH4	98.33	98.22	92.89 – 93.99	92.89 – 94.09	94.09 – 97.89	
** BH3S	99.33	99.23	95.60 – 97.10	95.60 – 97.50	97.50 – 98.80	
Deep Bedrock monitoring wells						
* BH1	99.95	100.83	81.66 – 84.71	81.66 – 85.02	85.02 – 94.85	
* BH3	98.64	98.52	80.53 - 83.88	80.53 – 84.28	84.28 – 94.84	
** BH3D	99.25	99.15	93.90 – 95.20	93.90 – 95.30	95.30 – 98.80	

m RSD - metres Referenced to Site Datum

^{*} Interpreted based on historical reports and/or field observations

^{**} Based on data provided in the 2019 GHD Phase Two ESA

*** Interpreted to be present on the neighbouring property to the south

On May 17, 2021, following a period of three days for stabilization after re-developing the monitoring wells, the groundwater levels were measured and are presented in Table 2 below. The groundwater table in the shallow overburden aquifer was measured at depths ranging between 0.70 and 1.19 m BGS on May 17, 2021. The groundwater elevations of two deep bedrock monitoring wells (BH1 and BH3) were also measured as part of this Phase Two ESA, however, these elevations were not used for an interpretation of groundwater flow.

Table 2: Groundwater Table Elevations Measured on May 17, 2021

Monitoring Well	Ground Surface Elevation (m RSD)	Top of Piezometer Elevation (m RSD)	Depth to Groundwater (m below TOP)	Groundwater Table Elevation (m RSD)	Depth to Groundwater (m BGS)	
Shallow Overb	Shallow Overburden monitoring wells					
* MW95-1	98.51	98.43	0.90	97.53	0.98	
* MW95-2	98.28	98.31	0.73	97.58	0.70	
*** BH4	98.33	98.22	1.08	97.14	1.19	
Deep Bedrock monitoring wells						
* BH1	99.85	100.83	8.33	92.50	7.35	
* BH3	98.64	98.52	6.05	92.47	6.17	

m RSD - meters Referenced to Site Datum

Three groundwater monitoring well water table elevations are required to triangulate groundwater elevations and determine an approximate groundwater flow direction. The groundwater table elevations in MW95-1, MW95-2 and BH4 were used for a determination of groundwater flow direction. Based on the measured groundwater table elevations in these monitoring wells, the local groundwater flow direction at the Phase Two Property is towards the west-southwest. This interpreted local groundwater flow direction is reasonable based on the local topography and groundwater recharge expected in the large field/park (former waste disposal site) to the east; however, it is expected that regional groundwater flow is toward the northwest in the direction of the nearest significant surface water body, the Ottawa River, which is 1.3 km to the northwest of the Phase Two Property.

No observations or indications of free product were observed in any of the monitoring wells accessed as part of this Phase Two ESA, as measured with an interface probe during water level measurements, and through observations of the purge water during development and sampling

m BGS - metres Below Ground Surface

^{*} Interpreted based on historical reports and/or field observations

^{***} Interpreted to be present on the neighbouring property to the south

of the monitoring wells. Slight to moderate petroleum hydrocarbon odours were observed in the purge water recovered from MW95-1 and MW95-2.

Given the shallow depth to groundwater and the interpreted flow direction, the underground utility corridors at the Phase Two Property do have the potential to affect contaminant distribution and transport, as they would create preferential pathways for lateral migration from the identified APEC (former waste disposal site to the north and east) towards the Property. Based on the depth to groundwater observed in the monitoring wells as part of this investigation, observed between 0.70 and 1.19 m BGS, the potential exists for migration of contaminants through underground utility service trenches (generally approximately 2 to 3 m BGS).

iii. Groundwater: Hydraulic Gradients

The horizontal hydraulic gradient was determined by plotting groundwater contours interpreted from groundwater elevations presented in Table 2 and then by dividing the difference in hydraulic head by the lateral separation distance in the groundwater contours. Based on the measured groundwater elevations in MW95-1, MW95-2 and BH4 the horizontal hydraulic gradient at the Phase Two Property is approximately 0.036 m/m.

iv. Course Grained Soil Texture

A substantial layer of fill, consisting of silty sand and gravel, which would be classified as coarse grained soil, is present to near full depth to bedrock on the Phase Two Property. It is interpreted that greater than 1/3 of the Phase Two Property has coarse grained soil. For the purposes of this Phase Two ESA, the soil conditions are considered to be coarse grained, which provides a more conservative comparison to the MECP site condition standards than the fine-grained values.

v. Soil Field Screening

Initial field screening of the soil samples consisted of visual and olfactory observations made at the time of sample collection during the drilling program as part of the 2019 GHD Phase Two ESA. Black staining, suspected to be associated with poor quality fill placement were observed in BH3S/BH3D in this unit from an approximate depth of 1.2 to 2.4 m BGS. No petroleum hydrocarbon odours were noted in the stained soil from BH3S/BH3D.

Additional field screening of the soil samples was completed using a PID. Combustible soil vapour screening concentrations in the soil samples recovered during the 2019 GHD Phase Tow ESA were found to range from 0 to 3.9 ppm, which is low and generally not considered indicative of significant PHC contamination.

vi. Soil Quality

Location and Depth of Soil Samples

The following soil samples, which were collected from the boreholes drilled as part of this Phase Two ESA, were submitted for laboratory analysis.

Table 3: Soil Samples Selected for Laboratory Analysis

Sample Location	Sample ID	Sample Depth (m BGS)	Analytical Parameters	
BH3D	BH3-SS3	1.2 – 1.8	PAHs, Metals & Inorganics	

Comparison of Soil Analytical Results to Applicable Site Conditions Standards

The analytical soil results were compared to the full depth generic site condition standards, with non-potable groundwater, course textured soil, for residential property use, as specified in Table 3 of the MECP Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act, April 15, 2011.

The aforementioned soil samples selected for laboratory analysis were submitted to AGAT under chain of custody No. T075943 on October 5, 2018. The laboratory certificate of analysis (AGAT Report # 18Z394508) is provided in Appendix E.

All of the analyzed soil samples were in compliance with the site condition standards. A full summary of the soil analytical results and comparison to the applicable site condition standards are presented in Table 5: Soil Analytical Results following the text of this report.

Comparison of TCLP Analytical Results to O.Reg. 558/00

A waste characterization sample was selected for laboratory analysis of toxicity characteristic leaching procedure (TCLP) analysis for flashpoint, leachate metals & inorganics, leachate VOCs and leachate PAHs. This sample was comprised of a composite of worst-case samples, as determined by field screening parameters.

The aforementioned composite soil sample selected for TCLP laboratory analysis was submitted to chain of custody No. T075943 on October 5, 2018. The laboratory certificate of analysis (AGAT Report # 18Z394508) is provided in Appendix E.

This composite sample was compared to the criteria specified in schedule IV of O.Reg. 558/00 and no measured parameter exceeded the toxicity criteria. Based on the analytical results and field screening, if excess soil generated from redevelopment of the Site cannot be reused as clean fill at an appropriate receiving site, it can be treated as solid non-hazardous waste.

Contaminants of Concern

The presence of a former waste disposal site on the north portion of the Phase One Property is a significant PCA which represents APEC #1 for the Property. The contaminants of potential concern (CPCs) in soil associated with the former waste disposal site are metals, PAHs and PHCs/BTEXs.

The contaminants of concern for a particular sample were based on the relative location and depth of the sample, visual and/or olfactory observations and combustible vapour screening concentrations.

Contaminants Related to Chemical and Biological Transformations

Contaminants related to chemical and biological transformations were not suspected to be present at the Phase Two Property and were not identified as part of the Phase Two ESA soil analysis.

Soil Serving as a Source of Contaminant Mass Contributing to Groundwater

Based on the analytical results, there is no soil that serves as a source of contaminant mass contributing to groundwater at the Phase Two Property.

Light or Dense Non-Aqueous Phase Liquids

The analytical results do not indicate the presence of light or dense non-aqueous phase liquids at the Phase Two Property.

vii. Groundwater Quality

Locations and Sample Depth Interval of Groundwater Samples

The groundwater samples were collected using a peristaltic pump with tubing lowered to between the top and approximate (vertical) center of the water column within each monitoring well and withdrawing the water at low flow rates. The groundwater sample locations, screen depths and parameters analyzed are presented in Table 4 below.

Table 4: Groundwater Samples Selected for Laboratory Analysis

Sample Location	Groundwater Level (m RSD)	Screen Depth (m RSD)	Analytical Parameters
BH3D	97.34*	93.90 – 95.20	PHCs, VOCs, Metals & Inorganics
BH3S	96.25*	95.60 – 97.10	PHCs, VOCs, Metals & Inorganics
MW6 (Duplicate of BH3S)	96.25*	95.60 – 97.10	PHCs, VOCs, Metals & Inorganics
MW95-1	97.53	95.51 – 97.03	PHCs, VOCs, PAHs, Metals & Inorganics
DUP-1 (Duplicate of MW95-1)	97.53	95.51 – 97.03	PHCs, VOCs, PAHs, Metals & Inorganics
MW95-2	97.58	95.04 – 96.56	PHCs, VOCs, PAHs, Metals & Inorganics
BH1	92.50	81.66 – 84.71	PHCs, VOCs, PAHs, Metals & Inorganics

m RSD - metres Referenced to Site Datum

Field Filtering

Samples for PHCs, BTEXs, VOCs, PAHs and general chemistry were unfiltered, while metals samples were field filtered using a dedicated 0.45 µm Waterra filter for each sample.

Comparison of Groundwater Analytical Results to Applicable Site Conditions Standards

The analytical groundwater results were compared to the full depth generic site condition standards, with non-potable groundwater, course textured soil, as specified in Table 3 of the MECP Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act, April 15, 2011.

The groundwater samples selected for laboratory analysis were submitted to AGAT under chain of custody Nos. T080076 and T118702 on October 19, 2018 and May 17, 2021, respectively. The laboratory certificates of analysis (AGAT Report #s 18Z399894 and 21Z747835) are provided in Appendix E. The following samples had exceedance concentrations reported compared to ('vs.') their respective site condition standards.

BH3S, collected from a screen depth of approximately 2.2-3.7 m BGS, had reported concentrations of PHC F2 range (170 μg/g vs. 150 μg/g) and PHC F3 range (860 μg/g vs. 500 μg/g).

All of the other groundwater samples collected at the Phase Two Property were in compliance with the site condition standards. It should be noted that the monitoring well BH3D was installed for vertical delineation purposes for BH3S; BH3D had no detectable PHC concentrations in a sample collected the same date as the aforementioned sample from BH3S.

^{*} Measured in 2018 as part of 2019 GHD Phase Two ESA

Monitoring well W95-2 had a reported chloroform concentration of 23.9 ug/L compared to the site condition standard of 2.4 ug/L. The reported chloroform concentration from MW95-2 is in the range of concentrations reported by the City of Ottawa for municipally treated drinking water. It is suspected that the observed chloroform exceedance is a result of a leaking watermain, is not representative of actual Site conditions and is not interpreted as an exceedance for the purposes of this report. Further exploration to the source of the chloroform should be undertaken at the time Site redevelopment.

A full summary of the groundwater analytical results and comparison to the applicable site condition standards are presented in Table 6: Groundwater Analytical Results following the text of this report.

Contaminants of Concern

The presence of a former waste disposal site on the north portion of the Phase One Property is a significant PCA #1 which represents APEC #1 for the Property. The CPCs in groundwater associated with the former waste disposal site are VOCs, metals, PAHs and PHCs/BTEXs.

The contaminants of concern for a particular sample were based on the relative location and depth of the sample, visual and/or olfactory observations of soil samples collected which could have come into contact with the groundwater table.

Contaminants Related to Chemical and Biological Transformations

Contaminants related to chemical and biological transformations were not suspected to be present at the Phase Two Property and were not identified as part of the Phase Two ESA groundwater analysis.

Soil Serving as a Source of Contaminant Mass Contributing to Groundwater

Based on the groundwater analytical results, there is no soil that serves as a source of contaminant mass contributing to groundwater at the Phase Two Property.

Light or Dense Non-Aqueous Phase Liquids

The presence of measurable levels LNAPL and/or DNAPL free product were not observed at the Phase Two Property, as measured with an interface probe and with observations of the purge water recovered from the monitoring wells.

The analytical groundwater results do not indicate the suspected presence of dense non-aqueous phase liquids at the Phase to Property.

viii. Sediment Quality

There were no natural surface water bodies at the Phase Two Property, and as such no sediment sampling was completed as part of the Phase Two ESA.

ix. Quality Assurance and Quality Control Results

One soil sample was submitted to the laboratory as a blind field duplicate sample at the time of the 2019 GHD Phase Two ESA. The 2019 GHD Phase Two ESA was completed for the entire commercial property for Dumaurier Plaza, and the duplicate sample analyzed at the time was from BH4, interpreted to be immediately south of the Phase Two Property. The duplicate sample was noted to have relative percent differences (RPDs) which were generally less than 40%. It was also noted that the parameters which were detected above the laboratory method detection limits in the duplicate samples, were generally detected at low concentrations, which could be an explanation for the variability in results. Additionally, the high degree of heterogeneity in soil samples can attribute to higher levels of variability in analytical ratios.

The groundwater sample (Dup-1) was submitted to the laboratory as a blind field duplicate sample of MW95-1, which was collected during this Phase Two ESA. The ratio of groundwater duplicate results to original sample results was generally less than 1% to 15 or 26% which meets the required ratio.

One blind field duplicate groundwater sample (MW6) was submitted for laboratory analysis of VOCs, PHCs, metals and inorganics for the groundwater samples collected from BH3S at the time of the 2019 GHD Phase Two ESA. These duplicate results were observed to be generally consistent for the VOCs and metals and inorganics parameter sets, but had some observed variability with respect to the PHC analytical results, which reported exceedances of the Site Condition Standards in the original sample but concentrations less than the laboratory method detection limits in the duplicate sample. The variability in the PHC results from this groundwater duplicate sample is suspected to be associated with sampling procedures and/or the presence of sediment in the original sample; sediment in PHC samples has been shown in previous groundwater quality assessments at other properties to result in false positive analytical results for the heavier fractions of PHCs.

The level of variability generally observed in the laboratory analytical results is considered to meet the objectives of confirmation of consistency in the laboratory data. The QA/QC duplicate sample results demonstrate that the data are reliable, appropriate and accurate in the determination of whether the phase two property meets the applicable site condition standards.

The laboratory made no qualifying statements regarding the sample handling or submission as part of this Phase Two ESA. Any laboratory remarks in certificates of analysis are related to internal QA and is not expected to impact the validity of any of the data.

All certificates of analysis were received pursuant to clause 47 (2) (b) of O.Reg. 153/04 and comply with subsection 47 (3) of O.Reg. 153/04.

The overall quality of the field data from the investigation with respect to the data quality objectives, demonstrate that decision-making was not affected, and the overall objectives of the investigation and the assessment were met.

x. Phase Two Conceptual Site Model

The presence of a former waste disposal site on the north portion of the Phase One Property (PCA #1) is a significant PCA which represents APEC #1 for the Property. The contaminants of potential concern (CPCs) associated with the former waste disposal site are VOCs (for groundwater only), metals, PAHs and PHCs/BTEXs.

Various underground utility services, including natural gas, electricity, water and sewers were identified at the Phase Two Property. The natural gas, water and sewer services are present in underground trenches which enter the Property from Dumaurier Avenue to the east and lead to the commercial building. Electricity enters the property through an underground service trench to the west of the commercial building. Given the shallow depth to groundwater and the interpreted flow direction, the underground utility corridors at the Phase Two Property do have the potential to affect contaminant distribution and transport, as they would create preferential pathways for lateral migration from the identified APEC (former waste disposal site to the north and east) towards the Property. Based on the depth to groundwater observed in the monitoring wells as part of this investigation, the potential exists for migration of contaminants through underground utility service trenches (generally approximately 2 to 3 m BGS).

The overburden stratigraphy of the Phase Two Property is present in eight geological units, including an asphalt or topsoil layer at ground surface, silty sand and gravel (fill) layer, sand, a native silty clay layer, a peat layer and a native silty sand and gravel layer. Historical reports referenced the presence of a layer of buried refuse/waste at the Phase Two Property, however, it should be noted that the specific investigations referenced were not available as part of this Phase Two ESA.

The shallow overburden (unconfined) aquifer is the aquifer of interest based on the PCAs, APECs and CPCs identified for the Phase Two Property. The shallow overburden aquifer is present in the native silty sand and gravel (till) layer, as well as in the sand and/or silty sand and gravel fill layers (where present in the former areas of backfilling).

The aquifer is expected to have moderate relative permeability in more porous stratigraphic units such as the silty sand and gravel, sand and/or potential refuse/waste fill, while the shallow aquifer in the silty sand or more clayey till layers are expected to have low permeability and restrict the movement of groundwater and associated contaminants.

The overburden soil is underlain by interbedded limestone, shale, dolomite and dolostone bedrock at depths ranging from approximately 3.7 to 5.3 m BGS.

The shallow overburden groundwater table was measured at depths ranging between 0.70 and 1.19 m BGS. The shallow groundwater aquifer was present within the overburden across the Phase Two Property. Monitoring from wells situated in the shallow aquifer was used for a determination of groundwater flow direction and hydraulic gradient. The horizontal hydraulic

gradient at the Phase Two Property was calculated to be approximately 0.036 m/m with a localized groundwater flow direction towards the west-southwest.

The proposed redevelopment of the Phase Two Property includes construction of one building, approximately 30 storeys in height, with subgrade parking, commercial ground floors and residential units above

The Phase Two Property and all other properties within 250 m of the property boundaries are supplied by Ottawa's municipal potable water supply system. The RSC does not specify agricultural use and there are no wells within 250 m of the property boundaries that are intended for use as a source of water for human consumption or agriculture. As such, the designation of non-potable groundwater setting is determined to be applicable [O.Reg. 153/04, section 35].

The Phase Two Property is not situated within or adjacent to an area of natural significance and does not include any land within 30 m of an area of natural significance. The pH of the soil was analyzed as part of this Phase Two ESA and was reported at 7.44. As such, the Phase Two Property is not considered to be an environmentally sensitive area [O.Reg. 153/04, section 41].

Review of the borehole/monitoring well logs completed as part of previous investigations was completed. It was determined that greater than 2/3 of the Phase Two Property has greater than 2 m of overburden soil. The Phase Two Property is not considered a shallow soil property.

The Phase Two Property does not include and does not have any land located within 30 m of a water body. The MECP site condition standards for use within 30 m of a water body do not apply [O.Reg. 153/04, section 43.1].

The full depth generic site condition standards, with non-potable groundwater, course textured soil, for residential/parkland/institutional property use, as specified in Table 3 of the MECP Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act, April 15, 2011 were determined to be the applicable site condition standards for the Phase Two Property as part of this Phase Two ESA.

All of the analyzed soil samples were in compliance with the site condition standards.

The groundwater sample BH3S, collected from a screen depth of approximately 2.2-3.7 m BGS, had reported concentrations of PHC F2 range (170 μ g/g vs. 150 μ g/g) and PHC F3 range (860 μ g/g vs. 500 μ g/g).

All of the other groundwater samples collected at the Phase Two Property were in compliance with the site condition standards. It should be noted that the monitoring well BH3D was installed for vertical delineation purposes for BH3S; BH3D had no detectable PHC concentrations in a sample collected the same date as the aforementioned sample from BH3S. The Phase Two Property is not in compliance with the site condition standards as of the certification date of May 17, 2021.

7. Conclusions

All of the analyzed soil samples were in compliance with the site condition standards.

The groundwater sample BH3S, collected in October of 2018 from a screen depth of approximately 2.2-3.7 m BGS, had reported concentrations of PHC F2 range (170 μ g/g vs. 150 μ g/g) and PHC F3 range (860 μ g/g vs. 500 μ g/g).

All of the other groundwater samples collected at the Phase Two Property were in compliance with the site condition standards. It should be noted that the monitoring well BH3D was installed for vertical delineation purposes for BH3S; BH3D had no detectable PHC concentrations in a sample collected the same date as the aforementioned sample from BH3S. The Phase Two Property is not in compliance with the site condition standards as of the certification date of May 17, 2021.

Historical environmental reports referenced the presence of a layer of buried refuse/waste at the Phase Two Property, however, the specific investigations (including associated borehole logs and laboratory analytical results) referenced were not available as part of this Phase Two ESA. Although there were no observations of refuse/waste or evidence of deleterious fill material identified in any of the boreholes drilled as part of the 2019 GHD Phase Two ESA or the 2019 Paterson Geotechnical Investigation, it is suspected that waste and/or poor environmental quality fill material may have been placed at the Property in locations not assessed as part of the aforementioned investigations. There is suspected soil and/or groundwater contamination at the Phase Two Property. Additional investigation and confirmation of soil and groundwater quality in this area of the Property is recommended at the time of excavation for site redevelopment. It should be noted that the proposed redevelopment includes excavation for at least two to three levels of underground parking, which is expected to be sufficient for remediation of the aforementioned environmental contamination at the Phase Two Property.

An environmental remediation program, including the bulk removal and off-site disposal of soil and groundwater in excess of the site condition standards is required for the Phase Two Property. Further delineation and confirmation of remediation sampling will be required prior to confirmation of compliance with the site condition standards and prior to the submission of a Record of Site Condition (RSC); however, these tasks can be completed at the time decommissioning and demolition of existing structures at the Phase Two Property in conjunction with the proposed redevelopment. The submission and acknowledgment of an RSC would be required prior to occupancy of the Phase Two Property for residential purposes following redevelopment, however, these tasks can be completed following decommissioning and demolition of existing structure at the Phase Two Property. The Phase Two ESA could be then updated at that time to show compliance with site condition standards.

Preparation of a soil management plan in accordance with O.Reg. 406/19 will be required as part of management of excess soil generated as part of construction activities. It is recommended that a remedial action plan be prepared to develop a strategy for remediation, including soil and groundwater management, during redevelopment.

i. Signatures

The Qualified Person for this study is Mr. Luke Lopers, P. Eng. Mr. Lopers has been a Professional Engineer, registered in Ontario since 2012 and has been working on environmental site assessments since 2006. Mr. Lopers has been an author, project manager and/or peer reviewer for hundreds of Phase One ESAs and Phase Two ESAs as well as previously filed RSCs.

The reviewer for this study is Mr. Don Plenderleith, P.Eng. Mr. Plenderleith is a Professional Engineer registered in Ontario since 1994 and has authored and/or reviewed hundreds of Phase One and Two ESAs in Ontario and the rest of Canada. The qualifications of the assessor/Qualified Person and reviewer are included in Appendix F.

Sincerely,

Luke Lopers, P.Eng., QP_{ESA}

Don Plenderleith, P.Eng., QP_{ESA}

Don Plenderletto



8. Limitations

The findings and conclusions of this Phase Two ESA are based on the information provided and/or reviewed as part of this study.

This Phase Two ESA has been completed with the standard of care generally expected in the industry for a study of this nature.

This Phase Two ESA has been prepared for the sole use of 3223701 Canada Inc. for the purposes of a due diligence assessment of the potential liabilities which may exist at the Phase Two Property. No other party is permitted to rely on the conclusions or findings of this report without the written consent of Lopers & Associates and 3223701 Canada Inc.

Changes to the physical setting of the Phase Two Property, Phase One Study Area and applicable regulations governing Phase One and Two Environmental Site Assessments have the potential to influence the validity of the conclusions and opinions presented in this Phase Two ESA.

9. References

Legal Survey Plan, Annis, O'Sullivan, Vollebekk Ltd., dated November 20, 2000.

City of Ottawa, geoOttawa mapping website, Visited May through June, 2021. http://maps.ottawa.ca/geoottawa/

Google Earth, Visited May through June, 2021.

"Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act", produced by the Ontario Ministry of the Environment, dated April 15, 2011.

Current Site Development Design Concept Plan, RLA Architecture, dated February 20, 2020 and Brigil, dated April 30, 2020.

"Phase I Environmental Site Assessment, 2831, 2833, 2835, 2841 and 2865 Dumaurier Avenue, Ottawa, Ontario", dated August 16, 2018, completed by GHD Limited for 3223701 Canada Inc.

"Phase II Environmental Site Assessment, 2831, 2833, 2835, 2841 and 2865 Dumaurier Avenue, Ottawa, Ontario", dated April 2, 2019, completed by GHD Limited for 3223701 Canada Inc.

"Geotechnical Investigation, Proposed Hi-Rise Building, 2829 Dumaurier Avenue, Ottawa, Ontario", dated December 18, 2019, completed by Paterson Group Inc. for 3223701 Canada Inc.

"Methane Gas Detection Monitoring Program (2015-2019), Dumaurier Plaza - 2829 Dumaurier Avenue, Closed Pinecrest Landfill Site, Ottawa, Ontario", dated August 26, 2020, completed by Wood Canada Limited for 1248816 Ontario Inc.

"Phase One Environmental Site Assessment, 2829 Dumaurier Avenue, Ottawa, Ontario" dated January 8, 2021 prepared for 3223701 Canada Inc. by Lopers & Associates.

AGAT Certificate of Analysis – Report # 18Z399894 - Soil Sample Submission October 5, 2018

AGAT Certificate of Analysis – Report # 18Z394508 - Groundwater Sample Submission October 19, 2018

AGAT Certificate of Analysis – Report # 21Z747835 - Groundwater Sample Submission May 17, 2021

10. Appendices

Appendix A – Sampling and Analysis Plan

Appendix B – Underground Utility Locates

Appendix C – Borehole Logs

Appendix D – Certificates of Equipment Calibration

Appendix E – Laboratory Certificates of Analysis

Appendix F – Qualifications of Assessors

Figures






Figure 1: Key Plan

Phase Two Environmental Site Assessment 2829 Dumaurier Avenue, Ottawa, Ontario 3223701 Canada Inc.

Project Reference No: LOP21-004C
Drawing No.: LOP21-004C-1
Date: June 9, 2021
Author: L. Lopers
Source: geoOttawa, Base Mapping






Figure 2: Site Plan

Phase Two Environmental Site Assessment 2829 Dumaurier Avenue, Ottawa, Ontario 3223701 Canada Inc.

Project Reference No: LOP21-004C
Drawing No.: LOP21-004C-2
Date: June 9, 2021
Author: L. Lopers

Source: geoOttawa, 2019 Aerial Imagery

Tables

Table 5: Soil Analytical Results

Phase Two Environmental Site Assessment 2829 DuMaurier Avenue Ottawa, Ontario

O.Reg.153/04 Table 1	O.Reg.153/04 Table 3	BH3D
----------------------	----------------------	------

			Background	Full Depth non-potable, coarse grained	1.2-1.8 mBG
Parameter	Units	MDL	residential/industrial	residential/ parkland/ institutional	Fill
Metals					
Antimony	ug/g dry	8.0	1.3	7.5	<0.8
Arsenic	ug/g dry	1	18	18	2
Barium	ug/g dry	2	220	390	56
Beryllium	ug/g dry	0.5	2.5	4	<0.5
Boron	ug/g dry	5	36	120	<5
Boron (Hot Water Soluble)	ug/g dry	0.1	NV	1.5	0.37
Cadmium	ug/g dry	0.5	1.2	1.2	<0.5
Chromium	ug/g dry	2	70	160	15
Cobalt	ug/g dry	0.5	21	22	4.7
Copper	ug/g dry	1	92	140	19
Lead	ug/g dry	1	120	120	28
Molybdenum	ug/g dry	0.5	2	6.9	<0.5
Nickel	ug/g dry	1	82	100	10
Selenium	ug/g dry	0.4	1.5	2.4	<0.4
Silver	ug/g dry	0.2	0.5	20	<0.2
Thallium	ug/g dry	0.4	1	1	<0.4
Uranium	ug/g dry	0.5	2.5	23	0.5
Vanadium	ug/g dry	1	86	86	21
Zinc	ug/g dry	5	290	340	124
Chromium VI	ug/g dry	0.2	0.66	8	<0.2
Cyanide	ug/g dry	0.04	0.051	0.051	<0.040
Mercury	ug/g dry	0.1	0.27	0.27	<0.10
Electrical Conductivity	ug/g dry	0.005	0.57	0.7	0.372
Sodium Adsorption Ratio	ug/g dry	NA	2.4	5	1.88
PAHs					
Naphthalene	ug/g dry	0.05	0.09	0.6	<0.05
Acenaphthylene	ug/g dry	0.05	0.093	0.15	<0.05
Acenaphthene	ug/g dry	0.05	0.072	7.9	<0.05
Fluorene	ug/g dry	0.05	0.12	62	<0.05
Phenanthrene	ug/g dry	0.05	0.69	6.2	0.06
Anthracene	ug/g dry	0.05	0.16	0.67	<0.05
Fluoranthene	ug/g dry	0.05	0.56	0.69	0.11
Pyrene	ug/g dry	0.05	1	78	0.09
Benz(a)anthracene	ug/g dry	0.05	0.36	0.5	0.06
Chrysene	ug/g dry	0.05	2.8	7	0.06
Benzo(b)fluoranthene	ug/g dry	0.05	0.47	0.78	0.07
Benzo(k)fluoranthene	ug/g dry	0.05	0.48	0.78	<0.05
Benzo(a)pyrene	ug/g dry	0.05	0.3	0.3	0.06
Indeno(1,2,3-cd)pyrene	ug/g dry	0.05	0.23	0.38	<0.05
Dibenz(a,h)anthracene	ug/g dry	0.05	0.1	0.1	<0.05
Benzo(g,h,i)perylene	ug/g dry	0.05	0.68	6.6	0.05
2-and 1-methyl Naphthalene	ug/g dry	0.05	0.59	0.99	<0.05
рН	NA	NA	NA	NA	7.44
Lab ID	-	-	-	-	9610086
Sample Date Notes	-	-	-	-	5-Oct-18

BOLD Exceeds MECP site condition standards
NA Not Analysed by laboratory

Table 6: Groundwater Analytical Results

Phase Two Environmental Site Assessment 2829 Dumaurier Avenue, Ottawa, Ontario

			Sample Location: Sample ID:	MW3S-101918	MW6-101918	BH3D MW3D-101918	BH1 BH1-GW1	MW MW95-1	95-1 Dup-1	MW95-2 MW95-2	Trip Blank	Trip Blank
			Sample 15.	WW33-101316	Duplicate of	WW3D-101516	BHI-GWI	1414433-1	Duplicate of	1010033-2		
			Sample Date:	October 19, 2018	BH3-21-GW2 October 19, 2018	October 19, 2018	May 17, 2021	May 17, 2021	MW95-2 May 17, 2021	May 17, 2021	October 19, 2018	May 17, 2021
		Method	Laborartory Sample ID:	9641876	9641879	9641877	2478945	2478991	2478993	2478992	9641881	2478995
Da sa	11	Detection Limit (MDL)	MECP Table 3 Standards Coarse Grain Soil									
Parameter Petroluem Hydrocarbons (PHCs)	Units	(IVIDL)	Coarse Grain Soil									
F1 PHCs (C6-C10) F2 PHCs (C10-C16)	ug/L ug/L	25 100	750 150	ND 170	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	-	-
F3 PHCs (C16-C34)	ug/L	100	500	860	ND	ND ND	ND	ND	ND	ND	-	-
F4 PHCs (C34-C50) Volatile Organic Compounds (VOC	ug/L Cs)	100	500	170	ND	ND	ND	ND	ND	ND	-	-
Acetone	ug/L	1.0	130000	ND	ND	ND ND	ND	ND	ND	ND	ND ND	ND
Benzene Bromodichloromethane	ug/L ug/L	0.20 0.40	44 85000	0.49 ND	0.85 ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Bromoform	ug/L	0.10	380	ND	ND	ND	ND	ND	ND	ND	ND	ND
Bromomethane Carbon Tetrachloride	ug/L ug/L	0.20 0.20	5.6 0.79	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Chlorobenzene	ug/L	0.10	630	0.64	1.3	ND	ND	ND	ND	ND	ND	ND
Chloroform Dibromochloromethane	ug/L ug/L	0.20 0.10	2.4 82000	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	23.9 ND	ND ND	ND ND
Dichlorodifluoromethane	ug/L	0.40	4400	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichlorobenzene 1,3-Dichlorobenzene	ug/L ug/L	0.10 0.10	4600 9600	ND ND	0.14 ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
1,4-Dichlorobenzene	ug/L	0.10	8	0.79	1.6	ND	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane 1,2-Dichloroethane	ug/L ug/L	0.30 0.20	320 1.6	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
1,1-Dichloroethylene	ug/L ug/L	0.20	1.6	ND	ND	ND	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethylene	ug/L	0.20	1.6	ND ND	0.27 ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
trans-1,2-Dichloroethylene 1,2-Dichloropropane	ug/L ug/L	0.20 0.20	1.6 16	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
1,3-Dichloropropene, total	ug/L	0.30	5.2	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Ethylbenzene Ethylene dibromide (dibromoethane, 1	ug/L 1 ug/L	0.10 0.10	2300 0.25	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Hexane	ug/L	0.20	51	ND	ND	ND	ND	ND	ND	ND	ND	ND
Methyl Ethyl Ketone (2-Butanone) Methyl Isobutyl Ketone	ug/L ug/L	1.0 1.0	470000 140000	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Methyl tert-butyl ether	ug/L	0.20	190	ND	ND	ND	ND	ND	ND	ND	ND	ND
Methylene Chloride Styrene	ug/L ug/L	0.30 0.10	610 1300	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
1,1,1,2-Tetrachloroethane	ug/L	0.10	3.3	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,1,2,2-Tetrachloroethane Tetrachloroethylene	ug/L ug/L	0.10 0.20	3.2 1.6	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Toluene	ug/L	0.20	18000	ND	0.32	ND	ND	ND	ND	ND	ND	ND
1,1,1-Trichloroethane 1,1,2-Trichloroethane	ug/L ug/L	0.30 0.20	640 4.7	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Trichloroethylene	ug/L	0.20	1.6	ND	ND	ND ND	ND	ND	ND	ND	ND ND	ND
Trichlorofluoromethane Vinyl Chloride	ug/L	0.40 0.17	2500 0.5	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
m/p-Xylene	ug/L ug/L	0.17	NV	ND ND	ND ND	ND ND	ND	ND ND	ND ND	ND	ND ND	ND
o-Xylene Xylenes, total	ug/L ug/L	0.10 0.20	NV 4200	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND
Polycyclic Aromatic Hydrocarbons		0.20	4200	ND	ND	ND	ND	ND	ND	ND	ND	ND
Acenaphthene Acenaphthylene	ug/L ug/L	0.20 0.20	600 1.8	-	-	-	ND ND	ND ND	ND ND	ND ND	-	-
Anthracene	ug/L ug/L	0.10	2.4	-	-	-	ND	ND	ND	ND ND	-	- -
Benzo[a]anthracene Benzo[a]pyrene	ug/L ug/L	0.20 0.01	4.7 0.81	-	-	-	ND ND	ND ND	ND ND	ND ND	-	-
Benzo[b]fluoranthene	ug/L	0.10	0.75	-	-	-	ND	ND	ND	ND ND	-	-
Benzo[g,h,i]perylene	ug/L	0.20	0.2	-	-	-	ND ND	ND ND	ND ND	ND	-	-
Benzo[k]fluoranthene Chrysene	ug/L ug/L	0.10 0.10	0.4 1	-	-	-	ND ND	ND ND	ND ND	ND ND	-	-
Dibenzo[a,h]anthracene	ug/L	0.20	0.52	-	-	-	ND	ND	ND	ND	-	-
Fluoranthene Fluorene	ug/L ug/L	0.20 0.20	130 400	-	-	-	ND ND	ND ND	ND ND	ND ND	-	-
Indeno[1,2,3-cd]pyrene	ug/L	0.20	0.2	-	-	-	ND	ND	ND	ND	-	-
1-Methylnaphthalene 2-Methylnaphthalene	ug/L ug/L	0.20 0.20	1800 1800	- -	- -	-	ND ND	ND ND	ND ND	ND ND	-	- -
Methylnaphthalene (1&2)	ug/L	0.20	1800	-	-	-	ND	ND	ND	ND	-	-
Naphthalene Phenanthrene	ug/L ug/L	0.20 0.10	1400 580	-	-		ND ND	ND ND	ND ND	ND ND	-	- -
Pyrene	ug/L	0.20	68	-	-	-	ND	ND	ND	ND	-	-
Metals Mercury	ug/L	0.02	0.29	ND	ND	ND	ND	ND	ND	ND	-	-
Antimony	ug/L	1.0	20000	ND	ND	ND	ND	ND	ND	ND	-	-
Arsenic Barium	ug/L ug/L	1 1	1900 29000	3.1 680	ND 688	ND 1110	1.8 102	5.1 1130	6.6 1110	4.6 227		- -
Beryllium	ug/L	0.5	67	ND	ND	ND	ND	ND	ND	ND	-	-
Boron Cadmium	ug/L ug/L	10 0.1	45000 2.7	54.8 ND	62.8 ND	20 ND	278 ND	24.3 ND	24.8 ND	16.4 0.28	-	-
Chromium	ug/L	1	810	12.6	10	14.5	ND	ND	ND	ND	-	-
Chromium (VI) Cobalt	ug/L ug/L	10 0.5	140 66	ND 1.2	ND 1.3	ND ND	ND ND	ND ND	ND ND	ND ND		-
Copper	ug/L ug/L	0.5	87	ND	ND	2.2	ND	ND	ND	ND	-	-
Lead Molybdenum	ug/L	0.1 0.5	25 9200	ND 1.5	ND 1.8	ND 1.3	ND 0.73	0.62 ND	0.53 ND	ND ND	-	- -
Nickel	ug/L ug/L	0.5	9200 490	ND	1.8 ND	1.3 ND	ND	ND ND	ND ND	ND ND	-	- -
Selenium	ug/L	1	63	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	1.4	-	-
Silver Sodium	ug/L ug/L	0.1 200	1.5 2300000	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND	ND ND		-
Thallium	ug/L	0.1	510	ND	ND	1.5	1	ND	ND	1.38	-	-
Uranium Vanadium	ug/L ug/L	0.1 0.5	420 250	3.3 ND	2.8 ND	4.1 6	ND ND	0.48 ND	0.47 66.3	ND 15.7	-	- -
Zinc	ug/L	5	1100	ND ND	ND	ND	ND	ND	ND	ND ND	-	-
General Inorganics Cyanide, free	ug/L	2	66	ND	ND	ND	ND	ND	ND	ND	_	-
рН	pH Units	0.1	NV	7.09	7.12	7.57	7.78	7.43	7.48	7.75	-	-
Chloride Sodium	mg/L mg/L	0.10 0.05	2300 2300	1150 384	1130 385	1400 606	83.1 84.4	925 292	928 291	316 132		- -
Electrical Conductivity	uS/cm	NV	NV NV	3603	3640	4580	768	3340	3290	1540	- -	-

NV - No value listed in MECP site condition standards - - Not Analyzed

ND - Not detected above laboratory method detection limits

BH3S-101918 - Sampling Completed by GHD - 2019 GHD Phase Two ESA

Appendix A

Sampling and Analysis Plan

(GHD, 2018)



Table of Contents

	1.	Background1						
	2.	Spec	Specific Objectives					
	3.	Utility	/ Service Clearances	2				
	4.	Spec	ific Requirements	2				
		4.1	Media for Investigation	2				
		4.2	Locations and Depths for Sampling	2				
		4.3	Parameters for Laboratory Analysis	3				
	5.	Quali	ity Assurance/Quality Control	4				
		5.1	Decontamination of Sampling Equipment	4				
		5.2	Field Duplicates	4				
		5.3	Trip Blanks	4				
		5.4	Soil Vapour Screening	4				
	6.	Stand	dard Operating Procedures	5				
		6.1	Well Development	5				
		6.2	Borehole Locating	5				
		6.3	Elevation Survey	5				
		6.4	Groundwater Elevation Survey	5				
		6.5	Groundwater Sampling	5				
Та	ble	Ind	lex					
	.Table	e 4.1.	Soil Sampling	3				
	Table	e 4.2.	Groundwater Sampling	4				

Attachment Index

Attachment A Proposed Borehole/Monitoring Well Locations



Background

A Phase Two Environmental Site Assessment is to be completed for the mixed commercial/institutional property identified as 2831, 2851, and 2865 DuMaurier Avenue in Ottawa, Ontario ("Site") to investigate the areas of potential environmental concern (APECs) identified by the Phase One ESA.

The Phase One ESA identified

- PCA#1 / APEC#1 (Item 30: Importation of Fill Material of Unknown Quality) | On-Site, importation of Fill material of unknown environmental quality used for grading the Site, specifically, for infilling previously observed drainage features at the Site.
- PCA#2 / APEC#2 (Item 58: Waste Disposal and Waste Management, including thermal treatment, landfilling and transfer of waste, other than use of biosolids as soil conditioners)
 Off-Site, a former landfill Site was identified to the east of DuMaurier Avenue, approximately 20 m east of the Site.

The contaminants of potential concern (CPCs) to be assessed as part of the Phase Two Environmental Site Assessment in the soil and groundwater are:

- APEC#1 | VOCs, Metals, PAHs
- APEC#2 | VOCs, Metals, PAHs

Select boreholes/monitoring wells placed in locations of the Site will be sampled to provide an assessment of the Contaminants of Potential Concern (CPCs) in the vicinity of each APEC.

Should additional contaminants be suspected during the course of the drilling program, additional sampling should be discussed with the project manager to determine appropriate analytical testing.

2. Specific Objectives

The following are the specific objectives of the planning of the site investigation component this Phase Two Environmental Site Assessment, as stated in O. Reg. 153/04:

- Plan an investigation that will achieve the general objectives of a Phase Two Environmental Site Assessment:
 - Through the use of appropriate and complete information base concerning the Phase Two property.
 - Through the conduct of an investigation based both on information obtained before the Phase Two Environmental Site Assessment begins and on the incorporation of information obtained during the Phase Two Environmental Site Assessment.
- 2. To develop a sampling and analysis plan that will adequately assess all areas of the Phase Two property where contaminants may be present in land or water on, in or under the property.



3. To develop a quality assurance program that is designed to effectively limit errors and bias in sampling and analysis through implementation of assessment and control measures that will ensure data are useful, appropriate and accurate in the determination of whether the Phase Two property, meets applicable site condition criteria.

3. Utility Service Clearances

Public and private utility service clearances will be provided to the field technician prior to commencing the drilling program. The project manager must be contacted immediately should any conflicts arise during the drilling program with the locations of underground services and the proposed borehole locations. Service clearances are included with the field instructions.

4. Specific Requirements

4.1 Media for Investigation

- Overburden soil sampling will be conducted on the day(s) of drilling.
- Groundwater monitoring wells will be installed during the drilling program to facilitate the collection of groundwater samples at a later date.
- No sediment is present on the Site, as such; sediment sampling will not be conducted as part of this investigation.
- No surface water bodies are present on the Site, as such; surface water sampling will not be conducted as part of this investigation.

4.2 Locations and Depths for Sampling

Locations

The proposed seven borehole locations are illustrated on the Proposed Borehole Location Plan sketch attached as Attachment A.

- Five boreholes advanced to practical auger refusal
- Approximately 1.5 m coring of bedrock at three borehole locations following refusal
- Install groundwater monitoring wells in all borehole locations including one nested well

The approximate locations and labelling of the boreholes/monitoring wells are indicated on the provided plan.

Depths

Continuous soil samples will be collected from the boreholes in 0.6 m intervals using stainless steel split spoons. Soil sampling will be conducted from ground surface down to proposed drilling depth (bedrock refusal).



Three of the groundwater monitoring wells will be screened screens within the upper layers of the bedrock. Two of the wells will be screened in the overburden material. Screens should be limited to a maximum wetted length of 3.0 m and a minimum total length of 1.5 m. The base of monitoring well screens used to assess PHCs should extend approximately 1.0 m below the expected groundwater table based on field observations. If additional drilling is required to intercept the groundwater table, please contact the project manager. Screens shall have a sand pack that extends a minimum of 0.15 m above the screen and must be sealed with a bentonite hole plug with a thickness of at least 0.6 m. If the depth of the groundwater and maximum screen length permits, monitoring well screens should straddle the groundwater table interface.

4.3 Parameters for Laboratory Analysis

Soil

A total of five original samples plus one duplicate sample will be selected for lab analysis. The following soil samples from the suggested depths below are suggestions for submittal for laboratory analysis of the specified analytical parameters:

Table 4.1 Soil Sampling

Location	Analytical Parameter	Approximate Depth/Stratigraphy
All Boreholes	Metals, PAHs, pH	 Sample Near water table interface, or Just above impermeable layer or Fill layer, or Area of obvious contamination
Duplicate Sample	DUP-1	Any material sampled for Metals, PAHs, and pH
Worst Case	Reg. 558 – laflesche unknown petroleum package	Select 1 sample for leachate (TCLP) Metal, Flashpoint, PAH, VOC, and PAH testing from borehole with most evident contamination. Bulk sample from the same borehole should be worst case soil followed by TCLP sample.

Should contamination be detected in other locations or evident contamination requiring vertical delineation is suspected in any borehole, this should be discussed with the project manager immediately.

Soil Jarring requirements:

- Metals, PAHs, pH one large soil jar and one vial
- Reg. 558 TCLP three large soil jars

Should any visually or olfactory observations be made with respect to the potential presence of contaminants in the soil at a specific depth in a particular borehole location, the soil sample with the suspected contaminants will be submitted for laboratory analysis in lieu of the sample depth referenced in the table above.



Groundwate.r

The following groundwater samples from the screened intervals will be submitted for laboratory analysis of the specified analytical parameters:

Table 4.2 Groundwater Sampling

Location	Analytical Parameters	Approximate Depth of Sample
All wells	Metals, VOCs, BTEX, pH	Screened Interval
Duplicate	DUP-1-Duplicate of Metals, VOCs, BTEX, pH	1/10 samples
Trip Blank	VOC	1/cooler

Should contamination be detected in other locations or evident contamination, this should be discussed with the project manager immediately.

5. Quality Assurance/Quality Control

5.1 Decontamination of Sampling Equipment

All non-dedicated sampling equipment such as stainless steel split spoons will be washed between uses.

Water level monitoring equipment, including water level meters and interface probes will be decontaminated with Alconox and rinsed with deionized water between water level readings to prevent cross contamination.

5.2 Field Duplicates

Field duplicate samples shall be collected in each medium (soil and groundwater) being sampled. At least one field duplicate sample will be submitted for laboratory analysis for every ten samples submitted for laboratory analysis.

Field duplicates will be selected from samples which have the greatest probability of environmental contamination (i.e., where field observations indicate potential contamination is present). A duplicate sample will be selected should the presence of contamination be suspected in any of the soil or groundwater samples.

5.3 Trip Blanks

One laboratory prepared trip blank shall be analyzed for VOC when submitting groundwater samples for analysis.

5.4 Soil Vapour Screening

All soil samples will be screened for organic vapours in the field using a Photoionization detector (PID) in the field. Soil samples with notably elevated combustible gas concentrations should be discussed with the Project Manager and may be selected for laboratory analysis.



6. Standard Operating Procedures

GHD standard operating procedures (SOP) shall be used during borehole drilling and soil sampling. Deviations to the SOP shall be discussed with the project manager.

6.1 Well Development

Groundwater monitoring wells will be developed on the day of drilling. At least three and up to ten well volumes will be removed from the monitoring wells in order to remove all sediment from the wells. In cases where the monitoring well goes dry prior to purging three well volumes, the well should be purged dry a minimum of three times, waiting approximately 30 minutes between purging events. Waterra tubing should be removed from the monitoring wells following well development.

6.2 Borehole Locating

The locations of all boreholes and monitoring wells must be measured in the field on the day of drilling. Borehole locations should be measured with respect to building corners or known property boundaries and shown on a plan.

6.3 Elevation Survey

An elevation survey of all boreholes and monitoring wells will be conducted following the completion of the drilling program. A fixed temporary benchmark should be used as a reference elevation; the top of the spindle of a fire hydrant is preferred for this purpose as geodetic elevations can be obtained for these points. The ground surface elevation of all boreholes should be surveyed. The top of riser of each monitoring well should also be surveyed; this will ensure maximum accuracy in the interpretation of groundwater elevations.

6.4 Groundwater Elevation Survey

Following a period of stabilization (one week is recommended) a groundwater elevation survey will be completed for all monitoring wells. The depth to groundwater is recorded prior to disturbance of the water column and is recorded with respect to the top of riser of the monitoring well.

6.5 Groundwater Sampling

Groundwater sampling is conducted following the collection of groundwater elevations. A peristaltic pump or Waterra tubing and footvalve are used for groundwater sampling. The wells are purged of standing water by removing at least one well volume. Samples are collected in dedicated bottles prepared by the laboratory. Samples are field filtered in the case of metals sampling.

Appendix B

Underground Utility Locates

(2018)

Monique Larocque

From:

Solutions@on1call.com

Sent:

Wednesday, September 19, 2018 10:51 AM

To:

moniquel@usl-1.com Request 20183813706

Subject: Attachments:

MapSelection 19092018 10492764.png; GHD.2831 Du Maurier.png

https://www.on1call.com/wp-content/themes/ooc/images/ooc-logo-2.png LOCATE REQUEST CONFIRMATION

TICKET #: 20183813706 REQUEST PRIORITY: STANDARD REQUEST TYPE: REGULAR

WORK TO BEGIN DATE:

09/26/2018

Update of Ticket #

Project #

Transmit date: 09/19/2018 10:51:00 AM

REQUESTOR'S CONTACT INFORMATION

Contractor ID#: 202

Company Phone #: (613) 226-8750

Contact Name: JACQUES DESJARDINS Cell #:

Alternate Contact Name: JEFF FORRESTER

Fax #: (613) 226-8677

Company name: USL Email: moniquel@usl-1.com Address: 775 TAYLOR CREEK DR Alternate Contact #:

DIG INFORMATION

Region/County: OTTAWA

Type of work: BORE HOLES

Mark & Fax: NO

Site Meet Req.: NO

Community:

Max Depth: 32.81 FT

Area is not marked: NO

City: OTTAWA Machine Dig: YES

Area is marked: YES

Address: 2831, DUMAURIER AVE To 2865

Hand Dig: NO

Directional Drilling: NO Work being done for: GHD

Intersecting Street 1: RAMSEY CRES

Public Property: YES

Intersecting Street 2: WATSON ST

Private Property: YES

DETAILED DESCRIPTION OF WORK

REMARKS

CORLOT=U Drilling trhourhout properties. Clear all of 2831 to 2865 DUmaurier Ave to all property lin es and to sidewalk

edge on Dumaurier Ave.

Civic # 2831, 2833, 2835, 2865.

MEMBERS NOTIFIED: The following owners of underground infrastructure in the area of your excavation site have been notified.

Member name Station Code

Initial Status

HYDRO OTTAWA (HOT1)

HOT1 Notification sent

PROMARK FOR ENBRIDGE GAS (ENOE01)

ENOE01

Notification sent

CITY OF OTTAWA WATER/SEWER (OTWAWS01) OTWAWS01

Notification sent

BLACK AND MC DONALD FOR CITY OF OTTAWA STREET LIGHTS (OTWASLO1)

OTWASL01

Notification sent

CLI FOR ROGERS (ROGOTT01) ROGOTT01

Notification sent

PROMARK FOR BELL CANADA (BCOE01) BCOE01Notification sent

MAP SELECTION: Map Selection provided by the excavator through Ontario One Call's map tool or through agent interpretation by phone

CONTRACTOR'S SKETCH: A file provided directly by the excavator, not generated by Ontario One Call:

IMPORTANT INFORMATION: Please read.

Defining "NC" - Non-Compliant

- Non-compliant members have not met their obligations under section 5 of the Ontario Underground Infrastructure Notification Act.ON1Call has notified these members to ensure they are aware of your excavation. In this circumstance, should the member not respond, the excavator should contact the member directly to obtain their locates or request a status. ON1Call will not be provided with a locate status from the member regarding this ticket and therefore, cannot provide further information at this time. For locate status contact information please refer to our website.

You have a valid locate when...

- You have reviewed your locate request information for accuracy. CONTACT Ontario One Call (ON1Call) IMMEDIATELY if changes are needed and obtain a corrected locate request confirmation.
- You have obtained locates or clearances from all ON1Call members listed in this ticket before beginning your dig.

You've met your obligations when...

- In addition to this locate request, you have DIRECTLY contacted all owners of infrastructure who ARE NOT current members of ON1Call (such as owned buried infrastructure on private property), as well as arranged for contract locates for your private lines on your private property where applicable. For a list of locate status contacts visit www.on1call.com.
- You respect the marks and instructions provided by the locators and dig with care; the marks and locator instructions MUST MATCH.
- You have obtained any necessary permits from the municipality in whichyou are excavating.

What does "Cleared" mean in the "Initial Status" section?

1. The information that you have provided about your dig will not affect that member's underground infrastructure and they have provided you with a clearance, if anything about your excavation changes, please ensure that you update your ticket immediately.

What are the images under "Map Selection":

- 1. A drawing created by an excavator directly within Ontario One Call's web ticket tool, this is expected to be an accurate rendition of the dig site, and it is the excavator's responsibility to ensure the location matches the information they provide under the 'Dig Location' section OR;
- 2. A drawing created by an Ontario One Call agent, this drawing is based on a verbal description by phone of the area by the excavator. Agents may create drawings that are larger than the proposed dig to minimize risk of interpretation. It is the excavator's responsibility to review these map selections for accuracy. Changes can be made by the excavator through the web ticket tool, to learn how visit www.on1call.com/contractors.
- 3. All drawings dictate which members are notified.

		20183	813706	_HOT1				Page 1 of 10
TELEC MARK	Fax:		y Locate S	heet ¹⁻⁹⁷⁷ -	GAS EMERGE 969-0999 mail:	NCY#	Request 201838	
613-723-9888	613-723-927		300-371-88				NORMAL	
Utilities Localed: •Bell •Gas •Hy	dro Ottawa D Hydro Dr	etions		wation Date	Excavation I 10/01/2018 0			Status STANDARD Homeowner C
Requested by: JACQUES DESJARDINS	Company: USL	1	am/ddiyyyy Phone: 61 3)-226-8751	Dext.	mmiddlyggy Fax/email: (613)-226-86	77 ext.		Contractor • Project 0
men/dahgay N/A 19/19/2		Locale 1st Inters		1 31 to 2865, CRES		Inters:	WATSON S	ī
Type of work: BORE HOLES					e afe	City:		
Caller's Remarks: CIVIC # 2831, 2833, 2835, 2865. MACH. DIG CORLOT=U DRILLING TRHOURHOUT PF DUMAURIER AVE75.793499, 45.350499, NB_SEGMENTS	S::2, NO_PLAN::513 828	, BOOE01,	ROGOTTON, C	OTWASLO1, OT	WAWSD1, EN	OB01, HOT	1 1	
Bell Enbridge Gas Hy Mark Clear Mark Clear Ma 1 1 1	droOttawa Street Ug irk Clear Mark		Lakefront lark Clear	Hydro One Mark Clea	Veridia ar Mark (C		nion Gas ark Clear	Videotron Mark Clear
LOCATED AREA: EXCAVATOR	R SHALL NOT WOP	K OUTS	IDE THE L	OCATED AR	EA WITHO	UT OBTA	AINING AN	HOTHER LOCATE
_ web _ Network y #	G-MOBILE	_ Thin	d Party Noti	fication				
_ Byers 🖢 Datapak: . 🚨 LAC	Multiviewer		***	DANGER	DO NOT	PROC	EED***	
Field Notes: CPU1389 NE123				l high volta cated area				
Other: 6N592-1, 6N4012-6 DPT Remarks:			1	cated area s upervis io				* * * * * * * * * * * * * * * * * * *
DF : Rolliders.			ог соп	tact Hydro	Ottawa at	613-7 ation.	38-6418	
					3-738-642		***************************************	
		1		Apply Stic	ker Here if F	Required	*2 5 2	
Excavator shall notify & receiv	e a clearance fron	Udility	rior to exc		the follow			
	riority Cable	rimment ition with	al Office Vid		NA			
Method of Field Marking: • P						-		
Caution: Locales are VOID after Caution: Any changes to location								oeines.
Located Area without a new locate service/property owner. For all Lo	e. Privately owned s	ervices w	ithin the loc	ated area ha				ith

Locator Name: ROOTS DAN Start Time: 9:00 **●** Emailed _ Mark & Fax _ Left on Site N/A ID#:_1717 End Time: 14:00 Print:

N/A Total Hours: 5HR 09/28/2018 Date Signature:

A copy of this Primary Locate Sheet and Auxiliary Locate Sheet(s) must be on site and in the hands of the machine operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

Ontario One Call at 1-800-400-2255 or www.on1call.com.

operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

THIS FORM VALID ONLY WITH Primary Locate Form. This sketch is not to scale. Any privately owned services within the located area have not been marked- check with service/property owner.

RAMSAY CRES

A copy of this Auxiliary Locate Sheetia) and the Primary Locate Sheet must be on site and in the hands of the machine operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

Street Light North

South

East

West

SW

N.

S.

E.

W.

SW

N.AE

A copy of this Auxiliary Locate Sheet(s) and the Primary Locate Sheet must be on site and in the hands of the machine operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

X

FROM: W.FC OF DUMAURIER AVE

Auxiliary Locate Sheet

Union Gas Emergency # 1-877-969-0999

Phone: 613-723-9868

Fax: 613-723-9277 Toll free: 1-800-371-B866 Email

Utilities ● 3el Localed: □ Videotron **©Peet Fibre**

Property Line - PL-ASPHALT EDGE -AE-Driveway - DW

Catch Basin

Demarcation (

Sidewalk

D Gas DHydroOttawa D Hydro One

Veridian connections

Date Located: 09/28/2018 mmháid/gygg

Request # 20183813706

Hamber of Services marked: (Specify building/house numbers)

N/A

LOCATED AREA: EXCAVATOR SHALL NOT WORK OUTSIDE THE LOCATED AREA WITHOUT OBTAINING ANOTHER LOCATE

FROM: 27.0M SOUTH OF N.FL OF 2831-2865 DUMAURIER AVE

TO: 6.0M SOUTH OF N.FL OF 2831-2865 DUMAURIER AVE

TO: 25.0M WEST OF W.FC OF DUMAURIER AVE

CAUTION: Hand dig within 1 M as measured horizontally from the field markings to avoid Legend demaging the underground utilities. If you damage the plant, you may be held liable. Building Line - BL If you damage underground plant, contact the facility owner immediately. Fence Line - FL-Depth varies and MUST he verified by hand digging or vacuum excavation. Face of Curb - FC-LOCATED AREA HAS BEEN ALTERED AS PER: Road Edge - RE-

Railway **Fole** 2831 Firsh to Grade Pedestal TO 2865 Pedestal Buried Cable **-8** Conduit Burled **ASW** Service Visa

CR

SW

Manhole Fibre Optic

Cable - FO-Bell Hydro Service -HS

Gas Main - GM Gas Service -

Gas Valva 汉 Hydrant

Transformer Hydro Hydro Pole X

Streat Light Cable SI Street Light North N. South S.

> East E. W. West

LOCATED AREA NTRANCE TO 2831-2885 Bell Bell CAUTION Cables May or May Not Be in Conduit Bui W.AE SW E AE W FC

THIS FORM VALID ONLY WITH Primary Locate Form. This sketch is not to scale.

DUMAURIER AVE

Any privately owned services within the located area have not been marked- check with service/property owner. A copy of this Auxiliary Locate Sheetis) and the Primary Locate Sheet must be on site and in the hands of the machine operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.

I I

ENTRANCE TO 2825

TELECUN.		Auxiliary L	ocate Sheet	Union Gas Emergency # 1-877-989-0999		
Phone 613-72	23-9888	Fax: 613-723-9277	Tall free: 1-800-371-8	Email		
Utilities 🗆 Bell 🗆 Gas	■ HydroOttawa	☐ Street Lighting	Date Located:	Request #	20183813706	
Located: OBlink OP	Pael Fibra 🗆	0	mmMddfyygg 09/28/	/2018		
Number of Services ma	irked: (Specify bu	iiding/house numbers				
LOCATED AREA: EXCA	AVATOR SHALL NO	OT WORK OUTSIDE	THE LOCATED ARE	A WITHOUT OBTAIN	NING ANOTHER	LOCATE
FROM, 27.0M SOUTH OF	N.FL OF 2831-2865	DUMAURIER AVE	TO: 6.0M SOUTH O	F N.FL OF 2831-2865	5 DUMAURIER AV	Æ_
FROM: W.FC OF DUMAU	IRIER AVE		TO: 25.0M WEST O	F W.FC OF DUMAUR	JER AVE	
Legend Building Line — BL— Fence Line — FL— Face of Curb — FC—	dama If yo Dept	I: Hend dig within 1.5M Iging the underground ou damage undergro th varies and MUST ED AREA HAS BEEN	utilities. If you damage ound plant, contact be verified by hand	ge the plant, you may the facility owner i I digging or vacuum	y be held liable. immediately.	
Road Edge — RE—	Market					
Property Line — PL— ASPHALT EDGE -AE-						
Driveway — DW—				5		
Catch Basin CB				Ā		
Sidewalk _SW_				Ø 4 (★)► 2	<u> </u>	
Demarcation DM				T	×	
Railway ###	—W.BL—				Age of the second secon	
Pole O	-					
Flush to Grade	2831 TO					
Pedestal X	10 m 2865 ≠					
Buried Cable — B —						
Conduit — C —	-EBL-	LOCATED	AREA			
Service Vire —BSW—			7 51 7 hund 5			
Manhole MH				4.		
Fibre Optic						
Cable — FO—						1
Gas Main — GM—						
Gas Service — GS—						
Gas Valve	885					4
Hydrant 🌣	ENTRANCE TO 2831-2885		HYDRO OTTAWA	NETWORK	<u> </u>	
Transformer 🔼	28	**************************************	# 1 He level her t a seeke was been a			325
Hydre Ottawa — H —	T 0 2					0.24
Hydro Pole X StreatLightCable — SL—	Ş					ENTRANCE TO 2825
Street Light 💢	₹ WAE+	SW	Note that the second			–Ĭÿ
North N.	E AE -	V. 11				- ∤ ፪
South S.	-w.Fc-L					
East E.			DUMAURIER /	AV/E		
West W.	TUICEN	THE PARTY AND VIOLET			* 41_	
		RM VALID ONLY WIT services within the local				en o r
A copy of this Auxiliary i						

operator during work operations. If sketch and markings do not coincide, the Excavator must obtain a new locate.



MESSAGE REGARDING REQUESTED LOCATE

Dear Excavator,

Hydro One has completed your locate request based on the information you provided to Ontario One Call. The underground facility locate on our **Distribution** system is valid for **60 days** from the date shown on the Underground Cable Stakeout Report attached. The 60 day validity <u>does not</u> include Transmission locate requests. Please be aware new underground facilities can be installed any time after this locate was completed. It is your responsibility to contact Ontario One Call for a new locate if any changes are known or suspected or for a Relocate if excavation continues beyond 60 days.

Hydro One expects excavators to protect and preserve the paint marks and flags placed at the time of the original locate ticket. If markings are removed due to weather or excavation work, the excavator is expected to recreate the markings based on the tie-in measurements provided on the original locate ticket. However, if an excavator would like Hydro One to refresh their markings, please contact Ontario One Call at 1-800-400-2255 to request a Remark.

WARNINGS AND DISCLAIMERS:

Hand dig cautiously 1 meter around Hydro One's Red Paint Markings as indicated on the Underground Cable Stakeout Report. It is understood that the attached information has been provided from our records, and represents our knowledge of the approximate location of **Hydro One** plant only: the contractor must request stakeouts from other utilities to establish the location of their plant. The company or contractor must exercise extreme caution where mechanical equipment is used in the vicinity of the underground cable plant and where necessary to locate by hand its actual position. Liability for damages rests with the company or contractor.

Thank you, Hydro One

20183922522



Dear Excavator:

We are in receipt of your recent request for a Bell relocate.

Please be advised that the original locate(s) issued for the request in question will remain valid for the duration of your project. If any of the exceptions below apply and you would like the site remarked for Bell or you would like to discuss your relocate request, please contact us during business hours at 1-844-225-5550, Option # 8:

- The excavator did not start their work within 60 days of the original locate completion date
- Tie in's/offsets used as measurements on the original Bell locate are no longer there
- The excavator suspects new Bell plant has been added in the locate area since the original locate
- The excavator has lost control of the site for an extended period of time (i.e. the excavation begins however the excavator has left site and did not return for 60 days or more)
- There is a sticker on your locate indicating there is a Bell Hydro line in the locate area and you're
 entitled to a Relocate of that area.

Bell expects excavators will protect and preserve the paint marks placed at the time of their original locate. If markings are removed due to weather or ongoing excavation work, the excavator is expected to recreate the markings based on the tie-in measurements provided on the original locate sheet.

If an excavator would like their markings refreshed they can contact the Bell LSP (Locate Service Provider) directly and arrange for this at the excavator's expense. The LSP contact information is available on the original locate sheet.

Sincerely,

Bell Screening Centre

DISCLAIMER

Warning!

The Excavator must have a copy of this locate on the job site during excavation.

Located Area: The Excavator must not work outside the area indicated by the Located Area in the Diagram without a further locate by the Company

Locate the plant: The plant location information provided is the best we have available but constitutes only an estimate. Depth of underground plant varies and the exact location must be determined by hand digging prior to excavation with mechanical equipment.

Mechanical equipment must not be used within one metre of the estimated location of the plant.

Hydro Ottawa must be notified prior to excavation and inspector on site

Expose the plant: Once the plant has been located by hand digging, it must be exposed along its length adjacent to or in the immediate vicinity of the proposed excavation. For this purpose, mechanical equipment must not be used within 0.5 metres of the plant.

Digging around the exposed plant: When the plant has been exposed, any further excavation within 0.3 metres, must only be done by hand digging and not with mechanical equipment.

Support Requirements: If the underground plant is exposed over a distance of more than 1.25 metres, the Facility Owner must be notified. Underground plant must be supported at all times.

O. Reg. 210/01 Oil and Gas Pipeline systems EXCERPTS

- 9. (1) No person shall dig, bore, trench, grade, excavate or break ground with mechanical equipment or explosives without first ascertaining the location of any pipeline that may be interfered with.
- 10. No person shall interfere with or damage any pipeline without authority to do so.

Technical Standards & Safety Act 2000 EXCERPT

37 (1) Every person who contravenes or fails to comply with any provision of this act or the regulations; etc... is guility of an offense and on conviction is liable to a fine of not more than \$50,000 or to imprisonment for a term of not more than one year, or to both.

Caution: The markings may disappear or be misplaced. Should sketch and markings not coincide, Excavator must obtain a new locate. This is based on information given at the time. Any changes to location or nature of work require a new locate. The Excavator must not work outside the indicated Located Area without a further locate. Privately owned services within the located area have not been marked - check with service/property owner.

Locate is VOID after 30 days.

For remarks contact Ontario One Call 1-800-400-2255, or www.on1call.com



DISCLAIMER

Warning!

The Excavator must have a copy of this locate on the job site during excavation.

Located Area: The Excavator must not work outside the area indicated by the Located Area in the Diagram without a further locate by the Company

Locate the plant: The plant location information provided is the best we have available but constitutes only an estimate. Depth of underground plant varies and the exact location must be determined by hand digging prior to excavation with mechanical equipment.

Mechanical equipment must not be used within one metre of the estimated location of the plant.

Hydro Ottawa must be notified prior to excavation and inspector on site

Expose the plant: Once the plant has been located by hand digging, it must be exposed along its length adjacent to or in the immediate vicinity of the proposed excavation. For this purpose, mechanical equipment must not be used within 0.5 metres of the plant.

Digging around the exposed plant: When the plant has been exposed, any further excavation within 0.3 metres, must only be done by hand digging and not with mechanical equipment.

Support Requirements: If the underground plant is exposed over a distance of more than 1.25 metres, the Facility Owner must be notified. Underground plant must be supported at all times.

O. Reg. 210/01 Oil and Gas Pipeline systems EXCERPTS

- 9. (1) No person shall dig, bore, trench, grade, excavate or break ground with mechanical equipment or explosives without first ascertaining the location of any pipeline that may be interfered with.
- No person shall interfere with or damage any pipeline without authority to do so.

Technical Standards & Safety Act 2000 EXCERPT

37 (1) Every person who contravenes or fails to comply with any provision of this act or the regulations; etc... is guility of an offense and on conviction is liable to a fine of not more than \$50,000 or to imprisonment for a term of not more than one year, or to both.

<u>Caution</u>: The markings may disappear or be misplaced. Should sketch and markings not coincide, Excavator must obtain a new locate. This is based on information given at the time. Any changes to location or nature of work require a new locate. The Excavator must not work outside the indicated Located Area without a further locate. Privately owned services within the located area have not been marked - check with service/property owner.

Locate is VOID after 30 days.

For remarks contact Ontario One Call 1-800-400-2255, or www.on1call.com



City of Ottawa Locate Report - Water and Sewer Utilities Rapport de localisation des conduites d'eau et d'égout d'Ottawa



For more information / Pour de plus amples renseignements : 3-1-1 or/ou (613) 580-2424, ext. (poste) 22336.

Date:	Work Order # / No d'ordre de travail :
26/9/18	11668505
Location of Work / Lieu de travail :	ON1CALL#/No d'appel ON1 :
2865 Dumaurier Ave.	201838137061
Type of Work / Type de travail :	☐ ArcView attached
bore hous	Plan ArcView ci-joint
Contractor / Entrepreneur :	Fax / Télécopieur :
USL.	1 ax / Telecopledi :
	e croquis n'est pas à l'échelle
OREIGH NOT TO Scale / L	Le croquis ir est pas a recrieile
280	Zie, Min Zie, William Zie, Will
Raw	key Cr
Contractor signature	
Signature de l'entrepreneur	Locator (please print) Marqueurs [en lettres moulées]
Method of marking / Méthode de marquage	०२० गणाः मृह्या गणातमः कृष्याः कामानादानामः । विवेशनाद्यां विवेशनाद्यां विवेशनाद्यां विवेशनाद्यां विवेशनाद्या
<u> </u>	
☐ Flags / Drapeaux ☐ Paint / Peinture	Other (specify) / Autre [précisez] :
Remarks / Commentaires :Cours in	lot blocking valves
Office copy : White Contractor copy Copie du bureau : Blanc Copie de l'entre	y: Yellow Void after 60 days. epreneur : Jaune Périmé après 60 jours.

Monique Larocque	
From: Sent: To: Cc: Subject: Attachments:	ESD-Locate / SE-Localiser <esd-locate@ottawa.ca> Thursday, September 27, 2018 8:01 AM 'moniquel@usl-1.com' ESD-Locate / SE-Localiser Locate: DUMAURIER AVE - 20183813706 11668505.pdf; City of Ottawa Disclaimer - ville d'Ottawa avis de non-responsabilité - Copy - Copy.pdf</esd-locate@ottawa.ca>
Please find attached the lo	cate for DUMAURIER AVE.
Thank you,	
Axel Grissa	
City of Ottawa	
Technology, Innovation & E	Engineering Support Services Public Works & Environmental Services Department
(613)-580-2424 x22336	
<http: en="" ottawa.ca=""></http:>	

Please note: City of Ottawa locates are only valid for sixty (60) days.



DISCLAIMER

The excavator must have a copy of this locate on the job site during excavation.

Locate area: The excavator must not work outside the area indicated in the location of work or located area in the diagram without an updated locate. Stakes or markings may disappear or be displaced. If any delays occur in acting on the stakeout information, or if markings become unclear, a new locate must be obtained.

Locating the plant: The plant location information provided is only an estimate. Depth of underground plant varies and the exact location must be determined by hand digging prior to excavation with mechanical equipment.

Warning: Do not use mechanical equipment within one (1) metre of the estimated location of the water or sewer plant. If the plant is larger than 406mm, mechanical equipment must not be used within three (3) meters.

Digging around exposed plants: Must do any further excavation within 0.3 metres of an exposed water or sewer plant by hand.

Contractors are to perform all work in accordance with applicable City of Ottawa By-laws and any applicable federal and provincial legislation or regulations, including but not limited to the *Public Utilities Act, R.S.O. 1990, c. P.52, s. 56(1)*; Ontario Regulation 210/01 under the Technical Safety Standards Act, 2000, S.O. 2000 c. 16; Ontario Regulation 213/91 under the Occupational Health and Safety Act, R.S.O. 1990, c. O.1.

AVIS DE NON-RESPONSABILITÉ

L'opérateur de l'excavatrice doit avoir en sa possession ce rapport de localisation pendant l'excavation.

Zone de localisation : l'opérateur de l'excavatrice ne doit pas creuser en dehors de la zone indiquée sur l'ordre de travail ni à l'extérieur de la zone indiquée sur le diagramme, à moins d'avoir en sa possession un rapport de localisation actualisé. Les piquets ou les marques peuvent disparaître ou être déplacés. S'il y a un retard à intervenir sur la base des données de surveillance ou si le marquage devient imprécis, il faut obtenir un nouveau rapport de localisation.

Déterminer l'emplacement des conduites : les renseignements sur l'emplacement des conduites sont approximatifs. Pour déterminer l'emplacement et la profondeur, on doit creuser manuellement avant d'utiliser une excavatrice.

Avertissement: n'utilisez pas d'équipement mécanique [excavatrice] à moins d'un [1] mètre de l'emplacement supposé de la conduite d'eau ou d'égout. Si la conduite compte plus de 406 mm de diamètre, aucun équipement mécanique ne doit être utilisé à moins [3] de trois mètres de celle-ci.

Creuser autour des conduites exposées : toute excavation à moins de 0,3 m d'une conduite d'eau ou d'égout doit se faire manuellement.

Les entrepreneurs doivent exécuter tous les travaux conformément aux règlements de la Ville d'Ottawa et aux lois et règlements fédéraux ou provinciaux applicables, y compris, mais sans s'y limiter, la Loi sur les services publics, L.R.O. 1990, chap. P.52, art. 56[1]; le Règlement 210/01 de l'Ontario en vertu de la Loi de 2000 sur les normes techniques et la sécurité, L.O. 2000, chap. 16; et le Règlement 213/91 de l'Ontario en vertu de la Loi sur la santé et la sécurité au travail L.R.O. 1990, chap. O.1.

3	ANADIAN	
	OCATORS IN	IC.
Phi	(905) 479-5674	En

ROGERS

ON 1 Call Ticket #:

LOCATOR	RS INC.	Primary Local	te Sheet	20183813706
Ph: (905)479-	5674 Email: ontario	@canadianlocators.com		
Contractor / Excavat	or:		Contact Name : JACQUES DESJARDIN	· S
Tel: 613-226-8750	Alt. Phone :	Email: moniquel@usl-1.com		
Received Date :	Excavation Date : Sep 26 2018	Revised Excavation Date:	Type of Work: BORE HOLES	
Locate Address :	enen er er er en elle er en	annen i Banarana ann ann an an an an an an an an an a	City / Municipality:	
Vearest Intersection	po de la composito de la compo	est tymas teining opsigo, opsigo objekt met er et erseperatuur	Iviium, vainne	
AMSEY CRES & Wethod of Field Mark	and the territories and the second of the se	ikes 🗹 Flags	марадына бүни авайлан түү өтө тогоо элэг начин ай тайг нуу бай түү сар тайгаас түүсөгүү	
	ing trhourhout prope	rties. Clear all of 2 Ave.//Civic # 2831, 2		ier Ave to all property line
Julilies Marked :	ngan sammanan an			This locate has multiple work areas
Coaxial Plant	Fibre Optics Plant	The state of the s		which are greater than 100 m apart :
Total Length:	Total Length :			
	Field skeich an	å Lormal ing stin	rn an anxilary la	suse sheed(s)
	This locate	is for Restall R.S. plan	ar classical extra classe.	
		mply sticker her	e if required	
AUTION : Lo	cate is VOID after 60) days!		
CAUTION : Ha Auxiliary Loca area or nature	nd dig within one (1	l) meter or 3.28 feet of s all known ROGERS new locate.		ocated Area defined on the ny changes to excavation
ocator's Name : (Ple	ase Print)			
ocator's Name : (Ple Jason Vanslyke Date :	ase Print) Start Time :	End Time :		



ROGERS Auxiliary Locate Sheet

ON 1 Call Ticket #:

20183813706

Ph: (905)479-5674 | Email: ontario@canadianlocators.com

Utilgies Marked :		<i>j</i>					
Coaxial Plant	205 m	☑ Fibre Opt	ics Plant 5	m		1	
Number of Service	s Marked : (speci	y building house numbers)					
						al a	
TO COME OF THE SERVICE COMMENT OF THE SERVICE OF TH	LOCATE	D AREA CONTAIL	NS ALL KI	NOWN RO	GERS INFRA	STRUCTURE	
nde se consideraminament de la companion de la La companion de la companion de		dialek di kirin kalikari kalikari kali kalikari kalikari kalikari kalikari kalikari kalikari kalikari kalikari Kalikari	ambala saladid dalam bahish adalam sashinan sashina	Іто:	concerce maintenine necessition is enterinetto intelestationalistication		en e
FROM: M/FI	5 DUMAURIER	AVENUE			RAMSEY CRESCE	MT	
FROM:	5 DUMAURIER	AVENUE		TO: W/RE DUMA	urier avenue		


Hand dig within 1 meter or 3.28 feet as measured horizontally from the field markings to avoid damaging the underground utilities.

If you damage the utilities, you may be held liable. For all cut cable, please call: 1-800-265-9501 immediately!

Depth of cable plant varies and MUST be determined by hand digging or vacuum excavation.

LOCATED AREA ALTERED AS PER:





LEGEND: Transformer Road Edge -RE Property Line -Streetlight (SL) Tree Fibre Optic FO 8ldg Line - BL Pedestal Manhole (%) Lot Line -- LL ---Hand Hole HH Cable / T.V. CATV ---Pole Face of Curb - FC -North Direction N Catch Basin [CB] Hydrant [[H]] Conduit --- C Valve Driveway - DW -North N East E Sidewalk Railway Measurement — Fence Line - FL Vault V Work Area South

A copy of this Auxiliary Locate Sheet(s) and the Primary Locate Sheet must be on site and in the hands of the machine operator during work operations. Should sketch and markings not coincide, a new locate MUST be obtained.

Ontario One Call TF

City of Ottawa Street Light Locate



NOTICE OF INTENT TO EXCAVATE

Header Code:

STANDARD

Red

Request Type:

NORMAL

Ticket No:

20183813706

Original Call Date:

09/19/2018 10:51:27 AM

Work To Begin Date:

09/26/2018

Company:

USL

Contact Name:

JACQUES DESJARDINS

Pager: Cell:

Contact Phone:

(613)-226-8750 ext.

Fax: Alternate Contact: (613)-226-8677 ext. JEFF FORRESTER

Alt. Phone:

Place:

AWATTO

Street: 2831

DUMAURIER AVE

Nearest Intersecting Street:

RAMSEY CRES

Second Intersecting Street:

WATSON ST

Subdivision:

OTTAWA

Additional Dig Information:

CIVIC #2831, 2833, 2835, 2865. CORLOT=U DRILLING TRHOURHOUT PROPERTIES. CLEAR ALL OF 2831 TO 2865 DUMAURIER AVE TO ALL PROPERTY LINES AND TO SIDEWALK EDGE ON DUMAURIER AVE. NO_PLAN::613 828

WO/JOB#:

ANYTIME

Type Of Work:

BORE HOLES

Remarks:

-75.793499 45.350499 NB_SEGMENTS::2 BCOE01 ROGOTT01 OTWASL01 OTWAWS01 ENOE01 HOT1

Ont Call#	20183813706	City of Ott	awa Street Light	Locate	
Date	09/19/2018 10:51:2	_	er: Lisa Bisaillon		Black& M ^c D
Requested	AM		13-526-1226		A 4 (10)
		-			
	USL		Instructions 2831 to 2865, DUMAU	IRIER AVE	
		RDINS	CIVIC # 2831, 2833, 2	835, 2865. CORLOT=	U DRILLING TRHOURHOUT
	(613)-226-8750 ext.				5 DUMAURIER AVE TO ALL E ON DUMAURIER AVE.
			NO_PLAN::613828) TO SIDEWALK EDG	E UN DUMAUNER AVE.
	JEFF FORRESTER				
Phone					
		LOCA	TOR SKETCH		
			ron orallon		
					4
	Name JACQUES DESJARDINS Phone (613)-226-8750 ext. e Contact JEFF FORRESTER Phone No Lig				
		' (Clear		
			Jicai		
	т.				
	*	No City of O	Hawa Street		
		140 City of C	llawa Sileet		
		Light assets	s in dig area	*	
		Light assets	ili dig alea		
		CLEAD DA	ACT CIDENAL	VI IZ	
		OLEAR PA	AST SIDEWA	1LN	





sL	Underground	Street	Light	Cable
* 1	Street Light		*	

Overhead/Aerial Wires Globe/Decorative Light △ Source/Transformer O Hydro Pole

Locator Notes/Comments:

Locate is valid for 60 days. If sketch is different from markings, location or nature of work changes, a new locate must be requested. Hand dig within 1m (3.28ft) on either side of markings. Depth of buried plant varies.

Cette fiche n'est pas valide 60 jours de calendrier apres le reperage. Si les marques ne concordent pas avec celles sur le croquis, un nouveau reperage est requis. Tout changement a l'emplacement ou a la nature du travail necessite un nouveau reperage. Creuser a la main un metre (3.28 pieds) du repere. La profondeur des installation varie d'un endroit a l'autre.

Date Located	09/21/2018
Time of day	
Located by	JUSTIN VAVROS
Signature	
	Page 2 of 2

Disclaimer



Warning!

The Excavator must have a copy of this locate on the job site during excavation.

Located Area: The Excavator must not work outside the area indicated, by the located area in the diagram, without a further locate completed by Black & McDonald Limited.

Locate the Plant: The plant location information provided is the best we have available, but constitutes only an estimate. Depth of underground plant varies and the exact location must be determined by hand digging prior to excavation with mechanical equipment.

Mechanical equipment must not be used within 1.0 meter of the estimated location of the plant.

Valid Documentation: This locate is valid only for the Agency accepting it. Other parties must obtain and accept their respective underground locate from **Ontario 1 Call**.

Excavator Alterations: Under no circumstance shall an Excavator touch or move an underground power cable. Arrangements must be made to have qualified personnel relocate any such cable.

Expose the plant: Once the plant has been located by hand digging, it must be exposed along its length adjacent to or in the immediate vicinity of the proposed excavation. For this purpose, mechanical equipment must not be used within 0.5 meters of the plant.

Digging around the Exposed Plant: When the plant has been exposed, any further excavation within 0.3 meters, must only be done by hand digging and not with mechanical equipment.

Support Requirements: If the underground plant is exposed over a distance of more than 1.25 meters, the Facility Owner must be notified. Underground plant must be supported at all times.

Private Cables: Please be advised that Black & McDonald Limited is not responsible for and does not locate private cables

New Cables: Be aware that new cables could be installed at any time after the locate has been completed. It is the Excavator's responsibility to call for new locates if any changes are known or suspected.

<u>Caution:</u> The markings may disappear or be misplaced. Should sketch and markings not coincide, the Excavator must obtain a new locate. This is based on the information given at the time. Any changes to location or nature of work require a new locate. The Excavator must not work outside the indicated located area without a further locate. Privately owned services within the located area have not been marked- check with service/property owner.

Liability: Any person or Excavator who interferes with or damages any underground electrical cable without having obtained a valid locate/clearance from **Black & McDonald Limited**, shall be liable for all cost incurred during the repair of the cable as well as any resulting legal actions.

This locate has been given as accurately as possible, but no locate is guaranteed. Excavators must always dig with extreme caution to prevent the possibility of damaging electrical cables and endangering safety.

Locate is void after 60 days

For remarks contact Ontario One Call 1-800-400-2255 or www.on1call.com



UNDERGROUND SERVICE LOCATORS - F	PRIVATE UTILITY REPORT DATE: 10-64-2018
ONE-CALL SYSTEMS INC.	10F3
775 TAYLOR CREEK DRIVE	PHONE (613) 226-8750
OTTAWA, ON, K4A 0Z9	FAX (613) 226-867
CUSTOMER: GHD	REQUESTED BY: RYAN
LOCATION OF WORK: 2865 DU MAURIGA	AUCLIMITS OF WORK: AS PER MAP
HYDRO H CABLE T.V.	T.V STEAM STEAM
GAS G SANITARY BELL B STORM	-(SAN ELECTRICAL(EL) -(ST-) COMMUNICATIONS COM
BELL B STORM UNIDENTIFIED CABLE UC FIBER OPTIC	
WATER W	TO ADDIVE A COLUMN APPENDING DAVID
LOCATES ONLY APPLICABLE TO INI	FO ABOVE - LOCATES VOID AFTER 30 DAYS!
	SKIETCH NOT TO SCALE
0 + 57M	
H + 574	34N REFERENCE
	NORTH
1	7
*	CATV
C.6 /	
 * 	
	2 M 24 P. 1720
	<u></u>
1 1	↑
6.6	
	C-6
1 †	
USL-1 as a Private utility locator, is not permitted to locate Publicly of	owned utilities. In some cases, Public utilities may be noted on a sketch, but are
Public utilities noted on the USL-1 sketch by referring to the Public t	ed for excavation purposes. It is the contractor's responsibility to verify any utility locate sheets for physical LOCATION AND ACCURACY, USL-1 DOES NOT
ASSUME LIABILITY FOR PUBLIC LOCATE INNACCURACIES.	that all buried utilities are Private. Regardless of when you are digging, and what
the proposed depth of excavation is, it is the law to notify Ontario Or	ne Call (or Info-Excavation in Quebec) to obtain Public utility locates.
COMMENTS: NO OTHER PRIVATE UTILIT	TIES DETECTED
THIS SKETCH IS NOT A PUBLIC UTILITY LOCATE/DOCUMENT	F. PUBLIC UTILITIES SHOWN ARE FOR REFERENCE ONLY. REFER TO
USL-1 DISCLAIMER - FORM 101. CONTRACTOR IS RESPONS	IBLE TO ENSURE THEY HAVE PUBLIC UTILITY LOCATES BEFORE
COMMENCING WORK.	CIONATURE
LOCATORS NAME: CHRIS WHARTON	SIGNATURE: · · · () // >
LOCATE RECEIVED AND REVIEWED BY	Print Name Signature
CALITION: HAND DIG WITH	IN 1.5 METERS OF MARKINGS
	IIN 1.3 METERS OF MARKINGS

	UNDERGROUND SERVICE LOCATORS - PRIV	ATE UTILITY REPORT DATE: 10-04-2018
i Ē	ONE-CALL SYSTEMS INC.	20F3
	775 TAYLOR CREEK DRIVE	PHONE (613) 226-875
	OTTAWA, ON, K4A 0Z9	FAX (613) 226-867
1701	CUSTOMER: GHD	REQUESTED BY: RYAN
Company town	LOCATION OF WORK: 2865 Du MAURIER AND	LIMITS OF WORK: AS PER MAP
	HYDRO H CABLE T.V T.	
	GAS G SANITARY -	ELECTRICAL -(ÆL-) COMMUNICATIONS COM
4	UNIDENTIFIED CABLE UC FIBER OPTIC FO	OC OTHER:
100	WATER W	BOVE - LOCATES VOID AFTER 30 DAYS!
Į	LOCATES ONLY APPLICABLE TO INFO P	SKETCH NOT TO SCAL
Take Service		C.B GRETOTING TO GOAL
Angeles IIS	^	
- Wasan	Ec.s	REFERENCE
		VORTH.
		1 1 2
i i	/	
	1	│
ı	DC.B	EL .
	2865 '	EL.
		17
6		
100		
		EL
	 USL-1 as a Private utility locator, is not permitted to locate Publicly owned FOR REFERENCE ONLY, and under no circumstances shall be used for experiments. 	utilities. In some cases, Public utilities may be noted on a sketch, but are
	Public utilities noted on the USL-1 sketch by referring to the Public utility is ASSUME LIABILITY FOR PUBLIC LOCATE INNACCURACIES.	poster sheets for physical LOCATION AND ACCURACY. USL-1 DOES NOT
100	If the proposed work area is on Private property, it does NOT mean that all the proposed depth of excavation is, it is the law to notify Ontario One Call	buried utilities are Private. Regardless of when you are digging, and what
	OMMENTS: NO OTHER PRIVATE UTILITIES	
	HIS SKETCH IS NOT A PUBLIC UTILITY LOCATE/DOCUMENT. PUB SL-1 DISCLAIMER - FORM 101. CONTRACTOR IS RESPONSIBLE	
C	OMMENCING WORK.	TO ENSURE THEY HAVE PUBLIC UTILITY LOCATES BEFORE
L	OCATORS NAME: CHRIS WHARTON S	SIGNATURE: (Mo
L	OCATE RECEIVED AND REVIEWED BY	Print Name Signature
	CAUTION: HAND DIG WITHIN	1.5 METERS OF MARKINGS
100-	ita - Citant Vellani - HOL 4 Dieli - HOL	

UNDERGROUND SERVICE	E LOCATORS - PRIV	ATE UTILITY REPOR	RT DATE: 10-04-2018	
ONE-CALL SYSTEMS INC	•		30F3	
775 TAYLOR CREEK DRIV	Æ			
OTTAWA, ON, K4A 0Z9				
CUSTOMER:	BHD			
LOCATION OF WORK: 2866	DU MAURIER ANT	LIMITS OF WORK: A	S PEL MAP	
HYDRO H	CABLE T.V T.	V STEAM	STEAM	
Cr to				
UNIDENTIFIED CABLE UC				
	DUCADI E TO INEO	POVE LOCATES VOI	D AFTER 30 DAVSI	
CUSTOMER: LOCATION OF WORK: BUS DV MANUEL AND LIMITS OF WORK: AS PEL MAP HYDRO - H - CABLE TV TV STEAM - STEAM				
	And the second s			
			// $(N)/$	
Д				
	<i>t</i> .	· \ \ .	NORTA	
			// / /	
	. 1	b //	/ / 1	
		- = 1 //		
		- t	4	
, , , , , , ,	1		8	
	1			
	† .			
	1	X = X	6.76	
		\	2	
		V	Ž	
20			2	
2865			2	
			A	
	**************************************	-		
USL-1 as a Private utility locator, is not	permitted to locate Publicly owner	utilities. In some cases, Public utilit	ies may be noted on a sketch, but are	
Public utilities noted on the USL-1 sketo	th by referring to the Public utility I	excavation purposes. It is the contra ocate sheets for physical LOCATION	ctor's responsibility to verify any NAND ACCURACY, USL-1 DOES NOT	
If the proposed work area is on Private;	property, it does NOT mean that a	ll buried utilities are Private. Regardi	ess of when you are digging, and what	
the proposed depth of excavation is, it is	s the law to notify Ontario One Cal	I (or Info-Excavation in Quebec) to o	btain Public utility locates.	
COMMENTS: NO OTHER	PRIVATE UTILITIE	ES DETECTED		
THIS SKETCH IS NOT A PUBLIC UTILIT	Ty locate/document. Pui	BLIC UTILITIES SHOWN ARE F	OR REFERENCE ONLY. REFER TO	
	TRACTOR IS RESPONSIBLE	TO ENSURE THEY HAVE PUB	BLIC UTILITY LOCATES BEFORE	
	YAP TON	SIGNATURE: (1)	1/2	
LOCATE RECEIVED AND REV	/IEWED BY —	Print Name	Signature	
CAUTION: HAN	D DIG WITHIN			
Affaita — Oliant Valleur — 130			FORMATO L COM	

USL-1 DISCLAIMER - FORM 101

- it is our Citoris responsibility to fully read and understand this document, prior to any ground disturbance taking place.
 Should any questions or clarifications be required, contact USL-1 before commencing work
- Locate is VOID after 30 days from the date the locate was completed. Contact USL-1 for remarks and/or new ticket requests, with a minimum notice of 5 business days.
- . If the scope of work, locate area, or site information changes, contact USL-1 before continuing work. In certain instances, a new ticket request may be required
- Any work within 1.5 metres intensity of a marked utility, must be hand dug or daylighted. Utility depths vary, as does the
 accuracy of the locate equipment, and therefore depths are typically not provided and should not be used for excavation
 purposes. Depth of utilities should also be verified by hand digging or daylighting. The best information is provided at the
 time of the locate, however the accuracy of field markings can vary with regard to equipment accuracy and external
 interference
- If the paint markings or flags on sits differ from that of the sketch provided, please contact USL-1 before commencing work. If possible, the issue will be clarified by USL-1 and/or a site meet may be requested with the appropriate parties
- work. If presently, are noted that the contract by court of the locates on site, with the operators and in/on the excevation equipment AT ALL TIMES
- It is the "Excevator/Contractor's" responsibility to read ALL locate sheets, both public and private, to ensure they
 understand what potential hezards or buried utilities exist in their work area
- Special purpose inostes such as sever condeling, loosie surveys, tunnel identification, conduit identification, ground fault
 detections, ground penetrating radar, well cap location, concrete scanning, or anything else that requires use of more than
 Radiodetection equipment, must be identified at the time of the original locate request. Should a USL-1 locator identify
 any special needs services during a normal Private utility locate, the client will be notified for the appropriate course of
- Not all buried utilities can be traced. In many instances, water and sewer lines, irrigation systems, grounding cables, fibre optic cables, heating cables, protection cables, and communication cables may not be traceable. Typically, sewer lines will be painted and lined up directionally from manhole to manhole where possible. It may not be possible to detect bends in the sewer lines between manholes. If tracer wires have been buried with the utility, they will be used to locate the buried utility where possible. If a buried utility cannot be traced, it will be noted on the USL-1 report. USL-1 is not liable for damage to untraceable utilities.
- Public utility locators have maps, plans and as-built diagrams for reference to work from. Private utility locators, for the most part, do not. USL-1 will attempt to locate any Private utilities on a site, using as-built plans provided to them. Building access is mandatory and must be arranged by our client. Any conduits or utilities noted entering or exiting a building will be traced if possible, as well as any other visible utilities observed on site, it is the responsibility of the contractor to provide any and all buried utility information and site contacts that they have. There is no guarantee that USL-1 can find all buried utilities if the property owner does not have records or information regarding their own buried utilities.
- USL-1 cannot be held liable for damage to Private water and/or sewer laterals unless building access is granted, and the utility is locatable.
- Thick snow and ice, frozen manhole lids, live traffic, parked care, construction debris and activities etc, are all factors that
 can interfere with USL-1's ability to perform Private utility locates. USL-1 cannot guaranty location of all buried utilities
 when such factors impede the locate process. It is the contractor's responsibility to ensure that the work areas are safe
 and accessible for locates, prior to USL-1's arrival to site
- USL-1 as a Private utility locator, is not permitted to locate Publicly owned utilities. In some cases, Public utilities may be
 noted on a sketch, but are FOR REFERENCE ONLY, and under no circumstances shall be used for excavation purposes.
 It is the contractor's responsibility to verify any Public utilities noted on the USL-1 sketch by referring to the Public utility
 locate sheets for physical LOCATION AND ACCURACY. USL-1 DOES NOT ASSUME LIABILTY FOR PUBLIC LOCATE
 INNACCURACIES
- If the proposed work area is on Private property, it does NOT mean that all buried utilities are Private. Regardless of where you are digging, and what the proposed depth of excavation is, it is the law to notify Ontario One Cali (or info-Excavation in Quebec) to obtain Public utility locates
- NCC PROPERTY assuming the contractor has been leaved a Land Access Permit from the NCC, it is typically indicated within the permit that it is the contractor's responsibility to contact NCC for utility locates of their buried utilities

USL-1 - January 2016

Appendix C

Borehole Logs

(GHD, 2019)

(Paterson, 2019)

REFERENCE No.: 11181273-A1 ENCLOSURE No.: BOREHOLE No.: BH3D / MW3D **BOREHOLE LOG ELEVATION:** 99.25 m Page: 1 of 1 **LEGEND** CLIENT: 3223701 Canada Inc. SS Split Spoon PROJECT: Geotechnical Investigation GS Auger Sample LOCATION: 2831, 2851, and 2865 DuMaurier Ave. ST Shelby Tube \blacksquare Water Level DESCRIBED BY: S. Wheeler CHECKED BY: L. Lopers 0 Water content (%) DATE (START): DATE (FINISH): 5 October 2018 5 October 2018 Atterberg limits (%) N Penetration Index based on MONITOR Split Spoon sample SCALE STRATIGRAPHY SAMPLE DATA WELL Penetration Index based on Dynamic Cone sample Stratigraphy Penetration Index / RQD Elevation (m) Shear Strength based on Field Vane Shear Strength based on Lab Vane Type and Number Recovery **DESCRIPTION OF** Depth □ Cu 000 Sensitivity Value of Soil BĠS SOIL AND BEDROCK Shear Strength based on Pocket Penetrometer SCALE FOR TEST RESULTS 50kPa 100kPa 150kPa 200kPa 20 30 40 50 60 70 80 meters 99.25 **GROUND SURFACE** % Ν ppm **TOPSOIL** 99.2 99.15 FILL - Gravelly silty sand, 99.0 Sand-SS1 46 25 brown, damp, compact 2.8 FILL - Sandy gravel, brown, 0.46 0.5 damp, compact SS2 50 3.0 19 1.0 98.0 Riser FILL - Silty sand, grey, moist WL 1.37 to wet, very loose to loose 10/15/2018 1.5 Black staining encountered SS3 71 3.9 10 2.0 SS4 13 2.8 2 **Rentonite** 96.8 2.5 PEAT - black, organics and 14 14 organic odour, wet, very loose 11 14 SS5 75 РΗ 0 10 10 40 40 4 3.0 11/11/11 40 40 4 40 40 4 SS₆ 83 0 3 Auger refusal encountered at 3.5 40 40 3.7 mbgs 95.6 **HIGHLY WEATHERED AND** =111 FRACTURED LIMESTONE-=111 grey 4.0 SOL.GDT RC1 90 0 11181273-A1-BOREHOLE LOGS.GPJ INSPEC 94.8 4.5 LIMESTONE- grey, poor quality Screen-RC2 100 35 5.0 93.9 5.36 -End of borehole 5.5 6.0 **BOREHOLE LOG** mbgs: meters below ground surface

BOREHOLE No.: BH3S / MW3S **BOREHOLE LOG ELEVATION:** 99.33 m Page: _1_ of _1_ **LEGEND** CLIENT: 3223701 Canada Inc. SS Split Spoon PROJECT: Geotechnical Investigation GS Auger Sample LOCATION: 2831, 2851, and 2865 DuMaurier Ave. ST Shelby Tube Ţ Water Level DESCRIBED BY: S. Wheeler CHECKED BY: L. Lopers 0 Water content (%) DATE (FINISH): __ DATE (START): 5 October 2018 5 October 2018 Atterberg limits (%) N Penetration Index based on MONITOR Split Spoon sample SCALE STRATIGRAPHY SAMPLE DATA WELL Penetration Index based on Dynamic Cone sample Stratigraphy Penetration Index / RQD Elevation (m) Shear Strength based on Field Vane Shear Strength based on Lab Vane Type and Number Recovery **DESCRIPTION OF** □ Cu Depth 000 Sensitivity Value of Soil BĠS SOIL AND BEDROCK Shear Strength based on Pocket Penetrometer SCALE FOR TEST RESULTS 50kPa 100kPa 150kPa 200kPa 20 30 40 50 60 70 80 meters 99.33 **GROUND SURFACE** % ppm Ν 99.23 Sand 0.46 0.5 Riser-1.0 Bentonite -WL 1.26 10/15/2018 1.5 1.83 -2.0 Sand-2.19 -2.5 Screen -3.0 3.5 95.6 371-BOREHOLE LOG 11181273-A1-BOREHOLE LOGS.GPJ INSPEC_SOL.GDT 8/11/18 Augered to practical refusal at 3.7 mbgs for direct well installation in overburden 4.0 4.5 5.0 5.5 - 6.0 mbgs: meters below ground surface

REFERENCE No.:

11181273-A1

ENCLOSURE No.:

SOIL PROFILE AND TEST DATA

Geotechnical Investigation 2829 Dumaurier Avenue Ottawa, Ontario

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

TBM - Top spindle of fire hydrant located at the northeast corner of subject site. Geodetic elevation = 74.952m.

FILE NO.

HOLE NO.

PG4928

REMARKS

DATUM

BORINGS BY CME 55 Power Auger			SAM	1PLE			Pen. Resist. Blows/0.3m	
SOIL DESCRIPTION	A PLOT			<u> </u>	Ħ O	DEPTH (m)	ELEV. (m)	• 50 mm Dia. Cone
	STRATA	TYPE	NUMBER	% RECOVERY	N VALUE or RQD			Pen. Resist. Blows/0.3m
GROUND SURFACE	٥.			2	z º	0-	-74.80	20 40 60 80
TOPSOIL 0.18 FILL: Brown clayey silt, some sand and gravel 0.86		& AU	1				7 1.00	
ILL: Brown silty sand		ss	2	42	7	1 -	-73.80	
ILL: Brown sand, trace gravel		ss	3	62	5	2-	-72.80	
2.90		ss	4	8	3	3-	-71.80	
oose, brown FINE SAND with silty lay		ss	5	75	5		7 1.00	
LACIAL TILL: Dense, brown silty	· · · · · · · · · · · · · · · · · · ·	ss	6	92	35	4-	-70.80	
and with gravel, clay and shale agments		∑ ss -	7	78	50+	5-	-69.80	
		RC -	1	100	67	6-	-68.80	
EEDROCK: Fair to excellent quality, reen shale interbedded with olomite		RC	2	93	88	7-	-67.80	
oioniile		RC	3	100	84	8-	-66.80	
		_				9-	-65.80	
		RC	4	97	92	10-	-64.80	20 40 60 80 10

SOIL PROFILE AND TEST DATA

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

Geotechnical Investigation 2829 Dumaurier Avenue Ottawa, Ontario

DATUM

TBM - Top spindle of fire hydrant located at the northeast corner of subject site. Geodetic elevation = 74.952m.

REMARKS

PG4928

FILE NO.

HOLE NO.

BORINGS BY CME 55 Power Auger					ATE	2019 Nov	ember 1	1 BH 1
SOIL DESCRIPTION		SAMPLE				DEPTH	ELEV.	Pen. Resist. Blows/0.3m ■ 50 mm Dia. Cone
GROUND SURFACE	STRATA P	TYPE	NUMBER	% RECOVERY	N VALUE or RQD	(m)	(m)	Pen. Resist. Blows/0.3m ■ 50 mm Dia. Cone ○ Water Content % 20 40 60 80
CHOOND CONTACE						10-	-64.80	<u> </u>
BEDROCK: Fair to excellent		RC	5	97	92	11-	-63.80	
quality, green shale interbedded with dolomite		_				12-	-62.80	
13.5	1	RC	6	100	98	13-	-61.80	
		RC	7	100	93	14-	-60.80	
BEDROCK: Good excellent quality,		_				15-	-59.80	
grey dolostone		RC	8	92	74	16-	-58.80	
						17-	-57.80	
1 <u>8.1</u> End of Borehole	9	RC	9	95	85	18-	-56.80	
(GWL @ 7.12m - Nov. 20, 2019)								
								20 40 60 80 100 Shear Strength (kPa) ▲ Undisturbed △ Remoulded

SOIL PROFILE AND TEST DATA

Geotechnical Investigation 2829 Dumaurier Avenue Ottawa, Ontario

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

TBM - Top spindle of fire hydrant located at the northeast corner of subject site.

DATUM Geodetic elevation = 74.952m. FILE NO. **PG4928**

REMARKS

BORINGS BY CME 55 Power Auger				D	ATE 2	2019 Nov	ember 1	1	HOL	E NO.	BH 2	2	
SOIL DESCRIPTION	PLOT		SAN	/IPLE		DEPTH (m)	ELEV.	Pen. R ● 5		_	ws/0.3 Cone		g Well
	STRATA	TYPE	NUMBER	% RECOVERY	N VALUE or RQD	(,	()	0 V	/ater	Cont	ent %		Monitoring Well
GROUND SURFACE	ω		Z	E E	z °	_	70.00	20	40	60	80)	Σď
Asphaltic concrete 0.08 FILL: Brown sand with gravel, 0.33 \crushed stone		& AU	1			0-	-73.38						
FILL: Brown silty sand, trace clay		ss	2	25	15	1 -	-72.38						
PEAT 2.03		ss	3	62	4	2-	-71.38						
Loose, grey FINE SAND with silt and clay		ss	4	62	6								
Grey SILTY CLAY , trace sand		ss	5	75	2	3-	-70.38					-2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2	
4.37		∑ss	6	0	50+	4-	-69.38						
		= RC RC	1	100	100	5-	-68.38						
BEDROCK: Excellent quality, green		_				6-	-67.38						
shale interbedded with dolostone		RC	3	98	89	7-	-66.38						
		RC	4	100	97	8-	-65.38						
		_				9-	-64.38						
		RC	5	100	100	10-	-63.38	20 Shea	40 ar Str	60 ength	80 n (kPa) 1	00

2829 Dumaurier Avenue

11 + 62.38

Geotechnical Investigation Ottawa, Ontario

SOIL PROFILE AND TEST DATA

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

TBM - Top spindle of fire hydrant located at the northeast corner of subject site. FILE NO. **DATUM** Geodetic elevation = 74.952m. **PG4928 REMARKS** HOLE NO. **BH 2** BORINGS BY CME 55 Power Auger DATE 2019 November 11 Pen. Resist. Blows/0.3m **SAMPLE** Monitoring Well Construction STRATA PLOT **DEPTH** ELEV. **SOIL DESCRIPTION** 50 mm Dia. Cone (m) (m) N VALUE or RQD RECOVERY NUMBER Water Content % **GROUND SURFACE** 80 20 10+63.38

RC 6 85 80 **BEDROCK:** Excellent quality, green shale interbedded with dolostone 12 + 61.38

RC 7 100 95 13+60.3813.49 14 + 59.38RC 8 95 88

15 + 58.38**BEDROCK:** Good to excellent quality, grey dolostone RC 9 100 98 16 + 57.38

17 + 56.38RC 10 98 98 18 + 55.38End of Borehole

(GWL @ 5.75m - Nov. 20, 2019) 40 60 80 100 Shear Strength (kPa) ▲ Undisturbed △ Remoulded

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

SOIL PROFILE AND TEST DATA

Geotechnical Investigation 2829 Dumaurier Avenue Ottawa, Ontario

DATUM

TBM - Top spindle of fire hydrant located at the northeast corner of subject site. Geodetic elevation = 74.952m.

FILE NO.

PG4928

REMARKS

BORINGS BY CME 55 Power Auger				D	ATE 2	2019 Nov	ember 1	1	HOLE	E NO.	BH 3		
SOIL DESCRIPTION	PLOT		SAN	/IPLE		DEPTH	ELEV.	Pen. R		Blow Dia. (Well) uc
	STRATA E	TYPE	NUMBER	% RECOVERY	N VALUE or RQD	(m)	(m)	O Water Content %				Construction	
GROUND SURFACE	\.; \.; \.	×		A	-	0-	73.56	20	40	60	80	2	$\overline{}$
Asphaltic concrete 0.08 FILL: Brown sand with gravel 0.28 FILL: Brown silty clay, trace sand 0.76		AU	1										
FILL: Dark brown silt, some sand 0.97		ss	2	50	4	1-	-72.56						
FILL: Grey-brown silty clay, some organics, trace sand		ss	3	0	3	2-	71.56						
3.05		ss	4	62	1	3-	-70.56						
GLACIAL TILL: Grey sandy silt, some clay and gravel	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ss	5	83	Р			Δ					
<u>3</u> . <u>8</u> 6	1,^^^^	≖ SS	6	100	50+	1	-69.56						
		RC -	1	100	88	4-	-69.56						
		RC	2	96	88	5-	-68.56						
BEDROCK: Good quality, green shale interbedded with dolostone		_				6-	-67.56						7 11 11 11 11 11 11 11 11 11 11 11 11 11
		RC =	3	98	93	7-	-66.56						E
		RC	4	100	100	8-	-65.56						
		=				9-	-64.56						
		RC	5	98	88	10-	-63.56	20 Shea	40 or Stre	60 enath	80 (kPa)	100	
								▲ Undist			emoulde	d	

SOIL PROFILE AND TEST DATA Geotechnical Investigation

2829 Dumaurier Avenue Ottawa, Ontario

154 Colonnade Road South, Ottawa, Ontario K2E 7J5

TBM - Top spindle of fire hydrant located at the northeast corner of subject site. Geodetic elevation = 74.952m.

FILE NO. **PG4928**

REMARKS

DATUM

HOLE NO.

BORINGS BY CME 55 Power Auger				D	ATE 2	2019 Nov	ember 1	1	HOLE	. NO. E	3H 3	
SOIL DESCRIPTION	PLOT		SAN	IPLE	ı	DEPTH	ELEV.	Pen. Re		Blows		Well
GROUND SURFACE	STRATA 1	TYPE	NUMBER	% RECOVERY	N VALUE or RQD	(m)	(m)					Monitoring Well
BEDROCK: Good quality, green shale interbedded with dolostone		- -		00	0.1		-63.56 -62.56					
12.20		RC	6	98	81	12-	-61.56					
		RC	7	90	57	13-	-60.56					
BEDROCK: Fair to excellent quality,		RC	8	100	92	14-	-59.56					
grey dolostone		- RC	9	95	95	15-	-58.56					
		-					-57.56					
10.11		RC	10	97	97		-56.56 -55.56					
End of Borehole		-				10	-33.30					
(GWL @ 5.94m - Nov. 20, 2019)								20 Sheai ▲ Undistu		60 ngth (△ Re	80 kPa) moulded	100

Appendix D

Certificates of Equipment Calibration



ENVIRONMENTAL AND SAFETY INC.

"Exceptional Customer Service!"

Certificate of Calibration

HORIBA U-52 Serial Number SGR2KAPX has been calibrated per the Manufacturers published instructions, using NIST traceable solutions and standards.

2, 2-Point pH	Cond.	Turb,	DO	ORP
4.00, 7.00	4.49 uS/cm	0, 100 NTU	8.91 mg/L @ 21 DegC	240mV
pH 4.0 Lot #0GK004 Exp11/22	Zero checked	Zero checked	Sodium Sulfite Zero	
pH 7.0 Lot# 0GE815 Exp.05/2022	Cond.Standard Lot#1GC833 Exp. 03/2022	StableCal Standard, 100 NTU Lot#A1007 Exp.01/2023	Oakton Zero Oxygen Solution Lot# 670227 Exp.03/2021	ORP Test Solution 240 mV
	Soluti	ions ref. to NIST SRM's		Lot # Lot #5235Exp 04/2025
May 1-2021	4,		Jell L	

RENTALS, SALES, SERVICE, SUPPORT

9 - 170 AMBASSADOR DR., MISSISSAUGA, ONTARIO L5T 2H9 PHONE: (905) 670-1304 TOLL FREE: (888) 285-2324 E-MAIL: SALES@MAXIMENVIRONMENTAL.COM 9 - 148 COLONNADE RD., OTTAWA, ONTARIO K2E 7R4 PHONE: (613) 224-4747 TOLL FREE: (888) 285-2324 E-MAIL: SALES@MAXIMENVIRONMENTAL.COM

Appendix E

Laboratory Certificates of Analysis

(Lopers, 2021 Groundwater)

(GHD, 2018 Groundwater)

(GHD, 2018 Soil)



CLIENT NAME: LOPERS & ASSOCIATES 30 LANSFIELD WAY OTTAWA, ON K2G 3V8 613-327-9073

ATTENTION TO: Luke Lopers

AGAT WORK ORDER: 21Z747835

TRACE ORGANICS REVIEWED BY: Neli Popnikolova, Senior Chemist WATER ANALYSIS REVIEWED BY: Amanjot Bhela, Inorganic Lab Manager

PROJECT: LOP21-004B

DATE REPORTED: May 25, 2021

PAGES (INCLUDING COVER): 16 VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

Notes	

Disclaimer:

- All work conducted herein has been done using accepted standard protocols, and generally accepted practices and methods. AGAT test methods may
 incorporate modifications from the specified reference methods to improve performance.
- All samples will be disposed of within 30 days after receipt unless a Long Term Storage Agreement is signed and returned. Some specialty analysis may
 be exempt, please contact your Client Project Manager for details.
- AGAT's liability in connection with any delay, performance or non-performance of these services is only to the Client and does not extend to any other
 third party. Unless expressly agreed otherwise in writing, AGAT's liability is limited to the actual cost of the specific analysis or analyses included in the
 services.
- This Certificate shall not be reproduced except in full, without the written approval of the laboratory.
- The test results reported herewith relate only to the samples as received by the laboratory.
- Application of guidelines is provided "as is" without warranty of any kind, either expressed or implied, including, but not limited to, warranties of
 merchantability, fitness for a particular purpose, or non-infringement. AGAT assumes no responsibility for any errors or omissions in the guidelines
 contained in this document.
- All reportable information as specified by ISO/IEC 17025:2017 is available from AGAT Laboratories upon request.

AGAT Laboratories (V1)

Page 1 of 16

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. Measurement Uncertainty is not taken into consideration when stating conformity with a specified requirement.



AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

SAMPLING SITE: Dumaurier

ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

O. Reg.	153((511)) - PAHs ((Water)

DATE RECEIVED: 2021-05-17								DATE REPORTED: 2021-05-25
		SAMPLE DESC SAMP	RIPTION: PLE TYPE:	BH1-GW1 Water	MW95-1 Water	MW95-2 Water	Dup-1 Water	
_			AMPLED:	2021-05-17	2021-05-17	2021-05-17	2021-05-17	
Parameter	Unit	G/S	RDL	2478945	2478991	2478992	2478993	
Naphthalene	μg/L	1400	0.20	<0.20	<0.20	<0.20	<0.20	
Acenaphthylene	μg/L	1.8	0.20	<0.20	<0.20	<0.20	<0.20	
Acenaphthene	μg/L	600	0.20	<0.20	<0.20	<0.20	<0.20	
Fluorene	μg/L	400	0.20	<0.20	<0.20	<0.20	<0.20	
Phenanthrene	μg/L	580	0.10	<0.10	<0.10	<0.10	<0.10	
Anthracene	μg/L	2.4	0.10	<0.10	<0.10	<0.10	<0.10	
Fluoranthene	μg/L	130	0.20	<0.20	<0.20	<0.20	<0.20	
Pyrene	μg/L	68	0.20	<0.20	<0.20	<0.20	<0.20	
Benzo(a)anthracene	μg/L	4.7	0.20	<0.20	<0.20	<0.20	<0.20	
Chrysene	μg/L	1	0.10	<0.10	<0.10	<0.10	<0.10	
Benzo(b)fluoranthene	μg/L	0.75	0.10	<0.10	<0.10	<0.10	<0.10	
Benzo(k)fluoranthene	μg/L	0.4	0.10	<0.10	<0.10	<0.10	<0.10	
Benzo(a)pyrene	μg/L	0.81	0.01	<0.01	<0.01	<0.01	<0.01	
Indeno(1,2,3-cd)pyrene	μg/L	0.2	0.20	<0.20	<0.20	<0.20	<0.20	
Dibenz(a,h)anthracene	μg/L	0.52	0.20	<0.20	<0.20	<0.20	<0.20	
Benzo(g,h,i)perylene	μg/L	0.2	0.20	<0.20	<0.20	<0.20	<0.20	
2-and 1-methyl Naphthalene	μg/L	1800	0.20	<0.20	<0.20	<0.20	<0.20	
Sediment				No	No	No	No	
Surrogate	Unit	Acceptabl	e Limits					
Naphthalene-d8	%	50-1	40	107	100	100	98	
Acridine-d9	%	50-1	40	113	86	73	120	
Terphenyl-d14	%	50-1	40	71	71	89	68	

Comments:

RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to Table 3: Full Depth Generic Site Condition Standards in a Non-Potable Ground Water Condition - Non-Potable Ground Water - All Types of Property Uses - Coarse Textured Soils

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

2478945-2478993 Note: The result for Benzo(b)Fluoranthene is the total of the Benzo(b)&(j)Fluoranthene isomers because the isomers co-elute on the GC column.

2- and 1-Methyl Naphthalene is a calculated parameter. The calculated value is the sum of 2-Methyl Naphthalene and 1-Methyl Naphthalene. The calculated parameter is non-accredited. The parameters that are components of the calculation are accredited.

Sediment parameter is comment only based on visual inspection of the sample prior to extraction and is not an accredited test.

Analysis perfored at AGAT Toronto (unless marked by *)



AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

SAMPLING SITE: Dumaurier

ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

O. Reg. 153(511) - PHCs F1 - F4 (with PAHs and VOC) (Water)

							DATE REPORTED: 2021-05-25
S	SAMPLE DESCI	RIPTION:	BH1-GW1	MW95-1	MW95-2	Dup-1	
	SAMPL	E TYPE:	Water	Water	Water	Water	
	DATE SA	MPLED:	2021-05-17	2021-05-17	2021-05-17	2021-05-17	
Unit	G/S	RDL	2478945	2478991	2478992	2478993	
μg/L	750	25	<25	<25	<25	<25	
μg/L	750	25	<25	<25	<25	<25	
μg/L	150	100	<100	<100	<100	<100	
μg/L		100	<100	<100	<100	<100	
μg/L	500	100	<100	<100	<100	<100	
μg/L		100	<100	<100	<100	<100	
μg/L	500	100	<100	<100	<100	<100	
μg/L		500	NA	NA	NA	NA	
			No	No	No	No	
Unit	Acceptable	Limits					
% Recovery	50-14	0	78	105	104	87	
% Recovery	60-14	0	93	94	80	87	
	Unit µg/L µg/L µg/L µg/L µg/L µg/L µg/L µg/	SAMPL DATE SA DATE	μg/L 750 25 μg/L 750 25 μg/L 150 100 μg/L 100 100 μg/L 500 100	SAMPLE TYPE: Water DATE SAMPLED: 2021-05-17 Unit G/S RDL 2478945 μg/L 750 25 <25	SAMPLE TYPE: Water Water DATE SAMPLED: 2021-05-17 2021-05-17 2021-05-17 Unit G / S RDL 2478945 2478991 μg/L 750 25 <25 <25 μg/L 150 100 <100 <100 μg/L 500 NA NA NA μg/L 500 NA NA NA No No No Unit Acceptable Limits	SAMPLE TYPE: Water Water Water DATE SAMPLED: 2021-05-17 2021-05-17 2021-05-17 Unit G/S RDL 2478945 2478991 2478992 μg/L 750 25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25 <25	SAMPLE TYPE: Water DATE SAMPLED: Water 2021-05-17 2021-05-17 2021-05-17 2021-05-17 2021-05-17 2021-05-17 Water 2021-05-17

Comments:

RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to Table 3: Full Depth Generic Site Condition Standards in a Non-Potable Ground Water Condition - Non-Potable Ground Water - All Types of Property Uses - Coarse Textured Soils

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

2478945-2478993 The C6-C10 fraction is calculated using toluene response factor.

C6-C10 (F1 minus BTEX) is a calculated parameter. The calculated value is F1 minus BTEX. The calculated parameter is non-accredited. The parameters that are components of the calculation are

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16-C50 and are only determined if the chromatogram of the C34 - C50 hydrocarbons indicates that hydrocarbons >C50 are present. The chromatogram has returned to baseline by the retention time of nC50.

Total C6 - C50 results are corrected for BTEX and PAH contributions.

C>10 - C16 (F2- Naphthalene) is a calculated parameter. The calculated value is F2 - Naphthalene.

C>16 - C34 (F3-PAH) is a calculated parameter. The calculated value is F3-PAH (PAH: sum of Phenanthrene, Benzo(a)anthracene, Benzo(b)fluoranthene, Benzo(k)fluoranthene, Benzo(a)pyrene, Fluoranthene, Dibenzo(a,h)anthracene, Indeno(1,2,3-c,d)pyrene and Pyrene).

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 + nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Sediment parameter is comment only based on visual inspection of the sample prior to extraction and is not an accredited test.

Analysis perfomed at AGAT Toronto (unless marked by *)





AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

SAMPLING SITE: Dumaurier

ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

O. Reg.	. 153(5	11) - VOCs	(Water)
---------	---------	------------	---------

DATE RECEIVED: 2021-05-17									DATE REPORTED: 2021-05-25
			RIPTION: LE TYPE: AMPLED:	BH1-GW1 Water 2021-05-17	MW95-1 Water 2021-05-17	MW95-2 Water 2021-05-17	Dup-1 Water 2021-05-17	Trip Blank Water	
Parameter	Unit	G/S	RDL	2478945	2478991	2478992	2478993	2478995	
Dichlorodifluoromethane	μg/L	4400	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Vinyl Chloride	μg/L	0.5	0.17	<0.17	<0.17	<0.17	<0.17	<0.17	
Bromomethane	μg/L	5.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Trichlorofluoromethane	μg/L	2500	0.40	< 0.40	< 0.40	< 0.40	< 0.40	< 0.40	
Acetone	μg/L	130000	1.0	<1.0	<1.0	<1.0	<1.0	<1.0	
1,1-Dichloroethylene	μg/L	1.6	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	
Methylene Chloride	μg/L	610	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	
trans- 1,2-Dichloroethylene	μg/L	1.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Methyl tert-butyl ether	μg/L	190	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
1,1-Dichloroethane	μg/L	320	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	
Methyl Ethyl Ketone	μg/L	470000	1.0	<1.0	<1.0	<1.0	<1.0	<1.0	
cis- 1,2-Dichloroethylene	μg/L	1.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Chloroform	μg/L	2.4	0.20	<0.20	<0.20	23.9	<0.20	<0.20	
1,2-Dichloroethane	μg/L	1.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
1,1,1-Trichloroethane	μg/L	640	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	
Carbon Tetrachloride	μg/L	0.79	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Benzene	μg/L	44	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
1,2-Dichloropropane	μg/L	16	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Trichloroethylene	μg/L	1.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Bromodichloromethane	μg/L	85000	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Methyl Isobutyl Ketone	μg/L	140000	1.0	<1.0	<1.0	<1.0	<1.0	<1.0	
1,1,2-Trichloroethane	μg/L	4.7	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Toluene	μg/L	18000	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Dibromochloromethane	μg/L	82000	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Ethylene Dibromide	μg/L	0.25	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Tetrachloroethylene	μg/L	1.6	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
1,1,1,2-Tetrachloroethane	μg/L	3.3	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Chlorobenzene	μg/L	630	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Ethylbenzene	μg/L	2300	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
m & p-Xylene	μg/L		0.20	<0.20	<0.20	<0.20	<0.20	<0.20	





AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

SAMPLING SITE:Dumaurier

ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

O. Reg. 153(511) - VOCs (Water)

DATE RECEIVED: 2021-05-17									DATE REPORTED: 2021-05-25
	S	AMPLE DESC SAMF	CRIPTION: PLE TYPE:	BH1-GW1 Water	MW95-1 Water	MW95-2 Water	Dup-1 Water	Trip Blank Water	
Parameter	Unit	DATE S G/S	RDL	2021-05-17 2478945	2021-05-17 2478991	2021-05-17 2478992	2021-05-17 2478993	2478995	
Bromoform	μg/L	380	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Styrene	μg/L	1300	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
1,1,2,2-Tetrachloroethane	μg/L	3.2	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
o-Xylene	μg/L		0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
1,3-Dichlorobenzene	μg/L	9600	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
1,4-Dichlorobenzene	μg/L	8	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
1,2-Dichlorobenzene	μg/L	4600	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
1,3-Dichloropropene	μg/L	5.2	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	
Xylenes (Total)	μg/L	4200	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
n-Hexane	μg/L	51	0.20	<0.20	<0.20	<0.20	<0.20	<0.20	
Surrogate	Unit	Acceptab	le Limits						
Toluene-d8	% Recovery	50-1	40	86	85	89	84	89	
4-Bromofluorobenzene	% Recovery	50-1	40	100	104	92	105	95	

Comments:

RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to Table 3: Full Depth Generic Site Condition Standards in a Non-Potable Ground Water Condition - Non-Potable Ground Water - All Types of Property Uses - Coarse Textured Soils

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

2478945-2478995 Xylenes total is a calculated parameter. The calculated value is the sum of m&p-Xylene and o-Xylene.

1,3-Dichloropropene total is a calculated parameter. The calculated value is the sum of Cis-1,3-Dichloropropene and Trans-1,3-Dichloropropene.

The calculated parameter is non-accredited. The parameters that are components of the calculation are accredited.

Analysis perfored at AGAT Toronto (unless marked by *)

Certified By:

NPoprikolof



SAMPLING SITE: Dumaurier

Certificate of Analysis

AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

O. Reg. 153(511) - Metals & Inorganics (Water)

DATE RECEIVED: 2021-05-17								D	DATE REPORTED: 2021-05-25			
	٤		CRIPTION: PLE TYPE: SAMPLED:	BH1-GW1 Water 2021-05-17		MW95-1 Water 2021-05-17		MW95-2 Water 2021-05-17		Dup-1 Water 2021-05-17		
Parameter	Unit	G/S	RDL	2478945	RDL	2478991	RDL	2478992	RDL	2478993		
Dissolved Antimony	μg/L	20000	1.0	<1.0	1.0	<1.0	1.0	<1.0	1.0	<1.0		
Dissolved Arsenic	μg/L	1900	1.0	1.8	1.0	5.1	1.0	4.6	1.0	6.6		
Dissolved Barium	μg/L	29000	2.0	102	20.0	1130	2.0	227	20.0	1110		
Dissolved Beryllium	μg/L	67	0.50	<0.50	0.50	<0.50	0.50	<0.50	0.50	<0.50		
Dissolved Boron	μg/L	45000	10.0	278	10.0	24.3	10.0	16.4	10.0	24.8		
Dissolved Cadmium	μg/L	2.7	0.20	<0.20	0.20	<0.20	0.20	0.28	0.20	<0.20		
Dissolved Chromium	μg/L	810	2.0	<2.0	2.0	<2.0	2.0	<2.0	2.0	<2.0		
Dissolved Cobalt	μg/L	66	0.50	<0.50	0.50	<0.50	0.50	< 0.50	0.50	<0.50		
Dissolved Copper	μg/L	87	1.0	<1.0	1.0	<1.0	1.0	<1.0	1.0	<1.0		
Dissolved Lead	μg/L	25	0.50	<0.50	0.50	0.62	0.50	<0.50	0.50	0.53		
Dissolved Molybdenum	μg/L	9200	0.50	0.73	0.50	<0.50	0.50	<0.50	0.50	<0.50		
Dissolved Nickel	μg/L	490	3.0	<3.0	3.0	<3.0	3.0	<3.0	3.0	<3.0		
Dissolved Selenium	μg/L	63	1.0	<1.0	1.0	<1.0	1.0	1.4	1.0	<1.0		
Dissolved Silver	μg/L	1.5	0.20	<0.20	0.20	<0.20	0.20	<0.20	0.20	<0.20		
Dissolved Thallium	μg/L	510	0.30	< 0.30	0.30	< 0.30	0.30	< 0.30	0.30	<0.30		
Dissolved Uranium	μg/L	420	0.50	1.00	0.50	<0.50	0.50	1.38	0.50	<0.50		
Dissolved Vanadium	μg/L	250	0.40	<0.40	0.40	0.48	0.40	< 0.40	0.40	0.47		
Dissolved Zinc	μg/L	1100	5.0	<5.0	5.0	<5.0	5.0	15.7	5.0	66.3		
Mercury	μg/L	0.29	0.02	< 0.02	0.02	< 0.02	0.02	< 0.02	0.02	<0.02		
Chromium VI	μg/L	140	2.000	<2.000	2.000	<2.000	2.000	<2.000	2.000	<2.000		
Cyanide, Free	μg/L	66	2	<2	2	<2	2	<2	2	<2		
Dissolved Sodium	μg/L	2300000	50	84400	250	292000	250	132000	250	291000		
Chloride	μg/L	2300000	100	83100	100	925000	100	316000	100	928000		
Electrical Conductivity	uS/cm	NA	2	768	2	3340	2	1540	2	3290		
рН	pH Units		NA	7.78	NA	7.43	NA	7.75	NA	7.48		





AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

SAMPLING SITE:Dumaurier

ATTENTION TO: Luke Lopers
SAMPLED BY:Luke Lopers

O. Reg. 153(511) - Metals & Inorganics (Water)

DATE RECEIVED: 2021-05-17 DATE REPORTED: 2021-05-25

Comments:

RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to Table 3: Full Depth Generic Site Condition Standards in a Non-Potable Ground Water Condition - Non-Potable Ground Water - All

Types of Property Uses - Coarse Textured Soils

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

2478945-2478993 Metals analysis completed on a filtered sample.

Dilution required, RDL has been increased accordingly.

Analysis perfored at AGAT Toronto (unless marked by *)

Amanjot Sheld & AMANJOT BHELD O CHEMIST ON THE STATE OF T



Exceedance Summary

AGAT WORK ORDER: 21Z747835

PROJECT: LOP21-004B

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: LOPERS & ASSOCIATES

ATTENTION TO: Luke Lopers

SAMPLEID	SAMPLE TITLE	GUIDELINE	ANALYSIS PACKAGE	PARAMETER	UNIT	GUIDEVALUE	RESULT
2478992	MW95-2	ON T3 NPGW CT	O. Reg. 153(511) - VOCs (Water)	Chloroform	μg/L	2.4	23.9

Quality Assurance

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B
SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835
ATTENTION TO: Luke Lopers
SAMPLED BY:Luke Lopers

			Trac	e Or	ganio	cs Ar	nalys	is							
RPT Date: May 25, 2021 DUPLICATE				REFERENCE MATERIAL			METHOD BLANK SPIKE			MAT	MATRIX SPIR				
DADAMETER		Sample	5 "4			Method Blank	Measured	Acceptable Limits		_	Acceptable Limits			Acceptable Limits	
PARAMETER	Batch	ld [.]	Dup #1	Dup #2	RPD		Value	Lower Upper	Recovery	Lower		Recovery	Lower	_	
O. Reg. 153(511) - PHCs F1 - F		and VOC)	(Water)				I				1				
F1 (C6-C10)	2475061		<25	<25	NA	< 25	102%	60%	140%	104%	60%	140%	107%	60%	140%
F2 (C10 to C16)	2479694		630	570	10.0%	< 100	110%	60%	140%	84%	60%	140%	84%	60%	140%
F3 (C16 to C34)	2479694		550	520	5.6%	< 100	100%	60%	140%	91%	60%	140%	81%	60%	140%
F4 (C34 to C50)	2479694		< 100	< 100	NA	< 100	101%	60%	140%	88%	60%	140%	84%	60%	140%
O. Reg. 153(511) - PHCs F1 - F		and VOC)	(Water)												
F2 (C10 to C16)	2490692		< 100	< 100	NA	< 100	112%	60%	140%	96%	60%	140%	61%	60%	140%
F3 (C16 to C34)	2490692		< 100	< 100	NA	< 100	106%	60%	140%	80%	60%	140%	64%	60%	140%
F4 (C34 to C50)	2490692		< 100	< 100	NA	< 100	86%	60%	140%	98%	60%	140%	95%	60%	
O Bog 152/511) BAHo (Wate	ne)														
O. Reg. 153(511) - PAHs (Water Naphthalene	2485371		<0.20	<0.20	NΙΔ	< 0.20	96%	50%	140%	102%	50%	140%	98%	50%	140%
Acenaphthylene					NA										
. ,	2485371		<0.20 <0.20	<0.20	NA NA	< 0.20	99% 92%	50% 50%	140% 140%	114% 96%	50% 50%	140%	101% 87%	50%	
Acenaphthene	2485371			<0.20	NA NA	< 0.20						140%		50%	
Fluorene	2485371		<0.20	<0.20	NA	< 0.20	100%	50%	140%	105%	50%	140%	93%	50%	140%
Phenanthrene	2485371		<0.10	<0.10	NA	< 0.10	97%	50%	140%	106%	50%	140%	93%	50%	140%
Anthracene	2485371		<0.10	<0.10	NA	< 0.10	99%	50%	140%	99%	50%	140%	91%	50%	140%
Fluoranthene	2485371		<0.20	<0.20	NA	< 0.20	101%	50%	140%	95%	50%	140%	97%	50%	140%
Pyrene	2485371		<0.20	<0.20	NA	< 0.20	100%	50%	140%	110%	50%	140%	97%	50%	140%
Benzo(a)anthracene	2485371		<0.20	<0.20	NA	< 0.20	79%	50%	140%	111%	50%	140%	83%	50%	140%
Chrysene	2485371		<0.10	<0.10	NA	< 0.10	106%	50%	140%	114%	50%	140%	99%	50%	140%
Benzo(b)fluoranthene	2485371		<0.10	<0.10	NA	< 0.10	121%	50%	140%	110%	50%	140%	98%	50%	140%
Benzo(k)fluoranthene	2485371		<0.10	<0.10	NA	< 0.10	112%	50%	140%	98%	50%	140%	87%	50%	140%
Benzo(a)pyrene	2485371		<0.01	<0.01	NA	< 0.01	128%	50%	140%	91%	50%	140%	94%	50%	140%
Indeno(1,2,3-cd)pyrene	2485371		<0.20	<0.20	NA	< 0.20	87%	50%	140%	82%	50%	140%	75%	50%	140%
Dibenz(a,h)anthracene	2485371		<0.20	<0.20	NA	< 0.20	77%	50%	140%	96%	50%	140%	83%	50%	140%
Benzo(g,h,i)perylene	2485371		<0.20	<0.20	NA	< 0.20	83%	50%	140%	84%	50%	140%	80%	50%	140%
O. Reg. 153(511) - VOCs (Wate	er)														
Dichlorodifluoromethane	2477800		<0.20	< 0.20	NA	< 0.20	92%	50%	140%	88%	50%	140%	93%	50%	140%
Vinyl Chloride	2477800		<0.17	<0.17	NA	< 0.17	111%	50%	140%	91%	50%	140%	96%	50%	140%
Bromomethane	2477800		<0.20	< 0.20	NA	< 0.20	101%	50%	140%	102%	50%	140%	85%	50%	140%
Trichlorofluoromethane	2477800		< 0.40	< 0.40	NA	< 0.40	97%	50%	140%	94%	50%	140%	109%	50%	140%
Acetone	2477800		<1.0	<1.0	NA	< 1.0	116%	50%	140%	107%	50%	140%	103%	50%	140%
1,1-Dichloroethylene	2477800		<0.30	<0.30	NA	< 0.30	98%	50%	140%	92%	60%	130%	84%	50%	140%
Methylene Chloride	2477800		<0.30	<0.30	NA	< 0.30	102%	50%		103%	60%	130%	98%	50%	
trans- 1,2-Dichloroethylene	2477800		<0.20	<0.20	NA	< 0.20	90%	50%		94%	60%	130%	85%	50%	
Methyl tert-butyl ether	2477800		<0.20	<0.20	NA	< 0.20	92%	50%	140%	92%	60%	130%	96%	50%	
1,1-Dichloroethane	2477800		<0.30	<0.30	NA	< 0.30	92%		140%	87%		130%	87%		140%
Methyl Ethyl Ketone	2477800		<1.0	<1.0	NA	< 1.0	96%	50%	140%	94%	50%	140%	85%	50%	140%
cis- 1,2-Dichloroethylene	2477800		<0.20	<0.20	NA	< 0.20	82%		140%	76%		130%	81%		140%

AGAT QUALITY ASSURANCE REPORT (V1)

Page 9 of 16

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. RPDs calculated using raw data. The RPD may not be reflective of duplicate values shown, due to rounding of final results.



AGAT WORK ORDER: 21Z747835

Quality Assurance

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B ATTENTION TO: Luke Lopers
SAMPLING SITE:Dumaurier SAMPLED BY:Luke Lopers

	Trace Organics Analysis (Continued)																
RPT Date: May 25, 2021		DUPLICATE			REFERENCE MATERIAL		METHOD BLANK SPIKE			MAT	MATRIX SPIKE						
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD	Method Blank	Measured		Acceptable Limits	Limite		Recovery		ptable nits	Recovery		eptable mits
		la la					Value	Lower	Upper		Lower	Upper]	Lower	Upper		
Chloroform	2477800		<0.20	<0.20	NA	< 0.20	97%	50%	140%	89%	60%	130%	75%	50%	140%		
1,2-Dichloroethane	2477800		<0.20	< 0.20	NA	< 0.20	101%	50%	140%	107%	60%	130%	116%	50%	140%		
1,1,1-Trichloroethane	2477800		<0.30	<0.30	NA	< 0.30	99%	50%	140%	80%	60%	130%	95%	50%	140%		
Carbon Tetrachloride	2477800		<0.20	<0.20	NA	< 0.20	95%	50%	140%	85%	60%	130%	100%	50%	140%		
Benzene	2477800		<0.20	<0.20	NA	< 0.20	103%	50%	140%	100%	60%	130%	94%	50%	140%		
1,2-Dichloropropane	2477800		<0.20	<0.20	NA	< 0.20	104%	50%	140%	94%	60%	130%	102%	50%	140%		
Trichloroethylene	2477800		<0.20	<0.20	NA	< 0.20	87%	50%	140%	78%	60%	130%	83%	50%	140%		
Bromodichloromethane	2477800		<0.20	<0.20	NA	< 0.20	101%	50%	140%	95%	60%	130%	101%	50%	140%		
Methyl Isobutyl Ketone	2477800		<1.0	<1.0	NA	< 1.0	102%	50%	140%	115%	50%	140%	105%	50%	140%		
1,1,2-Trichloroethane	2477800		<0.20	<0.20	NA	< 0.20	105%	50%	140%	96%	60%	130%	89%	50%	140%		
Toluene	2477800		<0.20	<0.20	NA	< 0.20	103%	50%	140%	105%	60%	130%	91%	50%	140%		
Dibromochloromethane	2477800		<0.10	<0.10	NA	< 0.10	96%	50%	140%	100%	60%	130%	93%	50%	140%		
Ethylene Dibromide	2477800		<0.10	<0.10	NA	< 0.10	96%	50%	140%	90%	60%	130%	87%	50%	140%		
Tetrachloroethylene	2477800		<0.20	<0.20	NA	< 0.20	87%	50%	140%	95%	60%	130%	86%	50%	140%		
1,1,1,2-Tetrachloroethane	2477800		<0.10	<0.10	NA	< 0.10	99%	50%	140%	87%	60%	130%	100%	50%	140%		
Chlorobenzene	2477800		<0.10	<0.10	NA	< 0.10	100%	50%	140%	95%	60%	130%	98%	50%	140%		
Ethylbenzene	2477800		<0.10	<0.10	NA	< 0.10	92%	50%	140%	93%	60%	130%	94%	50%	140%		
m & p-Xylene	2477800		<0.20	<0.20	NA	< 0.20	99%	50%	140%	101%	60%	130%	101%	50%	140%		
Bromoform	2477800		<0.10	<0.10	NA	< 0.10	104%	50%	140%	103%	60%	130%	102%	50%	140%		
Styrene	2477800		<0.10	<0.10	NA	< 0.10	96%	50%	140%	111%	60%	130%	101%	50%	140%		
1,1,2,2-Tetrachloroethane	2477800		<0.10	<0.10	NA	< 0.10	110%	50%	140%	106%	60%	130%	103%	50%	140%		
o-Xylene	2477800		<0.10	<0.10	NA	< 0.10	92%	50%	140%	89%	60%	130%	93%	50%	140%		
1,3-Dichlorobenzene	2477800		<0.10	<0.10	NA	< 0.10	86%	50%	140%	97%	60%	130%	97%	50%	140%		
1,4-Dichlorobenzene	2477800		<0.10	<0.10	NA	< 0.10	101%	50%	140%	90%	60%	130%	92%	50%	140%		
1,2-Dichlorobenzene	2477800		<0.10	<0.10	NA	< 0.10	106%	50%	140%	101%	60%	130%	112%	50%	140%		
n-Hexane	2477800		<0.20	<0.20	NA	< 0.20	84%	50%	140%	86%	60%	130%	90%	50%	140%		

Comments: When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

Certified By:



Page 10 of 16



Quality Assurance

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B
SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835
ATTENTION TO: Luke Lopers
SAMPLED BY:Luke Lopers

Water Analysis														
RPT Date: May 25, 2021		DUPLICATE				REFERENCE MATERIAL		METHOD BLANK SPIKE			MATRIX SPIKE			
PARAMETER	Batch Sample	Dup #1	Dup #2	RPD	Method Blank	Measured		eptable imits	Recovery	Lie	ptable nits	Recovery	Acceptable Limits	
	ld ld					Value	Lower	Upper		Lower	Upper		Lower	Upper
O. Reg. 153(511) - Metals & Ir	norganics (Water)													
Dissolved Antimony	2469759	<1.0	<1.0	NA	< 1.0	97%	70%	130%	104%	80%	120%	104%	70%	130%
Dissolved Arsenic	2469759	<1.0	<1.0	NA	< 1.0	90%	70%	130%	106%	80%	120%	106%	70%	130%
Dissolved Barium	2469759	38.4	40.3	4.8%	< 2.0	101%	70%	130%	96%	80%	120%	107%	70%	130%
Dissolved Beryllium	2469759	< 0.50	< 0.50	NA	< 0.50	103%	70%	130%	112%	80%	120%	118%	70%	130%
Dissolved Boron	2469759	69.6	71.9	3.3%	< 10.0	99%	70%	130%	104%	80%	120%	110%	70%	130%
Dissolved Cadmium	2469759	<0.20	<0.20	NA	< 0.20	NA	70%	130%	99%	80%	120%	108%	70%	130%
Dissolved Chromium	2469759	<2.0	<2.0	NA	< 2.0	96%	70%	130%	95%	80%	120%	101%	70%	130%
Dissolved Cobalt	2469759	< 0.50	< 0.50	NA	< 0.50	94%	70%	130%	93%	80%	120%	102%	70%	130%
Dissolved Copper	2469759	<1.0	<1.0	NA	< 1.0	95%	70%	130%	96%	80%	120%	102%	70%	130%
Dissolved Lead	2469759	<0.50	<0.50	NA	< 0.50	90%	70%	130%	95%	80%	120%	100%	70%	130%
Dissolved Molybdenum	2469759	<0.50	<0.50	NA	< 0.50	97%	70%	130%	96%	80%	120%	103%	70%	130%
Dissolved Nickel	2469759	<3.0	<3.0	NA	< 3.0	95%	70%	130%	91%	80%	120%	99%	70%	130%
Dissolved Selenium	2469759	<1.0	1.8	NA	< 1.0	100%	70%	130%	111%	80%	120%	112%	70%	130%
Dissolved Silver	2469759	< 0.20	< 0.20	NA	< 0.20	96%	70%	130%	96%	80%	120%	103%	70%	130%
Dissolved Thallium	2469759	<0.30	< 0.30	NA	< 0.30	93%	70%	130%	99%	80%	120%	104%	70%	130%
Dissolved Uranium	2469759	<0.50	<0.50	NA	< 0.50	97%	70%	130%	98%	80%	120%	102%	70%	130%
Dissolved Vanadium	2469759	< 0.40	< 0.40	NA	< 0.40	98%	70%	130%	94%	80%	120%	101%	70%	130%
Dissolved Zinc	2469759	<5.0	<5.0	NA	< 5.0	95%	70%	130%	89%	80%	120%	106%	70%	130%
Mercury	2480867	< 0.02	< 0.02	NA	< 0.02	104%	70%	130%	101%	80%	120%	100%	70%	130%
Chromium VI	2481695	<2.000	<2.000	NA	< 2	103%	70%	130%	106%	80%	120%	104%	70%	130%
Cyanide, Free	2476558	<2	<2	NA	< 2	103%	70%	130%	103%	80%	120%	111%	70%	130%
Dissolved Sodium	2478945 2478945	84400	82700	2.0%	< 50	99%	70%	130%	99%	80%	120%	99%	70%	130%
Chloride	2480867	87000	84900	2.4%	< 100	101%	70%	130%	106%	80%	120%	102%	70%	130%
Electrical Conductivity	2481240	1200	1220	1.7%	< 2	102%	90%	110%	NA			NA		
рН	2481240	5.92	5.68	4.1%	NA	101%	90%	110%	NA			NA		

Comments: NA Signifies Not Applicable

Duplicate NA: results are under 5X the RDL and will not be calculated.

manyot Bhells AMANJOT BHELA CHEMIST

Certified By:

Page 11 of 16

Method Summary

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835 ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE			
Trace Organics Analysis		·				
Naphthalene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Acenaphthylene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Acenaphthene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Fluorene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Phenanthrene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Anthracene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Fluoranthene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Pyrene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Benzo(a)anthracene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Chrysene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Benzo(b)fluoranthene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Benzo(k)fluoranthene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Benzo(a)pyrene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Indeno(1,2,3-cd)pyrene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Dibenz(a,h)anthracene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Benzo(g,h,i)perylene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
2-and 1-methyl Naphthalene	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Naphthalene-d8	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Acridine-d9	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Terphenyl-d14	ORG-91-5105	modified from EPA 3510C and EPA 8270E	GC/MS			
Sediment						
F1 (C6-C10)	VOL-91-5010	modified from MOE PHC-E3421	(P&T)GC/FID			
F1 (C6 to C10) minus BTEX	VOL-91-5010	modified from MOE PHC-E3421	P&T GC/FID			
Toluene-d8	VOL-91-5010	modified from MOE PHC-E3421	(P&T)GC/MS			
F2 (C10 to C16)	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
F2 (C10 to C16) minus Naphthalene	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
F3 (C16 to C34)	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
F3 (C16 to C34) minus PAHs	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
F4 (C34 to C50)	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
Gravimetric Heavy Hydrocarbons	VOL-91-5010	modified from MOE PHC-E3421	BALANCE			
Terphenyl	VOL-91-5010	modified from MOE PHC-E3421	GC/FID			
Dichlorodifluoromethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS			

Method Summary

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835 ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
		modified from EPA 5030B & EPA	
Vinyl Chloride	VOL-91-5001	8260D	(P&T)GC/MS
Bromomethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Trichlorofluoromethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Acetone	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1-Dichloroethylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Methylene Chloride	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
trans- 1,2-Dichloroethylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Methyl tert-butyl ether	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1-Dichloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Methyl Ethyl Ketone	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
cis- 1,2-Dichloroethylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Chloroform	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,2-Dichloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1,1-Trichloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Carbon Tetrachloride	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Benzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,2-Dichloropropane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Trichloroethylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Bromodichloromethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Methyl Isobutyl Ketone	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1,2-Trichloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Toluene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Dibromochloromethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Ethylene Dibromide	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Tetrachloroethylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1,1,2-Tetrachloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Chlorobenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Ethylbenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS

Method Summary

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835 ATTENTION TO: Luke Lopers SAMPLED BY:Luke Lopers

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
m & p-Xylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Bromoform	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Styrene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,1,2,2-Tetrachloroethane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
o-Xylene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,3-Dichlorobenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,4-Dichlorobenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,2-Dichlorobenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
1,3-Dichloropropene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Xylenes (Total)	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
n-Hexane	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
Toluene-d8	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS
4-Bromofluorobenzene	VOL-91-5001	modified from EPA 5030B & EPA 8260D	(P&T)GC/MS

Method Summary

CLIENT NAME: LOPERS & ASSOCIATES

PROJECT: LOP21-004B SAMPLING SITE:Dumaurier

AGAT WORK ORDER: 21Z747835
ATTENTION TO: Luke Lopers
SAMPLED BY:Luke Lopers

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Water Analysis		-	
Dissolved Antimony	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Arsenic	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Barium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Beryllium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Boron	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Cadmium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Chromium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Cobalt	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Copper	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Lead	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Molybdenum	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Nickel	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Selenium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Silver	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Thallium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Uranium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Vanadium	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Dissolved Zinc	MET-93-6103	modified from EPA 200.8 and EPA 3005A	ICP-MS
Mercury	MET-93-6100	modified from EPA 245.2 and SM 311.	² CVAAS
Chromium VI	INOR-93-6034	modified from QuickChem Method 10-124-13-1-B	LACHAT FIA
Cyanide, Free	INOR-93-6052	modified from ON MOECC E3015, SN 4500-CN- I, G-387	TECHNICON AUTO ANALYZER
Dissolved Sodium	MET-93-6105	modified from EPA 6010D	ICP/OES
Chloride	INOR-93-6004	modified from SM 4110 B	ION CHROMATOGRAPH
Electrical Conductivity	INOR-93-6000	SM 2510 B	PC TITRATE
рН	INOR-93-6000	modified from SM 4500-H+ B	PC TITRATE

Laboratories Laboratories Laboratories Laboratories LULISIIC 14. 6 5835 Coopers Avenue Mississauga, Ontario L4Z 1Y2 Ph: 905.712,5100 Fax: 905.712,5122 webearth.agatlabs.com

Laboratory Use Only Work Order #: 21770

Chain	of	Custody	Record
-------	----	---------	--------

Chain of Custody Record If this is a Drinking Water sample, please to	use Drinking Water Chain of Custody Form (potable water	er consumed by humans)	Cooler Quantity: Arrival Temperatures: 24 2,5 3,4
Report Information: Company: Contact: Address: Address: Contact: Address:	Regulatory Requirements: (Please check all applicable boxes) Regulation 153/04	Sewer Use	Custody Seal Intact: Yes No N/A Notes: Turnaround Time (TAT) Required:
Phone: Reports to be sent to: 1. Email: LukeC Logars ca 2. Email:	Table Indicate One	Region Prov. Water Quality Objectives (PWQO) Other Indicate One	Regular TAT (Most Analysis) Rush TAT (Rush Surcharges Apply) 3 Business
Project Information: Project: LOP21-001B Site Location: Dumanticr Sampled By: Luke CoperS	Record of Site Condition?	Report Guldeline on ertificate of Analysis Yes No	Please provide prior notification for rush TAT *TAT is exclusive of weekends and statutory holidays For 'Same Day' analysis, please contact your AGAT CPM
AGAT ID #: PO: Please note: If quotation number is not provided, client will be billed full price for analysis. Invoice Information: Bill To Same: Yes ID No Company: Contlact: Address: Email:	Sample Matrix Legend B Biota GW Ground Water O Oil P Paint S Soil SD Sediment SW Surface Water	Metals & Inorganics Metals - CrVI, Hg, CHWSB BTEX, F1-F4 PHCS Analyze F4G if required CYes CNO PAHS Total PCBs CAroclor	Landfill Disposal Characterization TOLP: TOLP. □ M& □ VOCS □ ABNS □ B(a)P □ PCBS STORES SOILS SPLP Rainwater Leach SPLP: □ Metals □ VOCS □ SVOCS Excess Soils Characterization Package pH, ICPMS Metals, BTEX, F1-F4 Salt - EC/SAR Potentially Hazardous or High Concentration (Y/N)
Sample Gentification Sampled Sampled Containers	Sample Comments/ Matrix Special Instructions Sow	Metals & Met	Landfill Disportive Community of the Community Haz
Samples Deliconiched Ru Wint Marris and Steel	Samples Received By (Print Name and Sign): Samples Received By (Print Name and Sign): Samples Received By (Print Name and Sign):	Both Bate (Date	



CLIENT NAME: GHD LIMITED 455 Phillip St

WATERLOO, ON N2V1C2

(519) 884-0510

ATTENTION TO: LUKE LOPERS

PROJECT: 11181273 (PO# 73513391)

AGAT WORK ORDER: 18Z399894

TRACE ORGANICS REVIEWED BY: Oksana Gushyla, Trace Organics Lab Supervisor

WATER ANALYSIS REVIEWED BY: Yris Verastegui, Report Reviewer

DATE REPORTED: Nov 13, 2018

PAGES (INCLUDING COVER): 14

VERSION*: 2

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

<u>IOTES</u>	
ERSION 2:Revised report issued November 13, 2018.	
nalytical Data from MW1, MW2 and MW4 redacted.	

All samples will be disposed of within 30 days following analysis. Please contact the lab if you require additional sample storage time.

AGAT Laboratories (V2)

Page 1 of 14

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation.



AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Reg. 153(51)) - PHCs F1 - F4	(-BTEX) (Water)
-----------------	------------------	-----------------

DATE RECEIVED: 2018-10-20						DATE REPORTED:	2018-11-13
			SAMPLI	E DESCRIPTION:	MW3S-101918	MW3D-101918	MW6-101918
				SAMPLE TYPE:	Water	Water	Water
			1	DATE SAMPLED:	2018-10-19	2018-10-19	2018-10-19
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	9641876	9641877	9641879
F1 (C6 - C10)	μg/L	25	2018-11-08	2018-11-09	<25	<25	<25
F1 (C6 to C10) minus BTEX	μg/L	25	2018-11-08	2018-11-09	<25	<25	<25
F2 (C10 to C16)	μg/L	100	2018-11-12	2018-11-12	170	<100	<100
F3 (C16 to C34)	μg/L	100	2018-11-12	2018-11-12	860	<100	<100
F4 (C34 to C50)	μg/L	100	2018-11-12	2018-11-12	170	<100	<100
Gravimetric Heavy Hydrocarbons	μg/L	500	2018-11-12	2018-11-12	NA	NA	NA
Surrogate	Unit	Acceptable Limits					
Terphenyl	%	60-140	2018-11-12	2018-11-12	85	84	100

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

9641620-9641879 The C6-C10 fraction is calculated using Toluene response factor.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and nC34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16 - C50 and are only determined if the chromatogram of the C34 - C50 Hydrocarbons indicated that hydrocarbons > C50 are present.

The chromatogram has returned to baseline by the retention time of nC50.

Total C6-C50 results are corrected for BTEX contributions.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC6 and nC10 response factors are within 30% of Toluene response factor.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Fractions 1-4 are quantified with the contribution of PAHs. Under Ontario Regulation 153, results are considered valid without determining the PAH contribution if not requested by the client.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:

Jung



AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Rea.	1530	(511)	- VOCs	(Water))
---------	------	-------	--------	---------	---

DATE RECEIVED: 2018-10-20	1						DATE REPORT	ED: 2018-11-13	
				SAMPL	E DESCRIPTION:			MW3S-101918	MW3D-101918
					SAMPLE TYPE:			Water	Water
					DATE SAMPLED:			2018-10-19	2018-10-19
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	RDL	RDL	9641876	9641877
Dichlorodifluoromethane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Vinyl Chloride	μg/L		0.17	2018-10-24	2018-10-25	0.68	0.17	<0.17	<0.17
Bromomethane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Trichlorofluoromethane	μg/L		0.40	2018-10-24	2018-10-25	1.60	0.40	<0.40	<0.40
Acetone	μg/L		1.0	2018-10-24	2018-10-25	4.0	1.0	<1.0	<1.0
1,1-Dichloroethylene	μg/L		0.30	2018-10-24	2018-10-25	1.20	0.30	<0.30	< 0.30
Methylene Chloride	μg/L		0.30	2018-10-24	2018-10-25	1.20	0.30	< 0.30	< 0.30
trans- 1,2-Dichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Methyl tert-butyl ether	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
1,1-Dichloroethane	μg/L		0.30	2018-10-24	2018-10-25	1.20	0.30	<0.30	< 0.30
Methyl Ethyl Ketone	μg/L		1.0	2018-10-24	2018-10-25	4.0	1.0	<1.0	<1.0
cis- 1,2-Dichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Chloroform	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
1,2-Dichloroethane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
1,1,1-Trichloroethane	μg/L		0.30	2018-10-24	2018-10-25	1.20	0.30	< 0.30	< 0.30
Carbon Tetrachloride	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Benzene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	0.49	<0.20
1,2-Dichloropropane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Trichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Bromodichloromethane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Methyl Isobutyl Ketone	μg/L		1.0	2018-10-24	2018-10-25	4.0	1.0	<1.0	<1.0
1,1,2-Trichloroethane	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Toluene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Dibromochloromethane	μg/L		0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
Ethylene Dibromide	μg/L		0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
Tetrachloroethylene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
1,1,1,2-Tetrachloroethane	μg/L		0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
Chlorobenzene	μg/L		0.10	2018-10-24	2018-10-25	0.40	0.10	0.64	<0.10
Ethylbenzene	μg/L		0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
m & p-Xylene	μg/L		0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20





AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Reg. 153(511) - VOCs ((Water)
-----------------	------------	---------

DATE RECEIVED: 2018-10-20						DATE REPORT	ED: 2018-11-13	
			SAMPLE	E DESCRIPTION:			MW3S-101918	MW3D-101918
				SAMPLE TYPE:			Water	Water
			[DATE SAMPLED:			2018-10-19	2018-10-19
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	RDL	RDL	9641876	9641877
Bromoform	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
Styrene	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
1,1,2,2-Tetrachloroethane	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
o-Xylene	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
1,3-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
1,4-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	0.79	<0.10
1,2-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	0.40	0.10	<0.10	<0.10
1,3-Dichloropropene	μg/L	0.30	2018-10-24	2018-10-25	1.20	0.30	<0.30	<0.30
Xylene Mixture	μg/L	0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
n-Hexane	μg/L	0.20	2018-10-24	2018-10-25	0.80	0.20	<0.20	<0.20
Surrogate	Unit	Acceptable Limits						
Toluene-d8	% Recovery	50-140	2018-10-24	2018-10-25		·	80	73
4-Bromofluorobenzene	% Recovery	50-140	2018-10-24	2018-10-25			109	91





AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE:2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Rea.	1530	(511)	- VOCs	(Water))
---------	------	-------	--------	---------	---

DATE RECEIVED: 2018-10-20								DATE REPORTED: 2018-11-13
				SAMPL	E DESCRIPTION:	MW6-101918	TRIP BLANK	
					SAMPLE TYPE:	Water	Water	
					DATE SAMPLED:	2018-10-19	2018-10-19	
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	9641879	9641881	
Dichlorodifluoromethane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Vinyl Chloride	μg/L		0.17	2018-10-24	2018-10-25	<0.17	<0.17	
Bromomethane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Trichlorofluoromethane	μg/L		0.40	2018-10-24	2018-10-25	<0.40	<0.40	
Acetone	μg/L		1.0	2018-10-24	2018-10-25	<1.0	<1.0	
1,1-Dichloroethylene	μg/L		0.30	2018-10-24	2018-10-25	<0.30	<0.30	
Methylene Chloride	μg/L		0.30	2018-10-24	2018-10-25	<0.30	<0.30	
trans- 1,2-Dichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Methyl tert-butyl ether	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
1,1-Dichloroethane	μg/L		0.30	2018-10-24	2018-10-25	<0.30	<0.30	
Methyl Ethyl Ketone	μg/L		1.0	2018-10-24	2018-10-25	<1.0	<1.0	
cis- 1,2-Dichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	0.27	<0.20	
Chloroform	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
1,2-Dichloroethane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
1,1,1-Trichloroethane	μg/L		0.30	2018-10-24	2018-10-25	<0.30	<0.30	
Carbon Tetrachloride	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Benzene	μg/L		0.20	2018-10-24	2018-10-25	0.85	<0.20	
1,2-Dichloropropane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Trichloroethylene	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Bromodichloromethane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Methyl Isobutyl Ketone	μg/L		1.0	2018-10-24	2018-10-25	<1.0	<1.0	
1,1,2-Trichloroethane	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Toluene	μg/L		0.20	2018-10-24	2018-10-25	0.32	<0.20	
Dibromochloromethane	μg/L		0.10	2018-10-24	2018-10-25	<0.10	<0.10	
Ethylene Dibromide	μg/L		0.10	2018-10-24	2018-10-25	<0.10	<0.10	
Tetrachloroethylene	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	
1,1,1,2-Tetrachloroethane	μg/L		0.10	2018-10-24	2018-10-25	<0.10	<0.10	
Chlorobenzene	μg/L		0.10	2018-10-24	2018-10-25	1.3	<0.10	
Ethylbenzene	μg/L		0.10	2018-10-24	2018-10-25	<0.10	<0.10	
m & p-Xylene	μg/L		0.20	2018-10-24	2018-10-25	<0.20	<0.20	

Certified By:

Jung



AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Rea. 15	53(511) - V(DCs (Water)
------------	--------------	-------------

				, ,	,		
DATE RECEIVED: 2018-10-20							DATE REPORTED: 2018-11-13
			SAMPL	E DESCRIPTION:	MW6-101918	TRIP BLANK	
				SAMPLE TYPE:	Water	Water	
				DATE SAMPLED:	2018-10-19	2018-10-19	
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	9641879	9641881	
Bromoform	μg/L	0.10	2018-10-24	2018-10-25	<0.10	<0.10	
Styrene	μg/L	0.10	2018-10-24	2018-10-25	<0.10	<0.10	
1,1,2,2-Tetrachloroethane	μg/L	0.10	2018-10-24	2018-10-25	<0.10	<0.10	
o-Xylene	μg/L	0.10	2018-10-24	2018-10-25	<0.10	<0.10	
1,3-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	<0.10	<0.10	
1,4-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	1.6	<0.10	
1,2-Dichlorobenzene	μg/L	0.10	2018-10-24	2018-10-25	0.14	<0.10	
1,3-Dichloropropene	μg/L	0.30	2018-10-24	2018-10-25	<0.30	< 0.30	
Xylene Mixture	μg/L	0.20	2018-10-24	2018-10-25	<0.20	<0.20	
n-Hexane	μg/L	0.20	2018-10-24	2018-10-25	<0.20	<0.20	
Surrogate	Unit	Acceptable Limits					
Toluene-d8	% Recovery	50-140	2018-10-24	2018-10-25	73	90	
4-Bromofluorobenzene	% Recovery	50-140	2018-10-24	2018-10-25	107	81	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

9641666 Dilution factor=4

The sample was diluted because it was foamy. The reporting detection limit has been corrected for the dilution factor used.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:

Jung



AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Reg. 15	3(511)	- Metals &	Inorganics	(Water)

DATE RECEIVED: 2018-10-	-20					DATE REPORTE	D: 2018-11-1	3
				E DESCRIPTION: SAMPLE TYPE: DATE SAMPLED:		MW3S-101918 Water 2018-10-19		MW3D-101918 Water 2018-10-19
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	RDL	9641876	RDL	9641877
Antimony	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	1.0	<1.0
Arsenic	μg/L	1.0	2018-10-25	2018-10-25	1.0	3.1	1.0	<1.0
Barium	μg/L	2.0	2018-10-25	2018-10-25	2.0	680	2.0	493
Beryllium	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	0.5	<0.5
Boron	μg/L	10.0	2018-10-25	2018-10-25	10.0	58.4	10.0	20.0
Cadmium	μg/L	0.2	2018-10-25	2018-10-25	0.2	<0.2	0.2	<0.2
Chromium	μg/L	2.0	2018-10-25	2018-10-25	2.0	12.6	2.0	14.5
Cobalt	μg/L	0.5	2018-10-25	2018-10-25	0.5	1.2	0.5	<0.5
Copper	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	1.0	2.2
Lead	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	0.5	<0.5
Molybdenum	μg/L	0.5	2018-10-25	2018-10-25	0.5	1.5	0.5	1.3
Nickel	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	1.0	1.0
Selenium	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	1.0	<1.0
Silver	μg/L	0.2	2018-10-25	2018-10-25	0.2	<0.2	0.2	<0.2
Thallium	μg/L	0.3	2018-10-25	2018-10-25	0.3	<0.3	0.3	< 0.3
Uranium	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	0.5	1.5
Vanadium	μg/L	0.4	2018-10-25	2018-10-25	0.4	3.3	0.4	4.1
Zinc	μg/L	5.0	2018-10-25	2018-10-25	5.0	<5.0	5.0	<5.0
Mercury	μg/L	0.02	2018-10-24	2018-10-24	0.02	<0.02	0.02	<0.02
Chromium VI	μg/L	5	2018-10-25	2018-10-25	5	<5	5	<5
Cyanide	μg/L	2	2018-10-26	2018-10-26	2	<2	2	<2
Sodium	μg/L	5000	2018-10-29	2018-10-29	2500	384000	2500	606000
Chloride	μg/L	5000	2018-10-25	2018-10-25	2000	1150000	5000	1400000
Electrical Conductivity	uS/cm	2	2018-10-25	2018-10-25	2	3630	2	4580
pH	pH Units	NA	2018-10-25	2018-10-25	NA	7.09	NA	7.57

Certified By:

Iris Verastegui



AGAT WORK ORDER: 18Z399894 PROJECT: 11181273 (PO# 73513391) 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE: 2865 DuMaurier

ATTENTION TO: LUKE LOPERS SAMPLED BY:S. Wheeler

O. Reg. 153(511)) - Metals & Inorganics ((Water)

DATE RECEIVED: 2018-10-2	20					DAT	E REPORTED: 2018-11-13
			SAMPLI	E DESCRIPTION:		MW6-101918	
				SAMPLE TYPE:		Water	
			1	DATE SAMPLED:		2018-10-19	
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	RDL	9641879	
Antimony	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	
Arsenic	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	
Barium	μg/L	2.0	2018-10-25	2018-10-25	2.0	688	
Beryllium	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	
Boron	μg/L	10.0	2018-10-25	2018-10-25	10.0	62.8	
Cadmium	μg/L	0.2	2018-10-25	2018-10-25	0.2	<0.2	
Chromium	μg/L	2.0	2018-10-25	2018-10-25	2.0	10.0	
Cobalt	μg/L	0.5	2018-10-25	2018-10-25	0.5	1.3	
Copper	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	
_ead	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	
Molybdenum	μg/L	0.5	2018-10-25	2018-10-25	0.5	1.8	
Nickel	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	
Selenium	μg/L	1.0	2018-10-25	2018-10-25	1.0	<1.0	
Silver	μg/L	0.2	2018-10-25	2018-10-25	0.2	<0.2	
Thallium	μg/L	0.3	2018-10-25	2018-10-25	0.3	<0.3	
Uranium	μg/L	0.5	2018-10-25	2018-10-25	0.5	<0.5	
√anadium	μg/L	0.4	2018-10-25	2018-10-25	0.4	2.8	
Zinc	μg/L	5.0	2018-10-25	2018-10-25	5.0	6.0	
Mercury	μg/L	0.02	2018-10-24	2018-10-24	0.02	<0.02	
Chromium VI	μg/L	5	2018-10-25	2018-10-25	5	<5	
Cyanide	μg/L	2	2018-10-26	2018-10-26	2	<2	
Sodium	μg/L	2500	2018-10-29	2018-10-29	2500	385000	
Chloride	μg/L	1000	2018-10-25	2018-10-25	2000	1130000	
Electrical Conductivity	uS/cm	2	2018-10-25	2018-10-25	2	3640	
H	pH Units	NA	2018-10-25	2018-10-25	NA	7.12	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

9641620-9641879 Elevated RDLs indicate the degree of sample dilutions prior to the analysis to keep analytes within the calibration range, reduce matrix interference and/or to avoid contaminating the instrument. Analysis performed at AGAT Toronto (unless marked by *)

Certified By:

Iris Verastegui

Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273 (PO# 73513391)
SAMPLING SITE:2865 DuMaurier

AGAT WORK ORDER: 18Z399894
ATTENTION TO: LUKE LOPERS
SAMPLED BY:S. Wheeler

			Trac	e Or	ganio	cs Ar	nalys	is							
RPT Date: Nov 13, 2018				DUPLICATI	E		REFEREN	REFERENCE MATERIAL		METHOD BLANK SPIKE			MATRIX SPIKE		KE
PARAMETER	Batch	Sample	Dup #1	Dup #2	RPD	Method Blank	Measured		ptable	Recovery		ptable nits	Recovery		ptable nits
		ld					Value	Lower	Upper	,	Lower	Upper	,	Lower	Upper
O. Reg. 153(511) - VOCs (Water)															
Dichlorodifluoromethane	9641620	9641620	< 0.20	< 0.20	NA	< 0.20	77%	50%	140%	104%	50%	140%	96%	50%	140%
Vinyl Chloride	9641620 9	9641620	< 0.17	< 0.17	NA	< 0.17	75%	50%	140%	81%	50%	140%	75%	50%	140%
Bromomethane	9641620 9	9641620	< 0.20	< 0.20	NA	< 0.20	79%	50%	140%	79%	50%	140%	71%	50%	140%
Trichlorofluoromethane	9641620 9	9641620	< 0.40	< 0.40	NA	< 0.40	71%	50%	140%	107%	50%	140%	87%	50%	140%
Acetone	9641620 9	9641620	< 1.0	< 1.0	NA	< 1.0	108%	50%	140%	111%	50%	140%	111%	50%	140%
1,1-Dichloroethylene	9641620 9	9641620	< 0.30	< 0.30	NA	< 0.30	81%	50%	140%	114%	60%	130%	119%	50%	140%
Methylene Chloride	9641620 9	9641620	< 0.30	< 0.30	NA	< 0.30	105%	50%	140%	114%	60%	130%	100%	50%	140%
trans- 1,2-Dichloroethylene	9641620 9	9641620	< 0.20	< 0.20	NA	< 0.20	98%	50%	140%	105%	60%	130%	109%	50%	140%
Methyl tert-butyl ether	9641620 9	9641620	< 0.20	< 0.20	NA	< 0.20	107%	50%	140%	98%	60%	130%	83%	50%	140%
1,1-Dichloroethane	9641620 9	9641620	< 0.30	< 0.30	NA	< 0.30	110%	50%	140%	102%	60%	130%	115%	50%	140%
Methyl Ethyl Ketone	9641620 9	9641620	< 1.0	< 1.0	NA	< 1.0	75%	50%	140%	112%	50%	140%	115%	50%	140%
cis- 1,2-Dichloroethylene	9641620		< 0.20	< 0.20	NA	< 0.20	105%	50%	140%	114%	60%	130%	108%	50%	140%
Chloroform	9641620		< 0.20	< 0.20	NA	< 0.20	119%	50%	140%	113%	60%	130%	107%	50%	140%
1,2-Dichloroethane	9641620 9		< 0.20	< 0.20	NA	< 0.20	119%	50%	140%	110%	60%	130%	105%	50%	140%
1,1,1-Trichloroethane	9641620		< 0.30	< 0.30	NA	< 0.30	109%	50%	140%	116%	60%	130%	80%	50%	140%
Carbon Tetrachloride	9641620 9	0641620	< 0.20	< 0.20	NA	< 0.20	114%	50%	140%	113%	60%	130%	102%	50%	140%
Benzene	9641620		< 0.20	< 0.20	NA	< 0.20	111%	50%	140%	109%	60%	130%	102%	50%	140%
1,2-Dichloropropane	9641620		< 0.20	< 0.20	NA	< 0.20	106%	50%	140%	118%	60%	130%	98%	50%	140%
Trichloroethylene	9641620		< 0.20	< 0.20	NA	< 0.20	106%	50%	140%	112%	60%	130%	87%	50%	140%
Bromodichloromethane	9641620		< 0.20	< 0.20	NA	< 0.20	100%	50%	140%	116%	60%	130%	95%	50%	140%
								=00/			=00/			=00/	4.400/
Methyl Isobutyl Ketone	9641620 9		< 1.0	< 1.0	NA	< 1.0	106%	50%	140%	111%	50%	140%	107%	50%	140%
1,1,2-Trichloroethane	9641620 9		< 0.20	< 0.20	NA	< 0.20	109%	50%	140%	92%	60%	130%	78%	50%	140%
Toluene	9641620 9		< 0.20	< 0.20	NA	< 0.20	98%	50%	140%	98%	60%	130%	81%	50%	140%
Dibromochloromethane	9641620 9		< 0.10	< 0.10	NA	< 0.10	100%	50%	140%	92%	60%	130%	79%	50%	140%
Ethylene Dibromide	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	101%	50%	140%	92%	60%	130%	81%	50%	140%
Tetrachloroethylene	9641620 9	9641620	< 0.20	< 0.20	NA	< 0.20	106%	50%	140%	101%	60%	130%	83%	50%	140%
1,1,1,2-Tetrachloroethane	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	115%	50%	140%	89%	60%	130%	74%	50%	140%
Chlorobenzene	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	106%	50%	140%	93%	60%	130%	77%	50%	140%
Ethylbenzene	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	100%	50%	140%	89%	60%	130%	72%	50%	140%
m & p-Xylene	9641620	9641620	< 0.20	< 0.20	NA	< 0.20	107%	50%	140%	95%	60%	130%	77%	50%	140%
Bromoform	9641620	9641620	< 0.10	< 0.10	NA	< 0.10	107%	50%	140%	78%	60%	130%	89%	50%	140%
Styrene	9641620 9	9641620	0.23	0.23	NA	< 0.10	116%	50%	140%	108%	60%	130%	88%	50%	140%
1,1,2,2-Tetrachloroethane	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	98%	50%	140%	104%	60%	130%	92%	50%	140%
o-Xylene	9641620	9641620	< 0.10	< 0.10	NA	< 0.10	112%	50%	140%	96%	60%	130%	74%	50%	140%
1,3-Dichlorobenzene	9641620	9641620	< 0.10	< 0.10	NA	< 0.10	114%	50%	140%	94%	60%	130%	73%	50%	140%
1,4-Dichlorobenzene	9641620 9	9641620	< 0.10	< 0.10	NA	< 0.10	110%	50%	140%	91%	60%	130%	79%	50%	140%
1,2-Dichlorobenzene	9641620		< 0.10	< 0.10	NA	< 0.10	107%		140%	85%		130%	70%		140%
1,3-Dichloropropene	9641620		< 0.30	< 0.30	NA	< 0.30	95%		140%	86%	60%		81%		140%
n-Hexane	9641620		< 0.20	< 0.20	NA	< 0.20	97%		140%	76%		130%	109%		140%

AGAT QUALITY ASSURANCE REPORT (V2)

Page 9 of 14

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation.



Quality Assurance

CLIENT NAME: GHD LIMITED PROJECT: 11181273 (PO# 73513391) AGAT WORK ORDER: 18Z399894 ATTENTION TO: LUKE LOPERS

SAMPLING SITE: 2865 DuM	AMPLING SITE:2865 DuMaurier					SAMPLED BY:S. Wheeler									
	-	Ггасе	Org	Organics Analysis (Continued)											
RPT Date: Nov 13, 2018				DUPLICAT	E		REFERE	NCE MA	TERIAL	METHOD	BLANK	SPIKE	MAT	RIX SPI	KE
PARAMETER	Batch	Sample	Dup #1	Dup #2	RPD	Method Blank	Measured		ptable nits	Recovery	Lin	ptable nits	Recovery	Lie	ptable nits
		ld	·	·			Value	Lower	Upper		Lower	Upper		Lower	Upper
O. Reg. 153(511) - PHCs F1 - F4	l (-BTEX) (Wa	iter)													
F1 (C6 - C10)	9641876 9	9641876	< 25	< 25	NA	< 25	96%	60%	140%	98%	60%	140%	94%	60%	140%
F2 (C10 to C16)		TW	< 100	< 100	NA	< 100	104%	60%	140%	76%	60%	140%	72%	60%	140%
F3 (C16 to C34)		TW	< 100	< 100	NA	< 100	102%	60%	140%	105%	60%	140%	85%	60%	140%
F4 (C34 to C50)		TW	< 100	< 100	NA	< 100	92%	60%	140%	93%	60%	140%	90%	60%	140%

Comments: Tap water analysis has been performed as QC sample testing for duplicate and matrix spike due to insufficient sample volume. When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

O. Reg.	153(511) - PHCs	F1 - F4 (-BTEX) (Water)
E4 (00	040)	0044070 0044

F1 (C6 - C10)	9641879 9641879	< 25	< 25	NA	< 25	99%	60%	140%	88%	60%	140%	94%	60%	140%	
F2 (C10 to C16)	TW	< 100	< 100	NA	< 100	92%	60%	140%	78%	60%	140%	77%	60%	140%	
F3 (C16 to C34)	TW	< 100	< 100	NA	< 100	94%	60%	140%	105%	60%	140%	95%	60%	140%	
F4 (C34 to C50)	TW	< 100	< 100	NA	< 100	86%	60%	140%	101%	60%	140%	90%	60%	140%	

Certified By:

Jeurg

AGAT QUALITY ASSURANCE REPORT (V2)

Page 10 of 14



Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273 (PO# 73513391)
SAMPLING SITE:2865 DuMaurier

AGAT WORK ORDER: 18Z399894
ATTENTION TO: LUKE LOPERS
SAMPLED BY:S. Wheeler

OAWI EINO SITE.2003 Duli	AWI LING STE. 2003 DUMAGNET														
				Wate	er Ar	alys	is								
RPT Date: Nov 13, 2018				UPLICATI	E		REFEREN	ICE MA	TERIAL	METHOD	BLANK	SPIKE	MAT	RIX SPI	KE
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD	Method Blank	Measured Value		eptable mits	Recovery		ptable nits	Recovery	Lin	ptable nits
		iu					value	Lower	Upper		Lower	Upper		Lower	Upper
O. Reg. 153(511) - Metals & In-	organics (Wate	er)													
Antimony	9641620 9	641620	<1.0	<1.0	NA	< 1.0	101%	70%	130%	101%	80%	120%	100%	70%	130%
Arsenic	9641620 9	641620	7.2	8.2	13.0%	< 1.0	100%	70%	130%	103%	80%	120%	106%	70%	130%
Barium	9641620 9	641620	747	706	5.6%	< 2.0	98%	70%	130%	104%	80%	120%	101%	70%	130%
Beryllium	9641620 9	641620	<0.5	<0.5	NA	< 0.5	98%	70%	130%	96%	80%	120%	112%	70%	130%
Boron	9641620 9	641620	26.3	25.1	NA	< 10.0	99%	70%	130%	99%	80%	120%	117%	70%	130%
Cadmium	9641620 9	641620	<0.2	<0.2	NA	< 0.2	101%	70%	130%	103%	80%	120%	99%	70%	130%
Chromium	9641620 9	641620	31.4	29.6	5.9%	< 2.0	99%	70%	130%	100%	80%	120%	103%	70%	130%
Cobalt	9641620 9	641620	2.2	2.1	NA	< 0.5	101%	70%	130%	101%	80%	120%	98%	70%	130%
Copper	9641620 9	641620	1.1	1.2	NA	< 1.0	100%	70%	130%	106%	80%	120%	94%	70%	130%
Lead	9641620 9	641620	<0.5	<0.5	NA	< 0.5	104%	70%	130%	103%	80%	120%	94%	70%	130%
Molybdenum	9641620 9	641620	0.6	0.6	NA	< 0.5	102%	70%	130%	101%	80%	120%	102%	70%	130%
Nickel	9641620 9	641620	1.5	1.6	NA	< 1.0	99%	70%	130%	102%	80%	120%	93%	70%	130%
Selenium	9641620 9	641620	1.8	5.3	NA	< 1.0	99%	70%	130%	99%	80%	120%	103%	70%	130%
Silver	9641620 9	641620	<0.2	<0.2	NA	< 0.2	101%	70%	130%	110%	80%	120%	96%	70%	130%
Thallium	9641620 9	641620	<0.3	<0.3	NA	< 0.3	102%	70%	130%	102%	80%	120%	93%	70%	130%
Uranium	9641620 9	641620	0.8	0.7	NA	< 0.5	107%	70%	130%	100%	80%	120%	91%	70%	130%
Vanadium	9641620 9	641620	4.7	4.4	6.6%	< 0.4	100%	70%	130%	100%	80%	120%	103%	70%	130%
Zinc	9641620 9	641620	<5.0	<5.0	NA	< 5.0	101%	70%	130%	99%	80%	120%	92%	70%	130%
Mercury	9641620 9	641620	< 0.02	< 0.02	NA	< 0.02	98%	70%	130%	99%	80%	120%	102%	70%	130%
Chromium VI	9641877 9	641877	<5	<5	NA	< 5	102%	70%	130%	101%	80%	120%	101%	70%	130%
Cyanide	9641666 9	641666	<2	<2	NA	< 2	97%	70%	130%	97%	80%	120%	79%	70%	130%
Sodium	9641879 9	641879	385000	383000	0.5%	< 500	96%	70%	130%	96%	80%	120%	90%	70%	130%
Chloride	9641878 9	641878	472000	460000	2.6%	< 100	95%	70%	130%	103%	70%	130%	95%	70%	130%
Electrical Conductivity	9641620 9	641620	5560	5790	4.1%	< 2	97%	90%	110%						
рН	9641620 9	641620	6.80	6.88	1.2%	NA	99%	90%	110%						

Comments: NA signifies Not Applicable.

Duplicate Qualifier: As the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL.



Method Summary

CLIENT NAME: GHD LIMITED

AGAT WORK ORDER: 18Z399894

PROJECT: 11181273 (PO# 73513391)

ATTENTION TO: LUKE LOPERS

SAMPLING SITE:2865 DuMaurier

SAMPLED BY:S. Wheeler

Of this Elito of E. 2000 Damadilo			
PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Trace Organics Analysis	·		
F1 (C6 - C10)	VOL-91- 5010	MOE PHC E3421	(P&T)GC/FID
F1 (C6 to C10) minus BTEX	VOL-91-5010	MOE PHC E3421	(P&T)GC/FID
F2 (C10 to C16)	VOL-91-5010	MOE PHC E3421	GC / FID
F3 (C16 to C34)	VOL-91-5010	MOE PHC E3421	GC / FID
F4 (C34 to C50)	VOL-91-5010	MOE PHC E3421	GC / FID
Gravimetric Heavy Hydrocarbons	VOL-91-5010	MOE PHC E3421	BALANCE
Terphenyl	VOL-91-5010		GC/FID
Dichlorodifluoromethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Vinyl Chloride	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Bromomethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Trichlorofluoromethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Acetone	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1-Dichloroethylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Methylene Chloride	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
trans- 1,2-Dichloroethylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Methyl tert-butyl ether	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1-Dichloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Methyl Ethyl Ketone	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
cis- 1,2-Dichloroethylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Chloroform	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,2-Dichloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1,1-Trichloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Carbon Tetrachloride	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Benzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,2-Dichloropropane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Trichloroethylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Bromodichloromethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Methyl Isobutyl Ketone	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1,2-Trichloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Toluene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Dibromochloromethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Ethylene Dibromide	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Tetrachloroethylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1,1,2-Tetrachloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Chlorobenzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Ethylbenzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
m & p-Xylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Bromoform	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Styrene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,1,2,2-Tetrachloroethane	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
o-Xylene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,3-Dichlorobenzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,4-Dichlorobenzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,2-Dichlorobenzene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
1,3-Dichloropropene	VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Xylene Mixture	VOL-91-5001 VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
n-Hexane	VOL-91-5001 VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
Toluene-d8	VOL-91-5001 VOL-91-5001	EPA SW-846 5030 & 8260	(P&T)GC/MS
I Oldelle-do	VOL-91-5001 VOL-91-5001	EPA SW-846 5030 & 8260 EPA SW-846 5030 & 8260	(P&T)GC/MS (P&T)GC/MS

Method Summary

CLIENT NAME: GHD LIMITED

AGAT WORK ORDER: 18Z399894

PROJECT: 11181273 (PO# 73513391)

ATTENTION TO: LUKE LOPERS

SAMPLING SITE:2865 DuMaurier

SAMPLED BY:S. Wheeler

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Water Analysis	1	1	1
Antimony	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Arsenic	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Barium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Beryllium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Boron	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Cadmium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Chromium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Cobalt	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Copper	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Lead	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Molybdenum	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Nickel	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Selenium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Silver	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Thallium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Uranium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Vanadium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Zinc	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Mercury	MET-93-6100	EPA SW-846 7470 & 245.1	CVAAS
Chromium VI	INOR-93-6034	SM 3500-Cr B	SPECTROPHOTOMETER
Cyanide	INOR-93-6052	MOE METHOD CN- 3015 & SM 4500 CN- I	TECHNICON AUTO ANALYZER
Sodium	MET-93-6105	EPA SW-846 6010C & 200.7	ICP/OES
Chloride	INOR-93-6004	SM 4110 B	ION CHROMATOGRAPH
Electrical Conductivity	INOR-93-6000	SM 2510 B	PC TITRATE
pH	INOR-93-6000	SM 4500-H+ B	PC TITRATE

Laboratories Ph: 90

5835 Coopers Avenue Mississauga, Ontario L4Z 1Y2

Ph: 905-712.5100 Fax: 905.712.5122 webearth.agatlabs.com **Laboratory Use Only**

		Cooler Quantity:
Chain of Custody Record If this is a Drinking Water sample, plea	use Drinking Water Chain of Custody Form (potable water consu	umed by humans) Arrival Temperatures: 2.4 2.6 2.0
Report Information: Company: Contact: Lyke Lopers Address: 174 colomade RD # 4000	(Please check all applicable boxes) Regulation 153/04 Sewer Use Table Indicate One Sanitary	Custody Seal Intact: Yes No Notes: Custody Seal Intact: Yes No Notes: Custody Seal Intact: Yes No Notes: Turnaround Time (TAT) Required:
Phone: Reports to be sent to: 1. Email: 2. Email: Phone: Fax: Luke. Logers @GHD. Com	☐ Ind/com ☐ Res/Park ☐ Agriculture ☐ Index on the state of the state	Regular TAT \$\infty\$ 5 to 7 Business Days
Project Information: Project: 118473 Site Location: 2865 Dymaurier Sampled By: 5 wheler	Record of Site Condition? Certific	For 'Same Day' analysis, please contact your AGAT CPM
AGAT Quote #: PO: 73 5 13 39 Please note: If quotation number is not provided, client will be billed full price for analysis. Invoice Information: Company: Contact: Address: Email:	Sample Matrix Legend B Biota GW Ground Water O Oil P Paint S Soil SD Sediment SW Surface Water	© CC CHg C CC Hg an Stom Metals P C NH ₃ C C NO ₃ +No ₂ C ABTEX P C C Hg Stom Metals P C NH ₃ C NO ₃ +No ₂ C ABTEX VOCS C ABNS
Sampled Sampled Containers Nav 1 - 10 19 18 10/19/18 12 12 12 13 14 15 15 15 15 15 15 15	mple Comments/ Special Instructions Crivi) Not Freld Filtered The Control of Freld Filtered The Crivin Not Freld Filtered	□ Hydride Metals ORPS: □ BHW ORPS: □ BHW □ Cr ⁶ □ □ CC □ PH □ SAR Full Metals SC Nutrients: □ T □ No, □ No
Samples Relinquished By (Print Name and Sign): Anthun Bian OA Date Date	Samples Received By (Print Name and Sign): Samples Received By (Print Name and Sign): Samples Received By (Print Name and Sign):	2000 V SOO Page of



CLIENT NAME: GHD LIMITED 455 Phillip St

WATERLOO, ON N2V1C2

(519) 884-0510

ATTENTION TO: LUKE LOPERS

PROJECT: 11181273-E2 (PO#73513391)

AGAT WORK ORDER: 18Z394508

SOIL ANALYSIS REVIEWED BY: Amanjot Bhela, Inorganic Supervisor

TRACE ORGANICS REVIEWED BY: Oksana Gushyla, Trace Organics Lab Supervisor

DATE REPORTED: Oct 15, 2018

PAGES (INCLUDING COVER): 16

VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

NOTES .									
Analytical Data from BH1, BH2, BH4 and BH5 has been redacted.									

All samples will be disposed of within 30 days following analysis. Please contact the lab if you require additional sample storage time.

AGAT Laboratories (V1)

Page 1 of 16

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro Agricultural Laboratory Association (WEALA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation.



AGAT WORK ORDER: 18Z394508
PRO JECT: 11181273-F2 (PO#73513391

PROJECT: 11181273-E2 (PO#73513391)
ATTENTION TO: LUKE LOPERS

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

SAMPLED BY:Steven Wheeler

•	\ /	•	٠ ,	

O. Reg. 153(511) - Metals & Inorganics (Soil)

DATE RECEIVED: 2018-10-0	7				DATE REPORTED: 2018	3-10-15
					ВН3	
			SAMPL	E DESCRIPTION:	SS3-10-5-18	
				SAMPLE TYPE:	Soil	
				DATE SAMPLED:	2018-10-05	
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	9610086	
Antimony	μg/g	0.8	2018-10-12	2018-10-12	<0.8	
Arsenic	μg/g	1	2018-10-12	2018-10-12	2	
Barium	μg/g	2	2018-10-12	2018-10-12	56	
Beryllium	μg/g	0.5	2018-10-12	2018-10-12	<0.5	
Boron	μg/g	5	2018-10-12	2018-10-12	<5	
Boron (Hot Water Soluble)	μg/g	0.10	2018-10-11	2018-10-11	0.37	
Cadmium	μg/g	0.5	2018-10-12	2018-10-12	<0.5	
Chromium	μg/g	2	2018-10-12	2018-10-12	15	
Cobalt	μg/g	0.5	2018-10-12	2018-10-12	4.7	
Copper	μg/g	1	2018-10-12	2018-10-12	19	
Lead	μg/g	1	2018-10-12	2018-10-12	28	
Molybdenum	μg/g	0.5	2018-10-12	2018-10-12	<0.5	
Nickel	μg/g	1	2018-10-12	2018-10-12	10	
Selenium	μg/g	0.4	2018-10-12	2018-10-12	<0.4	
Silver	μg/g	0.2	2018-10-12	2018-10-12	<0.2	
Thallium	μg/g	0.4	2018-10-12	2018-10-12	<0.4	
Uranium	μg/g	0.5	2018-10-12	2018-10-12	0.5	
Vanadium	μg/g	1	2018-10-12	2018-10-12	21	
Zinc	μg/g	5	2018-10-12	2018-10-12	124	
Chromium VI	μg/g	0.2	2018-10-11	2018-10-11	<0.2	
Cyanide	μg/g	0.040	2018-10-11	2018-10-11	<0.040	
Mercury	μg/g	0.10	2018-10-12	2018-10-12	<0.10	
Electrical Conductivity	mS/cm	0.005	2018-10-11	2018-10-11	0.372	
Sodium Adsorption Ratio	NA	NA	2018-10-11	2018-10-11	1.88	
pH, 2:1 CaCl2 Extraction	pH Units	NA	2018-10-11	2018-10-11	7.44 7.4	49
	,					

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

9610083-9610088 EC & SAR were determined on the DI water extract obtained from the 2:1 leaching procedure (2 parts DI water:1 part soil). pH was determined on the 0.01M CaCl2 extract prepared at 2:1 ratio. Analysis performed at AGAT Toronto (unless marked by *)





AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

O. Reg. 558	Metals and	Inorganics
-------------	------------	------------

DATE RECEIVED: 2018-10-07							DATE REPORTED: 2018-10-15
				SAMPL	E DESCRIPTION:	BH3-10-5-18	
					SAMPLE TYPE:	Soil	
				1	DATE SAMPLED:	2018-10-05	
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	9610090	
Arsenic Leachate	mg/L	2.5	0.010	2018-10-13	2018-10-13	<0.010	
Barium Leachate	mg/L	100	0.100	2018-10-13	2018-10-13	1.21	
Boron Leachate	mg/L	500	0.050	2018-10-13	2018-10-13	0.102	
Cadmium Leachate	mg/L	0.5	0.010	2018-10-13	2018-10-13	<0.010	
Chromium Leachate	mg/L	5	0.010	2018-10-13	2018-10-13	<0.010	
Lead Leachate	mg/L	5	0.010	2018-10-13	2018-10-13	0.196	
Mercury Leachate	mg/L	0.1	0.01	2018-10-13	2018-10-13	<0.01	
Selenium Leachate	mg/L	1	0.010	2018-10-13	2018-10-13	<0.010	
Silver Leachate	mg/L	5	0.010	2018-10-13	2018-10-13	<0.010	
Uranium Leachate	mg/L	10	0.050	2018-10-13	2018-10-13	<0.050	
Fluoride Leachate	mg/L	150	0.05	2018-10-12	2018-10-12	80.0	
Cyanide Leachate	mg/L	20	0.05	2018-10-12	2018-10-12	<0.05	
(Nitrate + Nitrite) as N Leachate	mg/L	1000	0.70	2018-10-12	2018-10-12	<0.70	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to O. Reg. 558 - Schedule IV Leachate Quality Criteria

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

Analysis performed at AGAT Toronto (unless marked by *)

manyot Shelds AMANDO BHELA S



AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

SAMPLING SITE: DuMaurier Avenue, Ottawa, ON

CLIENT NAME: GHD LIMITED

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

DATE RECEIVED: 2018-10-07	DATE REPORTED: 2018-10-15

SAMPLE DESCRIPTION: BH3-10-5-18 SAMPLE TYPE: Soil

O. Reg. 558 TCLP Preparation

				DATE SAMPLED:	2018-10-05
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	9610090
Analysis Start Date					2018/10/11
pH (Initial)	pH Units	N/A			7.96
pH (Final)	pH Units	N/A			5.41
Extraction Fluid					1

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to O. Reg. 558 - Schedule IV Leachate Quality Criteria

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

Analysis performed at AGAT Toronto (unless marked by *)



AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED

SAMPLING SITE: DuMaurier Avenue, Ottawa, ON

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

Flash Point Analysis								
DATE RECEIVED: 2018-10-07 DATE REPORTED: 2018-10-15								
				SAMPL	E DESCRIPTION:	BH3-10-5-18		
					SAMPLE TYPE:	Soil		
					DATE SAMPLED:	2018-10-05		
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	9610090		
Flash point (Pensky Martin Closed	Deg C		NA	2018-10-12	2018-10-12	>100		

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

Analysis performed at AGAT Calgary (unless marked by *)





AGAT WORK ORDER: 18Z394508
PRO JECT: 11181273-F2 (PO#73513391

PROJECT: 11181273-E2 (PO#73513391)
ATTENTION TO: LUKE LOPERS

SAMPLED BY:Steven Wheeler

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.aqatlabs.com

CLIENT NAME: GHD LIMITED
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

O. Reg. 153(511) - PAHs (Soil)

DATE RECEIVED: 2018-10-07					DATE REPORTED: 2018-10-15
				E DESCRIPTION: SAMPLE TYPE: DATE SAMPLED:	BH3 SS3-10-5-18 Soil 2018-10-05
Parameter	Unit	G/S RDL	Date Prepared	Date Analyzed	9610086
Naphthalene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Acenaphthylene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Acenaphthene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Fluorene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Phenanthrene	μg/g	0.05	2018-10-15	2018-10-15	0.06
Anthracene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Fluoranthene	μg/g	0.05	2018-10-15	2018-10-15	0.11
Pyrene	μg/g	0.05	2018-10-15	2018-10-15	0.09
Benz(a)anthracene	μg/g	0.05	2018-10-15	2018-10-15	0.06
Chrysene	μg/g	0.05	2018-10-15	2018-10-15	0.06
Benzo(b)fluoranthene	μg/g	0.05	2018-10-15	2018-10-15	0.07
Benzo(k)fluoranthene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Benzo(a)pyrene	μg/g	0.05	2018-10-15	2018-10-15	0.06
Indeno(1,2,3-cd)pyrene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Dibenz(a,h)anthracene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Benzo(g,h,i)perylene	μg/g	0.05	2018-10-15	2018-10-15	0.05
2-and 1-methyl Naphthalene	μg/g	0.05	2018-10-15	2018-10-15	<0.05
Moisture Content	%	0.1	2018-10-15	2018-10-15	15.1
Surrogate	Unit	Acceptable Limits			
Chrysene-d12	%	50-140	2018-10-15	2018-10-15	106

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

9610083-9610088 Results are based on the dry weight of the soil.

Note: The result for Benzo(b)Fluoranthene is the total of the Benzo(b)&j)Fluoranthene isomers because the isomers co-elute on the GC column.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:

Jung



AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

O. Reg. 558 - Benzo(a) pyrene

DATE RECEIVED: 2018-10-07 DATE REPORTED: 2018-10-15

SAMPLE DESCRIPTION: BH3-10-5-18

SAMPLE TYPE: Soil

DATE SAMPLED: 2018-10-05

 Parameter
 Unit
 G / S
 RDL
 Date Prepared
 Date Analyzed
 9610090

 Benzo(a)pyrene
 mg/L
 0.001
 0.001
 2018-10-15
 2018-10-15
 <0.001</td>

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to O. Reg. 558 - Schedule IV Leachate Quality Criteria

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

9610090 The sample was leached according to Regulation 558 protocol. Analysis was performed on the leachate.

Analysis performed at AGAT Toronto (unless marked by *)





AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED

SAMPLING SITE: DuMaurier Avenue, Ottawa, ON

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

O. Reg. 558 - PCBs									
DATE RECEIVED: 2018-10-07							DATE REPORTED: 2018-10-15		
				SAMPL	E DESCRIPTION:	BH3-10-5-18			
					SAMPLE TYPE:	Soil			
					DATE SAMPLED:	2018-10-05			
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	9610090			
Polychlorinated Biphenyls	mg/L	0.3	0.005	2018-10-12	2018-10-12	<0.005			
Surrogate	Unit	Acceptabl	le Limits						
Decachlorobiphenyl	%	60-1	30	2018-10-12	2018-10-12	99			

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to O. Reg. 558 - Schedule IV Leachate Quality Criteria

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

9610090 The soil sample was leached using the Regulation 558 procedure. Analysis was performed on the leachate.

Analysis performed at AGAT Toronto (unless marked by *)





AGAT WORK ORDER: 18Z394508

PROJECT: 11181273-E2 (PO#73513391)

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GHD LIMITED
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

ATTENTION TO: LUKE LOPERS SAMPLED BY:Steven Wheeler

	O. Reg. 558 - VOCs													
DATE RECEIVED: 2018-10-07							DATE REPORTED: 2018-10-15							
					E DESCRIPTION: SAMPLE TYPE: DATE SAMPLED:	BH3-10-5-18 Soil 2018-10-05								
Parameter	Unit	G/S	RDL	Date Prepared	Date Analyzed	9610090								
Vinyl Chloride	mg/L	0.2	0.030	2018-10-12	2018-10-15	<0.030								
1,1 Dichloroethene	mg/L	1.4	0.020	2018-10-12	2018-10-15	<0.020								
Dichloromethane	mg/L	5.0	0.030	2018-10-12	2018-10-15	< 0.030								
Methyl Ethyl Ketone	mg/L	200	0.090	2018-10-12	2018-10-15	<0.090								
Chloroform	mg/L	10.0	0.020	2018-10-12	2018-10-15	<0.020								
1,2-Dichloroethane	mg/L	0.5	0.020	2018-10-12	2018-10-15	<0.020								
Carbon Tetrachloride	mg/L	0.5	0.020	2018-10-12	2018-10-15	<0.020								
Benzene	mg/L	0.5	0.020	2018-10-12	2018-10-15	<0.020								
Trichloroethene	mg/L	5.0	0.020	2018-10-12	2018-10-15	<0.020								
Tetrachloroethene	mg/L	3.0	0.050	2018-10-12	2018-10-15	<0.050								
Chlorobenzene	mg/L	8.0	0.010	2018-10-12	2018-10-15	<0.010								
1,2-Dichlorobenzene	mg/L	20.0	0.010	2018-10-12	2018-10-15	<0.010								
1,4-Dichlorobenzene	mg/L	0.5	0.010	2018-10-12	2018-10-15	<0.010								
Surrogate	Unit	Acceptab	ole Limits											
Toluene-d8	% Recovery	60-	130	2018-10-12	2018-10-15	79								

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to O. Reg. 558 - Schedule IV Leachate Quality Criteria

Guideline values are for general reference only. The guidelines provided may or may not be relevant for the intended use. Refer directly to the applicable standard for regulatory interpretation.

9610090 Sample was prepared using Regulation 558 protocol and a zero headspace extractor.

Analysis performed at AGAT Toronto (unless marked by *)



Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273-E2 (PO#73513391)
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

AGAT WORK ORDER: 18Z394508
ATTENTION TO: LUKE LOPERS
SAMPLED BY:Steven Wheeler

Soil Analysis														
RPT Date: Oct 15, 2018		i i	DUPLICAT	E		REFERE	NCE MA	TERIAL	METHOD	BLANK	SPIKE	MAT	IKE	
PARAMETER	Batch Samp	le Dup #1	Dup #2	RPD	Method Blank	Measured		ptable nits	Recovery		ptable	Recovery		eptable mits
TANAMETER	ld ld	Jup #1	Sup #2	111 5		Value	Lower	Upper	110001019	Lower	Upper	110001019	Lower	Upper
O. Reg. 153(511) - Metals & Inor	ganics (Soil)						•						•	
Antimony	9610083 961008	3 < 0.8	<0.8	NA	< 0.8	98%	70%	130%	107%	80%	120%	74%	70%	130%
Arsenic	9610083 961008	3 2	2	NA	< 1	101%	70%	130%	112%	80%	120%	103%	70%	130%
Barium	9610083 961008	3 94	90	4.3%	< 2	89%	70%	130%	99%	80%	120%	86%	70%	130%
Beryllium	9610083 961008	3 < 0.5	< 0.5	NA	< 0.5	80%	70%	130%	112%	80%	120%	105%	70%	130%
Boron	9610083 961008	3 6	6	NA	< 5	101%	70%	130%	106%	80%	120%	90%	70%	130%
Boron (Hot Water Soluble)	9610083 961008	3 0.27	0.31	NA	< 0.10	114%	60%	140%	101%	70%	130%	118%	60%	140%
Cadmium	9610083 961008	3 < 0.5	<0.5	NA	< 0.5	102%	70%	130%	102%	80%	120%	97%	70%	130%
Chromium	9610083 961008	3 37	36	2.7%	< 2	74%	70%	130%	97%	80%	120%	100%	70%	130%
Cobalt	9610083 961008	8.2	8.0	2.5%	< 0.5	84%	70%	130%	102%	80%	120%	90%	70%	130%
Copper	9610083 961008	3 14	13	7.4%	< 1	84%	70%	130%	113%	80%	120%	92%	70%	130%
Lead	9610083 961008	3 11	11	0.0%	< 1	94%	70%	130%	100%	80%	120%	88%	70%	130%
Molybdenum	9610083 961008		<0.5	NA	< 0.5	94%	70%	130%	102%	80%	120%	94%	70%	130%
Nickel	9610083 961008		18	0.0%	< 1	89%	70%	130%	107%	80%	120%	93%	70%	130%
Selenium	9610083 961008		<0.4	NA	< 0.4	111%	70%	130%	98%	80%	120%	98%	70%	130%
Silver	9610083 961008		<0.2	NA	< 0.2	96%	70%	130%	102%	80%	120%	91%	70%	130%
Thallium	9610083 961008	3 < 0.4	<0.4	NA	< 0.4	86%	70%	130%	93%	80%	120%	92%	70%	130%
Uranium	9610083 961008		1.3	NA	< 0.5	83%	70%	130%	102%	80%	120%	94%	70%	130%
Vanadium	9610083 961008		40	2.5%	< 1	78%	70%	130%	96%	80%	120%	74%	70%	130%
Zinc	9610083 961008		57	1.7%	< 5	90%	70%	130%	110%	80%	120%	100%	70%	130%
Chromium VI	9610083 961008	3 <0.2	<0.2	NA	< 0.2	74%	70%	130%	100%	80%	120%	98%	70%	130%
Cyanide	9613642	<0.040	<0.040	NA	< 0.040	99%	70%	130%	105%	80%	120%	107%	70%	130%
Mercury	9610083 961008		<0.10	NA	< 0.10	97%	70%	130%	97%	80%	120%	91%	70%	130%
Electrical Conductivity	9610083 961008		1.88	0.5%	< 0.005		90%	110%	NA	0070	.2070	NA		
Sodium Adsorption Ratio	9610083 961008		16.0	3.2%	NA	NA	0070		NA			NA		
pH, 2:1 CaCl2 Extraction	9610083 961008		6.77	0.7%	NA	101%	80%	120%	NA			NA		
O. Reg. 558 Metals and Inorgani	cs													
Arsenic Leachate	9610090 961009	0.010	<0.010	NA	< 0.010	104%	90%	110%	105%	80%	120%	115%	70%	130%
Barium Leachate	9610090 961009		1.20	0.8%	< 0.100		90%	110%	102%	80%	120%	106%	70%	130%
Boron Leachate	9610090 961009		0.107	NA	< 0.050		90%	110%	94%	80%	120%	83%	70%	130%
Cadmium Leachate	9610090 961009		<0.010	NA	< 0.010		90%	110%	103%	80%	120%	111%	70%	130%
Chromium Leachate	9610090 961009		<0.010	NA	< 0.010		90%	110%	111%		120%	114%		130%
Lead Leachate	9610090 961009	0.196	0.191	2.6%	< 0.010	102%	90%	110%	98%	80%	120%	103%	70%	130%
Mercury Leachate	9610090 961009		<0.01	NA	< 0.01	99%		110%	101%		120%	103%	70%	130%
Selenium Leachate	9610090 961009		< 0.010	NA	< 0.010			110%	108%		120%	112%	70%	
Silver Leachate	9610090 961009		<0.010	NA	< 0.010			110%	106%		120%	102%	70%	
Uranium Leachate	9610090 961009		<0.050	NA	< 0.050			110%	101%		120%	111%	70%	
Fluoride Leachate	9610090 961009	0.08	0.08	NA	< 0.05	100%	90%	110%	108%	90%	110%	107%	70%	130%
Cyanide Leachate	9610090 961009		<0.05	NA	< 0.05	92%	90%	110%	104%		110%	84%	70%	130%
(Nitrate + Nitrite) as N Leachate	9610090 961009		<0.70	NA	< 0.70	98%		120%	97%		120%	100%	70%	

AGAT QUALITY ASSURANCE REPORT (V1)

Page 10 of 16

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation.



Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273-E2 (PO#73513391)
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

AGAT WORK ORDER: 18Z394508
ATTENTION TO: LUKE LOPERS
SAMPLED BY:Steven Wheeler

Soil Analysis (Continued)															
RPT Date: Oct 15, 2018 DUPLICATE							REFEREN	ICE MAT	ΓERIAL	METHOD	BLANK	SPIKE	MATRIX SPIKE		
PARAMETER	Batch Sample		Dup #1	Dup #2	RPD	Method Blank	Measured	Accep Lim		Recovery	Acceptable Limits		Recovery	Acceptab Limits	
		ld	,	'			Value	Lower	Upper		Lower	Upper		Lower	Upper

Comments: NA signifies Not Applicable.

Duplicate Qualifier: As the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL

Amanjot Bhells Amandot Bhells Ochemist Office Chemist Office Chemi

Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273-E2 (PO#73513391)
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

AGAT WORK ORDER: 18Z394508
ATTENTION TO: LUKE LOPERS
SAMPLED BY:Steven Wheeler

			Trac	e Or	gani	cs Ar	nalys	is							
RPT Date: Oct 15, 2018				UPLICAT	E		REFERE	NCE MA	TERIAL	METHOD	BLANK	SPIKE	MAT	RIX SPI	KE
PARAMETER	Batch	Sample	Dup #1	Dup #2	RPD	Method Blank	Measured		ptable nits	Recovery		ptable nits	Recovery		ptable
TAKAMETEK	Buton	ld	Dup # !	Dup #2	111 5		Value	Lower	Upper	recovery	Lower	Upper	Recovery	Lower	Upper
O. Reg. 153(511) - PAHs (Soil)															
Naphthalene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	92%	50%	140%	98%	50%	140%	93%	50%	140%
Acenaphthylene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	96%	50%	140%	98%	50%	140%	90%	50%	140%
Acenaphthene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	93%	50%	140%	98%	50%	140%	89%	50%	140%
Fluorene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	94%	50%	140%	94%	50%	140%	90%	50%	140%
Phenanthrene	9610086 96	310086	0.06	0.06	NA	< 0.05	97%	50%	140%	97%	50%	140%	90%	50%	140%
Anthracene	9610086 96	310086	< 0.05	< 0.05	NA	< 0.05	94%	50%	140%	91%	50%	140%	89%	50%	140%
Fluoranthene	9610086 96	310086	0.11	0.11	NA	< 0.05	98%	50%	140%	98%	50%	140%	98%	50%	140%
Pyrene	9610086 96	310086	0.09	0.08	NA	< 0.05	98%	50%	140%	99%	50%	140%	100%	50%	140%
Benz(a)anthracene	9610086 96	610086	0.06	0.06	NA	< 0.05	97%	50%	140%	95%	50%	140%	102%	50%	140%
Chrysene	9610086 96	610086	0.06	0.06	NA	< 0.05	96%	50%	140%	94%	50%	140%	104%	50%	140%
Benzo(b)fluoranthene	9610086 96	610086	0.07	0.07	NA	< 0.05	98%	50%	140%	97%	50%	140%	88%	50%	140%
Benzo(k)fluoranthene	9610086 96	310086	< 0.05	< 0.05	NA	< 0.05	98%	50%	140%	88%	50%	140%	97%	50%	140%
Benzo(a)pyrene	9610086 96	610086	0.06	0.06	NA	< 0.05	97%	50%	140%	95%	50%	140%	91%	50%	140%
Indeno(1,2,3-cd)pyrene	9610086 96	310086	< 0.05	< 0.05	NA	< 0.05	96%	50%	140%	91%	50%	140%	96%	50%	140%
Dibenz(a,h)anthracene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	95%	50%	140%	91%	50%	140%	90%	50%	140%
Benzo(g,h,i)perylene	9610086 96	610086	0.05	0.05	NA	< 0.05	97%	50%	140%	96%	50%	140%	97%	50%	140%
2-and 1-methyl Naphthalene	9610086 96	610086	< 0.05	< 0.05	NA	< 0.05	95%	50%	140%	91%	50%	140%	90%	50%	140%
O. Reg. 558 - PCBs															
Polychlorinated Biphenyls	9610090 96	610090	< 0.005	< 0.005	NA	< 0.005	103%	60%	130%	95%	60%	130%	NA	60%	130%
O. Reg. 558 - VOCs															
Vinyl Chloride	9610090 96	610090	< 0.030	< 0.030	NA	< 0.030	73%	60%	140%	79%	60%	140%	NA	60%	140%
1,1 Dichloroethene	9610090 96	310090	< 0.020	< 0.020	NA	< 0.020	85%	70%	130%	72%	70%	130%	NA	60%	140%
Dichloromethane	9610090 96	310090	< 0.030	< 0.030	NA	< 0.030	96%	70%	130%	85%	70%	130%	NA	60%	140%
Methyl Ethyl Ketone	9610090 96	310090	< 0.090	< 0.090	NA	< 0.090	117%	70%	130%	116%	70%	130%	NA	60%	140%
Chloroform	9610090 96	610090	< 0.020	< 0.020	NA	< 0.020	75%	70%	130%	85%	70%	130%	NA	60%	140%
1,2-Dichloroethane	9610090 96	610090	< 0.020	< 0.020	NA	< 0.020	96%	70%	130%	88%	70%	130%	NA	60%	140%
Carbon Tetrachloride	9610090 96	610090	< 0.020	< 0.020	NA	< 0.020	85%	70%	130%	94%	70%	130%	NA	60%	140%
Benzene	9610090 96	610090	< 0.020	< 0.020	NA	< 0.020	88%	70%	130%	87%	70%	130%	NA	60%	140%
Trichloroethene	9610090 96	610090	< 0.020	< 0.020	NA	< 0.020	99%	70%	130%	74%	70%	130%	NA	60%	140%
Tetrachloroethene	9610090 96	610090	< 0.050	< 0.050	NA	< 0.050	78%	70%	130%	71%	70%	130%	NA	60%	140%
Chlorobenzene	9610090 96	610090	< 0.010	< 0.010	NA	< 0.010	89%	70%	130%	79%	70%	130%	NA	60%	140%
1,2-Dichlorobenzene	9610090 96	610090	< 0.010	< 0.010	NA	< 0.010	94%	70%	130%	77%	70%	130%	NA	60%	140%
1,4-Dichlorobenzene	9610090 96	610090	< 0.010	< 0.010	NA	< 0.010	97%	70%	130%	85%	70%	130%	NA	60%	140%
O. Reg. 558 - Benzo(a) pyrene															
Benzo(a)pyrene	9610090 96	610090	< 0.001	< 0.001	NA	< 0.001	95%	70%	130%	94%	70%	130%	NA	70%	130%

Comments: When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

AGAT QUALITY ASSURANCE REPORT (V1)

Page 12 of 16



Quality Assurance

CLIENT NAME: GHD LIMITED
PROJECT: 11181273-E2 (PO#73513391)
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

AGAT WORK ORDER: 18Z394508
ATTENTION TO: LUKE LOPERS
SAMPLED BY:Steven Wheeler

Trace Organics Analysis (Continued)															
RPT Date: Oct 15, 2018 DUPLICATE							REFERE	NCE MA	TERIAL	METHOD	BLANK	SPIKE	MAT	KE	
PARAMETER	R Batch Sample Dup	Dup #1	Dup #2	RPD	Method Blank	Measured	Acceptable Limits		Recovery	Lin	ptable nits	Recovery	Lin	ptable nits	
		la la					Value	Lower	Upper]	Lower	Upper] ,	Lower	Upper

Flash Point Analysis

Flash point (Pensky Martin Closed 2424 butanol 35 35 0.0% 100% 80% 120%

Cup)

Comments: If the RPD value is NA, the results of the duplicates are under 5X the RDL and will not be calculated.



Method Summary

CLIENT NAME: GHD LIMITED

AGAT WORK ORDER: 18Z394508
PROJECT: 11181273-E2 (PO#73513391)

SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

SAMPLED BY:Steven Wheeler

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE					
Soil Analysis			·					
Antimony	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Arsenic	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Barium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Beryllium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Boron	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
		EPA SW 846 6010C; MSA, Part 3,						
Boron (Hot Water Soluble)	MET-93-6104	Ch.21	ICP/OES					
Cadmium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Chromium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Cobalt	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Copper	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Lead	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Molybdenum	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Nickel	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Selenium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Silver	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Thallium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Uranium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Vanadium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Zinc	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Chromium VI	INOR-93-6029	SM 3500 B; MSA Part 3, Ch. 25	SPECTROPHOTOMETER					
Cyanide	INOR-93-6052	MOE CN-3015 & E 3009 A;SM 4500 CN	TECHNICON AUTO ANALYZER					
Mercury	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS					
Electrical Conductivity	INOR-93-6036	McKeague 4.12, SM 2510 B	EC METER					
Sodium Adsorption Ratio	INOR-93-6007	McKeague 4.12 & 3.26 & EPA SW-846 6010C	⁶ ICP/OES					
pH, 2:1 CaCl2 Extraction	INOR-93-6031	MSA part 3 & SM 4500-H+ B	PH METER					
Arsenic Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Barium Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Boron Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Cadmium Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Chromium Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Lead Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Mercury Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Selenium Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Silver Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Uranium Leachate	MET-93-6103	EPA SW-846 1311 & 3010A & 6020A	ICP-MS					
Fluoride Leachate	INOR-93-6018	EPA SW-846-1311 & SM4500-F- C	ION SELECTIVE ELECTRODE					
Cyanide Leachate	INOR-93-6052	EPA SW-846-1311 & MOE 3015 & SM 4500 CN- I	TECHNICON AUTO ANALYZER					
(Nitrate + Nitrite) as N Leachate	INOR-93-6053	EPA SW 846-1311 & SM 4500 - NO3-	LACHAT FIA					
Analysis Start Date			N/A					
pH (Initial)	LAB 4025	EPA SW-846 1311	PH METER					
pH (Final)	LAB 4025	EPA SW-846 1311	PH METER					
Extraction Fluid	LAB-93-4025	EPA SW-846 1311	N/A					

Method Summary

CLIENT NAME: GHD LIMITED
PROJECT: 11181273-E2 (PO#73513391)
SAMPLING SITE:DuMaurier Avenue, Ottawa, ON

AGAT WORK ORDER: 18Z394508
ATTENTION TO: LUKE LOPERS
SAMPLED BY:Steven Wheeler

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE						
Trace Organics Analysis			1						
Flash point (Pensky Martin Closed Cup)	TO 2210	ASTM D93	Pensky Martin Closed Cup						
Naphthalene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Acenaphthylene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Acenaphthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Fluorene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Phenanthrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benz(a)anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Chrysene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benzo(b)fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benzo(k)fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benzo(a)pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Indeno(1,2,3-cd)pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Dibenz(a,h)anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benzo(g,h,i)perylene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
2-and 1-methyl Naphthalene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Moisture Content	ORG-91-5106	EPA SW-846 3541 & 8270	BALANCE						
Chrysene-d12	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS						
Benzo(a)pyrene	ORG-91-5114	EPA SW846 3540 & 8270	GC/MS						
Polychlorinated Biphenyls	ORG-91-5112	Regulation 558, EPA SW846 3510C/8082	GC/ECD						
Decachlorobiphenyl	ORG-91-5112	EPA SW846 3510C/8082	GC/ECD						
Vinyl Chloride	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
1,1 Dichloroethene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Dichloromethane	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Methyl Ethyl Ketone	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Chloroform	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
1,2-Dichloroethane	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Carbon Tetrachloride	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Benzene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Trichloroethene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Tetrachloroethene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Chlorobenzene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
1,2-Dichlorobenzene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
1,4-Dichlorobenzene	VOL-91-5001	EPA SW-846 5230B & 8260	(P&T)GC/MS						
Toluene-d8	VOL-91-5001	EPA SW-846 5230B & 8260 (P&T)GC/MS							



Laboratories IMel

18/10/09

16000

5835 Coopers Avenue Mississauga, Ontario L4Z 1Y2 **Laboratory Use Only**

Work Order #: 187394508

Cooler Quantity: Ole - on ice.

Ph: 905.712.5100 Fax: 905.712.5122 webearth.agatlabs.com

Chain of Custody Recor

Chain of Custody Recor	lease	se use Drinking Water Chain of Custody Form (potable water consumed by humans)											rival 1	Гетр	eratu	ıres:	10	.6	19.	31	10.1			
Report Information: Company: GHD Lts					(Plea	egulatory Requ	irements:		No R				eme	nt	Custody Seal Intact:									
Contact: Address: 179 (closinact Ottana, On 613 288 173	le Rd S	uste L	100		Regulation 153/04 Sewer Use Regulation 558 Table Indicate One Sanitary CCME								rnaı gula			Fime			equire					
Phone: Reports to be sent to: 1. Email: 2. Email: 4 13 288177 Lyke, Lope Steven. Wh		-com			Soil	Res/Park □ Agriculture Texture (Check One) □ Coarse	Stor	rm nte One	Objectives (P)						Rush TAT (Rush Surcharges Apply) 3 Business									
2. Email: Steven. Wh	eeler é	GOHD.	com		Fine MISA Indicate One								OR Date Required (Rush Surcharges May Apply):											
Project Information: Project: 1181273-E2 Site Location: Du Maurier Avenue, Ottana, on Sampled By: 4-even wheeler				_	Is this submission for a Report Guldeline on Certificate of Analysis Yes No Yes No							Please provide prior notification for rush TAT *TAT is exclusive of weekends and statutory holidays For 'Same Day' analysis, please contact your AGAT CPM												
AGAT Quote #: Please note: If quotation number is not provided, client will be billed full price for analysis.				Sa	ımple Matrix Leg	end	Ş	-	O. Reg										PCBs				127	
Invoice Information: Same as RPT MA- Bill To Same: Yes No Company: Contact: Address: Email:		GW O P S SD SW	Oil Paint Soil Sediment		Field Filtered - Metals, Hg, CrVI	s and Inorganics	stals 153 Metals (excl. Hydrides) de Metals 153 Metals (Incl. Hydride	ORPs: DBHWS DCI DCN	□SAR etals Scan	stc	Nutrients: OTP ONH, OTKN ONO, ONO, ONO, ONO,	es: ☐ voc ☐ BTEX ☐ THM	F1-F4			☐ Total ☐ Aroclors	Organochlorine Pesticides TCLP: M M&I OX VOCS		Flashpowt (TLLP)					
Sample Identification	Date Sampled	Time Sampled	# of Containers	Sam	nple itrix	Commen Special Instru		Y/N	Metals	All M	ORPs:	Full Metals (Regula	Nutrie I	Volatiles:	PHCs	ABNs	PAHS	PCBs: [Organ TCLP: D	Sewer Use	Fla		
BH1553-10-5-18	Oct, 5,18		2	9					X						1/8			X						COL
BH 2 555-10-5-18	11		2	9	2				X						Ú=			X					1	100
BH3553-10-5-18	(/		2	5				-	X						UA.			X						1,000
BH4452/3-10-5-16	11		2	15					X									X						
BH5 553 - 10-5-13	1/		2	5		<u> </u>			X									X						
BH3-10-5-18	11		5	5		1			X			\vdash						\times	-	>	4_	X		
															, iv					h			10	
												-			72						-			
												1												
Samples Relinquished By (Print Name and Sign):	0 0	Date C LC	Des ()	ne /	~	Samples Received By (Pri	nt Name and Sigo):	4 1 4		_			Don	110	10	n	mio	ام د	~~					

Appendix F

Qualifications of Assessors



PROFILE

Mr. Lopers is an environmental engineer with over 12 years of experience in environmental engineering specializing in due diligence investigations. Mr. Lopers has extensive experience in Phase I and II Environmental Site Assessments; environmental remediation, and investigations; record of site condition submissions; asset inventory, designated substance surveys and abatement projects; environmental expertise on legal issues; and coordination of various monitoring programs (groundwater, surface water, air).

Mr. Lopers has participated in various Property Condition and Building Envelope mandates at various residential and commercial properties throughout Ontario.

Mr. Lopers has a strong commitment to health and safety, having experience leading a regional health and safety committee as a certified employee representative. Mr. Lopers has extensive training including OSHA 40-hour HAZWOPER, ASP Health and Safety on Construction Sites in Quebec, Ontario Working at Heights, Emergency First Aid/CPR and WHMIS.

CONTACT

EMAIL:

Luke@Lopers.ca

LUKE LOPERS

Principal

LOPERS & ASSOCIATES

EDUCATION

University of Waterloo,

B.A.Sc., Honours Environmental Engineering

Management Science Option Designation - 2002 - 2008

PROFESSIONAL EXPERIENCE

Lopers & Associates, Principal, Project Manager, Senior Environmental Engineer

Ottawa, Ontario - 2020–Present

Responsible for the management, coordination, supervision, completion and delivery of Phase I/1 and II/2 Environmental Site Assessments, Environmental Remediation Programs, Environmental litigation support, Designated Substance Surveys, scope of work development, cost estimates and proposals

GHD Limited, Project Manager, Senior Environmental Engineer Ottawa, Ontario - 2013–2020

Responsible for the management, senior technical review, coordination, supervision, completion and delivery of Phase I/1 and II/2 Environmental Site Assessments, Environmental Remediation Programs, Environmental litigation support, Designated Substance Surveys, scope of work development, cost estimates and proposals Office Safety Captain and Joint Health and Safety Committee team leader

Paterson Group Inc., Project Manager, Environmental Engineer Ottawa, Ontario - 2009–2013

Responsible for supervision, completion and review for Phase I/1 and II/2 Environmental Site Assessments, Environmental Remediation Programs, Designated Substance Surveys

NEXT Environmental Inc., Site Investigation Staff

Burnaby, British Columbia - 2008–2009

Responsible for fieldwork and reporting for Stage/Phase I and II Environmental Site Assessments, Environmental Remediation Programs

PROFESSIONAL DESIGNATIONS

Licensed Professional Engineer (P.Eng.) with Professional Engineers Ontario (PEO) since 2012

Qualified Person (QP), Environmental Site Assessments with Ontario Ministry of the Environment, Conservation and Parks

PROJECT EXPERIENCE

Environmental Site Assessments

Project Engineer/Manager
Phase 1 Environmental Site
Assessment | Various Clients |
Ontario, Quebec and British
Columbia | 2006-2020

Project Engineer/Manager
Phase Two Environmental Site
Assessments | Various Clients |
Various Locations | 2008-2020

Project Manager
Phase One, Phase Two
Environmental Site
Assessments, Environmental
Delineation Quality Assurance
Program | Costco Wholesale |
Ottawa, ON | 2014-2019

Environmental Remediation Programs

Project Engineer
Underground Fuel Storage
Tank Removals and
Environmental Remediation
Programs in Vicinity of Active
Underground Services |
Ottawa, ON | 2010, 2012

Project Engineer/Manager for Phase I Environmental Site Assessments in support of acquisition/divestiture/regulatory requirements for various properties in Ontario, Quebec and British Columbia, including the following:

- Canadian Tire Retail Store and Gas Bar, CTR 417 2560 Princess Street, Kingston, Ontario
- Former Automotive Dealership and Service Garage, North Vancouver, British Columbia
- Former Philips Cable Plant, Brockville, Ontario
- Former Cornwall Cotton Mill, Cornwall, Ontario
- Retail Fuel Outlet and Automotive Service Garage, Ottawa, Ontario
- Jack Garland Airport Land, North Bay, Ontario
- Various Commercial/Residential Properties, Ontario and British Columbia
- Various Residential Properties, Ontario, Quebec and British Columbia
- Rochester Heights (811, 818 Gladstone Avenue), Ottawa, Ontario

Project Engineer/Manager for the following field investigation and/or regulatory reporting requirements for Phase II ESAs and other Site Investigations:

- Proposed Canadian Tire Development, CTR 693P Terry Fox Drive at Eagleson Road, Stittsville, Ontario
- Former Retail/Private Fuel Outlets, Ottawa/North Bay/Vancouver, Canada
- Operational/Former Industrial Facilities, Ottawa/Cornwall/Sarnia/Brockville/Gananoque, Ontario
- Existing Dry Cleaning Facilities, Ottawa/Arnprior, Ontario
- Automotive Service Garages, Ottawa/Vancouver, Canada
- Various Commercial/Residential Properties, Eastern Ontario
- Tetrachloroethylene Groundwater Plume, Commercial Property, Ottawa, Ontario
- Rochester Heights (811, 818 Gladstone Avenue), Ottawa, Ontario

Project Manager for the completion of a Phase One ESA for the potential acquisition of a commercial property. Upon discovery of APECs at the Site and significant data gaps in previous investigations, completed a Phase Two ESA to evaluate soil and groundwater quality at the Site. Further oversight of original owner's environmental consultants was completed to ensure adequate delineation and characterization of a dNAPL groundwater plume at the Site, present at significant depths in shale bedrock, which originated as a result of a former on-Site dry-cleaning operation.

Project Engineer for removal of underground heating oil storage tanks adjacent to residential buildings. Completed excavation supervision of contaminated soil around and below active underground services, including hydro, water and natural gas infrastructure at residential properties. Activities included oversight of removal of petroleum, impacted soil, and field screening and collection of confirmatory soil and groundwater samples for petroleum hydrocarbon analysis. Prepared Phase I, II and III Environmental Site Assessment reports.

Project Engineer Retail Fuel Outlet Decommissioning and Remediation | Ottawa, ON | 2012

Project Engineer/Manager Former Fuel Outlet Investigation and Remediation | Merrickville, ON | 2016-2017

Record of Site Conditions

Project Manager/Engineer Residential Redevelopment | Environmental Remediation Program and Record of Site Condition Submission | Ottawa | 2015

Project Manager/Engineer
Industrial Development |
Environmental Assessment and
Record of Site Condition
Submission | Township of
Edwardsburgh/Cardinal | 2015

Excess Soil Management

Project Engineer/Manager Management of Excess Soil | CTREL, Brigil, Ottawa Community Housing Corporation | Ottawa and Pembroke, Ontario | 2016, 2018

Designated Substance Surveys

Project Manager

Designated Substance Surveys and Hazardous Building Materials Assessment | Ottawa, Pembroke, Southeastern Ontario | 2010-2020

Environmental Litigation Support

Project Manager, Field Engineer, Expert Witness Ottawa, Ontario | 2014-2020 Project Engineer for UST removal and confirmatory soil sampling at former ESSO gas station in Ottawa, Ontario. Activities included oversight of removal of USTs and product lines, oversight of removal of petroleum-impacted soil and groundwater encountered and backfilling operations, and field screening and collection of confirmatory soil and groundwater samples for petroleum hydrocarbon analysis.

Project Engineer for confirmatory soil and groundwater sampling following UST removal at former Shell gas station. Activities included oversight of removal of petroleum-impacted soil, pumping of groundwater encountered and backfilling operations, and field screening and collection of confirmatory soil and groundwater samples for petroleum hydrocarbon analysis. Additional borehole/monitoring well drilling also completed.

Project Manager for delineation of soil contamination and groundwater sampling for a former automotive garage and gas station property in Ottawa, Ontario. Presented and implemented remedial action plan to remediate on-Site contamination. Directed staff in collection of post remediation confirmatory soil and groundwater samples for contaminants of concern. Prepared remediation closure report and record of site condition supporting documentation for submission to the Ministry of the Environment and Climate Change.

Project Manager for environmental assessments for a proposed industrial business park, in an existing industrial area within the Township of Edwardsburgh/Cardinal, Ontario. Prepared environmental assessment reports and record of site condition supporting documentation for submission to the Ministry of the Environment and Climate Change.

Project Engineer/Manager for sampling, analytical testing, development of soil management plans and monitoring during removal of excess soil generated as part of construction activities, including the following properties/facilities:

- Rochester Heights (811, 818 Gladstone Avenue), Ottawa, Ontario
- Residential redevelopment, 121 Parkdale Avenue, Ottawa, Ontario
- CTR 079, 1104 Pembroke Street East, Pembroke, Ontario
- CTR 297, 2010 Ogilvie Road, Ottawa, Ontario

Project Manager for asbestos containing material (ACM) surveys, designated substance surveys (DSSs), Hazardous Building Materials Assessments (HBMAs) or mould assessments at the following sites:

- DSSs at various municipal facilities for the City of Pembroke, Pembroke, Ontario. Preparation of Asbestos Management Plan.
- HBMAs at various institutional buildings for the Catholic District School Board of Eastern Ontario, Southeastern Ontario.
- DSSs and ACM surveys at various residential, buildings (dwellings and apartment buildings) for private residential clients, Ottawa, Ontario.
- DSS and abatement oversight during demolition, residential buildings (townhouses) for Ottawa Community Housing Corporation, 818 Gladstone Avenue, Ottawa, Ontario.

Project Manager, Field Engineer and Expert Witness for a fuel spill, remediation program, groundwater monitoring program and litigation review for redevelopment of a residential property adjacent to a central heating plant at an institutional facility.

Education

BEng Geological Engineering, École Polytechnique de Montreal, Montreal, Quebec, 1990

MSc Geophysics, University of British Columbia, Vancouver, British Columbia, 1983

BSc Geophysics, Honours, University of British Columbia, Vancouver, British Columbia, 1980

Certifications

Registered as PMP with Project Management Institute since 2012, requalified in 2018

Qualified Person (QP) for Environmental Site Assessments with Ontario Ministry of Environment and Conservation and Parks

Professional Affiliations

Licensed as P.Eng. with the Professional Engineers of Ontario (PEO) since 1994

Licensed as Ing. with l'Ordre des ingénieurs du Québec (OIQ), 1992

Licensed as P.Eng. with NAPEG (NWT and Nunavut), since 2009.

Licensed as P.Eng with Engineers Yukon since 2018

Federal Clearance Level

Secret ID # 95251065

DON PLENDERLEITH

Senior Environmental Engineer and Project Manager

PROFESSIONAL SUMMARY

Mr. Plenderleith has been an environmental engineer for 30 years. From 1990 to 2000 he worked at specialty firms in Montreal and Ottawa where he gained field and reporting experience in site assessment and remediation of retail fuel outlets and railway yards. In 1991 and 1992 he worked on a CIDA sponsored project to assess additional water resource potential in two provinces in Indonesia. He worked for Golder for 19 years on projects in Ottawa, the North and overseas.

His expertise covers all steps in contaminated site management: Phase I, II and III environmental site assessments (ESAs), risk assessments, remedial options evaluations, remedial action plans, tender plans and specifications, remediation project oversight, long-term monitoring and project closure. He has largely concentrated on federal sites since 2002 and was Golder's initial point of contact on the Environmental Standing Offer Agreement with PSPC in the National Capital over that time.

Don led Golder's national client service team for Federal government and was responsible to Golder's management for maintaining strong relations with the federal government. Locally, he provided project management and technical direction of a variety of environmental projects from the Ottawa office. Don mentored several junior professionals. His site portfolio included: military bases, Northern sites, navigational sites, correctional facilities, research labs, commercial buildings and Canadian embassies abroad. On several multi-year projects (Kingston Penitentiary and Connaught Ranges landfill) he directed all steps of site management from initial investigations, through to site closure.

Don is equally experienced at providing strategic and portfolio-level assistance to clients as well as site-specific level work. He has written contaminated sites management plans for several federal Departments. He helped to develop components of the FCSAP project manager's tool kit and has trained federal project managers in its use. He has provided program-level assistance to the FCSAP Secretariat for funding demand forecasting and long-term strategy and risk management. For nine years he led a multi-disciplinary team that performed contaminated site liability peer reviews for the Office of the Auditor General of Canada.

Don completed his engineering degree in French and is licensed to practice in Quebec. He frequently coordinates the French language component at bilingual meetings and workshops.

PROJECT EXPERIENCE - STANDING OFFER MANAGER

Public Services and Procurement Canada, National Capital Region, Environmental Engineering Standing Offer (2002-2019). Don managed Golder's Environmental Standing Offer Agreement (SOA) with PSPC in the National Capital Region from 2002 to 2019. He was the first point of contact with PSPC for new call-ups. He formed project teams from the approved resources and reviewed the work plans under each call-up. He was responsible and accountable for Golder's overall project performance to PSPC.

PROJECT EXPERIENCE - SENIOR PROJECT MANAGER

Phase I, II, and III and Remediation at Pittsburgh Institution and Kingston Penitentiary for PSPC/CSC near Kingston, Ontario Environmental Site Assessment, Remediation Planning and Implementation for the Pittsburgh Institution and Kingston Penitentiary, Kingston, Ontario from 2007 to 2015 - Don was the Senior Project Manager and project reviewer for the Phase I, II and III of contaminated sites on two similar projects at these federal penitentiaries. Don performed project management and provided technical direction during the full suite of services from site assessment through to remediation. Federal project management tools, and FCSAP technical tools (GOST) were used to assist with procedural compliance. Don assisted PSPC with the tender specification for both remediation projects and performed on-site supervision during the fast-track remediation work at Pittsburgh. Don also performed senior review of the draft and final reports.

Peer Review and Liability Review of US Steel Site in Hamilton Harbour for PSPC and Transport Canada (July-August 2016) Don was the Senior Project Manager for a Peer Review of reports pertaining to the US Steel site on Hamilton Harbour that the Hamilton Port Authority (HPA) was considering purchasing. TC requested the peer review and liability review in its oversight role over the HPA. Don brought a senior expert in at steel industry at Golder onto the project team. With his input some important gaps in the previous site assessments, management plans and liability estimates were identified to TC.

Contaminated Site
Reporting and Review for
Department of National
Defence Ottawa, Ontario,
Canada

Don has managed several projects for DND's Director General Environment, related to the financial reporting of DND's contaminated sites. He managed the EcoNet validation project in 2006, in which the systems and procedures by which site cost and liability information are input to DND's Contaminated Site database, Econet. Several of DND's major projects being run out of headquarters were reviewed in that exercise. In 2008 he assisted DND by producing the 2008 update of their Contaminated Sites Management Plan (CSMP) for Treasury Board submission. Nine divisional CSMPs were reviewed, summarized and incorporated into the departmental CSMP.

PROGRAM LEVEL WORK – FEDERAL CONTAMINATED SITES

Project Management Tools for Contaminated Sites, Ottawa, Ontario, Canada Mr. Plenderleith developed two of the FCSAP Project Management Tools: Status Reporting and Project Risk Management. He has provided training in the tools to federal project managers country-wide. He has delivered training sessions at RPIC National Contaminated Sites workshops on several occasions on the PM Tools, the Sustainable Development Tool (SDAT), and Guidance Tool for Selection of Technologies Tools (GOST).

Assistance to FCSAP for program-level Risk Management, PWGSC/ECCC Ottawa, Ontario

Don has led a team at Golder that provided assistance to the FCSAP Secretariat from 2013 to 2019 in the areas of cost projections for funding demand estimates. He devised a method of projecting the costs of unassessed sites based on closure costs of similar sites. This tool was used to estimate the funding demand for FCSAP Phase III and past Phase III. Don assisted the Secretariat with Long-Term Strategic planning for FSCAP post 2020 when the 15-year program is due to sunset.

Secondments to Federal Departments

Mr. Plenderleith has been seconded from Golder to the Department of Foreign Affairs and International Trade (now Global Affairs Canada "GAC") on three occasions to develop their Contaminated Sites Management Plans and to fill in while GAC was staffing their full-time environmental engineer position. Through these secondments he has developed a greater understanding of the role of federal custodians in managing their programs.

PROJECT EXPERIENCE - NORTHERN SITES

DEW Line Site Monitoring, Baffin Region, DND

(2015-19)

Mr. Plenderleith was the project director of Golder's DEW Line Monitoring contract with DND from four years 2015 to 2019. He was responsible for overall program quality and liaison with the client and management of Inuit subcontractors. The project was multi-disciplinary, involving geotechnical and environmental components. Mr. Plenderleith has developed a very positive working relationship with the hamlet of Qikiqtarjuaq and the Inuit staff from that community, many of whom have returned to work with Golder every year. All Inuit Participation Targets were exceeded.

Tundra Mine Remediation Monitoring PSPC/INAC (2016-2018)

Don was the Senior project director for Golder's Remediation Monitoring of Tundra Mine (NWT) for PSPC and INAC. This project is multi-disciplinary involving surface water and groundwater environmental monitoring and aquatic monitoring for the final stages of the remediation of Tundra Mine. Don has reviewed the monthly and annual monitoring reports produced for the Water Licence. His earlier experience with the RAP for Tundra has been valuable on this project.

Remedial Options Review and Remedial Action Planning Former Water Tanker Base, Inuvik Airport, NWT 2010-12 From 2010 to 2012, Mr. Plenderleith was the technical director for the Phase III ESA detailed site assessment and remediation planning of the former Water Tanker Base at the Inuvik Airport in NWT. The work included determining the contaminants of concern, delineation of contaminated soil and seasonal groundwater areas, and assessing remedial options. The remedial action plan reviewed chemical oxidation and removal & disposal options within the constraints of northern work season, and the distance to a disposal facility. Descriptions, costs, advantages and limitations were provided for several options. GNWT performed the remediation with own forces.