

OPSD 219.110

SILT FENCE BARRIER

COMMENCED. SILT FENCE TO BE MAINTAINED UNTIL VEGETATION IS ESTABLISHED OR UNTIL START OF SUBSEQUENT PHASE.
2. SILT SACK TO BE PLACED AND MAINTAINED UNDER COVER OF ALL CATCHBASINS. GEOTEXTILE SILT SACK IN STREET CBs TO REMAIN UNTIL ALL CURBS ARE CONSTRUCTED. GEOTEXTILE FABRIC IN RYCBs TO REMAIN UNTIL VEGETATION IS ESTABLISHED. ALL CATCHBASINS TO BE REGULARLY INSPECTED AND CLEANED, AS NECESSARY, UNTIL SOD AND CURBS ARE CONSTRUCTED.
3. CONTRACTOR TO PROVIDE DETAILS ON LOCATION(S) AND DESIGN OF DEWATERING TRAP(S) PRIOR TO COMMENCING WORK. CONTRACTOR ALSO RESPONSIBLE FOR MAINTAINING TRAP(S) AND ADJUSTING SIZE(S) IF DEEMED REQUIRED BY THE ENGINEER DURING CONSTRUCTION.
4. CONTRACTOR TO PROTECT EXISTING CATCHBASINS WITH FILTER CLOTH UNDER THE COVERS TO TRAP SEDIMENTATION. REFER TO IDENTIFIED STRUCTURES.

STM STRUCTURE TABLE						
NAME	RIM ELEV.	INVERT IN	INVERT IN AS-BUILT	INVERT OUT	INVERT OUT AS-BUILT	DESCRIPTION
MH1	82.15	W80.475		NE80.045		1200mmø OPSD-701.010
MH2	82.20	SW79.935 SE79.909		NW79.909		1200mmø OPSD-701.010
RYCB1	82.90			S81.450		OPSD-705.010

SAN STRUCTURE TABLE						
NAME	RIM ELEV.	INVERT IN	INVERT IN AS-BUILT	INVERT OUT	INVERT OUT AS-BUILT	DESCRIPTION
мн1 А	83.40	NW80.260		SE80.215		1200mmø OPSD-701.010

<u>LEGEND</u>	22222		
	- PROPERTY LINE		EXISTING TRAFFIC SIGN
	- FUTURE WIDENING	□ СВ	EXISTING CATCH BASIN
F.F.= 80.50	FINISHED FLOOR ELEVATION	• AD1	PROPOSED AREA DRAIN
DC	PROPOSED DEPRESSED CURB		
\overline{M}	WATER METER	MH	EXISTING COMBINED MANHOLI
	(SEE MECH. DRWG. FOR EXACT LOCATION)	300¢ COMBINED	EXISTING COMBINED SEWER
RM	REMOTE WATER METER (SEE MECH. DRWG, FOR EXACT LOCATION)	200¢ STORM	PROPOSED STORM SEWER
Į.	SIAMESE CONNECTIONS	4000 WATERMAIN	EXISTING WATERMAIN
77	(SEE MECH. DRWG. FOR EXACT LOCATION)	_2000 SANITARY	PROPOSED SANITARY SEWER
GG	- PROPOSED GAS SERVICE	1500 WATERMAIN	PROPOSED WATERMAIN
H	- EXISTING UNDERGROUND HYDRO		PROPOSED VALVE AND
	EXISTING OVERHEAD HYDRO	~	VALVE BOX
НМН	EXISTING HYDRO MANHOLE	⊗ 400V&VC	PROPOSED VALVE AND VALVE CHAMBER
O H/SL	EXISTING HYDRO AND LIGHT POLE	\ -FH	EXISTING FIRE HYDRANT
— — — G — — — —	- EXISTING GAS MAIN	SN	EXISTING SIGN
— — — B — — — —	- EXISTING BELL		EXISTING WATER VALVE
○вмн	EXISTING BELL MANHOLE	o SP	EXISTING WATER SERVICE STANDPOST
O ТМН	EXISTING TRAFFIC MANHOLE	◆ VB	EXISTING VALVE BOX
O TL	EXISTING TRAFFIC LIGHT	_	PROPOSED LIMITS OF
	PROPOSED RETAINING WALL		UNDERGROUND PARKING

WATER SERVICE IS REQUIRED, USE THERMAL INSULATION AS PER CITY STANDARDS WHEN COVER IS LESS THAN

4. ALL SERVICE LATERAL AND SURFACE RESTORATION WORK IN ACCORDANCE WITH CURRENT CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.

5. FULL PORT BACKWATER VALVE IS REQUIRED ON BOTH THE SANITARY AND STORM SERVICE CONNECTIONS.

6. WATER SERVICE CHLORINATION AND TESTING TO BE COMPLETED BY CITY

7. PROPOSED BUILDING INFORMATION TAKEN FROM EVOQ ARCHITECTS DRAWINGS.

8. AN EROSION AND SEDIMENTATION CONTROL PLAN WILL BE IMPLEMENTED ON THIS SITE. AS A MINIMUM THAT PLAN WILL INCLUDE A LIGHT DUTY SILT FENCE BARRIER
TO OPSD STANDARD 219.110 SURROUNDING THE SITE WHERE PRACTICAL AND SILT SACKS FITTED UNDER EXISTING STREET CATCH BASINS.

9. ALL SHOWN UTILITIES ARE APPROXIMATE AND ARE TO BE FIELD VERIFIED BY CONTRACTOR, ANY DISCREPANCIES ARE TO BE REPORTED TO IBI GROUP PRIOR TO CONTRACTOR MOBILIZING TO SITE.

10. CONTRACTOR RESPONSIBLE TO SUPPORT EXISTING UTILITIES THAT MAY BE AFFECTED DURING CONSTRUCTION

11. EXISTING CURBS AND SIDEWALKS ARE TO BE REMOVED AND REPLACED AS NOTED

BEST MANAGEMENT PRACTICES, TO PROVIDE FOR PROTECTION OF THE AREA DRAINAGE SYSTEM AND THE RECEIVING WATER ACTIVITIES. THIS INCLUDES LIMITING THE AMOUNT OF EXPOSED SOIL, USING FILTER CLOTH UNDER THE GRATES OF CATCHBASINS AND MANHOLES AND INSTALLING SILT FENCES AND EFFECTIVE SEDIMENT TRAPS. THE CONTRACTOR ACKNOWLEDGES THAT FAILURE TO IMPLEMENT APPROPRIATE EROSION AND SEDIMENT CONTROL MEASURES MAY BE SUBJECT TO PENALTIES IMPOSED BY ANY APPLICABLE REGULATORY AGENCIES.

13. BEARINGS SHOWN HEREON AND ELEVATIONS ARE INDICATED ON THE LOT SURVEY BY ANNIS, O'SULLIVAN, VOLLEBEKK LTD. DATED DECEMBER 24,

2019. 14. FOR GEOTECHNICAL INFORMATION SEE REPORT PG5211-1 BY PATERSON GROUP

15. CLAY SEAL TO BE INSTALLED IN SERVICE TRENCHES BETWEEN CONNECTION POINT AND CAP.

16. THE EXISTING BUILDING SERVICES ARE TO BE FIELD LOCATED AND DECOMMISSIONED AS PER CURRENT CITY STANDARDS. THE WATER SERVICES ARE TO BE BLANKED AT THE WATERMAIN BY CITY FORCES AS PART OF THE WATER PERMIT. EXISTING SEWERS ARE TO BE CAPPED AT THE PROPERTY LINE BY THE CONTRACTOR TO THE SATISFACTION OF THE CITY'S SEWER OPERATIONS STAFF.

LIGHT DUTY SILT FENCE AS PER OPSD-219.110 SILT SACK PLACED UNDER EXISTING CB COVER SEE C-010, FOR NOTES, LEGEND, CB TABLE, AND DETAILS REVISED PER ARCHITECT COORDINATION T.R.B. REVISED AS PER NEW SITE PLAN REVISED AS PER CITY COMMENTS REVISIONS







IBI GROUP 400 – 333 Preston Street Ottawa ON K1S 5N4 Canada tel 613 225 1311 fax 613 225 9868 ibigroup.com

Project Title

1995 CARLING AVENUE





Drawing Title LEGEND, NOTES, REMOVÁLS, AND SEROSION CONTROL PLAN REMOVÁLS, AND

1:200

Design	Date		
J.B.	APRIL 2020		
Drawn	Checked		
D.P.S./J.B.	T.R.B.		
Project No.	Drawing No.		
124829	C-010		