# 4159 Obsidian Street Transportation Impact Assessment

Step 1 Screening Report
Step 2 Scoping Report
Step 3 Strategy Report

### Prepared for:

Mattamy Homes Ltd. 50 Hines Road, Suite 100 Ottawa ON K2K 2M5

#### Prepared by:



August 2025

PN: 2025-011

# Table of Contents

1		Scre	ening	1
2		Exist	ing and Planned Conditions	1
	2.1		pposed Development	
	2.2		sting Conditions	
	2.7	2.1	Area Road Network	
	2.2	2.2	Existing Intersections	
		2.3	Existing Driveways	
		2.4	Cycling and Pedestrian Facilities	
		2.5	Existing Transit	
	2.2		Existing Area Traffic Management Measures	
		2.7	Existing Peak Hour Travel Demand	
		2.8	Collision Analysis	
	2.3		inned Conditions	
		3.1	Changes to the Area Transportation Network	
		3.2	Other Study Area Developments	
3	۷.۰		y Area and Time Periods	
	3.1		ıdy Area	
	3.2		ne Periods	
	3.3		rizon Years	
4	3.3		elopment-Generated Travel Demand	
-	4.1		ode Shares	
	4.1		p Generation	
	4.2		p Distribution	
	4.3 4.4		p Assignment	
_	4.4		nption Review	
6			elopment Design	
-	6.1		sign for Sustainable Modes	
	6.2		culation and Access	
7	0.2			
•	7.1		ing	
	7.1		rking Supply	
8			ndary Street Design	
9	0.4		sportation Demand Management	
	9.1		ntext for TDM	
	9.2		ed and Opportunity	
	9.3		M Program	
10			mary of Improvements Indicated and Modifications Options	
11	L	Conc	clusion	21
Li	ist o	f Fig	gures	
	-		a Context Plan	
Fi	gure 2	2: Cor	ncept Plan	



Figure 3: Existing Driveways	4
Figure 4: Study Area Pedestrian Facilities	5
Figure 5: Study Area Cycling Facilities	5
Figure 6: Existing Pedestrian Volumes	6
Figure 7: Existing Cyclist Volumes	6
Figure 8: Existing Study Area Transit Service	7
Figure 9: Existing Study Area Transit Stops	7
Figure 10: Existing Traffic Counts	8
Figure 11: Study Area Collision Records, 2018-2022	10
Figure 15: New Site Generated Auto Volumes	16
Table of Tables	
Table 1: Intersection Count Date	8
Table 2: Existing Intersection Operations	9
Table 3: TRANS Trip Generation Manual Recommended Mode Shares – South Nepean	13
Table 4: Proposed Development Mode Shares	14
Table 5: Trip Generation Person Trip Rates by Peak Period	14
Table 6: Person Trip Generation by Peak Period	14
Table 7: Trip Generation by Mode	14
Table 8: OD Survey Distribution – South Nepean	15
Table 9: Trip Assignment	15
Table 10: Exemption Review	16
Table 11: Boundary Street MMLOS Analysis	19

# List of Appendices

Appendix A – TIA Screening Form and Certification Form

Appendix B – Turning Movement Count Data

Appendix C – Synchro Intersection Worksheets – Existing Conditions

Appendix D – Realigned Greenbank Road Preliminary Design

Appendix E – TDM Checklist

Appendix F – Turning Templates

Appendix G – Adjacent Phase Site Plan (3718 Greenbank Road)

Appendix H – MMLOS Worksheet



## 1 Screening

This study has been prepared according to the City of Ottawa's 2017 Transportation Impact Assessment (TIA) Guidelines, incorporating the 2023 Revision to Transportation Impact Assessment Guidelines. Accordingly, a Step 1 Screening Form has been prepared and is included as Appendix A, along with the Certification Form for the TIA Study PM. As shown in the Screening Form, a TIA is required, and this study has been prepared to support site plan application.

# 2 Existing and Planned Conditions

#### 2.1 Proposed Development

The development site is located at 4159 Obsidian Street, and it is currently zoned as General Mixed-Use Zone (GM[2800] H(14.5)) and is proposed to be rezoned as residential. The site will be comprised of approximately 90 stacked townhome units, 119 vehicular parking spaces (16 residual spaces located within the previous phase) and 48 bicycle parking spaces. Vehicular access is proposed on Obsidian Street through the previous phase to the north (3718 Greenbank Road). The anticipated full build-out horizon is 2028 with construction occurring in a single phase. The development is within the Barrhaven South Urban Expansion Area Community Design Plan. Figure 1 illustrates the study area context. Figure 2 illustrates the proposed concept plan.





Figure 1: Area Context Plan

Source: http://maps.ottawa.ca/geoOttawa/ Accessed: February 28, 2025





#### 2.2 Existing Conditions

#### 2.2.1 Area Road Network

Greenbank Road: Greenbank Road is a City of Ottawa arterial road north of Barnsdale Road, with a two-lane crosssection. North of Kilbirnie Drive, a sidewalk and a bike lane are present on the east side of the road, and a multi-use pathway is present on the west side of the road. South of Kilbirnie Drive, there's a paved shoulder on the west side of the road and a gravel shoulder on the east side, and the road transitions to gravel shoulders on both sides. The posted limit is 60 km/h and the City protected right-of-way is 37.5 metres between Cambrian Road and Barnsdale Road.

Cambrian Road: Cambrian Road is a City of Ottawa arterial road, with a two-lane rural cross-section west of Seeley's Bay Street. A sidewalk is present on the north side of the road for approximately 180 metres west and 260 metres east of Apolune Street. The posted speed limit is 50 km/h, and the City-protected right-of-way is 37.5 metres.

Elevation Road: Elevation Road is a City of Ottawa collector road with a two-lane urban cross-section. Multi-Use Pathways are anticipated to be on both sides of the road. The unposted limit is assumed to be 40 km/h based on the traffic calming design of new neighbourhoods, and the right-of-way is 24.0 metres.

Apolune Street: Apolune Street is a City of Ottawa collector road with a two-lane urban cross-section including sidewalks on both sides. On-street parking is permitted on both sides of the road. The unposted speed limit is assumed to be 40 km/h based on the traffic calming design of new neighbourhoods, and the right-of-way is 24.0 metres.

Dundonald Drive: Dundonald Drive is a City of Ottawa collector road with a two-lane urban cross-section including sidewalks on both sides east of the future Realigned Greenbank Road. On-street parking is permitted on both sides of the road. To the west of the future Realigned Greenbank Road, Dundonald Road is currently under construction and is anticipated to include multi-use pathways on both sides of the road. The unposted speed limit is assumed to be 40 km/h based on the traffic calming design of new neighborhoods, and the measured right-of-way is 24.0 metres.

Kilbirnie Drive: Kilbirnie Drive is a City of Ottawa collector road with a two-lane urban cross-section including sidewalks on both sides of the road. On-street parking is permitted on both sides of the road. The unposted speed limit is assumed to be 50 km/h based on the Highway Traffic Act due to the age of the roadway prior to increase traffic calming measure implementation. The right-of-way is 22.0 metres.

Obsidian Street: Obsidian Street is a City of Ottawa local road with a two-lane urban cross-section including sidewalks on the east side of the road. On-street parking is permitted on both sides of the road. The unposted speed limit is assumed to be 30 km/h based on the traffic calming design of new neighbourhoods, and the right-of-way is 18.0 metres.

#### 2.2.2 Existing Intersections

The existing signalized area intersections within one kilometre of the site have been summarized below:

Cambrian Road

Apolune Street /Elevation Road at The intersection of Apolune Street/Elevation Road at Cambrian Road is currently an unsignalized intersection with stop control on the minor approach of Apolune Street/Elevation Road. All approaches consist of an auxiliary left-turn lane and a shared through/right-turn lane. No turn restrictions were noted.



Greenbank Road at Dundonald Drive


The intersection of Greenbank Road at Dundonald Drive is a signalized intersection. The northbound and southbound approaches each consist of an auxiliary left-turn lane, a through lane, and an auxiliary right-turn lane. The southbound approach additionally includes a two-way MUP crossing. The eastbound and westbound approaches each consist of a shared all-movements lane. No turn restrictions were noted.

Greenbank Road at Kilbirnie Drive

The intersection of Greenbank Road at Kilbirnie Drive is a signalized intersection. The northbound approach consists of an auxiliary left-turn lane, a through lane, a bike lane and an auxiliary right-turn lane, and the southbound approach consists of an auxiliary left-turn, a through lane, an auxiliary right-turn lane and protected two-way cycling crossing. The eastbound and westbound approaches each consist of an auxiliary left-turn lane and a shared through/right-turn lane. No turn restrictions were noted.

#### 2.2.3 Existing Driveways

Driveways to low-rise residential land uses exist on the west side of Obsidian Street within 200 metres north of the proposed site access. Figure 3 illustrates the existing driveways.



Source: <a href="http://maps.ottawa.ca/geoOttawa/">http://maps.ottawa.ca/geoOttawa/</a> Accessed: March 6, 2025


#### 2.2.4 Cycling and Pedestrian Facilities

Figure 4 illustrates the pedestrian facilities in the study area and Figure 5 illustrates the cycling facilities.

Sidewalks are provided along the east side of Obsidian Street and along the east side of Greenbank Road north of Kilbirnie Drive, and along the north of Cambrian Road for approximately 180 metres west and 260 metres east of Apolune Street. Sidewalks are also provided along both sides of Kilbirnie Drive, Apolune Street, Cambrian Road between Seeley's Bay Street and Greenbank Road, and Dundonald Drive east of the future Realigned Greenbank Road.



Cycling facilities include a bike lane is present on the east side of Greenbank Road north of Kilbirnie Drive, while a MUP is present on the west side. Multi-Use Pathways are also provided on both sides of Elevation Road. To the west of the future Realigned Greenbank Road, Dundonald Road is anticipated to include multi-use pathways on both sides of the road. Realigned Greenbank Road is also designated as a Cross-Town Bikeway.



Source: http://maps.ottawa.ca/geoOttawa/ Accessed: March 06, 2025





Figure 5: Study Area Cycling Facilities

Source: http://maps.ottawa.ca/geoOttawa/ Accessed: March 06, 2025

Pedestrian and cyclist volumes included in study area intersection counts, presented in Section 2.2.7, have been compiled and are illustrated in Figure 6 and Figure 7, respectively. The City of Ottawa notes that the collection data for active mode volumes may be lower than summer conditions, although this cannot be confirmed.





50

Figure 7: Existing Cyclist Volumes

#### 2.2.5 Existing Transit

Figure 8 illustrates the transit system map in the study area and Figure 9 illustrates nearby transit stops within 400 metres from the site. All transit information is from April 29, 2025 and is included for general information purposes and context to the surrounding area.

Within the study area, the route #75 travel along Kilbirnie Drive and River Mist Road. It is also noted that routes #671, #675, and #683 are high school routes that travel along Kilbirnie Drive and River Mist Road. The frequency of these routes within proximity of the proposed site based on April 29, 2025 service levels are:



Figure 8: Existing Study Area Transit Service

Paul Métivier

Perseus

Perseus

To Paul Métivier

Reparts

Complexe récréable

Recration Complexe récréable

Recreation Complexe récréable

Recration Complexe récréable

Recreation Complexe récr

Route #75 – 15-minute service in the peak period/direction and 30-minute service all-day

Source: <a href="http://www.octranspo.com/">http://www.octranspo.com/</a> Accessed: April 29, 2025




Figure 9: Existing Study Area Transit Stops

Source: <a href="http://www.octranspo.com/">http://www.octranspo.com/</a> Accessed: March 07, 2025

#### 2.2.6 Existing Area Traffic Management Measures

The existing area traffic management measures consist of bulb-outs framing parking on Kilbirnie Drive.



#### 2.2.7 Existing Peak Hour Travel Demand

Existing turning movement counts were acquired from the City of Ottawa for the existing study area intersections. Table 1 summarizes the intersection count dates.

Table 1: Intersection Count Date

Intersection	Count Date
Greenbank Road at Dundonald Drive	Wednesday, March 20, 2024
Greenbank Road at Kilbirnie Drive	Wednesday, March 20, 2024
Cambrian Road at Apolune Street/Elevation Road	Wednesday, March 23, 2022

Note: The count at Cambrian Road at Apolune Street/Elevation Road will be updated if future traffic analysis is required.

Figure 10 illustrates the existing traffic counts and Table 2 summarizes the existing intersection operations. The level of service for signalized intersections is based on volume to capacity ratio (v/c) calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection, and average delay for unsignalized intersections. Detailed turning movement count data is included in Appendix B and the Synchro worksheets are provided in Appendix C.

Figure 10: Existing Traffic Counts Apolune 52(73) 307(236) 9(0) Cambrian 73(80) 170(286) 1(0) 68(56) 32(41) 26(13) Dundonald Dundonald 112(117) 23(45) 218(245 103(84) Obsidian - 56(36) 8(39) 53(38) Kilbirnie Kilbirnie 85(103) 18(15) 85(73)



Table 2: Existing Intersection Operations

	•		AM Pe	ak Hour	,	PM Peak Hour			
Intersection	Lane	LOS	V/C	Delay (s)	Q (95 <sup>th</sup> )	LOS	V/C	Delay (s)	Q (95 <sup>th</sup> )
	EBL	Α	0.07	8.3	1.5	Α	0.07	8.2	1.5
	EBT/R	-	-	-	-	-	-	-	-
Cambrian Road at	WBL	Α	0.01	7.6	0.0	Α	-	0.0	0.0
Apolune	WBT/R	-	-	-	-	-	-	-	-
Street/Elevation	NBL	С	0.01	20.0	0.0	С	0.05	20.7	0.8
Road	NBT/R	В	0.01	13.1	0.0	В	0.01	10.0	0.0
Unsignalized	SBL	С	0.23	20.0	6.8	С	0.29	22.8	8.3
	SBT/R	В	0.16	11.5	4.5	В	0.11	10.7	3.0
	Overall	Α	-	4.0	-	Α	-	4.0	-
	EBL	Α	0.36	25.7	21.8	Α	0.43	27.8	26.7
	EBT/R	Α	0.32	10.1	13.1	Α	0.26	9.7	12.1
	WBL	Α	0.24	23.7	14.9	Α	0.17	23.2	12.0
	WBT/R	Α	0.20	9.2	9.5	Α	0.26	15.4	14.7
<b>Greenbank Road at</b>	NBL	Α	0.22	29.5	15.0	Α	0.31	30.5	20.2
Kilbirnie Drive	NBT	Α	0.16	12.7	29.8	Α	0.25	15.7	43.9
Signalized	NBR	Α	0.04	0.1	0.0	Α	0.07	0.2	0.0
	SBL	Α	0.18	29.5	12.2	Α	0.31	30.5	20.2
	SBT	Α	0.26	15.0	43.9	Α	0.29	16.1	51.0
	SBR	Α	0.10	1.6	3.4	Α	0.16	4.4	10.6
	Overall	Α	0.28	14.8	-	Α	0.33	16.5	-
	EB	В	0.69	28.2	48.1	С	0.73	33.3	56.5
	WB	Α	0.33	12.9	19.1	Α	0.27	13.4	18.4
	NBL	Α	0.33	33.8	20.9	Α	0.38	35.5	24.5
<b>Greenbank Road at</b>	NBT	Α	0.33	17.6	46.8	Α	0.36	19.1	56.6
<b>Dundonald Drive</b>	NBR	Α	0.02	0.1	0.0	Α	0.04	0.1	0.0
Signalized	SBL	Α	0.26	32.7	16.5	Α	0.30	35.1	18.8
	SBT	Α	0.28	17.4	39.6	Α	0.53	24.0	77.9
	SBR	Α	0.13	2.2	4.8	Α	0.19	5.5	11.3
	Overall	Α	0.50	19.8	-	Α	0.59	22.9	-
Notes: Saturation flow	w rate of 1800 v	/eh/h/lane			Delay = averag	e vehicle dela	v in seconds		

Notes: Saturation flow rate of 1800 veh/h/lane Queue is measured in metres

Peak Hour Factor = 0.90

Delay = average vehicle delay in seconds

m = metered queue

# = volume for the 95th %ile cycle exceeds capacity

During both the AM and PM peak hours, the study area intersections operate well. No capacity issues are noted.

#### 2.2.8 Collision Analysis

Collision data have been acquired from the City of Ottawa open data website (data.ottawa.ca) for five years prior to the commencement of this TIA for the surrounding study area road network. There are no collisions noted on the adjacent streets to the site during the 2018-2022 time period. Figure 11 illustrates the area collisions.





#### 2.3 Planned Conditions

#### 2.3.1 Changes to the Area Transportation Network

#### 2.3.1.1 Transportation Master Plan (2025)

The Transportation Master Plan (2025) includes a Capital Infrastructure Plan identifying transportation investment to support the forecasted growth and strategic connectivity and livability targets for the City. It also identifies committed projects, and a subset of priority projects that are expected to be implemented by 2046 based on current affordability assumptions. Area projects anticipated to impact travel in the study area that are included within the Capital Infrastructure Plan are:

- Transit Network
  - Priority
    - Median bus rapid transit from Barrhaven Centre Station to Kilbirnie Station (Southwest Transitway)
- Road Network
  - Committed
    - Greenbank Road Re-Alignment and Widening between Chapman Mills Drive and Cambrian Road
  - Priority
    - Greenbank Road Re-Alignment including new two-lane road from Cambrian Road to Kilbirnie Drive
    - Greenbank Road Re-Alignment including new two-lane road from Kilbirnie Drive to Barnsdale Road
  - Need-based



#### Barnsdale Road Widening from Highway 417 to Greenbank Road Extension

#### 2.3.1.2 Barrhaven South Urban Expansion Area Community Design Plan (CDP) (2018)

The Barrhaven South Urban Expansion Area CDP includes street hierarchy plan, pedestrian plan, transit facilities plan, and cycling facilities plan. The street hierarchy plan includes a westward extension of Kilbirnie Drive to the urban boundary. The planned 24.0 metre cross section of Kilbirnie Drive was envisioned to support pedestrian and cycling facilities and potentially be used as a local transit route. Cappamore Drive is identified as a new collector road in the CDP. It is designated as a potential local transit route and includes pedestrian and cycling facilities along the road. Streetscape elements are encouraged within the available boulevard space, with traffic calming and narrowing to reduce crossing distances noted along the collector and local roadways. Pathways linking neighbourhoods and providing connectivity to the park and ride are noted within the CDP.

#### 2.3.1.3 Cambrian Road Widening Environmental Assessment (EA)

The Cambrian Road Widening Environmental Assessment includes a four-lane cross section along Cambrian Road from Longfields Drive to the future Realigned Greenbank Road. Cross-section will include sidewalks on both sides and local connections to the adjacent eyebrow streets and signalized intersections. This EA has been approved by the Transportation Committee and City Council, but the widening is not considered in the City of Ottawa's Transportation Master Plan 2031 Affordable Road Network and therefore the timing of the widening is unknown.

#### 2.3.1.4 Greenbank Road Realignment and Southwest Transitway Extension

The Realigned Greenbank Road includes the design of a new 4-lane arterial roadway with a 2-lane separated median Bus Rapid Transit (BRT) and includes sidewalks and cycletracks on both sides of the road. The BRT will connect from Chapman Mills Drive to the new park-and-ride at Kilbirnie Drive. A park-and-ride facility is anticipated to be located at the southwest corner of the future intersection of the Kilbirnie Drive Extension and Realigned Greenbank Road to provide parking for approximately 400 vehicles at the terminus of the BRT line. Stations will be located at major intersections, including Darjeeling Avenue, Riverboat Heights, River Run Avenue, Cambrian Road, and Dundonald Drive. Local bus routes will also be able to enter and exit the Transitway corridor to service adjacent streets. The project also includes a new bridge over the Jock River. The recommended design plan from the Greenbank Road Realignment and Southwest Transitway Extension from Dundonald Drive to Barnsdale Road EA is included in Appendix D.

#### 2.3.2 Other Study Area Developments

Caivan's Ridge Phases 1-2 (3809 Borrisokane Road)

The proposed development application includes 279 townhouse units and 311 detached home units and is expected to generate 401 new AM peak hour two-way auto trips and 457 new PM peak hour two-way auto trips. The development is currently being constructed and will be assumed to be built out by 2026. (CGH Transportation, 2019)

#### Caivan's Ridge Phase 3-4 (3717Borrisokane Road)

The proposed development application includes 642 townhouse units and 61 detached housing units and is expected to generate 235 new AM peak hour two-way auto trips and 254 PM peak hour two-way auto trips. The development includes the extension of Dundonald Drive and Elevation Drive. The development is currently being constructed and will be assumed to be built out by 2026. (CGH Transportation, 2021)

#### Mattamy's Half Moon Bay South Phase 8 (3718 Greenbank Road)

The proposed development, located on the west of the Re-Aligned Greenbank Road corridor includes a mixture of 228 stacked townhouse units and is anticipated to generate 134 new AM peak hour two-way vehicle trips and 158 new PM peak hour two-way vehicle trips. The development is currently being constructed and will be assumed to be built out by 2026. (CGH Transportation, 2022)



#### 3809 Borrisokane Road

The proposed development includes a light industrial campus comprising three (3) one-storey and two (2) two-storey buildings. The development is anticipated to be built out by 2031 and is expected to generate 496 new AM peak hour two-way auto trips and 163 new PM peak hour two-way auto trips. (CGH Transportation, 2024)

#### Meadow's Phase 7-8 (3640 Greenbank Road)

The proposed development, which was named Phase 5 in the TIA, includes a plan of subdivision application. The concept plan considers a total of 221 townhouses and 125 detached homes. The development is expected to generate 294 new AM peak hour two-way vehicle trips and 334 new PM peak hour two-way vehicle trips. The development is currently being constructed and will be assumed to be built out by 2026. (CGH Transportation, 2018)

#### 3845 Cambrian Road

The proposed development consists of a gross floor area of 28,000 sq. ft. grocery store and a gross floor area of 5,430 sq. ft. retail store and is expected to generate 57 AM and 124 PM peak hour two-way auto trips. The TIA anticipated 2025 as the build-out year, however the construction has not yet begun, and it will be assumed to be built out by 2027. (CGH Transportation, 2023)

#### Metro Ontario Inc. (3831 Cambrian Road)

The proposed development includes a site plan application consisting of a 4,024-square-metre supermarket, an attached 929 square metre retail store, an 830 square metre retail building, and a 1,060 square metre mixed-use building. The development was initially anticipated to be built out by 2023 and to generate 146 AM and 110 PM peak hour two-way auto trips. This development will be assumed to be built out by 2025. (CGH Transportation, 2021)

#### 1045 Kilbirnie Drive

The proposed development consists of an elementary school and a childcare center with gross floor area of 4,781 square metres. The development is expected to generate 162 AM and 102 PM peak hour two-way auto trips and 22 AM peak hour school buses. The development is currently being constructed and will be assumed to be built out by 2026. (WSP, 2022)

#### Choice Properties (3850 Cambrian Road)

The proposed development includes a site plan application consisting of gross floor area of 17,000 sq. ft pharmacy and gross leasable area of 18,781 sq. ft retail buildings. The development was initially anticipated to be built out by 2024 and to generate 30 AM and 39 PM peak hour two-way auto trips. Construction is anticipated to commence in 2025, and the development will be assumed to be built out by 2026. (CGH Transportation, 2023)

#### Mattamy's Half Moon Bay West Phase 3

The proposed subdivision is situated within the Mattamy Development of Half Moon Bay West and includes 38 detached single-family homes, 190 townhomes, and a 0.43-hectare commercial block. The development is expected to generate 109 AM and 126 PM peak hour two-way auto trips and is currently being constructed and will be assumed to be built out by 2026. (CGH Transportation, 2021)

#### 3555 Borrisokane Road

The proposed development includes a site plan application consisting of a 31,360 sq. ft Korean community church. The development was initially anticipated to be built out by 2024 and to generate 33 AM and 39 PM peak hour two-way auto trips. This development will be assumed to be built out by 2026. (Castleglenn Consultants, 2024)



Minto's Quinn's Pointe Stages 4 (3882 Barnsdale Road and 3960 Greenbank Road)

The proposed development application includes a plan of subdivision application consisting of 536 single-family dwelling units, 493 townhomes, 100 apartment units, and two elementary schools. Phases 2 and 3 have been completed, and Phase 4 is currently being constructed and will be assumed to be built out by 2026. (Stantec, 2018)

Barrhaven South Future Neighborhood Phase 3 (3882 Barnsdale Road, 3960 Greenbank Road, 4000 Barnsdale Road, 3933 Borrisokane Road)

The proposed development is located within the S-1 Urban Expansion Area and includes a zoning amendment and plan of subdivision for the construction of 952 residential homes including park/open space on the eastern portion of Barrhaven South PH3. The western portion of Barrhaven South PH3 remains as industrial lands on the north side, with woodland and stormwater maintenance ponds on the south side. The development includes future extension of Kilbirnie Drive and is anticipated to be built out by 2030. The urban expansion planning exercise for this area is ongoing and no trip generation or traffic patterns have been forecast at this time.

# 3 Study Area and Time Periods

#### 3.1 Study Area

The study area will include the intersections of Cambrian Road at Elevation Road/Apolune Street, Greenbank Road at Kilbirnie Drive and the site accesses (future conditions) at Obsidian Street.

The boundary road will be Obsidian Street and Screenline 49 is beyond the study area limits at the Jock River and will not be analyzed as part of this study.

#### 3.2 Time Periods

As the proposed development is composed entirely of residential units the weekday AM and PM peak hours will be examined.

#### 3.3 Horizon Years

The anticipated build-out year is 2028. As a result, the full build-out plus five years horizon year is 2033.

# 4 Development-Generated Travel Demand

#### 4.1 Mode Shares

Examining the mode shares recommended in the TRANS Trip Generation Manual (2020) for the subject district, derived from the most recent National Capital Region Origin-Destination survey (OD Survey), the existing average district mode shares by land use for South Nepean have been summarized in Table 3Table 3.

Multi-Unit (Low-Rise) **Travel Mode** AM PM **Auto Driver** 49% 49% **Auto Passenger** 13% 13% 24% Transit 26% Cycling 2% 2% Walking 9% 12% **Total** 100% 100%

Table 3: TRANS Trip Generation Manual Recommended Mode Shares – South Nepean



Given the site is located beyond the typical 400-metre walking distance to local transit, a lower transit mode share is considered at this location. A 10% shift to the auto mode from the transit mode is proposed. The proposed modified mode share targets are summarized in Table 4.

Table 4: Proposed Development Mode Shares

Travel Mode	Multi-Unit (Low-Rise)				
Travel Mode	AM	PM			
Auto Driver	60%	59%			
Auto Passenger	13%	13%			
Transit	16%	14%			
Cycling	2%	2%			
Walking	9%	12%			
Total	100%	100%			

#### 4.2 Trip Generation

This TIA has been prepared using the vehicle and person trip rates for the residential dwellings using the TRANS Trip Generation Manual (2020). Table 5Table 5 summarizes the person trip rates for the proposed residential land use for each peak period.

Table 5: Trip Generation Person Trip Rates by Peak Period

Land Use	Land Use Code	Peak Period	Vehicle Trip Rate	Person Trip Rates
Multi-Unit Low-Rise	220	AM	-	1.35
widiti-onit tow-kise	(TRANS)	PM	-	1.58

Using the above person trip rates, the total person trip generation has been estimated. Table 6 summarizes the total person trip generation for the residential land use.

Table 6: Person Trip Generation by Peak Period

Land Hea	Units	AM Peak Period			PM Peak Period		
Land Use		In	Out	Total	In	Out	Total
Multi-Unit Low-Rise	90	37	85	122	80	62	142

Using the above mode share targets, the person trips by mode have been projected. Trip generation by peak hour has been forecasted using the prescribed peak period conversion factors presented in the TRANS Trip Generation Manual (2020) for the residential component. Table 7 summarizes the residential trip generation by mode and peak hour.

Table 7: Trip Generation by Mode

			M Peak I	lour		PM Peak Hour			
Travel Mode		Mode Share	In	Out	Total	Mode Share	In	Out	Total
	Auto Driver	60%	11	25	35	59%	21	16	37
e)	Auto Passenger	13%	2	6	8	13%	4	4	8
Ļ. Ši	Transit	16%	3	8	11	14%	5	4	9
Multi-Unit (Low-Rise)	Cycling	2%	0	1	1	2%	1	0	1
Σď	Walking	9%	2	4	6	12%	5	4	9
	Total	100%	18	44	61	100%	36	28	64

As shown above, a total of 35 AM and 37 PM new peak hour two-way vehicle trips are projected as a result of the proposed development.



#### 4.3 Trip Distribution

To understand the travel patterns of the subject development, the OD Survey has been reviewed to determine the travel for the residential component, and these patterns were applied based on the build-out of South Nepean. Table 8 below summarizes the distributions.

Table 8: OD Survey Distribution – South Nepean

To/From	Residential % of Trips
North	85%
South	5%
East	5%
West	5%
Total	100%

#### 4.4 Trip Assignment

Using the distribution outlined above, turning movement splits, and access to major transportation infrastructure, the trips generated by the site have been assigned to the study area road network. Table 9 summarizes the proportional assignment to the study area roadways, and Figure 12 illustrates the new site generated volumes.

Table 9: Trip Assignment

To/From	Locally Via	Externally Via
North	50% Cambrian Rd (W),	50% Borrisokane Rd (N),
	35% Greenbank Rd (N)	30% Greenbank Rd (N),
		5% Longfields Rd (N)
South	5% Greenbank Rd (S)	5% Hwy 416 (S)
East	5% Greenbank Rd (N)	5% Longfields Dr (N)
West	5% Kilbirnie Dr (W)	5% Barnsdale Rd
Total	100%	100%






Figure 12: New Site Generated Auto Volumes

# **Exemption Review**

Table 10 summarizes the exemptions for this TIA.

Table 10: Exemption Review

Module	Element	Explanation	Exempt/Required
Site Design and TDM			
Development Design	4.1.2 Circulation and Access	Only required for site plan and zoning by- law applications	Required
Development Design	4.1.3 New Street Networks	Only required for plans of subdivision	Exempt
Parking	4.2.1 Parking Supply	Only required for site plan and zoning by- law applications	Required
Boundary Street Design		All applications	Required
Transportation Demand Management	All Elements	Only required when the development generates more than 60 person-trips	Required
Network Impact			
Background Network Travel Demand	All Elements	Only required when one or more other Network Impact Modules are triggered	Exempt



Module	Element	Explanation	Exempt/Required
		when the development generates more than 75 auto or transit trips	
Demand Rationalization		Only required when one or more other Network Impact Modules when the development generates more than 75 auto trips	Exempt
Neighbourhood Traffic Calming	4.6.1 Adjacent Neighbourhoods	If the development meets all of the following criteria along the route(s) site generated traffic is expected to utilize between an arterial road and the site's access:  1. Access to Collector or Local; 2. "Significant sensitive land use presence" exists, where there is at least two of the following adjacent to the subject street segment:  • School (within 250m walking distance);  • Park;  • Retirement / Older Adult Facility (i.e. long-term care and retirement homes);  • Licenced Child Care Centre;  • Community Centre; or  • 50%, or greater, of adjacent property along the route(s) is occupied by residential lands and a minimum of 10 occupied residential units are present on the route.  3. Application is for Zoning By-Law Amendment or Draft Plan of Subdivision;  4. At least 75 site-generated auto trips;  5. Site Trip Infiltration is expected. Site traffic will increase peak hour vehicle volumes along the route by 50% or more.	Exempt
Transit	4.7.1 Transit Route Capacity 4.7.2 Transit Priority Requirements	Only required when the development generates more than 75 transit trips Only required when the development generates more than 75 auto trips	Exempt
Network Concept		Only required when proposed development generates more than 200 person-trips during the peak hour in excess of equivalent volume permitted by established zoning	Exempt



Module	Element	Explanation	Exempt/Required
Intersection Design	4.4.1-2/4.9.1 Intersection Control	Only required when the development generates more than 75 auto trips	Exempt
	4.4.3/4.9.2 Intersection Design	Only required when the development generates more than 75 auto trips	Exempt

# 6 Development Design

#### 6.1 Design for Sustainable Modes

The proposed development consists of stacked townhome units. A temporary 1.8-metre walkway is proposed along the eastern boundary, partly in the future location of the Realigned Greenbank Road sidewalk, and 1.8-metre midblock connections between the future Realigned Greenbank Road and the existing sidewalk along Obsidian Street are proposed along northern and southern property boundaries. Additionally, 1.8-metre internal walkways provide pedestrian access between buildings and the surrounding facilities. The infrastructure TDM checklist is provided in Appendix E.

Bicycle parking is located in surface racks interspersed throughout the site and cycling access is via the drive aisles connecting to the previous phase to the north (3718 Greenbank Road).

#### 6.2 Circulation and Access

Vehicular and cycling access is provided to Obsidian Street via the connection to the previous phase to the north. Garbage facilities are located to the west side of the surface parking lot. The Molok garbage collection truck can be accommodated on site. No circulation issues are noted with the internal drive aisles, and the standard fire lane geometry has been provided. Turning templates are provided in Appendix F. The previous phase site plan (3718 Greenbank Road) is also provided in Appendix G.

# 7 Parking

#### 7.1 Parking Supply

A total of 121 vehicle parking spaces are proposed with 105 located within the 4159 Obsidian Street site and an additional 16 located within the previous phase that are unoccupied. According to the parking provisions from the Zoning By-Law, 1.0 parking spaces per unit for residents and 0.2 parking spaces per unit for visitors are required, resulting in 108 vehicle parking spaces required with 90 spaces for residents and 18 spaces for visitors. Therefore, the site is proposed to meet this requirement.

According to the Zoning By-Law, the minimum bicycle parking provision is 0.5 bike spaces per unit, resulting in 45 bicycle parking spaces. The site proposes a total of 48 bicycle parking spaces, which exceeds the minimum bicycle parking requirement.

# 8 Boundary Street Design

Table 11 summarizes the MMLOS analysis for the boundary streets of Obsidian Street and future Re-Aligned Greenbank Road. The existing and future conditions for Obsidian Street will be the same and are considered in one row. The Obsidian Street analysis is based on the land use designation of "General Urban Area" and the future Re-Aligned Greenbank Road analysis is based on the policy area of "Within 300m of a school" given its proximity to the future public elementary school at the corner of Kilbirnie Drive at Robin Easey Avenue. The MMLOS worksheet has been provided in Appendix H.



Table 11: Boundary Street MMLOS Analysis

Commont	Pedesti	rian LOS	Bicyc	le LOS	Trans	it LOS	Truck LOS		
Segment	PLOS	Target	BLOS	Target	TLOS	Target	TrLOS	Target	
Obsidian Street	В	С	D	D	N/A	N/A	N/A	N/A	
Future Re-Aligned Greenbank Road	С	Α	Α	Α	Α	Α	Α	D	

Obsidian Street meets the pedestrian and bicycle LOS targets. The future Re-Aligned Greenbank Road will meet the bicycle, transit, and truck LOS targets, but will not meet the pedestrian LOS target despite having the most robust pedestrian facilities scored within the MMLOS framework. This situation is typical for arterial roads in policy areas associated with a LOS target of A given the anticipated curb lane vehicle volumes of arterial roads preclude the ability to meet LOS A outside of reducing operating speeds to 30 km/h. These treatments would not be consistent with the function of arterial roads as facilitating flow. No improvements, and no further analysis is required to address MMLOS as part of the study.

# 9 Transportation Demand Management

#### 9.1 Context for TDM

The subject site has been assumed to rely predominantly on auto modes due to being beyond the 400 metres walking distance of local transit stops. A shift from auto modes to transit modes in both the subject and surrounding developments is anticipated once the BRT network is extended along the Re-Aligned Greenbank Road Corridor to the new park-and-ride at Kilbirnie Drive, but any such shifts are expected to occur outside of the analysis horizons of this report. Overall, the modal shares are likely to be achieved and applicable supporting TDM measures should be provided.

The subject site is within the Barrhaven South Expansion Study Area Community Design Plan.

Total bedrooms within the development are subject to finalize layouts of the stacked townhomes and resident set up within those units. No age restrictions are noted.

#### 9.2 Need and Opportunity

The subject site has been assumed to rely predominantly on auto travel and those assumptions have been carried through the analysis. The risks of not meeting these mode shares are low due to the increased auto modes assumed and the limited scale of the development.

#### 9.3 TDM Program

The "suite of post occupancy TDM measures" has been summarized in the TDM checklists for the residential land uses. The checklist is provided in Appendix E. The key TDM measure recommended to be included is the unbundling of parking costs from purchase or rental costs. Given that bus service typically lags development and early servicing is not appropriate for the small scale of the subject development, no additional measures are considered applicable to the site. The future provision of BRT, sidewalks, and cycletracks along the Realigned Greenbank Road corridor in the future is expected to incur a large elective shift in modal shares towards transit, walking, and cycling, where future TDM measures would not be expected to be required to achieve these results.

# 10 Summary of Improvements Indicated and Modifications Options

The following summarizes the analysis and results presented in this TIA report:

#### **Proposed Site and Screening**

The proposed site includes 90 stacked townhome units



- Vehicular and cycling accesses will be provided along Obsidian Street via the connection to the previous phase to the north
- The development is proposed to be completed as a single phase by 2028
- The trip generation trigger was met for the TIA Screening
- This study was prepared in support of a site plan application
- Based on the exemption review, the Site Design and TDM components of the TIA are required

#### **Existing Conditions**

- Greenbank Road and Cambrian Road are arterial roads and Elevation Road, Apolune Street, Dundonald Drive, and Kilbirnie Drive are collector roads, and Obsidian Street is a local road in the study area
- Sidewalks are provided along the east side of Obsidian Street and Greenbank Road north of Kilbirnie Drive, and both sides of Kilbirnie Drive, Apolune Street, Cambrian Road between Seeley's Bay Street and Greenbank Road, and Dundonald Road east of the future Realigned Greenbank Road
- A bike lane is present on the east side of Greenbank Road north of Kilbirnie Drive and a MUP is present on the west side
- MUPs are provided on both sides of Elevation Road and MUPS are planned to be located on both sides of Dundonald Drive west of the future Realigned Greenbank Road
- Realigned Greenbank Road is designated as a Cross-Town Bikeway
- No collisions noted on the adjacent streets to the site during the 2018-2022 time period
- During peak hours in the existing conditions, the study area intersections operate well

#### **Planned Conditions**

- The westward extension of Kilbirnie Drive to the urban boundary is assumed to occur by site buildout
- The Cambrian Road widening and Greenbank Road realignment and southwest transitway extension are assumed to occur beyond the study horizon years

#### **Development Generated Travel Demand**

- The proposed development is forecasted to produce 63 AM and 66 PM two-way people trips
- Of the forecasted people trips, 36 AM and 38 PM two-way trips will be vehicle trips based on 60% and 59% modal share target
- Of the forecasted trips, 85% are anticipated to travel to the north, 5% to the south, 5% to the east, and 5% to the west

#### **Development Design**

- A temporary 1.8-metre walkway is proposed along the eastern boundary and 1.8-metre mid-block connections along northern and southern property boundaries
- Bicycle parking is located in surface racks interspersed throughout the site
- No circulation issues are noted with the internal drive aisles, and the standard fire lane geometry has been provided

#### **Parking**

• The zoning by-law requires 108 vehicle parking spaces including 90 residential parking spaces and 18 visitor parking spaces



- A total of 121 vehicle parking spaces are proposed, with 16 of the spaces located within the pervious phase, meeting the Zoning By-Law minimum
- The site provides 48 bicycle parking spaces, which exceeds the minimum site-specific Zoning By-Law requirement for 45 bicycle spaces

#### **Boundary Street Design**

- Obsidian Street meets pedestrian and cycling MMLOS targets and future Re-Aligned Greenbank Road will meet bicycle, transit, and truck MMLOS targets, but will not meet the pedestrian LOS target
- No additional pedestrian configurations could meet targets as they are limited by forecasted vehicle volumes and typical arterial operating speeds
- No improvements are required to address MMLOS within the study area

#### TDM

- Supportive TDM measures to be included within the proposed development should include the unbundling of parking costs from purchase or rental costs
- Additional transit uptake is anticipated once the Realigned Greenbank Road BRT corridor is constructed

#### 11 Conclusion

It is recommended that, from a transportation perspective, the proposed development application proceed.

Prepared By:

Reihaneh Azhdar

Reiharch Achdar

Transportation Engineering-Intern

Reviewed By:

ROFESSIONAL RAID ROSE OF ONTARIO

ROVESSIONAL ROSE OF ONTARIO

Andrew Harte, P.Eng.
Senior Transportation Engineer



# Appendix A

TIA Screening Form and PM Certification Form





City of Ottawa 2023 Revisions to 2017 TIA Guidelines Step 1 - Screening Form

Date: 2025-03-10
Project Number: 2025-011
Project Reference: HMBS Phase 7

1.1 Description of Proposed Development	
Municipal Address	4159 Obsidian Street
	Undeveloped block between future Re-Aligned
Description of Location	Greenbank Road and Obsidian Street, midblock
	between Dundonald Drive and Kilbirnie Drive
Land Use Classification	General Mixed-Use Zone (GM[2800] H(14.5) )
Development Size	96 stacked townhomes
	Proposed to access Obsidian Street through previous
Accesses	phase to north. Alternatively, new full move access will
	be located on Obsidian Street.
Phase of Development	Single Phase
Buildout Year	2027
TIA Requirement	Full TIA Required

1.2 Trip Generation Trigger	
Land Use Type	Multi-Family (Low-Rise)
Development Size	96 Units
Trip Generation Trigger	Yes

1.3 Location Triggers	
Does the development propose a new driveway to a boundary street that is	
designated as part of the Transit Priority Network, Rapid Transit network or	No
Cross-Town Bikeways?	
Is the development in a Hub, a Protected Major Transit Station Area (PMTSA), or a Design Priority Area (DPA)?	No
Location Trigger	No

1.4. Safety Triggers	
Are posted speed limits on a boundary street 80 km/hr or greater?	No
Are there any horizontal/vertical curvatures on a boundary street limits sight	No
lines at a proposed driveway?	INO
Is the proposed driveway within the area of influence of an adjacent traffic	
signal or roundabout (i.e. within 300 m of intersection in rural conditions, or	No
within 150 m of intersection in urban/ suburban conditions)?	
Is the proposed driveway within auxiliary lanes of an intersection?	No
Does the proposed driveway make use of an existing median break that	No
serves an existing site?	110
Is there is a documented history of traffic operations or safety concerns on	
the boundary streets within 500 m of the development?	No
Does the development include a drive-thru facility?	No
Safety Trigger	No



# **Certification Form for TIA Study PM**

#### **TIA Plan Reports**

On April 14, 2022, the Province's Bill 109 received Royal Assent providing legislative direction to implement the More Homes for Everyone Act, 2022 aiming to increase the supply of a range of housing options to make housing more affordable. Revisions have been made to the TIA guidelines to comply with Bill 109 and streamline the process for applicants and staff.

Individuals submitting TIA reports will be responsible for all aspects of development-related transportation assessment and reporting, and undertaking such work, in accordance and compliance with the City of Ottawa's Official Plan, the Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines.

By submitting the attached TIA report (and any associated documents) and signing this document, the individual acknowledges that they meet the four criteria listed below.

#### **CERTIFICATION**

I have reviewed and have a sound understanding of the objectives, needs and requirements of the City of Ottawa's Official Plan, Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines; (Update effective July 2023)

I have a sound knowledge of industry standard practice with respect to the preparation of transportation impact assessment reports, including multi modal level of service review;

I have substantial experience (more than 5 years) in undertaking and delivering transportation impact studies (analysis, reporting and geometric design) with strong background knowledge in transportation planning, engineering or traffic operations; and

I am either a licensed or registered<sup>1</sup> professional in good standing, whose field of expertise

is either transportation engineering

or transportation planning.

<sup>1</sup> License of registration body that oversees the profession is required to have a code of conduct and ethics guidelines that will ensure appropriate conduct and representation for transportation planning and/or transportation engineering works.

City Of Ottawa Planning, Real Estate and Economic Development 110 Laurier Avenue West, 4th fl. Ottawa, ON K1P 1J1 Tel.: 613-580-2424

Tel.: 613-580-2424 Fax: 613-560-6006

**Revision Date: June 2023** 

Dated at	this	day of	, 20
(City)			
Name :			
Professional title:			
Signature of individual certif	ier that s/he/they	meet the above criteria	
Office Contact Informatio	n (Please Print)		
Address:			
City / Postal Code:			
Telephone / Extension:			
Email Address:			
Stamp			

**Revision Date: June 2023** 

A. J. HARTE

A. J. HARTE 100149314

POVINCE OF ONTARIO

# Appendix B

**Turning Movement Counts** 





# **Project #24-105 - CGH Transportation**

# **Intersection Count Report**

Intersection: Greenbank Rd & Kilbirnie Dr

Municipality: Ottawa

Count Date: Wednesday, Mar 20, 2024

**Site Code:** 2410400002

**Count Categories:** Cars, Trucks, Bicycles, Pedestrians

**Count Period:** 07:00-10:00, 11:30-13:30, 15:00-18:00

Weather: Clear

**Comments:** 



### **Traffic Count Map**

Intersection: Greenbank Rd & Kilbirnie Dr Site Code: 2410400002

Municipality: Ottawa
Count Date: Mar 20, 2024





# **Traffic Count Summary**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002

Municipality: Ottawa Count Date: Mar 20, 2024

Site Code:

Greenbank Rd – Traffic Summary														
		North	Appr	oach T	otals									
		Include	s Cars, 1	rucks, B	icycles			Include	s Cars, 1	Trucks, B	icycles			
Hour	Left	Thru	Right	U-Turn	Total	Peds	Left	Thru	Right	U-Turn	Total	Peds	Total	
07:00 - 08:00	11	165	23	0	199	1	13	103	17	0	133	0	332	
08:00 - 09:00	22	194	64	1	281	2	58	144	27	0	229	11	510	
09:00 - 10:00	23	159	71	2	255	4	17	112	13	0	142	6	397	
BREAK														
11:30 - 12:00	4	56	25	1	86	0	10	51	13	0	74	1	160	
12:00 - 13:00	26	110	58	1	195	9	31	129	23	0	183	3	378	
13:00 - 13:30	12	55	23	0	90	4	12	36	6	0	54	4	144	
					В	REAK								
15:00 - 16:00	57	203	117	3	380	9	57	181	39	0	277	5	657	
16:00 - 17:00	52	221	88	1	362	11	66	218	75	0	359	8	721	
17:00 - 18:00	46	156	115	1	318	12	72	224	60	0	356	3	674	
GRAND TOTAL	253	1319	584	10	2166	52	336	1198	273	0	1807	41	3973	



# **Traffic Count Summary**

Intersection: Greenbank Rd & Kilbirnie Dr Site Code: 2410400002

Municipality: Ottawa Count Date: Mar 20, 2024

Kilbirnie Dr – Traffic Summary													
		East .	Appro	ach To	tals			West	Appro	oach T	otals		
		Include	s Cars, 1	rucks, Bi	cycles			Indude	s Cars, '	Trucks, B	icycles		
Hour	Left	Thru	Right	U-Turn	Total	Peds	Left	Thru	Right	U-Turn	Total	Peds	Tota
07:00 - 08:00	71	7	43	0	121	0	63	9	127	0	199	1	32
08:00 - 09:00	58	7	58	0	123	6	74	18	81	0	173	0	29
09:00 - 10:00	47	8	35	0	90	3	93	11	58	0	162	3	25
BREAK													
11:30 - 12:00	11	3	12	0	26	2	26	3	20	0	49	0	7
12:00 - 13:00	15	7	26	0	48	0	50	6	35	0	91	2	13
13:00 - 13:30	11	6	11	0	28	1	21	5	18	0	44	4	7
					В	REAK							
15:00 - 16:00	23	25	43	0	91	4	67	11	42	0	120	3	21
16:00 - 17:00	59	31	35	0	125	5	96	13	70	0	179	13	30
17:00 - 18:00	57	17	40	0	114	1	80	12	46	0	138	11	25
GRAND TOTAL	352	111	303	0	766	22	570	88	497	0	1155	37	192



Intersection: Greenbank Rd & Kilbirnie Dr

Site Code: 2410400002

Municipality: Ottawa

Count Date: Mar 20, 2024

	North Approach - Greenbank Rd															
			Cars				Ti	rucks				Bi	cycles			
Start Time	7	1	-	7	Total	7	1	<b>P</b>	4	Total	4	1	P	ŋ	Total	Total Peds
07:00	1	36	6	0	43	0	0	0	0	0	0	0	0	0	0	0
07:15	2	41	4	0	47	0	1	0	0	1	0	0	0	0	0	1
07:30	5	40	7	0	52	1	0	0	0	1	0	0	0	0	0	0
07:45	2	44	6	0	52	0	3	0	0	3	0	0	0	0	0	0
08:00	3	45	18	1	67	0	1	0	0	1	0	0	0	0	0	0
08:15	4	43	16	0	63	0	3	0	0	3	0	0	0	0	0	1
08:30	8	48	11	0	67	0	0	0	0	0	0	0	0	0	0	0
08:45	7	52	18	0	77	0	2	1	0	3	0	0	0	0	0	1
09:00	11	58	29	0	98	1	4	0	0	5	0	0	0	0	0	2
09:15	3	45	15	1	64	0	1	0	0	1	0	0	0	0	0	0
09:30	6	22	13	1	42	0	1	1	0	2	0	0	0	0	0	1
09:45	2	27	13	0	42	0	1	0	0	1	0	0	0	0	0	1
SUBTOTAL	54	501	156	3	714	2	17	2	0	21	0	0	0	0	0	7



#### **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr Site Code: 2410400002 Municipality: Ottawa

Count Date: Mar 20, 2024

	North Approach – Greenbank Rd															
	Cars Trucks Bicycles															
Start Time	4	1	-	J	Total	4	1	•	1	Total	4	1	*	1	Total	Total Peds
11:30	1	24	9	1	35	0	1	0	0	1	0	0	0	0	0	0
11:45	2	30	16	0	48	1	1	0	0	2	0	0	0	0	0	0
12:00	6	33	16	0	55	0	0	0	0	0	0	0	0	0	0	2
12:15	8	28	21	0	57	0	0	0	0	0	0	0	0	0	0	1
12:30	3	24	8	0	35	0	1	0	0	1	0	0	0	0	0	5
12:45	9	23	13	1	46	0	1	0	0	1	0	0	0	0	0	1
13:00	5	28	15	0	48	0	0	0	0	0	0	0	0	0	0	2
13:15	7	26	8	0	41	0	1	0	0	1	0	0	0	0	0	2
SUBTOTAL	41	216	106	2	365	1	5	0	0	6	0	0	0	0	0	13



Intersection: Greenbank Rd & Kilbirnie Dr

2410400002 Site Code: Municipality: Ottawa Mar 20, 2024

	North Approach – Greenbank Rd															
			Cars				Ti	rucks				Bi	cycles			
Start Time	- 1	1	-	J.	Total	4	1		J.	Total	4	1	1	<b>1</b>	Total	Total Peds
15:00	4	34	23	1	62	0	0	0	0	0	0	0	0	0	0	3
15:15	15	48	18	1	82	1	0	1	0	2	0	0	0	0	0	3
15:30	19	45	28	0	92	0	1	2	0	3	0	0	0	0	0	2
15:45	17	73	44	1	135	1	2	1	0	4	0	0	0	0	0	1
16:00	11	63	19	0	93	0	1	0	0	1	0	0	0	0	0	2
16:15	12	48	23	1	84	0	3	0	0	3	0	0	0	0	0	6
16:30	9	38	24	0	71	0	0	0	0	0	0	0	0	0	0	3
16:45	20	68	22	0	110	0	0	0	0	0	0	0	0	0	0	0
17:00	15	33	31	0	79	0	0	0	0	0	0	0	0	0	0	<u>1</u>
17:15	10	45	31	0	86	0	2	0	0	2	0	0	0	0	0	4
17:30	15	45	29	1	90	0	1	0	0	1	0	0	0	0	0	5
17:45	6	30	24	0	60	0	0	0	0	0	0	0	0	0	0	2
SUBTOTAL	153	570	316	5	1044	2	10	4	0	16	0	0	0	0	0	32
GRAND TOTAL	248	1287	578	10	2123	5	32	6	0	43	0	0	0	0	0	52

Count Date:



#### **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002 Site Code: Ottawa Municipality:

Count Date: Mar 20, 2024

South Approach - Greenbank Rd																
			Cars	_			T	rucks				Bi	cycles	_		
Start Time	4	1	*	J	Total	4	1	-	7	Total	4	1	•	J	Total	Total Peds
07:00	5	21	4	0	30	0	1	1	0	2	0	0	0	0	0	0
07:15	1	22	2	0	25	0	1	2	0	3	0	0	0	0	0	0
07:30	3	21	4	0	28	0	2	2	0	4	0	0	0	0	0	0
07:45	4	35	2	0	41	0	0	0	0	0	0	0	0	0	0	0
08:00	17	30	8	0	55	1	3	0	0	4	0	0	0	0	0	0
08:15	15	33	6	0	54	0	1	0	0	1	0	0	0	0	0	4
08:30	12	38	4	0	54	0	0	2	0	2	0	0	0	0	0	5
08:45	12	39	4	0	55	1	0	3	0	4	0	0	0	0	0	2
09:00	1	30	6	0	37	0	1	1	0	2	0	0	0	0	0	3
09:15	8	24	4	0	36	0	4	0	0	4	0	0	0	0	0	2
09:30	3	28	1	0	32	0	0	0	0	0	0	0	0	0	0	1
09:45	5	24	1	0	30	0	1	0	0	1	0	0	0	0	0	0
SUBTOTAL	86	345	46	0	477	2	14	11	0	27	0	0	0	0	0	17



Intersection: Greenbank Rd & Kilbirnie Dr

2410400002 Site Code: Municipality: Ottawa Mar 20, 2024

	South Approach - Greenbank Rd															
	Cars Trucks Bicycles															
Start Time	4	1	*	J	Total	4	1		1	Total	4	1	•	1	Total	Total Peds
11:30	5	24	5	0	34	0	0	1	0	1	0	0	0	0	0	0
11:45	5	26	6	0	37	0	1	1	0	2	0	0	0	0	0	1
12:00	12	32	4	0	48	0	0	0	0	0	0	0	0	0	0	0
12:15	7	35	5	0	47	0	1	0	0	1	0	0	0	0	0	1
12:30	5	31	5	0	41	0	0	0	0	0	0	0	0	0	0	0
12:45	6	29	9	0	44	1	1	0	0	2	0	0	0	0	0	2
13:00	6	18	4	0	28	0	0	0	0	0	0	0	0	0	0	1
13:15	6	17	2	0	25	0	1	0	0	1	0	0	0	0	0	3
SUBTOTAL	52	212	40	0	304	1	4	2	0	7	0	0	0	0	0	8

Count Date:



#### **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002 Site Code: Ottawa Municipality:

Count Date: Mar 20, 2024

South Approach - Greenbank Rd																
	Cars Trucks												icycles			
Start Time	4	1	-	J	Total	4	1	<b>P</b>	<b>1</b>	Total	4	1	<b>P</b>	7	Total	Total Peds
15:00	9	42	12	0	63	0	0	0	0	0	0	0	0	0	0	3
15:15	15	40	10	0	65	0	0	0	0	0	0	0	0	0	0	1
15:30	9	51	13	0	73	2	2	0	0	4	0	0	0	0	0	1_
15:45	22	45	4	0	71	0	1	0	0	1	0	0	0	0	0	0
16:00	19	53	16	0	88	0	1	1	0	2	0	0	0	0	0	1
16:15	10	51	15	0	76	0	0	1	0	1	0	0	0	0	0	5
16:30	17	49	25	0	91	0	1	0	0	1	0	0	0	0	0	0
16:45	20	62	17	0	99	0	1	0	0	1	0	0	0	0	0	2
17:00	17	50	13	0	80	0	1	0	0	1	0	0	0	0	0	0
17:15	18	47	14	0	79	0	0	0	0	0	0	0	0	0	0	0
17:30	17	62	18	0	97	0	0	0	0	0	0	0	0	0	0	2
17:45	20	64	15	0	99	0	0	0	0	0	0	0	0	0	0	1
SUBTOTAL	193	616	172	0	981	2	7	2	0	11	0	0	0	0	0	16
GRAND TOTAL	331	1173	258	0	1762	5	25	15	0	45	0	0	0	0	0	41



Intersection: Greenbank Rd & Kilbirnie Dr

Mar 20, 2024

2410400002 Site Code: Municipality: Ottawa

	East Approach - Kilbirnie Dr															
			Cars				T	rucks				Bio	cycles			
Start Time	4	1	*	<b>Q</b>	Total	4	1	<b>P</b>	4	Total	4	1	<b>P</b>	1	Total	Total Peds
07:00	11	0	8	0	19	0	1	0	0	1	0	0	0	0	0	0
07:15	17	1	12	0	30	0	1	2	0	3	0	0	0	0	0	0
07:30	18	1	10	0	29	0	1	1	0	2	0	0	0	0	0	0
07:45	25	2	10	0	37	0	0	0	0	0	0	0	0	0	0	0
08:00	19	0	12	0	31	0	1	1	0	2	0	0	0	0	0	0
08:15	13	1	10	0	24	1	0	0	0	1	0	0	0	0	0	2
08:30	17	0	17	0	34	0	1	0	0	1	0	0	0	0	0	4
08:45	8	4	18	0	30	0	0	0	0	0	0	0	0	0	0	0
09:00	13	0	11	0	24	1	2	0	0	3	0	0	0	0	0	0
09:15	9	3	8	0	20	0	0	0	0	0	0	0	0	0	0	1
09:30	13	0	6	0	19	0	1	0	0	1	0	0	0	0	0	0
09:45	10	1	9	0	20	1	1	1	0	3	0	0	0	0	0	2
SUBTOTAL	173	13	131	0	317	3	9	5	0	17	0	0	0	0	0	9

Count Date:



#### **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002 Site Code: Ottawa Municipality:

Count Date: Mar 20, 2024

	East Approach - Kilbirnie Dr															
	Cars Trucks Bicycles															
Start Time	4	1	*	J	Total	4	1	<b>P</b>	4	Total	4	1	1	4	Total	Total Peds
11:30	2	1	5	0	8	0	1	0	0	1	0	0	0	0	0	2
11:45	9	0	7	0	16	0	1	0	0	1	0	0	0	0	0	0
12:00	5	0	11	0	16	0	1	0	0	1	0	0	0	0	0	0
12:15	3	2	5	0	10	1	1	0	0	2	0	0	0	0	0	0
12:30	4	0	10	0	14	0	2	0	0	2	0	0	0	0	0	0
12:45	2	0	0	0	2	0	1	0	0	1	0	0	0	0	0	0
13:00	7	1	8	0	16	0	1	0	0	1	0	0	0	0	0	1
13:15	4	1	3	0	8	0	3	0	0	3	0	0	0	0	0	0
SUBTOTAL	36	5	49	0	90	1	11	0	0	12	0	0	0	0	0	3



Intersection: Greenbank Rd & Kilbirnie Dr

2410400002 Site Code: Municipality: Ottawa

Mar 20, 2024

East Approach - Kilbirnie Dr																
	Cars Trucks Bicycles															
Start Time	4	1	-	J	Total	4	1		4	Total	4	1	1	J	Total	Total Peds
15:00	7	5	12	0	24	0	0	0	0	0	0	0	0	0	0	0
15:15	5	1	10	0	16	0	2	0	0	2	0	0	0	0	0	3
15:30	5	6	10	0	21	0	1	0	0	1	0	0	0	0	0	0
15:45	5	6	11	0	22	1	4	0	0	5	0	0	0	0	0	1
16:00	13	5	10	0	28	3	3	0	0	6	0	0	0	0	0	2
16:15	11	4	4	0	19	0	10	1	0	11	0	0	0	0	0	2
16:30	13	3	14	0	30	0	1	1	0	2	0	0	0	0	0	1
16:45	19	4	5	0	28	0	1	0	0	1	0	0	0	0	0	0
17:00	6	4	6	0	16	0	2	0	0	2	0	0	0	0	0	0
17:15	12	2	10	0	24	0	1	0	0	1	0	0	0	0	0	0
17:30	14	1	12	0	27	0	1	0	0	1	0	0	0	0	0	1
17:45	25	5	12	0	42	0	1	0	0	1	0	0	0	0	0	0
SUBTOTAL	135	46	116	0	297	4	27	2	0	33	0	0	0	0	0	10
GRAND TOTAL	344	64	296	0	704	8	47	7	0	62	0	0	0	0	0	22

Count Date:



#### **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002 Site Code: Ottawa Municipality:

Mar 20, 2024

	West Approach - Kilbirnie Dr															
	Cars Trucks Bicycles															
Start Time	4	1	*	<b>Q</b>	Total	4	1	<b>*</b>	4	Total	4	1	<b>P</b>	4	Total	Total Peds
07:00	13	0	31	0	44	0	1	0	0	1	0	0	0	0	0	0
07:15	16	0	25	0	41	0	2	0	0	2	0	0	0	0	0	0
07:30	19	2	34	0	55	1	1	0	0	2	0	0	0	0	0	0
07:45	14	1	37	0	52	0	2	0	0	2	0	0	0	0	0	1
08:00	22	1	17	0	40	0	1	0	0	1	0	0	0	0	0	0
08:15	13	1	22	0	36	0	1	0	0	1	0	0	0	0	0	0
08:30	18	0	20	0	38	0	3	0	0	3	0	0	0	0	0	0
08:45	21	0	22	0	43	0	11	0	0	11	0	0	0	0	0	0
09:00	32	1	21	0	54	1	1	0	0	2	0	0	0	0	0	2
09:15	29	5	19	0	53	1	1	1	0	3	0	0	0	0	0	0
09:30	12	0	8	0	20	0	1	1	0	2	0	0	0	0	0	1
09:45	18	1	8	0	27	0	1	0	0	1	0	0	0	0	0	0
SUBTOTAL	227	12	264	0	503	3	26	2	0	31	0	0	0	0	0	4

Count Date:



Greenbank Rd & Kilbirnie Dr

Mar 20, 2024

Intersection: 2410400002 Site Code: Municipality: Ottawa

							W	lest l	Appro	ach	- Kilbi	rnie I	)r			
		(	Cars				Ti	rucks				Bi	cycles			
Start Time	4	1	*	1	Total	4	1	*	1	Total	4	1	•	1	Total	Total Peds
11:30	17	0	10	0	27	0	0	0	0	0	0	0	0	0	0	0
11:45	9	0	10	0	19	0	3	0	0	3	0	0	0	0	0	0
12:00	16	0	10	0	26	0	1	0	0	1	0	0	0	0	0	0
12:15	11	1	7	0	19	0	0	0	0	0	0	0	0	0	0	0
12:30	11	0	11	0	22	0	2	0	0	2	0	0	0	0	0	1
12:45	12	1	7	0	20	0	1	0	0	1	0	0	0	0	0	1
13:00	8	2	9	0	19	0	1	0	0	1	0	0	0	0	0	3
13:15	13	1	9	0	23	0	1	0	0	1	0	0	0	0	0	1
SUBTOTAL	97	5	73	0	175	0	9	0	0	9	0	0	0	0	0	6

Count Date:



## **Traffic Count Data**

Intersection: Greenbank Rd & Kilbirnie Dr 2410400002 Site Code:

Ottawa Municipality: Count Date: Mar 20, 2024

							N	lest A	\ppro	ach -	- Kilbi	rnie I	Dr			
			Cars				T	rucks				Bi	icycles			
Start Time	4	1	<b>P</b>	J	Total	4	1	<b>P</b>	7	Total	4	1		7	Total	Total Peds
15:00	7	3	8	0	18	0	0	0	0	0	0	0	0	0	0	0
15:15	19	1	5	0	25	0	1	0	0	1	0	0	0	0	0	0
15:30	14	2	14	0	30	1	0	1	0	2	0	0	0	0	0	3
15:45	25	3	14	0	42	1	1	0	0	2	0	0	0	0	0	0
16:00	33	3	27	0	63	0	2	0	0	2	0	0	0	0	0	6
16:15	29	3	16	0	48	0	1	1	0	2	0	0	0	0	0	7
16:30	17	1	11	0	29	0	1	0	0	1	0	0	0	0	0	0
16:45	17	2	15	0	34	0	0	0	0	0	0	0	0	0	0	0
17:00	24	2	5	0	31	0	1	0	0	1	0	0	0	0	0	2
17:15	25	1	14	0	40	0	0	0	0	0	0	0	0	0	0	1
17:30	11	4	14	0	29	0	1	0	0	1	0	0	0	0	0	2
17:45	20	3	13	0	36	0	0	0	0	0	0	0	0	0	0	6
SUBTOTAL	241	28	156	0	425	2	8	2	0	12	0	0	0	0	0	27
GRAND TOTAL	565	45	493	0	1103	5	43	4	0	52	0	0	0	0	0	37



**Specified Period** 

**One Hour Peak** 

07:00:00 To: 10:00:00

08:15:00 From: To:

09:15:00

Greenbank Rd & Kilbirnie Dr Intersection:

Site Code: 2410400002 Count Date: Mar 20, 2024 Weather conditions:

Clear

#### \*\* Unsignalized Intersection \*\*

#### Major Road: Greenbank Rd runs N/S

#### North Approach Out In Total 305 280 585 11 3 14 0 0 316 283 599



Peds: 4



Kil	hir	nia	Dr

	Totals		₽	₩
7	0	0	0	0
1	85	84	1	0
$\Rightarrow$	18	2	16	0
4	85	85	0	0



	Kill	birnie I	)r	
	Totals	⊖	₽	₫6
C	0	0	0	0
£	56	56	0	0
-	8	5	3	0
F	53	51	2	0

117 75 192

52 164

23 28

0 0

	West	: Appr	oach
	Out	In	Total
	171	119	290
Ъ	17	5	22
<b>%</b>	0	0	0
	188	124	312



Peds: 14

	Sout	h Appı	roach
	Out	In	Total
	200	337	537
<b>D</b>	9	11	20
₫6	0	0	0
	209	348	557

📾 - Cars

🚨 - Trucks

♣ - Bicycles

#### Comments

## **Peak Hour Summary**



Greenbank Rd & Kilbirnie Dr Intersection: 2410400002 Site Code: Count Date: Mar 20, 2024 07:00 - 10:00 Period:

									Pea	ık Ho	our [	ata	(08:	15 -	09:1	5)									
		,	North <i>F</i> Greenl	ipproac oank Ro	h I			5	outh <i>A</i> Greenl	ipproac oank Ro	h I				East Ap Kilbir	proach nie Dr	1				West A Kilbir	pproad nie Dr	h		Total Vehic
Start Time	4	1	*	J	Peds	Total	4	1		4	Peds	Total	4	1	<b>P</b>	4	Peds	Total	4	1	*	J	Peds	Total	es
08:15	4	46	16	0	1	66	15	34	6	0	4	55	14	1	10	0	2	25	13	2	22	0	0	37	183
08:30	8	48	11	0	0	67	12	38	6	0	5	56	17	1	17	0	4	35	18	3	20	0	0	41	199
08:45	7	54	19	0	1	80	13	39	7	0	2	59	8	4	18	0	0	30	21	11	22	0	0	54	223
09:00	12	62	29	0	2	103	1	31	7	0	3	39	14	2	11	0	0	27	33	2	21	0	2	56	225
Grand Total	31	210	75	0	4	316	41	142	26	0	14	209	53	8	56	0	6	117	85	18	85	0	2	188	830
Approach %	9.8	66.5	23.7	0		-	19.6	67.9	12.4	0		-	45.3	6.8	47.9	0		-	45.2	9.6	45.2	0		-	
Totals %	3.7	25.3	9	0		38.1	4.9	17.1	3.1	0		25.2	6.4	1	6.7	0		14.1	10.2	2.2	10.2	0		22.7	
PHF	0.65	0.85	0.65	0		0.77	0.68	0.91	0.93	0		0.89	0.78	0.5	0.78	0		0.84	0.64	0.41	0.97	0		0.84	0.92
Cars	30	201	74	0		305	40	140	20	0		200	51	5	56	0		112	84	2	85	0		171	788
% Cars	96.8	95.7	98.7	0		96.5	97.6	98.6	76.9	0		95.7	96.2	62.5	100	0		95.7	98.8	11.1	100	0		91	94.9
Trucks	1	9	1	0		11	1	2	6	0		9	2	3	0	0		5	1	16	0	0		17	42
% Trucks	3.2	4.3	1.3	0		3.5	2.4	1.4	23.1	0		4.3	3.8	37.5	0	0		4.3	1.2	88.9	0	0		9	5.1
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	-0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
Peds					4	-					14	-					6	-					2	,	26
% Peds					15.4	-					53.8	-					23.1	-					7.7	-	



**Specified Period** 

**One Hour Peak** 

From:

To:

11:30:00 To: 13:30:00 11:45:00

12:45:00

Greenbank Rd & Kilbirnie Dr Intersection:

2410400002 Site Code: Count Date: Mar 20, 2024 Weather conditions:

Clear

#### \*\* Unsignalized Intersection \*\*

#### Major Road: Greenbank Rd runs N/S

**East Approach** 

Out In Total

40

8 14

62 48 110

0 0

#### North Approach Out In Total 195 204 399 5 2 0 0 198 206 404

Kilbirnie Dr





# Peds: 8

Kil	hi	rn	i۵	n

₽		Totals		_	N
0	0	0	7	<u>;</u>	W E
0	47	47	4	Pe	<b>V</b>
6	1	7	-		\$
0	38	38	7		Daday 2

_		Totals		
ĕds	C	0	0	0
	1.	33	33	0
	-	7	2	5
	F	22	21	1

	Wes	t Appr	oach
	Out	In	Total
	86	92	178
۵	6	5	11
₫6	0	0	0
	92	97	189

	4	1	•	J.
Totals	29	126	21	0
	29	124	20	0
다	0	2	1	0
<i>₫</i> %	0	0	0	0
	Gree	nbank	Rd	

Peds: 2

	Sout	h Appı	roach
	Out	In	Total
	173	174	347
₽	3	3	6
₫6	0	0	0
	176	177	353

	- Cars	- Q	Tru	cks	₫6 -	Bicycles
--	--------	-----	-----	-----	------	----------

#### Comments





Greenbank Rd & Kilbirnie Dr Intersection: 2410400002 Site Code: Count Date: Mar 20, 2024 11:30 - 13:30 Period:

									Pea	ık Ho	our C	ata	(11:	45 -	12:4	5)									
		,	orth <i>F</i> Greenl	Approac bank Ro	h I			2	outh <i>A</i> Greenl	ipproac oank Ro	h I				East A <sub>l</sub> Ki <b>l</b> bir	pproach nie Dr	ľ				West A Kilbir	pproacl nie Dr	h		Total Vehic
Start Time	4	1	*	4	Peds	Total	4	1		4	Peds	Total	4	1		1	Peds	Total	4	1		1	Peds	Total	es
11:45	3	31	16	0	0	50	5	27	7	0	1	39	9	1	7	0	0	17	9	3	10	0	0	22	128
12:00	6	33	16	0	2	55	12	32	4	0	0	48	5	1	11	0	0	17	16	1	10	0	0	27	147
12:15	8	28	21	0	- 1	57	7	36	5	0	1	48	4	3	5	0	0	12	11	1	7	0	0	19	136
12:30	3	25	8	0	- 5	36	- 5	31	5	0	0	41	4	2	10	0	0	16	- 11	2	- 11	0	1	24	117
Grand Total	20	117	61	0	8	198	29	126	21	0	2	176	22	7	33	0	0	62	47		38	0		92	528
Approach %	10.1	59.1	30.8	0		-	16.5	71.6	11.9	0		-	35.5	11.3	53.2	0		-	51.1	7.6	41.3	0		,	
Totals %	3.8	22.2	11.6	0		37.5	5.5	23.9	4	0		33.3	4.2	1.3	6.3	0		11.7	8.9	1.3	7.2	0		17.4	
PHF	0.63	0.89	0.73	0		0.87	0.6	0.88	0.75	0		0.92	0.61	0.58	0.75	0		0.91	0.73	0.58	0.86	0		0.85	0.9
Cars	19	115	61	0		195	29	124	20	0		173	21	2	33	0		56	47	1	38	0		86	510
% Cars	95	98.3	100	0		98.5	100	98.4	95.2	0		98.3	95.5	28.6	100	0		90.3	100	14.3	100	0		93.5	96.6
Trucks	1	2	0	0		3	0	2	1	0		3	1	5	0	0		6	0	6	0	0		6	18
% Trucks	5	1.7	0	0		1.5	0	1.6	4.8	0		1.7	4.5	71.4	0	0		9.7	0	85.7	0	0		6.5	3.4
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
Peds					8	-					2	-					0	-					1	-	11
% Peds					72.7	-					18.2	-					0	-					9.1	-	



Greenbank Rd & Kilbirnie Dr

# **Peak Hour Diagram**

**Specified Period** 

**One Hour Peak** 

From:

To:

15:00:00 To: 18:00:00 15:30:00

16:30:00

2410400002 Site Code: Count Date: Mar 20, 2024

Intersection:

Weather conditions:

Clear

#### \*\* Unsignalized Intersection \*\*

#### Major Road: Greenbank Rd runs N/S

#### North Approach Out In Total 404 338 742 11 18 7 0 0 415 345 760





	Out	In	Total
	90	118	208
	23	7	30
₩	0	0	0
	113	125	238

Kilbirnie Dr

ॐ	₽		Totals	
0	0	0	0	7
0	2	101	103	1
0	4	11	15	$\Rightarrow$
0	2	71	73	4



Peds: 7

Peds: 11

	Totals		₽	<i>₫</i> %
C	0	0	0	0
L	36	35	1	0
-	39	21	18	0
F	38	34	4	0

Kilbirnie Dr

West Approach

	Out	In	Total
	183	195	378
	8	23	31
₫6	0	0	0
	191	218	409

	4	t	r	J
Totals	62	204	50	0
	60	200	48	0
₽	2	4	2	0
₫%	0	0	0	0

**Greenbank Rd** 

	Sout	h Appı	roach
	Out	In	Total
	308	334	642
۵۵	8	13	21
₫%	0	0	0
	316	347	663

📾 - Cars

🚨 - Trucks

♣ - Bicycles

#### Comments

## **Peak Hour Summary**



Greenbank Rd & Kilbirnie Dr Intersection: 2410400002 Site Code: Count Date: Mar 20, 2024 15:00 - 18:00 Period:

	Peak Hour Data (15:30 - 16:30)																								
		,	North <i>F</i> Greenl	Approac bank Ro	:h i				South A Greenl	pproac	h I				East A <sub>l</sub> Ki <b>l</b> bir	pproach nie Dr				1	West A Ki <b>l</b> bir	pproacl nie Dr	n		Total Vehic
Start Time	4	1	*	4	Peds	Total	4	1		4	Peds	Total	•	1	P.	4	Peds	Total	4	1	۳.	J	Peds	Total	es
15:30	19	46	30	0	2	95	11	53	13	0	1	77	5	7	10	0	0	22	15	2	15	0	3	32	226
15:45	18	75	45	1	1	139	22	46	4	0	0	72	6	10	11	0	1	27	26	4	14	0	0	44	282
16:00	11	64	19	0	2	94	19	54	17	0	- 1	90	16	8	10	0	2	34	33	5	27	0	6	65	283
16:15	12	51	23	1	6	87	10	51	16	0	5	77	-11	14	5	0	2	30	29	4	17	0	7	50	244
Grand Total	60	236	117	2	11	415	62	204	50	0	7	316	38	39	36	0	5	113	103	15	73	0	16	191	1035
Approach %	14.5	56.9	28.2	0.5		-	19.6	64.6	15.8	0		-	33.6	34.5	31.9	0		-	53.9	7.9	38.2	0		-	
Totals %	5.8	22.8	11.3	0.2		40.1	6	19.7	4.8	0		30.5	3.7	3.8	3.5	0		10.9	10	1.4	7.1	0		18.5	
PHF	0.79	0.79	0.65	0.5		0.75	0.7	0.94	0.74	0		0.88	0.59	0.7	0.82	0		0.83	0.78	0.75	0.68	0		0.73	0.91
Cars	59	229	114	2		404	60	200	48	0		308	34	21	35	0		90	101	11	71	0		183	985
% Cars	98.3	97	97.4	100		97.3	96.8	98	96	0		97.5	89.5	53.8	97.2	0		79.6	98.1	73.3	97.3	0		95.8	95.2
Trucks	1	7	3	0		11	2	4	2	0		8	4	18	1	0		23	2	4	2	0		8	50
% Trucks	1.7	3	2.6	0		2.7	3.2	2	4	0		2.5	10.5	46.2	2.8	0		20.4	1.9	26.7	2.7	0		4.2	4.8
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
Peds					11	-					7	-					5	-					16	-	39
% Peds					28.2	-					17.9	-					12.8	-					41	-	

Wed Mar 23, 2022

Full Length (7 AM-10 AM, 11:30 AM-1:30 PM, 3 PM-6 PM) All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on Crosswalk)

All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103



						_							_											_	_
Leg	South					- 1	North						West						East						
Direction	Northb			**		-	Southbou					. 10	Eastbou					. Tata	Westbou			**		34	
Time	L	T	R		App Per		L	T		U	App		L	T	R	U	App F		L	T	R	U	App F		Int
2022-03-23 7:00AM	0		0	0	2	0	11	0		0	27	0	15	26	5	0	46	0	3	68	8	0	79	0	15-
7:15AM	0		0	0	0	0	14	0		0	34	0	11	21	1	0	33	0	1	57	10	0	68	0	13
7:30AM	0		0	0	1	0	15	0		0	44	0	8	35	5	0	48	0	0	79	14	0	93	0	18
7:45AM	1	0	0		1	0	9	1		0	29	0	19	38	2	0	59	0	2	80	16	0	98	0	18
Hourly Total	1	3	0	0	4	0	49	1		0	134	0	53	120	13	0	186	0	6	284	48	0	338	0	66:
8:00AM	1	1	0	0	2	0	19	0		0	42	1	23	55	1	0	79	0	1	70	11	0	82	0	20:
8:15AM	0		1	0	1	0	11	1		0	36	3	13	41	2	0	56	0	4	79	11	0	94	0	18
8:30AM	1	0	0		2	0	24	0		0	49	2	18	36	1	0	55 42	0	2	78	14	0	94	0	19
8:45AM		1	0	0		0	22	0		0	50	3	10	28	4	0		0	5	68	11	0	84	0	17
Hourly Total			1	0	6	0	76	1		0	177	9	64	160 27	8	0	232	0	12	295	47	0	354	0	76
9:00AM	3	_	3	0	6	0	12	1		0	34	3	18		2	0		_	2	69	18	0	89	0	170
9:15AM	2		0		3	0	7	0		0	16	3	15	37	4	0	56	0	1	47	14	0	62	0	13
9:30AM	2		2	0	4	0	10	0		0	27	1	12	32	3	0	47	0	2	33	12	0	47	0	12
9:45AM	2		3	0	6	0	16	1		0	33	0	10	27	1	0	38	0	4	44	19	0	67	0	14
Hourly Total	9		8	0	19	0	45	2		0	110	7	55	123	10	0	188	0	9	193	63	0	265	0	58
11:30AM	0		3		4	0	9	0		0	23	0	7	29	0	0	36	0	2	40	11	0	53	0	11
11:45AM	_		4	0	7	0	14	1		0	24	0	13	27	0	0	40	0	2	54	11	0	67	0	13
Hourly Total	_		7	0	11	0	23	1		0	47	0	20	56	0	0	76	0	4	94	22	0	120	0	25
12:00PM	2		5	0	7	0	12	3		0	30	0	14	37	1	0	52	0	0	45	11	0	56	0	14
12:15PM	_		3		6	0	10	0		0	20	0	9	39	1	0	49	0	2	35	19	0	56	0	13
12:30PM	3		1	0	5	0	12	1		0	26	0	12	32	3	0	47	0	2	27	14	0	43	0	12
12:45PM	1	1	2	0	4	0	13	0		0	23	0	9	39	1	0	49	0	2	37	11	0	50	0	12
Hourly Total	9		11	0	22	0	47	4		0	99	0	44	147	6	0	197	0	6	144	55	0	205	0	52
1:00PM	0		1	0	2	0	13	2		0	29	0	8	28	3	0	39	0	1	38	13	0	52	0	12
1:15PM	4		3	0	8	0	8	0		0	19	0	10	45	5	0	60	0	1	40	10	0	51	0	13
Hourly Total	. 4	2	4	0	10	0	21	2	25	0	48	0	18	73	8	0	99	0	2	78	23	0	103	0	26
3:00PM	4	_	3	0	8	0	15	1		0	47	0	16	50	1	0	67	0	1	53	11	0	65	0	18
3:15PM	3	1	2	0	6	0	8	0		0	18	0	16	71	2	0	89	0	0	56	14	0	70	0	18
3:30PM	8	1	4	0	13	0	18	3	17	0	38	1	11	63	1	0	75	0	2	43	14	0	59	0	18
3:45PM	5	0	1	0	6	0	21	0		0	38	0	19	68	0	0	87	0	0	63	16	0	79	0	21
Hourly Total	20	3	10	0	33	0	62	4	75	0	141	1	62	252	4	0	318	0	3	215	55	0	273	0	76
4:00PM	1	0	2	0	3	0	20	0	14	0	34	0	19	80	0	0	99	0	0	56	17	0	73	0	20
4:15PM	2	0	0	0	2	0	17	0		0	33	- 0	16	68	0	0	84	0	0	55	22	0	77	0	19
4:30PM	2	0	5	0	7	0	14	2	21	0	37	0	26	70	0	0	96	0	0	62	18	0	80	0	22
4:45PM	2	1	0	0	3	0	14	0	19	0	33	0	16	74	0	0	90	0	0	59	11	0	70	0	19
Hourly Total	7	1	7	0	15	0	65	2	70	0	137	0	77	292	0	0	369	0	0	232	68	0	300	0	82
5:00PM	0	0	0	0	0	0	12	0	27	0	39	0	18	69	1	0	88	0	0	52	11	0	63	0	19
5:15PM	2	0	1	0	3	0	16	1	20	0	37	0	20	78	0	0	98	0	0	51	12	0	63	0	20
5:30PM	0	1	1	0	2	0	10	0	19	0	29	0	18	74	0	0	92	0	2	54	18	0	74	0	19
5:45PM	. 0	0	1	0	1	0	10	0		0	20	0	20	71	0	0	91	0	0	37	17	0	54	0	16
Hourly Total	. 2	1	3	0	6	0	48	1	76	0	125	0	76	292	1	0	369	0	2	194	58	0	254	0	75
Total	. 57	18	51	0	126	0	436	18	564	0	1018	17	469	1515	50	0	2034	0	44	1729	439	0	2212	0	539
% Approach	45.2%	14.3%	10.5%	0%	-	- 4	12.8%	1.8%	55.4% 0	%	-	-	23.1% 7	74.5%	2.5% (	)%	-	-	2.0% 7	8.2% 1	9.8%	0%	-		
% Total	1.1%	0.3%	0.9%	0% :	2.3%	-1	8.1% (	0.3%	10.5% 0	% 1	8.9%	-	8.7% 2	28.1%	0.9% 0	9% 3	37.7%	-	0.8% 3	2.1%	8.1%	0% 4	11.0%		
Lights and Motorcycles	44	13	42	0	99	-1	416	11	533	0	960	-	437	1467	40	0	1944	-	37	1669	411	0	2117		512
% Lights and						$\top$																		$\neg$	
Motorcycles	77.2%	72.2%	32.4%	0% 7	3.6%	- 9	95.4% 6	1.1%	94.5% 0	% 9	94.3%	-	93.2% 9	96.8%	30.0% (	9% 9	95.6%	-	84.1% 9	6.5% 9	3.6%	0% 9	5.7%		95.09
Heavy	13	4	9	0	26	Ξ	20	5	31	0	56		32	48	10	0	90		7	59	28	0	94		26
% Heavy	22.8%	22.2%	17.6%	0% <b>2</b>	0.6%	1	4.6% 2	7.8%	5.5% 0	%	5.5%	-	6.8%	3.2%	20.0% (	)%	4.4%	-	15.9%	3.4%	6.4%	0%	4.2%	-	4.99
Bicycles on Road	0	1	0	0	1	1	0	2	0	0	2	Ξ	0	0	0	0	0	Ξ	0	1	0	0	1		
% Bicycles on Road	0%	5.6%	0%	0%	0.8%	I	0% 1	1.1%	0% 0	%	0.2%	_	0%	0%	0% 0	)%	0%		0%	0.1%	0%	0%	0%		0.19
Pedestrians	-	-	-	-	-	0	-	_	-	-	-	17	-	-	-	-	-	0	-		-	-	-	0	
% Pedestrians	-	-	-	-	-	-	-	-	-	-	- 1	00%	-	-	-	-	-	-	-	-	-	-	-	-	
Bicycles on Crosswalk	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	
% Bicycles on Crosswalk	-	-	-	-	-	-	-	-	-	-	-	0%	-	-	-	-	-	-	-	-	-	-	-		

<sup>\*</sup>Pedestrians and Bicycles on Crosswalk. L: Left, R: Right, T: Thru, U: U-Turn

5562791 - COVID - CAMBRIAN RD @ APOLUNE ST ... - TMC


Wed Mar 23, 2022

Full Length (7 AM-10 AM, 11:30 AM-1:30 PM, 3 PM-6 PM)
All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on

All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103





Out: 112 In: 126 Total: 238 [S] South

1 of 8 2 of 8

Wed Mar 23, 2022

AM Peak (7:45 AM - 8:45 AM)
All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on Crosswalk)

All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103



Leg	South					North						West						East					П	
Direction	Northb	ound				Southb	ound					Eastbou	and					Westbo	ound					
Time	L	T	R	U	App Ped*	L	Т	R	U	App	Ped*	L	T	R	U	App P	ed*	L	T	R	U	App P	ed*	Int
2022-03-23 7:45AM	1	0	0	0	1 0	9	1	19	0	29	0	19	38	2	0	59	0	2	80	16	0	98	0	187
8:00AM	1	1	0	0	2 0	19	0	23	0	42	1	23	55	1	0	79	0	1	70	11	0	82	0	205
8:15AM	0	0	1	0	1 0	11	1	24	0	36	3	13	41	2	0	56	0	4	79	11	0	94	0	187
8:30AM	1	0	0	0	1 0	24	0	25	0	49	2	18	36	1	0	55	0	2	78	14	0	94	0	199
Total	3	1	1	0	<b>5</b> 0	63	2	91	0	156	6	73	170	6	0	249	0	9	307	52	0	368	0	778
% Approach	60.0%	20.0%	20.0%	0%		40.4%	1.3%	58.3%	0%	-	-	29.3%	68.3%	2.4% (	0%	-	-	2.4% 8	33.4%	14.1%	0%	-	-	
% Total	0.4%	0.1%	0.1%	0%	0.6% -	8.1%	0.3%	11.7%	0%	20.1%	-	9.4%	21.9%	0.8%	0% 3	2.0%	-	1.2%	39.5%	6.7%	0% 4	7.3%	-	-
PHF	0.750	0.250	0.250	- (	).625 -	0.656	0.500	0.910	-	0.796	-	0.793	0.773	0.750	-	0.788	-	0.563	0.956	0.813	- 1	0.936	日	0.948
Lights and Motorcycles	1	1	1	0	3 -	59	0	85	0	144	-	65	161	3	0	229	-	9	298	45	0	352	-	728
% Lights and Motorcycles		100%	100%	n94 <b>6</b>	0.0%	93,7%	094	93,4%	094	02 3%		80 0%	04 7%	50.0% (	194.	2 0%		100%	07 194	86.5%	no4. <b>c</b>	15 794	П	93.6%
Heavy	2	0		0.00	2 -	33.776	_	6	_	12	_	8	9	30.070		20	_	0	8	7	0	15	7	49
% Heavy	_	0%			0.0%	_		6.6%	_	7.7%	_	11.0%		50.0% (	_		-	_	_	13.5%	<u> </u>	4.1%	$\dashv$	6.3%
Bicycles on Road	00.770	0.0		0	0.070 -	0.570			0.0	7.770	_	0	0.570	0		0.070	-	0.0	2.070	0	0	1	-1	0.570
% Bicycles on Road	0%	0%	0%		0% -	0%	_	0%	_	0%	_	0%	0%	0% (		0%	_		0.3%		_	0.3%	-1	0,1%
Pedestrians	070	070	0 /0	0 70	0.00	0.70	0 / 0	070	0 /0	070	6	070	070	0701	0 /0	070	0	070	0.570	070	0 /0	0.570	0	0.170
% Pedestrians	-			-	- 0	<del>-</del>			_		100%	_			-		- 0	<u> </u>			-		-4	_
Bicycles on Crosswalk	-	_		÷		<u> </u>	_		_	_	100%	_	_		÷	_	-	<u> </u>	_		_		- 0	
% Bicycles on Crosswalk	_			-	- 0	<u> </u>			_		0%	_			-		U				-		۰	
70 DICYCIES OII Crosswalk			-	-							0%		-		-	-	-		-		-			-

<sup>\*</sup>Pedestrians and Bicycles on Crosswalk. L: Left, R: Right, T: Thru, U: U-Turn

5562791 - COVID - CAMBRIAN RD @ APOLUNE ST ... - TMC

Wed Mar 23, 2022

AM Peak (7:45 AM - 8:45 AM)

All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on


All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103





Total: 282 In: 156 Out: 126



Out: 17 In: 5 Total: 22 [S] South

3 of 8 4 of 8

Wed Mar 23, 2022

Midday Peak (11:45 AM - 12:45 PM) All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on Crosswalk)

All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103



Leg	South					North					٦	West						East						
Direction	Northb	ound				Southb	ound					Eastbo	ınd					Westbo	und					
Time	L	Т	R	U	App Ped*	L	T	R	U	App Peo	1*	L	T	R	U	App P	ed*	L	T	R	U	App Pe	ed∗	Int
2022-03-23 11:45AM	2	1	4	0	7 0	14	1	9	0	24	0	13	27	0	0	40	0	2	54	11	0	67	0	138
12:00PM	2	0	5	0	7 0	12	3	15	0	30	0	14	37	1	0	52	0	0	45	11	0	56	0	145
12:15PM	3	0	3	0	<b>6</b> 0	10	0	10	0	20	0	9	39	1	0	49	0	2	35	19	0	56	0	131
12:30PM	3	1	1	0	<b>5</b> 0	12	1	13	0	26	0	12	32	3	0	47	0	2	27	14	0	43	0	121
Total	10	2	13	0	<b>25</b> 0	48	5	47	0	100	0	48	135	5	0	188	0	6	161	55	0	222	0	535
% Approach	40.0%	8.0%	52.0%	0%		48.0%	5.0%	47.0% (	)%	-	-1	25.5%	71.8%	2.7% (	)%	-	-	2.7%	72.5%	24.8%	0%	-	-	-
% Total	1.9%	0.4%	2.4%	0%	4.7% -	9.0%	0.9%	8.8% (	0% 1	8.7%	-	9.0%	25.2%	0.9% (	)% 3	35.1%	-	1.1%	30.1%	10.3%	0% 4	11.5%	-	-
PHF	0.833	0.500	0.650	- 1	0.893 -	0.857	0.417	0.783	-	0.833	-	0.857	0.865	0.417	-	0.904	-	0.750	0.745	0.724	-	0.828	-	0.922
Lights and Motorcycles	7	2	9	0	18 -	43	5	43	0	91	-	45	131	3	0	179	-	4	151	51	0	206	-	494
% Lights and Motorcycles		100%	69.2%	0% 7	2.0% -	89.6%	100%	91.5% (	)% <b>9</b>	01.0%	_	93.8%	97.0%	60.0% (	)% 9	95.2%		66.7%	93.8%	92.7%	0% 9	92.8%	_	92.3%
Heavy	3	0	4	0	7 -	5	0	4	0	9	-	3	4	2	0	9	-	2	10	4	0	16	-	41
% Heavy	30.0%	0%	30.8%	0% 2	8.0% -	10.4%	0%	8.5% (	)%	9.0%	-1	6.3%	3.0%	40.0% (	)%	4.8%	-	33.3%	6.2%	7.3%	0%	7.2%	-	7.7%
Bicycles on Road	0	0	0	0	0 -	0	0	0	0	0	-	0	0	0	0	0	-	0	0	0	0	0	-	0
% Bicycles on Road	0%	0%	0%	0%	0% -	0%	0%	0% 0	)%	0%	-	0%	0%	0% 0	)%	0%	-	0%	0%	0%	0%	0%	-	0%
Pedestrians	-	-	-	-	- 0	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	
% Pedestrians	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Bicycles on Crosswalk	-	-	-	-	- 0	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	
% Bicycles on Crosswalk	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

<sup>\*</sup>Pedestrians and Bicycles on Crosswalk. L: Left, R: Right, T: Thru, U: U-Turn

5562791 - COVID - CAMBRIAN RD @ APOLUNE ST ... - TMC

Wed Mar 23, 2022

Midday Peak (11:45 AM - 12:45 PM)

All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on

All Movements


ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103





Total: 205 In: 100 Out: 105

47 5 48



Out: 16 In: 25 Total: 41 [S] South

5 of 8 6 of 8

Wed Mar 23, 2022 PM Peak (3:45 PM - 4:45 PM) - Overall Peak Hour

All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on Crosswalk)

All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103



Leg	South						North						West					Ea	st					
Direction	Northbo	ound	l				Southb	ound					Eastbou	and				w	estbound	i				
Time	L	T	R	U	App	Ped*	L	T	R	U	App	Ped*	L	T	R	U	App Ped	T	_ т	R	U	App Pe	d*	Int
2022-03-23 3:45PM	5	0	1	0	6	0	21	0	17	0	38	0	19	68	0	0	87 (		63	16	0	79	0	210
4:00PM	1	0	2	0	3	0	20	0	14	0	34	0	19	80	0	0	99 (		) 56	17	0	73	0	209
4:15PM	2	0	0	0	2	0	17	0	16	0	33	0	16	68	0	0	84 (	Т	) 55	22	0	77	0	196
4:30PM	2	0	5	0	7	0	14	2	21	0	37	0	26	70	0	0	96 (		) 62	18	0	80	0	220
Total	10	0	8	0	18	0	72	2	68	0	142	0	80	286	0	0	366	0	236	73	0	309	0	835
% Approach	55.6%	D% 4	14.4% (	)%	-	-	50.7%	1.4%	47.9%	0%	-	-	21.9%	78.1%	0% (	)%	-	- 09	6 76.4%	23.6%	0%	-	-	-
% Total	1.2%	0%	1.0% (	)%	2.2%	-	8.6%	0.2%	8.1%	0%	17.0%	-	9.6%	34.3%	0% (	)% 4	13.8%	- 09	6 28.3%	8.7%	0% 3	37.0%	-	-
PHF	0.500	-	0.400	-	0.643	-	0.857	0.250	0.810	-	0.928	-	0.769	0.894	-	-	0.924	Т	- 0.937	0.830	-	0.966	-	0.952
Lights and Motorcycles	9	0	8	0	17	-	72	1	66	0	139	-	78	280	0	0	358	-	230	70	0	300	-	814
% Lights and																		Г						
Motorcycles	90.0%	_		_	4.4%	-	-	50.0%				-	97.5%			_		+	6 97.5%		_		-	97.5%
Heavy	1	0	0	0	1	-	0	0	2	0	2	-	2	6	0	0	8	1	) 6	3	0	9	-	20
% Heavy	10.0%	0%	0% (	)%	5.6%	-	0%	0%	2.9%	0%	1.4%	-	2.5%	2.1%	0% (	)%	2.2%	- 0%	6 2.5%	4.1%	0%	2.9%	-	2.4%
Bicycles on Road	0	0	0	0	0	-	0	1	0	0	1	-	0	0	0	0	0		0 0	0	0	0	-	1
% Bicycles on Road	0%	0%	0% (	)%	0%	-	0%	50.0%	0%	0%	0.7%	-	0%	0%	0% (	)%	0%	- 0%	6 0%	0%	0%	0%	-	0.1%
Pedestrians	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	- (			-	-	-	0	
% Pedestrians	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	T		-	-	-	-	-
Bicycles on Crosswalk	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	- (			-	-	-	0	
% Bicycles on Crosswalk	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	T	-		-	-	-	-

<sup>\*</sup>Pedestrians and Bicycles on Crosswalk. L: Left, R: Right, T: Thru, U: U-Turn

#### 5562791 - COVID - CAMBRIAN RD @ APOLUNE ST ... - TMC

Wed Mar 23, 2022

PM Peak (3:45 PM - 4:45 PM) - Overall Peak Hour

All Classes (Lights and Motorcycles, Heavy, Pedestrians, Bicycles on Road, Bicycles on


All Movements

ID: 932641, Location: 45.246542, -75.752395, Site Code: 40238103





Total: 295 In: 142 Out: 153



Out: 2 In: 18 Total: 20 [S] South

7 of 8 8 of 8



# Project #24-105 - CGH Transportation

# **Intersection Count Report**

Intersection: Greenbank Rd & Dundonald Dr

Municipality: Ottawa

Count Date: Wednesday, Mar 20, 2024

**Site Code:** 2410400001

**Count Categories:** Cars, Trucks, Bicycles, Pedestrians

**Count Period:** 07:00-10:00, 11:30-13:30, 15:00-18:00

Weather: Clear


**Comments:** 



# **Traffic Count Map**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Municipality: Ottawa
Count Date: Mar 20, 2024





# **Traffic Count Summary**

Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001

Municipality: Ottawa

Count Date: Mar 20, 2024

			Gree	nban	k Rd -	- Traf	fic Su	ımma	ary				
		North	Appr	oach T	otals			South	Appr	oach T	otals		
		Include	s Cars, 1	rucks, B	icycles			Include	s Cars, 1	Trucks, B	icycles		
Hour	Left	Thru	Right	U-Turn	Total	Peds	Left	Thru	Right	U-Turn	Total	Peds	Total
07:00 - 08:00	12	106	41	0	159	1	28	176	4	0	208	0	367
08:00 - 09:00	21	170	66	0	257	3	46	216	15	1	278	1	535
09:00 - 10:00	34	159	70	0	263	8	38	193	10	0	241	6	504
					В	REAK							
11:30 - 12:00	9	70	19	0	98	0	4	83	3	0	90	0	188
12:00 - 13:00	28	149	61	0	238	4	18	175	11	1	205	6	443
13:00 - 13:30	12	77	26	0	115	2	6	55	5	1	67	2	182
					В	REAK							
15:00 - 16:00	48	297	104	0	449	10	57	219	16	1	293	1	742
16:00 - 17:00	49	281	107	0	437	8	72	248	29	0	349	6	786
17:00 - 18:00	39	276	123	0	438	1	66	258	18	2	344	3	782
GRAND TOTAL	252	1585	617	0	2454	37	335	1623	111	6	2075	25	4529



# **Traffic Count Summary**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Municipality: Ottawa
Count Date: Mar 20, 2024

			Dun	donal	d Dr -	Traf	fic Su	ımma	iry				
		East /	Appro	ach To	tals			West	Appro	oach T	otals		
		Include	s Cars, 1	Trucks, Bi	cycles			Indude	s Cars, '	Trucks, B	icycles		
Hour	Left	Thru	Right	U-Turn	Total	Peds	Left	Thru	Right	U-Turn	Total	Peds	Tota
07:00 - 08:00	17	14	31	0	62	1	89	15	74	0	178	2	24
08:00 - 09:00	28	26	53	0	107	3	84	26	82	0	192	4	299
09:00 - 10:00	22	25	57	0	104	3	93	22	76	0	191	3	29
					В	REAK							
11:30 - 12:00	3	3	19	0	25	1	28	8	12	0	48	7	7.
12:00 - 13:00	17	10	34	0	61	5	69	5	29	0	103	10	16
13:00 - 13:30	1	7	16	0	24	3	24	6	11	0	41	8	6
					В	REAK							
15:00 - 16:00	15	38	45	0	98	1	88	31	67	0	186	5	284
16:00 - 17:00	21	36	47	0	104	9	115	29	60	0	204	4	308
17:00 - 18:00	7	31	43	0	81	4	94	23	31	0	148	14	22'
GRAND TOTAL	131	190	345	0	666	30	684	165	442	0	1291	57	195



Intersection: Greenbank Rd & Dundonald Dr

Mar 20, 2024

Site Code: 2410400001 Municipality: Ottawa

							Nor	th A	pproa	ich -	Green	bank	c Rd			
			Cars				Ti	rucks	_			Bi	cycles			
Start Time	4	1	<b>P</b>	J	Total	4	1		4	Total	4	1	*	J	Total	Total Peds
07:00	2	21	6	0	29	0	0	0	0	0	0	0	0	0	0	0
07:15	5	19	11	0	35	1	0	0	0	1	0	0	0	0	0	0
07:30	3	28	10	0	41	0	1	0	0	1	0	0	0	0	0	0
07:45	1	36	14	0	51	0	1	0	0	1	0	0	0	0	0	1
08:00	2	41	18	0	61	1	1	1	0	3	0	0	0	0	0	0
08:15	0	35	12	0	47	0	2	0	0	2	0	0	0	0	0	0
08:30	8	40	16	0	64	1	0	0	0	1	0	0	0	0	0	0
08:45	8	49	19	0	76	1	2	0	0	3	0	0	0	0	0	3
09:00	23	54	25	0	102	0	1	0	0	1	0	0	0	0	0	6
09:15	4	38	19	0	61	0	0	1	0	1	0	0	0	0	0	2
09:30	4	29	14	0	47	0	3	0	0	3	0	0	0	0	0	0
09:45	3	33	11	0	47	0	1	0	0	1	0	0	0	0	0	0
SUBTOTAL	63	423	175	0	661	4	12	2	0	18	0	0	0	0	0	12

Count Date:



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001 Municipality: Ottawa

Count Date: Mar 20, 2024

							Noi	rth A	ppro	ach -	Green	ıbanl	c Rd			
			Cars				T	rucks	_			Bi	cycles	_		
Start Time	4	1	1	J	Total	4	1	<b>P</b>	J.	Total	4	1	1	J	Total	Total Peds
11:30	5	28	11	0	44	0	1	0	0	1	0	0	0	0	0	0
11:45	4	41	8	0	53	0	0	0	0	0	0	0	0	0	0	0
12:00	5	33	10	0	48	0	0	0	0	0	0	0	0	0	0	0
12:15	13	47	21	0	81	0	1	0	0	1	0	0	0	0	0	1
12:30	5	25	20	0	50	0	0	0	0	0	0	0	0	0	0	3
12:45	5	42	9	0	56	0	1	1	0	2	0	0	0	0	0	0
13:00	4	43	10	0	57	0	0	0	0	0	0	0	0	0	0	2
13:15	7	34	14	0	55	1	0	2	0	3	0	0	0	0	0	0
SUBTOTAL	48	293	103	0	444	1	3	3	0	7	0	0	0	0	0	6



Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001 Municipality: Ottawa

Count Date: Mar 20, 2024

							Noi	th A	pproa	ach -	Greer	ıbank	c Rd			
			Cars				T	rucks				Bi	cycles			
Start Time	- 🐄	1	-	J	Total	4	1	-	J.	Total	4	1	<b>**</b>	J.	Total	Total Peds
15:00	9	53	22	0	84	0	0	0	0	0	0	0	0	0	0	(
15:15	7	67	22	0	96	0	1	0	0	1	0	0	0	0	0	C
15:30	17	80	29	0	126	0	3	2	0	5	0	0	0	0	0	5
15:45	15	91	28	0	134	0	2	1	0	3	0	0	0	0	0	5
16:00	7	72	24	0	103	0	1	0	0	1	0	0	0	0	0	4
16:15	12	66	25	0	103	0	3	0	0	3	0	0	0	0	0	C
16:30	11	57	35	0	103	0	0	0	0	0	0	0	0	0	0	4
16:45	19	82	23	0	124	0	0	0	0	0	0	0	0	0	0	C
17:00	7	69	29	0	105	0	0	0	0	0	0	0	0	0	0	0
17:15	8	71	37	0	116	0	2	0	0	2	0	0	0	0	0	C
17:30	12	81	29	0	122	0	0	0	0	0	0	0	0	0	0	0
17:45	12	53	28	0	93	0	0	0	0	0	0	0	0	0	0	1
SUBTOTAL	136	842	331	0	1309	0	12	3	0	15	0	0	0	0	0	19
GRAND TOTAL	247	1558	609	0	2414	5	27	8	0	40	0	0	0	0	0	37



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Site Code: 2410400001 Municipality: Ottawa

Count Date: Mar 20, 2024

							Sou	th A	pproa	ach -	Green	bank	c Rd			
			Cars				T	rucks	_			Bi	cycles			
Start Time	4	1	*	J	Total	4	1	<b>P</b>	4	Total	4	1	1	J.	Total	Total Peds
07:00	2	38	2	0	42	0	0	0	0	0	0	0	0	0	0	0
07:15	6	43	1	0	50	2	2	0	0	4	0	0	0	0	0	0
07:30	6	42	1	0	49	0	4	0	0	4	0	0	0	0	0	0
07:45	12	47	0	0	59	0	0	0	0	0	0	0	0	0	0	0
08:00	8	54	3	0	65	1	1	2	0	4	0	0	0	0	0	0
08:15	6	48	3	0	57	0	1	0	0	1	0	0	0	0	0	0
08:30	16	53	4	0	73	0	0	0	0	0	0	0	0	0	0	1
08:45	15	59	3	1	78	0	0	0	0	0	0	0	0	0	0	0
09:00	19	52	2	0	73	1	1	0	0	2	0	0	0	0	0	5
09:15	9	50	3	0	62	1	3	0	0	4	0	0	0	0	0	0
09:30	5	37	4	0	46	1	0	0	0	1	0	0	0	0	0	1_
09:45	1	49	1	0	51	1	1	0	0	2	0	0	0	0	0	0
SUBTOTAL	105	572	27	1	705	7	13	2	0	22	0	0	0	0	0	7



Intersection: Greenbank Rd & Dundonald Dr

2410400001 Site Code: Municipality: Ottawa Mar 20, 2024 Count Date:

							Sou	th A	pproa	ach -	Green	bank	Rd			
			Cars				Ti	rucks				Bi	cycles			
Start Time	4	1	*	J	Total	4	1	-	1	Total	4	1	•	1	Total	Total Peds
11:30	2	43	2	0	47	0	0	0	0	0	0	0	0	0	0	0
11:45	2	39	1	0	42	0	1	0	0	1	0	0	0	0	0	0
12:00	5	50	3	1	59	0	0	0	0	0	0	0	0	0	0	0
12:15	7	40	4	0	51	1	1	0	0	2	0	0	0	0	0	2
12:30	2	48	1	0	51	0	0	0	0	0	0	0	0	0	0	2
12:45	3	35	3	0	41	0	1	0	0	1	0	0	0	0	0	2
13:00	3	30	1	0	34	0	0	0	0	0	0	0	0	0	0	2
13:15	3	25	4	1	33	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL	27	310	19	2	358	1	3	0	0	4	0	0	0	0	0	8



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr 2410400001 Site Code:

Ottawa Municipality:

Count Date: Mar 20, 2024

							Sou	ıth A	pproa	ach -	Green	ıbank	c Rd			
			Cars				Т	rucks				Bi	cycles			
Start Time	*	<u> </u>	-	7	Total	4	1	P	<u>1</u>	Total	4	1	<b>P</b>	<u>u</u>	Total	Total Peds
15:00	7	53	2	0	62	0	0	0	0	0	0	0	0	0	0	1_
15:15	13	53	2	1	69	0	0	0	0	0	0	0	0	0	0	0
15:30	18	50	7	0	75	2	1	0	0	3	0	0	0	0	0	0
15:45	16	61	5	0	82	1	1	0	0	2	0	0	0	0	0	0
16:00	22	68	6	0	96	0	1	0	0	1	0	0	0	0	0	0
16:15	15	62	8	0	85	0	1	0	0	1	0	0	0	0	0	1
16:30	17	57	5	0	79	0	2	0	0	2	0	0	0	0	0	1
16:45	18	56	10	0	84	0	1	0	0	1	0	0	0	0	0	4
17:00	7	67	5	0	79	0	1	0	0	1	0	0	0	0	0	0
17:15	20	53	8	1	82	0	0	0	0	0	0	0	0	0	0	1
17:30	18	65	3	0	86	0	0	0	0	0	0	0	0	0	0	1
17:45	21	72	2	1	96	0	0	0	0	0	0	0	0	0	0	1
SUBTOTAL	192	717	63	3	975	3	8	0	0	11	0	0	0	0	0	10
GRAND TOTAL	324	1599	109	6	2038	11	24	2	0	37	0	0	0	0	0	25



Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001 Municipality: Ottawa Count Date: Mar 20, 2024

							Ea	st Ap	proa	ch - I	Dundo	nald	Dr			
		-	Cars				Ti	rucks				Bi	cycles			
Start Time	4	1	-	J.	Total	4	1	-	4	Total	4	1	1	J	Total	Total Peds
07:00	5	1	7	0	13	1	0	0	0	1	0	0	0	0	0	0
07:15	4	6	7	0	17	0	0	0	0	0	0	0	0	0	0	0
07:30	3	2	9	0	14	0	0	0	0	0	0	0	0	0	0	0
07:45	4	5	8	0	17	0	0	0	0	0	0	0	0	0	0	1
08:00	7	7	11	0	25	0	0	0	0	0	0	0	0	0	0	0
08:15	6	6	14	0	26	1	0	0	0	1	0	0	0	0	0	1
08:30	5	5	8	0	18	0	1	0	0	1	0	0	0	0	0	0
08:45	8	6	20	0	34	1	1	0	0	2	0	0	0	0	0	2
09:00	7	14	29	0	50	0	1	0	0	1	0	0	0	0	0	1
09:15	5	3	11	0	19	0	1	0	0	1	0	0	0	0	0	0
09:30	5	1	6	0	12	0	0	0	0	0	0	0	0	0	0	2
09:45	4	5	11	0	20	1	0	0	0	1	0	0	0	0	0	0
SUBTOTAL	63	61	141	0	265	4	4	0	0	8	0	0	0	0	0	7



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Municipality: Ottawa

Count Date: Mar 20, 2024

	East Approach - Dundonald Dr															
	Cars Trucks Bicycles															
Start Time	4	1	*	1	Total	4	1	<b>*</b>	1	Total	4	1	•	4	Total	Total Peds
11:30	1	1	9	0	11	0	0	0	0	0	0	0	0	0	0	0
11:45	1	2	10	0	13	1	0	0	0	1	0	0	0	0	0	1
12:00	11	1	10	0	22	0	0	0	0	0	0	0	0	0	0	1_
12:15	2	2	6	0	10	0	0	0	0	0	0	0	0	0	0	3
12:30	3	5	8	0	16	0	0	0	0	0	0	0	0	0	0	1
12:45	1	2	10	0	13	0	0	0	0	0	0	0	0	0	0	0
13:00	1	5	11	0	17	0	0	0	0	0	0	0	0	0	0	3
13:15	0	2	5	0	7	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL	20	20	69	0	109	1	0	0	0	1	0	0	0	0	0	9



Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001 Municipality: Ottawa

Count Date: Mar 20, 2024

	East Approach - Dundonald Dr															
			Cars				Т	rucks	_			Bi	cycles	_		
Start Time	4	1	<b>P</b>	J	Total	1	1	<b>P</b>	<u>1</u>	Total	4	1	<b>P</b>	<u>u</u>	Total	Total Peds
15:00	1	10	9	0	20	0	0	0	0	0	0	0	0	0	0	
15:15	5	8	12	0	25	1	1	0	0	2	0	0	0	0	0	
15:30	1	12	20	0	33	0	0	0	0	0	0	0	0	0	0	
15:45	6	7	4	0	17	1	0	0	0	1	0	0	0	0	0	
16:00	2	15	14	0	31	0	0	0	0	0	0	0	0	0	0	
16:15	3	7	17	0	27	0	0	1	0	1	0	0	0	0	0	
16:30	6	4	3	0	13	1	0	0	0	1	0	0	0	0	0	
16:45	9	10	12	0	31	0	0	0	0	0	0	0	0	0	0	
17:00	2	5	12	0	19	0	0	0	0	0	0	0	0	0	0	
17:15	3	8	9	0	20	0	0	0	0	0	0	0	0	0	0	
17:30	1	8	12	0	21	0	0	0	0	0	0	0	0	0	0	1
17:45	1	10	10	0	21	0	0	0	0	0	0	0	0	0	0	
SUBTOTAL	40	104	134	0	278	3	1	1	0	5	0	0	0	0	0	14
GRAND TOTAL	123	185	344	0	652	8	5	1	0	14	0	0	0	0	0	31



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Municipality: Ottawa

Count Date: Mar 20, 2024

	West Approach - Dundonald Dr															
	Cars Trucks							Bicycles								
Start Time	7			<u>'</u>	Total	7			-+	Total	7			-+	Total	Total Peds
07:00	15	4	17	0	36	0	0	0	0	0	0	0	0	0	0	1
07:15	18	4	22	0	44	1	0	0	0	1	0	0	0	0	0	1
07:30	30	1	20	0	51	1	0	0	0	1	0	0	0	0	0	0
07:45	24	6	13	0	43	0	0	2	0	2	0	0	0	0	0	0
08:00	19	8	19	0	46	0	0	0	0	0	0	0	0	0	0	1
08:15	25	8	22	0	55	0	0	0	0	0	0	0	0	0	0	0
08:30	18	7	22	0	47	0	0	0	0	0	0	0	0	0	0	1
08:45	22	3	19	0	44	0	0	0	0	0	0	0	0	0	0	2
09:00	44	8	37	0	89	0	0	4	0	4	0	0	0	0	0	1_
09:15	27	5	21	0	53	1	0	0	0	1	0	0	0	0	0	2
09:30	9	5	8	0	22	0	0	0	0	0	0	0	0	0	0	0
09:45	12	4	6	0	22	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL	263	63	226	0	552	3	0	6	0	9	0	0	0	0	0	9



Intersection: Greenbank Rd & Dundonald Dr

Site Code: 2410400001
Municipality: Ottawa
Count Date: Mar 20, 2024

	West Approach - Dundonald Dr															
	Cars Trucks Bicycles															
Start Time	4	1	-	1	Total	4	1	•	7	Total	4	1	•	1	Total	Total Peds
11:30	16	4	5	0	25	0	0	0	0	0	0	0	0	0	0	3
11:45	12	4	6	0	22	0	0	1	0	1	0	0	0	0	0	4
12:00	20	0	10	0	30	0	0	0	0	0	0	0	0	0	0	2
12:15	18	2	8	0	28	1	0	0	0	1	0	0	0	0	0	3
12:30	15	1	8	0	24	0	0	0	0	0	0	0	0	0	0	2
12:45	15	2	3	0	20	0	0	0	0	0	0	0	0	0	0	3
13:00	9	4	4	0	17	0	0	0	0	0	0	0	0	0	0	7
13:15	15	1	6	0	22	0	1	1	0	2	0	0	0	0	0	1
SUBTOTAL	120	18	50	0	188	1	1	2	0	4	0	0	0	0	0	25



## **Traffic Count Data**

Intersection: Greenbank Rd & Dundonald Dr Site Code: 2410400001

Site Code: 2410400001 Municipality: Ottawa Count Date: Mar 20, 2024

	West Approach - Dundonald Dr															
	Cars Trucks Bicycles															
Start Time	4	1	-	J	Total	4	1		J.	Total	4	1		J	Total	Total Peds
15:00	19	4	8	0	31	0	0	0	0	0	0	0	0	0	0	2
15:15	15	1	8	0	24	0	0	0	0	0	0	0	0	0	0	0
15:30	25	9	12	0	46	0	0	0	0	0	0	0	0	0	0	2
15:45	29	15	38	0	82	0	2	1	0	3	0	0	0	0	0	1
16:00	33	7	19	0	59	0	2	0	0	2	0	0	0	0	0	0
16:15	29	8	14	0	51	1	2	0	0	3	0	0	0	0	0	0
16:30	28	3	8	0	39	0	0	0	0	0	0	0	0	0	0	4
16:45	24	7	19	0	50	0	0	0	0	0	0	0	0	0	0	0
17:00	22	4	6	0	32	0	0	0	0	0	0	0	0	0	0	3
17:15	22	4	11	0	37	0	0	0	0	0	0	0	0	0	0	6
17:30	26	8	9	0	43	0	1	0	0	1	0	0	0	0	0	3
17:45	24	6	5	0	35	0	0	0	0	0	0	0	0	0	0	2
SUBTOTAL	296	76	157	0	529	1	7	1	0	9	0	0	0	0	0	23
GRAND TOTAL	679	157	433	0	1269	5	8	9	0	22	0	0	0	0	0	57



**Specified Period** 

**One Hour Peak** 

From:

To:

07:00:00 To: 10:00:00 08:30:00

09:30:00

Greenbank Rd & Dundonald Dr Intersection:

2410400001 Site Code: Count Date: Mar 20, 2024 Weather conditions: Clear

### \*\* Signalized Intersection \*\*

#### Major Road: Greenbank Rd runs N/S

#### North Approach Out In Total 303 393 11 5 0 0 309 398 707



East	App	roa	ch

	Out	In	Total
	121	78	199
	5	2	7
₩	0	0	0
	126	80	206

#### **Dundonald Dr**

	Totals		₽	₫6
7	0	0	0	0
4	112	111	1	0
$\rightarrow$	23	23	0	0
4	103	99	4	0



Peds: 6

Peds: 11



Dun	dona	d	Dr

Totals		ها	<b>₫</b>	
0	0	0	0	
68	68	0	0	
32	28	4	0	
26	25	1	0	
	0	<b>0</b> 0 <b>68</b> 68	<b>0</b> 0 0 <b>68</b> 68 0	<b>0</b> 0 0 0 0 <b>68</b> 68 0 0

### West Approach

	Out	In	Total
	233	166	399
	5	7	12
₫6	0	0	0
	238	173	411

	4	1	•	J.
Totals	61	218	12	1
	59	214	12	1
₽	2	4	0	0
₫	0	0	0	0

4	t	r	J.		Sout	h App	roa
61	218	12	1		Out	In	Tot
59	214	12	1	<b>⊟</b>	286	306	5
2	4	0	0	D.	6	8	
0	0	0	0	<i>₫</i> %	0	0	
Gree	nbank	Rd		· ·	292	314	6

📾 - Cars

🚨 - Trucks

♣ - Bicycles

#### Comments





Greenbank Rd & Dundonald Dr Intersection: 2410400001 Site Code:

Count Date: Mar 20, 2024 07:00 - 10:00 Period:

	Peak Hour Data (08:30 - 09:30)																								
		-	North <i>F</i> Greenl	oank Ro	h I				outh A Greent	pproac	h I				East A	pproach onald Dr	1				West A Dundo	proacl nald Dr	h r		Total Vehic
Start Time	4	1	•	4	Peds	Total	4	1	*	1	Peds	Total	4	1	12	4	Peds	Total	4	1	*	1	Peds	Total	es
08:30	9	40	16	0	0	65	16	53	4	0	1	73	5	6	8	0	0	19	18	7	22	0	1	47	204
08:45	9	51	19	0	3	79	15	59	3	- 1	0	78	9	7	20	0	2	36	22	3	19	0	2	44	237
09:00	23	55	25	0	6	103	20	53	2	0	5	75	7	15	29	0	1	51	44	8	41	0	1	93	322
09:15	4	38	20	0	2	62	10	53	3	0	0	66	5	4	- 11	0	0	20	28	5	21	0	2	54	202
Grand Total	45	184	80	0	11	309	61	218	12		6	292	26	32	68	0	3	126	112	23	103	0	6	238	965
Approach %	14.6	59.5	25.9	0		-	20.9	74.7	4.1	0.3		-	20.6	25.4	54	0		-	47.1	9.7	43.3	0		-	
Totals %	4.7	19.1	8.3	0		32	6.3	22.6	1.2	0.1		30.3	2.7	3.3	7	0		13.1	11.6	2.4	10.7	0		24.7	_
PHF	0.49	0.84	0.8	0		0.75	0.76	0.92	0.75	0.25		0.94	0.72	0.53	0.59	0		0.62	0.64	0.72	0.63	0		0.64	0.75
Cars	43	181	79	0		303	59	214	12	- 1		286	25	28	68	0		121	111	23	99	0		233	943
% Cars	95.6	98.4	98.8	0		98.1	96.7	98.2	100	100		97.9	96.2	87.5	100	0		96	99.1	100	96.1	0		97.9	97.7
Trucks	2	3	1	0		6	2	4	0	0		6	1	4	0	0		5	1	0	4	0		5	22
% Trucks	4.4	1.6	1.3	0		1.9	3.3	1.8	0	0		2.1	3.8	12.5	0	0		4	0.9	0	3.9	0		2.1	2.3
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
Peds					11	-					6	-					3	-					6	-	26
% Peds					42.3	-					23.1						11.5						23.1	-	



**Specified Period** 

**One Hour Peak** 

From:

To:

11:30:00 To: 13:30:00 11:45:00

12:45:00

Greenbank Rd & Dundonald Dr Intersection:

2410400001 Site Code: Count Date: Mar 20, 2024 Weather conditions:

Clear

### \*\* Signalized Intersection \*\*

#### Major Road: Greenbank Rd runs N/S

**East Approach** 

Out In Total

61

0

43 104

0 0

0

62 43 105

#### North Approach Out In Total **232** 276 508 4 0 0 233 279 512



Peds: 4



#### **Dundonald Dr**

	Totals		₽	₫6
7	0	0	0	0
4	66	65	1	0
-	7	7	0	0
4	33	32	1	0



	Totals		₽	₫6
C	0	0	0	0
L	34	34	0	0
-	10	10	0	0
F	18	17	1	0

**Dundonald Dr** 

	West Approach								
	Out	In	Total						
3	104	85	189						
b	2	1	3						
e.	۸	١٨	l n						

106 86 192

	4	1	•	J
Totals	17	179	9	1
<del>=</del>	16	177	9	1
₽	1	2	0	C
₫%	0	0	0	C
	Gree	nbank	Rd	

Peds: 4

	Sout	n Appi	roacn
	Out	In	Total
	203	196	399
	3	3	6
₫6	0	0	0
	206	199	405

📾 - Cars

🚨 - Trucks

♣ - Bicycles

#### Comments

## **Peak Hour Summary**



Greenbank Rd & Dundonald Dr Intersection: 2410400001 Site Code:

Count Date: Mar 20, 2024 11:30 - 13:30 Period:

									Pea	ık Ho	our [	ata	(11:4	<b>15</b> -	12:4	5)									
	North Approach South Approach Greenbank Rd Greenbank Rd								East Approach Dundonald Dr					'	West A Dundo	pproacl nald Dr	1		Total Vehic						
Start Time	4	1	•	J	Peds	Total	4	1		4	Peds	Total	4	1	P	J	Peds	Total	4	1		J	Peds	Total	es
11:45	4	41	8	0	0	53	2	40	1	0	0	43	2	2	10	0	1	14	12	4	7	0	4	23	133
12:00	5	33	10	0	0	48	5	50	3	1	0	59	11	1	10	0	1	22	20	0	10	0	2	30	159
12:15	13	48	21	0	- 1	82	8	41	4	0	2	53	2	2	6	0	3	10	19	2	8	0	3	29	174
12:30	5	25	20	0	3	50	2	48	- 1	0	2	51	3	- 5	8	0	1	16	15	1	8	0	2	24	141
Grand Total	27	147	59	0	4	233	17	179	9		4	206	18	10	34	0	6	62	66		33	0	11	106	607
Approach %	11.6	63.1	25.3	0		-	8.3	86.9	4.4	0.5		-	29	16.1	54.8	0		-	62.3	6.6	31.1	0		-	
Totals %	4.4	24.2	9.7	0		38.4	2.8	29.5	1.5	0.2		33.9	3	1.6	5.6	0		10.2	10.9	1.2	5.4	0		17.5	
PHF	0.52	0.77	0.7	0		0.71	0.53	0.9	0.56	0.25		0.87	0.41	0.5	0.85	0		0.7	0.83	0.44	0.83	0		0.88	0.87
Cars	27	146	59	0		232	16	177	9	1		203	17	10	34	0		61	65	7	32	0		104	600
% Cars	100	99.3	100	0		99.6	94.1	98.9	100	100		98.5	94.4	100	100	0		98.4	98.5	100	97	0		98.1	98.8
Trucks	0	1	0	0		1	1	2	0	0		3	1	0	0	0		1	1	0	1	0		2	7
% Trucks	0	0.7	0	0		0.4	5.9	1.1	0	0		1.5	5.6	0	0	0		1.6	1.5	0	3	0		1.9	1.2
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
Peds					4	-					4	-					6	-					- 11	-	25
% Peds					16	-					16	-					24						44	-	



**Specified Period** 

**One Hour Peak** 

From:

To:

15:00:00 To: 18:00:00 15:30:00

16:30:00

Greenbank Rd & Dundonald Dr Intersection:

2410400001 Site Code: Count Date: Mar 20, 2024 Weather conditions: Clear

### \*\* Signalized Intersection \*\*

### Major Road: Greenbank Rd runs N/S

#### North Approach Out In Total 466 412 878 18 0 0

478 418 896

	4		<b>1</b>	LÎ.						
Totals	109	318	51	0						
	106	309	51	0						
₽	3	9	0	0						
₫	0	0	0	0						
Greenbank Rd										

# **East Approach**

	Out	In	Total
	108	116	224
	2	6	8
₩	0	0	0
	110	122	232

#### **Dundonald Dr**

	Totals		₽	₫6
7	0	0	0	0
4	117	116	1	0
-	45	39	6	0
4	84	83	1	0



Peds: 1

Peds: 14

	Dun	donald	Dr
	Totals		Ę.
-		0	

	Totals		۴Đ	46
C	0	0	0	0
L	56	55	1	0
-	41	41	0	0
₽	13	12	1	0

#### West Approach

	Out	In	Total
	238	218	456
₽	8	6	14
₫6	0	0	0
	246	224	470

	4	t	•	J
Totals	74	245	26	0
	71	241	26	0
	3	4	0	0
₫%	0	0	0	0

**Greenbank Rd** 

l l		Sout	h Appı	roach
0		Out	In	Total
0	⊟	338	404	742
0	₽	7	11	18
0	<i>₫</i> %	0	0	0
		345	415	760

📾 - Cars



♣ - Bicycles

#### Comments





Greenbank Rd & Dundonald Dr Intersection: 2410400001 Site Code:

Count Date: Mar 20, 2024 15:00 - 18:00 Period:

	Peak Hour Data (15:30 - 16:30)																								
		-	North <i>F</i> Greenl	oank Ro	h I				outh A Greenl	ipproac oank Ro	h i				East A	pproach onald Dr	1				West A Dundo	pproacl nald Dr	h r		Total Vehic
Start Time	4	1	•	1	Peds	Total	4	1		1	Peds	Total	4	1	*	1	Peds	Total	4	1	•	1	Peds	Total	es
15:30	17	83	31	0	5	131	20	51	7	0	0	78	1	12	20	0	0	33	25	9	12	0	2	46	288
15:45	15	93	29	0	5	137	17	62	5	0	0	84	7	7	4	0	1	18	29	17	39	0	1	85	324
16:00	7	73	24	0	4	104	22	69	6	0	0	97	2	15	14	0	1	31	33	9	19	0	0	61	293
16:15	12	69	25	0	0	106	15	63	8	0	1	86	3	7	18	0	2	28	30	10	14	0	0	54	274
Grand Total	51	318	109	0	14	478	74	245	26	0		345	13	41	56	0	4	110	117	45	84	0	3	246	1179
Approach %	10.7	66.5	22.8	0		-	21.4	71	7.5	0		-	11.8	37.3	50.9	0		-	47.6	18.3	34.1	0		-	
Totals %	4.3	27	9.2	0		40.5	6.3	20.8	2.2	0		29.3	1.1	3.5	4.7	0		9.3	9.9	3.8	7.1	0		20.9	
PHF	0.75	0.85	0.88	0		0.87	0.84	0.89	0.81	0		0.89	0.46	0.68	0.7	0		0.83	0.89	0.66	0.54	0		0.72	0.91
Cars	51	309	106	0		466	71	241	26	0		338	12	41	55	0		108	116	39	83	0		238	1150
% Cars	100	97.2	97.2	0		97.5	95.9	98.4	100	0		98	92.3	100	98.2	0		98.2	99.1	86.7	98.8	0		96.7	97.5
Trucks	0	9	3	0		12	3	4	0	0		7	1	0	1	0		2	1	6	1	0		8	29
% Trucks	0	2.8	2.8	0		2.5	4.1	1.6	0	0		2	7.7	0	1.8	0		1.8	0.9	13.3	1.2	0		3.3	2.5
Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0
% Bicycles	0	0	0	0		0	0	0	0	0		0	0	0	. 0	0		0	0	0	0	0		0	0
Peds					14	-					- 1	-					4	-					3	-	22
% Peds					63.6	-					4.5	-					18.2						13.6	-	

# Appendix C

Synchro Intersection Worksheets – Existing Conditions



Lanes, Volumes, Timings
1: Elevation/Apolune & Cambrian

Existing AM Peak Hour

# HCM 2010 TWSC 1: Elevation/Apolune & Cambrian

Existing AM Peak Hour

	•	<b>→</b>	*	1	•	•	1	<b>†</b>	1	-	ļ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	f)		7	f)		7	<b>1</b>		*	1>	
Traffic Volume (vph)	73	170	6	9	307	52	3	1	1	63	2	91
Future Volume (vph)	73	170	6	9	307	52	3	1	1	63	2	91
Satd. Flow (prot)	1658	1736	0	1658	1707	0	1658	1614	0	1658	1489	0
Flt Permitted	0.950			0.950			0.950			0.950		
Satd. Flow (perm)	1658	1736	0	1658	1707	0	1658	1614	0	1658	1489	0
Lane Group Flow (vph)	81	196	0	10	399	0	3	2	0	70	103	0
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Control Type: Unsignalized												
Intersection Capacity Utiliza	tion 45.0%			IC	U Level	of Service	A .					
Analysis Period (min) 15												

Intersection												
Int Delay, s/veh	4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	ĵ.		×	1		*	1		*	1>	
Traffic Vol., veh/h	73	170	6	9	307	52	3	1	1	63	2	91
Future Vol, veh/h	73	170	6	9	307	52	3	1	1	63	2	91
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-		None	-	-	None	-	-	None	-		None
Storage Length	37.5		-	37.5		-	30		-	30	-	-
Veh in Median Storage		0	-	-	0	-	-	0	-	-	0	_
Grade. %	-,	0		-	0			0			0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mymt Flow	81	189	7	10	341	58	3	1	1	70	2	101
	•	100			011				·	, ,	_	101
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	399	0	0	196	0	0	797	774	193	746	748	370
	399	-	U	190	-	-	355	355	193	390	390	3/0
Stage 1 Stage 2			-				442	419	-	356	358	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	4.12		•	4.12			6.12	5.52	0.22	6.12	5.52	0.22
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218		-	3.518	4.018		3.518		3.318
Pot Cap-1 Maneuver	1160	-		1377	-	-	305	329	849	330	341	676
Stage 1	1100		-	13//		-	662	630	049	634	608	0/0
Stage 1			-		-	-	594	590	-	661	628	-
Platoon blocked, %	-	-	•	-		•	094	590	•	001	020	-
Mov Cap-1 Maneuver	1160	-	-	1377	-	-	243	304	849	310	315	676
Mov Cap-1 Maneuver	1100		-	1011	-	-	243	304	049	310	315	0/0
Stage 1							616	586	_	590	604	-
Stage 2	-						500	586	-	613	584	-
Staye 2							500	500	_	013	504	_
Approach	EB			WB			NB			SB		
HCM Control Delay, s	2.4			0.2			17.2			14.9		
HCM LOS							С			В		
Minor Lane/Major Mvn	nt I	NBLn1	NBI n2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBI n2	
Capacity (veh/h)		243	448	1160	-	LDIX	1377		-	310	660	
HCM Lane V/C Ratio		0.014		0.07		-	0.007	-		0.226		
HCM Control Delay (s)	١	20	13.1	8.3	-	-	7.6	-		20	11.5	
HCM Lane LOS		C	13.1 B	0.5 A			7.0 A			20 C	П.5	
HCM 95th %tile Q(veh	Λ	0	0	0.2			0			0.9	0.6	
HOW SOUL YOUR CI(VELL	1	U	U	0.2			U			0.9	0.0	

Existing AM Peak Hour

Synchro 11 Report

Page 3

	•	$\rightarrow$	*	1	•	•	1	<b>†</b>	-	1	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1>		*	13		*	<b>†</b>	7	7	<b>†</b>	7
Traffic Volume (vph)	85	18	85	53	8	56	41	142	26	31	210	75
Future Volume (vph)	85	18	85	53	8	56	41	142	26	31	210	75
Satd. Flow (prot)	1658	1330	0	1626	1424	0	1658	1745	1230	1642	1712	1483
Flt Permitted	0.711			0.684			0.950			0.950		
Satd. Flow (perm)	1239	1330	0	1171	1424	0	1658	1745	1230	1642	1712	1483
Satd. Flow (RTOR)		94			62				132			132
Lane Group Flow (vph)	94	114	0	59	71	0	46	158	29	34	233	83
Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Protected Phases		4			8		5	2		1	6	
Permitted Phases	4			8					2			6
Detector Phase	4	4		8	8		5	2	2	1	6	6
Switch Phase												
Minimum Initial (s)	10.0	10.0		10.0	10.0		5.0	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.6	28.6		28.6	28.6		11.1	28.1	28.1	11.1	28.1	28.1
Total Split (s)	30.0	30.0		30.0	30.0		19.0	31.0	31.0	19.0	31.0	31.0
Total Split (%)	37.5%	37.5%		37.5%	37.5%		23.8%	38.8%	38.8%	23.8%	38.8%	38.8%
Yellow Time (s)	3.3	3.3		3.3	3.3		3.7	3.7	3.7	3.7	3.7	3.7
All-Red Time (s)	3.3	3.3		3.3	3.3		2.4	2.4	2.4	2.4	2.4	2.4
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.6	6.6		6.6	6.6		6.1	6.1	6.1	6.1	6.1	6.1
Lead/Lag							Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?							Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	None	None		None	None		None	Max	Max	None	Max	Max
Act Effct Green (s)	12.5	12.5		12.5	12.5		7.3	33.9	33.9	6.9	31.2	31.2
Actuated g/C Ratio	0.21	0.21		0.21	0.21		0.12	0.58	0.58	0.12	0.53	0.53
v/c Ratio	0.36	0.32		0.24	0.20		0.22	0.16	0.04	0.18	0.26	0.10
Control Delay	25.7	10.1		23.7	9.2		29.5	12.7	0.1	29.5	15.0	1.6
Queue Delay	0.0	0.0		0.0	0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	25.7	10.1		23.7	9.2		29.5	12.7	0.1	29.5	15.0	1.6
LOS	С	В		С	Α		С	В	Α	С	В	Α
Approach Delay		17.1			15.8			14.4			13.2	
Approach LOS		В			В			В			В	
Queue Length 50th (m)	9.6	1.9		5.9	0.9		4.8	6.1	0.0	3.5	17.1	0.0
Queue Length 95th (m)	21.8	13.1		14.9	9.5		15.0	29.8	0.0	12.2	43.9	3.4
Internal Link Dist (m)		340.0			278.8			525.9			476.9	
Turn Bay Length (m)	45.0			17.5			75.0		20.0	95.0		40.0
Base Capacity (vph)	511	603		482	623		376	1008	766	373	908	849
Starvation Cap Reductn	0	0		0	0		0	0	0	0	0	0
Spillback Cap Reductn	0	0		0	0		0	0	0	0	0	0
Storage Cap Reductn	0	0		0	0		0	0	0	0	0	0
Reduced v/c Ratio	0.18	0.19		0.12	0.11		0.12	0.16	0.04	0.09	0.26	0.10

Intersection Summary

Cycle Length: 80
Actuated Cycle Length: 58.7

Natural Cycle: 70
Control Type: Semi Act-Uncoord
Maximum v/c Ratio: 0.36


Scenario 1 HMBS P7 12:30 pm 03-20-2025 Existing

Lanes, Volumes, Timings 2: Greenbank & Kilbirnie

Existing AM Peak Hour

Intersection Signal Delay: 14.8 Intersection Capacity Utilization 43.1% Analysis Period (min) 15 Intersection LOS: B ICU Level of Service A

Splits and Phases: 2: Greenbank & Kilbirnie



Existing AM Peak Hour

Synchro 11 Report

Page 5

	•	$\rightarrow$	7	1	•	*	1	1	1	1	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4		*	<b>^</b>	7	7	<b>†</b>	7
Traffic Volume (vph)	112	23	103	26	32	68	61	218	13	45	184	80
Future Volume (vph)	112	23	103	26	32	68	61	218	13	45	184	80
Satd. Flow (prot)	0	1606	0	0	1602	0	1658	1745	1483	1658	1745	1483
Flt Permitted		0.812			0.899		0.950			0.950		
Satd. Flow (perm)	0	1335	0	0	1454	0	1658	1745	1483	1658	1745	1483
Satd. Flow (RTOR)		52			76				129			129
Lane Group Flow (vph)	0	264	0	0	141	0	68	242	14	50	204	89
Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Protected Phases		4			8		5	2		1	6	
Permitted Phases	4			8					2			6
Detector Phase	4	4		8	8		5	2	2	1	6	6
Switch Phase												
Minimum Initial (s)	10.0	10.0		10.0	10.0		5.0	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	33.3	33.3		33.3	33.3		11.1	31.1	31.1	11.1	31.1	31.1
Total Split (s)	33.3	33.3		33.3	33.3		15.1	31.1	31.1	15.1	31.1	31.1
Total Split (%)	41.9%	41.9%		41.9%	41.9%		19.0%	39.1%	39.1%	19.0%	39.1%	39.1%
Yellow Time (s)	3.3	3.3		3.3	3.3		3.7	3.7	3.7	3.7	3.7	3.7
All-Red Time (s)	3.0	3.0		3.0	3.0		2.4	2.4	2.4	2.4	2.4	2.4
Lost Time Adjust (s)		0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)		6.3			6.3		6.1	6.1	6.1	6.1	6.1	6.1
Lead/Lag							Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?							Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	None	None		None	None		None	Max	Max	None	Max	Max
Act Effct Green (s)		16.8			16.8		7.7	26.5	26.5	7.4	26.3	26.3
Actuated g/C Ratio		0.26			0.26		0.12	0.42	0.42	0.12	0.41	0.41
v/c Ratio		0.68			0.32		0.34	0.33	0.02	0.26	0.28	0.13
Control Delay		26.9			12.5		34.6	18.3	0.1	33.4	18.0	2.2
Queue Delay		0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay		26.9			12.5		34.6	18.3	0.1	33.4	18.0	2.2
LOS		С			В		С	В	Α	С	В	Α
Approach Delay		26.9			12.5			20.9			16.1	
Approach LOS		С			В			С			В	
Queue Length 50th (m)		24.6			6.6		8.1	21.6	0.0	6.0	18.1	0.0
Queue Length 95th (m)		47.9			18.9		21.2	48.4	0.0	16.8	40.8	4.8
Internal Link Dist (m)		151.1			120.0			476.9			285.2	
Turn Bay Length (m)							60.0		35.0	120.0		90.0
Base Capacity (vph)		616			682		243	725	691	243	719	687
Starvation Cap Reductn		0			0		0	0	0	0	0	0
Spillback Cap Reductn		0			0		0	0	0	0	0	0
Storage Cap Reductn		0			0		0	0	0	0	0	0
Reduced v/c Ratio		0.43			0.21		0.28	0.33	0.02	0.21	0.28	0.13
Intersection Cummens												

Cycle Length: 79.5
Actuated Cycle Length: 63.8

Natural Cycle: 80 Control Type: Semi Act-Uncoord Maximum v/c Ratio: 0.68


Scenario 1 HMBS P7 12:30 pm 03-20-2025 Existing

Lanes, Volumes, Timings 3: Greenbank & Dundonald

Existing AM Peak Hour

Intersection Signal Delay: 19.8 Intersection Capacity Utilization 52.8% Analysis Period (min) 15 Intersection LOS: B ICU Level of Service A

Splits and Phases: 3: Greenbank & Dundonald



Lanes, Volumes, Timings 1: Elevation/Apolune & Cambrian

Existing PM Peak Hour

HCM 2010 TWSC	
1: Elevation/Apolune & Cambrian	

Existing PM Peak Hour

	•	$\rightarrow$	*	-	•	•	1	Ť	1	-	Į.	4														
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	Intersection													
Lane Configurations	LDL K	î,	LDIN	WDL *	₩ <b>1</b>	WDIX	NDL	1001 13	NUN	SDL k	<b>1</b>	JUIN	Int Delay, s/veh	4												
Traffic Volume (vph)	80	286	0	0	236	73	10	0	8	72	2	68		•			14/D1		14/00	N.D.	NIDE	NDD	001		000	
Future Volume (vph)	80	286	0	0	236	73	10	0	8	72	2	68	Movement	EBL		EBR '	WBL		WBR	NBL		NBR	SBL		SBR	
Satd. Flow (prot)	1658	1745	0		1684	0	1658	1483	0	1658	1490	0	Lane Configurations	7	Þ		٦	Þ		٦	ĵ.		٦	ĥ		
Flt Permitted	0.950	11 10			1001		0.950	1100		0.950	1100		Traffic Vol, veh/h	80		0	0	236	73	10	0	8	72	2		
Satd. Flow (perm)	1658	1745	0	1745	1684	0	1658	1483	0	1658	1490	0	Future Vol, veh/h	80		0	0	236	73	10	0	8	72	2		
Lane Group Flow (vph)	89	318	0	0	343	0	11	9	0	80	78	0	Conflicting Peds, #/hi			0	0	0	0	0	0	0	0	0		
Sign Control		Free			Free			Stop			Stop		Sign Control						Free		- · · · p				Stop	
•											- 11-1	_	RT Channelized	-		None	-		None	-		None	-		None	
Intersection Summary													Storage Length	37.5			37.5	-	-	30	-		30	-		
Control Type: Unsignalized													Veh in Median Storag				-	-	-	-	-	-	-	0		
Intersection Capacity Utilizat	tion 43.4%			IC'	CU Level o	of Service	Α						Grade, %	-		-	-	0	-	-	0	-	-	0	-	
Analysis Period (min) 15													Peak Hour Factor	90		90	90	90	90	90	90	90	90	90		
													Heavy Vehicles, %	2		2	2	2	2	2	2	2	2	2		
													Mvmt Flow	89	318	0	0	262	81	11	0	9	80	2	76	
													Major/Minor	Major1		Ma	ajor2		N	/linor1		M	linor2			
													Conflicting Flow All	343	0	0	318	0	0	838	839	318	804	799	303	
													Stage 1	-	-	-	-	-	-	496	496	-	303	303	-	
													Stage 2	-	-	-	-	-	-	342	343	-	501	496	-	
													Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22	
													Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-	
													Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-	
													Follow-up Hdwy	2.218	-	- 2	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318	
													Pot Cap-1 Maneuver	1216	-	- '	1242	-	-	286	302	723	301	319	737	
													Stage 1	-	-	-	-	-	-	556	545		706	664	-	
													Stage 2		-	-	-	-	_	673	637		552	545	-	
													Platoon blocked, %													
													r latouri blockeu, 70		-	-		-	-							
													Mov Cap-1 Maneuve		-		1242	-	-	241	280		281	296	737	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve				1242	-	-	241	280	723	281 281	296	737 -	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1			- '		- - -	-	241 515		723 -	281 281 654	296 664		
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve		-	- '	-	-	- - -	241	280	723 -	281 281	296	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1	· -	-	- - -	-	-	- - -	241 515	280 505	723 -	281 281 654	296 664	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2	· _	- - -	- - -	- - -	-	- - -	241 515 602	280 505	723 -	281 281 654 505	296 664	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach	- - - EB	-	- - -	- - - WB	-	- - -	241 515 602 NB	280 505	723 - - -	281 281 654 505	296 664	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay,	- - - EB	-	- - -	- - -	-	- - -	241 515 602 NB 15.9	280 505	723 - - -	281 281 654 505 SB 16.8	296 664	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach	- - - EB	-	- - -	- - - WB	-	- - -	241 515 602 NB	280 505	723 - - -	281 281 654 505	296 664	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS	EB 1.8	-		- - - WB	-	-	241 515 602 NB 15.9	280 505 637	723	281 281 654 505 SB 16.8 C	296 664 505	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS	EB 1.8	- - - NBLn1 N	- · · · · · · · · · · · · · · · · · · ·	- - - WB 0	- - - - EBT	- - - - -	241 515 602 NB 15.9 C	280 505 637 WBT	723 - WBR S	281 281 654 505 SB 16.8 C	296 664 505	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS  Minor Lane/Major My Capacity (veh/h)	EB 1.8	- - - NBLn1 N	NBLn2	- - - WB 0	-	- - - - -	241 515 602 NB 15.9	280 505 637	723 - - - WBR S	281 281 654 505 SB 16.8 C	296 664 505 68Ln2 707	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS  Minor Lane/Major Mv Capacity (veh/h) HCM Lane V/C Ratio	EB 1.8	NBLn1 N 241 0.046	NBLn2 723 0.012 0	WB 0  EBL 1216 0.073	- - - - EBT	- - - - - EBR	241 515 602 NB 15.9 C	280 505 637 WBT	723 - - - - WBR S	281 281 654 505 SB 16.8 C	296 664 505 6BLn2 707 0.11	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS  Minor Lane/Major M. Capacity (veh/h) HCM Lane V/C Ratio HCM Control Delay (Delay)	EB 1.8	NBLn1 N 241 0.046 20.7	NBLn2 723 0.012 0	WB 0  EBL 1216 0.073 8.2	- - - - - EBT	- - - - - EBR	241 515 602 NB 15.9 C	280 505 637 WBT	723 - - - - - - -	281 281 654 505 SB 16.8 C	296 664 505 6BLn2 707 0.11 10.7	-	
													Mov Cap-1 Maneuve Mov Cap-2 Maneuve Stage 1 Stage 2  Approach HCM Control Delay, HCM LOS  Minor Lane/Major Mv Capacity (veh/h) HCM Lane V/C Ratio	EB 1.8	NBLn1 N 241 0.046	NBLn2 723 0.012 0	WB 0  EBL 1216 0.073	- - - - EBT	EBR -	241 515 602 NB 15.9 C	280 505 637 WBT	723 - - - - - - -	281 281 654 505 SB 16.8 C	296 664 505 68Ln2 707 0.11 10.7 B	-	

Existing PM Peak Hour

Synchro 11 Report

Page 3

	•	$\rightarrow$	*	1	•	*	1	Ť	1	1	Ţ	1
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	1		7	ĵ.		7	<b>†</b>	7	1	<b>^</b>	7
Traffic Volume (vph)	103	15	73	38	39	36	62	204	50	62	236	117
Future Volume (vph)	103	15	73	38	39	36	62	204	50	62	236	117
Satd. Flow (prot)	1658	1455	0	1523	1305	0	1642	1745	1455	1658	1728	1469
Flt Permitted	0.703			0.694			0.950			0.950		
Satd. Flow (perm)	1225	1455	0	1113	1305	0	1640	1745	1455	1658	1728	1437
Satd. Flow (RTOR)		81			40				132			132
Lane Group Flow (vph)	114	98	0	42	83	0	69	227	56	69	262	130
Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Protected Phases		4			8		5	2		1	6	
Permitted Phases	4			8					2			6
Detector Phase	4	4		8	8		5	2	2	1	6	6
Switch Phase												
Minimum Initial (s)	10.0	10.0		10.0	10.0		5.0	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.6	28.6		28.6	28.6		11.1	28.1	28.1	11.1	28.1	28.1
Total Split (s)	30.0	30.0		30.0	30.0		19.0	31.0	31.0	19.0	31.0	31.0
Total Split (%)	37.5%	37.5%		37.5%	37.5%		23.8%	38.8%	38.8%	23.8%	38.8%	38.8%
Yellow Time (s)	3.3	3.3		3.3	3.3		3.7	3.7	3.7	3.7	3.7	3.7
All-Red Time (s)	3.3	3.3		3.3	3.3		2.4	2.4	2.4	2.4	2.4	2.4
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.6	6.6		6.6	6.6		6.1	6.1	6.1	6.1	6.1	6.1
Lead/Lag							Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?							Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	None	None		None	None		None	Max	Max	None	Max	Max
Act Effct Green (s)	13.1	13.1		13.1	13.1		8.2	31.5	31.5	8.2	31.4	31.4
Actuated g/C Ratio	0.22	0.22		0.22	0.22		0.14	0.52	0.52	0.14	0.52	0.52
v/c Ratio	0.43	0.26		0.17	0.26		0.31	0.25	0.07	0.31	0.29	0.16
Control Delay	27.8	9.7		23.2	15.4		30.5	15.7	0.2	30.5	16.1	4.4
Queue Delay	0.0	0.0		0.0	0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	27.8	9.7		23.2	15.4		30.5	15.7	0.2	30.5	16.1	4.4
LOS	С	Α		С	В		С	В	Α	С	В	Α
Approach Delay		19.4			18.0			16.1			15.0	
Approach LOS		В			В			В			В	
Queue Length 50th (m)	12.2	1.7		4.2	4.3		7.4	17.6	0.0	7.4	20.8	0.0
Queue Length 95th (m)	26.7	12.1		12.0	14.7		20.2	43.9	0.0	20.2	51.0	10.6
Internal Link Dist (m)		340.0			278.8			525.9			472.4	
Turn Bay Length (m)	45.0			17.5			75.0		20.0	95.0		40.0
Base Capacity (vph)	496	637		451	552		367	913	825	370	904	814
Starvation Cap Reductn	0	0		0	0		0	0	0	0	0	0
Spillback Cap Reductn	0	0		0	0		0	0	0	0	0	0
Storage Cap Reductn	0	0		0	0		0	0	0	0	0	0
Reduced v/c Ratio	0.23	0.15		0.09	0.15		0.19	0.25	0.07	0.19	0.29	0.16

L	n	t	e	r	s	e	C	tı	C	I	1	١	9	U	l	ľ	1	1	1	l	

Cycle Length: 80 Actuated Cycle Length: 60.1

Natural Cycle: 70
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 0.43


Scenario 1 HMBS P7 12:30 pm 03-20-2025 Existing

Lanes, Volumes, Timings 2: Greenbank & Kilbirnie

Existing PM Peak Hour

Intersection Signal Delay: 16.5 Intersection Capacity Utilization 50.9% Analysis Period (min) 15 Intersection LOS: B ICU Level of Service A

Splits and Phases: 2: Greenbank & Kilbirnie



Lane Group

Lane Configurations		٠	<b>→</b>	*	1	•	•	1	<b>†</b>	1	-	ļ	1
Traffic Volume (vph) 103 15 73 38 39 36 62 204 50 62 236 Future Volume (vph) 103 15 73 38 39 36 62 204 50 62 236 Future Volume (vph) 100 1500 1800 1800 1800 1800 1800 1800	Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Traffic Volume (vph) 103 15 73 38 39 36 62 204 50 62 236 Future Volume (vph) 103 15 73 38 39 36 62 204 50 62 236 Ideal Flow (vphpl) 1800 1800 1800 1800 1800 1800 1800 180	Lane Configurations	*	1		*	1		*	<b>^</b>	7	*	<b>^</b>	7
Real Flow (vphpl)   1800   1	Traffic Volume (vph)	103		73	38		36	62	204	50	62	236	117
Total Lost time (s) 6.6 6.6 6.6 6.6 6.6 6.1 6.1 6.1 6.1 6.1	Future Volume (vph)	103	15	73	38	39	36	62	204	50	62	236	117
Lane Util, Factor 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.0	Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Frpb, ped/bikes	Total Lost time (s)	6.6	6.6		6.6	6.6		6.1	6.1	6.1	6.1	6.1	6.1
Fipb, ped/bikes	Lane Util. Factor	1.00	1.00		1.00	1.00		1.00	1.00	1.00	1.00	1.00	1.00
Frit Protected 0.95 1.00 0.88 1.00 0.93 1.00 1.00 0.85 1.00 1.00 Filt Protected 0.95 1.00 0.90 0.90 0.90 0.90 0.90 0.90 0.90	Frpb, ped/bikes	1.00	1.00		1.00	0.99		1.00	1.00	1.00	1.00	1.00	0.98
Fit Protected 0.95 1.00 0.95 1.00 0.95 1.00 1.00 0.95 1.00 1.00 0.95 1.00 1.00 Satd. Flow (prot) 1656 1455 1523 1305 1642 1745 1455 1658 1728 1 151 Permitted 0.70 1.00 0.69 1.00 0.95 1.0	Flpb, ped/bikes	1.00	1.00		1.00	1.00		1.00	1.00	1.00	1.00	1.00	1.00
Satd. Flow (prot)         1656         1455         1523         1305         1642         1745         1455         1658         1728         1 Fil Permitted         0.70         1.00         0.69         1.00         0.95         1.00         1.09         5.95         1.00         1.00         0.95         1.00         0.95         1.00         0.95         1.00         0.95         1.00         0.95         1.00         0.95         1.00         0.95         1.00         0.90         <	Frt	1.00	0.88		1.00	0.93		1.00	1.00	0.85	1.00	1.00	0.85
Fit Permitted	Flt Protected	0.95	1.00		0.95	1.00		0.95	1.00	1.00	0.95	1.00	1.00
Satd, Flow (perm)         1225         1455         1112         1305         1642         1745         1455         1658         1728         1           Peak-hour factor, PHF         0.90         0.60         0.60         0.60         0.60         0.60         <	Satd. Flow (prot)	1656	1455		1523	1305		1642	1745	1455	1658	1728	1437
Peak-hour factor, PHF         0.90         0.00	Flt Permitted	0.70	1.00		0.69	1.00		0.95	1.00	1.00	0.95	1.00	1.00
Adj. Flow (vph)	Satd. Flow (perm)	1225	1455		1112	1305		1642	1745	1455	1658	1728	1437
RTOR Reduction (vph)	Peak-hour factor, PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Lane Group Flow (vph) 114 30 0 42 50 0 69 227 26 69 262  Confl. Peds. (#/hr) 1 1 1 1  Heavy Vehicles (%) 2% 27% 3% 11% 46% 3% 3% 2% 4% 2% 3%  Turn Type Perm NA Perm NA Prot NA Perm Prot NA Prot Protected Phases 4 8 5 2 1 6  Permitted Phases 4 8 5 2 1 6  Actuated Green, G (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 5.0 29.9 5.0 29.9 29.9 6.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0	Adj. Flow (vph)	114	17	81	42	43	40	69	227	56	69	262	130
Confl. Peds. (#/hr)	RTOR Reduction (vph)	0	68	0	0	33	0	0	0	30	0	0	69
Heavy Vehicles (%)	Lane Group Flow (vph)	114	30	0	42	50	0	69	227	26	69	262	61
Turn Type         Perm         NA         Perm         NA         Prot         NA         Perm         Perm         Prot         NA	Confl. Peds. (#/hr)	1					1	1					1
Protected Phases	Heavy Vehicles (%)	2%	27%	3%	11%	46%	3%	3%	2%	4%	2%	3%	3%
Permitted Phases 4 Actuated Green, G (s) 10.5 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Actuated g/c Ratio 0.16 0.16 0.16 0.16 0.16 0.08 0.47 0.47 0.08 0.47 Clearance Time (s) 6.6 6.6 6.6 6.6 6.6 6.1 6.1 6.1 6.1 6.1	Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Actuated Green, G (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 10.5 5.0 29.9 29.9 5.0 29.9 Effective Green, g (s) 10.5 10.5 10.5 10.5 10.5 10.5 10.5 10.5	Protected Phases		4			8		5	2		1	6	
Effective Green, g (s)         10.5         10.5         10.5         10.5         29.9         29.9         29.9         5.0         29.9           Actuated g/C Ratio         0.16         0.16         0.16         0.16         0.16         0.08         0.47         0.47         0.08         0.47           Clearance Time (s)         6.6         6.6         6.6         6.6         6.6         6.1         6.1         6.1         6.1         6.1           Vehicle Extension (s)         3.0	Permitted Phases	4			8					2			6
Actuated g/C Ratio 0.16 0.16 0.16 0.16 0.16 0.08 0.47 0.47 0.08 0.47 Clearance Time (s) 6.6 6.6 6.6 6.6 6.6 6.1 6.1 6.1 6.1 6.1	Actuated Green, G (s)	10.5	10.5		10.5	10.5		5.0	29.9	29.9	5.0	29.9	29.9
Clearance Time (s)         6.6         6.6         6.6         6.6         6.6         6.1         6.2         8.0           Vis Ratio Perm         0.02         0.04         0.	Effective Green, g (s)	10.5	10.5		10.5	10.5		5.0	29.9	29.9	5.0	29.9	29.9
Vehicle Extension (s)         3.0         4.0         4.0         4.0         4.0         4.0         4.0         4.0         4.0         4.0         4.0         5.0         3.3         2.8         10.8         9.3         28.5         10.8         9.3         28.5         10.8         9.3         28.5         10.8         9.3         28.5         10.0         1.00	Actuated g/C Ratio	0.16	0.16		0.16	0.16		0.08	0.47	0.47	0.08	0.47	0.47
Lane Grp Cap (vph)         200         237         181         213         127         812         677         129         804           v/s Ratio Prot         0.02         0.04         c0.04         0.13         0.04         c0.15           v/s Ratio Perm         c0.09         0.04         0.02         0.02         0.02           v/c Ratio         0.57         0.13         0.23         0.23         0.54         0.28         0.04         0.53         0.33           Uniform Delay, d1         24.8         22.9         23.3         23.3         28.5         10.5         9.3         28.5         10.8           Progression Factor         1.00 <td< td=""><td>Clearance Time (s)</td><td>6.6</td><td>6.6</td><td></td><td>6.6</td><td>6.6</td><td></td><td>6.1</td><td>6.1</td><td>6.1</td><td>6.1</td><td>6.1</td><td>6.1</td></td<>	Clearance Time (s)	6.6	6.6		6.6	6.6		6.1	6.1	6.1	6.1	6.1	6.1
v/s Ratio Prot         0.02         0.04         c0.04         0.13         0.04         c0.15           v/s Ratio Perm         c0.09         0.04         0.04         0.02         0.02         0.02           v/c Ratio         0.57         0.13         0.23         0.23         0.54         0.28         0.04         0.53         0.33           Uniform Delay, d1         24.8         22.9         23.3         23.3         28.5         10.5         9.3         28.5         10.8           Progression Factor         1.00         1	Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0	3.0	3.0	3.0	3.0
v/s Ratio Prot         0.02         0.04         c0.04         0.13         0.04         c0.15           v/s Ratio Perm         c0.09         0.04         0.04         0.02         0.02         0.02           v/c Ratio         0.57         0.13         0.23         0.23         0.54         0.28         0.04         0.53         0.33         0.03           Uniform Delay, d1         24.8         22.9         23.3         23.3         28.5         10.5         9.3         28.5         10.8           Progression Factor         1.00         1	Lane Grp Cap (vph)	200	237		181	213		127	812	677	129	804	669
v/c Ratio         0.57         0.13         0.23         0.23         0.54         0.28         0.04         0.53         0.33           Uniform Delay, d1         24.8         22.9         23.3         23.3         28.5         10.5         9.3         28.5         10.8           Progression Factor         1.00			0.02			0.04		c0.04	0.13		0.04	c0.15	
Uniform Delay, d1         24.8         22.9         23.3         23.3         28.5         10.5         9.3         28.5         10.8           Progression Factor         1.00         1.10         1.10         1.11         1.11         1.11         1.11         1.12         1.11         1.12         1.12         1.11         1.12         1.12         1.12         1.11         1.12         1.11         1.12         1.12         1.12         1.12 <t< td=""><td>v/s Ratio Perm</td><td>c0.09</td><td></td><td></td><td>0.04</td><td></td><td></td><td></td><td></td><td>0.02</td><td></td><td></td><td>0.04</td></t<>	v/s Ratio Perm	c0.09			0.04					0.02			0.04
Progression Factor         1.00         1.10         1.00         1.00         1.00         1.10         1.00         1.10 <td>v/c Ratio</td> <td>0.57</td> <td>0.13</td> <td></td> <td>0.23</td> <td>0.23</td> <td></td> <td>0.54</td> <td>0.28</td> <td>0.04</td> <td>0.53</td> <td>0.33</td> <td>0.09</td>	v/c Ratio	0.57	0.13		0.23	0.23		0.54	0.28	0.04	0.53	0.33	0.09
Incremental Delay, d2   3.7   0.2   0.7   0.6   4.7   0.9   0.1   4.2   1.1	Uniform Delay, d1	24.8	22.9		23.3	23.3		28.5	10.5	9.3	28.5	10.8	9.6
Delay (s)       28.5       23.2       24.0       23.9       33.2       11.4       9.4       32.7       11.9         Level of Service       C       C       C       C       C       B       A       C       B         Approach Delay (s)       26.0       23.9       15.4       14.4         Approach LOS       C       C       B       B         Intersection Summary         HCM 2000 Control Delay       17.9       HCM 2000 Level of Service       B         HCM 2000 Volume to Capacity ratio       0.41	Progression Factor	1.00	1.00		1.00	1.00		1.00	1.00	1.00	1.00	1.00	1.00
Delay (s)       28.5       23.2       24.0       23.9       33.2       11.4       9.4       32.7       11.9         Level of Service       C       C       C       C       C       B       A       C       B         Approach LOS       C       C       C       B       B       B         Intersection Summary         HCM 2000 Control Delay       17.9       HCM 2000 Level of Service       B         HCM 2000 Volume to Capacity ratio       0.41	Incremental Delay, d2	3.7	0.2		0.7	0.6		4.7	0.9	0.1	4.2	1.1	0.3
Approach Delay (s)         26.0         23.9         15.4         14.4           Approach LOS         C         C         B         B           Intersection Summary           HCM 2000 Control Delay         17.9         HCM 2000 Level of Service         B           HCM 2000 Volume to Capacity ratio         0.41		28.5	23.2		24.0	23.9		33.2	11.4	9.4	32.7	11.9	9.8
Approach LOS         C         C         B         B           Intersection Summary           HCM 2000 Control Delay         17.9         HCM 2000 Level of Service         B           HCM 2000 Volume to Capacity ratio         0.41         0.41	Level of Service	С	С		С	С		С	В	Α	С	В	Α
Approach LOS         C         C         B         B           Intersection Summary         HCM 2000 Control Delay         17.9         HCM 2000 Level of Service         B           HCM 2000 Volume to Capacity ratio         0.41         0.41	Approach Delay (s)		26.0			23.9			15.4			14.4	
HCM 2000 Control Delay         17.9         HCM 2000 Level of Service         B           HCM 2000 Volume to Capacity ratio         0.41			С			С			В			В	
HCM 2000 Volume to Capacity ratio 0.41	Intersection Summary												
					H	CM 2000	Level of	Service		В			
	HCM 2000 Volume to Capa	acity ratio											
	Actuated Cycle Length (s)			64.2	Sı	um of lost	time (s)			18.8			
Intersection Capacity Utilization 50.9% ICU Level of Service A	Intersection Capacity Utiliza	ation		50.9%	IC	U Level	of Service			Α			
Analysis Period (min) 15	Analysis Period (min)			15									

O					•		*		-	-		-
Lane Configurations Traffic Volume (vph)	117	<b>45</b>	84	13	<b>4</b> 3	56	<b>1</b> 74	<b>↑</b> 245	<b>7</b> 26	<b>5</b> 1	<b>↑</b> 318	<b>1</b> 09
Future Volume (vph)	117	45	84	13	41	56	74	245	26	51	318	109
Satd. Flow (prot)	0	1627	0	0	1615	00	1658	1745	1483	1658	1745	1483
Fit Permitted	U	0.815	U	U	0.949	U	0.950	1/45	1463	0.950	1740	1403
	0	1357	0	0	1542	0	1658	4745	4.400	1658	4745	4400
Satd. Flow (perm)	0		0	0		0	1008	1745	1483	1008	1745	1483
Satd. Flow (RTOR)	0	32	0	0	62 122	0	82	070	120 29	57	252	121
Lane Group Flow (vph)	0	273	U	0		U		272			353	121
Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Protected Phases Permitted Phases	,	4		0	8		5	2	0	1	6	_
	4			8	0		_	0	2		^	6
Detector Phase	4	4		8	8		5	2	2	1	6	6
Switch Phase	40.0	40.0		40.0	40.0			40.0	40.0		40.0	40.0
Minimum Initial (s)	10.0	10.0 33.3		10.0 33.3	10.0 33.3		5.0	10.0	10.0 31.1	5.0	10.0	10.0 31.1
Minimum Split (s)	33.3						11.1	31.1		11.1	31.1	
Total Split (s)	33.3	33.3		33.3	33.3		21.1	31.1	31.1	21.1 24.7%	31.1	31.1
Total Split (%)	38.9%	38.9%		38.9%	38.9%		24.7%	36.4%	36.4%		36.4%	36.4%
Yellow Time (s)	3.3	3.3		3.3	3.3		3.7	3.7	3.7	3.7	3.7	3.7
All-Red Time (s)	3.0	3.0		3.0	3.0		2.4	2.4	2.4	2.4	2.4	2.4
Lost Time Adjust (s)		0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)		6.3			6.3		6.1	6.1	6.1	6.1	6.1	6.1
Lead/Lag							Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?		N.I.		N.			Yes	Yes	Yes	Yes	Yes	Yes
Recall Mode	None	None		None	None		None	Max	Max	None	Max	Max
Act Effct Green (s)		17.8			17.8		8.9	29.6	29.6	8.0	26.1	26.1
Actuated g/C Ratio		0.26			0.26		0.13	0.43	0.43	0.12	0.38	0.38
v/c Ratio		0.73			0.27		0.38	0.36	0.04	0.30	0.53	0.19
Control Delay		33.3			13.4		35.5	19.1	0.1	35.1	24.0	5.5
Queue Delay		0.0			0.0		0.0	0.0	0.0	0.0	0.0	0.0
Total Delay		33.3			13.4		35.5	19.1	0.1	35.1	24.0	5.5
LOS		С			В		D	В	Α	D	С	Α
Approach Delay		33.3			13.4			21.2			20.9	
Approach LOS		С			В			С			С	
Queue Length 50th (m)		29.0			6.1		10.1	26.0	0.0	7.0	36.6	0.0
Queue Length 95th (m)		56.5			18.4		24.5	56.6	0.0	18.8	77.9	11.3
Internal Link Dist (m)		151.3			120.5			472.4			285.4	
Turn Bay Length (m)							60.0		35.0	120.0		90.0
Base Capacity (vph)		572			665		375	754	708	375	663	638
Starvation Cap Reductn		0			0		0	0	0	0	0	0
Spillback Cap Reductn		0			0		0	0	0	0	0	0
Storage Cap Reductn		0			0		0	0	0	0	0	0
Reduced v/c Ratio		0.48			0.18		0.22	0.36	0.04	0.15	0.53	0.19
Intersection Summary												

EBL EBT EBR WBL WBT WBR NBL NBT NBR SBL

Cycle Length: 85.5
Actuated Cycle Length: 68.6

Natural Cycle: 80 Control Type: Semi Act-Uncoord Maximum v/c Ratio: 0.73


c Critical Lane Group

#### Lanes, Volumes, Timings 3: Greenbank & Dundonald

Existing PM Peak Hour

Intersection Signal Delay: 22.9 Intersection Capacity Utilization 58.8% Analysis Period (min) 15 Intersection LOS: C ICU Level of Service B

Splits and Phases: 3: Greenbank & Dundonald



HCM Signalized Intersection Capacity Analysis 3: Greenbank & Dundonald

Existing PM Peak Hour


	۶	<b>→</b>	*	•	+	•	1	1	~	1	Ţ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4		7	<b>^</b>	7	1	<b>^</b>	7
Traffic Volume (vph)	117	45	84	13	41	56	74	245	26	51	318	109
Future Volume (vph)	117	45	84	13	41	56	74	245	26	51	318	109
Ideal Flow (vphpl)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Total Lost time (s)		6.3			6.3		6.1	6.1	6.1	6.1	6.1	6.1
Lane Util. Factor		1.00			1.00		1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.95			0.93		1.00	1.00	0.85	1.00	1.00	0.85
Fit Protected		0.98			0.99		0.95	1.00	1.00	0.95	1.00	1.00
Satd. Flow (prot)		1626			1616		1658	1745	1483	1658	1745	1483
Flt Permitted		0.81			0.95		0.95	1.00	1.00	0.95	1.00	1.00
Satd. Flow (perm)		1356			1543		1658	1745	1483	1658	1745	1483
Peak-hour factor, PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	130	50	93	14	46	62	82	272	29	57	353	121
RTOR Reduction (vph)	0	24	0	0	46	0	0	0	17	0	0	74
Lane Group Flow (vph)	0	249	0	0	76	0	82	272	12	57	353	47
Turn Type	Perm	NA		Perm	NA		Prot	NA	Perm	Prot	NA	Perm
Protected Phases		4			8		5	2		1	6	
Permitted Phases	4			8					2			6
Actuated Green, G (s)		17.8			17.8		7.3	29.6	29.6	5.0	27.3	27.3
Effective Green, g (s)		17.8			17.8		7.3	29.6	29.6	5.0	27.3	27.3
Actuated g/C Ratio		0.25			0.25		0.10	0.42	0.42	0.07	0.39	0.39
Clearance Time (s)		6.3			6.3		6.1	6.1	6.1	6.1	6.1	6.1
Vehicle Extension (s)		3.0			3.0		3.0	3.0	3.0	3.0	3.0	3.0
Lane Grp Cap (vph)		340			387		170	728	619	116	671	571
v/s Ratio Prot							c0.05	0.16		0.03	c0.20	
v/s Ratio Perm		c0.18			0.05				0.01			0.03
v/c Ratio		0.73			0.20		0.48	0.37	0.02	0.49	0.53	0.08
Uniform Delay, d1		24.4			20.9		30.0	14.3	12.1	31.7	16.8	13.8
Progression Factor		1.00			1.00		1.00	1.00	1.00	1.00	1.00	1.00
Incremental Delay, d2		7.9			0.2		2.2	1.5	0.1	3.3	2.9	0.3
Delay (s)		32.3			21.2		32.2	15.7	12.2	35.0	19.7	14.1
Level of Service		С			С		С	В	В	С	В	В
Approach Delay (s)		32.3			21.2			19.0			20.1	
Approach LOS		С			С			В			С	
Intersection Summary												
HCM 2000 Control Delay			22.4	Н	CM 2000	Level of S	Service		С			
HCM 2000 Volume to Capac	ity ratio		0.59									
Actuated Cycle Length (s)			70.9	Si	um of lost	time (s)			18.5			
Intersection Capacity Utilizat	ion		58.8%	IC	U Level	of Service			В			
Analysis Period (min)			15									
á `a												


c Critical Lane Group

# Appendix D

Realigned Greenbank Road Preliminary Design







# Appendix E

**TDM Checklist** 



## **TDM Measures Checklist:**

Residential Developments (multi-family, condominium or subdivision)

_		
		Legend
	BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users
	BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance
	*	The measure is one of the most dependably effective tools to encourage the use of sustainable modes

	TDM	measures: Residential developments	Check if proposed & add descriptions
	1.	TDM PROGRAM MANAGEMENT	
	1.1	Program coordinator	
BASIC *	1.1.1	Designate an internal coordinator, or contract with an external coordinator	
	1.2	Travel surveys	
BETTER	1.2.1	Conduct periodic surveys to identify travel-related behaviours, attitudes, challenges and solutions, and to track progress	
	2.	WALKING AND CYCLING	
	2.1	Information on walking/cycling routes & des	tinations
BASIC	2.1.1	Display local area maps with walking/cycling access routes and key destinations at major entrances (multi-family, condominium)	
	2.2	Bicycle skills training	
BETTER	2.2.1	Offer on-site cycling courses for residents, or subsidize off-site courses	

	TDM	measures: Residential developments	Check if proposed & add descriptions
	3.	TRANSIT	
	3.1	Transit information	
BASIC	3.1.1	Display relevant transit schedules and route maps at entrances (multi-family, condominium)	
BETTER	3.1.2	Provide real-time arrival information display at entrances (multi-family, condominium)	
	3.2	Transit fare incentives	
BASIC	★ 3.2.1	Offer PRESTO cards preloaded with one monthly transit pass on residence purchase/move-in, to encourage residents to use transit	
BETTER	3.2.2	Offer at least one year of free monthly transit passes on residence purchase/move-in	
	3.3	Enhanced public transit service	
BETTER	★ 3.3.1	Contract with OC Transpo to provide early transit services until regular services are warranted by occupancy levels (subdivision)	
	3.4	Private transit service	
BETTER	3.4.1	Provide shuttle service for seniors homes or lifestyle communities (e.g. scheduled mall or supermarket runs)	
	4.	CARSHARING & BIKESHARING	
	4.1	Bikeshare stations & memberships	
BETTER	4.1.1	Contract with provider to install on-site bikeshare station (multi-family)	
BETTER	4.1.2	Provide residents with bikeshare memberships, either free or subsidized (multi-family)	
	4.2	Carshare vehicles & memberships	
BETTER	4.2.1	Contract with provider to install on-site carshare vehicles and promote their use by residents	
BETTER	4.2.2	Provide residents with carshare memberships, either free or subsidized	
	5.	PARKING	
	5.1	Priced parking	
BASIC	★ 5.1.1	Unbundle parking cost from purchase price (condominium)	$\square$
BASIC	5.1.2	Unbundle parking cost from monthly rent	☑′


12

Version 1.0 (30 June 2017)

TDM	measures: Residential developments	Check if proposed & add descriptions
6.	TDM MARKETING & COMMUNICATIONS	
6.1	Multimodal travel information	
BASIC ★ 6.1.1	Provide a multimodal travel option information package to new residents	
6.2	Personalized trip planning	
BETTER ★ 6.2.1	Offer personalized trip planning to new residents	

# **TDM-Supportive Development Design and Infrastructure Checklist:**

Residential Developments (multi-family or condominium)



	TDM-	supportive design & infrastructure measures: Residential developments	Check if completed & add descriptions, explanations or plan/drawing references
	1.	WALKING & CYCLING: ROUTES	
	1.1	Building location & access points	
BASIC	1.1.1	Locate building close to the street, and do not locate parking areas between the street and building entrances	$\square$
BASIC	1.1.2	Locate building entrances in order to minimize walking distances to sidewalks and transit stops/stations	$\square$
BASIC	1.1.3	Locate building doors and windows to ensure visibility of pedestrians from the building, for their security and comfort	$oldsymbol{oldsymbol{\boxtimes}}'$
	1.2	Facilities for walking & cycling	
REQUIRED	1.2.1	Provide convenient, direct access to stations or major stops along rapid transit routes within 600 metres; minimize walking distances from buildings to rapid transit; provide pedestrian-friendly, weather-protected (where possible) environment between rapid transit accesses and building entrances; ensure quality linkages from sidewalks through building entrances to integrated stops/stations (see Official Plan policy 4.3.3)	⊠′
REQUIRED	1.2.2	Provide safe, direct and attractive pedestrian access from public sidewalks to building entrances through such measures as: reducing distances between public sidewalks and major building entrances; providing walkways from public streets to major building entrances; within a site, providing walkways along the front of adjoining buildings, between adjacent buildings, and connecting areas where people may congregate, such as courtyards and transit stops; and providing weather protection through canopies, colonnades, and other design elements wherever possible (see Official Plan policy 4.3.12)	⊠

14

	TDM-s	supportive design & infrastructure measures: Residential developments	Check if completed & add descriptions, explanations or plan/drawing references
REQUIRED	1.2.3	Provide sidewalks of smooth, well-drained walking surfaces of contrasting materials or treatments to differentiate pedestrian areas from vehicle areas, and provide marked pedestrian crosswalks at intersection sidewalks (see Official Plan policy 4.3.10)	Ø
REQUIRED	1.2.4	Make sidewalks and open space areas easily accessible through features such as gradual grade transition, depressed curbs at street corners and convenient access to extra-wide parking spaces and ramps (see Official Plan policy 4.3.10)	⊠′
REQUIRED	1.2.5	Include adequately spaced inter-block/street cycling and pedestrian connections to facilitate travel by active transportation. Provide links to the existing or planned network of public sidewalks, multi-use pathways and onroad cycle routes. Where public sidewalks and multi-use pathways intersect with roads, consider providing traffic control devices to give priority to cyclists and pedestrians (see Official Plan policy 4.3.11)	<b>∀</b>
BASIC	1.2.6	Provide safe, direct and attractive walking routes from building entrances to nearby transit stops	
BASIC	1.2.7	Ensure that walking routes to transit stops are secure, visible, lighted, shaded and wind-protected wherever possible	
BASIC	1.2.8	Design roads used for access or circulation by cyclists using a target operating speed of no more than 30 km/h, or provide a separated cycling facility	☑′
	1.3	Amenities for walking & cycling	
BASIC	1.3.1	Provide lighting, landscaping and benches along walking and cycling routes between building entrances and streets, sidewalks and trails	
BASIC	1.3.2	Provide wayfinding signage for site access (where required, e.g. when multiple buildings or entrances exist) and egress (where warranted, such as when directions to reach transit stops/stations, trails or other common destinations are not obvious)	

	TDM-s	supportive design & infrastructure measures:  Residential developments	add descriptions, explanations or plan/drawing references
	2.	WALKING & CYCLING: END-OF-TRIP FACILI	TIES
	2.1	Bicycle parking	
REQUIRED	2.1.1	Provide bicycle parking in highly visible and lighted areas, sheltered from the weather wherever possible (see Official Plan policy 4.3.6)	lacksquare
REQUIRED	2.1.2	Provide the number of bicycle parking spaces specified for various land uses in different parts of Ottawa; provide convenient access to main entrances or well-used areas (see Zoning By-law Section 111)	☑′
REQUIRED	2.1.3	Ensure that bicycle parking spaces and access aisles meet minimum dimensions; that no more than 50% of spaces are vertical spaces; and that parking racks are securely anchored (see Zoning By-law Section 111)	⊠′
BASIC	2.1.4	Provide bicycle parking spaces equivalent to the expected number of resident-owned bicycles, plus the expected peak number of visitor cyclists	
	2.2	Secure bicycle parking	
REQUIRED	2.2.1	Where more than 50 bicycle parking spaces are provided for a single residential building, locate at least 25% of spaces within a building/structure, a secure area (e.g. supervised parking lot or enclosure) or bicycle lockers (see Zoning By-law Section 1111)	
BETTER	2.2.2	Provide secure bicycle parking spaces equivalent to at least the number of units at condominiums or multifamily residential developments	
	2.3	Bicycle repair station	
BETTER	2.3.1	Provide a permanent bike repair station, with commonly used tools and an air pump, adjacent to the main bicycle parking area (or secure bicycle parking area, if provided)	
	3.	TRANSIT	
	3.1	Customer amenities	
BASIC	3.1.1	Provide shelters, lighting and benches at any on-site transit stops	
BASIC	3.1.2	Where the site abuts an off-site transit stop and insufficient space exists for a transit shelter in the public right-of-way, protect land for a shelter and/or install a shelter	
BETTER	3.1.3	Provide a secure and comfortable interior waiting area by integrating any on-site transit stops into the building	


11


		TDM-s	supportive design & infrastructure measures: Residential developments	Check if completed & add descriptions, explanations or plan/drawing references
		4.	RIDESHARING	
		4.1	Pick-up & drop-off facilities	
	BASIC	4.1.1	Provide a designated area for carpool drivers (plus taxis and ride-hailing services) to drop off or pick up passengers without using fire lanes or other no-stopping zones	
		5.	CARSHARING & BIKESHARING	
		5.1	Carshare parking spaces	
	BETTER	5.1.1	Provide up to three carshare parking spaces in an R3, R4 or R5 Zone for specified residential uses (see Zoning By-law Section 94)	
		5.2	Bikeshare station location	
	BETTER	5.2.1	Provide a designated bikeshare station area near a major building entrance, preferably lighted and sheltered with a direct walkway connection	
		6.	PARKING	
		6.1	Number of parking spaces	
F	REQUIRED	6.1.1	Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for	
	BASIC	6.1.2	Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking	
	BASIC	6.1.3	Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (see Zoning By-law Section 104)	
	BETTER	6.1.4	Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (see Zoning By-law Section 111)	
		6.2	Separate long-term & short-term parking areas	
	BETTER	6.2.1	Provide separate areas for short-term and long-term parking (using signage or physical barriers) to permit access controls and simplify enforcement (i.e. to discourage residents from parking in visitor spaces, and vice versa)	

# Appendix F

Turning Templates








# Appendix G

Adjacent Phase Site Plan (3718 Greenbank Road)





# Appendix H

MMLOS Worksheet



# Multi-Modal Level of Service - Segments Form

Consultant	CGH Transportation Inc	Project	2025-011
Scenario	Exsiting/Future	Date	2025-03-31
Comments			

OF OMENIES		Obsidian Greenbank Road				
SEGMENTS			Existing/Future	Future		
Pedestrian	Sidewalk Width Boulevard Width		1.8 m < 0.5 m	≥ 2 m > 2 m		
	Avg Daily Curb Lane Traffic Volume		≤ 3000	> 3000		
	Operating Speed On-Street Parking		> 30 to 50 km/h yes	> 50 to 60 km/h no		
	Exposure to Traffic PLoS		В	С	-	-
	Effective Sidewalk Width					
	Pedestrian Volume					
	Crowding PLoS		-	-	-	-
	Level of Service		-	-	-	-
Bicycle	Type of Cycling Facility		Mixed Traffic	Physically Separated		
	Number of Travel Lanes		≤ 2 (no centreline)			
	Operating Speed		≥ 50 to 60 km/h			
	# of Lanes & Operating Speed LoS		D	-	-	-
	Bike Lane (+ Parking Lane) Width					
	Bike Lane Width LoS	D	-	-	-	-
	Bike Lane Blockages					
	Blockage LoS		-	-	-	-
	Median Refuge Width (no median = < 1.8 m)		< 1.8 m refuge			
	No. of Lanes at Unsignalized Crossing Sidestreet Operating Speed		≤ 3 lanes >50 to 60 km/h			
	Unsignalized Crossing - Lowest LoS		C	A	-	_
	Level of Service		D	Α	-	-
Transit	Facility Type			Segregated ROW		
	Friction or Ratio Transit:Posted Speed	Α				
	Level of Service		-	Α	-	-
Truck	Truck Lane Width			≤ 3.5 m		
	Travel Lanes per Direction	Δ.		> 1		
	Level of Service	Α	-	Α	-	-