

SECURE SITE DESIGN L.L.C.
(a VICTOR STANLEY, INC. affiliate)

TOLL FREE (USA & CANADA): 1-888-4MT-94M (888-888-4726)
410-286-5075 • FAX 410-478-0175
P.O. BOX 307, DUNKIN, MD 20754 U.S.A.
INFO@SECURESITEDESIGN.COM
WWW.SECURESITEDESIGN.COM

* ALL DIMENSIONS ARE IN MILLIMETERS *

HOLES ARE PRESENT ONLY WHEN GALVANIZED OPTION IS SPECIFIED

FORMED FROM 60mm O.D. SCHEDULE 40 STEEL PIPE

VIEW A

127mm O.D.

19mm O.D.

65mm O.D. HOLE SPACING

81mm

GROUND LEVEL

27mm

99mm

25mm

850mm CENTER-TO-CENTER

AVAILABLE OPTIONS:

POWDER COATING
12 AVAILABLE COLORS, CUSTOM COLORS (INCLUDING THE RAL RANGE AT AN ADDITIONAL COST)
ALL POWDER COAT FINISHES ARE DONE AT VICTOR STANLEY, INC. (VSI) TO MATCH THE VSI PRODUCT LINE)
OTHER FINISHES: GALVANIZED (SPECIAL QUOTE NEEDED)

NOTES:

- DRAWINGS NOT TO SCALE. DO NOT SCALE DRAWINGS.
- ALL FABRICATED METAL COMPONENTS ARE STEEL, SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.O.I.C. POLYESTER POWDER COATINGS. PRODUCTS ARE FULLY CLEANED AND PREHEATED, PREHEATED AND COATED WHEEL NOT TO FILL CREVICES AND BULLDO COATING FILL. COATED PARTS ARE THEN FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS (200-250 MICROMS).
- IT IS NOT RECOMMENDED TO LOCATE ANCHOR BOLTS UNTIL THE BIKE RACK IS IN PLACE. THIS SECURE SITE DESIGN, L.L.C. PRODUCT MUST BE PERMANENTLY AFFIXED TO THE GROUND. CONSULT YOUR LOCAL CODES FOR REGULATIONS.
- ANCHOR BOLTS NOT PROVIDED BY SECURE SITE DESIGN L.L.C.
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE. CONTACT MANUFACTURER FOR DETAILS.
- THIS PRODUCT IS SHIPPED FULLY ASSEMBLED.

BRCS-103
CYCLESENTRY SERIES BIKE RACK
SHOWN: STANDARD SURFACE MOUNT

MOUNTING
STANDARD IN-GROUND AND SURFACE (AS SHOWN)

Copyright 2011 SECURE SITE DESIGN, L.L.C. ALL RIGHTS RESERVED
REV. 01/15/11 DRAWN R.J.C. 2010-323

VICTOR STANLEY, INC.
Manufacturers of Quality Site Furnishings since 1962

P.O. DRAWER 300 - DUNKIN, MD 20754 USA
TOLL FREE: (800) 386-2679 (USA & CANADA)
TEL: (301) 855-8300 - FAX: (410) 257-7579
WEB SITE: HTTP://WWW.VICTORSTANLEY.COM

* ALL DIMENSIONS ARE IN MILLIMETERS *

TOP BAND VARIES BETWEEN PRODUCTS

AVAILABLE WITH ANY COMBINATION OF DECALLED LID AND TOP BAND

10mm x 25mm VERTICAL SOLID STEEL BARS

10mm x 64mm HORIZONTAL SOLID STEEL BARS

138-LITER CAPACITY HIGH DENSITY PLASTIC LINER (WEIGHT NOT TO EXCEED 2.7kg) SETS ON 6mm x 51mm SUPPORT BARS

LEVELING FEET WITH 10mm DIAMETER THREADED STEEL SHAFT

10mm x 76mm SOLID STEEL BARS

19mm ANCHOR BOLT HOLES

19mm SOLID STEEL TOP RING

71mm

1333mm

455mm

190mm

AVAILABLE OPTIONS:

POWDER COATING
10 STANDARD COLORS, 2 OPTIONAL METALLIC COLORS, CUSTOM COLORS (INCLUDING THE RAL RANGE)

SECURITY
STANDARD WITH LOCKABLE LATCH (AS SHOWN). AVAILABLE WITH OPTIONAL KEYS LOCK BOX. LID SOLID IN PLACE. AVAILABLE WITH OPTIONAL MOUNT WITH 3 IN-LINE ANCHOR HOLES AND OPTIONAL BOTTOM PLATE COVER.

NOTES:

- DRAWINGS NOT TO SCALE. DO NOT SCALE DRAWINGS.
- ALL FABRICATED METAL COMPONENTS ARE STEEL, SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.O.I.C. POLYESTER POWDER COATINGS. PRODUCTS ARE FULLY CLEANED AND PREHEATED, PREHEATED AND COATED WHEEL NOT TO FILL CREVICES AND BULLDO COATING FILL. COATED PARTS ARE THEN FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS (200-250 MICROMS).
- ODL IMPREGNATED BRONZE BUSHINGS AND STAINLESS STEEL PIVOT PINS FOR DOOR MOVEMENT, STANDARD 6mm SOLID STEEL LATCH ASSEMBLY OR OPTIONAL PATENTED STAINLESS STEEL KEYS LOCK ASSEMBLY.
- THIS VICTOR STANLEY, INC. PRODUCT MUST BE PERMANENTLY AFFIXED TO THE GROUND. CONSULT YOUR LOCAL CODES FOR REGULATIONS.
- VICTOR STANLEY, INC. PLASTIC LINER LINERS ARE BUILT ON TOOLING DESIGNED FOR AND OWNED BY VICTOR STANLEY, INC. THEY OFFER MAXIMUM CAPACITY AND STRENGTH WITH LIGHTWEIGHT CONSTRUCTION USING CRITICAL WELDED JOINTS, INTERNAL WINDLAYS, AND HIGH-STRENGTH MATERIALS. THIS REDUCES HANDLING DIFFICULTY AND FACILITATES EASY EMPTYING AND STORAGE WHILE AFFORDING LONG SERVICE LIFE.
- ANCHOR BOLT NOT PROVIDED BY VICTOR STANLEY, INC.
- FOR HIGH SALT AMBIENT CLIMATES, HOT-DIP GALVANIZING BEFORE POWDER COATING IS AVAILABLE. HOT-DIP GALVANIZING IS PERFORMED FOR VICTOR STANLEY, INC. BY AN EXPERIENCED QUALIFIED FIRM TO WHICH PRODUCTS ARE SHIPPED FOR GALVANIZING. HOT-DIP GALVANIZING INCLUDES AN AGGRESSIVE PRE-TREATMENT AND IMMERSION IN A TANK OF CHARGED LIQUID ZINC AT OR AROUND 890°F (480°C). THE RESULTING SURFACE IS RESISTANT TO RUST BUT HAS SOME UNEVENNESS RESULTING FROM THE BONDING OF THE ZINC TO THE STEEL SURFACE. AS A RESULT, THE POWDER-COATING SURFACE FINISH OVER THAT GALVANIZED SURFACE MAY EXHIBIT BUMPS, UNEVENNESS, AND MAY NOT BE AS SMOOTH AS THE STANDARD FINISH; THIS UNEVEN AND INCONSISTENT FINISH IS NORMAL FOR GALVANIZING. CONTACT MANUFACTURER FOR DETAILS.
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE. CONTACT MANUFACTURER FOR DETAILS.
- THIS PRODUCT IS SHIPPED FULLY ASSEMBLED.

SD-242
IRONITES SERIES SIDE-DOOR RECYCLING STATION
SHOWN: (2) STANDARD TAPERED FORMED LID

Copyright 2014 VICTOR STANLEY, INC. ALL RIGHTS RESERVED
REV. 6/2/14 DRAWN C.B.B. 2014-510

VICTOR STANLEY
Create a timeless moment.

* ALL DIMENSIONS ARE IN MILLIMETERS *

645mm

800mm

550mm

425mm

SEAT HEIGHT

38mm x 84mm SLATS

19mm SOLID STEEL ROD

CLEARANCE FOR 10mm ANCHOR BOLTS

6mm x 64mm HORIZONTAL STEEL BARS

10mm x 25mm VERTICAL SOLID STEEL BARS

38mm TUBULAR STEEL RING (USED FOR ADDITIONAL SUPPORT)

10mm x 76mm CENTER BRACE FOR ADDITIONAL SUPPORT

1690mm

1740mm CENTER-TO-CENTER

AVAILABLE OPTIONS:

POWDER COATING
10 STANDARD COLORS, 2 OPTIONAL METALLIC COLORS, CUSTOM COLORS (INCLUDING THE RAL RANGE)

SLAT TYPES
LPE WOOD (AS SHOWN) OR 2nd SITE SYSTEMS REINFORCED RECYCLED PLASTIC SLATS
2nd SITE SYSTEMS COLORS: GRAY, MAPLE, CHERRY, AND WALNUT

NOTES:

- DRAWINGS NOT TO SCALE. DO NOT SCALE DRAWINGS.
- ALL FABRICATED METAL COMPONENTS ARE STEEL, SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.O.I.C. POLYESTER POWDER COATINGS. PRODUCTS ARE FULLY CLEANED AND PREHEATED, PREHEATED AND COATED WHEEL NOT TO FILL CREVICES AND BULLDO COATING FILL. COATED PARTS ARE THEN FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS (200-250 MICROMS).
- IT IS NOT RECOMMENDED TO LOCATE ANCHOR BOLTS UNTIL BENCH IS IN PLACE. THIS VICTOR STANLEY, INC. PRODUCT MUST BE PERMANENTLY AFFIXED TO THE GROUND. CONSULT YOUR LOCAL CODES FOR REGULATIONS.
- ANCHOR BOLTS NOT PROVIDED BY VICTOR STANLEY, INC.
- FOR HIGH SALT AMBIENT CLIMATES, HOT-DIP GALVANIZING BEFORE POWDER COATING IS AVAILABLE. HOT-DIP GALVANIZING IS PERFORMED FOR VICTOR STANLEY, INC. BY AN EXPERIENCED QUALIFIED FIRM TO WHICH PRODUCTS ARE SHIPPED FOR GALVANIZING. HOT-DIP GALVANIZING INCLUDES AN AGGRESSIVE PRE-TREATMENT AND IMMERSION IN A TANK OF CHARGED LIQUID ZINC AT OR AROUND 890°F (480°C). THE RESULTING SURFACE IS RESISTANT TO RUST BUT HAS SOME UNEVENNESS RESULTING FROM THE BONDING OF THE ZINC TO THE STEEL SURFACE. AS A RESULT, THE POWDER-COATING SURFACE FINISH OVER THAT GALVANIZED SURFACE MAY EXHIBIT BUMPS, UNEVENNESS, AND MAY NOT BE AS SMOOTH AS THE STANDARD FINISH; THIS UNEVEN AND INCONSISTENT FINISH IS NORMAL FOR GALVANIZING. CONTACT MANUFACTURER FOR DETAILS.
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE. CONTACT MANUFACTURER FOR DETAILS.
- THIS PRODUCT IS SHIPPED PARTIALLY UNASSEMBLED.

S-13
IRONITES SERIES CONToured BENCH
SHOWN: STANDARD 1.8 METER LENGTH
STANDARD LPE WOOD SLATS

Copyright 2017 VICTOR STANLEY, INC. ALL RIGHTS RESERVED
REV. 8/28/17 DRAWN V.F.T. 2017-755

APPROVED
By Adam Brown at 9:44 am, Feb 07, 2023

Adam Brown

ADAM BROWN
MANAGER, DEVELOPMENT REVIEW - RURAL
PLANNING, REAL ESTATE & ECONOMIC DEVELOPMENT
DEPARTMENT, CITY OF OTTAWA

CLIENT LOGO:

FASTFRATE
CBRE

KEY PLAN:

FILE NUMBER: PROJECT NUMBER:

RECORD OF REVISIONS:

1			
2			
3			
4			
5			
6			
7			
8			
9			
10			

ISSUED FOR SITE PLAN APPROVAL 2022-09-26

NUMBER: REVISION: DATE: (MM/DD/YYYY)

PROFESSIONAL STAMP:

ASSOCIATION OF LANDSCAPE ARCHITECTS
ONIA
Dana Matichuk
MEMBER
2010-2023

CIVITAS GROUP
ARCHITECTURE & LANDSCAPE ARCHITECTURE

CIVITAS ARCHITECTURE INC. OTTAWA, ON 1-613-742-7482
14 CHAMBERLAIN AVENUE, SUITE 101 CANADA K1S 1V9 WWW.CIVITAS-INC.CA

CONSULTANT LOGO:

PROJECT TITLE:
NEW WAREHOUSE & CROSS DOCK FACILITY

301 SOMME STREET, OTTAWA, ON

DRAWING TITLE:
FENCING AND GATE DETAILS

DRAWN BY: S. PARENT DRAWING NUMBER:
DATE: 2022-09-26
REVIEWED BY: S. PARENT
APPROVED BY: D. MATICHUK
PRINT DATE: REVISION NUMBER:
ISSUED DATE: 2022-09-26

CLIENT PROJECT #: PROJECT #:
- 2001

DO NOT SCALE THE DRAWING. USE FIGURE DIMENSIONS ONLY. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL DIMENSIONS AND NOTIFYING THE ARCHITECT OF ANY DISCREPANCIES BEFORE CONSTRUCTION COMMENCES. THE DRAWING IS TO BE READ IN CONJUNCTION WITH ALL STRUCTURAL, MECHANICAL, ELECTRICAL, CIVIL AND OTHER CONSULTANT DRAWINGS. THIS DRAWING SHALL NOT BE USED FOR CONSTRUCTION PURPOSES UNLESS SIGNED BY THE ARCHITECT. COPYRIGHT RESERVED. ALL PARTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE ARCHITECT AND SHALL NOT BE USED WITHOUT THE EXPRESSED PERMISSION FROM THE ARCHITECT.